according to Hazard Communication Standard; 29 CFR 1910.1200



SC JOHNSON PROFESSIONAL® EZ CARE™ FLOOR COATING

Version 1.0 Print Date 12/18/2024

SDS Number 350000043504 Revision Date 03/10/2023 GEN SOF Number 77162

1. PRODUCT AND COMPANY IDENTIFICATION

Product information

: SC JOHNSON PROFESSIONAL® EZ CARE™ FLOOR Product name

COATING

Recommended use : Floor Polish/Cleaner

Restrictions on use : Use only as directed on label

supplier

Manufacturer, importer, : S.C. Johnson & Son, Inc.

1525 Howe Street

Racine WI 53403-2236

Telephone : +1-800-558-5252

Emergency telephone

number

: 24 Hour Medical Emergency Phone: (866)231-5406 24 Hour Transport Emergency Phone: (800)424-9300

2. HAZARDS IDENTIFICATION

Classification of the substance or mixture

Globally Harmonized System (GHS) Classification

This product does not meet the criteria for classification in any hazard class according to regulation OSHA 29 CFR 1910.1200.

Labelling

Precautionary statements

Other hazards None identified

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name CAS-No.	Weight percent
-----------------------	----------------

according to Hazard Communication Standard; 29 CFR 1910.1200



SC JOHNSON PROFESSIONAL® EZ CARE™ FLOOR COATING

Version 1.0 Print Date 12/18/2024

Revision Date 03/10/2023 SDS Number 350000043504 GEN SOF Number 77162

Diethylene glycol monoethyl ether	111-90-0	5.00 - 10.00
Tributyoxyethyl phosphate	78-51-3	1.00 - 5.00
Zinc oxide	1314-13-2	1.00 - 5.00

The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

For additional information on product ingredients, see www.whatsinsidescjohnson.com.

4. FIRST AID MEASURES

Description of first aid measures

Eye contact : No special requirements

Skin contact : No special requirements

Inhalation : No special requirements.

Ingestion : No special requirements

Most important symptoms and effects, both acute and delayed

Eyes : No adverse effects expected when used as directed.

Skin effect : No adverse effects expected when used as directed.

Inhalation : No adverse effects expected when used as directed.

Ingestion : No adverse effects expected when used as directed.

Indication of any immediate medical attention and special treatment needed

See Description of first aid measures unless otherwise stated.

5. FIREFIGHTING MEASURES

Suitable extinguishing

media

: Use water spray, alcohol-resistant foam, dry chemical or

carbon dioxide.

Specific hazards during : Container may melt and leak in heat of fire.

according to Hazard Communication Standard; 29 CFR 1910.1200



SC JOHNSON PROFESSIONAL® EZ CARE™ FLOOR COATING

Version 1.0 Print Date 12/18/2024

Revision Date 03/10/2023 SDS Number 350000043504 GEN SOF Number 77162

firefighting

Further information: Fight fire with normal precautions from a reasonable distance.

Standard procedure for chemical fires. Wear full protective clothing and positive pressure self-contained breathing

apparatus.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Wash thoroughly after handling.

Environmental precautions

Outside of normal use, avoid release to the environment.

Methods and materials for containment and

cleaning up

Dike large spills.

Clean residue from spill site.

7. HANDLING AND STORAGE

Handling

Precautions for safe

handling

: Avoid contact with skin, eyes and clothing. For personal protection see section 8.

KEEP OUT OF REACH OF CHILDREN AND PETS.

Advice on protection

against fire and explosion

: Normal measures for preventive fire protection.

Storage

Requirements for storage

areas and containers

: Keep container closed when not in use.

according to Hazard Communication Standard; 29 CFR 1910.1200



SC JOHNSON PROFESSIONAL® EZ CARE™ FLOOR COATING

Version 1.0 Print Date 12/18/2024

Revision Date 03/10/2023 SDS Number 350000043504

GEN_SOF Number 77162

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits

Components	CAS-No.	mg/m3	ppm	Non- standard units	Basis
Zinc oxide	1314-13-2	5 mg/m3	-	-	OSHA TWA
Zinc oxide	1314-13-2	5 mg/m3	-	-	OSHA TWA
Zinc oxide	1314-13-2	15 mg/m3	-	-	OSHA TWA
Zinc oxide	1314-13-2	10 mg/m3	-	-	ACGIH STEL
Zinc oxide	1314-13-2	2 mg/m3	-	-	ACGIH TWA

Personal protective equipment

Respiratory protection : No special requirements.

Hand protection : No special requirements.

Eye protection : No special requirements.

Skin and body protection : No special requirements.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. Wash thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form : liquid

Color : white

Odour : Fruity Floral

according to Hazard Communication Standard; 29 CFR 1910.1200



SC JOHNSON PROFESSIONAL® EZ CARE™ FLOOR COATING

Version 1.0 Print Date 12/18/2024

Revision Date 03/10/2023 SDS Number 350000043504 GEN SOF Number 77162

Odour Threshold : Test not applicable for this product type

pН : 8.45

at (25 °C)

Melting point/freezing point : 32 °F

Initial boiling point and

boiling range

: 100 C

Flash point : > 94 °C

> 201.2 °F

Method: Tag Closed Cup (TCC)

Evaporation rate : Test not applicable for this product type

: The product is not flammable. Flammability (solid, gas)

explosive limits

Upper/lower flammability or : Test not applicable for this product type

Vapour pressure : Test not applicable for this product type

Vapour density

Relative density : 1.03 g/cm3

Solubility(ies) : dispersible

Partition coefficient: n-

octanol/water

: Test not applicable for this product type

Auto-ignition temperature : Test not applicable for this product type

according to Hazard Communication Standard; 29 CFR 1910.1200



SC JOHNSON PROFESSIONAL® EZ CARE™ FLOOR COATING

Version 1.0 Print Date 12/18/2024

Revision Date 03/10/2023 SDS Number 350000043504 GEN SOF Number 77162

Decomposition temperature : Test not applicable for this product type

Viscosity, dynamic : 6.0 mPa.s

Viscosity, kinematic : Test not applicable for this product type

Oxidizing properties : Test not applicable for this product type

Volatile Organic : 0.1 % - additional exemptions may apply

Compounds
Total VOC (wt. %)*

*as defined by US Federal and State Consumer Product

Regulations

Other information : None identified

10. STABILITY AND REACTIVITY

Reactivity: No dangerous reaction known under conditions of normal use.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous

reactions

: If accidental mixing occurs and toxic gas is formed, exit area

immediately. Do not return until well ventilated.

Conditions to avoid : Direct sources of heat.

Incompatible materials : Do not mix with bleach or any other household cleaners.

Incompatible materials : Do not mix with bleach or any other household cleaners.

Strong bases

Hazardous decomposition: Thermal decomposition can lead to release of irritating gases

according to Hazard Communication Standard; 29 CFR 1910.1200



SC JOHNSON PROFESSIONAL® EZ CARE™ FLOOR COATING

Version 1.0 Print Date 12/18/2024

Revision Date 03/10/2023 SDS Number 350000043504 GEN_SOF Number 77162

products and vapours.

11. TOXICOLOGICAL INFORMATION

Acute oral toxicity : LD50 > 5000 mg/kg Acute inhalation toxicity : LC50 > 10 mg/L

Acute dermal toxicity : LD50 > 5000 mg/kg

GHS Properties	Classification	Routes of entry
Acute toxicity	No classification proposed	Oral
Acute toxicity	No classification proposed	Dermal
Acute toxicity	No classification proposed	Inhalation - Dust and Mist
Acute toxicity	No classification proposed	Inhalation - Vapour
Acute toxicity	No classification proposed	Inhalation - Gas
Skin irritation	No classification proposed	-
Eye irritation	No classification proposed	-
Skin sensitisation	No classification proposed	-
Respiratory sensitisation	No classification proposed	-
Germ cell mutagenicity	No classification proposed	-
Carcinogenicity	No classification proposed	-
Reproductive toxicity	No classification proposed	-
Specific target organ toxicity - single exposure	No classification proposed	-
Specific target organ toxicity - repeated	No classification proposed	-

according to Hazard Communication Standard; 29 CFR 1910.1200



SC JOHNSON PROFESSIONAL® EZ CARE™ FLOOR COATING

Version 1.0 Print Date 12/18/2024

Revision Date 03/10/2023 SDS Number 350000043504 GEN_SOF Number 77162

exposure		
Aspiration hazard	No classification proposed	-

Other information : see user defined free text

Aggravated Medical

Condition

None known.

12. ECOLOGICAL INFORMATION

Product: The product itself has not been tested.

Toxicity

The ingredients in this formula have been reviewed and no adverse impact to the environment is expected when used according to label directions.

Toxicity to fish

Components	End point	Species	Value	Exposure time
Diethylene glycol monoethyl ether	flow- through test LC50	Ictalurus punctatus	6,010 mg/l	96 h
Tributyoxyethyl phosphate	semi- static test LC50 Measured	Oncorhynchus mykiss (rainbow trout)	24 mg/l	96 h
Zinc oxide				

Toxicity to aquatic invertebrates

Components	End point	Species	Value	Exposure time
Diethylene glycol monoethyl ether	static test EC50	Daphnia magna (Water flea)	1,982 mg/l	48 h

according to Hazard Communication Standard; 29 CFR 1910.1200



SC JOHNSON PROFESSIONAL® EZ CARE™ FLOOR COATING

Version 1.0 Print Date 12/18/2024

Revision Date 03/10/2023 SDS Number 350000043504 GEN_SOF Number 77162

T	ributyoxyethyl phosphate	static test EC50 Measured	Daphnia magna (Water flea)	53 mg/l	48 h
Z	inc oxide				

Toxicity to aquatic plants

Components	End point	Species	Value	Exposure time
Diethylene glycol monoethyl ether	static test EC50 Read- across (Analogy)	Desmodesmus subspicatus (green algae)	> 100 mg/l	96 h
Tributyoxyethyl phosphate	static test EC50	Pseudokirchneriella subcapitata (green algae)	61 mg/l	72 h
Zinc oxide				

Persistence and degradability

ersistence and degradability				
Component	Biodegradation	Exposure time	Summary	
Diethylene glycol monoethyl ether	100 %	28 d	Readily biodegradable.	
Tributyoxyethyl phosphate	87 %	28 d	Readily biodegradable.	
Zinc oxide	No data available			

Bioaccumulative potential

Component	Bioconcentration factor (BCF)	Partition Coefficient n- Octanol/water (log)
Diethylene glycol monoethyl	3,162	0.54

according to Hazard Communication Standard; 29 CFR 1910.1200



SC JOHNSON PROFESSIONAL® EZ CARE™ FLOOR COATING

Version 1.0 Print Date 12/18/2024

Revision Date 03/10/2023 SDS Number 350000043504

GEN_SOF Number 77162

ether		
Tributyoxyethyl phosphate	5.8 Measured	3.75 Measured
Zinc oxide	No data available	

Mobility

Component	End point	Value
Diethylene glycol monoethyl ether	No data available	
Tributyoxyethyl phosphate	log Koc	2.5
Zinc oxide	No data available	

PBT and vPvB assessment

Component	Results
Diethylene glycol monoethyl ether	Not fulfilling PBT and vPvB criteria
Tributyoxyethyl phosphate	Not fulfilling PBT and vPvB criteria

Other adverse effects : None known.

13. DISPOSAL CONSIDERATIONS

Consumer may discard empty container in trash, or recycle where facilities exist.

14. TRANSPORT INFORMATION

Please refer to the Bill of Lading/receiving documents for up-to-date shipping information.

Land transport

Not classified as dangerous in the meaning of transport regulations.

Sea transport

Not classified as dangerous in the meaning of transport regulations.

Air transport

Not classified as dangerous in the meaning of transport regulations.

according to Hazard Communication Standard; 29 CFR 1910.1200



SC JOHNSON PROFESSIONAL® EZ CARE™ FLOOR COATING

Version 1.0 Print Date 12/18/2024

Revision Date 03/10/2023 SDS Number 350000043504 GEN_SOF Number 77162

15. REGULATORY INFORMATION

Notification status : All ingredients of this product are listed or are excluded from

listing on the U.S. Toxic Substances Control Act (TSCA)

Chemical Substance Inventory.

California Prop. 65 : This product is not subject to the reporting requirements under

California's Proposition 65.

State Right To Know

Massachusetts RTK	Zinc oxide	1314-13-2
	Zinc oxide	1314-13-2
Minnesota HSL	Diethylene glycol monoethyl ether	111-90-0
	Zinc oxide	1314-13-2
	Diethylene glycol monoethyl ether	111-90-0
	Zinc oxide	1314-13-2
New Jersey HRTK	Zinc oxide	1314-13-2
	Zinc oxide	1314-13-2
Pennsylvania RTKL	Water	7732-18-5
	Acrylic polymers	
	Diethylene glycol monoethyl ether	111-90-0
	Zinc oxide	1314-13-2
	Ammonium Hydroxide	1336-21-6
	Potassium hydroxide	1310-58-3
	2-ethoxyethanol	110-80-5
	Ethylene glycol	107-21-1
	Hydrogen Peroxide	7722-84-1
	Butan-1-ol	71-36-3
	Water	7732-18-5
	Acrylic polymers	
	Diethylene glycol monoethyl ether	111-90-0
	Zinc oxide	1314-13-2
	Ammonium Hydroxide	1336-21-6
	Potassium hydroxide	1310-58-3
	2-ethoxyethanol	110-80-5
	Ethylene glycol	107-21-1
	Butan-1-ol	71-36-3

according to Hazard Communication Standard; 29 CFR 1910.1200



SC JOHNSON PROFESSIONAL® EZ CARE™ FLOOR COATING

Version 1.0 Print Date 12/18/2024

Revision Date 03/10/2023

SDS Number 350000043504 GEN_SOF Number 77162

16. OTHER INFORMATION

HMIS	Ratin	gs
------	-------	----

Health	1	
Flammability	0	
Reactivity	0	

NFPA Ratings

NI FA Natiliya		
Health	1	
Fire	0	
Reactivity	0	
Special	-	

This information is being provided in accordance with the Occupational Safety and Health Administration (OSHA) regulation (29 CFR 1910.1200). The information supplied is designed for workplaces where product use and frequency of exposure exceeds that established for the labeled consumer use.

Further information

This document has been prepared using data from sources considered to be technically reliable. It does not constitute a warranty, expressed or implied, as to the accuracy of the information contained herein. Actual conditions of use are beyond the seller's control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State, Provincial and Local laws and regulations.

Prepared by	SC Johnson Global Safety Assessment &
	Regulatory Affairs (GSARA)