According to EC No 1907/2006 as amended as at the date of this SDS

Bio Methanol

Version Revision Date: SDS Number: Date of last issue: 17.08.2023

2.3 28.02.2025 800010034380 Print Date 07.03.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Bio Methanol Product code : S811F

Registration number EU : 01-2119433307-44-xxxx

CAS-No. : 67-56-1

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Please refer to section 16 and/or the annexes for the regis-

stance/Mixture tered uses under REACH.

Solvent., Raw material for use in the chemical industry.

Uses advised against :

This product must not be used in applications other than those listed in Section 1 without first seeking the advice of the sup-

plier.

This product must not be used in applications other than the

above without first seeking the advice of the supplier.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier : Shell Chemicals Europe B.V.

PO Box 2334

3000 CH Rotterdam

Netherlands

Telephone : +31 (0)10 441 5137 / +31 (0)10 441 5191 Telefax : +31 (0)20 716 8316 / +31 (0)20 713 9230

Contact for Safety Data

Sheet

: sccmsds@shell.com

1.4 Emergency telephone number

+44 (0) 1235 239 670 (This telephone number is available 24 hours per day, 7 days per

week)

Poisons Centre: 070 245 245

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 2 H225: Highly flammable liquid and vapour.

Acute toxicity, Category 3, Inhalation H331: Toxic if inhaled.

Acute toxicity, Category 3, Dermal H311: Toxic in contact with skin.

According to EC No 1907/2006 as amended as at the date of this SDS

Bio Methanol

Version Revision Date: SDS Number: Date of last issue: 17.08.2023

2.3 28.02.2025 800010034380 Print Date 07.03.2025

Acute toxicity, Category 3, Oral H301: Toxic if swallowed.

Specific target organ toxicity - single exposure, Category 1, Visual system

, Nervous system

H370: Causes damage to organs.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :







Signal word : Danger

Hazard statements : PHYSICAL HAZARDS:

H225 Highly flammable liquid and vapour.

HEALTH HAZARDS:

H311 Toxic in contact with skin.

H301 Toxic if swallowed. H331 Toxic if inhaled.

H370 Causes damage to organs (Eyes, Nervous system).

ENVIRONMENTAL HAZARDS:

Not classified as environmental hazard according to

CLP criteria.

Precautionary statements : Prevention:

P210 Keep away from heat/ sparks/ open flames/ hot surfac-

es. No smoking.

P243 Take precautionary measures against static discharge.

P280 Wear protective gloves/ protective clothing/ eye protec-

tion/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. P304 + P340 IF INHALED: Remove person to fresh air and

keep comfortable for breathing.

P301 + P310 IF SWALLOWED: Immediately call a POISON

CENTER/ doctor.

Storage:

No precautionary phrases.

Disposal:

No precautionary phrases.

According to EC No 1907/2006 as amended as at the date of this SDS

Bio Methanol

Version Revision Date: SDS Number: Date of last issue: 17.08.2023

2.3 28.02.2025 800010034380 Print Date 07.03.2025

2.3 Other hazards

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

In use, may form flammable/explosive vapour-air mixture.

Even with proper grounding and bonding, this material can still accumulate an electrostatic charge.

If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable airvapour mixtures can occur.

SECTION 3: Composition/information on ingredients

3.1 Substances

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Methanol	67-56-1 200-659-6 603-001-00-X 01-2119433307-44	Flam. Liq. 2; H225 Acute Tox. 3; H331 Acute Tox. 3; H301 STOT SE 1; H370 (Visual system, Nervous system) specific concentration limit STOT SE 1; H370 >= 10 % STOT SE 2; H371 3 - < 10 % Acute oral toxicity: Acute toxicity estimate 100 mg/kg bw Acute inhalation toxicity: Acute toxicity estimate 3 mg/l Acute dermal toxicity: Acute toxicity estimate 300 mg/kg bw	<= 100

According to EC No 1907/2006 as amended as at the date of this SDS

Bio Methanol

Version Revision Date: SDS Number: Date of last issue: 17.08.2023

2.3 28.02.2025 800010034380 Print Date 07.03.2025

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : DO NOT DELAY.

Keep victim calm. Obtain medical treatment immediately.

Protection of first-aiders : When administering first aid, ensure that you are wearing the

appropriate personal protective equipment according to the

incident, injury and surroundings.

If inhaled : Call emergency number for your location / facility.

Remove to fresh air. Do not attempt to rescue the victim unless proper respiratory protection is worn. If the victim has difficulty breathing or tightness of the chest, is dizzy, vomiting, or unresponsive, give 100% oxygen with rescue breathing or Cardio-Pulmonary Resuscitation as required and transport to

the nearest medical facility.

In case of skin contact : Remove contaminated clothing. Immediately flush skin with

large amounts of water for at least 15 minutes. Transport to

the nearest medical facility for additional treatment.

In case of eye contact : Flush eye with copious quantities of water.

Remove contact lenses, if present and easy to do. Continue

insing.

If persistent irritation occurs, obtain medical attention.

If swallowed : If swallowed, do not induce vomiting: transport to nearest

medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.

Rinse mouth.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Respiratory irritation signs and symptoms may include a tem-

porary burning sensation of the nose and throat, coughing,

and/or difficulty breathing.

Breathing of high vapour concentrations may cause central nervous system (CNS) depression resulting in dizziness, light-

headedness, headache and nausea.

Skin irritation signs and symptoms may include a burning sen-

sation, redness, swelling, and/or blisters.

Eye irritation signs and symptoms may include a burning sen-

sation, redness, swelling, and/or blurred vision.

Symptoms may vary by the agent. Symptoms may extend to being locally corrosive to involving generalized systems in-

According to EC No 1907/2006 as amended as at the date of this SDS

Bio Methanol

Version Revision Date: SDS Number: Date of last issue: 17.08.2023

2.3 28.02.2025 800010034380 Print Date 07.03.2025

cluding respiratory system, circulatory system, central nervous system (CNS), and may lead to death.

Defatting dermatitis signs and symptoms may include a burning sensation and/or a dried/cracked appearance.

Acute methanol toxicity may progress as follows: drowsiness or fatigue, and mild irritation of the eyes and mucous membranes; this may be followed (in about 18 to 24 hours and in some cases up to 72 hours) by more severe central nervous system (CNS) effects and visual disturbances including diminished eyesight or blindness, metabolic acidosis (metabolism to formic acid) and deep respirations.

Breathing of high vapour concentrations may cause central nervous system (CNS) depression resulting in dizziness, light-headedness, headache, nausea and loss of coordination. Continued inhalation may result in unconsciousness and death.

Acute irritation of the respiratory system leading to tightness of the chest and an asthmatic condition.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : IMMEDIATE TREATMENT IS EXTREMELY IMPORTANT!

Call a doctor or poison control center for guidance.

Treat symptomatically.

Causes acidosis. Causes central nervous system depression. Symptoms and effects may be delayed for 18 to 24 hours and in some cases up to 72 hours. Treatment of poisoning may require use of ethanol. Treatment of acidosis may include correction with alkali solution, haemodialysis and supportive measures such as correction of electrolyte imbalances, where necessary. Potassium supplements may also be required. May lead to respiratory depression and or central nervous system (CNS) depression resulting difficulty breathing, dizziness, light-headedness, headache, nausea and loss of coordination. Continued exposure may result in unconsciousness and death.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam, water spray or fog. Dry chemical pow-

der, carbon dioxide, sand or earth may be used for small fires

only.

Unsuitable extinguishing

media

None

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

: The vapour is heavier than air, spreads along the ground and

distant ignition is possible.

Carbon monoxide may be evolved if incomplete combustion

According to EC No 1907/2006 as amended as at the date of this SDS

Bio Methanol

Version Revision Date: SDS Number: Date of last issue: 17.08.2023

2.3 28.02.2025 800010034380 Print Date 07.03.2025

occurs.

5.3 Advice for firefighters

Special protective equipment :

for firefighters

Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to

relevant Standards (e.g. Europe: EN469).

Specific extinguishing meth-

ods

Standard procedure for chemical fires.

Further information : Clear fire area of all non-emergency personnel.

Keep adjacent containers cool by spraying with water.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Observe the relevant local and international regulations

Notify authorities if any exposure to the general public or the

environment occurs or is likely to occur.

Local authorities should be advised if significant spillages

cannot be contained.

The vapour is heavier than air, spreads along the ground and

distant ignition is possible.

Vapour may form an explosive mixture with air.

6.1.1 For non emergency personnel: Avoid contact with skin, eyes and clothing.

Isolate hazard area and deny entry to unnecessary or unpro-

tected personnel.

Stay upwind and keep out of low areas. 6.1.2 For emergency responders:

Avoid contact with skin, eyes and clothing.

Isolate hazard area and deny entry to unnecessary or unpro-

tected personnel.

Stay upwind and keep out of low areas.

6.2 Environmental precautions

Environmental precautions

Shut off leaks, if possible without personal risks. Remove all possible sources of ignition in the surrounding area. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. Attempt to disperse the vapour or to direct its flow to a safe location for example by using fog sprays. Take precautionary measures against static discharge. Ensure electrical continuity by bonding and grounding (conthing) all aguinment.

ing and grounding (earthing) all equipment. Ventilate contaminated area thoroughly.

According to EC No 1907/2006 as amended as at the date of this SDS

Bio Methanol

Version Revision Date: SDS Number: Date of last issue: 17.08.2023

2.3 28.02.2025 800010034380 Print Date 07.03.2025

Monitor area with combustible gas indicator.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : For large liquid spills (> 1 drum), transfer by mechanical

means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely For small liquid spills (< 1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove

contaminated soil and dispose of safely.

6.4 Reference to other sections

For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet., For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures : Avoid breathing of or direct contact with material. Only use in

well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see

Section 8 of this Safety Data Sheet.

Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this

material.

Ensure that all local regulations regarding handling and stor-

age facilities are followed.

Advice on safe handling : Avoid contact with skin, eyes and clothing.

Use local exhaust ventilation if there is risk of inhalation of

vapours, mists or aerosols.

Bulk storage tanks should be diked (bunded).

Extinguish any naked flames. Do not smoke. Remove ignition

sources. Avoid sparks.

Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment to

reduce the risk.

The vapours in the head space of the storage vessel may lie in the flammable/explosive range and hence may be flamma-

ble

Properly dispose of any contaminated rags or cleaning mate-

rials in order to prevent fires.

Do NOT use compressed air for filling, discharging, or han-

dling operations.

According to EC No 1907/2006 as amended as at the date of this SDS

Bio Methanol

Version Revision Date: SDS Number: Date of last issue: 17.08.2023

2.3 28.02.2025 800010034380 Print Date 07.03.2025

Product Transfer : Refer to guidance under Handling section.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

The vapour is heavier than air. Beware of accumulation in pits and confined spaces. Refer to section 15 for any additional specific legislation covering the packaging and storage of this

product.

Packaging material : Suitable material: For containers, or container linings use mild

steel, stainless steel.

Unsuitable material: Natural, butyl, neoprene or nitrile rubbers.

Container Advice : Containers, even those that have been emptied, can contain

explosive vapours. Do not cut, drill, grind, weld or perform

similar operations on or near containers.

7.3 Specific end use(s)

Specific use(s) : Ensure that all local regulations regarding handling and stor-

age facilities are followed.

See additional references that provide safe handling practices: American Petroleum Institute 2003 (Protection Against Ignitions Arising out of Static, Lightning and Stray Currents) or National Fire Protection Agency 77 (Recommended Practices

on Static Electricity).

IEC/TS 60079-32-1: Electrostatic hazards, guidance

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Methanol	67-56-1	TLV 15 min	250 ppm	BE OEL
			333 mg/m3	
	Further inform	nation: Absorption of	the agent through the skin, the	he mucous
	membranes o	r the eyes makes up	an important part of total exp	posure. This
	absorption car	n be the result of dire	ect contact as well as the pre	sence in air.
Methanol		TLV 8 hr	200 ppm	BE OEL
			266 mg/m3	
	Further information: Absorption of the agent through the skin, the mucous			
	membranes or the eyes makes up an important part of total exposure. This			
	absorption can be the result of direct contact as well as the presence in air.			
Methanol		TWA	200 ppm	2006/15/EC
			260 mg/m3	
	Further information: Indicative, Identifies the possibility of significant uptake			
	through the skin			

Biological occupational exposure limits

According to EC No 1907/2006 as amended as at the date of this SDS

Bio Methanol

Version Revision Date: SDS Number: Date of last issue: 17.08.2023

2.3 28.02.2025 800010034380 Print Date 07.03.2025

No biological limit allocated.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Methanol	Workers	Inhalation	Acute systemic ef- fects	260 mg/kg
Methanol	Workers	Dermal	Long-term systemic effects	40 mg/kg/day
Methanol	Workers	Inhalation	Long-term systemic effects	260 mg/kg
Methanol	Consumers	Inhalation	Acute systemic effects	50 mg/kg
Methanol	Consumers	Dermal	Long-term systemic effects	8 mg/kg/day
Methanol	Consumers	Inhalation	Long-term systemic effects	50 mg/kg
Methanol	Consumers	Oral	Long-term systemic effects	8 mg/kg/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name		Environmental Compartment	Value
Methanol			
Remarks:	Exposure	assessments have not been presented for the	environment
	therefore	PNEC values not required.	

8.2 Exposure controls

Engineering measures

Read in conjunction with the Exposure Scenario for your specific use contained in the Annex. Use sealed systems as far as possible.

Adequate explosion-proof ventilation to control airborne concentrations below the exposure guidelines/limits.

Local exhaust ventilation is recommended.

Firewater monitors and deluge systems are recommended.

Eye washes and showers for emergency use.

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or for subsequent recycle.

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

Personal protective equipment

Read in conjunction with the Exposure Scenario for your specific use contained in the Annex.

According to EC No 1907/2006 as amended as at the date of this SDS

Bio Methanol

Date of last issue: 17.08.2023 Version Revision Date: SDS Number:

800010034380 2.3 28.02.2025 Print Date 07.03.2025

The provided information is made in consideration of the PPE directive (Council Directive 89/686/EEC) and the CEN European Committee for Standardisation (CEN) standards.

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Eye protection Wear goggles for use against liquids and gas.

Wear full face shield if splashes are likely to occur.

Approved to EU Standard EN166.

Hand protection

Remarks Where hand contact with the product may occur the use of

> gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. Longer term protection: Butyl rubber. Incidental contact/Splash protection: Nitrile rubber. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moistur-

izer is recommended.

Skin and body protection Where risk of splashing or in spillage clean up, use chemical

> resistant one-piece overall with integral hood. Wear antistatic and flame-retardant clothing.

Wear chemical and heat resistant gloves and boots. Where

risk of splashing, also wear an apron.

Protective clothing approved to EU Standard EN14605.

If engineering controls do not maintain airborne concentra-Respiratory protection

> tions to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are unsuitable (e.g. airborne

According to EC No 1907/2006 as amended as at the date of this SDS

Bio Methanol

Version Revision Date: SDS Number: Date of last issue: 17.08.2023

2.3 28.02.2025 800010034380 Print Date 07.03.2025

concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing appa-

ratus.

Where air-filtering respirators are suitable, select an appro-

priate combination of mask and filter.

Select a filter suitable for organic gases and vapours [Type A

boiling point > 65°C (149°F)] meeting EN14387.

Thermal hazards : Not applicable

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid

Colour : Data not available

Odour : characteristic

Odour Threshold : Data not available

Melting / freezing point : -97,5 °C

Boiling point/boiling range : 64,4 - 64,6 °C

Flammability

Flammability (solid, gas) : Not applicable

Lower explosion limit and upper explosion limit / flammability limit

Upper explosion limit /

Upper flammability limit

44 %(V)

Lower explosion limit /

Lower flammability limit

6,1 %(V)

Flash point : 10 °C

Method: Abel

Auto-ignition temperature : 455 °C

Method: ASTM E-659

Decomposition temperature

Decomposition tempera-

ture

Data not available

pH : Not applicable

Viscosity

According to EC No 1907/2006 as amended as at the date of this SDS

Bio Methanol

Version Revision Date: SDS Number: Date of last issue: 17.08.2023

2.3 28.02.2025 800010034380 Print Date 07.03.2025

Viscosity, dynamic : 0,59 mPa.s (20 °C)

Method: ASTM D445

Viscosity, kinematic : Data not available

Solubility(ies)

Water solubility : Completely miscible. (20 °C)

Partition coefficient: n-

octanol/water

log Pow: < 0

Vapour pressure : 13,1 kPa (20 °C)

55,7 kPa (50 °C)

Relative density : Data not available

Density : 792 - 793 kg/m3 (20 °C)

Method: ASTM D4052

Relative vapour density : Data not available

9.2 Other information

Explosive properties : Not applicable

Oxidizing properties : Data not available

Evaporation rate : 1,9

Method: ASTM D 3539, nBuAc=1

6,3

Method: DIN 53170, di-ethyl ether=1

Conductivity: > 10,000 pS/m, A number of factors,

for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid, This material is not expected to be a static accumu-

lator.

Surface tension : 22,6 mN/m, 20 °C

Molecular weight : 32 g/mol

SECTION 10: Stability and reactivity

10.1 Reactivity

The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.

According to EC No 1907/2006 as amended as at the date of this SDS

Bio Methanol

Version Revision Date: SDS Number: Date of last issue: 17.08.2023

2.3 28.02.2025 800010034380 Print Date 07.03.2025

10.2 Chemical stability

No hazardous reaction is expected when handled and stored according to provisions

10.3 Possibility of hazardous reactions

Hazardous reactions : Reacts with strong oxidising agents.

10.4 Conditions to avoid

Conditions to avoid : Avoid heat, sparks, open flames and other ignition sources.

Prevent vapour accumulation.

In certain circumstances product can ignite due to static elec-

tricity.

10.5 Incompatible materials

Materials to avoid : Strong oxidising agents.

10.6 Hazardous decomposition products

Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids and gases including carbon monoxide, carbon dioxide, sulphur oxides and unidentified organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of:

exposure

Exposure may occur via inhalation, ingestion, skin absorption,

skin or eye contact, and accidental ingestion.

Acute toxicity

Components:

Methanol:

Acute oral toxicity : Acute toxicity estimate: 100 mg/kg bw

Remarks: Expert judgement

LD 50 (Rat): >= 1187 - 2769 mg/kg bw

Method: Test(s) equivalent or similar to OECD Test Guideline

401

Remarks: Toxic if swallowed.

There is a marked difference in acute oral toxicity between animals and man, man being more susceptible than animals. The estimated fatal dose for man is 100 milliliters (1/2 cup).

Acute inhalation toxicity : Acute toxicity estimate: 3 mg/l

Exposure time: 4 h

Test atmosphere: vapour Remarks: Expert judgement

According to EC No 1907/2006 as amended as at the date of this SDS

Bio Methanol

Version Revision Date: SDS Number: Date of last issue: 17.08.2023

2.3 28.02.2025 800010034380 Print Date 07.03.2025

LC 50 (Cat): 43,7 mg/l Exposure time: 6 h Test atmosphere: vapour

Method: Acceptable non-standard method.

Remarks: Toxic if inhaled.

Acute dermal toxicity : Acute toxicity estimate: 300 mg/kg bw

Remarks: Expert judgement

LD50 Dermal (Rabbit): 17100 mg/kg bw Remarks: Toxic in contact with skin.

Skin corrosion/irritation

Components:

Methanol:

Species : Rabbit

Method : Acceptable non-standard method.

Remarks : Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Components:

Methanol:

Species : Rabbit

Method : Acceptable non-standard method.

Remarks : Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Components:

Methanol:

Species : Guinea pig

Method : Test(s) equivalent or similar to OECD Test Guideline 406
Remarks : Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Components:

Methanol:

Genotoxicity in vitro : Method: OECD Test Guideline 471

Remarks: Based on available data, the classification criteria

are not met.

Method: Test(s) equivalent or similar to OECD Test Guideline

476

Remarks: Based on available data, the classification criteria

According to EC No 1907/2006 as amended as at the date of this SDS

Bio Methanol

Version Revision Date: SDS Number: Date of last issue: 17.08.2023

2.3 28.02.2025 800010034380 Print Date 07.03.2025

are not met.

Method: Literature data

Remarks: Based on available data, the classification criteria

are not met.

Genotoxicity in vivo : Species: Mouse

Method: Test(s) equivalent or similar to OECD Test Guideline

474

Remarks: Based on available data, the classification criteria

are not met.

Species: Mouse

Method: Literature data

Remarks: Based on available data, the classification criteria

are not met.

Germ cell mutagenicity- As-

sessment

This product does not meet the criteria for classification in

categories 1A/1B.

Carcinogenicity

Components:

Methanol:

Species : Mouse, male and female

Application Route : Inhalation

Method : Test(s) equivalent or similar to OECD Test Guideline 453
Remarks : Based on available data, the classification criteria are not met.

Species : Rat, male and female

Application Route : Inhalation

Method : Test(s) equivalent or similar to OECD Test Guideline 453
Remarks : Based on available data, the classification criteria are not met.

Carcinogenicity - Assess-

ment

This product does not meet the criteria for classification in

categories 1A/1B.

Material	GHS/CLP Carcinogenicity Classification
Methanol	No carcinogenicity classification.

Reproductive toxicity

Components:

Methanol:

Effects on fertility : Species: Rat

Sex: male and female Application Route: Inhalation

According to EC No 1907/2006 as amended as at the date of this SDS

Bio Methanol

Version Revision Date: SDS Number: Date of last issue: 17.08.2023

2.3 28.02.2025 800010034380 Print Date 07.03.2025

Method: Equivalent or similar to OECD Test Guideline 416 Remarks: Based on available data, the classification criteria

are not met.

Reproductive toxicity - As-

sessment

This product does not meet the criteria for classification in

categories 1A/1B.

STOT - single exposure

Components:

Methanol:

Exposure routes : Oral, Inhalation, Dermal

Target Organs : Central nervous system, optic nerve

Remarks : Causes damage to organs.

High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea; continued inhalation may result in unconsciousness and/or death. Visual system: may cause marked impairment of vision or

blindness.

STOT - repeated exposure

Components:

Methanol:

Remarks : Visual system: may cause decreased color perception.

Based on available data, the classification criteria are not met.

Repeated dose toxicity

Components:

Methanol:

Species : Monkey, male

Application Route : Oral

Method : Literature data

Target Organs : No specific target organs noted

Species : Rat, male and female

Application Route : Inhalation Test atmosphere : vapour

Method : Test(s) equivalent or similar to OECD Test Guideline 453

Target Organs : No specific target organs noted

According to EC No 1907/2006 as amended as at the date of this SDS

Bio Methanol

Version Revision Date: SDS Number: Date of last issue: 17.08.2023

2.3 28.02.2025 800010034380 Print Date 07.03.2025

Aspiration toxicity

Components:

Methanol:

Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

Further information

Product:

Remarks : Unless indicated otherwise, the data presented is representa-

tive of the product as a whole, rather than for individual com-

ponent(s).

Components:

Methanol:

Remarks : Classifications by other authorities under varying regulatory

frameworks may exist.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Methanol:

Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): 15.400 mg/l

Exposure time: 96 h

Method: Other guideline method. Remarks: Practically non toxic: LL/EL/IL50 > 100 mg/l

LL/EL/1L50 > 100 mg/

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 18.260 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 202 Remarks: Practically non toxic:

LL/EL/IL50 > 100 mg/l

According to EC No 1907/2006 as amended as at the date of this SDS

Bio Methanol

Version Revision Date: SDS Number: Date of last issue: 17.08.2023

2.3 28.02.2025 800010034380 Print Date 07.03.2025

Toxicity to algae/aquatic plants : EC50 (Selenastrum capricornutum (green algae)): 22.000

mg/l

Exposure time: 96 h

Method: OECD Test Guideline 201 Remarks: Practically non toxic: LL/EL/IL50 > 100 mg/l

Toxicity to microorganisms : IC50 (Activated sludge): > 1.000 mg/l

Exposure time: 3 h

Method: OECD Test Guideline 209 Remarks: Practically non toxic: LL/EL/IL50 > 100 mg/l

Toxicity to fish (Chronic tox-

icity)

NOEC: 7.900 mg/l

Exposure time: 200 d Species: Oryzias latipes (Japanese medaka)

Method: Other guideline method.

Remarks: NOEC/NOEL > 100 mg/l

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOEC: 208 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea)

Method: Based on quantitative structure-activity relationship

(QSAR) modelling

Remarks: NOEC/NOEL > 100 mg/l

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: Not Persistent per IMO criteria.

International Oil Pollution Compensation (IOPC) Fund definition: "A non-persistent oil is oil, which, at the time of shipment, consists of hydrocarbon fractions, (a) at least 50% of which, by volume, distills at a temperature of 340°C (645°F) and (b) at least 95% of which, by volume, distills at a temperature of 370°C (700°F) when tested by the ASTM Method D-86/78 or any subsequent revision

thereof."

Components:

Methanol:

Biodegradability : Biodegradation: 82,7 %

Exposure time: 5 d

Method: Other guideline method. Remarks: Readily biodegradable.

Oxidises rapidly by photo-chemical reactions in air.

According to EC No 1907/2006 as amended as at the date of this SDS

Bio Methanol

Version Revision Date: SDS Number: Date of last issue: 17.08.2023

2.3 28.02.2025 800010034380 Print Date 07.03.2025

12.3 Bioaccumulative potential

Components:

Methanol:

Bioaccumulation : Species: Cyprinus carpio (Carp)

Exposure time: 72 h

Bioconcentration factor (BCF): 1

Method: Test(s) equivalent or similar to OECD Test Guideline

305

Remarks: Does not bioaccumulate significantly.

12.4 Mobility in soil

Components:

Methanol:

Mobility : Remarks: If product enters soil, it will be highly mobile and

may contaminate groundwater.

12.5 Results of PBT and vPvB assessment

Components:

Methanol:

Assessment : The substance does not fulfill all screening criteria for persis-

tence, bioaccumulation and toxicity and hence is not consid-

ered to be PBT or vPvB..

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to

have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological infor-

mation

Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Recover or recycle if possible.

It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to

According to EC No 1907/2006 as amended as at the date of this SDS

Bio Methanol

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 17.08.2023

 2.3
 28.02.2025
 800010034380
 Print Date 07.03.2025

determine the proper waste classification and disposal methods in compliance with applicable regulations.

Do not dispose into the environment, in drains or in water

courses.

Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment. Waste, spills or used product is dangerous waste.

Disposal should be in accordance with applicable regional, national, and local laws and regulations.

Local regulations may be more stringent than regional or national requirements and must be complied with.

MARPOL - see International Convention for the Prevention of Pollution from Ships (MARPOL 73/78) which provides technical aspects at controlling pollutions from ships.

Contaminated packaging : Drain container thoroughly.

After draining, vent in a safe place away from sparks and fire.

Residues may cause an explosion hazard. Do not, puncture, cut, or weld uncleaned drums. Send to drum recoverer or metal reclaimer.

Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand.

SECTION 14: Transport information

14.1 UN number or ID number

ADN : 1230
ADR : 1230
RID : 1230
IMDG : 1230
IATA : 1230

14.2 UN proper shipping name

ADN : METHANOL
ADR : METHANOL
RID : METHANOL
IMDG : METHANOL

IATA : Methanol

14.3 Transport hazard class(es)

ADN : 3 **ADR** : 3

According to EC No 1907/2006 as amended as at the date of this SDS

Bio Methanol

Version Revision Date: SDS Number: Date of last issue: 17.08.2023

2.3 28.02.2025 800010034380 Print Date 07.03.2025

 RID
 : 3

 IMDG
 : 3

 IATA
 : 3

14.4 Packing group

ADN

Packing group : II
Classification Code : FT1
Labels : 3 (6.1)

CDNI Inland Water Waste : NST 8192 Methanol

Agreement

ADR

Packing group : II
Classification Code : FT1
Hazard Identification Number : 336
Labels : 3 (6.1)

RID

Packing group : II
Classification Code : FT1
Hazard Identification Number : 336
Labels : 3 (6.1)

IMDG

Packing group : II Labels : 3 (6.1)

IATA

Packing group : II Labels : 3 (6.1)

14.5 Environmental hazards

ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

rid

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

Remarks : Special Precautions: Refer to Section 7, Handling & Storage,

for special precautions which a user needs to be aware of or

needs to comply with in connection with transport.

14.7 Maritime transport in bulk according to IMO instruments

Pollution category : Y Ship type : 3

Product name : Methanol

According to EC No 1907/2006 as amended as at the date of this SDS

Bio Methanol

Version Revision Date: SDS Number: Date of last issue: 17.08.2023

2.3 28.02.2025 800010034380 Print Date 07.03.2025

Additional Information: This product may be transported under nitrogen blanketing.

Nitrogen is an odourless and invisible gas. Exposure to nitrogen enriched atmospheres displaces available oxygen which may cause asphyxiation or death. Personnel must observe strict safety precautions when involved with a confined space

Transport in bulk according to Annex II of Marpol and the IBC

Code

entry.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - List of substances subject to authorisation (Annex XIV) : Product is not subject to Authorisation under REACH.

22

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).

This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Methanol

22 Methanol

Other regulations:

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

The components of this product are reported in the following inventories:

AIIC : Listed

DSL : Listed

IECSC : Listed

ENCS : Listed

KECI : Listed

NZIoC : Listed

According to EC No 1907/2006 as amended as at the date of this SDS

Bio Methanol

Version Revision Date: SDS Number: Date of last issue: 17.08.2023

2.3 28.02.2025 800010034380 Print Date 07.03.2025

PICCS : Listed

TSCA : Listed

TCSI : Listed

15.2 Chemical safety assessment

A Chemical Safety Assessment has been carried out for this substance.

SECTION 16: Other information

Full text of other abbreviations

2006/15/EC : Europe. Indicative occupational exposure limit values

BE OEL : Belgium. Occupational exposure limit values

2006/15/EC / TWA : Limit Value - eight hours
BE OEL / TLV 8 hr : Long term exposure limit
BE OEL / TLV 15 min : Short term exposure limit

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA -European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI -Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

According to EC No 1907/2006 as amended as at the date of this SDS

Bio Methanol

Version Revision Date: SDS Number: Date of last issue: 17.08.2023

2.3 28.02.2025 800010034380 Print Date 07.03.2025

Further information

Training advice : Provide adequate information, instruction and training for op-

erators.

Other information : For Industry guidance and tools on REACH please visit the

CEFIC website at http://cefic.org/Industry-support.

The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not consid-

ered to be PBT or vPvB.

A vertical bar (|) in the left margin indicates an amendment

from the previous version.

Sources of key data used to compile the Safety Data

Sheet

The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU

IUCLID date base, EC 1272 regulation, etc).

Identified Uses according to the Use Descriptor System

Uses - Worker

Title : Manufacture of substance

- Industrial

Uses - Worker

Title : Use as an intermediate

- Industrial

Uses - Worker

Title : Distribution of substance

- Industrial

Uses - Worker

Title : Formulation & (re)packing of substances and mixtures

- Industrial

Uses - Worker

Title : Use in Cleaning Agents

- Industrial

Uses - Worker

Title : Use in Cleaning Agents

- Professional

Uses - Worker

Title : Use as a fuel

- Industrial

According to EC No 1907/2006 as amended as at the date of this SDS

Bio Methanol

Version Revision Date: SDS Number: Date of last issue: 17.08.2023

2.3 28.02.2025 800010034380 Print Date 07.03.2025

Uses - Worker

Title : Use as a fuel

- Professional

Uses - Worker

Title : Use in laboratories

- Industrial

Uses - Worker

Title : Use in laboratories

- Professional

Identified Uses according to the Use Descriptor System

Uses - Consumer

Title : Use as a fuel

- Consumer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

BE / EN

According to EC No 1907/2006 as amended as at the date of this SDS

Bio Methanol

Version Revision Date: SDS Number: Date of last issue: 17.08.2023

2.3 28.02.2025 800010034380 Print Date 07.03.2025

Exposure Scenario - Worker

30000000552	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Manufacture of substance- Industrial
Use Descriptor	Sector of Use: SU 3, SU8, SU9 Process Categories: PROC 1, PROC 2, PROC 3, PROC 4, PROC 8a, PROC 8b, PROC 15 Environmental Release Categories: ERC1, ERC4
Scope of process	Manufacture of the substance or use as a process chemical or extraction agent. Includes recycling/ recovery, material transfers, storage, maintenance and loading (including marine vessel/barge, road/rail car and bulk container), sampling and associated laboratory activities.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
Section 2.1	Control of Worker Exposure
Product Characteristics	
Physical form of product	Liquid, vapour pressure > 10 kPa at STP
Concentration of the Substance in Mixture/Article	Covers use of substance/product up to 100% (unless stated differently).,
Frequency and Duration of	Use
Covers daily exposures up to	8 hours (unless stated differently).
Other Operational Conditio	
Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.	
Contributing Scenarios	Risk Management Measures
General exposures (closed systems)	No specific measures identified.
General exposures (closed systems) with sample collection General measures (skin irritants).	Provide extraction ventilation at points where emissions occur.
General exposures (closed systems)Use in contained batch processes	Provide extraction ventilation at points where emissions occur.
General exposures (open systems)Batch processwith sample collection	Provide extraction ventilation at points where emissions occur.
Process sampling	Provide extraction ventilation at points where emissions occur.
Laboratory activities	Handle in a fume cupboard or under extract ventilation.
Bulk transfers(open sys-	Ensure material transfers are under containment or extract

According to EC No 1907/2006 as amended as at the date of this SDS

Bio Methanol

Version Revision Date: SDS Number: Date of last issue: 17.08.2023

2.3 28.02.2025 800010034380 Print Date 07.03.2025

tems)with potential for aerosol generation.	ventilation.	
Bulk transfers(closed systems)	Ensure material transfers are under containment or extract ventilation.	
Equipment cleaning and maintenance	Drain down and flush system prior to equipment opening or maintenance.	
Storage.General measures (skin irritants).	Provide extraction ventilation at points where emissions occur.	
Section 2.2	Control of Environmental Exposure	
No exposure assessment presented for the environment.		

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
The ECETOC TRA tool has indicated.	been used to estimate workplace exposures unless otherwise

Section 3.2 - Environment

No exposure assessment presented for the environment.

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	
Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.	

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 -Environment	
No exposure assessment presented for the environment.	

According to EC No 1907/2006 as amended as at the date of this SDS

Bio Methanol

Version Revision Date: SDS Number: Date of last issue: 17.08.2023

2.3 28.02.2025 800010034380 Print Date 07.03.2025

Exposure Scenario - Worker

30000000554	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Use as an intermediate- Industrial
Use Descriptor	Sector of Use: SU 3, SU8, SU9 Process Categories: PROC 1, PROC 2, PROC 3, PROC 4, PROC 8a, PROC 8b, PROC 15 Environmental Release Categories: ERC6a
Scope of process	Use of substance as an intermediate (not related to Strictly Controlled Conditions). Includes recycling/ recovery, material transfers, storage, sampling, associated laboratory activities, maintenance and loading (including marine vessel/barge, road/rail car and bulk container).

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Section 2.1	Control of Worker Exposure	
Product Characteristics	•	
Physical form of product	Liquid, vapour pressure > 10 kPa at STP	
Concentration of the Substance in Mixture/Article	Covers use of substance/product up to 100% (unless stated differently).,	
Frequency and Duration of	Use	
Covers daily exposures up to	8 hours (unless stated differently).	
Other Operational Conditio	ns affecting Exposure	
Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.		
Contributing Scenarios	Risk Management Measures	
General exposures (closed systems)	No specific measures identified.	
General exposures (closed systems) with sample collection General measures (skin irritants).	Provide extraction ventilation at points where emissions occur.	
General exposures (closed systems)Use in contained batch processes	Provide extraction ventilation at points where emissions occur.	
General exposures (open systems)Batch processwith sample collection	Provide extraction ventilation at points where emissions occur.	
Process sampling	Provide extraction ventilation at points where emissions occur.	
Laboratory activities	Handle in a fume cupboard or under extract ventilation.	
Bulk transfers(open sys-	Ensure material transfers are under containment or extract	

According to EC No 1907/2006 as amended as at the date of this SDS

Bio Methanol

Version Revision Date: SDS Number: Date of last issue: 17.08.2023

2.3 28.02.2025 800010034380 Print Date 07.03.2025

tems)with potential for aer-	ventilation.	
osol generation.		
Bulk transfers(closed sys-	Ensure material transfers are under containment or extract	
tems)	ventilation.	
Equipment cleaning and	Drain down and flush system prior to equipment opening or	
maintenance	maintenance.	
Storage.General measures	Provide extraction ventilation at points where emissions oc-	
(skin irritants).	cur.	
Section 2.2	Control of Environmental Exposure	
No exposure assessment presented for the environment.		

SECTION 3	EXPOSURE ESTIMATION	
Section 3.1 - Health		
The ECETOC TRA tool has b	peen used to estimate workplace exposures unless otherwise	

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

Section 3.2 - Environment

No exposure assessment presented for the environment.

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO	
Section 4.1 - Health		
Duralista di sun accuracione que mati aumanta dita accesa dita DN/M/EL cultare tha Diale Managaranta		

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 -Environment No exposure assessment presented for the environment.

According to EC No 1907/2006 as amended as at the date of this SDS

Bio Methanol

Version Revision Date: SDS Number: Date of last issue: 17.08.2023

2.3 28.02.2025 800010034380 Print Date 07.03.2025

Exposure Scenario - Worker

30000000556		
SECTION 1	EXPOSURE SCENARIO TITLE	
Title	Distribution of substance- Industrial	
Use Descriptor	Sector of Use: SU 3, SU8, SU9 Process Categories: PROC 1, PROC 2, PROC 3, PROC 4, PROC 8a, PROC 8b, PROC 9, PROC 15 Environmental Release Categories: ERC1, ERC2, ERC3, ERC4, ERC5, ERC6a, ERC7	
Scope of process	Loading (including marine vessel/barge, rail/road car and IBC loading) and repacking (including drums and small packs) of substance, including its sampling, storage, unloading distribution and associated laboratory activities.	

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Section 2.1	Control of Worker Exposure	
Product Characteristics		
Physical form of product	Liquid, vapour pressure > 10 kPa at STP	
Concentration of the Sub-	Covers use of substance/product up to 100% (unless stated	1
stance in Mixture/Article	differently).,	
Frequency and Duration of	Use	
Covers daily exposures up to	8 hours (unless stated differently).	
Other Operational Conditio		
	an 20°C above ambient temperature (unless stated differently)).
Assumes a good basic stand	ard of occupational hygiene is implemented.	
Contributing Scenarios	Risk Management Measures	
General exposures (closed systems)	No other specific measures identified.	
General exposures (closed systems) with sample collection General measures (skin irritants).	No other specific measures identified.	
General exposures (closed systems)Use in contained batch processes	No other specific measures identified.	
General exposures (open systems)Batch processwith sample collection	Provide extraction ventilation at points where emissions occur.	
Product sampling.	Provide extraction ventilation at points where emissions occur.	
Laboratory activities	Provide extraction ventilation at points where emissions occur.	

According to EC No 1907/2006 as amended as at the date of this SDS

Bio Methanol

Version Revision Date: SDS Number: Date of last issue: 17.08.2023

2.3 28.02.2025 800010034380 Print Date 07.03.2025

Bulk transfers(closed systems)	Ensure material transfers are under containment or extract ventilation.	
Bulk transfers(open systems)	Ensure material transfers are under containment or extract ventilation.	
Drum and small package filling	Provide extraction ventilation at points where emissions occur.	
Equipment cleaning and maintenance	Drain down and flush system prior to equipment opening or maintenance.	
Storage.	Store substance within a closed system.	
Section 2.2 Control of Environmental Exposure		
No exposure assessment presented for the environment.		

SECTION 3	EXPOSURE ESTIMATION	
Section 3.1 - Health		
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise		

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

Section 3.2 - Environment

No exposure assessment presented for the environment.

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 - Environment

No exposure assessment presented for the environment.

According to EC No 1907/2006 as amended as at the date of this SDS

Bio Methanol

Version Revision Date: SDS Number: Date of last issue: 17.08.2023

2.3 28.02.2025 800010034380 Print Date 07.03.2025

Exposure Scenario - Worker

Exposure occitatio Work	Exposure Scenario - Worker	
30000000560		
SECTION 1	EXPOSURE SCENARIO TITLE	
Title	Formulation & (re)packing of substances and mixtures- Industrial	
Use Descriptor	Sector of Use: SU 3, SU 10 Process Categories: PROC 1, PROC 2, PROC 3, PROC 4, PROC 5, PROC 8a, PROC 8b, PROC 9, PROC 14, PROC 15 Environmental Release Categories: ERC2	
Scope of process	Formulation, packing and re-packing of the substance and its mixtures in batch or continuous operations, including storage, materials transfers, mixing, tabletting, compression, pelletisation, extrusion, large and small scale packing, sampling, maintenance and associated laboratory activities.	

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES		
Section 2.1	Control of Worker Exposure		
Product Characteristics			
Physical form of product	Liquid, vapour pressure > 10 kPa at STP		
Concentration of the Substance in Mixture/Article	Covers use of substance/product up to 100% (unless stated differently).,		
Frequency and Duration of	Use		
	8 hours (unless stated differently).		
Other Operational Condition	ns affecting Exposure		
Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.			
Contributing Scenarios	Risk Management Measures		
General exposures (closed systems)	No other specific measures identified.		
General exposures (closed systems) with sample collectionGeneral measures (skin irritants).	No other specific measures identified.		
General exposures (closed systems)Use in contained batch processes	No other specific measures identified.		
General exposures (open systems)Batch processwith sample collectionwith potential for aerosol generation.	Provide extraction ventilation at points where emissions occur.		
Batch processes at elevated temperatures	Provide extraction ventilation at points where emissions occur.		

According to EC No 1907/2006 as amended as at the date of this SDS

Bio Methanol

Version Revision Date: SDS Number: Date of last issue: 17.08.2023

2.3 28.02.2025 800010034380 Print Date 07.03.2025

Process sampling	Provide extraction ventilation at points where emissions occur.	
Laboratory activities	Handle in a fume cupboard or under extract ventilation.	
Bulk transfers	Provide extraction ventilation at points where emissions occur.	
Mixing operations (open systems) with potential for aerosol generation.	Provide extraction ventilation at points where emissions occur.	
ManualTransfer from/pouring from containers	Provide extraction ventilation at points where emissions occur.	
Drum/batch transfers	Provide extraction ventilation at points where emissions occur.	
Production or preparation or articles by tabletting, compression, extrusion or pelletisation	Provide extraction ventilation at points where emissions occur.	
Drum and small package filling	Ensure material transfers are under containment or extract ventilation.	
Equipment cleaning and maintenance	Drain down and flush system prior to equipment opening or maintenance.	
Storage.	Store substance within a closed system.	
Section 2.2	Control of Environmental Exposure	
No exposure assessment pro	esented for the environment.	

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise	

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

Section 3.2 - Environment

No exposure assessment presented for the environment.

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE
	EXPOSURE SCENARIO
Section 4.1 - Health	

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

According to EC No 1907/2006 as amended as at the date of this SDS

Bio Methanol

Version Revision Date: SDS Number: Date of last issue: 17.08.2023

2.3 28.02.2025 800010034380 Print Date 07.03.2025

Section 4.2 -Environment

No exposure assessment presented for the environment.

According to EC No 1907/2006 as amended as at the date of this SDS

Bio Methanol

Version Revision Date: SDS Number: Date of last issue: 17.08.2023

2.3 28.02.2025 800010034380 Print Date 07.03.2025

Exposure Scenario - Worker

30000000565	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Use in Cleaning Agents- Industrial
Use Descriptor	Sector of Use: SU 3 Process Categories: PROC 1, PROC 2, PROC 3, PROC 4, PROC 7, PROC 8a, PROC 8b, PROC 10, PROC 13 Environmental Release Categories: ERC4
Scope of process	Covers the use as a component of cleaning products including transfer from storage, pouring/unloading from drums or containers. Exposures during mixing/diluting in the preparatory phase and cleaning activities (including spraying, brushing, dipping, wiping, automated and by hand), related equipment cleaning and maintenance.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Section 2.1	Control of Worker Exposure	
Product Characteristics		
Physical form of product	Liquid, vapour pressure > 10 kPa at STP	
Concentration of the Sub-	Covers use of substance/product up to 100% (unless stated	
stance in Mixture/Article	differently).,	
Frequency and Duration of	Use	
Covers daily exposures up to	8 hours (unless stated differently).	
Other Operational Conditio		
Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.		
Contributing Scenarios	Risk Management Measures	
Bulk transfers	Ensure material transfers are under containment or extract ventilation.	
Automated process with (semi) closed systems.Use in contained systems	Ensure material transfers are under containment or extract ventilation.	
Automated process with (semi) closed systems.Use in contained systems	Ensure material transfers are under containment or extract ventilation.	
Application of cleaning products in closed systemsUse in contained systems	Ensure material transfers are under containment or extract ventilation.	
Filling/ preparation of equipment from drums or containers.Dedicated facility	Ensure material transfers are under containment or extract ventilation.	

According to EC No 1907/2006 as amended as at the date of this SDS

Bio Methanol

Version Revision Date: SDS Number: Date of last issue: 17.08.2023

2.3 28.02.2025 800010034380 Print Date 07.03.2025

No exposure assessment pre	sented for the environment.	
Section 2.2	Control of Environmental Exposure	
Storage.Product sampling.	Ensure material transfers are under contaventilation.	ainment or extract
Equipment cleaning and maintenance	Ensure material transfers are under conta ventilation.	ainment or extract
CleaningManualSurfacesno spraying	Provide the operation with a properly site	d receiving hood.
Cleaning with high pressure washers	Carry out in a vented booth or extracted of Stay upwind/ keep distance from source. Clean equipment and the work area ever Ensure control measures are regularly intained.	y day.
Cleaning with low-pressure washers	Provide the operation with a properly sited receiving hood.	
Degreasing small objects in cleaning station	Provide the operation with a properly sited receiving hood.	
processesTreatment by heating	Trovide the operation with a property sited receiving mood.	
Use in contained batch	Provide the operation with a properly site	d receiving hood

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
The ECETOC TRA tool has b	peen used to estimate workplace exposures unless otherwise

indicated.

Section 3.2 -Environment No exposure assessment presented for the environment.

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	
Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management	
Measures/Operational Conditions outlined in Section 2 are implemented.	

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 -Environment
No exposure assessment presented for the environment.

According to EC No 1907/2006 as amended as at the date of this SDS

Bio Methanol

Version Revision Date: SDS Number: Date of last issue: 17.08.2023

2.3 28.02.2025 800010034380 Print Date 07.03.2025

30000000566	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Use in Cleaning Agents- Professional
Use Descriptor	Sector of Use: SU 22 Process Categories: PROC 1, PROC 2, PROC 3, PROC 4, PROC 8a, PROC 8b, PROC 10, PROC 11, PROC 13 Environmental Release Categories: ERC8a, ERC8d
Scope of process	Covers the use as a component of cleaning products including pouring/unloading from drums or containers; and exposures during mixing/diluting in the preparatory phase and cleaning activities (including spraying, brushing, dipping, wiping automated and by hand).

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES		
Section 2.1	Control of Worker Exposure		
Product Characteristics			
Physical form of product	Liquid, vapour pressure > 10 kPa at STP		
Concentration of the Substance in Mixture/Article	Covers use of substance/product up to 1 differently).,	00% (unless stated	
Frequency and Duration of	Use		
Covers daily exposures up to	8 hours (unless stated differently).		
Other Operational Condition	ns affecting Exposure		
	an 20°C above ambient temperature (unles ard of occupational hygiene is implemente		
Contributing Scenarios	Risk Management Measures		

Contributing Scenarios Risk		Management Measures	
Filling/ preparation of equipment from drums or containers.Dedicated facility		Limit the substance content in the product to 5 %. , or: Ensure material transfers are under containment or extra ventilation.	ct
Automated process with (sem closed systems.Use in contain systems	,	Provide the operation with a properly sited receiving hood	d.
Automated process with (semi) closed systems.Use in contained systemsDrum/batch transfers		Provide the operation with a properly sited receiving hood	d.
Semi Automated process. (e. Semi automatic application of floor care and maintenance pucts)	f	Provide the operation with a properly sited receiving hood Avoid carrying out activities involving exposure for more than 4 hours	d.
Filling/ preparation of equipm from drums or containers.Nor dedicated facility		Limit the substance content in the product to 5 %. , or: Ensure material transfers are under containment or extra	ct

According to EC No 1907/2006 as amended as at the date of this SDS

Bio Methanol

Version Revision Date: SDS Number: Date of last issue: 17.08.2023

2.3 28.02.2025 800010034380 Print Date 07.03.2025

	ventilation.
Dipping, immersion and pouring- ManualCleaningSurfaces	Provide the operation with a properly sited receiving hood.
Cleaning with low-pressure washersRolling, Brushingno spraying	Limit the substance content in the product to 5 %.
Cleaning with high pressure washersSpraying	Limit the substance content in the product to 5 %. Avoid carrying out activities involving exposure for more than 4 hours Use long handled tools where possible. Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.
SprayingManualSurfacesCleaning	Limit the substance content in the product to 5 %. , or: Provide the operation with a properly sited receiving hood.
Ad hoc manual application via trigger sprays, dipping, etc.Rolling, Brushing	Limit the substance content in the product to 5 %. , or: Provide the operation with a properly sited receiving hood.
Ad hoc manual application via trigger sprays, dipping, etc.Rolling, Brushing	Limit the substance content in the product to 5 %.
Application of cleaning products in closed systems	Ensure material transfers are under containment or extract ventilation. Avoid carrying out activities involving exposure for more than 4 hours
Cleaning of medical devices	Provide the operation with a properly sited receiving hood. Avoid carrying out activities involving exposure for more than 4 hours
Equipment cleaning and maintenance	Limit the substance content in the product to 5 %.
Storage.General measures (skin irritants).	Ensure material transfers are under containment or extract ventilation.

Section 2.2	Control of Environmental Exposure	
No exposure assessment pro	esented for the environment.	

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
The ECETOC TRA tool has be indicated.	een used to estimate workplace exposures unless otherwise

Section	3)	-Enviro	nmont

According to EC No 1907/2006 as amended as at the date of this SDS

Bio Methanol

Version Revision Date: SDS Number: Date of last issue: 17.08.2023

2.3 28.02.2025 800010034380 Print Date 07.03.2025

SECTION 4 GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO

Section 4.1 - Health

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 - Environment

According to EC No 1907/2006 as amended as at the date of this SDS

Bio Methanol

Version Revision Date: SDS Number: Date of last issue: 17.08.2023

2.3 28.02.2025 800010034380 Print Date 07.03.2025

Exposure Scenario - Worker

Use as a fuel(closed sys-

Equipment cleaning and

tems)

maintenance

Storage.

30000000562	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Use as a fuel- Industrial
Use Descriptor	Sector of Use: SU 3, SU 10 Process Categories: PROC 1, PROC 2, PROC 3, PROC 8a, PROC 8b, PROC 16 Environmental Release Categories: ERC7
Scope of process	Covers the use as a fuel (or fuel additive) and includes activities associated with its transfer, use, equipment maintenance and handling of waste.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES		
Section 2.1	Control of Worker Exposure		
Product Characteristics			
Physical form of product	Liquid, vapour pressure > 10 kPa at STP		
Concentration of the Substance in Mixture/Article	Covers use of substance/product up to 100% (unless stated differently).,		
Frequency and Duration of	Use		
Covers daily exposures up to	8 hours (unless stated differently).		
Other Operational Conditio			
Contributing Scenarios	ard of occupational hygiene is implemented. Risk Management Measures		
Bulk transfers	No other specific measures identified.		
Drum/batch transfers	Provide extraction ventilation at points where emissions occur.		
General exposures (closed systems)	No other specific measures identified.		
	No other specific measures identified. Provide extraction ventilation at points where emissions occur.		

maintenance.

No other specific measures identified.

Store substance within a closed system.

Drain down and flush system prior to equipment opening or

According to EC No 1907/2006 as amended as at the date of this SDS

Bio Methanol

Version Revision Date: SDS Number: Date of last issue: 17.08.2023

2.3 28.02.2025 800010034380 Print Date 07.03.2025

Section 2.2	Control of Environmental Exposure	
No exposure assessment pres	sented for the environment.	

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
The ECETOC TRA tool has be	been used to estimate workplace exposures unless otherwise
indicated.	

Section 3.2 - Environment

No exposure assessment presented for the environment.

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - He	alth
Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management	
Measures/Operational Conditions outlined in Section 2 are implemented.	
Where other Rick Management Measures/Operational Conditions are adopted, then users	

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 - Environment

According to EC No 1907/2006 as amended as at the date of this SDS

Bio Methanol

Version Revision Date: SDS Number: Date of last issue: 17.08.2023

2.3 28.02.2025 800010034380 Print Date 07.03.2025

30000000563	
3000000000	
050510114	EVECUIES COENTRE STATE
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Use as a fuel- Professional
Use Descriptor	Sector of Use: SU 22
	Process Categories: PROC 1, PROC 2, PROC 3, PROC 8a,
	PROC 8b, PROC 16
	Environmental Release Categories: ERC9a, ERC9b
Scope of process	Covers the use as a fuel (or fuel additive) and includes activi-
- Coope of process	ties associated with its transfer, use, equipment maintenance and handling of waste.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Section 2.1	Control of Worker Exposure	
Product Characteristics		
Physical form of product	Liquid, vapour pressure > 10 kPa at STP	
Concentration of the Substance in Mixture/Article	Covers use of substance/product up to 100% (unless stated differently).,	
Frequency and Duration of		
Covers daily exposures up to	8 hours (unless stated differently).	
Other Operational Conditio	ns affecting Exposure	
Assumes a good basic stand	an 20°C above ambient temperature (unless stated differently). ard of occupational hygiene is implemented.	
Contributing Scenarios	Risk Management Measures	
Drum/batch transfersDedicated facility	Avoid carrying out activities involving exposure for more than 1 hour.	
Bulk transfersDedicated facility	Avoid carrying out activities involving exposure for more than 1 hour.	
General exposures (closed systems)	No other specific measures identified.	
General exposures (closed systems)General measures (skin irritants).	No other specific measures identified.	
General exposures (closed systems)Batch process	No other specific measures identified.	
Use as a fuel(closed systems)	No other specific measures identified.	
Equipment cleaning and maintenance	Drain down system prior to equipment opening or maintenance. Avoid carrying out activities involving exposure for more than 1 hour.	

According to EC No 1907/2006 as amended as at the date of this SDS

Bio Methanol

Version Revision Date: SDS Number: Date of last issue: 17.08.2023

2.3 28.02.2025 800010034380 Print Date 07.03.2025

Storage.	Store substance within a closed system.	
Section 2.2	Control of Environmental Exposure	
No exposure assessment presented for the environment.		

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
The ECETOC TRA tool has be indicated.	peen used to estimate workplace exposures unless otherwise

Section 3.2 - Environment

No exposure assessment presented for the environment.

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO	
Section 4.1 - Health		
Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management		
Measures/Operational Conditions outlined in Section 2 are implemented.		
Where other Risk Management Measures/Operational Conditions are adopted, then users		
should ensure that risks are r	nanaged to at least equivalent levels.	

Section 4.2 -Environment

According to EC No 1907/2006 as amended as at the date of this SDS

Bio Methanol

Version Revision Date: SDS Number: Date of last issue: 17.08.2023

2.3 28.02.2025 800010034380 Print Date 07.03.2025

30000000567	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Use in laboratories- Industrial
Use Descriptor	Sector of Use: SU 3, SU 10 Process Categories: PROC 10, PROC 15 Environmental Release Categories: ERC4
Scope of process	Use of the substance within laboratory settings, including material transfers and equipment cleaning.

SECTION 2	OPERATIONAL CONDITIONS AND RIS	K MANAGEMENT	
Section 2.1	Control of Worker Exposure		
Product Characteristics	•		
Physical form of product	Liquid, vapour pressure > 10 kPa at STP	Liquid, vapour pressure > 10 kPa at STP	
Concentration of the Sub-	Covers use of substance/product up to 100% (unless stated		
stance in Mixture/Article	differently).,		
Frequency and Duration of Use			
Covers daily exposures up to 8 hours (unless stated differently).			
Other Operational Conditio	ns affecting Exposure		
Assumes use at not more than 20°C above ambient temperature (unless stated differently).			
Assumes a good basic standard of occupational hygiene is implemented.			
Contributing Scenarios	Risk Management Measures		
Laboratory activities	Handle in a fume cupboard or under extract ventilation.		
CleaningRolling, Brush-	Handle in a fume cupboard or under extract ventilation.		
ingVessel and container	,		
cleaning			
Section 2.2	Control of Environmental Exposure		
No exposure assessment pre	sented for the environment.		

SECTION 3	EXPOSURE ESTIMATION	
Section 3.1 - Health		
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.		

Section 3.2 -Environment	
No exposure assessment presented for the environment.	

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	

According to EC No 1907/2006 as amended as at the date of this SDS

Bio Methanol

Version Revision Date: SDS Number: Date of last issue: 17.08.2023

2.3 28.02.2025 800010034380 Print Date 07.03.2025

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 -Environment

According to EC No 1907/2006 as amended as at the date of this SDS

Bio Methanol

Version Revision Date: SDS Number: Date of last issue: 17.08.2023

2.3 28.02.2025 800010034380 Print Date 07.03.2025

Exposure ocertailo - Worker	
30000000568	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Use in laboratories- Professional
Use Descriptor	Sector of Use: SU 22 Process Categories: PROC 10, PROC 15 Environmental Release Categories: ERC8a
Scope of process	Use of small quantities within laboratory settings, including material transfers and equipment cleaning.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MAN MEASURES	IAGEMENT	
Section 2.1	Control of Worker Exposure		
Product Characteristics			
Physical form of product	Liquid, vapour pressure > 10 kPa at STP		
Concentration of the Sub-	Covers use of substance/product up to 100% (unless stated		
stance in Mixture/Article	differently).,		
Frequency and Duration of	Use		
Covers daily exposures up to 8 hours (unless stated differently).			
Other Operational Conditio	ns affecting Exposure		
Assumes use at not more that	Assumes use at not more than 20°C above ambient temperature (unless stated differently).		
Assumes a good basic stand	ard of occupational hygiene is implemented.		
Contributing Scenarios	Risk Management Measures		
Laboratory activities	Handle in a fume cupboard or under extract ventilation.		
CleaningRolling, Brush-	Handle in a fume cupboard or under extract ventilation.		
ingVessel and container	'		
cleaning			
Section 2.2	Control of Environmental Exposure		
No exposure assessment pre	esented for the environment.		

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	

Section 3.2 -Environment	
No exposure assessment presented for the environment.	

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	

According to EC No 1907/2006 as amended as at the date of this SDS

Bio Methanol

Version Revision Date: SDS Number: Date of last issue: 17.08.2023

2.3 28.02.2025 800010034380 Print Date 07.03.2025

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 - Environment

According to EC No 1907/2006 as amended as at the date of this SDS

Bio Methanol

Version Revision Date: SDS Number: Date of last issue: 17.08.2023

2.3 28.02.2025 800010034380 Print Date 07.03.2025

Exposure Scenario - Consumer

30000001066	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Use as a fuel - Consumer
Use Descriptor	Sector of Use: SU 21
	Product Categories: PC13
	Environmental Release Categories: ERC9a, ERC9b
Scope of process	Covers consumer uses in liquid fuels.

SECTION 2	OPERATIONAL CONDITIONS AN MEASURES	D RISK MANAGEMENT	
Section 2.1	Control of Consumer Exposure		
Product Characteristics			
Physical form of product	Liquid, vapour pressure > 10 Pa		
Concentration of the Sub-	Covers concentration up to (%): 100	0 %	
stance in Mixture/Article			
Amounts Used			
for each use event, covers a	amount up to (g):	37.500	
Frequency and Duration o	f Use		
Covers use up to (days/year):		104	
Exposure (hours/event):		0,05	
Other Operational Conditions affecting Exposure			
Covers use at ambient temperatures.			
Covers use in room size of 2	20m3		

Covers use under typical household ventilation.

Product Categories	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
Fuels Liquid: Automotive Refuelling.	Covers concentrations up to 100 %
	covers use up to 104 day/year
	Covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 210 cm2
	For each use event, covers amount up to 37.500 g
	Covers outdoor use.
	Covers use in room size of 100 m3
	Covers exposure up to 0,05 hours/event
Fuels	Covers concentrations up to 80 %
	covers use up to 104 day/year
	Covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 210 cm2
	For each use event, covers amount up to 800 g
	Covers outdoor use.

According to EC No 1907/2006 as amended as at the date of this SDS

Bio Methanol

Version Revision Date: SDS Number: Date of last issue: 17.08.2023

2.3 28.02.2025 800010034380 Print Date 07.03.2025

Covers use in room size of 20 m3
Covers exposure up to 0,01 hours/event

	Section 2.2	Control of Environmental Exposure	
ſ	No exposure assessment pre	sented for the environment.	

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	

The ECETOC TRA tool has been used to estimate consumer exposures unless otherwise indicated.

The Consexpo model has been used to estimate consumer exposures unless otherwise indicated.

Section 3.2 - Environment

No exposure assessment presented for the environment.

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE
	EXPOSURE SCENARIO
A 41 44 11 141	

Section 4.1 - Health

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 - Environment