This Safety data sheet is subject to the Egyptian standard ES 8398 "Safety data sheet for chemical products" According to ISO 11014 /2009

Methyl PROXITOL

Print Date 01.12.2023 Revision Date 24.11.2023 Version 1.5

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Methyl PROXITOL

Product code : U5141 CAS-No. : 107-98-2

Other means of identification : 1-methoxy-2-propanol, PGME, PM, Propylene glycol monomethyl

ether

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the : Solvent.

Substance/Mixture

Uses advised against : This product must not be used in applications other than the

above without first seeking the advice of the supplier.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier : SHELL MARKETS (MIDDLE EAST) LIMITED

CHEMICALS PO Box 307 JEBEL ALI, DUBAI

Unit.Arab Emir. : +971 4 405 4400 : +971 4 329 3311

Contact for Safety Data

Sheet

Telefax

Telephone

ontact for Safety Data

1.4 Emergency telephone number

+ (65) 6542 9595 (Alert-SGS)

+31 (0)10 231 7393

UAT for SPS2020 - New ER number

Other information : PROXITOL is a trademark owned by Shell Trademark

Management B.V. and Shell Brands Inc. and used by affiliates

of Shell plc.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

GHS Classification

1 / 19 800001005738 EG

This Safety data sheet is subject to the Egyptian standard ES 8398 "Safety data sheet for chemical products" According to ISO 11014 /2009

Methyl PROXITOL

Print Date 01.12.2023 Revision Date 24.11.2023 Version 1.5

Flammable liquids : Category 3 Acute toxicity (Oral) : Category 5

Specific target organ toxicity -

single exposure

: Category 3 (Narcotic effects)

2.2 Label elements

GHS-Labelling

Hazard pictograms





Signal word : Warning

Hazard statements : PHYSICAL HAZARDS:

H226 Flammable liquid and vapour.

HEALTH HAZARDS:

H303 May be harmful if swallowed. H336 May cause drowsiness or dizziness.

ENVIRONMENTAL HAZARDS:

Not classified as an environmental hazard under GHS criteria.

Precautionary statements : **Prevention:**

P210 Keep away from heat, hot surfaces, sparks, open flames

and other ignition sources. No smoking.

P240 Ground and bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting

equipment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharges.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/ protective clothing/ eye

protection/ face protection.

Response:

P303 + P361 + P353 + P310 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. Immediately call a POISON CENTER/ doctor. P370 + P378 In case of fire: Use appropriate media to

extinguish.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/

doctor if you feel unwell.

P312 Call a POISON CENTER/ doctor if you feel unwell.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container

tightly closed. P235 Keep cool. P405 Store locked up.

Disposal:

This Safety data sheet is subject to the Egyptian standard ES 8398 "Safety data sheet for chemical products" According to ISO 11014 /2009

		Methyl PROXITOL
Print Date 01.12.2023	Revision Date 24.11.2023	Version 1.5

P501 Dispose of contents and container to appropriate waste site or reclaimer in accordance with local and national regulations.

2.3 Other hazards

Vapours are heavier than air. Vapours may travel across the ground and reach remote ignition sources causing a flashback fire danger.

Even with proper grounding and bonding, this material can still accumulate an electrostatic charge. If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable airvapour mixtures can occur.

SECTION 3: Composition/information on ingredients

3.1 Substances

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
1-Methoxypropane-2-ol	107-98-2	>= 99,6
2-methoxypropanol	1589-47-5	<0,1

SECTION 4: First aid measures

4.1 Description of first aid measures

•		
General advice	:	Not expected to be a health hazard when used under normal conditions.
Protection of first-aiders	:	When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.
If inhaled	:	Remove to fresh air. If rapid recovery does not occur, transport to nearest medical facility for additional treatment.
In case of skin contact	:	Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention.
In case of eye contact	:	Flush eye with copious quantities of water. Remove contact lenses, if present and easy to do. Continue rinsing. If persistent irritation occurs, obtain medical attention.
If swallowed	:	If swallowed, do not induce vomiting: transport to nearest

3 / 19 800001005738

medical facility for additional treatment. If vomiting occurs

This Safety data sheet is subject to the Egyptian standard ES 8398 "Safety data sheet for chemical products" According to ISO 11014 /2009

Methyl PROXITOL

Print Date 01.12.2023 Revision Date 24.11.2023 Version 1.5

spontaneously, keep head below hips to prevent aspiration. Rinse mouth.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Breathing of high vapour concentrations may cause central

nervous system (CNS) depression resulting in dizziness, light-headedness, headache, nausea and loss of coordination. Continued inhalation may result in unconsciousness and

death.

Skin irritation signs and symptoms may include a burning

sensation, redness, or swelling.

Eye irritation signs and symptoms may include a burning sensation, redness, swelling, and/or blurred vision.

Ingestion may result in nausea, vomiting and/or diarrhoea. Defatting dermatitis signs and symptoms may include a burning sensation and/or a dried/cracked appearance.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Call a doctor or poison control center for guidance.

Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam, water spray or fog. Dry chemical

powder, carbon dioxide, sand or earth may be used for small

fires only.

Unsuitable extinguishing

media

: None

5.2 Special hazards arising from the substance or mixture

Specific hazards during

firefighting

: The vapour is heavier than air, spreads along the ground and

5.3 Advice for firefighters

Special protective equipment

for firefighters

distant ignition is possible. Carbon monoxide may be evolved if incomplete combustion occurs.

: Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to

relevant Standards (e.g. Europe: EN469).

Specific extinguishing

methods

: Standard procedure for chemical fires.

Further information : Clear fire area of all non-emergency personnel.

Keep adjacent containers cool by spraying with water.

4 / 19 800001005738 EG

This Safety data sheet is subject to the Egyptian standard ES 8398 "Safety data sheet for chemical products" According to ISO 11014 /2009

Methyl PROXITOL		
Version 1.5	Revision Date 24 11 2023	Print Date 01 12 2023

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions

: Observe the relevant local and international regulations Notify authorities if any exposure to the general public or the environment occurs or is likely to occur.

Local authorities should be advised if significant spillages

cannot be contained.

The vapour is heavier than air, spreads along the ground and

distant ignition is possible.

Vapour may form an explosive mixture with air. Avoid contact with skin, eves and clothing.

Isolate hazard area and deny entry to unnecessary or

unprotected personnel.

Stay upwind and keep out of low areas.

6.2 Environmental precautions

Environmental precautions

: Shut off leaks, if possible without personal risks. Remove all possible sources of ignition in the surrounding area. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. Attempt to disperse the vapour or to direct its flow to a safe location for example by using fog sprays. Take precautionary measures against static discharge. Ensure electrical continuity by bonding and grounding (earthing) all equipment.

Ventilate contaminated area thoroughly. Monitor area with combustible gas indicator.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up

: For large liquid spills (> 1 drum), transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely For small liquid spills (< 1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.

This Safety data sheet is subject to the Egyptian standard ES 8398 "Safety data sheet for chemical products" According to ISO 11014 /2009

Print Date 01.12.2023 Revision Date 24.11.2023 Version 1.5

6.4 Reference to other sections

For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet., For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.

SECTION 7: Handling and storage

General Precautions : Avoid breathing of or direct contact with material. Only use in

well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see

Section 8 of this Safety Data Sheet.

Use the information in this data sheet as input to a risk assessment of local circumstances to help determine

appropriate controls for safe handling, storage and disposal of

this material.

Ensure that all local regulations regarding handling and

storage facilities are followed.

7.1 Precautions for safe handling

Advice on safe handling : Avoid contact with skin, eyes and clothing.

Use local exhaust ventilation if there is risk of inhalation of

vapours, mists or aerosols.

Bulk storage tanks should be diked (bunded).

Extinguish any naked flames. Do not smoke. Remove ignition

sources. Avoid sparks.

Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment

to reduce the risk.

The vapours in the head space of the storage vessel may lie

in the flammable/explosive range and hence may be

flammable.

Properly dispose of any contaminated rags or cleaning

materials in order to prevent fires.

Do NOT use compressed air for filling, discharging, or

handling operations.

Product Transfer : Refer to guidance under Handling section.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: The vapour is heavier than air. Beware of accumulation in pits and confined spaces. Refer to section 15 for any additional specific legislation covering the packaging and storage of this

product.

Packaging material : Suitable material: For containers, or container linings use

mild steel, stainless steel.

Unsuitable material: Natural, butyl, neoprene or nitrile

rubbers.

This Safety data sheet is subject to the Egyptian standard ES 8398 "Safety data sheet for chemical products" According to ISO 11014 /2009

	Me	ethyl PROXITOL
Print Date 01.12.2023	Revision Date 24.11.2023	Version 1.5
Container Advice	: Containers, even those that have been explosive vapours. Do not cut, drill, grir similar operations on or near containers	nd, weld or perform
7.3 Specific end use(s)		
Specific use(s)	: Not applicable	
	Ensure that all local regulations regardistorage facilities are followed. See additional references that provide a American Petroleum Institute 2003 (Prolignitions Arising out of Static, Lightning National Fire Protection Agency 77 (Reson Static Electricity). IEC/TS 60079-32-1: Electrostatic hazar	safe handling practices: otection Against and Stray Currents) or ecommended Practices

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Biological occupational exposure limits

No biological limit allocated.

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany http://www.dguv.de/inhalt/index.jsp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

8.2 Exposure controls

This Safety data sheet is subject to the Egyptian standard ES 8398 "Safety data sheet for chemical products" According to ISO 11014 /2009

Methyl PROXITOL

Print Date 01.12.2023

Revision Date 24.11.2023

Version 1.5

Engineering measuresThe level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

Use sealed systems as far as possible.

Adequate explosion-proof ventilation to control airborne concentrations below the exposure quidelines/limits.

Local exhaust ventilation is recommended.

Firewater monitors and deluge systems are recommended.

Eye washes and showers for emergency use.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

General Information:

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

Personal protective equipment

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Eye protection : If material is handled such that it could be splashed into eyes,

protective eyewear is recommended.

Hand protection

Remarks : Where hand contact with the product may occur the use of

gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. Longer term protection: butyl-

rubber Nitrile rubber gloves.

Incidental contact/Splash protection: Nitrile rubber gloves. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe

acceptable so long as appropriate maintenance and

This Safety data sheet is subject to the Egyptian standard ES 8398 "Safety data sheet for chemical products" According to ISO 11014 /2009

Methyl PROXITOL

Print Date 01.12.2023

Revision Date 24.11.2023

Version 1.5

replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

Skin and body protection

Skin protection is not required under normal conditions of use. For prolonged or repeated exposures use impervious clothing over parts of the body subject to exposure.

If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to relevant Standard, and provide employee skin care programmes.

Wear antistatic and flame-retardant clothing, if a local risk

Respiratory protection

: If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers.

Where air-filtering respirators are unsuitable (e.g. airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus.

Where air-filtering respirators are suitable, select an appropriate combination of mask and filter.

If air-filtering respirators are suitable for conditions of use: Select a filter suitable for organic gases and vapours [Type A

boiling point >65°C (149°F)].

assessment deems it so.

Environmental exposure controls

General advice

Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour.

Minimise release to the environment. An environmental assessment must be made to ensure compliance with local

environmental legislation.

Information on accidental release measures are to be found in

This Safety data sheet is subject to the Egyptian standard ES 8398 "Safety data sheet for chemical products" According to ISO 11014 /2009

Methyl PROXITOL

Print Date 01.12.2023 Revision Date 24.11.2023 Version 1.5

section 6.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : Liquid.

Colour : clear Odour : Ethereal

Odour Threshold : Data not available pH : Data not available

Melting / freezing point : -96 °C

Boiling point/boiling range : 117 - 125 °C

Flash point : 30 °C

Method: ASTM D93 (PMCC)

Evaporation rate : 0,75

Method: ASTM D 3539, nBuAc=1

Flammability

Flammability (solid, gas) : Data not available

Lower explosion limit and upper explosion limit / flammability limit

Upper explosion limit : 13,1 %(V)

Lower explosion limit : 1,9 %(V)

Vapour pressure : 1,170 Pa (20 °C)

Relative vapour density : 3,1

Relative density : 0,92 (20 °C)

Method: ASTM D4052

Density : 920 - 923 kg/m3 (20 °C)

Method: ASTM D4052

Solubility(ies)

Water solubility : completely soluble (20 °C)

Solubility in other solvents : Data not available

This Safety data sheet is subject to the Egyptian standard ES 8398 "Safety data sheet for chemical products" According to ISO 11014 /2009

Methyl PROXITOL

Print Date 01.12.2023 Revision Date 24.11.2023 Version 1.5

Partition coefficient: n-

octanol/water

: log Pow: 0,37

Auto-ignition temperature : 290 °C

Decomposition temperature : Data not available

Viscosity

Viscosity, dynamic : Data not available
Viscosity, kinematic : Data not available
Explosive properties : Not applicable
Oxidizing properties : Data not available

9.2 Other information

Surface tension : 70,7 mN/m, 20 °C

Conductivity: > 10,000 pS/m

A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid, This material is not expected to be

a static accumulator.

Molecular weight : 90,12 g/mol

SECTION 10: Stability and reactivity

10.1 Reactivity

The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.

10.2 Chemical stability

No hazardous reaction is expected when handled and stored according to provisions

10.3 Possibility of hazardous reactions

Hazardous reactions : Reacts with strong oxidising agents.

10.4 Conditions to avoid

Conditions to avoid : Avoid heat, sparks, open flames and other ignition sources.

Prevent vapour accumulation.

In certain circumstances product can ignite due to static

electricity.

This Safety data sheet is subject to the Egyptian standard ES 8398 "Safety data sheet for chemical products" According to ISO 11014 /2009

Methyl PROXITOL

Print Date 01.12.2023 Revision Date 24.11.2023 Version 1.5

10.5 Incompatible materials

Materials to avoid : Strong oxidising agents.

10.6 Hazardous decomposition products

Hazardous decomposition

products

: Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids and gases including carbon monoxide, carbon dioxide, sulphur oxides and unidentified organic compounds will be evolved when this material undergoes combustion or thermal or oxidative

degradation.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Basis for assessment : Information given is based on product testing.

> Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for

individual component(s).

exposure

Information on likely routes of : Exposure may occur via inhalation, ingestion, skin absorption,

skin or eye contact, and accidental ingestion.

Acute toxicity

Components:

1-Methoxypropane-2-ol:

Acute oral toxicity : LD50: $> 2000 - <= 5000 \,\text{mg/kg}$

Remarks: May be harmful if swallowed.

Acute inhalation toxicity : Remarks: Low toxicity by inhalation.

: LD50 : > 5000 mg/kg Acute dermal toxicity

Remarks: Low toxicity

Skin corrosion/irritation

Components:

1-Methoxypropane-2-ol:

Remarks: Not irritating to skin., Prolonged/repeated contact may cause defatting of the skin which can lead to dermatitis.

Serious eye damage/eye irritation

Components:

This Safety data sheet is subject to the Egyptian standard ES 8398 "Safety data sheet for chemical products" According to ISO 11014 /2009

Methyl PROXITOL

Print Date 01.12.2023 Revision Date 24.11.2023 Version 1.5

1-Methoxypropane-2-ol:

Remarks: Slightly irritating to the eye., Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Components:

1-Methoxypropane-2-ol:

Remarks: Not a sensitiser., Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Components:

1-Methoxypropane-2-ol:

: Remarks: No evidence of mutagenic activity.

Carcinogenicity

Components:

1-Methoxypropane-2-ol:

Remarks: Not carcinogenic in animal studies.

Material	GHS/CLP Carcinogenicity Classification
1-Methoxypropane-2-ol	No carcinogenicity classification.
2-methoxypropanol	No carcinogenicity classification.

Reproductive toxicity

Components:

1-Methoxypropane-2-ol:

Remarks: Does not impair fertility., Causes foetotoxicity in animals at doses which are maternally toxic., Causes adverse effects on the foetus based on animal studies.

STOT - single exposure

Components:

1-Methoxypropane-2-ol:

Remarks: High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea; continued inhalation may result in unconsciousness.

This Safety data sheet is subject to the Egyptian standard ES 8398 "Safety data sheet for chemical products" According to ISO 11014 /2009

Methyl PROXITOL

Print Date 01.12.2023 Revision Date 24.11.2023 Version 1.5

STOT - repeated exposure

Components:

1-Methoxypropane-2-ol:

Remarks: Kidney: caused kidney effects in male rats which are not considered relevant to humans. Based on available data, the classification criteria are not met.

Aspiration toxicity

Components:

1-Methoxypropane-2-ol:

Not an aspiration hazard.

Further information

Components:

1-Methoxypropane-2-ol:

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

SECTION 12: Ecological information

12.1 Toxicity

Basis for assessment : Ecotoxicological data are based on product testing.

> Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for

individual component(s).

Components:

1-Methoxypropane-2-ol:

Toxicity to fish (Acute : Remarks: Practically non toxic:

toxicity) LC/EC/IC50 > 1000 mg/l

Toxicity to daphnia and other

: Remarks: Practically non toxic: aquatic invertebrates (Acute LC/EC/IC50 > 1000 mg/l

toxicity)

Toxicity to algae (Acute : Remarks: Practically non toxic:

toxicity) LC/EC/IC50 > 1000 mg/l

Toxicity to bacteria (Acute

Remarks: Data not available toxicity)

This Safety data sheet is subject to the Egyptian standard ES 8398 "Safety data sheet for chemical products" According to ISO 11014 /2009

Methyl PROXITOL

Print Date 01.12.2023 Revision Date 24.11.2023 Version 1.5

Toxicity to fish (Chronic

toxicity)

Toxicity to daphnia and other

aquatic invertebrates (Chronic toxicity)

: Remarks: Data not available

: Remarks: Data not available

12.2 Persistence and degradability

Components:

1-Methoxypropane-2-ol:

Biodegradability : Remarks: Readily biodegradable meeting the 10 day window

criterion., Oxidises rapidly by photo-chemical reactions in air.

12.3 Bioaccumulative potential

Product:

Partition coefficient: n-

: log Pow: 0,37

octanol/water

Components:

1-Methoxypropane-2-ol:

Bioaccumulation : Remarks: Does not bioaccumulate significantly.

12.4 Mobility in soil

Components:

1-Methoxypropane-2-ol:

: Remarks: Dissolves in water., If product enters soil, it will be Mobility

highly mobile and may contaminate groundwater.

12.5 Results of PBT and vPvB assessment

no data available

12.6 Other adverse effects

no data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Recover or recycle if possible.

> It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Do not dispose into the environment, in drains or in water

courses.

Waste product should not be allowed to contaminate soil or

This Safety data sheet is subject to the Egyptian standard ES 8398 "Safety data sheet for chemical products" According to ISO 11014 /2009

	Methyl P	ROXITOL
Print Date 01.12.2023	Revision Date 24.11.2023	Version 1.5
Contaminated packaging :	ground water, or be disposed of into the environm Waste, spills or used product is dangerous wasted. Disposal should be in accordance with applicable national, and local laws and regulations. Local regulations may be more stringent than regulational requirements and must be complied with MARPOL - see International Convention for the Pollution from Ships (MARPOL 73/78) which provide technical aspects at controlling pollutions from ships and container thoroughly. After draining, vent in a safe place away from sparal Residues may cause an explosion hazard. Do not, puncture, cut, or weld uncleaned drums. Send to drum recoverer or metal reclaimer. Dispose in accordance with prevailing regulations to a recognized collector or contractor. The complete collector or contractor should be established to a recognized collector or contractor. The complete collector or contractor should be established to a recognized collector or contractor. The complete collector or contractor should be established to a recognized collector or contractor. The complete collector or contractor should be established to a recognized collector or contractor. The complete collector or contractor should be established to a recognized collector or contractor.	nent. e regional, pional or divides pips. earks and fire. es, preferably petence of beforehand. es, preferably petence of

Local legislation

SECTION 14: Transport information

14.1 UN number

ADR : 3092 **IMDG** 3092 **IATA** : 3092

14.2 Proper shipping name

ADR : 1-METHOXY-2-PROPANOL **IMDG** : 1-METHOXY-2-PROPANOL

IATA : 1-METHOXY-2-PROPANOL

14.3 Transport hazard class

ADR : 3 **IMDG** : 3 : 3 **IATA**

14.4 Packing group

ADR

Packing group : III Classification Code : F1

This Safety data sheet is subject to the Egyptian standard ES 8398 "Safety data sheet for chemical products" According to ISO 11014 /2009

INICHIAL LIVOVII OF	Methyl	PROXITOL
---------------------	--------	-----------------

Print Date 01.12.2023 Revision Date 24.11.2023 Version 1.5

Hazard Identification Number : 30 Labels 3 **IMDG** Packing group : 111 Labels : 3 IATA Packing group : 111 Labels 3

14.5 Environmental hazards

ADR

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

Remarks : Special Precautions: Refer to Section 7, Handling & Storage,

for special precautions which a user needs to be aware of or

needs to comply with in connection with transport.

14.7 Maritime transport in bulk according to IMO instruments

: Z Pollution category Ship type 3

Product name : Propylene glycol monoalkyl ether

Additional Information : This product may be transported under nitrogen blanketing.

> Nitrogen is an odourless and invisible gas. Exposure to nitrogen may cause asphyxiation or death. Personnel must observe strict safety precautions when involved with a confined space entry. Transport in bulk according to Annex II

of Marpol and the IBC Code

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Other regulations : The regulatory information is not intended to be

comprehensive. Other regulations may apply to this material.

The components of this product are reported in the following inventories:

AIIC : Listed DSL Listed

This Safety data sheet is subject to the Egyptian standard ES 8398 "Safety data sheet for chemical products" According to ISO 11014 /2009

		Methyl PROXITOL
Print Date 01.12.2023	Revision Date 24.11.2023	Version 1.5
IECSC ENCS KECI NZIOC PICCS TSCA TCSI	: Listed: Listed: Listed: Listed: Listed: Listed: Listed: Listed: Listed	

SECTION 16: Other information

Abbreviations and Acronyms

: The standard abbreviations and acronyms used in this document can be looked up in reference literature (e.g. scientific dictionaries) and/or websites.

ACGIH = American Conference of Governmental Industrial Hygienists

ADR = European Agreement concerning the International

Carriage of Dangerous Goods by Road

AICS = Australian Inventory of Chemical Substances ASTM = American Society for Testing and Materials

BEL = Biological exposure limits

BTEX = Benzene, Toluene, Ethylbenzene, Xylenes

CAS = Chemical Abstracts Service

CEFIC = European Chemical Industry Council CLP = Classification Packaging and Labelling

COC = Cleveland Open-Cup

DIN = Deutsches Institut fur Normung DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level

DSL = Canada Domestic Substance List

EC = European Commission

EC50 = Effective Concentration fifty

ECETOC = European Center on Ecotoxicology and

Toxicology Of Chemicals

ECHA = European Chemicals Agency

EINECS = The European Inventory of Existing Commercial

Chemical Substances

EL50 = Effective Loading fifty

ENCS = Japanese Existing and New Chemical Substances

Inventory

EWC = European Waste Code

GHS = Globally Harmonised System of Classification and

Labelling of Chemicals

IARC = International Agency for Research on Cancer

IATA = International Air Transport Association

IC50 = Inhibitory Concentration fifty

IL50 = Inhibitory Level fifty

IMDG = International Maritime Dangerous Goods

INV = Chinese Chemicals Inventory

IP346 = Institute of Petroleum test method N° 346 for the

This Safety data sheet is subject to the Egyptian standard ES 8398 "Safety data sheet for chemical products" According to ISO 11014 /2009

	Met	hyl PROXITOL
Print Date 01.12.2023	Revision Date 24.11.2023	Version 1.5
	determination of polycyclic aromatics DMSO-extractables KECI = Korea Existing Chemicals Inventory LC50 = Lethal Concentration fifty LD50 = Lethal Dose fifty per cent. LL/EL/IL = Lethal Loading/Effective Loading/Inhibitory load LL50 = Lethal Loading fifty MARPOL = International Convention for the Prevention of Pollution From Ships NOEC/NOEL = No Observed Effect Concentration / No Observed Effect Level OE_HPV = Occupational Exposure - High Production Volu PBT = Persistent, Bioaccumulative and Toxic PICCS = Philippine Inventory of Chemicals and Chemical Substances PNEC = Predicted No Effect Concentration REACH = Registration Evaluation And Authorisation Of Chemicals RID = Regulations Relating to International Carriage of Dangerous Goods by Rail SKIN_DES = Skin Designation STEL = Short term exposure limit TRA = Targeted Risk Assessment TSCA = US Toxic Substances Control Act TWA = Time-Weighted Average vPvB = very Persistent and very Bioaccumulative	
Further information		
Training advice	: Provide adequate information, instruction operators.	and training for
Other information	: A vertical bar () in the left margin indicate from the previous version.	es an amendment
Sources of key data used to compile the Safety Data Sheet	: The quoted data are from, but not limited sources of information (e.g. toxicological dealth Services, material suppliers' data, IUCLID date base, EC 1272 regulation, expenses the supplier of the supplier	data from Shell CONCAWE, EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.