

SAFETY DATA SHEET

Prepared according to GB/T 16483, GB/T 17519

NEODOL 1

800001001059

Initial release date: 2006.02.23

Version 5.1

Revision Date 2023.11.21

Print Date 2023.11.28

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : NEODOL 1
Product code : V2705
Synonyms : C11 alcohol
CAS-No. : 112-42-5

Manufacturer or supplier's details

Supplier : SHELL EASTERN CHEMICALS (S)
A REGISTERED BUSINESS OF SHELL EASTERN
TRADING (PTE) LTD (UEN:198902087C)
9 North Buona Vista Drive , #07-01
The Metropolis Tower 1
Singapore 138588
Singapore
Telephone : +65 6384 8269
Telefax : +65 6384 8454
Contact for Safety Data Sheet : If you have any enquiries about the content of this SDS
please email sccmsds@shell.com 如果您有关于该SDS内容的
任何质询, 请发电邮联系 sccmsds@shell.com

Emergency telephone number : +86-532-83889090

Recommended use of the chemical and restrictions on use

Recommended use : Use in detergent manufacture.
Restrictions on use : This product must not be used in applications other than the
above without first seeking the advice of the supplier.
Other information : NEODOL is a trademark owned by Shell Trademark
Management B.V. and Shell Brands Inc. and used by affiliates
of Royal Dutch Shell plc.

2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	Liquid at 20 °C.
Colour	colourless
Odour	mild

GHS Classification

Skin irritation : Category 3
Eye irritation : Category 2A

SAFETY DATA SHEET

Prepared according to GB/T 16483, GB/T 17519

NEODOL 1

800001001059

Initial release date: 2006.02.23

Version 5.1 Revision Date 2023.11.21 Print Date 2023.11.28

Aspiration hazard : Category 2
Short-term (acute) aquatic hazard : Category 1
Long-term (chronic) aquatic hazard : Category 2

GHS label elements

Hazard pictograms : 

Signal word : Warning

Hazard statements : PHYSICAL HAZARDS:
Not classified as a physical hazard under GHS criteria.
HEALTH HAZARDS:
H316 Causes mild skin irritation.
H319 Causes serious eye irritation.
H305 May be harmful if swallowed and enters airways.
ENVIRONMENTAL HAZARDS:
H400 Very toxic to aquatic life.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements :
Prevention:
P264 Wash hands thoroughly after handling.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
P273 Avoid release to the environment.
Response:
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P331 Do NOT induce vomiting.
P391 Collect spillage.
Storage:
P405 Store locked up.

Disposal:
P501 Dispose of contents and container to appropriate waste site or reclaimer in accordance with local and national regulations.

SAFETY DATA SHEET

Prepared according to GB/T 16483, GB/T 17519

NEODOL 1

800001001059

Initial release date: 2006.02.23

Version 5.1

Revision Date 2023.11.21

Print Date 2023.11.28

Other hazards which do not result in classification

Repeated exposure may cause skin dryness or cracking. Harmful: May cause lung damage if swallowed.

Physical and chemical hazards	Not classified as flammable but will burn.
Health Hazards	Inhalation: No specific hazards under normal use conditions. Skin: Causes mild skin irritation. Eyes: Causes serious eye irritation. Ingestion: No specific hazards under normal use conditions.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Substance

Hazardous components

Chemical name	CAS-No.	Classification	Concentration (% w/w)
Undecan-1-ol	112-42-5	Skin Irrit.3; H316 Eye Irrit.2A; H319 Asp. Tox.2; H305 Aquatic Acute1; H400 Aquatic Chronic2; H411	<= 100

For explanation of abbreviations see section 16.

4. FIRST-AID MEASURES

General advice	: Not expected to be a health hazard when used under normal conditions.
If inhaled	: No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.
In case of skin contact	: Remove contaminated clothing. Immediately flush skin with large amounts of water for at least 15 minutes, and follow by washing with soap and water if available. If redness, swelling, pain and/or blisters occur, transport to the nearest medical facility for additional treatment.
In case of eye contact	: Immediately flush eye(s) with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Transport to the nearest medical facility for additional treatment.
If swallowed	: In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.

SAFETY DATA SHEET

Prepared according to GB/T 16483, GB/T 17519

NEODOL 1

800001001059

Initial release date: 2006.02.23

Version 5.1	Revision Date 2023.11.21	Print Date 2023.11.28
Most important symptoms and effects, both acute and delayed	<p>: Not considered to be an inhalation hazard under normal conditions of use.</p> <p>Possible respiratory irritation signs and symptoms may include a temporary burning sensation of the nose and throat, coughing, and/or difficulty breathing.</p> <p>Skin irritation signs and symptoms may include a burning sensation, redness, or swelling.</p> <p>Eye irritation signs and symptoms may include a burning sensation, redness, swelling, and/or blurred vision.</p> <p>No specific hazards under normal use conditions.</p> <p>Ingestion may result in nausea, vomiting and/or diarrhoea.</p> <p>Defatting dermatitis signs and symptoms may include a burning sensation and/or a dried/cracked appearance.</p>	
Protection of first-aiders	<p>: When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.</p>	
Notes to physician	<p>: IMMEDIATE TREATMENT IS EXTREMELY IMPORTANT!</p> <p>Call a doctor or poison control center for guidance.</p> <p>Treat symptomatically.</p>	

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	: Alcohol-resistant foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
Unsuitable extinguishing media	: Do not use water in a jet.
Specific hazards during firefighting	: Carbon monoxide may be evolved if incomplete combustion occurs.
	Will float and can be reignited on surface water.
	The vapour is heavier than air, spreads along the ground and distant ignition is possible.
Specific extinguishing methods	: Standard procedure for chemical fires.
	Clear fire area of all non-emergency personnel.
	Keep adjacent containers cool by spraying with water.
Special protective equipment for firefighters	: Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

SAFETY DATA SHEET

Prepared according to GB/T 16483, GB/T 17519

NEODOL 1

800001001059

Initial release date: 2006.02.23

Version 5.1

Revision Date 2023.11.21

Print Date 2023.11.28

6. ACCIDENTAL RELEASE MEASURES

- | | |
|---|---|
| Personal precautions, protective equipment and emergency procedures | : Observe all relevant local and international regulations.
Notify authorities if any exposure to the general public or the environment occurs or is likely to occur.
Local authorities should be advised if significant spillages cannot be contained.

: Avoid contact with spilled or released material. Immediately remove all contaminated clothing. For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet. For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.
Stay upwind and keep out of low areas.
Be ready for fire or possible exposure. |
| Environmental precautions | : Prevent from spreading or entering into drains, ditches or rivers by using sand, earth, or other appropriate barriers.
Use appropriate containment to avoid environmental contamination.
Ventilate contaminated area thoroughly. |
| Methods and materials for containment and cleaning up | : For large liquid spills (> 1 drum), transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.
For small liquid spills (< 1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely. |
| Additional advice | : For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet.
For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet. |

7. HANDLING AND STORAGE

Handling

- | | |
|---------------------|--|
| General Precautions | : Avoid breathing of or direct contact with material. Only use in well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet.
Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.
Ensure that all local regulations regarding handling and |
|---------------------|--|

SAFETY DATA SHEET

Prepared according to GB/T 16483, GB/T 17519

NEODOL 1

800001001059

Initial release date: 2006.02.23

Version 5.1	Revision Date 2023.11.21	Print Date 2023.11.28
storage facilities are followed.		
Advice on safe handling	:	Avoid contact with skin, eyes and clothing. Do not empty into drains. Sudden Release of Pressure Hazard
Avoidance of contact	:	Copper. Copper alloys. Strong oxidising agents. Aluminum
Product Transfer	:	Keep containers closed when not in use. Do not use compressed air for filling discharge or handling.
Storage		
Conditions for safe storage	:	Refer to section 15 for any additional specific legislation covering the packaging and storage of this product.
Other data	:	Bulk storage tanks should be diked (bunded). Vapours from tanks should not be released to atmosphere. Breathing losses during storage should be controlled by a suitable vapour treatment system. Nitrogen blanket recommended for large tanks (capacity 100 m3 or higher). Insulation (lagging) will minimize heat loss in areas of low ambient temperature. Tanks should be fitted with heating coils in areas where ambient conditions can result in handling temperatures below the freezing point/pour point of the product.
Packaging material	:	Suitable material: Stainless steel., Epoxy resins, Polyester. Unsuitable material: Aluminum, Copper., Copper alloys.
Container Advice	:	Containers, even those that have been emptied, can contain explosive vapours. Do not cut, drill, grind, weld or perform similar operations on or near containers.
Specific use(s)	:	Not applicable
Ensure that all local regulations regarding handling and storage facilities are followed.		

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Components with workplace control parameters

Biological occupational exposure limits

No biological limit allocated.

Monitoring Methods

SAFETY DATA SHEET

Prepared according to GB/T 16483, GB/T 17519

NEODOL 1

800001001059

Initial release date: 2006.02.23

Version 5.1

Revision Date 2023.11.21

Print Date 2023.11.28

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

GBZ 159 Specifications of air sampling for hazardous substances monitoring in the workplace.

GBZ/T 160 Determination of toxic substances in the air of workplace.

GBZ/T 192 Determination of dust in the air of workplace.

GBZ/T 300 Determination of toxic substances in the air of workplace

Engineering measures

: Adequate ventilation to control airborne concentrations below the exposure guidelines/limits.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

Eye washes and showers for emergency use.

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances.

Appropriate measures include:

General Information:

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

Do not ingest. If swallowed, then seek immediate medical assistance.

Personal protective equipment

Protective measures

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Respiratory protection

: If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation.

SAFETY DATA SHEET

Prepared according to GB/T 16483, GB/T 17519

NEODOL 1

800001001059

Initial release date: 2006.02.23

Version 5.1

Revision Date 2023.11.21

Print Date 2023.11.28

Check with respiratory protective equipment suppliers.
Where air-filtering respirators are unsuitable (e.g. airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus.
Where air-filtering respirators are suitable, select an appropriate combination of mask and filter.
If air-filtering respirators are suitable for conditions of use:
Select a filter suitable for the combination of organic gases and vapours and particles [Type A/Type P boiling point >65°C (149°F)].

Hand protection Remarks

: Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. Longer term protection: Nitrile rubber gloves. Incidental contact/Splash protection: PVC or neoprene rubber gloves. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

Eye protection

: Wear goggles for use against liquids and gas.
Wear full face shield if splashes are likely to occur.

Skin and body protection

: Skin protection is not required under normal conditions of use. For prolonged or repeated exposures use impervious clothing over parts of the body subject to exposure.
If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to relevant Standard, and provide employee skin care programmes.

Thermal hazards

: Not applicable

Hygiene measures

: Wash hands before eating, drinking, smoking and using the toilet.
Launder contaminated clothing before re-use.

SAFETY DATA SHEET

Prepared according to GB/T 16483, GB/T 17519

NEODOL 1

800001001059

Initial release date: 2006.02.23

Version 5.1

Revision Date 2023.11.21

Print Date 2023.11.28

Environmental exposure controls

General advice : Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour.
Minimise release to the environment. An environmental assessment must be made to ensure compliance with local environmental legislation.
Information on accidental release measures are to be found in section 6.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: Liquid at 20 °C.
Colour	: colourless
Odour	: mild
Odour Threshold	: Data not available
pH	: Data not available
Melting / freezing point	: Data not available
pour point	11 °C / 52 °F
Boiling point/boiling range	: 245 °C / 473 °F
Flash point	: 121 °C / 250 °F
Evaporation rate	: Data not available
Flammability (solid, gas)	: Not applicable
Upper explosion limit	: Data not available
Lower explosion limit	: Data not available
Vapour pressure	: 0.4 Pa
Relative vapour density	: 4.5
Relative density	: 0.831 (25 °C / 77 °F) Method: ASTM D4052
Density	: 830 kg/m ³ (20 °C / 68 °F) Method: ASTM D4052
Solubility(ies)	
Water solubility	: 19.1 mg/l (25 °C / 77 °F)
Partition coefficient: n-octanol/water	: log Pow: 4.72
Auto-ignition temperature	: Data not available

SAFETY DATA SHEET

Prepared according to GB/T 16483, GB/T 17519

NEODOL 1

800001001059

Initial release date: 2006.02.23

Version 5.1	Revision Date 2023.11.21	Print Date 2023.11.28
Decomposition temperature	: Data not available	
Viscosity		
Viscosity, dynamic	: Typical 17 mPa.s (20 °C / 68 °F) Method: ASTM D445	
Viscosity, dynamic	50 mPa.s (Not applicable /) Method: ASTM D445	
Viscosity, kinematic	: 11.0 mm ² /s (40 °C / 104 °F) Method: ASTM D445	
	18 mm ² /s (25 °C / 77 °F) Method: ASTM D445	
Explosive properties	: Not classified	
Oxidizing properties	: Data not available	
Surface tension	: Data not available	
Conductivity	: Electrical conductivity: > 10,000 pS/m A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid, This material is not expected to be a static accumulator.	
Particle size	: Data not available	
Molecular weight	: 172 - 173 g/mol	

10. STABILITY AND REACTIVITY

Reactivity	: Stable at normal ambient temperature and pressure., May oxidise in the presence of air.
Chemical stability	: The product is chemically stable. Stable under normal conditions.
Possibility of hazardous reactions	: None known.
Conditions to avoid	: Extremes of temperature and direct sunlight.
Incompatible materials	: Copper. Copper alloys. Strong oxidising agents. Aluminum

SAFETY DATA SHEET

Prepared according to GB/T 16483, GB/T 17519

NEODOL 1

800001001059

Initial release date: 2006.02.23

Version 5.1 Revision Date 2023.11.21 Print Date 2023.11.28

Hazardous decomposition products : None expected under normal use conditions.

11. TOXICOLOGICAL INFORMATION

Basis for assessment : Information given is based on product testing, and/or similar products, and/or components.
Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

Exposure routes : Exposure may occur via inhalation, ingestion, skin absorption, skin or eye contact, and accidental ingestion.

Acute toxicity

Components:

Undecan-1-ol:

Acute oral toxicity : LD50 Rat: > 5000 mg/kg
Remarks: Low toxicity

Acute inhalation toxicity : Remarks: Low toxicity
Based on available data, the classification criteria are not met.

Acute dermal toxicity : LD50 Rabbit: > 5000 mg/kg
Remarks: Low toxicity

Skin corrosion/irritation

Components:

Undecan-1-ol:

Remarks: Causes mild skin irritation.

Serious eye damage/eye irritation

Components:

Undecan-1-ol:

Remarks: Causes serious eye irritation.

Respiratory or skin sensitisation

Components:

Undecan-1-ol:

Remarks: Not a sensitiser.
Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Components:

Undecan-1-ol:

SAFETY DATA SHEET

Prepared according to GB/T 16483, GB/T 17519

NEODOL 1

800001001059

Initial release date: 2006.02.23

Version 5.1

Revision Date 2023.11.21

Print Date 2023.11.28

: Remarks: No evidence of mutagenic activity.

Carcinogenicity

Components:

Undecan-1-ol:

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

Material	GHS/CLP Carcinogenicity Classification
Undecan-1-ol	No carcinogenicity classification.

Reproductive toxicity

Components:

Undecan-1-ol:

: Remarks: Not a developmental toxicant., Based on available data, the classification criteria are not met., Does not impair fertility.

STOT - single exposure

Components:

Undecan-1-ol:

Remarks: Based on available data, the classification criteria are not met.

STOT - repeated exposure

Components:

Undecan-1-ol:

Remarks: Based on available data, the classification criteria are not met.

Aspiration toxicity

Components:

Undecan-1-ol:

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

Further information

Components:

Undecan-1-ol:

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

SAFETY DATA SHEET

Prepared according to GB/T 16483, GB/T 17519

NEODOL 1

800001001059

Initial release date: 2006.02.23

Version 5.1

Revision Date 2023.11.21

Print Date 2023.11.28

12. ECOLOGICAL INFORMATION

Basis for assessment : Information given is based on product testing, and/or similar products, and/or components.
Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

Ecotoxicity

Components:

Undecan-1-ol :

Toxicity to fish (Acute toxicity) : Remarks: LC/EC/IC50 >1 - <=10 mg/l
Toxic

Toxicity to crustacean (Acute toxicity) : Remarks: Very toxic.
LC/EC/IC50 < 1 mg/l

Toxicity to algae/aquatic plants (Acute toxicity) : Remarks: LC/EC/IC50 >1 - <=10 mg/l
Toxic

M-Factor (Short-term (acute) aquatic hazard) : 1

Toxicity to microorganisms (Acute toxicity) : Remarks: LC/EC/IC50 > 100 mg/l
Practically non toxic:
Based on available data, the classification criteria are not met.

Toxicity to fish (Chronic toxicity) : Remarks: Data not available

Toxicity to crustacean(Chronic toxicity) : Remarks: NOEC/NOEL > 0.01 - <=0.1 mg/l

Persistence and degradability

Components:

Undecan-1-ol :

Biodegradability : Remarks: Readily biodegradable.
Oxidises rapidly by photo-chemical reactions in air.

Bioaccumulative potential

Product:

Partition coefficient: n-octanol/water : log Pow: 4.72

Components:

Undecan-1-ol :

Bioaccumulation : Remarks: Bioaccumulation is unlikely to occur due to metabolism and excretion.

Mobility in soil

Components:

Undecan-1-ol :

Mobility : Remarks: Floats on water., If product enters soil, it will be

SAFETY DATA SHEET

Prepared according to GB/T 16483, GB/T 17519

NEODOL 1

800001001059

Initial release date: 2006.02.23

Version 5.1

Revision Date 2023.11.21

Print Date 2023.11.28

highly mobile and may contaminate groundwater.

Other adverse effects

no data available

13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues

: Recover or recycle if possible.

It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.

Do not dispose into the environment, in drains or in water courses.

Waste product should not be allowed to contaminate soil or water.

Disposal should be in accordance with applicable regional, national, and local laws and regulations.

Local regulations may be more stringent than regional or national requirements and must be complied with.

Contaminated packaging

: Drain container thoroughly.

After draining, vent in a safe place away from sparks and fire.

Residues may cause an explosion hazard.

Do not puncture, cut, or weld uncleaned drums.

Send to drum recoverer or metal reclaimer.

Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand.

Local legislation

Remarks

: If potential for exposure exists refer to Section 8 for specific personal protective equipment.

14. TRANSPORT INFORMATION

International Regulations

ADR

UN number

: 3082

Proper shipping name

: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(Undecan-1-ol)

Class

: 9

Packing group

: III

Labels

: 9

SAFETY DATA SHEET

Prepared according to GB/T 16483, GB/T 17519

NEODOL 1

800001001059

Initial release date: 2006.02.23

Version 5.1 Revision Date 2023.11.21 Print Date 2023.11.28

Hazard Identification Number : 90
Environmentally hazardous : yes

IATA-DGR

UN/ID No. : UN 3082
Proper shipping name : Environmentally hazardous substances, liquid, n.o.s.
(Undecan-1-ol)
Class : 9
Packing group : III
Labels : 9

IMDG-Code

UN number : UN 3082
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,
N.O.S.
(Undecan-1-ol)
Class : 9
Packing group : III
Labels : 9
Marine pollutant : yes

Maritime transport in bulk according to IMO instruments

Pollution category : X
Ship type : 2
Product name : Undecyl alcohol

Special precautions for user

Remarks : Special Precautions: Refer to Section 7, Handling & Storage,
for special precautions which a user needs to be aware of or
needs to comply with in connection with transport.

Additional Information : This product may be transported under nitrogen blanketing.
Nitrogen is an odourless and invisible gas. Exposure to
nitrogen enriched atmospheres displaces available oxygen
which may cause asphyxiation or death. Personnel must
observe strict safety precautions when involved with a
confined space entry.
Transport in bulk according to Annex II of Marpol and the IBC
Code

15. REGULATORY INFORMATION

National regulatory information

Rotterdam Convention (Prior Informed Consent)
Not applicable

Stockholm Convention (Persistent Organic Pollutants)
Not applicable

Law on the Prevention and Control of Occupational Diseases

The categories of occupational disease:
Not applicable

Occupational Disease Classification list:
Not applicable

SAFETY DATA SHEET

Prepared according to GB/T 16483, GB/T 17519

NEODOL 1

800001001059

Initial release date: 2006.02.23

Version 5.1

Revision Date 2023.11.21

Print Date 2023.11.28

Regulations on Safety Management of Hazardous Chemicals

Catalogue of Hazardous Chemicals : Not applicable

Identification of Major Hazard Installations for Hazardous Chemicals (GB 18218) : Not applicable

Hazardous Chemicals for Priority Management under SAWS : Not applicable

Regulations on Labour Protection in Workplaces where Toxic Substances are Used

Catalogue of Highly Toxic Chemicals : Not applicable

Regulation of Environmental Management on the First Import of Chemicals and the Import and Export of Toxic Chemicals

Catalogue of Toxic Chemicals Severely Restricted in China : Not applicable

Other international regulations

The components of this product are reported in the following inventories:

DSL	: Listed
IECSC	: Listed
ENCS	: Listed
KECI	: Listed
NZIoC	: Listed
PICCS	: Listed
TSCA	: Listed
TCSI	: Listed

16. OTHER INFORMATION

Full text of H-Statements

H305	May be harmful if swallowed and enters airways.
H316	Causes mild skin irritation.
H319	Causes serious eye irritation.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Aquatic Acute	Short-term (acute) aquatic hazard
Aquatic Chronic	Long-term (chronic) aquatic hazard
Asp. Tox.	Aspiration hazard
Eye Irrit.	Eye irritation
Skin Irrit.	Skin irritation

Abbreviations and Acronyms

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with

SAFETY DATA SHEET

Prepared according to GB/T 16483, GB/T 17519

NEODOL 1

800001001059

Initial release date: 2006.02.23

Version 5.1

Revision Date 2023.11.21

Print Date 2023.11.28

x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Further information

- Training advice : Provide adequate information, instruction and training for operators.
- Other information : A vertical bar (|) in the left margin indicates an amendment from the previous version.
- Sources of key data used to compile the Safety Data Sheet : The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID data base, EC 1272 regulation, etc).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CN / EN