

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## Methyl PROXITOL Acetate

Version	Revision Date:	SDS Number:	Print Date: 12/01/2023
9.1	11/24/2023	800001004875	Date of last issue: 09/16/2020

---

### SECTION 1. IDENTIFICATION

Product name : Methyl PROXITOL Acetate

Product code : U5126

Synonyms : 1-methoxy-2-propanol acetate, 1-methoxy-2-propyl acetate, PGMEA, PMA

CAS-No. : 108-65-6

#### Manufacturer or supplier's details

Company : **Shell Chemical LP**  
PO Box 576  
HOUSTON TX 77001  
USA

SDS Request : 1-800-240-6737

Customer Service : 1-855-697-4355

#### Emergency telephone number

Chemtrec Domestic (24 hr) : 1-800-424-9300

Chemtrec International (24 hr) : 1-703-527-3887

#### Recommended use of the chemical and restrictions on use

Recommended use : Solvent.

Restrictions on use : This product must not be used in applications other than the above without first seeking the advice of the supplier.

Other information : PROXITOL is a registered trademark of Shell trademark Management BV.

---

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids : Category 3

Specific target organ toxicity - single exposure (Oral) : Category 3 (Central nervous system)

#### GHS label elements

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR  
1910.1200

## Methyl PROXITOL Acetate

Version  
9.1

Revision Date:  
11/24/2023

SDS Number:  
800001004875

Print Date: 12/01/2023  
Date of last issue: 09/16/2020

Hazard pictograms

:



Signal word

:

Warning

Hazard statements

:

**PHYSICAL HAZARDS:**  
H226 Flammable liquid and vapour.  
**HEALTH HAZARDS:**  
H336 May cause drowsiness or dizziness.  
**ENVIRONMENTAL HAZARDS:**  
Not classified as an environmental hazard under GHS criteria.

Precautionary statements

:

### **Prevention:**

P210 Keep away from heat/ sparks/ open flames/ hot surfaces.  
No smoking.  
P233 Keep container tightly closed.  
P240 Ground/bond container and receiving equipment.  
P241 Use explosion-proof electrical/ ventilating/ lighting equip-  
ment.  
P242 Use only non-sparking tools.  
P243 Take precautionary measures against static discharge.  
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves/ protective clothing/ eye protection/  
face protection.

### **Response:**

P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off  
immediately all contaminated clothing. Rinse skin with water/  
shower.  
P370 + P378 In case of fire: Use appropriate media to extin-  
guish.  
P304 + P340 IF INHALED: Remove victim to fresh air and keep  
at rest in a position comfortable for breathing.  
P312 Call a POISON CENTER or doctor/ physician if you feel  
unwell.

### **Storage:**

P403 + P233 Store in a well-ventilated place. Keep container  
tightly closed.  
P405 Store locked up.  
P235 Keep cool.

### **Disposal:**

P501 Dispose of contents and container to appropriate waste  
site or reclaimer in accordance with local and national regula-  
tions.

### **Other hazards which do not result in classification**

Vapours are heavier than air. Vapours may travel across the ground and reach remote ignition  
sources causing a flashback fire danger.

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## Methyl PROXITOL Acetate

Version  
9.1

Revision Date:  
11/24/2023

SDS Number:  
800001004875

Print Date: 12/01/2023  
Date of last issue: 09/16/2020

Even with proper grounding and bonding, this material can still accumulate an electrostatic charge.  
If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur.  
Slightly irritating to respiratory system.  
Slightly irritating to the eye.  
Repeated exposure may cause skin dryness or cracking.  
The classification of this material is based on OSHA HCS 2012 criteria.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Substance

#### Hazardous components

Chemical name	Synonyms	CAS-No.	Concentration (% w/w)
1-Methoxy-2-acetoxyp propane	2-methoxy-1-methylethyl acetate	108-65-6	>= 99.8

#### Further information

Contains:

Chemical name	Identification number	Concentration (% w/w)
2-methoxypropyl acetate	70657-70-4	<0.1
2-methoxypropanol	1589-47-5	<=0.01
1-Methoxypropane-2-ol	107-98-2	<=0.01
Butylated hydroxytoluene	128-37-0	<=0.0025

### SECTION 4. FIRST-AID MEASURES

General advice : Not expected to be a health hazard when used under normal conditions.

If inhaled : Remove to fresh air. If rapid recovery does not occur, transport to nearest medical facility for additional treatment.

In case of skin contact : Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available.  
If persistent irritation occurs, obtain medical attention.

In case of eye contact : Flush eye with copious quantities of water.  
Remove contact lenses, if present and easy to do. Continue rinsing.  
If persistent irritation occurs, obtain medical attention.

If swallowed : In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.

Most important symptoms and effects, both acute and : Breathing of high vapour concentrations may cause central nervous system (CNS) depression resulting in dizziness, light-

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## Methyl PROXITOL Acetate

Version	Revision Date:	SDS Number:	Print Date: 12/01/2023
9.1	11/24/2023	800001004875	Date of last issue: 09/16/2020

---

delayed		headedness, headache, nausea and loss of coordination. Continued inhalation may result in unconsciousness and death. Skin irritation signs and symptoms may include a burning sensation, redness, or swelling. Eye irritation signs and symptoms may include a burning sensation, redness, swelling, and/or blurred vision. Ingestion may result in nausea, vomiting and/or diarrhoea.
Protection of first-aiders	:	When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.
Indication of any immediate medical attention and special treatment needed	:	Call a doctor or poison control center for guidance. Treat symptomatically. Causes central nervous system depression.

---

### SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	:	Alcohol-resistant foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
Unsuitable extinguishing media	:	None
Specific hazards during fire-fighting	:	The vapour is heavier than air, spreads along the ground and distant ignition is possible. Carbon monoxide may be evolved if incomplete combustion occurs.
Specific extinguishing methods	:	Standard procedure for chemical fires.
Further information	:	Clear fire area of all non-emergency personnel. Keep adjacent containers cool by spraying with water.
Special protective equipment for firefighters	:	Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	:	Observe the relevant local and international regulations Notify authorities if any exposure to the general public or the environment occurs or is likely to occur. Local authorities should be advised if significant spillages cannot be contained. The vapour is heavier than air, spreads along the ground and
---	---	--

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## Methyl PROXITOL Acetate

Version  
9.1

Revision Date:  
11/24/2023

SDS Number:  
800001004875

Print Date: 12/01/2023  
Date of last issue: 09/16/2020

distant ignition is possible.  
Vapour may form an explosive mixture with air.  
Avoid contact with skin, eyes and clothing.  
Isolate hazard area and deny entry to unnecessary or unprotected personnel.  
Stay upwind and keep out of low areas.

Environmental precautions : Shut off leaks, if possible without personal risks. Remove all possible sources of ignition in the surrounding area. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. Attempt to disperse the vapour or to direct its flow to a safe location for example by using fog sprays. Take precautionary measures against static discharge. Ensure electrical continuity by bonding and grounding (earthing) all equipment. Ventilate contaminated area thoroughly. Monitor area with combustible gas indicator.

Methods and materials for containment and cleaning up : For large liquid spills (> 1 drum), transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely. For small liquid spills (< 1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.

Additional advice : For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet.  
For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.

U.S. regulations may require reporting releases of this material to the environment which exceed the reportable quantity (refer to Section 15) to the National Response Center at (800) 424-8802.

### SECTION 7. HANDLING AND STORAGE

Technical measures : Avoid breathing of or direct contact with material. Only use in well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet.  
Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.  
Ensure that all local regulations regarding handling and stor-

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## Methyl PROXITOL Acetate

Version  
9.1

Revision Date:  
11/24/2023

SDS Number:  
800001004875

Print Date: 12/01/2023  
Date of last issue: 09/16/2020

- 
- age facilities are followed.
- Advice on safe handling : Avoid contact with skin, eyes and clothing.  
Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols.  
Bulk storage tanks should be diked (bunded).  
Extinguish any naked flames. Do not smoke. Remove ignition sources. Avoid sparks.  
Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment to reduce the risk.  
The vapours in the head space of the storage vessel may lie in the flammable/explosive range and hence may be flammable.  
Properly dispose of any contaminated rags or cleaning materials in order to prevent fires.  
Do NOT use compressed air for filling, discharging, or handling operations.
- Avoidance of contact : Strong oxidising agents.
- Product Transfer : Refer to guidance under Handling section.
- Conditions for safe storage : The vapour is heavier than air. Beware of accumulation in pits and confined spaces.  
Refer to section 15 for any additional specific legislation covering the packaging and storage of this product.
- Packaging material : Suitable material: For containers, or container linings use mild steel, stainless steel.  
Unsuitable material: Natural, butyl, neoprene or nitrile rubbers.
- Container Advice : Containers, even those that have been emptied, can contain explosive vapours. Do not cut, drill, grind, weld or perform similar operations on or near containers.
- Specific use(s) : Not applicable

Ensure that all local regulations regarding handling and storage facilities are followed.  
See additional references that provide safe handling practices: American Petroleum Institute 2003 (Protection Against Ignitions Arising out of Static, Lightning and Stray Currents) or National Fire Protection Agency 77 (Recommended Practices on Static Electricity).  
IEC/TS 60079-32-1: Electrostatic hazards, guidance

---

## SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

### Components with workplace control parameters

Contains no substances with occupational exposure limit values.

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## Methyl PROXITOL Acetate

Version  
9.1

Revision Date:  
11/24/2023

SDS Number:  
800001004875

Print Date: 12/01/2023  
Date of last issue: 09/16/2020

### Biological occupational exposure limits

No biological limit allocated.

### Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods <http://www.cdc.gov/niosh/>

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods <http://www.osha.gov/>

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances <http://www.hse.gov.uk/>

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany <http://www.dguv.de/inhalt/index.jsp>

L'Institut National de Recherche et de Sécurité, (INRS), France <http://www.inrs.fr/accueil>

### Engineering measures

- : The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:
- Use sealed systems as far as possible.
  - Adequate explosion-proof ventilation to control airborne concentrations below the exposure guidelines/limits.
  - Local exhaust ventilation is recommended.
  - Firewater monitors and deluge systems are recommended.
  - Eye washes and showers for emergency use.
  - Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

#### General Information:

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned.

Practice good housekeeping.

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## Methyl PROXITOL Acetate

Version  
9.1

Revision Date:  
11/24/2023

SDS Number:  
800001004875

Print Date: 12/01/2023  
Date of last issue: 09/16/2020

### Personal protective equipment

**Respiratory protection** : If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are unsuitable (e.g. airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. If air-filtering respirators are suitable for conditions of use: Select a filter suitable for organic gases and vapours [Type A boiling point >65°C (149°F)].

Respirator selection, use and maintenance should be in accordance with the requirements of the OSHA Respiratory Protection Standard, 29 CFR 1910.134.

**Hand protection**  
**Remarks**

: Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. Longer term protection: butyl-rubber Nitrile rubber gloves. Incidental contact/Splash protection: Nitrile rubber gloves. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

**Eye protection** : If material is handled such that it could be splashed into eyes, protective eyewear is recommended.

**Skin and body protection** : Skin protection is not required under normal conditions of



# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## Methyl PROXITOL Acetate

Version  
9.1

Revision Date:  
11/24/2023

SDS Number:  
800001004875

Print Date: 12/01/2023  
Date of last issue: 09/16/2020

use.

For prolonged or repeated exposures use impervious clothing over parts of the body subject to exposure.

If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to relevant Standard, and provide employee skin care programmes.

Wear antistatic and flame-retardant clothing, if a local risk assessment deems it so.

Protective measures : Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

### Environmental exposure controls

General advice : Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour.  
Minimise release to the environment. An environmental assessment must be made to ensure compliance with local environmental legislation.  
Information on accidental release measures are to be found in section 6.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Liquid.

Colour : clear

Odour : Ethereal

Odour Threshold : Data not available

pH : Not applicable

Melting / freezing point : -65 °C / -85 °F

Boiling point/boiling range : 143 - 149 °C / 289 - 300 °F

Flash point : 45 °C / 113 °F

Evaporation rate : 0.3  
Method: ASTM D 3539, nBuAc=1

Flammability  
Flammability (solid, gas) : Data not available

Lower explosion limit and upper explosion limit / flammability limit  
Upper explosion limit / upper flammability limit : 7 %(V)

Lower explosion limit / Lower flammability limit : 1.5 %(V)

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## Methyl PROXITOL Acetate

Version	Revision Date:	SDS Number:	Print Date: 12/01/2023
9.1	11/24/2023	800001004875	Date of last issue: 09/16/2020

---

Vapour pressure	: 502 Pa (25 °C / 77 °F)
Relative vapour density	: 4.6
Relative density	: 0.96 - 0.97 (20 °C / 68 °F) Method: ASTM D4052
Density	: 967 kg/m <sup>3</sup> (20 °C / 68 °F) Method: ASTM D4052
Solubility(ies) Water solubility	: 198 g/l (20 °C / 68 °F) )
Partition coefficient: n-octanol/water	: log Pow: 1.2
Auto-ignition temperature	: 333 °C / 631 °F
Decomposition temperature	: Data not available
Viscosity Viscosity, dynamic	: 1.23 mPa.s (20 °C / 68 °F)  Method: ASTM D445
Viscosity, kinematic	: Data not available
Explosive properties	: Not applicable
Oxidizing properties	: Data not available
Surface tension	: 27.6 mN/m, 20 °C / 68 °F
Conductivity	: Electrical conductivity: > 10,000 pS/m  A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid, This material is not expected to be a static accumulator.
Molecular weight	: 132 g/mol
Particle size	: Data not available

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity	: The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.
Chemical stability	: No hazardous reaction is expected when handled and stored according to provisions

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## Methyl PROXITOL Acetate

Version	Revision Date:	SDS Number:	Print Date: 12/01/2023
9.1	11/24/2023	800001004875	Date of last issue: 09/16/2020

---

Possibility of hazardous reactions	: Reacts with strong oxidising agents.
Conditions to avoid	: Avoid heat, sparks, open flames and other ignition sources. Prevent vapour accumulation. In certain circumstances product can ignite due to static electricity.
Incompatible materials	: Strong oxidising agents.
Hazardous decomposition products	: Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids and gases including carbon monoxide, carbon dioxide, sulphur oxides and unidentified organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation.

---

### SECTION 11. TOXICOLOGICAL INFORMATION

Basis for assessment	: Information given is based on product testing. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).
----------------------	---

#### Information on likely routes of exposure

Exposure may occur via inhalation, ingestion, skin absorption, skin or eye contact, and accidental ingestion.

#### Acute toxicity

##### Components:

##### **1-Methoxy-2-acetoxyp propane:**

Acute oral toxicity	: LD50 : > 5000 mg/kg Remarks: Low toxicity
---------------------	--

Acute inhalation toxicity	: Remarks: Low toxicity by inhalation.
---------------------------	--

Acute dermal toxicity	: LD50 : > 5000 mg/kg Remarks: Low toxicity
-----------------------	--

#### Skin corrosion/irritation

##### Components:

##### **1-Methoxy-2-acetoxyp propane:**

Remarks: Not irritating to skin., Prolonged/repeated contact may cause defatting of the skin which can lead to dermatitis.

#### Serious eye damage/eye irritation

##### Components:

##### **1-Methoxy-2-acetoxyp propane:**

Remarks: Slightly irritating to the eye., Based on available data, the classification criteria are not

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR  
1910.1200

## Methyl PROXITOL Acetate

Version  
9.1

Revision Date:  
11/24/2023

SDS Number:  
800001004875

Print Date: 12/01/2023  
Date of last issue: 09/16/2020

met.

### Respiratory or skin sensitisation

#### Components:

##### **1-Methoxy-2-acetoxyp propane:**

Remarks: Not a skin sensitiser.

### Germ cell mutagenicity

#### Components:

##### **1-Methoxy-2-acetoxyp propane:**

Genotoxicity in vivo : Remarks: Non mutagenic, Based on available data, the classification criteria are not met.

### Carcinogenicity

#### Components:

##### **1-Methoxy-2-acetoxyp propane:**

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

### IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

### OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

### NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

### Reproductive toxicity

#### Components:

##### **1-Methoxy-2-acetoxyp propane:**

Effects on fertility :

Remarks: Does not impair fertility.  
Not a developmental toxicant.

### STOT - single exposure

#### Components:

##### **1-Methoxy-2-acetoxyp propane:**

Remarks: Inhalation of vapours or mists may cause irritation to the respiratory system.

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## Methyl PROXITOL Acetate

Version  
9.1

Revision Date:  
11/24/2023

SDS Number:  
800001004875

Print Date: 12/01/2023  
Date of last issue: 09/16/2020

### STOT - repeated exposure

#### Components:

##### **1-Methoxy-2-acetoxyp propane:**

Remarks: Kidney: caused kidney effects in male rats which are not considered relevant to humans, Based on available data, the classification criteria are not met.

### Aspiration toxicity

#### Components:

##### **1-Methoxy-2-acetoxyp propane:**

Not an aspiration hazard.

### Further information

#### Components:

##### **1-Methoxy-2-acetoxyp propane:**

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

---

## SECTION 12. ECOLOGICAL INFORMATION

Basis for assessment : Ecotoxicological data are based on product testing. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

### Ecotoxicity

#### Components:

##### **1-Methoxy-2-acetoxyp propane:**

Toxicity to fish (Acute toxicity) : Remarks: Low toxicity  
LC/EC/IC50 > 100 mg/l

Toxicity to daphnia and other aquatic invertebrates (Acute toxicity) : Remarks: Low toxicity  
LC/EC/IC50 > 100 mg/l

Toxicity to algae (Acute toxicity) : Remarks: Low toxicity  
LC/EC/IC50 > 100 mg/l

Toxicity to fish (Chronic toxicity) : Remarks: NOEC/NOEL > 10 - <=100 mg/l

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : Remarks: NOEC/NOEL > 100 mg/l

Toxicity to microorganisms (Acute toxicity) : Remarks: Low toxicity  
LC/EC/IC50 > 100 mg/l

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## Methyl PROXITOL Acetate

Version  
9.1

Revision Date:  
11/24/2023

SDS Number:  
800001004875

Print Date: 12/01/2023  
Date of last issue: 09/16/2020

---

### Persistence and degradability

#### Components:

##### **1-Methoxy-2-acetoxyp propane:**

Biodegradability : Remarks: Readily biodegradable.  
Oxidises rapidly by photo-chemical reactions in air.

### Bioaccumulative potential

#### Components:

##### **1-Methoxy-2-acetoxyp propane:**

Bioaccumulation : Remarks: Does not bioaccumulate significantly.

### Mobility in soil

#### Components:

##### **1-Methoxy-2-acetoxyp propane:**

Mobility : Remarks: Dissolves in water.  
If product enters soil, it will be highly mobile and may contaminate groundwater.

### Other adverse effects

no data available

---

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : Recover or recycle if possible.  
It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.  
Do not dispose into the environment, in drains or in water courses.  
Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment.  
Waste, spills or used product is dangerous waste.

Disposal should be in accordance with applicable regional, national, and local laws and regulations.  
Local regulations may be more stringent than regional or national requirements and must be complied with.

MARPOL - see International Convention for the Prevention of Pollution from Ships (MARPOL 73/78) which provides technical aspects at controlling pollutions from ships.

Contaminated packaging : Drain container thoroughly.  
After draining, vent in a safe place away from sparks and fire.  
Residues may cause an explosion hazard.

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR  
1910.1200

## Methyl PROXITOL Acetate

Version  
9.1

Revision Date:  
11/24/2023

SDS Number:  
800001004875

Print Date: 12/01/2023  
Date of last issue: 09/16/2020

Do not, puncture, cut, or weld uncleaned drums.  
Send to drum recoverer or metal reclaimer.

Dispose in accordance with prevailing regulations, preferably  
to a recognized collector or contractor. The competence of  
the collector or contractor should be established beforehand.

### SECTION 14. TRANSPORT INFORMATION

#### National Regulations

##### US Department of Transportation Classification (49 CFR Parts 171-180)

UN/ID/NA number : UN 3272  
Proper shipping name : Esters, n.o.s.  
Class : 3  
Packing group : III  
Labels : 3  
ERG Code : 127  
Marine pollutant : no

#### International Regulations

##### IATA-DGR

UN/ID No. : UN 3272  
Proper shipping name : Esters, n.o.s.  
(Propylene Glycol Monomethyl Ether Acetate)  
Class : 3  
Packing group : III  
Labels : 3

##### IMDG-Code

UN number : UN 3272  
Proper shipping name : ESTERS, N.O.S.  
(Propylene Glycol Monomethyl Ether Acetate)  
Class : 3  
Packing group : III  
Labels : 3  
Marine pollutant : no

#### Maritime transport in bulk according to IMO instruments

Pollution category : Z  
Ship type : 3  
Product name : Propylene glycol methyl ether acetate

#### Special precautions for user

Remarks : Special Precautions: Refer to Section 7, Handling & Storage,  
for special precautions which a user needs to be aware of or  
needs to comply with in connection with transport.

**Additional Information** : This product may be transported under nitrogen blanketing.  
Nitrogen is an odourless and invisible gas. Exposure to nitro-

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR  
1910.1200

## Methyl PROXITOL Acetate

Version  
9.1

Revision Date:  
11/24/2023

SDS Number:  
800001004875

Print Date: 12/01/2023  
Date of last issue: 09/16/2020

gen may cause asphyxiation or death. Personnel must observe strict safety precautions when involved with a confined space entry.  
Transport in bulk according to Annex II of Marpol and the IBC Code

### SECTION 15. REGULATORY INFORMATION

#### EPCRA - Emergency Planning and Community Right-to-Know Act

\*: This material does not contain any components with a CERCLA RQ.

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

#### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards** : Flammable (gases, aerosols, liquids, or solids)  
Specific target organ toxicity (single or repeated exposure)

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

#### Clean Water Act

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

#### US State Regulations

##### California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

#### Other regulations:

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

#### The components of this product are reported in the following inventories:

AIIC : Listed  
DSL : Listed  
IECSC : Listed  
ENCS : Listed  
KECI : Listed  
NZIoC : Listed



# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR  
1910.1200

## Methyl PROXITOL Acetate

Version  
9.1

Revision Date:  
11/24/2023

SDS Number:  
800001004875

Print Date: 12/01/2023  
Date of last issue: 09/16/2020

---

PICCS	:	Listed
TSCA	:	Listed
TCSI	:	Listed

---

### SECTION 16. OTHER INFORMATION

#### Further information

NFPA Rating (Health, Fire, Reactivity) 0, 2, 0

#### Full text of other abbreviations

Abbreviations and Acronyms : The standard abbreviations and acronyms used in this document can be looked up in reference literature (e.g. scientific dictionaries) and/or websites.

ACGIH = American Conference of Governmental Industrial Hygienists  
ADR = European Agreement concerning the International Carriage of Dangerous Goods by Road  
AICS = Australian Inventory of Chemical Substances  
ASTM = American Society for Testing and Materials  
BEL = Biological exposure limits  
BTEX = Benzene, Toluene, Ethylbenzene, Xylenes  
CAS = Chemical Abstracts Service  
CEFIC = European Chemical Industry Council  
CLP = Classification Packaging and Labelling  
COC = Cleveland Open-Cup  
DIN = Deutsches Institut für Normung  
DMEL = Derived Minimal Effect Level  
DNEL = Derived No Effect Level  
DSL = Canada Domestic Substance List  
EC = European Commission  
EC50 = Effective Concentration fifty  
ECETOC = European Center on Ecotoxicology and Toxicology Of Chemicals  
ECHA = European Chemicals Agency  
EINECS = The European Inventory of Existing Commercial Chemical Substances  
EL50 = Effective Loading fifty  
ENCS = Japanese Existing and New Chemical Substances Inventory  
EWC = European Waste Code  
GHS = Globally Harmonised System of Classification and Labelling of Chemicals  
IARC = International Agency for Research on Cancer  
IATA = International Air Transport Association  
IC50 = Inhibitory Concentration fifty  
IL50 = Inhibitory Level fifty  
IMDG = International Maritime Dangerous Goods

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## Methyl PROXITOL Acetate

Version  
9.1

Revision Date:  
11/24/2023

SDS Number:  
800001004875

Print Date: 12/01/2023  
Date of last issue: 09/16/2020

INV = Chinese Chemicals Inventory  
IP346 = Institute of Petroleum test method N° 346 for the determination of polycyclic aromatics DMSO-extractables  
KECI = Korea Existing Chemicals Inventory  
LC50 = Lethal Concentration fifty  
LD50 = Lethal Dose fifty per cent.  
LL/EL/IL = Lethal Loading/Effective Loading/Inhibitory loading  
LL50 = Lethal Loading fifty  
MARPOL = International Convention for the Prevention of Pollution From Ships  
NOEC/NOEL = No Observed Effect Concentration / No Observed Effect Level  
OE\_HPVS = Occupational Exposure - High Production Volume  
PBT = Persistent, Bioaccumulative and Toxic  
PICCS = Philippine Inventory of Chemicals and Chemical Substances  
PNEC = Predicted No Effect Concentration  
REACH = Registration Evaluation And Authorisation Of Chemicals  
RID = Regulations Relating to International Carriage of Dangerous Goods by Rail  
SKIN\_DES = Skin Designation  
STEL = Short term exposure limit  
TRA = Targeted Risk Assessment  
TSCA = US Toxic Substances Control Act  
TWA = Time-Weighted Average  
vPvB = very Persistent and very Bioaccumulative

A vertical bar (|) in the left margin indicates an amendment from the previous version.

Sources of key data used to compile the Safety Data Sheet : The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID data base, EC 1272 regulation, etc).

Revision Date : 11/24/2023

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN