According to EC No 1907/2006 as amended as at the date of this SDS

### CARADOL SP30-45

Version 1.3 Revision Date 03.07.2019 Print Date 06.09.2022

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : CARADOL SP30-45

Product code : U317C Synonyms : Polyol

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the : Use for the manufacture of polyurethane products.

Substance/Mixture

Uses advised against : This product must not be used in applications other than the

above without first seeking the advice of the supplier.

# 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier : Shell Chemicals Europe B.V.

PO Box 2334

3000 CH Rotterdam

Netherlands

Telephone : +31 (0)10 441 5137 / +31 (0)10 441 5191 Telefax : +31 (0)20 716 8316/ +31 (0)20 713 9230

Email Contact for Safety Data : sccmsds@shell.com

Sheet

### 1.4 Emergency telephone number

+46 (0)8 767 65 90

Giftinformationscentralen: 112 (I icke akuta situationer är numret till

Giftinformationscentralen 08-33 12 31)

Other information : CARADOL is a trademark owned by Shell Trademark

Management B.V. and Shell Brands Inc. and used by affiliates

of Royal Dutch Shell plc.

: This product is a Polymer which is exempt from the obligation

to register under REACH in accordance with Article II, Section

9.

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

## Classification (REGULATION (EC) No 1272/2008)

Based on available data this substance / mixture does not meet the classification criteria.

#### 2.2 Label elements

1 / 20 800001004874 SE

According to EC No 1907/2006 as amended as at the date of this SDS

## **CARADOL SP30-45**

Version 1.3 Revision Date 03.07.2019 Print Date 06.09.2022

### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms : No Hazard Symbol required

Signal word No signal word

Hazard statements PHYSICAL HAZARDS:

Not classified as a physical hazard

according to CLP criteria. **HEALTH HAZARDS:** 

Not classified as a health hazard under CLP

**ENVIRONMENTAL HAZARDS:** 

Not classified as environmental hazard

according to CLP criteria.

Prevention: Precautionary statements

No precautionary phrases.

Response:

No precautionary phrases.

Storage:

No precautionary phrases.

Disposal:

No precautionary phrases.

#### 2.3 Other hazards

The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB.

### **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

### **Hazardous components**

Chemical name	CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration [%]
Polyalkylene glycol	9082-00-2		50 - 60
Styrene-acrylonitrile polymer	57913-80-1		40 - 50

## **SECTION 4: First aid measures**

# 4.1 Description of first aid measures

## CARADOL SP30-45

Version 1.3 Revision Date 03.07.2019 Print Date 06.09.2022 General advice : Not expected to be a health hazard when used under normal

conditions.

Protection of first-aiders : When administering first aid, ensure that you are wearing the

appropriate personal protective equipment according to the

incident, injury and surroundings.

If inhaled : No treatment necessary under normal conditions of use.

If symptoms persist, obtain medical advice.

In case of skin contact : Remove contaminated clothing. Flush exposed area with

> water and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention.

: Flush eye with copious quantities of water. In case of eye contact

Remove contact lenses, if present and easy to do. Continue

rinsina.

If persistent irritation occurs, obtain medical attention.

If swallowed : In general no treatment is necessary unless large quantities

are swallowed, however, get medical advice.

### 4.2 Most important symptoms and effects, both acute and delayed

**Symptoms** : Not considered to be an inhalation hazard under normal

conditions of use.

Possible respiratory irritation signs and symptoms may include

a temporary burning sensation of the nose and throat.

coughing, and/or difficulty breathing.

No specific hazards under normal use conditions.

Skin irritation signs and symptoms may include a burning

sensation, redness, or swelling.

Eve irritation signs and symptoms may include a burning sensation, redness, swelling, and/or blurred vision. Ingestion may result in nausea, vomiting and/or diarrhoea.

### 4.3 Indication of any immediate medical attention and special treatment needed

**Treatment** : Call a doctor or poison control center for guidance.

> Treat symptomatically. Following cases of gross overexposure, investigation of liver, kidney and eye function may be advisable. Records of such incidents should be maintained

for future reference.

### **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

Suitable extinguishing media : Large fires should only be fought by properly trained fire

> fighters., Alcohol-resistant foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used

3/20 800001004874

SE

## **CARADOL SP30-45**

Version 1.3 Revision Date 03.07.2019 Print Date 06.09.2022

for small fires only.

Unsuitable extinguishing

media

: Do not use water in a jet.

## 5.2 Special hazards arising from the substance or mixture

Specific hazards during

firefighting

: Will only burn if enveloped in a pre-existing fire. Hazardous

combustion products may include: Carbon dioxide

Unidentified organic and inorganic compounds. Toxic gases

Carbon monoxide.

# 5.3 Advice for firefighters

Special protective equipment

for firefighters

: Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to

relevant Standards (e.g. Europe: EN469).

Standard procedure for chemical fires.

Specific extinguishing

methods

Further information

: Clear fire area of all non-emergency personnel.

All storage areas should be provided with adequate fire

fighting facilities.

Keep adjacent containers cool by spraying with water.

#### **SECTION 6: Accidental release measures**

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Observe all relevant local and international regulations.

6.1.1 For non emergency personnel: Avoid contact with skin, eyes and clothing.

Avoid inhaling vapour and/or mists.

Extinguish any naked flames. Do not smoke. Remove ignition

sources. Avoid sparks.

6.1.2 For emergency responders:

Avoid contact with skin, eyes and clothing.

Avoid inhaling vapour and/or mists.

Extinguish any naked flames. Do not smoke. Remove ignition

sources. Avoid sparks.

### 6.2 Environmental precautions

Environmental precautions : Remove all possible sources of ignition in the surrounding

area.

Prevent from spreading or entering into drains, ditches or rivers by using sand, earth, or other appropriate barriers. Use appropriate containment to avoid environmental

contamination.

Ventilate contaminated area thoroughly.

4 / 20 800001004874 SE

## **CARADOL SP30-45**

Version 1.3 Revision Date 03.07.2019 Print Date 06.09.2022

#### 6.3 Methods and materials for containment and cleaning up

Methods for cleaning up

: For large liquid spills (> 1 drum), transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely For small liquid spills (< 1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.

Proper disposal should be evaluated based on regulatory status of this material (refer to Section 13), potential contamination from subsequent use and spillage, and regulations governing disposal in the local area.

#### 6.4 Reference to other sections

For guidance on selection of personal protective equipment see Chapter 8 of this Safety Data Sheet., For guidance on disposal of spilled material see Chapter 13 of this Safety Data Sheet.

### **SECTION 7: Handling and storage**

**General Precautions** 

: Avoid breathing of or direct contact with material. Only use in well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet.

Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of

this material.

Ensure that all local regulations regarding handling and

storage facilities are followed.

#### 7.1 Precautions for safe handling

Advice on safe handling

In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. Use local exhaust extraction over processing area. Avoid unintentional contact with isocyanates to prevent

uncontrolled polymerisation.

Avoid contact with skin, eyes and clothing.

Air-dry contaminated clothing in a well-ventilated area before

laundering.

Do not empty into drains. Handling Temperature:

Ambient.

When handling product in drums, safety footwear should be worn and proper handling equipment should be used.

Extinguish any naked flames. Do not smoke. Remove ignition

# CARADOL SP30-45

Version 1.3 Revision Date 03.07.2019 Print Date 06.09.2022

sources. Avoid sparks.

**Product Transfer** : Lines should be purged with nitrogen before and after product

transfer. Keep containers closed when not in use.

#### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Refer to section 15 for any additional specific legislation covering the packaging and storage of this product.

Other data : Prevent all contact with water and with moist atmosphere.

Tanks must be clean, dry and rust-free. Prevent ingress of water. Must be stored in a diked (bunded) well- ventilated area, away from sunlight, ignition sources and other sources of heat. Nitrogen blanket recommended for large tanks (capacity 100 m3 or higher). Drums should be stacked to a

maximum of 3 high.

Storage period : 24 month(s)

Storage Temperature: Ambient.

Storage should be handled at temperatures such that viscosities are less than 500 cSt; typically at 25-50 °C. Tanks should be fitted with heating coils in areas where the ambient temperatures are below the recommended product handling temperatures. Heating coil skin temperatures should not

exceed 100 °C.

: Suitable material: Stainless steel., For container paints, use Packaging material

epoxy paint, zinc silicate paint.

Unsuitable material: Copper., Copper alloys.

7.3 Specific end use(s)

Specific use(s) : Not applicable.

Ensure that all local regulations regarding handling and

storage facilities are followed.

# **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

**Occupational Exposure Limits** 

**Biological occupational exposure limits** 

No biological limit allocated.

### CARADOL SP30-45

Version 1.3 Revision Date 03.07.2019 Print Date 06.09.2022

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

No DNEL value has been established.

#### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Exposure assessments have not been presented for the environment therefore PNEC values not required.

#### **Monitoring Methods**

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany http://www.dguv.de/inhalt/index.jsp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

#### 8.2 Exposure controls

Engineering measuresWhere material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

Adequate ventilation to control airborne concentrations.

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

#### General Information:

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

#### Personal protective equipment

The provided information is made in consideration of the PPE directive (Council Directive 89/686/EEC) and the CEN European Committee for Standardisation (CEN) standards.

Personal protective equipment (PPE) should meet recommended national standards. Check with

## **CARADOL SP30-45**

Version 1.3 Revision Date 03.07.2019 Print Date 06.09.2022

PPE suppliers.

Eve protection : If material is handled such that it could be splashed into eyes,

protective eyewear is recommended. Approved to EU Standard EN166.

Hand protection

Remarks : Where hand contact with the product may occur the use of

gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. Longer term protection: Nitrile rubber. Incidental contact/Splash protection: PVC. neoprene or nitrile rubber gloves For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. Suitability and durability of a glove is dependent on usage. e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must

perfumed moisturizer is recommended.

Skin and body protection : Skin protection is not ordinarily required beyond standard

work clothes.

It is good practice to wear chemical resistant gloves.

only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-

Respiratory protection : No respiratory protection is ordinarily required under normal

conditions of use.

In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material.

Hygiene measures : Wash hands before eating, drinking, smoking and using the

toilet. Launder contaminated clothing before re-use.

#### **Environmental exposure controls**

## CARADOL SP30-45

Version 1.3 Revision Date 03.07.2019 Print Date 06.09.2022

General advice : Local guidelines on emission limits for volatile substances

must be observed for the discharge of exhaust air containing

Minimise release to the environment. An environmental assessment must be made to ensure compliance with local

environmental legislation.

Information on accidental release measures are to be found in

section 6.

Take appropriate measures to fulfill the requirements of relevant environmental protection legislation. Avoid

contamination of the environment by following advice given in Section 6. If necessary, prevent undissolved material from being discharged to waste water. Waste water should be treated in a municipal or industrial waste water treatment plant

before discharge to surface water.

# **SECTION 9: Physical and chemical properties**

## 9.1 Information on basic physical and chemical properties

**Appearance** : Viscous liquid.

Colour : white

Odour : odourless

Odour Threshold : Data not available : Data not available На

: -15 °C Melting / freezing point

Boiling point/boiling range : Data not available

: > 200 °C Flash point

Method: ASTM D-93 / PMCC

: Data not available Evaporation rate

Flammability (solid, gas) : Not applicable

Upper explosion limit : Data not available Lower explosion limit : Data not available Vapour pressure : Data not available Relative vapour density : Data not available Relative density : Data not available

: 1.020 kg/m3 (25 °C) Density

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-: Data not available

According to EC No 1907/2006 as amended as at the date of this SDS

### CARADOL SP30-45

Version 1.3 Revision Date 03.07.2019 Print Date 06.09.2022

octanol/water

Auto-ignition temperature : Data not available

Decomposition temperature : Data not available

Viscosity

Viscosity, dynamic : 6.000 mPa.s (20 °C)

50 mPa.s (> 100 °C)

Viscosity, kinematic : Data not available
Explosive properties : Not applicable
Oxidizing properties : Data not available

9.2 Other information

Surface tension : Data not available

Conductivity: > 10,000 pS/m

A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid, This material is not expected to be

a static accumulator.

Molecular weight : Data not available

### **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.

#### 10.2 Chemical stability

No hazardous reaction is expected when handled and stored according to provisions, Hygroscopic.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Polymerises exothermically with di-isocyanates at ambient

temperatures.

The reaction becomes progressively more vigorous and can be violent at higher temperatures if the miscibility of reaction partners is good or is supported by stirring or by the presence

of solvents.

Reacts with strong oxidising agents.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames, and sparks.

According to EC No 1907/2006 as amended as at the date of this SDS

## CARADOL SP30-45

Version 1.3 Revision Date 03.07.2019 Print Date 06.09.2022

Product cannot ignite due to static electricity.

10.5 Incompatible materials

Materials to avoid : Avoid contact with isocyanates, copper and copper alloys,

zinc, strong oxidizing agents, and water.

10.6 Hazardous decomposition products

Hazardous decomposition

products

: Unknown toxic products may be formed.

### **SECTION 11: Toxicological information**

## 11.1 Information on toxicological effects

Basis for assessment : Information given is based on data obtained from similar

substances.

exposure

Information on likely routes of : Exposure may occur via inhalation, ingestion, skin absorption,

skin or eye contact, and accidental ingestion.

#### Acute toxicity

### **Product:**

Acute oral toxicity : LD 50 Rat, male and female: > 5.000 mg/kg

Method: OECD Test Guideline 401

Remarks: Based on available data, the classification criteria

are not met.

: LD50 Rat, male and female: > 20 mg/l Acute inhalation toxicity

> Exposure time: 4 h Test atmosphere: vapour

Method: OECD Test Guideline 403

Remarks: Based on available data, the classification criteria

are not met.

# Skin corrosion/irritation

#### Product:

Species: Rabbit

Method: Test(s) equivalent or similar to OECD Test Guideline 404

Remarks: Slightly irritating to skin., Insufficient to classify.

#### Serious eye damage/eye irritation

# **Product:**

Species: Rabbit

Method: OECD Test Guideline 405

Remarks: Slightly irritating., Insufficient to classify.

11/20 800001004874 SE

## **CARADOL SP30-45**

Version 1.3 Revision Date 03.07.2019 Print Date 06.09.2022

### Respiratory or skin sensitisation

#### **Product:**

Species: Guinea pig

Method: OECD Test Guideline 406

Remarks: Based on available data, the classification criteria are not met.

## Germ cell mutagenicity

### **Product:**

: Method: Test(s) equivalent or similar to OECD Guideline 471 Remarks: Based on available data, the classification criteria are not met.

Mothod: Directive 6

: Method: Directive 67/548/EEC, Annex V, B.10. Remarks: Based on available data, the classification criteria are not met.

: Test species: RatMethod: Directive 67/548/EEC, Annex V, B.12.

Remarks: Based on available data, the classification criteria are not met.

# Carcinogenicity

## **Product:**

Material	GHS/CLP Carcinogenicity Classification
Polyalkylene glycol	No carcinogenicity classification.
Styrene-acrylonitrile polymer	No carcinogenicity classification.

#### Reproductive toxicity

#### **Product:**

: Species: Rat

Sex: male and female Application Route: Inhalation

Method: Equivalent or similar to OECD Test Guideline 416 Remarks: Based on available data, the classification criteria

are not met.

Effects on foetal development

: Species: Rat, female Application Route: Oral

Method: OECD Test Guideline 414

Remarks: Based on available data, the classification criteria

are not met.

According to EC No 1907/2006 as amended as at the date of this SDS

### CARADOL SP30-45

Version 1.3 Revision Date 03.07.2019 Print Date 06.09.2022

#### STOT - single exposure

#### **Product:**

**Exposure routes: Inhalation** 

Target Organs: Central nervous system Remarks: May cause drowsiness or dizziness.

### STOT - repeated exposure

#### **Product:**

Remarks: Based on available data, the classification criteria are not met.

## Repeated dose toxicity

#### **Product:**

Rat. male and female: Application Route: Inhalation Test atmosphere: Gas

Method: OECD Test Guideline 413

Target Organs: No specific target organs noted

### **Aspiration toxicity**

#### **Product:**

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

#### **Further information**

#### **Product:**

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

#### Summary on evaluation of the CMR properties

Germ cell mutagenicity-

: This product does not meet the criteria for classification in

Assessment categories 1A/1B.

Carcinogenicity -

: This product does not meet the criteria for classification in

Assessment categories 1A/1B.

Reproductive toxicity -

: This product does not meet the criteria for classification in

Assessment categories 1A/1B.

## **CARADOL SP30-45**

Version 1.3 Revision Date 03.07.2019 Print Date 06.09.2022

## **SECTION 12: Ecological information**

### 12.1 Toxicity

Basis for assessment

**Product:** 

: Information given is based on product testing.

Faviaitu ta fiab //

Toxicity to fish (Acute

toxicity)

: LC50 (Danio rerio (zebra fish)): > 100 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203 Remarks: Practically non toxic:

LL/EL/IL50 > 100 mg/l

Toxicity to crustacean (Acute

toxicity)

: EC50 (Daphnia magna (Water flea)): 105,8 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202 Remarks: Practically non toxic:

LL/EL/IL50 > 100 mg/l

Toxicity to algae/aquatic

plants (Acute toxicity)

: EC50 (Desmodesmus subspicatus (green algae)): > 100 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201 Remarks: Practically non toxic:

LL/EL/IL50 > 100 mg/l

Toxicity to fish (Chronic

Toxicity to crustacean

(Chronic toxicity)

toxicity)

: Remarks: Data not available

: NOEC: >= 10 mg/l

Exposure time: 21 d
Species: Daphnia magna (Water flea)

Method: OECD Test Guideline 211
Remarks: NOEC/NOEL > 10 - <=100 mg/l

Toxicity to microorganisms

(Acute toxicity)

: EC50 (Activated sludge, domestic waste): > 1.000 mg/l

Exposure time: 3 h

Method: OECD Test Guideline 209 Remarks: Practically non toxic:

LL/EL/IL50 > 100 mg/l

### 12.2 Persistence and degradability

**Product:** 

Biodegradability : Biodegradation: 86,6 %

Exposure time: 28 d

Method: OECD Test Guideline 301F Remarks: Readily biodegradable.

#### 12.3 Bioaccumulative potential

14 / 20 800001004874 SE

According to EC No 1907/2006 as amended as at the date of this SDS

## **CARADOL SP30-45**

Version 1.3 Revision Date 03.07.2019 Print Date 06.09.2022

**Product:** 

Bioaccumulation : Remarks: Does not bioaccumulate significantly.

Partition coefficient: n-

octanol/water

: Remarks: Data not available

12.4 Mobility in soil

**Product:** 

Mobility : Remarks: If product enters soil, it will be highly mobile and

may contaminate groundwater., Dissolves in water.

12.5 Results of PBT and vPvB assessment

Product:

Assessment : The substance does not fulfill all screening criteria for

persistence, bioaccumulation and toxicity and hence is not

considered to be PBT or vPvB.

12.6 Other adverse effects

no data available

# **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Product : Recover or recycle if possible.

It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.

Do not dispose into the environment, in drains or in water

courses

Waste product should not be allowed to contaminate soil or

water.

Disposal should be in accordance with applicable regional,

national, and local laws and regulations.

Local regulations may be more stringent than regional or

national requirements and must be complied with.

Disposal, transport, storage and handling should be in accordance with SE regulation Avfallsförordning (2011:927).

Contaminated packaging : Drain container thoroughly.

After draining, vent in a safe place away from sparks and fire.

Send to drum recoverer or metal reclaimer.

Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand.

## CARADOL SP30-45

Version 1.3 Revision Date 03.07.2019 Print Date 06.09.2022

> Packing: Emptying: Place the package upside down, and tilt slightly, circa 10 degrees, to enable drainage in such a way that the lowest part of the package is at the exit orifice. On some packing an extra hole must be made. Drainage should be carried out at room temperature (at least 15 °C). Wait until the package is drip dry. Do not close package after draining. Please note the risks connected with emptying package and containers with flammable liquids. Emptied package should be ventilated in a safe place away from sparks and fire. Residues may be an explosion risk. Do not puncture, cut or weld in noncleaned package, containers or drums.

Local legislation

Remarks Suggestion for emptied package:

15 01 02: Plastic packaging 15 01 04 metallic packaging.

Packages containing any remaining product and which have not been emptied until drip dry, must be handled as dangerous waste and must be well sealed before disposal.

Suggestion for waste code:

15 01 10: Packaging containing residues of or contaminated

by dangerous substances

## **SECTION 14: Transport information**

14.1 UN number

**ADR** : Not regulated as a dangerous good **RID** : Not regulated as a dangerous good **IMDG** : Not regulated as a dangerous good IATA Not regulated as a dangerous good

14.2 Proper shipping name

**ADR** : Not regulated as a dangerous good RID Not regulated as a dangerous good **IMDG** Not regulated as a dangerous good Not regulated as a dangerous good **IATA** 

14.3 Transport hazard class

**ADR** : Not regulated as a dangerous good : Not regulated as a dangerous good RID Not regulated as a dangerous good **IMDG** IATA Not regulated as a dangerous good

14.4 Packing group

ADR Not regulated as a dangerous good Not regulated as a dangerous good RID **IMDG** Not regulated as a dangerous good Not regulated as a dangerous good **IATA** 

14.5 Environmental hazards

**ADR** : Not regulated as a dangerous good

## **CARADOL SP30-45**

Version 1.3 Revision Date 03.07.2019 Print Date 06.09.2022

RID : Not regulated as a dangerous good : Not regulated as a dangerous good

14.6 Special precautions for user

Remarks : Special Precautions: Refer to Section 7, Handling & Storage,

for special precautions which a user needs to be aware of or

needs to comply with in connection with transport.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Pollution category : Y Ship type : 3

Product name : Acrylonitrile-Styrene Copolymer Dispersion in Polyether Polyol

**Additional Information**: This product may be transported under nitrogen blanketing.

Nitrogen is an odourless and invisible gas. Exposure to nitrogen enriched atmospheres displaces available oxygen which may cause asphyxiation or death. Personnel must observe strict safety precautions when involved with a

confined space entry.

### **SECTION 15: Regulatory information**

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

: This product does not contain substances of very high concern

(Regulation (EC) No

1907/2006 (REACH), Article 57).

REACH - List of substances subject to authorisation

(Annex XIV)

: Product is not subject to Authorisation under REACH.

Other regulations : The regulatory information is not intended to be

comprehensive. Other regulations may apply to this material.

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of

Chemicals (REACH), annex XIV.

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of

Chemicals (REACH), annex XVII.

Directive 2004/37/EC on the protection of workers from the risks related to exposure to carcinogens or mutagens at work

and its amendments.

Directive 1994/33/EC on the protection of young people at

work and its amendments.

Council Directive 92/85/EEC on the introduction of measures

## **CARADOL SP30-45**

Version 1.3 Revision Date 03.07.2019 Print Date 06.09.2022

to encourage improvements in the safety and health at work of pregnant workers and workers who have recently given birth or are breastfeeding and its amendments.

#### The components of this product are reported in the following inventories:

AIIC : Listed DSL Listed **IECSC** Listed **ENCS** Listed KECI : Listed **NZIoC** : Listed **PICCS** : Listed **TSCA** : Listed TCSI : Listed

#### 15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

#### **SECTION 16: Other information**

Abbreviations and Acronyms : The standard abbreviations and acronyms used in this

document can be looked up in reference literature (e.g.

scientific dictionaries) and/or websites.

ACGIH = American Conference of Governmental Industrial

**Hygienists** 

ADR = European Agreement concerning the International

Carriage of Dangerous Goods by Road

AICS = Australian Inventory of Chemical Substances ASTM = American Society for Testing and Materials

BEL = Biological exposure limits

BTEX = Benzene, Toluene, Ethylbenzene, Xylenes

CAS = Chemical Abstracts Service

CEFIC = European Chemical Industry Council

CLP = Classification Packaging and Labelling

COC = Cleveland Open-Cup

DIN = Deutsches Institut fur Normung DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

DSL = Canada Domestic Substance List

EC = European Commission

EC50 = Effective Concentration fifty

ECETOC = European Center on Ecotoxicology and

**Toxicology Of Chemicals** 

ECHA = European Chemicals Agency

EINECS = The European Inventory of Existing Commercial

**Chemical Substances** 

## CARADOL SP30-45

Version 1.3 Revision Date 03.07.2019 Print Date 06.09.2022

EL50 = Effective Loading fifty

ENCS = Japanese Existing and New Chemical Substances

Inventory

EWC = European Waste Code

GHS = Globally Harmonised System of Classification and

Labelling of Chemicals

IARC = International Agency for Research on Cancer

IATA = International Air Transport Association

IC50 = Inhibitory Concentration fifty

IL50 = Inhibitory Level fifty

IMDG = International Maritime Dangerous Goods

INV = Chinese Chemicals Inventory

IP346 = Institute of Petroleum test method N° 346 for the determination of polycyclic aromatics DMSO-extractables

KECI = Korea Existing Chemicals Inventory

LC50 = Lethal Concentration fifty LD50 = Lethal Dose fifty per cent.

LL/EL/IL = Lethal Loading/Effective Loading/Inhibitory loading

LL50 = Lethal Loading fifty

MARPOL = International Convention for the Prevention of

Pollution From Ships

NOEC/NOEL = No Observed Effect Concentration / No

Observed Effect Level

OE HPV = Occupational Exposure - High Production Volume

PBT = Persistent, Bioaccumulative and Toxic

PICCS = Philippine Inventory of Chemicals and Chemical

Substances

PNEC = Predicted No Effect Concentration

REACH = Registration Evaluation And Authorisation Of

Chemicals

RID = Regulations Relating to International Carriage of

Dangerous Goods by Rail SKIN DES = Skin Designation STEL = Short term exposure limit TRA = Targeted Risk Assessment

TSCA = US Toxic Substances Control Act

TWA = Time-Weighted Average

vPvB = very Persistent and very Bioaccumulative

# **Further information**

Training advice : Provide adequate information, instruction and training for

operators.

Other information : For Industry guidance and tools on REACH please visit the

CEFIC website at http://cefic.org/Industry-support. The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not

considered to be PBT or vPvB.

A vertical bar (|) in the left margin indicates an amendment

from the previous version.

According to EC No 1907/2006 as amended as at the date of this SDS

# **CARADOL SP30-45**

Version 1.3 Revision Date 03.07.2019 Print Date 06.09.2022

Sources of key data used to compile the Safety Data Sheet

: The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID date base, EC 1272 regulation, etc).

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.