

# SAFETY DATA SHEET

IMO (International Maritime Organization) SDS per SOLAS regulation VI/5-1

## NEODENE 1214

Version 2.4

Revision Date 04.11.2024

Print Date 11.11.2024

### 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : NEODENE 1214

Product code : V1159, V1235

#### Manufacturer or supplier's details

Supplier : **Shell - See 'Shipper' section of the Bill of Lading**  
and/or 'Supplier' section of the Bunker Delivery Note for details

Telephone : See Bill of Lading and/or Bunker Delivery Note

Emergency telephone number : +1 703-527-3887

#### Recommended use of the chemical and restrictions on use

Recommended use : Use as an intermediate in industrial chemicals manufacture.

Restrictions on use : This product must not be used in applications other than the above without first seeking the advice of the supplier.  
This product must not be used in applications other than those listed in Section 1 without first seeking the advice of the supplier.

Other information : NEODENE is a trademark owned by Shell Trademark Management B.V. and Shell Brands Inc. and used by affiliates of Shell plc.

Other information : See Section 14 for transportation information related to the Bill of Lading, other shipping documents.

### 2. HAZARDS IDENTIFICATION

#### GHS Classification

Flammable liquids : Category 4

Aspiration hazard : Category 1

Skin irritation : Category 3

#### GHS-Labeling

Hazard pictograms :



Signal word : Danger

Hazard statements : PHYSICAL HAZARDS:

# SAFETY DATA SHEET

IMO (International Maritime Organization) SDS per SOLAS regulation VI/5-1

## NEODENE 1214

Version 2.4

Revision Date 04.11.2024

Print Date 11.11.2024

H227 Combustible liquid.

HEALTH HAZARDS:

H304 May be fatal if swallowed and enters airways.

H316 Causes mild skin irritation.

ENVIRONMENTAL HAZARDS:

Not classified as an environmental hazard under GHS criteria.

Precautionary statements

: **Prevention:**

P210 Keep away from heat/ sparks/ open flames/ hot surfaces.  
No smoking.

P243 Take precautionary measures against static discharge.

P280 Wear protective gloves/ protective clothing/ eye  
protection/ face protection.

**Response:**

P370+P378 In case of fire: Use appropriate media for  
extinction.

P301 + P310 IF SWALLOWED: Immediately call a POISON  
CENTER/doctor.

P331 Do NOT induce vomiting.

P332 + P313 If skin irritation occurs: Get medical advice/  
attention.

**Storage:**

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

**Disposal:**

P501 Dispose of contents and container to appropriate waste  
site or reclaimer in accordance with local and national  
regulations.

### Other hazards which do not result in classification

This material is a static accumulator.

Even with proper grounding and bonding, this material can still accumulate an electrostatic  
charge.

If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-  
vapour mixtures can occur.

Vapours are heavier than air. Vapours may travel across the ground and reach remote ignition  
sources causing a flashback fire danger.

Will float and can be reignited on surface water.

Repeated exposure may cause skin dryness or cracking.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture

: Mixture

#### Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
---------------	---------	--------------------------

# SAFETY DATA SHEET

IMO (International Maritime Organization) SDS per SOLAS regulation VI/5-1

## NEODENE 1214

Version 2.4

Revision Date 04.11.2024

Print Date 11.11.2024

dodec-1-ene	112-41-4	60 - 70 %
1-Tetradecene	1120-36-1	30 - 40 %

### Further information

Contains:

## 4. FIRST-AID MEASURES

- General advice : Not expected to be a health hazard when used under normal conditions.
- If inhaled : No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.
- In case of skin contact : Remove contaminated clothing. Immediately flush skin with large amounts of water for at least 15 minutes, and follow by washing with soap and water if available. If redness, swelling, pain and/or blisters occur, transport to the nearest medical facility for additional treatment.
- In case of eye contact : Flush eye with copious quantities of water.  
Remove contact lenses, if present and easy to do. Continue rinsing.  
If persistent irritation occurs, obtain medical attention.
- If swallowed : Call emergency number for your location / facility.  
If swallowed, do not induce vomiting: transport to nearest medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.  
If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (38.3°C), shortness of breath, chest congestion or continued coughing or wheezing.
- Most important symptoms and effects, both acute and delayed : Not considered to be an inhalation hazard under normal conditions of use.  
Possible respiratory irritation signs and symptoms may include a temporary burning sensation of the nose and throat, coughing, and/or difficulty breathing.  
Skin irritation signs and symptoms may include a burning sensation, redness, or swelling.  
No specific hazards under normal use conditions.  
Eye irritation signs and symptoms may include a burning sensation, redness, swelling, and/or blurred vision.  
If material enters lungs, signs and symptoms may include coughing, choking, wheezing, difficulty in breathing, chest congestion, shortness of breath, and/or fever.  
If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (38.3°C), shortness of

# SAFETY DATA SHEET

IMO (International Maritime Organization) SDS per SOLAS regulation VI/5-1

## NEODENE 1214

Version 2.4

Revision Date 04.11.2024

Print Date 11.11.2024

breath, chest congestion or continued coughing or wheezing.  
Defatting dermatitis signs and symptoms may include a  
burning sensation and/or a dried/cracked appearance.

Protection of first-aiders : When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.

Notes to physician : Call a doctor or poison control center for guidance.  
Potential for chemical pneumonitis.  
Treat symptomatically.

### 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

Unsuitable extinguishing media : Do not use water in a jet.

Specific hazards during firefighting : Clear fire area of all non-emergency personnel.  
Hazardous combustion products may include:  
A complex mixture of airborne solid and liquid particulates and gases (smoke).  
Carbon monoxide.  
Unidentified organic and inorganic compounds.  
Flammable vapours may be present even at temperatures below the flash point.  
The vapour is heavier than air, spreads along the ground and distant ignition is possible.  
Will float and can be reignited on surface water.

Specific extinguishing methods : Standard procedure for chemical fires.  
Keep adjacent containers cool by spraying with water.

Special protective equipment for firefighters : Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Observe all relevant local and international regulations.  
Notify authorities if any exposure to the general public or the environment occurs or is likely to occur.

# SAFETY DATA SHEET

IMO (International Maritime Organization) SDS per SOLAS regulation VI/5-1

## NEODENE 1214

Version 2.4

Revision Date 04.11.2024

Print Date 11.11.2024

Local authorities should be advised if significant spillages cannot be contained.

- : Avoid contact with skin, eyes and clothing.  
Isolate hazard area and deny entry to unnecessary or unprotected personnel.  
Do not breathe fumes, vapour.  
Do not operate electrical equipment.

- Environmental precautions
- : Shut off leaks, if possible without personal risks. Remove all possible sources of ignition in the surrounding area. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. Attempt to disperse the vapour or to direct its flow to a safe location for example by using fog sprays. Take precautionary measures against static discharge. Ensure electrical continuity by bonding and grounding (earthing) all equipment.  
Monitor area with combustible gas indicator.

- Methods and materials for containment and cleaning up
- : For small liquid spills (< 1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.  
For large liquid spills (> 1 drum), transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.  
  
Ventilate contaminated area thoroughly.  
If contamination of site occurs remediation may require specialist advice.

- Additional advice
- : For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet.  
For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.

---

## 7. HANDLING AND STORAGE

- General Precautions
- : Avoid breathing of or direct contact with material. Only use in well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet.  
Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of

# SAFETY DATA SHEET

IMO (International Maritime Organization) SDS per SOLAS regulation VI/5-1

## NEODENE 1214

Version 2.4

Revision Date 04.11.2024

Print Date 11.11.2024

this material.

Ensure that all local regulations regarding handling and storage facilities are followed.

Advice on safe handling : Avoid inhaling vapour and/or mists.  
Avoid contact with skin, eyes and clothing.  
Extinguish any naked flames. Do not smoke. Remove ignition sources. Avoid sparks.  
Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols.  
Bulk storage tanks should be diked (bunded).  
When using do not eat or drink.

The vapour is heavier than air, spreads along the ground and distant ignition is possible.

Avoidance of contact : Strong oxidising agents.

Product Transfer : Even with proper grounding and bonding, this material can still accumulate an electrostatic charge. If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur. Be aware of handling operations that may give rise to additional hazards that result from the accumulation of static charges. These include but are not limited to pumping (especially turbulent flow), mixing, filtering, splash filling, cleaning and filling of tanks and containers, sampling, switch loading, gauging, vacuum truck operations, and mechanical movements. These activities may lead to static discharge e.g. spark formation. Restrict line velocity during pumping in order to avoid generation of electrostatic discharge ( $\leq 1$  m/s until fill pipe submerged to twice its diameter, then  $\leq 7$  m/s). Avoid splash filling. Do NOT use compressed air for filling, discharging, or handling operations.

Refer to guidance under Handling section.

### Storage

Conditions for safe storage : Refer to section 15 for any additional specific legislation covering the packaging and storage of this product.

Other data : Storage Temperature:  
Ambient.

Bulk storage tanks should be diked (bunded).  
Locate tanks away from heat and other sources of ignition.  
Cleaning, inspection and maintenance of storage tanks is a specialist operation, which requires the implementation of strict procedures and precautions.  
Must be stored in a diked (bunded) well-ventilated area, away from sunlight, ignition sources and other sources of heat.  
Keep away from aerosols, flammables, oxidizing agents,

# SAFETY DATA SHEET

IMO (International Maritime Organization) SDS per SOLAS regulation VI/5-1

## NEODENE 1214

Version 2.4

Revision Date 04.11.2024

Print Date 11.11.2024

corrosives and from other flammable products which are not harmful or toxic to man or to the environment.  
Electrostatic charges will be generated during pumping. Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment to reduce the risk.  
The vapours in the head space of the storage vessel may lie in the flammable/explosive range and hence may be flammable.

Packaging material : Suitable material: For containers, or container linings use mild steel, stainless steel., For container paints, use epoxy paint, zinc silicate paint.  
Unsuitable material: Avoid prolonged contact with natural, butyl or nitrile rubbers.

Container Advice : Do not cut, drill, grind, weld or perform similar operations on or near containers.

Specific use(s) : Not applicable

See additional references that provide safe handling practices for liquids that are determined to be static accumulators: American Petroleum Institute 2003 (Protection Against Ignitions Arising out of Static, Lightning and Stray Currents) or National Fire Protection Agency 77 (Recommended Practices on Static Electricity).  
IEC/TS 60079-32-1: Electrostatic hazards, guidance

## 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

### Components with workplace control parameters

### Biological occupational exposure limits

No biological limit allocated.

### Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods  
<http://www.cdc.gov/niosh/>

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods  
<http://www.osha.gov/>

# SAFETY DATA SHEET

IMO (International Maritime Organization) SDS per SOLAS regulation VI/5-1

## NEODENE 1214

Version 2.4

Revision Date 04.11.2024

Print Date 11.11.2024

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances  
<http://www.hse.gov.uk/>

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA) , Germany  
<http://www.dguv.de/inhalt/index.jsp>

L'Institut National de Recherche et de Sécurité, (INRS), France <http://www.inrs.fr/accueil>

### Protective measures

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

### Engineering measures

: Use sealed systems as far as possible.  
Adequate explosion-proof ventilation to control airborne concentrations below the exposure guidelines/limits.  
Local exhaust ventilation is recommended.  
Firewater monitors and deluge systems are recommended.  
Eye washes and showers for emergency use.  
Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.  
The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances.  
Appropriate measures include:

#### General Information:

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned.  
Practice good housekeeping.  
Define procedures for safe handling and maintenance of controls.  
Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.  
Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.  
Drain down system prior to equipment break-in or maintenance.  
Retain drain downs in sealed storage pending disposal or subsequent recycle.

### Personal protective equipment

Respiratory protection : If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation.  
Check with respiratory protective equipment suppliers.  
Where air-filtering respirators are unsuitable (e.g. airborne concentrations are high, risk of oxygen deficiency, confined



# SAFETY DATA SHEET

IMO (International Maritime Organization) SDS per SOLAS regulation VI/5-1

## NEODENE 1214

Version 2.4

Revision Date 04.11.2024

Print Date 11.11.2024

space) use appropriate positive pressure breathing apparatus. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter.

If air-filtering respirators are suitable for conditions of use: Select a filter suitable for organic gases and vapours [Type A boiling point >65°C (149°F)].

Hand protection

Remarks

: Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. Longer term protection: Nitrile rubber gloves. Incidental contact/Splash protection: PVC, neoprene or nitrile rubber gloves For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

Eye protection

: If material is handled such that it could be splashed into eyes, protective eyewear is recommended.

Skin and body protection

: Skin protection is not required under normal conditions of use. For prolonged or repeated exposures use impervious clothing over parts of the body subject to exposure. If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to relevant Standard, and provide employee skin care programmes.

Wear antistatic and flame-retardant clothing, if a local risk assessment deems it so.

Thermal hazards

: Not applicable

Hygiene measures

: Wash hands before eating, drinking, smoking and using the toilet.

# SAFETY DATA SHEET

IMO (International Maritime Organization) SDS per SOLAS regulation VI/5-1

## NEODENE 1214

Version 2.4

Revision Date 04.11.2024

Print Date 11.11.2024

Laundry contaminated clothing before re-use.  
Do not ingest. If swallowed, then seek immediate medical assistance.

### Environmental exposure controls

General advice : Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour.  
Minimise release to the environment. An environmental assessment must be made to ensure compliance with local environmental legislation.  
Information on accidental release measures are to be found in section 6.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Liquid at room temperature.

Colour : colourless

Odour : Mild hydrocarbon

Odour Threshold : Data not available

pH : Not applicable

Melting / freezing point : -30 °C / -22 °F

Boiling point/boiling range : 205 - 251 °C / 401 - 484 °F

Flash point : 83 °C / 181 °F

Evaporation rate : Data not available

Flammability (solid, gas) : Not applicable

Lower explosion limit : estimated value(s) 0.5 %(V)

Vapour pressure : 41 Pa (31 °C / 88 °F)

Relative vapour density : Data not available

Relative density : 0.76 (20 °C / 68 °F)  
Method: ASTM D4052

Density : ca. 768 kg/m<sup>3</sup> (16 °C / 61 °F)  
Method: ASTM D4052

Solubility(ies)

# SAFETY DATA SHEET

IMO (International Maritime Organization) SDS per SOLAS regulation VI/5-1

## NEODENE 1214

Version 2.4

Revision Date 04.11.2024

Print Date 11.11.2024

Water solubility	: < 0.5 mg/l (25 °C / 77 °F)
Partition coefficient: n-octanol/water	: log Pow: 6.1 - 7.1 Calculated value(s)
Auto-ignition temperature	: ca. 240 °C / 464 °F
Decomposition temperature	: Data not available
Viscosity	
Viscosity, dynamic	: 1.2 mPa.s (38 °C / 100 °F) Method: ASTM D445
Viscosity, dynamic	: 1.54 mPa.s (20 °C / 68 °F) Method: ASTM D445
Viscosity, kinematic	: 2.6 mm <sup>2</sup> /s (20 °C / 68 °F) Method: ASTM D445
Explosive properties	: Not applicable
Oxidizing properties	: Data not available
Surface tension	: Data not available
Conductivity	: Low conductivity: < 100 pS/m, The conductivity of this material makes it a static accumulator., A liquid is typically considered nonconductive if its conductivity is below 100 pS/m and is considered semi-conductive if its conductivity is below 10,000 pS/m., Whether a liquid is nonconductive or semi-conductive, the precautions are the same., A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid
Particle size	: Data not available
Molecular weight	: estimated value(s) 176 - 179 g/mol

### 10. STABILITY AND REACTIVITY

Reactivity	: The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.
Chemical stability	: No hazardous reaction is expected when handled and stored according to provisions Stable under normal conditions of use.

# SAFETY DATA SHEET

IMO (International Maritime Organization) SDS per SOLAS regulation VI/5-1

## NEODENE 1214

Version 2.4

Revision Date 04.11.2024

Print Date 11.11.2024

Possibility of hazardous reactions	: Reacts with strong oxidising agents.
Conditions to avoid	: Avoid heat, sparks, open flames and other ignition sources.  In certain circumstances product can ignite due to static electricity.
Incompatible materials	: Strong oxidising agents.
Hazardous decomposition products	: Hazardous decomposition products are not expected to form during normal storage. Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids and gases including carbon monoxide, carbon dioxide, sulphur oxides and unidentified organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation.

### 11. TOXICOLOGICAL INFORMATION

Basis for assessment	: Information given is based on product testing, and/or similar products, and/or components. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).
Information on likely routes of exposure	: Exposure may occur via inhalation, ingestion, skin absorption, skin or eye contact, and accidental ingestion.

#### Acute toxicity

##### Product:

Acute oral toxicity	: LD50 : > 5,000 mg/kg Remarks: Low toxicity Based on available data, the classification criteria are not met.
Acute inhalation toxicity	: Remarks: Low toxicity if inhaled. Based on available data, the classification criteria are not met.
Acute dermal toxicity	: LD50 : > 5,000 mg/kg Remarks: Low toxicity Based on available data, the classification criteria are not met.

##### Components:

##### **dodec-1-ene:**

# SAFETY DATA SHEET

IMO (International Maritime Organization) SDS per SOLAS regulation VI/5-1

## NEODENE 1214

Version 2.4

Revision Date 04.11.2024

Print Date 11.11.2024

- Acute oral toxicity : LD 50 Rat, male and female: > 5,000 mg/kg  
Method: Test(s) equivalent or similar to OECD Test Guideline 420  
Remarks: Based on available data, the classification criteria are not met.  
Low toxicity  
LD50 >5000 mg/kg
- Acute inhalation toxicity : LC 50 Rat, male: > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Test(s) equivalent or similar to OECD Test Guideline 403  
Remarks: Based on available data, the classification criteria are not met.  
Low toxicity if inhaled.
- Acute dermal toxicity : LD 50 Rabbit, male and female: > 2,000 mg/kg  
Method: OECD Test Guideline 402  
Remarks: May be harmful in contact with skin.  
LD50 >2000 - <=5000 mg/kg  
Based on available data, the classification criteria are not met.
- 1-Tetradecene:**  
Acute oral toxicity : LD50 : > 5000 mg/kg  
Remarks: Low toxicity  
Based on available data, the classification criteria are not met.
- Acute inhalation toxicity : Remarks: Low toxicity if inhaled.  
Based on available data, the classification criteria are not met.
- Acute dermal toxicity : LD50 : > 5000 mg/kg  
Remarks: Low toxicity  
Based on available data, the classification criteria are not met.

### Skin corrosion/irritation

#### Product:

Remarks: Causes mild skin irritation.

#### Components:

##### **dodec-1-ene:**

Species: Rabbit

Method: Test(s) equivalent or similar to OECD Test Guideline 404

Remarks: Causes mild skin irritation.

##### **1-Tetradecene:**

Remarks: Causes mild skin irritation., Repeated exposure may cause skin dryness or cracking.

# SAFETY DATA SHEET

IMO (International Maritime Organization) SDS per SOLAS regulation VI/5-1

## NEODENE 1214

Version 2.4

Revision Date 04.11.2024

Print Date 11.11.2024

### Serious eye damage/eye irritation

#### Product:

Remarks: Not irritating to eye.

#### Components:

##### **dodec-1-ene:**

Species: Rabbit

Method: Test(s) equivalent or similar to OECD Test Guideline 405

Remarks: Based on available data, the classification criteria are not met., Not irritating to eye.

##### **1-Tetradecene:**

Remarks: Not irritating to eye.

### Respiratory or skin sensitisation

#### Product:

Remarks: Not a sensitiser., Based on available data, the classification criteria are not met.

#### Components:

##### **dodec-1-ene:**

Species: Guinea pig

Method: Test(s) equivalent or similar to OECD Test Guideline 406

Remarks: Based on available data, the classification criteria are not met., Not a sensitiser.

##### **1-Tetradecene:**

Remarks: Not a sensitiser., Based on available data, the classification criteria are not met.

### Germ cell mutagenicity

#### Product:

: Remarks: Non mutagenic

#### Components:

##### **dodec-1-ene:**

Genotoxicity in vitro

: Method: OECD Test Guideline 471

Remarks: Based on available data, the classification criteria are not met., Non mutagenic

: Method: Test(s) equivalent or similar to OECD Test Guideline 473

Remarks: Based on available data, the classification criteria are not met., Non mutagenic

: Test species: MouseMethod: OECD Test Guideline 471

Remarks: Based on available data, the classification criteria are not met., Non mutagenic

Germ cell mutagenicity-

: This product does not meet the criteria for classification in

# SAFETY DATA SHEET

IMO (International Maritime Organization) SDS per SOLAS regulation VI/5-1

## NEODENE 1214

Version 2.4

Revision Date 04.11.2024

Print Date 11.11.2024

Assessment

categories 1A/1B.

**1-Tetradecene:**

: Remarks: Non mutagenic

### Carcinogenicity

#### Product:

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

#### Components:

**dodec-1-ene:**

Carcinogenicity -  
Assessment

: This product does not meet the criteria for classification in  
categories 1A/1B.

**1-Tetradecene:**

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

Material	GHS/CLP Carcinogenicity Classification
dodec-1-ene	No carcinogenicity classification.
1-Tetradecene	No carcinogenicity classification.

### Reproductive toxicity

#### **Product:**

:  
Remarks: Not a developmental toxicant., Based on available data, the classification criteria are not met., Does not impair fertility.

#### **Components:**

**dodec-1-ene:**

: Species: Rat  
Sex: male and female  
Application Route: Oral

Method: OECD Test Guideline 422

Remarks: Based on available data, the classification criteria are not met., Does not impair fertility.

Effects on foetal  
development

: Species: Rat, female  
Application Route: Oral

# SAFETY DATA SHEET

IMO (International Maritime Organization) SDS per SOLAS regulation VI/5-1

## NEODENE 1214

Version 2.4

Revision Date 04.11.2024

Print Date 11.11.2024

Method: OECD Test Guideline 414

Remarks: Based on available data, the classification criteria are not met., Not a developmental toxicant.

Reproductive toxicity -  
Assessment

: This product does not meet the criteria for classification in categories 1A/1B.

### 1-Tetradecene:

Remarks: Not a developmental toxicant., Based on available data, the classification criteria are not met., Does not impair fertility.

### STOT - single exposure

#### Product:

Remarks: Based on available data, the classification criteria are not met.

#### Components:

##### **dodec-1-ene:**

Remarks: Based on available data, the classification criteria are not met.

##### **1-Tetradecene:**

Remarks: Based on available data, the classification criteria are not met.

### STOT - repeated exposure

#### Product:

Remarks: Based on available data, the classification criteria are not met.

#### Components:

##### **dodec-1-ene:**

Remarks: Based on available data, the classification criteria are not met., Repeated exposure may cause skin dryness or cracking.

##### **1-Tetradecene:**

Remarks: Based on available data, the classification criteria are not met.

### Repeated dose toxicity

#### Components:

##### **dodec-1-ene:**

Rat, male and female:

Application Route: Oral

Method: OECD Test Guideline 408

Target Organs: No specific target organs noted



# SAFETY DATA SHEET

IMO (International Maritime Organization) SDS per SOLAS regulation VI/5-1

## NEODENE 1214

Version 2.4

Revision Date 04.11.2024

Print Date 11.11.2024

Rat, male and female:  
Application Route: Inhalation  
Test atmosphere: vapour  
Method: Test(s) equivalent or similar to OECD Test Guideline 413  
Target Organs: No specific target organs noted

### Aspiration toxicity

#### Product:

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

#### Components:

##### **dodec-1-ene:**

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

##### **1-Tetradecene:**

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

### Further information

#### Product:

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

#### Components:

##### **dodec-1-ene:**

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

##### **1-Tetradecene:**

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

---

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

Basis for assessment : Incomplete ecotoxicological data are available for this product. The information given below is based partly on a knowledge of the components and the ecotoxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

#### Product:

# SAFETY DATA SHEET

IMO (International Maritime Organization) SDS per SOLAS regulation VI/5-1

## NEODENE 1214

Version 2.4

Revision Date 04.11.2024

Print Date 11.11.2024

Toxicity to fish (Acute toxicity) : Remarks: Not toxic at limit of water solubility:

Toxicity to daphnia and other aquatic invertebrates (Acute toxicity) : Remarks: Not toxic at limit of water solubility:

Toxicity to algae (Acute toxicity) : Remarks: Not toxic at limit of water solubility:

Toxicity to fish (Chronic toxicity) : Remarks: Data not available

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : Remarks: Data not available

Toxicity to bacteria : Remarks: Not toxic at limit of water solubility:

### **Components:**

#### **dodec-1-ene :**

Toxicity to fish (Acute toxicity) : LC50 (Oncorhynchus mykiss (rainbow trout)): > 0.0034 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203  
Remarks: No toxicity at the limit of solubility

Toxicity to daphnia and other aquatic invertebrates (Acute toxicity) : EC50 (Daphnia magna (Water flea)): > 0.0028 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202  
Remarks: No toxicity at the limit of solubility

Toxicity to algae (Acute toxicity) : EC50 (Pseudokirchneriella subcapitata (algae)): > 0.00093 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
Remarks: Not toxic at limit of water solubility:

Toxicity to bacteria : NOEC (Secondary Effluent): 2 mg/l  
Exposure time: 336 h  
Method: OECD Test Guideline 301D  
Remarks: No toxicity at the limit of solubility

Toxicity to fish (Chronic toxicity) : Remarks: Data not available

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : Remarks: Data not available

#### **1-Tetradecene :**

Toxicity to fish (Acute toxicity) : Remarks: Not toxic at limit of water solubility:

Toxicity to daphnia and other aquatic invertebrates (Acute toxicity) : Remarks: Not toxic at limit of water solubility:

Toxicity to algae (Acute toxicity) : Remarks: Not toxic at limit of water solubility:

# SAFETY DATA SHEET

IMO (International Maritime Organization) SDS per SOLAS regulation VI/5-1

## NEODENE 1214

Version 2.4

Revision Date 04.11.2024

Print Date 11.11.2024

toxicity)

Toxicity to bacteria : Remarks: Not toxic at limit of water solubility:

Toxicity to fish (Chronic toxicity) : Remarks: Data not available

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : Remarks: Data not available

### Persistence and degradability

#### Product:

Biodegradability : Remarks: Not Persistent per IMO criteria.

#### Components:

##### **dodec-1-ene :**

Biodegradability : Biodegradation: 72.4 - 74.5 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301D  
Remarks: Readily biodegradable.

##### **1-Tetradecene :**

Biodegradability : Remarks: Readily biodegradable.

### Bioaccumulative potential

#### Product:

Bioaccumulation : Remarks: Has the potential to bioaccumulate.

Partition coefficient: n-octanol/water : log Pow: 6.1 - 7.1Remarks: Calculated value(s)

#### Components:

##### **dodec-1-ene :**

Bioaccumulation : Remarks: Has the potential to bioaccumulate.

##### **1-Tetradecene :**

Bioaccumulation : Remarks: Has the potential to bioaccumulate.

### Mobility in soil

#### Product:

Mobility : Remarks: Floats on water., Adsorbs to soil and has low mobility

#### Components:

##### **dodec-1-ene :**

Mobility : Remarks: If it enters soil, it will adsorb to soil particles and will not be mobile., Floats on water.

##### **1-Tetradecene :**

Mobility : Remarks: Floats on water., Adsorbs to soil and has low mobility

### Other adverse effects

# SAFETY DATA SHEET

IMO (International Maritime Organization) SDS per SOLAS regulation VI/5-1

## NEODENE 1214

Version 2.4

Revision Date 04.11.2024

Print Date 11.11.2024

### **Product:**

Additional ecological information : Does not have ozone depletion potential.

### **Components:**

#### **dodec-1-ene :**

Results of PBT and vPvB assessment : The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB.

Additional ecological information : Data not available

---

## 13. DISPOSAL CONSIDERATIONS

### **Disposal methods**

Waste from residues : Recover or recycle if possible.  
It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.  
Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment.  
Do not dispose into the environment, in drains or in water courses.  
Do not dispose of tank water bottoms by allowing them to drain into the ground. This will result in soil and groundwater contamination.  
Waste arising from a spillage or tank cleaning should be disposed of in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand.  
MARPOL - see International Convention for the Prevention of Pollution from Ships (MARPOL 73/78) which provides technical aspects at controlling pollutions from ships.

Contaminated packaging : Drain container thoroughly.  
After draining, vent in a safe place away from sparks and fire.  
Residues may cause an explosion hazard. Do not puncture, cut or weld uncleaned drums.  
Send to drum recoverer or metal reclaimer.  
Comply with any local recovery or waste disposal regulations.

---

## 14. TRANSPORT INFORMATION

### **International Regulations**

# SAFETY DATA SHEET

IMO (International Maritime Organization) SDS per SOLAS regulation VI/5-1

## NEODENE 1214

Version 2.4

Revision Date 04.11.2024

Print Date 11.11.2024

### IATA-DGR

Not regulated as a dangerous good

### IMDG-Code

Not regulated as a dangerous good

### Special precautions for user

Remarks : Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

**Additional Information** : This product may be transported under nitrogen blanketing. Nitrogen is an odourless and invisible gas. Exposure to nitrogen enriched atmospheres displaces available oxygen which may cause asphyxiation or death. Personnel must observe strict safety precautions when involved with a confined space entry.  
Transport in bulk according to Annex II of Marpol and the IBC Code

## 15. REGULATORY INFORMATION

Other regulations : The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

International Convention for the Safety of Life at Seas (SOLAS) Regulation VI/5-1.RESOLUTION MSC.286(86) ;  
RECOMMENDATIONS FOR MATERIAL SAFETY DATA SHEETS (MSDS) FOR MARPOL ANNEX I OIL CARGO AND OIL FUEL.

### The components of this product are reported in the following inventories:

AIIC	: Listed
DSL	: Listed
IECSC	: Listed
ENCS	: Listed
KECI	: Listed
NZIoC	: Listed
PICCS	: Listed
TSCA	: Listed
TCSI	: Listed

## 16. OTHER INFORMATION

Abbreviations and Acronyms : The standard abbreviations and acronyms used in this document can be looked up in reference literature (e.g. scientific dictionaries) and/or websites.

# SAFETY DATA SHEET

IMO (International Maritime Organization) SDS per SOLAS regulation VI/5-1

## NEODENE 1214

Version 2.4

Revision Date 04.11.2024

Print Date 11.11.2024

### Further information

Training advice : Provide adequate information, instruction and training for operators.

Other information : A vertical bar (|) in the left margin indicates an amendment from the previous version.

Sources of key data used to compile the Safety Data Sheet : The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID data base, EC 1272 regulation, etc).

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.