

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 28.03.2023 |
| 3.0 | 21.11.2023 | 800001001081 | Print Date 28.11.2023 |

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

| | |
|------------------------|-------------------------|
| Trade name | : Normal-Pentane |
| Product code | : Q1116 |
| Registration number EU | : 01-2119459286-30-0001 |
| Synonyms | : n-Pentane |
| CAS-No. | : 109-66-0 |

| | |
|--------|-------------|
| EC-No. | : 203-692-4 |
|--------|-------------|

1.2 Relevant identified uses of the substance or mixture and uses advised against

| | |
|-----------------------------------|--|
| Use of the Sub- stance/Mixture | : Industrial Solvent. Please refer to section 16 and/or the annexes for the registered uses under REACH. |
| Uses advised against | : This product must not be used in applications other than the above without first seeking the advice of the supplier. |

1.3 Details of the supplier of the safety data sheet

| | |
|----------------------------------|---|
| Manufacturer/Supplier | : Shell Chemicals Europe B.V. PO Box 2334 3000 CH Rotterdam Netherlands |
| Telephone | : +31 (0)10 441 5137 / +31 (0)10 441 5191 |
| Telefax | : +31 (0)20 716 8316 / +31 (0)20 713 9230 |
| Contact for Safety Data Sheet | : sccmsds@shell.com |

1.4 Emergency telephone number

+44 (0) 1235 239 670
Nationaal Vergiftigingen Informatie Centrum (NVIC): Tel. nr. +31(0)88 755 8000 (24 uur per dag en 7 dagen per week).
(Uitsluitend bestemd om artsen te informeren bij accidentele vergiftigingen).

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

| | |
|-------------------------------|---|
| Flammable liquids, Category 1 | H224: Extremely flammable liquid and vapour. |
| Aspiration hazard, Category 1 | H304: May be fatal if swallowed and enters airways. |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 28.03.2023 |
| 3.0 | 21.11.2023 | 800001001081 | Print Date 28.11.2023 |

Specific target organ toxicity - single exposure, Category 3, Narcotic effects

H336: May cause drowsiness or dizziness.

Long-term (chronic) aquatic hazard, Category 2

H411: Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms

:



Signal word

:

Danger

Hazard statements

:

PHYSICAL HAZARDS:
H224 Extremely flammable liquid and vapour.
HEALTH HAZARDS:
H304 May be fatal if swallowed and enters airways.
H336 May cause drowsiness or dizziness.
ENVIRONMENTAL HAZARDS:
H411 Toxic to aquatic life with long lasting effects.

Supplemental Hazard Statements

:

EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statements

:

Prevention:
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P243 Take action to prevent static discharges.
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P273 Avoid release to the environment.
Response:
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P331 Do NOT induce vomiting.
Storage:
P403 + P235 Store in a well-ventilated place. Keep cool.
Disposal:
P501 Dispose of contents/ container to an approved waste disposal plant.

2.3 Other hazards

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

Version 3.0 Revision Date: 21.11.2023 SDS Number: 800001001081 Date of last issue: 28.03.2023
Print Date 28.11.2023

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

May form flammable/explosive vapour-air mixture.

This material is a static accumulator.

Even with proper grounding and bonding, this material can still accumulate an electrostatic charge.

If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur.

SECTION 3: Composition/information on ingredients

3.1 Substances

Components

| Chemical name | CAS-No. EC-No. | Concentration (% w/w) |
|---------------|-----------------------|-----------------------|
| pentane | 109-66-0 203-692-4 | 100 |

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Not expected to be a health hazard when used under normal conditions.
- Protection of first-aiders : When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.
- If inhaled : Remove to fresh air. If rapid recovery does not occur, transport to nearest medical facility for additional treatment.
- In case of skin contact : Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available.
If persistent irritation occurs, obtain medical attention.
- In case of eye contact : Flush eye with copious quantities of water.
Remove contact lenses, if present and easy to do. Continue rinsing.
If persistent irritation occurs, obtain medical attention.
- If swallowed : Call emergency number for your location / facility.
If swallowed, do not induce vomiting: transport to nearest medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 28.03.2023 |
| 3.0 | 21.11.2023 | 800001001081 | Print Date 28.11.2023 |

If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (38.3°C), shortness of breath, chest congestion or continued coughing or wheezing.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Breathing of high vapour concentrations may cause central nervous system (CNS) depression resulting in dizziness, light-headedness, headache, nausea and loss of coordination. Continued inhalation may result in unconsciousness and death.

No specific hazards under normal use conditions.
Skin irritation signs and symptoms may include a burning sensation, redness, or swelling.

No specific hazards under normal use conditions.
Eye irritation signs and symptoms may include a burning sensation, redness, swelling, and/or blurred vision.

If material enters lungs, signs and symptoms may include coughing, choking, wheezing, difficulty in breathing, chest congestion, shortness of breath, and/or fever.
If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (38.3°C), shortness of breath, chest congestion or continued coughing or wheezing.

Defatting dermatitis signs and symptoms may include a burning sensation and/or a dried/cracked appearance.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.
Call a doctor or poison control center for guidance.
Potential for chemical pneumonitis.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

Unsuitable extinguishing media : Do not use water in a jet.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Clear fire area of all non-emergency personnel.
Hazardous combustion products may include:
A complex mixture of airborne solid and liquid particulates and gases (smoke).

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 28.03.2023 |
| 3.0 | 21.11.2023 | 800001001081 | Print Date 28.11.2023 |

Carbon monoxide.
Unidentified organic and inorganic compounds.
Flammable vapours may be present even at temperatures below the flash point.
The vapour is heavier than air, spreads along the ground and distant ignition is possible.
Will float and can be reignited on surface water.

5.3 Advice for firefighters

Special protective equipment for firefighters : Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

Specific extinguishing methods : Standard procedure for chemical fires.

Further information : Keep adjacent containers cool by spraying with water.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Observe all relevant local and international regulations. Notify authorities if any exposure to the general public or the environment occurs or is likely to occur. Local authorities should be advised if significant spillages cannot be contained.

6.1.1 For non emergency personnel:
Avoid contact with skin, eyes and clothing.
Isolate hazard area and deny entry to unnecessary or unprotected personnel.
Do not breathe fumes, vapour.
Do not operate electrical equipment.

6.1.2 For emergency responders:
Avoid contact with skin, eyes and clothing.
Isolate hazard area and deny entry to unnecessary or unprotected personnel.
Do not breathe fumes, vapour.
Do not operate electrical equipment.

6.2 Environmental precautions

Environmental precautions : Shut off leaks, if possible without personal risks. Remove all possible sources of ignition in the surrounding area. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. Attempt to disperse the vapour or to direct its flow to a safe location for

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 28.03.2023 |
| 3.0 | 21.11.2023 | 800001001081 | Print Date 28.11.2023 |

example by using fog sprays. Take precautionary measures against static discharge. Ensure electrical continuity by bonding and grounding (earthing) all equipment. Monitor area with combustible gas indicator.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : For small liquid spills (< 1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.

For large liquid spills (> 1 drum), transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.

Ventilate contaminated area thoroughly.
If contamination of site occurs remediation may require specialist advice.

6.4 Reference to other sections

For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet.,
For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures : Avoid breathing of or direct contact with material. Only use in well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet.

Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.

Ensure that all local regulations regarding handling and storage facilities are followed.

Advice on safe handling : Avoid inhaling vapour and/or mists.

Avoid contact with skin, eyes and clothing.

Extinguish any naked flames. Do not smoke. Remove ignition sources. Avoid sparks.

Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols.

Bulk storage tanks should be diked (bunded).

When using do not eat or drink.

The vapour is heavier than air, spreads along the ground and

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 28.03.2023 |
| 3.0 | 21.11.2023 | 800001001081 | Print Date 28.11.2023 |

distant ignition is possible.

Product Transfer : Even with proper grounding and bonding, this material can still accumulate an electrostatic charge. If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur. Be aware of handling operations that may give rise to additional hazards that result from the accumulation of static charges. These include but are not limited to pumping (especially turbulent flow), mixing, filtering, splash filling, cleaning and filling of tanks and containers, sampling, switch loading, gauging, vacuum truck operations, and mechanical movements. These activities may lead to static discharge e.g. spark formation. Restrict line velocity during pumping in order to avoid generation of electrostatic discharge (≤ 1 m/s until fill pipe submerged to twice its diameter, then ≤ 7 m/s). Avoid splash filling. Do NOT use compressed air for filling, discharging, or handling operations.

Refer to guidance under Handling section.

Hygiene measures : Wash hands before eating, drinking, smoking and using the toilet. Launder contaminated clothing before re-use. Do not ingest. If swallowed, then seek immediate medical assistance.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Refer to section 15 for any additional specific legislation covering the packaging and storage of this product.

Further information on storage stability : Storage Temperature:
Ambient.

Bulk storage tanks should be diked (bunded).
Locate tanks away from heat and other sources of ignition.
Cleaning, inspection and maintenance of storage tanks is a specialist operation, which requires the implementation of strict procedures and precautions.
Must be stored in a diked (bunded) well-ventilated area, away from sunlight, ignition sources and other sources of heat.
Keep away from aerosols, flammables, oxidizing agents, corrosives and from other flammable products which are not harmful or toxic to man or to the environment.
Electrostatic charges will be generated during pumping.
Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment to reduce the risk.
The vapours in the head space of the storage vessel may lie in the flammable/explosive range and hence may be flammable.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

Version 3.0 Revision Date: 21.11.2023 SDS Number: 800001001081 Date of last issue: 28.03.2023
Print Date 28.11.2023

- Packaging material : Suitable material: For containers, or container linings use mild steel, stainless steel., For container paints, use epoxy paint, zinc silicate paint.
Unsuitable material: Avoid prolonged contact with natural, butyl or nitrile rubbers.
- Container Advice : Do not cut, drill, grind, weld or perform similar operations on or near containers.

7.3 Specific end use(s)

- Specific use(s) : Please refer to section 16 and/or the annexes for the registered uses under REACH.

See additional references that provide safe handling practices for liquids that are determined to be static accumulators: American Petroleum Institute 2003 (Protection Against Ignitions Arising out of Static, Lightning and Stray Currents) or National Fire Protection Agency 77 (Recommended Practices on Static Electricity).
IEC/TS 60079-32-1: Electrostatic hazards, guidance

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

| Components | CAS-No. | Value type (Form of exposure) | Control parameters | Basis |
|---------------------------------|----------|-------------------------------|--------------------------------------|------------|
| pentane | 109-66-0 | TLV-8hr | 600 ppm 1.800 mg/m ³ | NL WG |
| pentane | | TWA | 1.000 ppm 3.000 mg/m ³ | 2006/15/EC |
| Further information: Indicative | | | | |

Biological occupational exposure limits

No biological limit allocated.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

| Substance name | End Use | Exposure routes | Potential health effects | Value |
|----------------|-----------|-----------------|----------------------------|------------------------|
| pentane | Workers | Dermal | Long-term systemic effects | 432 mg/kg bw/day |
| pentane | Workers | Inhalation | Long-term systemic effects | 3000 mg/m ³ |
| pentane | Consumers | Dermal | Long-term systemic effects | 214 mg/kg bw/day |
| pentane | Consumers | Inhalation | Long-term systemic effects | 643 mg/m ³ |
| pentane | Consumers | Oral | Long-term systemic effects | 214 mg/kg bw/day |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

Version 3.0 Revision Date: 21.11.2023 SDS Number: 800001001081 Date of last issue: 28.03.2023
Print Date 28.11.2023

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

| Substance name | Environmental Compartment | Value |
|----------------|---------------------------|-----------------------|
| pentane | Water | 0,23 mg/l |
| pentane | Sediment | 1,2 mg/kg |
| pentane | Soil | 0,55 mg/kg wet weight |
| pentane | Sewage treatment plant | 3,6 mg/l |

8.2 Exposure controls

Engineering measures

Read in conjunction with the Exposure Scenario for your specific use contained in the Annex.
Use sealed systems as far as possible.

Adequate explosion-proof ventilation to control airborne concentrations below the exposure guidelines/limits.

Local exhaust ventilation is recommended.

Eye washes and showers for emergency use.

Firewater monitors and deluge systems are recommended.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

General Information:

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or for subsequent recycle.

Personal protective equipment

Read in conjunction with the Exposure Scenario for your specific use contained in the Annex. The provided information is made in consideration of the PPE directive (Council Directive 89/686/EEC) and the CEN European Committee for Standardisation (CEN) standards.

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Eye protection : Wear goggles for use against liquids and gas.
Approved to EU Standard EN166.

Hand protection

Remarks : Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

Version
3.0

Revision Date:
21.11.2023

SDS Number:
800001001081

Date of last issue: 28.03.2023
Print Date 28.11.2023

suitable chemical protection. Longer term protection: Nitrile rubber gloves. Incidental contact/Splash protection: PVC or neoprene rubber gloves. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

Skin and body protection : Skin protection is not required under normal conditions of use.
For prolonged or repeated exposures use impervious clothing over parts of the body subject to exposure.

If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to relevant Standard, and provide employee skin care programmes.
Protective clothing approved to EU Standard EN14605.

Wear antistatic and flame-retardant clothing, if a local risk assessment deems it so.

Respiratory protection : If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are unsuitable (e.g. airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus.
Where air-filtering respirators are suitable, select an appropriate combination of mask and filter.
If air-filtering respirators are suitable for conditions of use: Select a filter suitable for organic gases and vapours [Type AX boiling point < 65°C (149°F)] meeting EN14387.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 28.03.2023 |
| 3.0 | 21.11.2023 | 800001001081 | Print Date 28.11.2023 |

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

| | | |
|--|---|--|
| Physical state | : | liquid |
| Colour | : | colourless |
| Odour | : | Paraffinic |
| Odour Threshold | : | 990 ppm |
| Melting / freezing point | : | Data not available |
| Boiling point/boiling range | : | < 36 °C |
| Flammability | | |
| Flammability (solid, gas) | : | Not applicable |
| Lower explosion limit and upper explosion limit / flammability limit | | |
| Upper explosion limit / upper flammability limit | : | 7,8 %(V) |
| Lower explosion limit / Lower flammability limit | : | 1,4 %(V) |
| Flash point | : | Typical -50 °C Method: IP 170 |
| Auto-ignition temperature | : | 404 °C |
| Decomposition temperature | | |
| Decomposition temperature | : | Data not available |
| pH | : | Not applicable |
| Viscosity | | |
| Viscosity, dynamic | : | Data not available |
| Viscosity, kinematic | : | Typical 0,35 mm ² /s (25 °C) Method: ASTM D445 |
| | | Typical 0,62 mm ² /s (0 °C) Method: ASTM D445 |
| Solubility(ies) | | |
| Water solubility | : | Data not available |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 28.03.2023 |
| 3.0 | 21.11.2023 | 800001001081 | Print Date 28.11.2023 |

Partition coefficient: n-octanol/water : log Pow: 3,39

Vapour pressure : 270 hPa (0 °C)
720 hPa (20 °C)
1.570 hPa (50 °C)

Relative density : Data not available

Density : Typical 632 kg/m³ (15 °C)
Method: ASTM D4052

Relative vapour density : 2,5

Particle characteristics
Particle size : Data not available

9.2 Other information

Explosives : Not classified

Oxidizing properties : Not applicable

Evaporation rate : 12
Method: ASTM D 3539, nBuAc=1
1
Method: DIN 53170, di-ethyl ether=1

Conductivity : 1,1 pS/m
Low conductivity: < 100 pS/m

The conductivity of this material makes it a static accumulator., A liquid is typically considered nonconductive if its conductivity is below 100 pS/m and is considered semi-conductive if its conductivity is below 10,000 pS/m., Whether a liquid is nonconductive or semi-conductive, the precautions are the same., A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid

Surface tension : Data not available

Molecular weight : 72 g/mol

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 28.03.2023 |
| 3.0 | 21.11.2023 | 800001001081 | Print Date 28.11.2023 |

SECTION 10: Stability and reactivity

10.1 Reactivity

The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.

10.2 Chemical stability

No hazardous reaction is expected when handled and stored according to provisions
Stable under normal conditions of use.

10.3 Possibility of hazardous reactions

Hazardous reactions : Reacts with strong oxidising agents.

10.4 Conditions to avoid

Conditions to avoid : Avoid heat, sparks, open flames and other ignition sources.

In certain circumstances product can ignite due to static electricity.

10.5 Incompatible materials

Materials to avoid : Strong oxidising agents.

10.6 Hazardous decomposition products

Hazardous decomposition products are not expected to form during normal storage.
Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids and gases including carbon monoxide, carbon dioxide, sulphur oxides and unidentified organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure : Exposure may occur via inhalation, ingestion, skin absorption, skin or eye contact, and accidental ingestion.

Acute toxicity

Components:

pentane:

Acute oral toxicity : LD50 (Rat, male and female): > 5.000 mg/kg
Method: OECD Test Guideline 401
Remarks: Based on available data, the classification criteria are not met.

Acute inhalation toxicity : LC50 (Rat, male and female): > 20 mg/l
Exposure time: 4 h

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 28.03.2023 |
| 3.0 | 21.11.2023 | 800001001081 | Print Date 28.11.2023 |

Test atmosphere: vapour
Method: OECD Test Guideline 403
Remarks: Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Components:

pentane:

| | | |
|---------|---|---|
| Species | : | Rabbit |
| Method | : | Test(s) equivalent or similar to OECD Test Guideline 404 |
| Remarks | : | Slightly irritating to skin. Insufficient to classify. |

Serious eye damage/eye irritation

Components:

pentane:

| | | |
|---------|---|---|
| Species | : | Rabbit |
| Method | : | OECD Test Guideline 405 |
| Remarks | : | Slightly irritating. Insufficient to classify. |

Respiratory or skin sensitisation

Components:

pentane:

| | | |
|---------|---|---|
| Species | : | Guinea pig |
| Method | : | OECD Test Guideline 406 |
| Remarks | : | Based on available data, the classification criteria are not met. |

Germ cell mutagenicity

Components:

pentane:

| | | |
|-----------------------|---|---|
| Genotoxicity in vitro | : | Method: Test(s) equivalent or similar to OECD Guideline 471 Remarks: Based on available data, the classification criteria are not met. |
|-----------------------|---|---|

Method: Directive 67/548/EEC, Annex V, B.10.
Remarks: Based on available data, the classification criteria are not met.

| | | |
|----------------------|---|--|
| Genotoxicity in vivo | : | Species: Rat Method: Directive 67/548/EEC, Annex V, B.12. Remarks: Based on available data, the classification criteria are not met. |
|----------------------|---|--|

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

Version 3.0 Revision Date: 21.11.2023 SDS Number: 800001001081 Date of last issue: 28.03.2023
Print Date 28.11.2023

Germ cell mutagenicity- Assessment : This product does not meet the criteria for classification in categories 1A/1B.

Carcinogenicity

Components:

pentane:

Carcinogenicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

| Material | GHS/CLP Carcinogenicity Classification |
|----------|--|
| pentane | No carcinogenicity classification. |

Reproductive toxicity

Components:

pentane:

Effects on fertility : Species: Rat
Sex: male and female
Application Route: Inhalation

Method: Equivalent or similar to OECD Test Guideline 416
Remarks: Based on available data, the classification criteria are not met.

Reproductive toxicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

STOT - single exposure

Components:

pentane:

Exposure routes : Inhalation
Target Organs : Central nervous system
Remarks : May cause drowsiness or dizziness.

STOT - repeated exposure

Components:

pentane:

Remarks : Based on available data, the classification criteria are not met.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 28.03.2023 |
| 3.0 | 21.11.2023 | 800001001081 | Print Date 28.11.2023 |

Repeated dose toxicity

Components:

pentane:

| | | |
|-------------------|---|---------------------------------|
| Species | : | Rat, male and female |
| Application Route | : | Inhalation |
| Test atmosphere | : | Gas |
| Method | : | OECD Test Guideline 413 |
| Target Organs | : | No specific target organs noted |

Aspiration toxicity

Components:

pentane:

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

| | | |
|------------|---|---|
| Assessment | : | The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher. |
|------------|---|---|

Further information

Product:

| | | |
|---------|---|--|
| Remarks | : | Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s). |
|---------|---|--|

Components:

pentane:

| | | |
|---------|---|---|
| Remarks | : | Classifications by other authorities under varying regulatory frameworks may exist. |
|---------|---|---|

SECTION 12: Ecological information

12.1 Toxicity

Components:

pentane:

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 28.03.2023 |
| 3.0 | 21.11.2023 | 800001001081 | Print Date 28.11.2023 |

-
- | | | |
|--|---|---|
| Toxicity to fish | : | LC50 (Oncorhynchus mykiss (rainbow trout)): 4,26 mg/l Exposure time: 96 h Method: OECD Test Guideline 203 Remarks: Toxic LL/EL/IL50 > 1 <= 10 mg/l |
| Toxicity to daphnia and other aquatic invertebrates | : | EC50 (Daphnia magna (Water flea)): 2,7 mg/l Exposure time: 48 h Method: Test(s) equivalent or similar to OECD Guideline 202 Remarks: Toxic LL/EL/IL50 > 1 <= 10 mg/l |
| Toxicity to algae/aquatic plants | : | EC50 (Scenedesmus capricornutum (fresh water algae)): 10,7 mg/l Exposure time: 72 h Method: OECD Test Guideline 201 Remarks: Harmful LL/EL/IL50 >10 <= 100 mg/l |
| Toxicity to microorganisms | : | NOEL (Tetrahymena pyriformis): 23,7 mg/l Exposure time: 48 h Method: Based on quantitative structure-activity relationship (QSAR) modelling Remarks: NOEC/NOEL >100 mg/l |
| Toxicity to fish (Chronic toxicity) | : | NOELR: 6,165 mg/l Exposure time: 28 d Species: Oncorhynchus mykiss (rainbow trout) Method: Based on quantitative structure-activity relationship (QSAR) modelling Remarks: NOEC/NOEL > 1.0 - <= 10 mg/l |
| Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) | : | NOELR: 10,76 mg/l Exposure time: 21 d Species: Daphnia magna (Water flea) Method: Based on quantitative structure-activity relationship (QSAR) modelling Remarks: no data available |

12.2 Persistence and degradability

Components:

pentane:

- | | | |
|------------------|---|---|
| Biodegradability | : | Biodegradation: 87 % Exposure time: 28 d Method: Test(s) equivalent or similar to OECD Guideline 301 F Remarks: Readily biodegradable. Oxidises rapidly by photo-chemical reactions in air. |
|------------------|---|---|

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 28.03.2023 |
| 3.0 | 21.11.2023 | 800001001081 | Print Date 28.11.2023 |

12.3 Bioaccumulative potential

Components:

pentane:

Bioaccumulation : Species: Pimephales promelas (fathead minnow)
Bioconcentration factor (BCF): 171
Method: Based on quantitative structure-activity relationship (QSAR) modelling
Remarks: Does not bioaccumulate significantly.

12.4 Mobility in soil

Components:

pentane:

Mobility : Remarks: Floats on water., If the product enters soil, one or more constituents will or may be mobile and may contaminate groundwater.

12.5 Results of PBT and vPvB assessment

Components:

pentane:

Assessment : The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB..

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

Components:

pentane:

Additional ecological information : In view of the high rate of loss from solution, the product is unlikely to pose a significant hazard to aquatic life.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 28.03.2023 |
| 3.0 | 21.11.2023 | 800001001081 | Print Date 28.11.2023 |

SECTION 13: Disposal considerations

13.1 Waste treatment methods

- Product : Recover or recycle if possible.
It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.
Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment.
Do not dispose into the environment, in drains or in water courses.
Do not dispose of tank water bottoms by allowing them to drain into the ground. This will result in soil and groundwater contamination.
Waste arising from a spillage or tank cleaning should be disposed of in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand.
- Waste, spills or used product is dangerous waste.
- Disposal should be in accordance with applicable regional, national, and local laws and regulations.
Local regulations may be more stringent than regional or national requirements and must be complied with.
- MARPOL - see International Convention for the Prevention of Pollution from Ships (MARPOL 73/78) which provides technical aspects at controlling pollutions from ships.
- Contaminated packaging : Drain container thoroughly.
After draining, vent in a safe place away from sparks and fire.
Residues may cause an explosion hazard. Do not puncture, cut or weld uncleaned drums.
Send to drum recoverer or metal reclaimer.
Comply with any local recovery or waste disposal regulations.

SECTION 14: Transport information

14.1 UN number or ID number

- | | |
|------|--------|
| ADN | : 1265 |
| ADR | : 1265 |
| RID | : 1265 |
| IMDG | : 1265 |
| IATA | : 1265 |

14.2 UN proper shipping name

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 28.03.2023 |
| 3.0 | 21.11.2023 | 800001001081 | Print Date 28.11.2023 |

ADN : PENTANES

ADR : PENTANES

RID : PENTANES

IMDG : PENTANES

IATA : PENTANES

14.3 Transport hazard class(es)

ADN : 3

ADR : 3

RID : 3

IMDG : 3

IATA : 3

14.4 Packing group

ADN

Packing group : I
Classification Code : F1
Labels : 3 (N2)
CDNI Inland Water Waste Agreement : NST 8963 Solvent

ADR

Packing group : I
Classification Code : F1
Hazard Identification Number : 33
Labels : 3

RID

Packing group : I
Classification Code : F1
Hazard Identification Number : 33
Labels : 3

IMDG

Packing group : I
Labels : 3

IATA

Packing group : I
Labels : 3

14.5 Environmental hazards

ADN

Environmentally hazardous : yes

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 28.03.2023 |
| 3.0 | 21.11.2023 | 800001001081 | Print Date 28.11.2023 |

Marine pollutant : no

14.6 Special precautions for user

Remarks : Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

14.7 Maritime transport in bulk according to IMO instruments

Pollution category : Y
Ship type : 3
Product name : Pentane (all isomers)

Additional Information : This product may be transported under nitrogen blanketing. Nitrogen is an odourless and invisible gas. Exposure to nitrogen enriched atmospheres displaces available oxygen which may cause asphyxiation or death. Personnel must observe strict safety precautions when involved with a confined space entry.

Transport in bulk according to Annex II of Marpol and the IBC Code

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - List of substances subject to authorisation (Annex XIV) : Product is not subject to Authorisation under REACH.

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. P5a FLAMMABLE LIQUIDS

E2 ENVIRONMENTAL HAZARDS

Other regulations:

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

Product is subject to Major accident risk decision 2015 (BRZO+) based on Seveso III directive (2012/18/EU).

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 28.03.2023 |
| 3.0 | 21.11.2023 | 800001001081 | Print Date 28.11.2023 |

The components of this product are reported in the following inventories:

| | |
|-------|----------|
| AIIC | : Listed |
| DSL | : Listed |
| IECSC | : Listed |
| ENCS | : Listed |
| KECI | : Listed |
| NZIoC | : Listed |
| PICCS | : Listed |
| TSCA | : Listed |
| TCSI | : Listed |

15.2 Chemical safety assessment

A Chemical Safety Assessment has been carried out for this substance.

SECTION 16: Other information

Full text of other abbreviations

| | |
|------------------|--|
| 2006/15/EC | : Europe. Indicative occupational exposure limit values |
| NL WG | : Netherlands. Law on Labour conditions - Occupational Exposure Limits |
| 2006/15/EC / TWA | : Limit Value - eight hours |
| NL WG / TLV-8hr | : Time Weighted Average |

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test popula-

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 28.03.2023 |
| 3.0 | 21.11.2023 | 800001001081 | Print Date 28.11.2023 |

tion; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECL - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Training advice : Provide adequate information, instruction and training for operators.

Other information : For Industry guidance and tools on REACH please visit the CEFIC website at <http://cefic.org/Industry-support>.
The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB.

A vertical bar (|) in the left margin indicates an amendment from the previous version.

This product is classified as H304 (May be fatal if swallowed and enters airways). The risk relates to potential for aspiration. The risk arising from aspiration hazard is solely related to the physico-chemical properties of the substance. The risk can therefore be controlled by implementing risk management measures tailored to this specific hazard and included within Section 8 of the SDS. An exposure scenario is not presented.

This product is classified as R66 / EUH066 (Repeated exposure may cause skin dryness or cracking). The risk relates to the potential for repeated or prolonged dermal contact. The risk arising from contact is solely related to the physico-chemical properties of the substance. The risk can therefore be controlled by implementing risk management measures tailored to this specific hazard and included within Section 8 of the SDS. An exposure scenario is not presented.

Sources of key data used to compile the Safety Data Sheet : The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID data base, EC 1272 regulation, etc).

Classification of the mixture:

Classification procedure:

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

| | | | |
|----------------|------------------------------|-----------------------------|---|
| Version 3.0 | Revision Date: 21.11.2023 | SDS Number: 800001001081 | Date of last issue: 28.03.2023 Print Date 28.11.2023 |
|----------------|------------------------------|-----------------------------|---|

| | | |
|-------------------|------|--|
| Flam. Liq. 1 | H224 | On basis of test data. |
| Asp. Tox. 1 | H304 | Expert judgement and weight of evidence determination. |
| STOT SE 3 | H336 | Expert judgement and weight of evidence determination. |
| Aquatic Chronic 2 | H411 | Expert judgement and weight of evidence determination. |

Identified Uses according to the Use Descriptor System

Uses - Worker

Title : Manufacture of substance- Industrial

Uses - Worker

Title : Distribution of substance- Industrial

Uses - Worker

Title : Formulation & (re)packing of substances and mixtures- Industrial

Uses - Worker

Title : Uses in Coatings- Industrial

Uses - Worker

Title : Use in Cleaning Agents- Industrial

Uses - Worker

Title : Use in Cleaning Agents- Professional

Uses - Worker

Title : Blowing agents- Industrial

Uses - Worker

Title : Functional Fluids- Industrial

Uses - Worker

Title : Functional Fluids- Professional

Uses - Worker

Title : Use in laboratories- Industrial

Uses - Worker

Title : Use in laboratories- Professional

Identified Uses according to the Use Descriptor System

Uses - Consumer

Title : Uses in Coatings
- Consumer

Uses - Consumer

Title : Use in Cleaning Agents
- Consumer

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 28.03.2023 |
| 3.0 | 21.11.2023 | 800001001081 | Print Date 28.11.2023 |

Uses - Consumer

Title : Other Consumer Uses
- Consumer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

NL / EN

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

Version 3.0 Revision Date: 21.11.2023 SDS Number: 800001001081 Date of last issue: 28.03.2023
Print Date 28.11.2023

Exposure Scenario - Worker

| | |
|---|---|
| 300000000640 Manufacture of Substance - Industrial | |
| SECTION 1 | EXPOSURE SCENARIO TITLE |
| Title | Manufacture of substance- Industrial |
| Use Descriptor | Sector of Use: SU3 Process Categories: PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC15 Environmental Release Categories: ERC1, ERC4, ESVOC SpERC 1.1.v1 |
| Scope of process | Manufacture of the substance or use as a process chemical or extraction agent. Includes recycling/ recovery, material transfers, storage, maintenance and loading (including marine vessel/barge, road/rail car and bulk container), sampling and associated laboratory activities. |

ethoxylate :

| | |
|------------------|--|
| SECTION 2 | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES |
|------------------|--|

ethoxylate :

| | |
|--|--|
| Section 2.1 | Control of Worker Exposure |
| Product Characteristics | |
| Physical form of product | Liquid, vapour pressure > 10 kPa at STP |
| Concentration of the Substance in Mixture/Article | Covers percentage substance in the product up to 100%, Unless stated otherwise., |
| Frequency and Duration of Use | |
| Covers daily exposures up to 8 hours (unless stated differently). | |
| Other Operational Conditions affecting Exposure | |
| Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented. | |

ethoxylate :

| | |
|---|--|
| Contributing Scenarios | Risk Management Measures |
| General exposures (closed systems)PROC1PROC2PROC3 | No other specific measures identified. |
| General exposures (open systems)PROC4 | No other specific measures identified. |
| Process samplingPROC8b | No other specific measures identified. |
| Laboratory activitiesPROC15 | No other specific measures identified. |
| Bulk transfers(open sys- | No other specific measures identified. |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

Version 3.0 Revision Date: 21.11.2023 SDS Number: 800001001081 Date of last issue: 28.03.2023
Print Date 28.11.2023

| | |
|--|---|
| tems)PROC8b | |
| Bulk transfers(closed systems)PROC8b | No other specific measures identified. |
| Equipment cleaning and maintenancePROC8a | No other specific measures identified. |
| Storage.PROC1PROC2 | Store substance within a closed system. |

ethoxylate

:

| Section 2.2 | Control of Environmental Exposure |
|---|-----------------------------------|
| Substance is complex UVCB. | |
| Predominantly hydrophobic. | |
| Readily biodegradable. | |
| Amounts Used | |
| Fraction of EU tonnage used in region: | 0,1 |
| Regional use tonnage (tonnes/year): | 2,2E+04 |
| Fraction of Regional tonnage used locally: | 1 |
| Annual site tonnage (tonnes/year): | 2,2E+04 |
| Maximum daily site tonnage (kg/day): | 7,2E+04 |
| Frequency and Duration of Use | |
| Continuous release. | |
| Emission Days (days/year): | 300 |
| Environmental factors not influenced by risk management | |
| Local freshwater dilution factor: | 10 |
| Local marine water dilution factor: | 100 |
| Other Operational Conditions affecting Environmental Exposure | |
| Release fraction to air from process (initial release prior to RMM): | 5,0E-02 |
| Release fraction to wastewater from process (initial release prior to RMM): | 3,0E-03 |
| Release fraction to soil from process (initial release prior to RMM): | 1,0E-04 |
| Technical conditions and measures at process level (source) to prevent release | |
| Common practices vary across sites thus conservative process release estimates used. | |
| Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil | |
| Risk from environmental exposure is driven by freshwater sediment. | |
| Prevent discharge of undissolved substance to or recover from onsite wastewater. | |
| If discharging to domestic sewage treatment plant, no onsite wastewater treatment required. | |
| Treat air emission to provide a typical removal efficiency of (%) | 90 |
| Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%) | 88 |
| If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of (%) | 0 |
| Organisational measures to prevent/limit release from site | |
| Do not apply industrial sludge to natural soils. | |
| Sludge should be incinerated, contained or reclaimed. | |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

Version 3.0 Revision Date: 21.11.2023 SDS Number: 800001001081 Date of last issue: 28.03.2023
Print Date 28.11.2023

| Conditions and Measures related to municipal sewage treatment plant | |
|---|---------|
| Estimated substance removal from wastewater via domestic sewage treatment (%) | 96,9 |
| Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%) | 96,9 |
| Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d) | 2,2E+05 |
| Assumed domestic sewage treatment plant flow (m3/d) | 1,0E+04 |
| Conditions and Measures related to external treatment of waste for disposal | |
| During manufacturing no waste of the substance is generated. | |
| Conditions and measures related to external recovery of waste | |
| During manufacturing no waste of the substance is generated. | |

ethoxylate :

| SECTION 3 | EXPOSURE ESTIMATION |
|-----------|---------------------|
|-----------|---------------------|

ethoxylate :

| Section 3.1 - Health |
|---|
| The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated. |

ethoxylate :

| Section 3.2 -Environment |
|--|
| The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model. |

ethoxylate :

| SECTION 4 | GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO |
|-----------|---|
|-----------|---|

ethoxylate :

| Section 4.1 - Health |
|---|
| Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. |

ethoxylate :

| Section 4.2 -Environment |
|--|
| Guidance is based on assumed operating conditions which may not be applicable to all |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 28.03.2023 |
| 3.0 | 21.11.2023 | 800001001081 | Print Date 28.11.2023 |

| |
|---|
| sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. |
|---|

| |
|---|
| Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. |
|---|

| |
|---|
| Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination. |
|---|

| |
|--|
| Further details on scaling and control technologies are provided in SpERC factsheet (http://cefic.org/en/reach-for-industries-libraries.html). |
|--|

ethoxylate

:

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

Version 3.0 Revision Date: 21.11.2023 SDS Number: 800001001081 Date of last issue: 28.03.2023
Print Date 28.11.2023

Exposure Scenario - Worker

| | |
|--|--|
| 300000000641 Distribution of Substance - Industrial | |
| SECTION 1 | EXPOSURE SCENARIO TITLE |
| Title | Distribution of substance- Industrial |
| Use Descriptor | Sector of Use: SU3 Process Categories: PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC9, PROC15 Environmental Release Categories: ERC1, ERC2, ERC3, ERC4, ERC5, ERC6a, ERC6b, ERC 6C,, ERC7, ESVOC SpERC 1.1b.v1 |
| Scope of process | Loading (including marine vessel/barge, rail/road car and IBC loading) and repacking (including drums and small packs) of substance, including its sampling, storage, unloading distribution and associated laboratory activities. |

ethoxylate :

| | |
|------------------|--|
| SECTION 2 | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES |
|------------------|--|

ethoxylate :

| | |
|--|--|
| Section 2.1 | Control of Worker Exposure |
| Product Characteristics | |
| Physical form of product | Liquid, vapour pressure > 10 kPa at STP |
| Concentration of the Substance in Mixture/Article | Covers percentage substance in the product up to 100%, Unless stated otherwise., |
| Frequency and Duration of Use | |
| Covers daily exposures up to 8 hours (unless stated differently). | |
| Other Operational Conditions affecting Exposure | |
| Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented. | |

ethoxylate :

| | |
|---|--|
| Contributing Scenarios | Risk Management Measures |
| General exposures (closed systems)PROC1PROC2PROC3 | No other specific measures identified. |
| General exposures (open systems)PROC4 | No other specific measures identified. |
| Process samplingPROC3 | No other specific measures identified. |
| Laboratory activitiesPROC15 | No other specific measures identified. |
| Bulk transfers(closed sys- | No other specific measures identified. |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

Version 3.0 Revision Date: 21.11.2023 SDS Number: 800001001081 Date of last issue: 28.03.2023
Print Date 28.11.2023

| | |
|--|---|
| tems)PROC8b | |
| Bulk transfers(open systems)PROC8b | No other specific measures identified. |
| Drum and small package fillingPROC9 | No other specific measures identified. |
| Equipment cleaning and maintenancePROC8a | No other specific measures identified. |
| Storage.PROC1PROC2 | Store substance within a closed system. |

ethoxylate :

| Section 2.2 | Control of Environmental Exposure |
|---|-----------------------------------|
| Substance is complex UVCB. | |
| Predominantly hydrophobic. | |
| Readily biodegradable. | |
| Amounts Used | |
| Fraction of EU tonnage used in region: | 0,1 |
| Regional use tonnage (tonnes/year): | 3,6E+03 |
| Fraction of Regional tonnage used locally: | 2,0E-03 |
| Annual site tonnage (tonnes/year): | 7,2 |
| Maximum daily site tonnage (kg/day): | 360 |
| Frequency and Duration of Use | |
| Continuous release. | |
| Emission Days (days/year): | 20 |
| Environmental factors not influenced by risk management | |
| Local freshwater dilution factor: | 10 |
| Local marine water dilution factor: | 100 |
| Other Operational Conditions affecting Environmental Exposure | |
| Release fraction to air from process (initial release prior to RMM): | 1,0E-03 |
| Release fraction to wastewater from process (initial release prior to RMM): | 1,0E-05 |
| Release fraction to soil from process (initial release prior to RMM): | 1,0E-05 |
| Technical conditions and measures at process level (source) to prevent release | |
| Common practices vary across sites thus conservative process release estimates used. | |
| Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil | |
| Risk from environmental exposure is driven by freshwater sediment. | |
| No wastewater treatment required. | |
| Treat air emission to provide a typical removal efficiency of (%) | 90 |
| Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%) | 0 |
| If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of (%) | 0 |
| Organisational measures to prevent/limit release from site | |
| Do not apply industrial sludge to natural soils. | |
| Sludge should be incinerated, contained or reclaimed. | |
| Conditions and Measures related to municipal sewage treatment plant | |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

Version 3.0 Revision Date: 21.11.2023 SDS Number: 800001001081 Date of last issue: 28.03.2023
Print Date 28.11.2023

| | |
|---|---------|
| Estimated substance removal from wastewater via domestic sewage treatment (%) | 96,0 |
| Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%) | 96,0 |
| Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d) | 2,7E+06 |
| Assumed domestic sewage treatment plant flow (m3/d) | 2,0E+03 |
| Conditions and Measures related to external treatment of waste for disposal | |
| External treatment and disposal of waste should comply with applicable local and/or regional regulations. | |
| Conditions and measures related to external recovery of waste | |
| External recovery and recycling of waste should comply with applicable local and/or regional regulations. | |

ethoxylate :

| | |
|------------------|----------------------------|
| SECTION 3 | EXPOSURE ESTIMATION |
|------------------|----------------------------|

ethoxylate :

Section 3.1 - Health

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

ethoxylate :

Section 3.2 -Environment

The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

ethoxylate :

| | |
|------------------|--|
| SECTION 4 | GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO |
|------------------|--|

ethoxylate :

Section 4.1 - Health

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.
Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

ethoxylate :

Section 4.2 -Environment

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

Version
3.0

Revision Date:
21.11.2023

SDS Number:
800001001081

Date of last issue: 28.03.2023
Print Date 28.11.2023

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

ethoxylate

:

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

Version 3.0 Revision Date: 21.11.2023 SDS Number: 800001001081 Date of last issue: 28.03.2023
Print Date 28.11.2023

Exposure Scenario - Worker

| | |
|---|---|
| 300000000642 Formulation & (Re)packing of Substances and Mixtures - Industrial | |
| SECTION 1 | EXPOSURE SCENARIO TITLE |
| Title | Formulation & (re)packing of substances and mixtures- Industrial |
| Use Descriptor | Sector of Use: SU3 Process Categories: PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9, PROC14, PROC15 Environmental Release Categories: ERC2, ESVOC SpERC 2.2.v1 |
| Scope of process | Formulation, packing and re-packing of the substance and its mixtures in batch or continuous operations, including storage, materials transfers, mixing, tableting, compression, pelletisation, extrusion, large and small scale packing, sampling, maintenance and associated laboratory activities. |

ethoxylate :

| | |
|------------------|--|
| SECTION 2 | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES |
|------------------|--|

ethoxylate :

| | |
|--|--|
| Section 2.1 | Control of Worker Exposure |
| Product Characteristics | |
| Physical form of product | Liquid, vapour pressure > 10 kPa at STP |
| Concentration of the Substance in Mixture/Article | Covers percentage substance in the product up to 100%, Unless stated otherwise., |
| Frequency and Duration of Use | |
| Covers daily exposures up to 8 hours (unless stated differently). | |
| Other Operational Conditions affecting Exposure | |
| Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented. | |

ethoxylate :

| | |
|--|--|
| Contributing Scenarios | Risk Management Measures |
| General exposures (closed systems)PROC1PROC2PROC3 | No other specific measures identified. |
| General exposures (open systems)PROC4 | No other specific measures identified. |
| Batch processes at elevated temperaturesOperation is carried out at elevated temperature | Provide a good standard of controlled ventilation (10 to 15 air changes per hour). |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

Version 3.0 Revision Date: 21.11.2023 SDS Number: 800001001081 Date of last issue: 28.03.2023
Print Date 28.11.2023

| | |
|---|---|
| (> 20°C above ambient temperature).PROC3 | |
| Process samplingPROC3 | No other specific measures identified. |
| Laboratory activitiesPROC15 | No other specific measures identified. |
| Bulk transfersPROC8b | No other specific measures identified. |
| Mixing operations (open systems)PROC5 | No other specific measures identified. |
| ManualTransfer from/pouring from containersNon-dedicated facilityPROC8a | No other specific measures identified. |
| Drum/batch transfersDedicated facilityPROC8b | No other specific measures identified. |
| Production or preparation or articles by tableting, compression, extrusion or pelletisationPROC14 | No other specific measures identified. |
| Drum and small package fillingPROC9 | No other specific measures identified. |
| Equipment cleaning and maintenancePROC8a | No other specific measures identified. |
| Storage.PROC1PROC2 | Store substance within a closed system. |

ethoxylate :

| Section 2.2 | Control of Environmental Exposure |
|---|-----------------------------------|
| Substance is complex UVCB. | |
| Predominantly hydrophobic. | |
| Readily biodegradable. | |
| Amounts Used | |
| Fraction of EU tonnage used in region: | 0,1 |
| Regional use tonnage (tonnes/year): | 3,4E+03 |
| Fraction of Regional tonnage used locally: | 1 |
| Annual site tonnage (tonnes/year): | 3,4E+03 |
| Maximum daily site tonnage (kg/day): | 1,1E+04 |
| Frequency and Duration of Use | |
| Continuous release. | |
| Emission Days (days/year): | 300 |
| Environmental factors not influenced by risk management | |
| Local freshwater dilution factor: | 10 |
| Local marine water dilution factor: | 100 |
| Other Operational Conditions affecting Environmental Exposure | |
| Release fraction to air from process (after typical onsite RMMs consistent with EU Solvent Emissions Directive requirements): | 2,5E-02 |
| Release fraction to wastewater from process (initial release prior to RMM): | 2,0E-03 |
| Release fraction to soil from process (initial release prior to RMM): | 1,0E-04 |
| Technical conditions and measures at process level (source) to prevent release | |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

Version 3.0 Revision Date: 21.11.2023 SDS Number: 800001001081 Date of last issue: 28.03.2023
Print Date 28.11.2023

| | |
|--|---------|
| Common practices vary across sites thus conservative process re-lease estimates used. | |
| Technical onsite conditions and measures to reduce or limit discharges, air emis-sions and releases to soil | |
| Risk from environmental exposure is driven by freshwater sediment. | |
| Prevent discharge of undissolved substance to or recover from onsite wastewater. | |
| If discharging to domestic sewage treatment plant, no onsite wastewater treatment required. | |
| Treat air emission to provide a typical removal efficiency of (%) | 0 |
| Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%) | 77,2 |
| If discharging to domestic sewage treatment plant, provide the re-quired onsite wastewater removal efficiency of (%) | 0 |
| Organisational measures to prevent/limit release from site | |
| Do not apply industrial sludge to natural soils. | |
| Sludge should be incinerated, contained or reclaimed. | |
| Conditions and Measures related to municipal sewage treatment plant | |
| Estimated substance removal from wastewater via domestic sewage treatment (%) | 96,0 |
| Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%) | 96,0 |
| Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d) | 6,5E+04 |
| Assumed domestic sewage treatment plant flow (m3/d) | 2,0E+03 |
| Conditions and Measures related to external treatment of waste for disposal | |
| External treatment and disposal of waste should comply with applicable local and/or regional regulations. | |
| Conditions and measures related to external recovery of waste | |
| External recovery and recycling of waste should comply with applicable local and/or regional regulations. | |

ethoxylate :

| | |
|------------------|----------------------------|
| SECTION 3 | EXPOSURE ESTIMATION |
|------------------|----------------------------|

ethoxylate :

Section 3.1 - Health

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

ethoxylate :

Section 3.2 -Environment

The Hydrocarbon Block Method has been used to calculate environmental exposure with

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

Version 3.0 Revision Date: 21.11.2023 SDS Number: 800001001081 Date of last issue: 28.03.2023
Print Date 28.11.2023

the Petrorisk model.

ethoxylate :

| | |
|------------------|--|
| SECTION 4 | GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO |
|------------------|--|

ethoxylate :

Section 4.1 - Health

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

ethoxylate :

Section 4.2 -Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

ethoxylate :

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

Version 3.0 Revision Date: 21.11.2023 SDS Number: 800001001081 Date of last issue: 28.03.2023
Print Date 28.11.2023

Exposure Scenario - Worker

| | |
|--|--|
| 300000000643 Use in Coatings - Industrial | |
| SECTION 1 | EXPOSURE SCENARIO TITLE |
| Title | Uses in Coatings- Industrial |
| Use Descriptor | Sector of Use: SU3 Process Categories: PROC1, PROC2, PROC3, PROC4, PROC5, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC14, PROC15 Environmental Release Categories: ERC4, ESVOC SpERC 4.3a.v1 |
| Scope of process | Covers the use in coatings (paints, inks, adhesives, etc) including exposures during use (including materials receipt, storage, preparation and transfer from bulk and semi-bulk, application by spray, roller, spreader, dip, flow, fluidised bed on production lines and film formation) and equipment cleaning, maintenance and associated laboratory activities. |

ethoxylate :

| | |
|------------------|--|
| SECTION 2 | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES |
|------------------|--|

ethoxylate :

| | |
|--|--|
| Section 2.1 | Control of Worker Exposure |
| Product Characteristics | |
| Physical form of product | Liquid, vapour pressure > 10 kPa at STP |
| Concentration of the Substance in Mixture/Article | Covers percentage substance in the product up to 100%, Unless stated otherwise., |
| Frequency and Duration of Use | |
| Covers daily exposures up to 8 hours (unless stated differently). | |
| Other Operational Conditions affecting Exposure | |
| Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented. | |

ethoxylate :

| | |
|---|---|
| Contributing Scenarios | Risk Management Measures |
| General exposures (closed systems)PROC1 | No other specific measures identified. |
| General exposures (closed systems)with sample collectionUse in contained systemsPROC2 | No other specific measures identified. |
| Film formation - force dry- | Provide a good standard of controlled ventilation (10 to 15 air |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

Version 3.0 Revision Date: 21.11.2023 SDS Number: 800001001081 Date of last issue: 28.03.2023
Print Date 28.11.2023

| | |
|---|---|
| ing, stoving and other technologies. Operation is carried out at elevated temperature (> 20°C above ambient temperature). PROC2 | changes per hour). |
| Mixing operations (closed systems) Use in contained batch processes PROC3 | No other specific measures identified. |
| Film formation - air drying PROC4 | No other specific measures identified. |
| Preparation of material for application Mixing operations (open systems) PROC5 | No other specific measures identified. |
| Spraying (automatic/robotic) PROC7 | No other specific measures identified. |
| Manual Spraying PROC7 | No other specific measures identified. |
| Material transfers PROC8a PROC8b | No other specific measures identified. |
| Roller, spreader, flow application PROC10 | No other specific measures identified. |
| Dipping, immersion and pouring PROC13 | No other specific measures identified. |
| Laboratory activities PROC15 | No other specific measures identified. |
| Material transfers Drum/batch transfers Transfer from/pouring from containers PROC9 | No other specific measures identified. |
| Production or preparation or articles by tableting, compression, extrusion or pelletisation PROC14 | No specific measures identified. |
| Equipment cleaning and maintenance PROC8a | No other specific measures identified. |
| Storage. PROC1 | Store substance within a closed system. |

ethoxylate

:

| Section 2.2 | Control of Environmental Exposure |
|--|-----------------------------------|
| Substance is complex UVCB. | |
| Predominantly hydrophobic. | |
| Readily biodegradable. | |
| Amounts Used | |
| Fraction of EU tonnage used in region: | 0,1 |
| Regional use tonnage (tonnes/year): | 2,1 |
| Fraction of Regional tonnage used locally: | 1 |
| Annual site tonnage (tonnes/year): | 2,1 |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

Version 3.0 Revision Date: 21.11.2023 SDS Number: 800001001081 Date of last issue: 28.03.2023
Print Date 28.11.2023

| | |
|---|---------|
| Maximum daily site tonnage (kg/day): | 110 |
| Frequency and Duration of Use | |
| Continuous release. | |
| Emission Days (days/year): | 20 |
| Environmental factors not influenced by risk management | |
| Local freshwater dilution factor: | 10 |
| Local marine water dilution factor: | 100 |
| Other Operational Conditions affecting Environmental Exposure | |
| Release fraction to air from process (initial release prior to RMM): | 9,8E-01 |
| Release fraction to wastewater from process (initial release prior to RMM): | 7,0E-03 |
| Release fraction to soil from process (initial release prior to RMM): | 0 |
| Technical conditions and measures at process level (source) to prevent release | |
| Common practices vary across sites thus conservative process re-release estimates used. | |
| Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil | |
| Risk from environmental exposure is driven by freshwater sediment. | |
| Prevent discharge of undissolved substance to or recover from onsite wastewater. | |
| No wastewater treatment required. | |
| Treat air emission to provide a typical removal efficiency of (%) | 90 |
| Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%) | 0 |
| If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of (%) | 0 |
| Organisational measures to prevent/limit release from site | |
| Do not apply industrial sludge to natural soils. | |
| Sludge should be incinerated, contained or reclaimed. | |
| Conditions and Measures related to municipal sewage treatment plant | |
| Estimated substance removal from wastewater via domestic sewage treatment (%) | 96,0 |
| Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%) | 96,0 |
| Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d) | 1,9E+04 |
| Assumed domestic sewage treatment plant flow (m3/d) | 2,0E+03 |
| Conditions and Measures related to external treatment of waste for disposal | |
| External treatment and disposal of waste should comply with applicable local and/or regional regulations. | |
| Conditions and measures related to external recovery of waste | |
| External recovery and recycling of waste should comply with applicable local and/or regional regulations. | |

ethoxylate :

SECTION 3

EXPOSURE ESTIMATION

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

Version 3.0 Revision Date: 21.11.2023 SDS Number: 800001001081 Date of last issue: 28.03.2023
Print Date 28.11.2023

ethoxylate :

Section 3.1 - Health

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

ethoxylate :

Section 3.2 -Environment

The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

ethoxylate :

SECTION 4

GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO

ethoxylate :

Section 4.1 - Health

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

ethoxylate :

Section 4.2 -Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

ethoxylate :

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

Version 3.0 Revision Date: 21.11.2023 SDS Number: 800001001081 Date of last issue: 28.03.2023
Print Date 28.11.2023

Exposure Scenario - Worker

| | |
|---|---|
| 300000000644 Use in Cleaning Agents - Industrial | |
| SECTION 1 | EXPOSURE SCENARIO TITLE |
| Title | Use in Cleaning Agents- Industrial |
| Use Descriptor | Sector of Use: SU3 Process Categories: PROC1, PROC2, PROC3, PROC4, PROC7, PROC8a, PROC8b, PROC10, PROC13 Environmental Release Categories: ERC4, ESVOC SpERC 4.4a.v1 |
| Scope of process | Covers the use as a component of cleaning products including transfer from storage, pouring/unloading from drums or containers. Exposures during mixing/diluting in the preparatory phase and cleaning activities (including spraying, brushing, dipping, wiping, automated and by hand), related equipment cleaning and maintenance. |

ethoxylate :

| | |
|------------------|--|
| SECTION 2 | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES |
|------------------|--|

ethoxylate :

| | |
|--|--|
| Section 2.1 | Control of Worker Exposure |
| Product Characteristics | |
| Physical form of product | Liquid, vapour pressure > 10 kPa at STP |
| Concentration of the Substance in Mixture/Article | Covers percentage substance in the product up to 100%, Unless stated otherwise., |
| Frequency and Duration of Use | |
| Covers daily exposures up to 8 hours (unless stated differently). | |
| Other Operational Conditions affecting Exposure | |
| Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented. | |

ethoxylate :

| | |
|--|--|
| Contributing Scenarios | Risk Management Measures |
| Bulk transfersPROC8a | No other specific measures identified. |
| Automated process with (semi) closed systems.Use in contained systemsPROC2 | No other specific measures identified. |
| Automated process with (semi) closed systems.Drum/batch transfersPROC3 | No other specific measures identified. |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

Version 3.0 Revision Date: 21.11.2023 SDS Number: 800001001081 Date of last issue: 28.03.2023
Print Date 28.11.2023

| | |
|---|---|
| Application of cleaning products in closed systemsPROC2 | No other specific measures identified. |
| Filling/ preparation of equipment from drums or containers.PROC8b | No other specific measures identified. |
| Use in contained batch processesPROC4 | No other specific measures identified. |
| Degreasing small objects in cleaning stationPROC13 | No other specific measures identified. |
| Cleaning with low-pressure washersPROC10 | No other specific measures identified. |
| Cleaning with high pressure washersPROC7 | No other specific measures identified. |
| ManualSurfacesCleaningPROC10 | No other specific measures identified. |
| Storage. | Store substance within a closed system. |

ethoxylate

:

| Section 2.2 | Control of Environmental Exposure |
|---|-----------------------------------|
| Substance is complex UVCB. | |
| Predominantly hydrophobic. | |
| Readily biodegradable. | |
| Amounts Used | |
| Fraction of EU tonnage used in region: | 0,1 |
| Regional use tonnage (tonnes/year): | 7,5 |
| Fraction of Regional tonnage used locally: | 1 |
| Annual site tonnage (tonnes/year): | 7,5 |
| Maximum daily site tonnage (kg/day): | 380 |
| Frequency and Duration of Use | |
| Continuous release. | |
| Emission Days (days/year): | 20 |
| Environmental factors not influenced by risk management | |
| Local freshwater dilution factor: | 10 |
| Local marine water dilution factor: | 100 |
| Other Operational Conditions affecting Environmental Exposure | |
| Release fraction to air from process (initial release prior to RMM): | 1 |
| Release fraction to wastewater from process (initial release prior to RMM): | 3,0E-05 |
| Release fraction to soil from process (initial release prior to RMM): | 0 |
| Technical conditions and measures at process level (source) to prevent release | |
| Common practices vary across sites thus conservative process release estimates used. | |
| Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil | |
| Risk from environmental exposure is driven by freshwater. | |
| Prevent discharge of undissolved substance to or recover from onsite wastewater. | |
| No wastewater treatment required. | |
| Treat air emission to provide a typical removal efficiency of (%) | 70 |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

Version 3.0 Revision Date: 21.11.2023 SDS Number: 800001001081 Date of last issue: 28.03.2023
Print Date 28.11.2023

| | |
|---|---------|
| Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of \geq (%) | 0 |
| If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of (%) | 0 |
| Organisational measures to prevent/limit release from site | |
| Do not apply industrial sludge to natural soils. | |
| Sludge should be incinerated, contained or reclaimed. | |
| Conditions and Measures related to municipal sewage treatment plant | |
| Estimated substance removal from wastewater via domestic sewage treatment (%) | 96,0 |
| Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%) | 96,0 |
| Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d) | 4,3E+06 |
| Assumed domestic sewage treatment plant flow (m3/d) | 2,0E+03 |
| Conditions and Measures related to external treatment of waste for disposal | |
| External treatment and disposal of waste should comply with applicable local and/or regional regulations. | |
| Conditions and measures related to external recovery of waste | |
| External recovery and recycling of waste should comply with applicable local and/or regional regulations. | |

ethoxylate :

| | |
|------------------|----------------------------|
| SECTION 3 | EXPOSURE ESTIMATION |
|------------------|----------------------------|

ethoxylate :

Section 3.1 - Health

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

ethoxylate :

Section 3.2 -Environment

The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

ethoxylate :

| | |
|------------------|--|
| SECTION 4 | GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO |
|------------------|--|

ethoxylate :

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 28.03.2023 |
| 3.0 | 21.11.2023 | 800001001081 | Print Date 28.11.2023 |

Section 4.1 - Health

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.
Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

ethoxylate :

Section 4.2 -Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

ethoxylate :

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

Version 3.0 Revision Date: 21.11.2023 SDS Number: 800001001081 Date of last issue: 28.03.2023
Print Date 28.11.2023

Exposure Scenario - Worker

| | |
|---|---|
| 300000000661 Use in Cleaning Agents - Professional | |
| SECTION 1 | EXPOSURE SCENARIO TITLE |
| Title | Use in Cleaning Agents- Professional |
| Use Descriptor | Sector of Use: SU22 Process Categories: PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC10, PROC11, PROC13 Environmental Release Categories: ERC8a, ERC8d, ESVOC SpERC 8.4b.v1 |
| Scope of process | Covers the use as a component of cleaning products including pouring/unloading from drums or containers; and exposures during mixing/diluting in the preparatory phase and cleaning activities (including spraying, brushing, dipping, wiping automated and by hand). |

ethoxylate :

| | |
|------------------|--|
| SECTION 2 | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES |
|------------------|--|

ethoxylate :

| | |
|--|--|
| Section 2.1 | Control of Worker Exposure |
| Product Characteristics | |
| Physical form of product | Liquid, vapour pressure > 10 kPa at STP |
| Concentration of the Substance in Mixture/Article | Covers percentage substance in the product up to 100%, Unless stated otherwise., |
| Frequency and Duration of Use | |
| Covers daily exposures up to 8 hours (unless stated differently). | |
| Other Operational Conditions affecting Exposure | |
| Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented. | |

ethoxylate :

| | |
|--|--|
| Contributing Scenarios | Risk Management Measures |
| Filling/ preparation of equipment from drums or containers.Dedicated facilityPROC8b | No other specific measures identified. |
| Automated process with (semi) closed systems.Use in contained systemsPROC2 | No other specific measures identified. |
| Automated process with (semi) closed systems.Drum/batch transfersUse in contained systemsPROC3 | No other specific measures identified. |
| Semi Automated process. (e.g.: Semi au- | No other specific measures identified. |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

Version 3.0 Revision Date: 21.11.2023 SDS Number: 800001001081 Date of last issue: 28.03.2023
Print Date 28.11.2023

| | |
|---|---|
| automatic application of floor care and maintenance products)PROC4 | |
| Filling/ preparation of equipment from drums or containers.Non-dedicated facilityPROC8a | No other specific measures identified. |
| ManualSurfacesCleaningDipping, immersion and pouringPROC13 | No other specific measures identified. |
| Cleaning with low-pressure washers-Rolling, Brushingno sprayingPROC10 | No other specific measures identified. |
| Cleaning with high pressure washers-SprayingIndoorPROC11 | No other specific measures identified. |
| Cleaning with high pressure washers-SprayingOutdoorPROC11 | No other specific measures identified. |
| ManualSurfacesCleaningSprayingPROC10 | No other specific measures identified. |
| Ad hoc manual application via trigger sprays, dipping, etc.Rolling, BrushingPROC10 | No other specific measures identified. |
| Cleaning of medical devicesPROC4 | No other specific measures identified. |
| Storage. | Store substance within a closed system. |

ethoxylate

:

| Section 2.2 | Control of Environmental Exposure |
|---|-----------------------------------|
| Substance is complex UVCB. | |
| Predominantly hydrophobic. | |
| Readily biodegradable. | |
| Amounts Used | |
| Fraction of EU tonnage used in region: | 0,1 |
| Regional use tonnage (tonnes/year): | 7,5 |
| Fraction of Regional tonnage used locally: | 5,0E-04 |
| Annual site tonnage (tonnes/year): | 3,8E-03 |
| Maximum daily site tonnage (kg/day): | 1,0E-02 |
| Frequency and Duration of Use | |
| Continuous release. | |
| Emission Days (days/year): | 365 |
| Environmental factors not influenced by risk management | |
| Local freshwater dilution factor: | 10 |
| Local marine water dilution factor: | 100 |
| Other Operational Conditions affecting Environmental Exposure | |
| Release fraction to air from wide dispersive use (regional only): | 2,0E-02 |
| Release fraction to wastewater from wide dispersive use: | 1,0E-06 |
| Release fraction to soil from wide dispersive use (regional only): | 0 |
| Technical conditions and measures at process level (source) to prevent release | |
| Common practices vary across sites thus conservative process release estimates used. | |
| Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil | |
| Risk from environmental exposure is driven by freshwater. | |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

Version 3.0 Revision Date: 21.11.2023 SDS Number: 800001001081 Date of last issue: 28.03.2023
Print Date 28.11.2023

| | |
|---|---------|
| No wastewater treatment required. | |
| Treat air emission to provide a typical removal efficiency of (%) | |
| Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of \geq (%) | 0 |
| If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of (%) | 0 |
| Organisational measures to prevent/limit release from site | |
| Do not apply industrial sludge to natural soils. | |
| Sludge should be incinerated, contained or reclaimed. | |
| Conditions and Measures related to municipal sewage treatment plant | |
| Estimated substance removal from wastewater via domestic sewage treatment (%) | 96,0 |
| Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%) | 96,0 |
| Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d) | 1,9E+02 |
| Assumed domestic sewage treatment plant flow (m3/d) | 2,0E+03 |
| Conditions and Measures related to external treatment of waste for disposal | |
| External treatment and disposal of waste should comply with applicable local and/or regional regulations. | |
| Conditions and measures related to external recovery of waste | |
| External recovery and recycling of waste should comply with applicable local and/or regional regulations. | |

ethoxylate :

| | |
|------------------|----------------------------|
| SECTION 3 | EXPOSURE ESTIMATION |
|------------------|----------------------------|

ethoxylate :

| |
|---|
| Section 3.1 - Health |
| The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated. |

ethoxylate :

| |
|--|
| Section 3.2 -Environment |
| The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model. |

ethoxylate :

| | |
|------------------|--|
| SECTION 4 | GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO |
|------------------|--|

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 28.03.2023 |
| 3.0 | 21.11.2023 | 800001001081 | Print Date 28.11.2023 |

ethoxylate :

Section 4.1 - Health

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

ethoxylate :

Section 4.2 -Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

ethoxylate :

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

Version 3.0 Revision Date: 21.11.2023 SDS Number: 800001001081 Date of last issue: 28.03.2023
Print Date 28.11.2023

Exposure Scenario - Worker

| | |
|---|---|
| 300000000666 Use as a Blowing Agent - Industrial | |
| SECTION 1 | EXPOSURE SCENARIO TITLE |
| Title | Blowing agents- Industrial |
| Use Descriptor | Sector of Use: SU3 Process Categories: PROC1, PROC2, PROC3, PROC8b, PROC9, PROC12 Environmental Release Categories: ERC4, ESVOC SpERC 4.9.v1 |
| Scope of process | Use as a blowing agent for rigid and flexible foams, including material transfers, mixing and injection, curing, cutting, storage and packing. |

ethoxylate :

| | |
|------------------|--|
| SECTION 2 | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES |
|------------------|--|

ethoxylate :

| | |
|--|---|
| Section 2.1 | Control of Worker Exposure |
| Product Characteristics | |
| Physical form of product | Liquid, vapour pressure > 10 kPa at STP |
| Concentration of the Substance in Mixture/Article | Covers percentage substance in the product up to 100%., Unless stated otherwise., |
| Frequency and Duration of Use | |
| Covers daily exposures up to 8 hours (unless stated differently). | |
| Other Operational Conditions affecting Exposure | |
| Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented. | |

ethoxylate :

| | |
|--|--|
| Contributing Scenarios | Risk Management Measures |
| Bulk transfersDedicated facilityPROC8b | No other specific measures identified. |
| Mixing operations (closed systems)PROC1 | No other specific measures identified. |
| Extrusion and expansion of polymer massPROC12 | No other specific measures identified. |
| Cutting and shavingPROC12 | No other specific measures identified. |
| Collection and re-processing of shavings, cuttings, etc.PROC12 | No other specific measures identified. |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

Version 3.0 Revision Date: 21.11.2023 SDS Number: 800001001081 Date of last issue: 28.03.2023
Print Date 28.11.2023

| | |
|---|--|
| Product packagingPROC12 | No other specific measures identified. |
| Storage.PROC2 | No other specific measures identified. |
| Mixing operations (closed systems)Operation is carried out at elevated temperature (> 20°C above ambient temperature).PROC3 | Provide a good standard of controlled ventilation (10 to 15 air changes per hour). |
| Intermediate polymer storageOperation is carried out at elevated temperature (> 20°C above ambient temperature).PROC3 | Provide a good standard of controlled ventilation (10 to 15 air changes per hour). |
| Centrifuging including dischargingOperation is carried out at elevated temperature (> 20°C above ambient temperature).PROC3 | Provide a good standard of controlled ventilation (10 to 15 air changes per hour). |
| Drying and storagePROC12 | No other specific measures identified. |
| Semi-bulk packagingPROC8b | No other specific measures identified. |
| Treatment by heatingOperation is carried out at elevated temperature (> 20°C above ambient temperature).PROC12 | Provide a good standard of controlled ventilation (10 to 15 air changes per hour). |
| Article formation in mouldOperation is carried out at elevated temperature (> 20°C above ambient temperature).PROC12 | Provide a good standard of controlled ventilation (10 to 15 air changes per hour). |
| Cutting by heated wire-ManualPROC12 | No other specific measures identified. |
| Mixing operations (closed systems)PROC3 | No other specific measures identified. |
| Drum and small package fillingFilling/ preparation of equipment from drums or containers.PROC9 | No other specific measures identified. |
| FoamingPROC12 | No other specific measures identified. |
| CompressionPROC12 | No other specific measures identified. |

ethoxylate

:

| | |
|----------------------------|--|
| Section 2.2 | Control of Environmental Exposure |
| Substance is complex UVCB. | |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

Version 3.0 Revision Date: 21.11.2023 SDS Number: 800001001081 Date of last issue: 28.03.2023
Print Date 28.11.2023

| | |
|---|---------|
| Predominantly hydrophobic. | |
| Readily biodegradable. | |
| Amounts Used | |
| Fraction of EU tonnage used in region: | 0,1 |
| Regional use tonnage (tonnes/year): | 1,5E+03 |
| Fraction of Regional tonnage used locally: | 1 |
| Annual site tonnage (tonnes/year): | 1,5E+03 |
| Maximum daily site tonnage (kg/day): | 1,5E+04 |
| Frequency and Duration of Use | |
| Continuous release. | |
| Emission Days (days/year): | 100 |
| Environmental factors not influenced by risk management | |
| Local freshwater dilution factor: | 10 |
| Local marine water dilution factor: | 100 |
| Other Operational Conditions affecting Environmental Exposure | |
| Release fraction to air from process (initial release prior to RMM): | 1 |
| Release fraction to wastewater from process (initial release prior to RMM): | 3,0E-04 |
| Release fraction to soil from process (initial release prior to RMM): | 0 |
| Technical conditions and measures at process level (source) to prevent release | |
| Common practices vary across sites thus conservative process re-lease estimates used. | |
| Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil | |
| Risk from environmental exposure is driven by soil. | |
| Prevent discharge of undissolved substance to or recover from onsite wastewater. | |
| No wastewater treatment required. | |
| Treat air emission to provide a typical removal efficiency of (%) | 0 |
| Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%) | 0 |
| If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of (%) | 0 |
| Organisational measures to prevent/limit release from site | |
| Do not apply industrial sludge to natural soils. | |
| Sludge should be incinerated, contained or reclaimed. | |
| Conditions and Measures related to municipal sewage treatment plant | |
| Estimated substance removal from wastewater via domestic sewage treatment (%) | 96 |
| Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%) | 96 |
| Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d) | 4,3E+05 |
| Assumed domestic sewage treatment plant flow (m3/d) | 2,0E+03 |
| Conditions and Measures related to external treatment of waste for disposal | |
| External treatment and disposal of waste should comply with applicable local and/or regional regulations. | |
| Conditions and measures related to external recovery of waste | |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

Version 3.0 Revision Date: 21.11.2023 SDS Number: 800001001081 Date of last issue: 28.03.2023
Print Date 28.11.2023

External recovery and recycling of waste should comply with applicable local and/or regional regulations.

ethoxylate :

| | |
|------------------|----------------------------|
| SECTION 3 | EXPOSURE ESTIMATION |
|------------------|----------------------------|

ethoxylate :

| |
|-----------------------------|
| Section 3.1 - Health |
|-----------------------------|

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

ethoxylate :

| |
|---------------------------------|
| Section 3.2 -Environment |
|---------------------------------|

The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

ethoxylate :

| | |
|------------------|--|
| SECTION 4 | GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO |
|------------------|--|

ethoxylate :

| |
|-----------------------------|
| Section 4.1 - Health |
|-----------------------------|

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.
Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

ethoxylate :

| |
|---------------------------------|
| Section 4.2 -Environment |
|---------------------------------|

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

ethoxylate :

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

Version 3.0 Revision Date: 21.11.2023 SDS Number: 800001001081 Date of last issue: 28.03.2023
Print Date 28.11.2023

Exposure Scenario - Worker

| | |
|---|---|
| 300000000667 Use as Functional Fluids - Industrial | |
| SECTION 1 | EXPOSURE SCENARIO TITLE |
| Title | Functional Fluids- Industrial |
| Use Descriptor | Sector of Use: SU3 Process Categories: PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC9 Environmental Release Categories: ERC7, ESVOC SpERC 7.13a.v1 |
| Scope of process | Use as functional fluids e.g. cable oils, transfer oils, coolants, insulators, refrigerants, hydraulic fluids in industrial equipment including maintenance and related material transfers. |

ethoxylate :

| | |
|------------------|--|
| SECTION 2 | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES |
|------------------|--|

ethoxylate :

| | |
|--|---|
| Section 2.1 | Control of Worker Exposure |
| Product Characteristics | |
| Physical form of product | Liquid, vapour pressure > 10 kPa at STP |
| Concentration of the Substance in Mixture/Article | Covers percentage substance in the product up to 100%., Unless stated otherwise., |
| Frequency and Duration of Use | |
| Covers daily exposures up to 8 hours (unless stated differently). | |
| Other Operational Conditions affecting Exposure | |
| Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented. | |

ethoxylate :

| | |
|---|--|
| Contributing Scenarios | Risk Management Measures |
| Bulk transfers(closed systems)PROC1PROC2 | No other specific measures identified. |
| Drum/batch transfersDedicated facilityPROC8b | No other specific measures identified. |
| Filling of articles/equipment(closed systems)PROC9 | No other specific measures identified. |
| Filling/ preparation of equipment from drums or containers.Non-dedicated facilityPROC8a | No other specific measures identified. |
| General exposures (closed | No other specific measures identified. |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

Version 3.0 Revision Date: 21.11.2023 SDS Number: 800001001081 Date of last issue: 28.03.2023
Print Date 28.11.2023

| | |
|--|--|
| systems)PROC1PROC2PROC3 | |
| General exposures (open systems)PROC4 | No other specific measures identified. |
| General exposures (open systems)elevated temperature-PROC4 | Provide a good standard of controlled ventilation (10 to 15 air changes per hour). |
| Remanufacture of reject articlesPROC9 | No other specific measures identified. |
| Equipment maintenance-PROC8a | No other specific measures identified. |
| Storage.PROC1PROC2 | Store substance within a closed system. |

ethoxylate

:

| | |
|---|--|
| Section 2.2 | Control of Environmental Exposure |
| Substance is complex UVCB. | |
| Predominantly hydrophobic. | |
| Readily biodegradable. | |
| Amounts Used | |
| Fraction of EU tonnage used in region: | 0,1 |
| Regional use tonnage (tonnes/year): | 1,6E+02 |
| Fraction of Regional tonnage used locally: | 6,3E-02 |
| Annual site tonnage (tonnes/year): | 10 |
| Maximum daily site tonnage (kg/day): | 5,0E+02 |
| Frequency and Duration of Use | |
| Continuous release. | |
| Emission Days (days/year): | 20 |
| Environmental factors not influenced by risk management | |
| Local freshwater dilution factor: | 10 |
| Local marine water dilution factor: | 100 |
| Other Operational Conditions affecting Environmental Exposure | |
| Release fraction to air from process (initial release prior to RMM): | 1,0E-02 |
| Release fraction to wastewater from process (initial release prior to RMM): | 3,0E-04 |
| Release fraction to soil from process (initial release prior to RMM): | 1,0E-03 |
| Technical conditions and measures at process level (source) to prevent release | |
| Common practices vary across sites thus conservative process release estimates used. | |
| Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil | |
| Risk from environmental exposure is driven by freshwater sediment. | |
| Prevent discharge of undissolved substance to or recover from onsite wastewater. | |
| No wastewater treatment required. | |
| Treat air emission to provide a typical removal efficiency of (%) | 0 |
| Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%) | 0 |
| If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of (%) | 0 |
| Organisational measures to prevent/limit release from site | |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

Version 3.0 Revision Date: 21.11.2023 SDS Number: 800001001081 Date of last issue: 28.03.2023
Print Date 28.11.2023

| | |
|---|---------|
| Do not apply industrial sludge to natural soils. | |
| Sludge should be incinerated, contained or reclaimed. | |
| Conditions and Measures related to municipal sewage treatment plant | |
| Estimated substance removal from wastewater via domestic sewage treatment (%) | 96 |
| Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%) | 96 |
| Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d) | 4,3E+05 |
| Assumed domestic sewage treatment plant flow (m3/d) | 2,0E+03 |
| Conditions and Measures related to external treatment of waste for disposal | |
| External treatment and disposal of waste should comply with applicable local and/or regional regulations. | |
| Conditions and measures related to external recovery of waste | |
| External recovery and recycling of waste should comply with applicable local and/or regional regulations. | |

ethoxylate :

| | |
|------------------|----------------------------|
| SECTION 3 | EXPOSURE ESTIMATION |
|------------------|----------------------------|

ethoxylate :

| |
|---|
| Section 3.1 - Health |
| The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated. |

ethoxylate :

| |
|--|
| Section 3.2 -Environment |
| The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model. |

ethoxylate :

| | |
|------------------|--|
| SECTION 4 | GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO |
|------------------|--|

ethoxylate :

| |
|---|
| Section 4.1 - Health |
| Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

Version
3.0

Revision Date:
21.11.2023

SDS Number:
800001001081

Date of last issue: 28.03.2023
Print Date 28.11.2023

ethoxylate

:

Section 4.2 -Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

ethoxylate

:

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

Version 3.0 Revision Date: 21.11.2023 SDS Number: 800001001081 Date of last issue: 28.03.2023
Print Date 28.11.2023

Exposure Scenario - Worker

| | |
|---|---|
| 300000000668 Use as Functional Fluids - Professional | |
| SECTION 1 | EXPOSURE SCENARIO TITLE |
| Title | Functional Fluids- Professional |
| Use Descriptor | Sector of Use: SU22 Process Categories: PROC1, PROC2, PROC3, PROC8a, PROC9, PROC20 Environmental Release Categories: ERC9a, ERC9b, ESVOC SpERC 9.13b.v1 |
| Scope of process | Use as functional fluids e.g. cable oils, transfer oils, coolants, insulators, refrigerants, hydraulic fluids in professional equipment including maintenance and related material transfers. |

ethoxylate :

| | |
|------------------|--|
| SECTION 2 | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES |
|------------------|--|

ethoxylate :

| | |
|--|---|
| Section 2.1 | Control of Worker Exposure |
| Product Characteristics | |
| Physical form of product | Liquid, vapour pressure > 10 kPa at STP |
| Concentration of the Substance in Mixture/Article | Covers percentage substance in the product up to 100%., Unless stated otherwise., |
| Frequency and Duration of Use | |
| Covers daily exposures up to 8 hours (unless stated differently). | |
| Other Operational Conditions affecting Exposure | |
| Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented. | |

ethoxylate :

| | |
|--|--|
| Contributing Scenarios | Risk Management Measures |
| Drum/batch transfersNon-dedicated facilityPROC8a | No other specific measures identified. |
| Transfer from/pouring from containersDedicated facilityPROC9 | No other specific measures identified. |
| Filling/ preparation of equipment from drums or containers.Dedicated facilityPROC9 | No other specific measures identified. |
| General exposures (closed systems)PROC1PROC2PROC3 | No other specific measures identified. |
| Operation of equipment containing engine oils and simi- | No other specific measures identified. |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

Version 3.0 Revision Date: 21.11.2023 SDS Number: 800001001081 Date of last issue: 28.03.2023
Print Date 28.11.2023

| | |
|---|--|
| lar.PROC20 | |
| Operation of equipment containing engine oils and similar.elevated temperature-PROC20 | Provide a good standard of controlled ventilation (10 to 15 air changes per hour). |
| Remanufacture of reject articlesPROC9 | No other specific measures identified. |
| Equipment maintenance-PROC8a | No other specific measures identified. |
| Storage.PROC1PROC2 | Store substance within a closed system. |

ethoxylate

:

| Section 2.2 | Control of Environmental Exposure |
|---|-----------------------------------|
| Substance is complex UVCB. | |
| Predominantly hydrophobic. | |
| Readily biodegradable. | |
| Amounts Used | |
| Fraction of EU tonnage used in region: | 0,1 |
| Regional use tonnage (tonnes/year): | 50 |
| Fraction of Regional tonnage used locally: | 5,0E-04 |
| Annual site tonnage (tonnes/year): | 2,5E-02 |
| Maximum daily site tonnage (kg/day): | 6,8E-02 |
| Frequency and Duration of Use | |
| Continuous release. | |
| Emission Days (days/year): | 365 |
| Environmental factors not influenced by risk management | |
| Local freshwater dilution factor: | 10 |
| Local marine water dilution factor: | 100 |
| Other Operational Conditions affecting Environmental Exposure | |
| Release fraction to air from wide dispersive use (regional only): | 5,0E-02 |
| Release fraction to wastewater from wide dispersive use: | 2,5E-02 |
| Release fraction to soil from wide dispersive use (regional only): | 2,5E-02 |
| Technical conditions and measures at process level (source) to prevent release | |
| Common practices vary across sites thus conservative process release estimates used. | |
| Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil | |
| Risk from environmental exposure is driven by freshwater. | |
| No wastewater treatment required. | |
| Treat air emission to provide a typical removal efficiency of (%) | |
| Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%) | 0 |
| If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of (%) | 0 |
| Organisational measures to prevent/limit release from site | |
| Do not apply industrial sludge to natural soils. | |
| Sludge should be incinerated, contained or reclaimed. | |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

Version 3.0 Revision Date: 21.11.2023 SDS Number: 800001001081 Date of last issue: 28.03.2023
Print Date 28.11.2023

| Conditions and Measures related to municipal sewage treatment plant | |
|---|---------|
| Estimated substance removal from wastewater via domestic sewage treatment (%) | 96 |
| Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%) | 96 |
| Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d) | 1,0E+03 |
| Assumed domestic sewage treatment plant flow (m3/d) | 2,0E+03 |
| Conditions and Measures related to external treatment of waste for disposal | |
| External treatment and disposal of waste should comply with applicable local and/or regional regulations. | |
| Conditions and measures related to external recovery of waste | |
| External recovery and recycling of waste should comply with applicable local and/or regional regulations. | |

ethoxylate :

| | |
|------------------|----------------------------|
| SECTION 3 | EXPOSURE ESTIMATION |
|------------------|----------------------------|

ethoxylate :

| Section 3.1 - Health |
|---|
| The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated. |

ethoxylate :

| Section 3.2 -Environment |
|--|
| The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model. |

ethoxylate :

| | |
|------------------|--|
| SECTION 4 | GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO |
|------------------|--|

ethoxylate :

| Section 4.1 - Health |
|---|
| Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. |

ethoxylate :

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 28.03.2023 |
| 3.0 | 21.11.2023 | 800001001081 | Print Date 28.11.2023 |

Section 4.2 -Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

ethoxylate

:

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

Version 3.0 Revision Date: 21.11.2023 SDS Number: 800001001081 Date of last issue: 28.03.2023
Print Date 28.11.2023

Exposure Scenario - Worker

| | |
|--|---|
| 300000000669 Use in Laboratories - Industrial | |
| SECTION 1 | EXPOSURE SCENARIO TITLE |
| Title | Use in laboratories- Industrial |
| Use Descriptor | Sector of Use: SU3 Process Categories: PROC10, PROC15 Environmental Release Categories: ERC2, ERC4 |
| Scope of process | Use of the substance within laboratory settings, including material transfers and equipment cleaning. |

ethoxylate :

| | |
|------------------|--|
| SECTION 2 | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES |
|------------------|--|

ethoxylate :

| | |
|--|--|
| Section 2.1 | Control of Worker Exposure |
| Product Characteristics | |
| Physical form of product | Liquid, vapour pressure > 10 kPa at STP |
| Concentration of the Substance in Mixture/Article | Covers percentage substance in the product up to 100%, Unless stated otherwise., |
| Frequency and Duration of Use | |
| Covers daily exposures up to 8 hours (unless stated differently). | |
| Other Operational Conditions affecting Exposure | |
| Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented. | |

ethoxylate :

| | |
|-------------------------------|--|
| Contributing Scenarios | Risk Management Measures |
| Laboratory activitiesPROC15 | No other specific measures identified. |
| CleaningPROC10 | No other specific measures identified. |

ethoxylate :

| | |
|--|--|
| Section 2.2 | Control of Environmental Exposure |
| Substance is complex UVCB. | |
| Predominantly hydrophobic. | |
| Readily biodegradable. | |
| Amounts Used | |
| Fraction of EU tonnage used in region: | 0,1 |
| Regional use tonnage (tonnes/year): | 5 |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

Version 3.0 Revision Date: 21.11.2023 SDS Number: 800001001081 Date of last issue: 28.03.2023
Print Date 28.11.2023

| | |
|---|---------|
| Fraction of Regional tonnage used locally: | 0,4 |
| Annual site tonnage (tonnes/year): | 2 |
| Maximum daily site tonnage (kg/day): | 100 |
| Frequency and Duration of Use | |
| Continuous release. | |
| Emission Days (days/year): | 20 |
| Environmental factors not influenced by risk management | |
| Local freshwater dilution factor: | 10 |
| Local marine water dilution factor: | 100 |
| Other Operational Conditions affecting Environmental Exposure | |
| Release fraction to air from process (initial release prior to RMM): | 2,5E-02 |
| Release fraction to wastewater from process (initial release prior to RMM): | 2,0E-02 |
| Release fraction to soil from process (initial release prior to RMM): | 1,0E-04 |
| Technical conditions and measures at process level (source) to prevent release | |
| Common practices vary across sites thus conservative process re-release estimates used. | |
| Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil | |
| Risk from environmental exposure is driven by freshwater sediment. | |
| No wastewater treatment required. | |
| Treat air emission to provide a typical removal efficiency of (%) | 0 |
| Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%) | 0 |
| If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of (%) | 0 |
| Organisational measures to prevent/limit release from site | |
| Do not apply industrial sludge to natural soils. | |
| Sludge should be incinerated, contained or reclaimed. | |
| Conditions and Measures related to municipal sewage treatment plant | |
| Estimated substance removal from wastewater via domestic sewage treatment (%) | 96,9 |
| Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%) | 96,9 |
| Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d) | 6,5E+03 |
| Assumed domestic sewage treatment plant flow (m3/d) | 2,0E+03 |
| Conditions and Measures related to external treatment of waste for disposal | |
| External treatment and disposal of waste should comply with applicable local and/or regional regulations. | |
| Conditions and measures related to external recovery of waste | |
| External recovery and recycling of waste should comply with applicable local and/or regional regulations. | |

ethoxylate :

SECTION 3

EXPOSURE ESTIMATION

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

Version 3.0 Revision Date: 21.11.2023 SDS Number: 800001001081 Date of last issue: 28.03.2023
Print Date 28.11.2023

ethoxylate :

Section 3.1 - Health

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

ethoxylate :

Section 3.2 -Environment

The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

ethoxylate :

SECTION 4

GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO

ethoxylate :

Section 4.1 - Health

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

ethoxylate :

Section 4.2 -Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

ethoxylate :

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

Version 3.0 Revision Date: 21.11.2023 SDS Number: 800001001081 Date of last issue: 28.03.2023
Print Date 28.11.2023

Exposure Scenario - Worker

| | |
|--|---|
| 300000000670 Use in Laboratories - Professional | |
| SECTION 1 | EXPOSURE SCENARIO TITLE |
| Title | Use in laboratories- Professional |
| Use Descriptor | Sector of Use: SU22 Process Categories: PROC10, PROC15 Environmental Release Categories: ERC8a, ESVOC SpERC 8.17.v1 |
| Scope of process | Use of small quantities within laboratory settings, including material transfers and equipment cleaning. |

ethoxylate :

| | |
|------------------|--|
| SECTION 2 | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES |
|------------------|--|

ethoxylate :

| | |
|--|---|
| Section 2.1 | Control of Worker Exposure |
| Product Characteristics | |
| Physical form of product | Liquid, vapour pressure > 10 kPa at STP |
| Concentration of the Substance in Mixture/Article | Covers percentage substance in the product up to 100%., Unless stated otherwise., |
| Frequency and Duration of Use | |
| Covers daily exposures up to 8 hours (unless stated differently). | |
| Other Operational Conditions affecting Exposure | |
| Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented. | |

ethoxylate :

| | |
|-------------------------------|--|
| Contributing Scenarios | Risk Management Measures |
| Laboratory activitiesPROC15 | No other specific measures identified. |
| CleaningPROC10 | No other specific measures identified. |

ethoxylate :

| | |
|--|--|
| Section 2.2 | Control of Environmental Exposure |
| Substance is complex UVCB. | |
| Predominantly hydrophobic. | |
| Readily biodegradable. | |
| Amounts Used | |
| Fraction of EU tonnage used in region: | 0,1 |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

Version 3.0 Revision Date: 21.11.2023 SDS Number: 800001001081 Date of last issue: 28.03.2023
Print Date 28.11.2023

| | |
|---|---------|
| Regional use tonnage (tonnes/year): | 5 |
| Fraction of Regional tonnage used locally: | 5,0E-04 |
| Annual site tonnage (tonnes/year): | 2,5E-03 |
| Maximum daily site tonnage (kg/day): | 6,9E-03 |
| Frequency and Duration of Use | |
| Continuous release. | |
| Emission Days (days/year): | 365 |
| Environmental factors not influenced by risk management | |
| Local freshwater dilution factor: | 10 |
| Local marine water dilution factor: | 100 |
| Other Operational Conditions affecting Environmental Exposure | |
| Release fraction to air from wide dispersive use (regional only): | 0,5 |
| Release fraction to wastewater from wide dispersive use: | 0,5 |
| Release fraction to soil from wide dispersive use (regional only): | 0 |
| Technical conditions and measures at process level (source) to prevent release | |
| Common practices vary across sites thus conservative process re-lease estimates used. | |
| Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil | |
| Risk from environmental exposure is driven by freshwater sediment. | |
| No wastewater treatment required. | |
| Treat air emission to provide a typical removal efficiency of (%) | 0 |
| Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%) | 0 |
| If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of (%) | 0 |
| Organisational measures to prevent/limit release from site | |
| Do not apply industrial sludge to natural soils. | |
| Sludge should be incinerated, contained or reclaimed. | |
| Conditions and Measures related to municipal sewage treatment plant | |
| Estimated substance removal from wastewater via domestic sewage treatment (%) | 96 |
| Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%) | 96 |
| Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d) | 89 |
| Assumed domestic sewage treatment plant flow (m3/d) | 2,0E+03 |
| Conditions and Measures related to external treatment of waste for disposal | |
| External treatment and disposal of waste should comply with applicable local and/or regional regulations. | |
| Conditions and measures related to external recovery of waste | |
| External recovery and recycling of waste should comply with applicable local and/or regional regulations. | |

ethoxylate :

SECTION 3

EXPOSURE ESTIMATION

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

Version 3.0 Revision Date: 21.11.2023 SDS Number: 800001001081 Date of last issue: 28.03.2023
Print Date 28.11.2023

ethoxylate :

Section 3.1 - Health

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

ethoxylate :

Section 3.2 -Environment

The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

ethoxylate :

SECTION 4

GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO

ethoxylate :

Section 4.1 - Health

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

ethoxylate :

Section 4.2 -Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

ethoxylate :

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

Version 3.0 Revision Date: 21.11.2023 SDS Number: 800001001081 Date of last issue: 28.03.2023
Print Date 28.11.2023

Exposure Scenario - Consumer

| | |
|---|---|
| 300000001087 Use in Coatings - Consumer, n-Pentane | |
| SECTION 1 | EXPOSURE SCENARIO TITLE |
| Title | Uses in Coatings - Consumer |
| Use Descriptor | Sector of Use: SU21 Product Categories: PC1, PC4, PC8 (excipient only), PC9a, PC9b, PC9c, PC15, PC18, PC23, PC24, PC31, PC34 Environmental Release Categories: ERC8a, ERC8d, ESVOC SpERC 8.3c.v1 |
| Scope of process | Covers the use in coatings (paints, inks, adhesives, etc) including exposures during use (including product transfer and preparation, application by brush, spray by hand or similar methods) and equipment cleaning. |

ethoxylate

:

| | |
|------------------|--|
| SECTION 2 | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES |
|------------------|--|

ethoxylate

:

| | |
|--|--|
| Section 2.1 | Control of Consumer Exposure |
| Product Characteristics | |
| Physical form of product | Liquid, vapour pressure > 10 Pa at STP |
| Concentration of the Substance in Mixture/Article | Unless stated otherwise. |
| | Covers concentration up to (%): 100 % |
| Amounts Used | |
| Unless stated otherwise. | |
| covers amount up to (g): | 138.000 |
| covers skin contact area (cm2): | 857,5 |
| Frequency and Duration of Use | |
| Unless stated otherwise. | |
| Covers use up to (days/year): | 365 |
| covers use up to (times/day of use): | 1 |
| Exposure (hours/event): | 6 |
| Other Operational Conditions affecting Exposure | |
| Unless stated otherwise. | |
| Covers use at ambient temperatures. | |
| Covers use in room size of 20m3 | |
| Covers use under typical household ventilation. | |

ethoxylate

:

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

Version
3.0

Revision Date:
21.11.2023

SDS Number:
800001001081

Date of last issue: 28.03.2023
Print Date 28.11.2023

| Product Categories | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES |
|--|---|
| Adhesives, sealants Glues, hobby use. | Covers concentrations up to 3 % |
| | covers use up to 365 day/year |
| | Covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 35,73 cm2 |
| | For each use event, covers amount up to 5 g |
| | Covers use under typical household ventilation. Covers use in room size of 20m3 |
| | for each use event Covers exposure up to 4 hours/event |
| Adhesives, sealants Glues DIY-use (carpet glue, tile glue, wood parquet glue). | Covers concentrations up to 3,3 % |
| | covers use up to 1 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 110,00 cm2 |
| | For each use event, covers amount up to 6.390 g |
| | Covers use under typical household ventilation. |
| | Covers use in room size of 20 m3 |
| | for each use event Covers exposure up to 6,00 hours/event |
| | Avoid using when windows closed. |
| Adhesives, sealants Glue from spray. | Covers concentrations up to 11 % |
| | covers use up to 6 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 35,73 cm2 |
| | For each use event, covers amount up to 85,05 g |
| | Covers use under typical household ventilation. |
| | Covers use in room size of 20 m3 |
| | for each use event Covers exposure up to 4,00 hours/event |
| Adhesives, sealants Sealants. | Covers concentrations up to 2,5 % |
| | covers use up to 365 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 35,73 cm2 |
| | For each use event, covers amount up to 25 g |
| | Covers use under typical household ventilation. |
| | Covers use in room size of 20 m3 |
| | for each use event Covers exposure up to 1,00 hours/event |
| Anti-Freeze and de-icing products Washing car window. | Covers concentrations up to 1 % |
| | covers use up to 365 day/year |
| | covers use up to 1 times/day of use |
| | For each use event, covers amount up to 0,5 g |
| | Covers use in a one car garage (34 m3) under typical ventilation. |
| | Covers use in room size of 34 m3 |
| | for each use event Covers exposure up to 0,02 hours/event |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

Version 3.0 Revision Date: 21.11.2023 SDS Number: 800001001081 Date of last issue: 28.03.2023
Print Date 28.11.2023

| | |
|--|---|
| Anti-Freeze and de-icing products Pouring into radiator. | Covers concentrations up to 2,5 % |
| | covers use up to 365 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 428,00 cm2 |
| | For each use event, covers amount up to 2.000 g |
| | Covers use in a one car garage (34 m3) under typical ventilation. |
| | Covers use in room size of 34 m3 |
| | for each use event Covers exposure up to 0,17 hours/event |
| Anti-Freeze and de-icing products Lock de-icer. | Covers concentrations up to 45 % |
| | covers use up to 365 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 214,40 cm2 |
| | For each use event, covers amount up to 4 g |
| | Covers use in a one car garage (34 m3) under typical ventilation. |
| | Covers use in room size of 34 m3 |
| | for each use event Covers exposure up to 0,25 hours/event |
| Biocidal products (e.g. Disinfectants, pest control) (excipient only). Laundry and dish washing products. | Covers concentrations up to 3,5 % |
| | covers use up to 365 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 857,50 cm2 |
| | For each use event, covers amount up to 15 g |
| | Covers use under typical household ventilation. |
| | Covers use in room size of 20m3 |
| | for each use event Covers exposure up to 0,50 hours/event |
| Biocidal products (e.g. Disinfectants, pest control) (excipient only). Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners). | Covers concentrations up to 5 % |
| | covers use up to 128 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 857,50 cm2 |
| | For each use event, covers amount up to 27 g |
| | Covers use under typical household ventilation. |
| | Covers use in room size of 20m3 |
| | for each use event Covers exposure up to 0,33 hours/event |
| Biocidal products (e.g. Disinfectants, pest control) (excipient only). Cleaners, trigger sprays (all purpose | Covers concentrations up to 11 % |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

Version 3.0 Revision Date: 21.11.2023 SDS Number: 800001001081 Date of last issue: 28.03.2023
Print Date 28.11.2023

| | |
|---|---|
| cleaners, sanitary products, glass cleaners). | |
| | covers use up to 128 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 428,00 cm2 |
| | For each use event, covers amount up to 35 g |
| | Covers use under typical household ventilation. |
| | Covers use in room size of 20m3 |
| | for each use event Covers exposure up to 0,17 hours/event |
| Coatings and paints, thinners, paint removers Waterborne latex wall paint. | Covers concentrations up to 1,5 % |
| | covers use up to 4 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 428,75 cm2 |
| | For each use event, covers amount up to 2.760 g |
| | Covers use under typical household ventilation. |
| | Covers use in room size of 20 m3 |
| | for each use event Covers exposure up to 2,20 hours/event |
| | Avoid using when windows closed. |
| Coatings and paints, thinners, paint removers Solvent rich, high solid, water borne paint. | Covers concentrations up to 5 % |
| | covers use up to 6 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 428,75 cm2 |
| | For each use event, covers amount up to 744 g |
| | Covers use under typical household ventilation. |
| | Covers use in room size of 20 m3 |
| | for each use event Covers exposure up to 2,20 hours/event |
| | Avoid using when windows closed. |
| Coatings and paints, thinners, paint removers Aerosol spray can. | Covers concentrations up to 50 % |
| | covers use up to 2 day/year |
| | covers use up to 1 times/day of use |
| | For each use event, covers amount up to 215 g |
| | Covers use in a one car garage (34 m3) under typical ventilation. |
| | Covers use in room size of 34 m3 |
| | for each use event Covers exposure up to 0,33 hours/event |
| Coatings and paints, thinners, paint removers Removers (paint-, glue-, wall paper-, sealant-remover). | Covers concentrations up to 14 % |
| | covers use up to 3 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 857,50 cm2 |
| | For each use event, covers amount up to 491 g |
| | Covers use under typical household ventilation. |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

Version 3.0 Revision Date: 21.11.2023 SDS Number: 800001001081 Date of last issue: 28.03.2023
Print Date 28.11.2023

| | |
|---|---|
| | Covers use in room size of 20 m3 |
| | for each use event Covers exposure up to 2,00 hours/event |
| | Avoid using when windows closed. |
| Fillers, Putties Fillers and putty. | Covers concentrations up to 0,02 % |
| | covers use up to 12 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 35,73 cm2 |
| | For each use event, covers amount up to 85 g |
| | Covers use under typical household ventilation. |
| | Covers use in room size of 20 m3 |
| | for each use event Covers exposure up to 4,00 hours/event |
| Fillers, Putties Plasters and floor equalizers. | Covers concentrations up to 1,8 % |
| | covers use up to 12 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 857,50 cm2 |
| | For each use event, covers amount up to 900 g |
| | Covers use under typical household ventilation. |
| | Covers use in room size of 20 m3 |
| | for each use event Covers exposure up to 2,00 hours/event |
| | Avoid using when windows closed. |
| Fillers, Putties Modelling clay. | Covers concentrations up to 0,27 % |
| | covers use up to 365 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 254,40 cm2 |
| | For each use event, assumes swallowed amount of 1 g |
| Finger paints | Covers concentrations up to 0,02 % |
| | covers use up to 365 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 254,40 cm2 |
| | For each use event, assumes swallowed amount of 1,35 g |
| Non-metal-surface treatment products Waterborne latex wall paint. | Covers concentrations up to 1,5 % |
| | covers use up to 4 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 428,75 cm2 |
| | For each use event, covers amount up to 2.760 g |
| | Covers use under typical household ventilation. |
| | Covers use in room size of 20m3 |
| | for each use event Covers exposure up to 2,20 hours/event |
| | Avoid using when windows closed. |
| Non-metal-surface treatment products Solvent rich, high solid, water borne paint. | Covers concentrations up to 5 % |
| | covers use up to 6 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 428,75 cm2 |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

Version 3.0 Revision Date: 21.11.2023 SDS Number: 800001001081 Date of last issue: 28.03.2023
Print Date 28.11.2023

| | |
|--|--|
| | For each use event, covers amount up to 744 g |
| | Covers use under typical household ventilation. |
| | Covers use in room size of 20 m ³ |
| | for each use event Covers exposure up to 2,20 hours/event |
| | Avoid using when windows closed. |
| Non-metal-surface treatment products Aerosol spray can. | Covers concentrations up to 50 % |
| | covers use up to 2 day/year |
| | covers use up to 1 times/day of use |
| | For each use event, covers amount up to 215 g |
| | Covers use in a one car garage (34 m ³) under typical ventilation. |
| | Covers use in room size of 34 m ³ |
| | for each use event Covers exposure up to 0,33 hours/event |
| Non-metal-surface treatment products Removers (paint-, glue-, wall paper-, sealant-remover). | Covers concentrations up to 14 % |
| | covers use up to 3 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm ²): 857,50 cm ² |
| | For each use event, covers amount up to 491 g |
| | Covers use under typical household ventilation. |
| | Covers use in room size of 20 m ³ |
| | for each use event Covers exposure up to 2,00 hours/event |
| | Avoid using when windows closed. |
| Ink and toners | Covers concentrations up to 10 % |
| | covers use up to 365 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm ²): 71,40 cm ² |
| | For each use event, covers amount up to 40 g |
| | Covers use under typical household ventilation. |
| | Covers use in room size of 20m ³ |
| | for each use event Covers exposure up to 2,20 hours/event |
| Leather tanning, dye, finishing, impregnation and care products Polishes, wax / cream (floor, furniture, shoes). | Covers concentrations up to 6 % |
| | covers use up to 29 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm ²): 430,00 cm ² |
| | For each use event, covers amount up to 56 g |
| | Covers use under typical household ventilation. |
| | Covers use in room size of 20m ³ |
| | for each use event Covers exposure up to 1,23 hours/event |
| Leather tanning, dye, finishing, impregnation and care products Polishes, spray (furniture, shoes). | Covers concentrations up to 50 % |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

Version 3.0 Revision Date: 21.11.2023 SDS Number: 800001001081 Date of last issue: 28.03.2023
Print Date 28.11.2023

| | |
|--|--|
| | covers use up to 8 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 430,00 cm2 |
| | For each use event, covers amount up to 56 g |
| | Covers use under typical household ventilation. |
| | Covers use in room size of 20m3 |
| | for each use event Covers exposure up to 0,33 hours/event |
| Lubricants, greases, re- lease products Liquids. | Covers concentrations up to 100 % |
| | covers use up to 4 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 468,00 cm2 |
| | For each use event, covers amount up to 2.200 g |
| | Covers use in a one car garage (34 m3) under typical ventila- tion. |
| | Covers use in room size of 34 m3 |
| | for each use event Covers exposure up to 0,17 hours/event |
| Lubricants, greases, re- lease products Pastes. | Covers concentrations up to 20 % |
| | covers use up to 10 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 468,00 cm2 |
| | For each use event, covers amount up to 34 g |
| | for each use event Covers exposure up to 4 hours/event |
| Lubricants, greases, re- lease products Sprays. | Covers concentrations up to 50 % |
| | covers use up to 6 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 428,75 cm2 |
| | For each use event, covers amount up to 73 g |
| | Covers use under typical household ventilation. |
| | Covers use in room size of 20 m3 |
| | for each use event Covers exposure up to 0,17 hours/event |
| Polishes and wax blends Polishes, wax / cream (floor, furniture, shoes). | Covers concentrations up to 2,4 % |
| | covers use up to 29 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 430,00 cm2 |
| | For each use event, covers amount up to 142 g |
| | Covers use under typical household ventilation. |
| | Covers use in room size of 20 m3 |
| | for each use event Covers exposure up to 1,23 hours/event |
| Polishes and wax blends Polishes, spray (furniture, shoes). | Covers concentrations up to 50 % |
| | covers use up to 8 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 430,00 cm2 |
| | For each use event, covers amount up to 35 g |
| | Covers use under typical household ventilation. |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

Version 3.0 Revision Date: 21.11.2023 SDS Number: 800001001081 Date of last issue: 28.03.2023
Print Date 28.11.2023

| | |
|---|---|
| | Covers use in room size of 20 m3 |
| | for each use event Covers exposure up to 0,33 hours/event |
| Textile dyes, finishing and impregnating products; including bleaches and other processing aids | Covers concentrations up to 1,1 % |
| | covers use up to 365 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 857,50 cm2 |
| | For each use event, covers amount up to 45 g |
| | Covers use under typical household ventilation. |
| | Covers use in room size of 20m3 |
| | for each use event Covers exposure up to 1,00 hours/event |
| | Avoid using in room size less than (m3): 34 |

ethoxylate

:

| Section 2.2 | Control of Environmental Exposure |
|---|-----------------------------------|
| Substance is complex UVCB. | |
| Predominantly hydrophobic. | |
| Readily biodegradable. | |
| Amounts Used | |
| Fraction of EU tonnage used in region: | 0,1 |
| Regional use tonnage (tonnes/year): | 1 |
| Fraction of Regional tonnage used locally: | 5,0E-04 |
| Annual site tonnage (tonnes/year): | 5,0E-04 |
| Maximum daily site tonnage (kg/day): | 1,4E-03 |
| Frequency and Duration of Use | |
| Continuous release. | |
| Emission Days (days/year): | 365 |
| Environmental factors not influenced by risk management | |
| Local freshwater dilution factor: | 10 |
| Local marine water dilution factor: | 100 |
| Other Operational Conditions affecting Environmental Exposure | |
| Release fraction to air from wide dispersive use (regional only): | 0,99 |
| Release fraction to wastewater from wide dispersive use: | 1,0E-02 |
| Release fraction to soil from wide dispersive use (regional only): | 5,0E-03 |
| Conditions and Measures related to municipal sewage treatment plant | |
| Risk from environmental exposure is driven by freshwater. | |
| Estimated substance removal from wastewater via domestic sewage treatment (%) | 96,0 |
| Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d) | 25 |
| Assumed domestic sewage treatment plant flow (m3/d) | 2,0E+03 |
| Conditions and Measures related to external treatment of waste for disposal | |
| External treatment and disposal of waste should comply with applicable local and/or regional regulations. | |
| Conditions and measures related to external recovery of waste | |
| External recovery and recycling of waste should comply with applicable local and/or regional regulations. | |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

Version 3.0 Revision Date: 21.11.2023 SDS Number: 800001001081 Date of last issue: 28.03.2023
Print Date 28.11.2023

ethoxylate

:

SECTION 3

EXPOSURE ESTIMATION

ethoxylate

:

Section 3.1 - Health

The ECETOC TRA tool has been used to estimate consumer exposures unless otherwise indicated.

ethoxylate

:

Section 3.2 -Environment

The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

ethoxylate

:

SECTION 4

GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO

ethoxylate

:

Section 4.1 - Health

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

ethoxylate

:

Section 4.2 -Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

ethoxylate

:

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

Version 3.0 Revision Date: 21.11.2023 SDS Number: 800001001081 Date of last issue: 28.03.2023
Print Date 28.11.2023

Exposure Scenario - Consumer

| | |
|--|---|
| 300000001089 Use in Cleaning Agents - Consumer, n-Pentane | |
| SECTION 1 | EXPOSURE SCENARIO TITLE |
| Title | Use in Cleaning Agents - Consumer |
| Use Descriptor | Sector of Use: SU21 Product Categories: PC3, PC4, PC8 (excipient only), PC9a, PC24, PC35, PC38 Environmental Release Categories: ERC8a, ERC8d, ESVOC SpERC 8.4c.v1 |
| Scope of process | Covers general exposures to consumers arising from the use of household products sold as washing and cleaning products, aerosols, coatings, de-icers, lubricants and air care products. |

ethoxylate :

| | |
|------------------|--|
| SECTION 2 | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES |
|------------------|--|

ethoxylate :

| | |
|--|--|
| Section 2.1 | Control of Consumer Exposure |
| Product Characteristics | |
| Physical form of product | Liquid, vapour pressure > 10 Pa at STP |
| Concentration of the Substance in Mixture/Article | Unless stated otherwise. |
| | Covers concentration up to (%): 100 % |
| Amounts Used | |
| Unless stated otherwise. | |
| covers amount up to (g): | 13.800 |
| covers skin contact area (cm ²): | 857,50 |
| Frequency and Duration of Use | |
| Unless stated otherwise. | |
| Covers use up to (days/year): | 365 |
| covers use up to (times/day of use): | 4 |
| Exposure (hours/event): | 8 |
| Other Operational Conditions affecting Exposure | |
| Unless stated otherwise. | |
| Covers use at ambient temperatures. | |
| Covers use in room size of 20m ³ | |
| Covers use under typical household ventilation. | |

ethoxylate :

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

Version
3.0

Revision Date:
21.11.2023

SDS Number:
800001001081

Date of last issue: 28.03.2023
Print Date 28.11.2023

| Product Categories | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES |
|--|--|
| Air care products Air care, instant action (aerosol sprays). | Covers concentrations up to 50 % |
| | covers use up to 365 day/year |
| | covers use up to 4 times/day of use |
| | For each use event, covers amount up to 0,1 g |
| | Covers use under typical household ventilation. |
| | Covers use in room size of 20 m ³ |
| | for each use event Covers exposure up to 0,25 hours/event |
| Air care products Air care, instant action (aerosol sprays). pesticides (excipient only). | Covers concentrations up to 50 % |
| | covers use up to 365 day/year |
| | covers use up to 4 times/day of use |
| | For each use event, covers amount up to 5 g |
| | Covers use under typical household ventilation. |
| | Covers use in room size of 20 m ³ |
| | for each use event Covers exposure up to 0,25 hours/event |
| Air care products Air care, continuous action (solid and liquid). | Covers concentrations up to 10 % |
| | covers use up to 365 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm ²): 35,70 cm ² |
| | For each use event, covers amount up to 0,48 g |
| | Covers use under typical household ventilation. |
| | Covers use in room size of 20 m ³ |
| | for each use event Covers exposure up to 8,00 hours/event |
| Air care products Air care, continuous action (solid and liquid). pesticides (excipient only). | Covers concentrations up to 25 % |
| | covers use up to 365 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm ²): 35,70 cm ² |
| | For each use event, covers amount up to 0,48 g |
| | Covers use under typical household ventilation. |
| | Covers use in room size of 20 m ³ |
| | for each use event Covers exposure up to 8,00 hours/event |
| Anti-Freeze and de-icing products Washing car window. | Covers concentrations up to 1 % |
| | covers use up to 365 day/year |
| | covers use up to 1 times/day of use |
| | For each use event, covers amount up to 0,5 g |
| | Covers use in a one car garage (34 m ³) under typical ventilation. |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

Version 3.0 Revision Date: 21.11.2023 SDS Number: 800001001081 Date of last issue: 28.03.2023
Print Date 28.11.2023

| | |
|--|---|
| | Covers use in room size of 34 m3 |
| | for each use event Covers exposure up to 0,02 hours/event |
| Anti-Freeze and de-icing products Pouring into radiator. | Covers concentrations up to 2,5 % |
| | covers use up to 365 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 428,00 cm2 |
| | For each use event, covers amount up to 2.000 g |
| | Covers use in a one car garage (34 m3) under typical ventilation. |
| | Covers use in room size of 34 m3 |
| | for each use event Covers exposure up to 0,17 hours/event |
| Anti-Freeze and de-icing products Lock de-icer. | Covers concentrations up to 45 % |
| | covers use up to 365 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 214,40 cm2 |
| | For each use event, covers amount up to 4 g |
| | Covers use in a one car garage (34 m3) under typical ventilation. |
| | Covers use in room size of 34 m3 |
| | for each use event Covers exposure up to 0,25 hours/event |
| Biocidal products (e.g. Disinfectants, pest control) (excipient only). Laundry and dish washing products. | Covers concentrations up to 3,5 % |
| | covers use up to 365 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 857,50 cm2 |
| | For each use event, covers amount up to 15 g |
| | Covers use under typical household ventilation. |
| | Covers use in room size of 20m3 |
| | for each use event Covers exposure up to 0,50 hours/event |
| Biocidal products (e.g. Disinfectants, pest control) (excipient only). Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners). | Covers concentrations up to 5 % |
| | covers use up to 128 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 857,50 cm2 |
| | For each use event, covers amount up to 27 g |
| | Covers use under typical household ventilation. |
| | Covers use in room size of 20m3 |
| | for each use event Covers exposure up to 0,33 hours/event |
| Biocidal products (e.g. Disinfectants, pest control) | Covers concentrations up to 11 % |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

Version 3.0 Revision Date: 21.11.2023 SDS Number: 800001001081 Date of last issue: 28.03.2023
Print Date 28.11.2023

| | |
|---|---|
| (excipient only). Cleaners, trigger sprays (all purpose cleaners, sanitary products, glass cleaners). | |
| | covers use up to 128 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 428,00 cm2 |
| | For each use event, covers amount up to 35 g |
| | Covers use under typical household ventilation. |
| | Covers use in room size of 20m3 |
| | for each use event Covers exposure up to 0,17 hours/event |
| Coatings and paints, thinners, paint removers Waterborne latex wall paint. | Covers concentrations up to 1,5 % |
| | covers use up to 4 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 428,75 cm2 |
| | For each use event, covers amount up to 2.760 g |
| | Covers use under typical household ventilation. |
| | Covers use in room size of 20 m3 |
| | for each use event Covers exposure up to 2,20 hours/event |
| | Avoid using when windows closed. |
| Coatings and paints, thinners, paint removers Solvent rich, high solid, water borne paint. | Unless stated otherwise. Covers concentrations up to 5 % |
| | covers use up to 6 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 428,75 cm2 |
| | For each use event, covers amount up to 744 g |
| | Covers use under typical household ventilation. |
| | Covers use in room size of 20 m3 |
| | for each use event Covers exposure up to 2,20 hours/event |
| | Avoid using when windows closed. |
| Coatings and paints, thinners, paint removers Aerosol spray can. | Covers concentrations up to 50 % |
| | covers use up to 2 day/year |
| | covers use up to 1 times/day of use |
| | For each use event, covers amount up to 215 g |
| | Covers use in a one car garage (34 m3) under typical ventilation. |
| | Covers use in room size of 34 m3 |
| | for each use event Covers exposure up to 0,33 hours/event |
| Coatings and paints, thinners, paint removers Removers (paint-, glue-, wall paper-, sealant-remover). | Covers concentrations up to 14 % |
| | covers use up to 3 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 857,50 cm2 |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

Version 3.0 Revision Date: 21.11.2023 SDS Number: 800001001081 Date of last issue: 28.03.2023
Print Date 28.11.2023

| | |
|---|---|
| | For each use event, covers amount up to 491 g |
| | Covers use under typical household ventilation. |
| | Covers use in room size of 20 m ³ |
| | Avoid using when windows closed. |
| | for each use event Covers exposure up to 2,00 hours/event |
| Lubricants, greases, re- lease products Liquids. | Covers concentrations up to 100 % |
| | covers use up to 4 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm ²): 468,00 cm ² |
| | For each use event, covers amount up to 2.200 g |
| | Covers use in a one car garage (34 m ³) under typical ventila- tion. |
| | Covers use in room size of 34 m ³ |
| | for each use event Covers exposure up to 0,17 hours/event |
| Lubricants, greases, re- lease products Pastes. | Covers concentrations up to 20 % |
| | covers use up to 10 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm ²): 468,00 cm ² |
| | For each use event, covers amount up to 34 g |
| | for each use event Covers exposure up to 4 hours/event |
| Lubricants, greases, re- lease products Sprays. | Covers concentrations up to 50 % |
| | covers use up to 6 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm ²): 428,75 cm ² |
| | For each use event, covers amount up to 73 g |
| | Covers use under typical household ventilation. |
| | Covers use in room size of 20 m ³ |
| | for each use event Covers exposure up to 0,17 hours/event |
| Washing and cleaning products (including solvent based products) Laundry and dish washing products. | Covers concentrations up to 3,5 % |
| | covers use up to 365 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm ²): 857,50 cm ² |
| | For each use event, covers amount up to 15 g |
| | Covers use under typical household ventilation. |
| | Covers use in room size of 20 m ³ |
| | for each use event Covers exposure up to 0,5 hours/event |
| Washing and cleaning products (including solvent based products) Cleaners, liquids (all purpose clean- ers, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners). | Covers concentrations up to 5 % |
| | covers use up to 128 day/year |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

Version 3.0 Revision Date: 21.11.2023 SDS Number: 800001001081 Date of last issue: 28.03.2023
Print Date 28.11.2023

| | |
|--|---|
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 857,50 cm2 |
| | For each use event, covers amount up to 27 g |
| | Covers use under typical household ventilation. |
| | Covers use in room size of 20 m3 |
| | for each use event Covers exposure up to 0,33 hours/event |
| Washing and cleaning products (including solvent based products) Cleaners, trigger sprays (all purpose cleaners, sanitary products, glass cleaners). | Covers concentrations up to 11 % |
| | covers use up to 128 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 428,00 cm2 |
| | For each use event, covers amount up to 35 g |
| | Covers use under typical household ventilation. |
| | Covers use in room size of 20m3 |
| | for each use event Covers exposure up to 0,17 hours/event |
| Welding and soldering products (with flux coatings or flux cores.), flux products | Covers concentrations up to 5 % |
| | covers use up to 365 day/year |
| | covers use up to 1 times/day of use |
| | For each use event, covers amount up to 12 g |
| | Covers use under typical household ventilation. |
| | Covers use in room size of 20 m3 |
| | for each use event Covers exposure up to 1,00 hours/event |
| | Avoid using when windows closed. |

ethoxylate

:

| Section 2.2 | Control of Environmental Exposure |
|--|-----------------------------------|
| Substance is complex UVCB. | |
| Predominantly hydrophobic. | |
| Readily biodegradable. | |
| Amounts Used | |
| Fraction of EU tonnage used in region: | 0,1 |
| Regional use tonnage (tonnes/year): | 42 |
| Fraction of Regional tonnage used locally: | 5,0E-04 |
| Annual site tonnage (tonnes/year): | 2,1E-02 |
| Maximum daily site tonnage (kg/day): | 5,7E-02 |
| Frequency and Duration of Use | |
| Continuous release. | |
| Emission Days (days/year): | 365 |
| Environmental factors not influenced by risk management | |
| Local freshwater dilution factor: | 10 |
| Local marine water dilution factor: | 100 |
| Other Operational Conditions affecting Environmental Exposure | |
| Release fraction to air from wide dispersive use (regional only): | 0,95 |
| Release fraction to wastewater from wide dispersive use: | 2,5E-02 |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

Version 3.0 Revision Date: 21.11.2023 SDS Number: 800001001081 Date of last issue: 28.03.2023
Print Date 28.11.2023

| | |
|---|---------|
| Release fraction to soil from wide dispersive use (regional only): | 2,5E-02 |
| Conditions and Measures related to municipal sewage treatment plant | |
| Risk from environmental exposure is driven by freshwater. | |
| Estimated substance removal from wastewater via domestic sewage treatment (%) | 96 |
| Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d) | 9E+02 |
| Assumed domestic sewage treatment plant flow (m3/d) | 2,0E+03 |
| Conditions and Measures related to external treatment of waste for disposal | |
| External treatment and disposal of waste should comply with applicable local and/or regional regulations. | |
| Conditions and measures related to external recovery of waste | |
| External recovery and recycling of waste should comply with applicable local and/or regional regulations. | |

ethoxylate :

| | |
|------------------|----------------------------|
| SECTION 3 | EXPOSURE ESTIMATION |
|------------------|----------------------------|

ethoxylate :

Section 3.1 - Health

The ECETOC TRA tool has been used to estimate consumer exposures unless otherwise indicated.

ethoxylate :

Section 3.2 -Environment

The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

ethoxylate :

| | |
|------------------|--|
| SECTION 4 | GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO |
|------------------|--|

ethoxylate :

Section 4.1 - Health

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.
Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

ethoxylate :

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 28.03.2023 |
| 3.0 | 21.11.2023 | 800001001081 | Print Date 28.11.2023 |

| |
|---------------------------------|
| Section 4.2 -Environment |
|---------------------------------|

| |
|--|
| Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. |
|--|

| |
|--|
| Further details on scaling and control technologies are provided in SpERC factsheet (http://cefic.org/en/reach-for-industries-libraries.html). |
|--|

ethoxylate

:

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

Version 3.0 Revision Date: 21.11.2023 SDS Number: 800001001081 Date of last issue: 28.03.2023
Print Date 28.11.2023

Exposure Scenario - Consumer

| | |
|---|---|
| 300000001091 Other Consumer Uses - Consumer, n-Pentane | |
| SECTION 1 | EXPOSURE SCENARIO TITLE |
| Title | Other Consumer Uses - Consumer |
| Use Descriptor | Sector of Use: SU21 Product Categories: PC28, PC39 Environmental Release Categories: ERC8a, ERC8d, ESVOC SpERC 8.16.v1 |
| Scope of process | Consumer uses e.g. as a carrier in cosmetics/personal care products, perfumes and fragrances. Note: For cosmetic and personal care products, risk assessment only required for the environment under REACH as human health is covered by alternative legislation. |

ethoxylate :

| | |
|-------------------------------|--|
| SECTION 2 | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES |
| Additional Information | No exposure assessment presented for human health. |

ethoxylate :

| | |
|--------------------------------|-------------------------------------|
| Section 2.1 | Control of Consumer Exposure |
| Product Characteristics | |

ethoxylate :

| | |
|---------------------------|--|
| Product Categories | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES |
|---------------------------|--|

ethoxylate :

| | |
|--|--|
| Section 2.2 | Control of Environmental Exposure |
| Substance is complex UVCB. | |
| Predominantly hydrophobic. | |
| Readily biodegradable. | |
| Amounts Used | |
| Fraction of EU tonnage used in region: | 0,1 |
| Regional use tonnage (tonnes/year): | 72 |
| Fraction of Regional tonnage used locally: | 5,0E-04 |
| Annual site tonnage (tonnes/year): | 3,6E-02 |
| Maximum daily site tonnage (kg/day): | 9,9E-02 |
| Frequency and Duration of Use | |
| Continuous release. | |
| Emission Days (days/year): | 365 |
| Environmental factors not influenced by risk management | |
| Local freshwater dilution factor: | 10 |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

Version 3.0 Revision Date: 21.11.2023 SDS Number: 800001001081 Date of last issue: 28.03.2023
Print Date 28.11.2023

| | |
|---|---------|
| Local marine water dilution factor: | 100 |
| Other Operational Conditions affecting Environmental Exposure | |
| Release fraction to air from wide dispersive use (regional only): | 0,95 |
| Release fraction to wastewater from wide dispersive use: | 2,5E-02 |
| Release fraction to soil from wide dispersive use (regional only): | 2,5E-02 |
| Conditions and Measures related to municipal sewage treatment plant | |
| Risk from environmental exposure is driven by freshwater sediment. | |
| Estimated substance removal from wastewater via domestic sewage treatment (%) | 96 |
| Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d) | 1,4E+03 |
| Assumed domestic sewage treatment plant flow (m3/d) | 2,0E+03 |
| Conditions and Measures related to external treatment of waste for disposal | |
| External treatment and disposal of waste should comply with applicable local and/or regional regulations. | |
| Conditions and measures related to external recovery of waste | |
| External recovery and recycling of waste should comply with applicable local and/or regional regulations. | |

ethoxylate :

| | |
|------------------|----------------------------|
| SECTION 3 | EXPOSURE ESTIMATION |
|------------------|----------------------------|

ethoxylate :

| |
|-----------------------------|
| Section 3.1 - Health |
|-----------------------------|

No exposure assessment presented for human health.

ethoxylate :

| |
|---------------------------------|
| Section 3.2 -Environment |
|---------------------------------|

The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

ethoxylate :

| | |
|------------------|--|
| SECTION 4 | GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO |
|------------------|--|

ethoxylate :

| |
|-----------------------------|
| Section 4.1 - Health |
|-----------------------------|

No exposure assessment presented for human health.

ethoxylate :

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Normal-Pentane

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 28.03.2023 |
| 3.0 | 21.11.2023 | 800001001081 | Print Date 28.11.2023 |

Section 4.2 -Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

ethoxylate

: