Material Safety Data Sheet

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

Material Name	:	**CARADOL SC56-02**
Uses	:	Use for the manufacture of polyurethane products.
Product Code	:	U3164
Supplier	:	SHELL EASTERN CHEMICALS (S) A REGISTERED BUSINESS OF SHELL EASTERN TRADING (PTE) LTD (UEN:198902087C) 9 North Buona Vista Drive , #07-01 The Metropolis Tower 1 Singapore 138588 Singapore
Telephone	:	+65 6384 8737
Fax	:	+65 6384 8454
Emergency Telephone Number	:	+ (65) 6542 9595 (Alert-SGS)
Other Information	:	CARADOL is a trademark owned by Shell Trademark Management B.V. and Shell Brands Inc. and used by affiliates of Royal Dutch Shell plc.

2. COMPOSITION/INFORMATION ON INGREDIENTS

Material Formal Name	:	Polyoxyalkylene triol
Synonyms	:	Polyol
CAS No.	:	25791-96-2
Additional Information	:	Refer to chapter 16 for full text of EC R-phrases.

3. HAZARDS IDENTIFICATION

Health Hazards	:	No specific hazards.

4. FIRST AID MEASURES

General Information	:	Not expected to be a health hazard when used under normal conditions.
Inhalation	:	Remove to fresh air. If rapid recovery does not occur, transport to nearest medical facility for additional treatment.
Skin Contact	:	Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available.
Eye Contact	:	Immediately flush eyes with large amounts of water for at least 15 minutes while holding eyelids open. Transport to the nearest medical facility for additional treatment.
Ingestion	:	Wash out mouth with water and obtain medical attention.

Advice to Physician	:	Treat symptomatically. Following cases of gross over-exposure, investigation of liver, kidney and eye function may be advisable. Records of such incidents should be maintained for future reference.

5. FIRE FIGHTING MEASURES

Specific Hazards	:	Clear fire area of all non-emergency personnel. Will only burn if enveloped in a pre-existing fire. Hazardous combustion products may include: Carbon dioxide. Unidentified organic and inorganic compounds. Toxic products. Carbon monoxide.
Extinguishing Media	:	Large fires should only be fought by properly trained fire fighters. Alcohol-resistant foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
Unsuitable Extinguishing Media	:	Do not use water in a jet.
Protective Equipment for Firefighters	:	Wear full protective clothing and self-contained breathing apparatus.
Additional Advice	:	All storage areas should be provided with adequate fire fighting facilities. Keep adjacent containers cool by spraying with water.

6. ACCIDENTAL RELEASE MEASURES

Observe all relevant local and international regulations.

Protective measures	:	Avoid contact with spilled or released material. For guidance on selection of personal protective equipment see Chapter 8 of this Material Safety Data Sheet. Avoid inhaling vapour and/or mists. Avoid contact with the skin. Extinguish any naked flames. Do not smoke. Remove ignition sources. Avoid sparks. Remove all possible sources of ignition in the surrounding area. Prevent from spreading or entering into drains, ditches or rivers by using sand, earth, or other appropriate barriers. Use appropriate containment to avoid environmental contamination. Ventilate contaminated area thoroughly.
Clean Up Methods	:	For large liquid spills (> 1 drum), transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely. For small liquid spills (< 1 drum), transfer by mechanical means to a labelled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.
Additional Advice	:	Proper disposal should be evaluated based on regulatory status of this material (refer to Section 13), potential contamination from subsequent use and spillage, and regulations governing disposal in the local area. Observe all relevant local regulations.

7. HANDLING AND STORAGE

General Precautions	:	Avoid breathing vapours or contact with material. Only use in well ventilated areas. Wash thoroughly after handling. On guidance on selection of personal protective equipment see Chapter 8 of this Material Safety Data Sheet. For comprehensive advice on handling, product transfer, storage and tank cleaning refer to the product supplier.
Handling	:	In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. Use local exhaust extraction over processing area. Avoid unintentional contact with isocyanates to prevent uncontrolled polymerisation. Avoid contact with skin, eyes, and clothing. Air-dry contaminated clothing in a well-ventilated area before laundering. Extinguish any naked flames. Do not smoke. Remove ignition sources. Avoid sparks. Do not empty into drains. Handling Temperature: Ambient. When handling product in drums, safety footwear should be worn and proper handling equipment should be used.
Storage	:	Prevent all contact with water and with moist atmosphere. Tanks must be clean, dry and rust-free. Prevent ingress of water. Must be stored in a diked (bunded) well-ventilated area, away from sunlight, ignition sources and other sources of heat. Nitrogen blanket recommended for large tanks (capacity 100 m3 or higher). Drums should be stacked to a maximum of 3 high. Maximum storage time: 12 months. Storage Temperature: Ambient. Storage should be handled at temperatures such that viscosities are less than 500 cSt; typically at 25-50 °C. Tanks should be fitted with heating coils in areas where the ambient temperatures are below the recommended product handling temperatures. Heating coil skin temperatures should not exceed 100 °C.
Product Transfer	:	Lines should be purged with nitrogen before and after product transfer. Keep containers closed when not in use.
Unsuitable Materials	:	Copper. Copper alloys.
Additional Information	:	Ensure that all local regulations regarding handling and storage facilities are followed. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

If the American Conference of Governmental Industrial Hygienists (ACGIH) value is provided on this document, it is provided for information only.

Occupational Exposure Limits

None established.

Exposure Controls	:	Exhaust emission systems should be designed in accordance

		with local conditions; the air should always be moved away from the source of vapour generation and the person working at this point. Adequate ventilation to control airborne concentrations.
Personal Protective Equipment	:	Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.
Respiratory Protection	:	No respiratory protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material.
Hand Protection	:	Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.
Eye Protection	:	Chemical splash goggles (chemical monogoggles). Approved to EU Standard EN166, AS/NZS:1337.
Protective Clothing	:	Chemical and cold resistant gloves/gauntlets, boots, and apron.
Monitoring Methods	:	Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate. Examples of sources of recommended air monitoring methods are given below or contact supplier. Further national methods may be available. National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods, http://www.cdc.gov/niosh/nmam/nmammenu.html. Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods, http://www.osha-slc.gov/dts/sltc/methods/toc.html. Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances, http://www.hsl.gov.uk/publications/mdhs.aspx. Berufsgenossenschaftliches Institut für Arbeitssicherheit (BIA), Germany http://www.hvbg.de/d/bia/index.html. L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/securite/hygiene_securite_travail.html.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	Clear colourless Liquid.
Odour	:	Odourless
pH	:	Data not available.
Boiling point	:	> 300 °C / 572 °F
Flash point	:	Typical 200 °C / 392 °F
Explosion / Flammability limits in air	:	Data not available.
Vapour pressure	:	Not applicable
Density	:	Typical 1,017 kg/m3 at 20 °C / 68 °F
Water solubility	:	Slightly soluble.
Solubility in other solvents	:	Data not available.
Dynamic viscosity	:	650 mPa.s at 20 °C / 68 °F
Vapour density (air=1)	:	at < 150 °C / < 302 °FNot applicable

10. STABILITY AND REACTIVITY

Stability	:	Stable. Hygroscopic.
Conditions to Avoid	:	Heat, flames, and sparks.
Materials to Avoid	:	Avoid contact with isocyanates, copper and copper alloys, zinc, strong oxidizing agents, and water.
Hazardous Decomposition Products	:	Unknown toxic products may be formed.
Hazardous Reactions	:	The reaction becomes progressively more vigorous and can be violent at higher temperatures if the miscibility of reaction partners is good or is supported by stirring or by the presence of solvents. Reacts with strong oxidising agents.

11. TOXICOLOGICAL INFORMATION

Basis for Assessment	:	Information given is based on product testing, and/or similar products, and/or components.
Acute Oral Toxicity	:	Expected to be of low toxicity: LD50 >2000 mg/kg , Rat
Acute Dermal Toxicity	:	Expected to be of low toxicity: LD50 >2000 mg/kg , Rat
Acute Inhalation Toxicity	:	Data not available.
Skin Irritation	:	Expected to be non-irritating to skin.
Eye Irritation	:	Expected to be non-irritating to eyes.
Respiratory Irritation	:	Data not available.
Sensitisation	:	Not expected to be a skin sensitiser.
Repeated Dose Toxicity	:	Data not available.
Mutagenicity	:	Not expected to be mutagenic.
Carcinogenicity	:	Data not available.
Reproductive and Developmental Toxicity	:	Data not available.

12. ECOLOGICAL INFORMATION

Acute Toxicity		
Fish	:	Expected to have low toxicity: LC/EC/IC50 > 1000 mg/l
Aquatic Invertebrates	:	Expected to have low toxicity: LC/EC/IC50 > 1000 mg/l
Algae	:	Expected to have low toxicity: LC/EC/IC50 > 1000 mg/l
Microorganisms	:	Expected to have low toxicity: LC/EC/IC50 > 100 mg/l
Chronic Toxicity		
Fish	:	Data not available.
Aquatic Invertebrates	:	Data not available.
Mobility	:	If product enters soil, one or more constituents will be highly mobile and may contaminate groundwater. Sinks in fresh water; may float or sink in seawater.
Bioaccumulation	:	Does not bioaccumulate significantly, MW > 1000.

13. DISPOSAL CONSIDERATIONS

Material Disposal	:	Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.

		Do not dispose into the environment, in drains or in water courses. Waste product should not be allowed to contaminate soil or water.
Container Disposal	:	Drain container thoroughly. After draining, vent in a safe place away from sparks and fire. Send to drum recoverer or metal reclaimer.
Local Legislation	:	Disposal should be in accordance with applicable regional, national, and local laws and regulations. Local regulations may be more stringent than regional or national requirements and must be complied with.

14. TRANSPORT INFORMATION

Land (as per ADR classification): Not regulated
This material is not classified as dangerous under ADR regulations.

IMDG
This material is not classified as dangerous under IMDG regulations.

IATA (Country variations may apply)
This material is either not classified as dangerous under IATA regulations or needs to follow country specific requirements.

Additional Information	**:**	**This product may be transported under nitrogen blanketing. Nitrogen is an odourless and invisible gas. Exposure to nitrogen may cause asphyxiation or death. Personnel must observe strict safety precautions when involved with a confined space entry.**

15. REGULATORY INFORMATION

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

EC Classification	:	Not classified as dangerous under EC criteria.	
Chemical Inventory Status			
AICS	:	Listed.	
DSL	:	Listed.	
INV (CN)	:	Listed.	
TSCA	:	Listed.	
KECI (KR)	:	Listed.	KE-24605
PICCS (PH)	:	Listed.	
EINECS	:		All components listed or polymer exempt.

16. OTHER INFORMATION

Additional Information	:	For further information, contact your local Shell company or agent.

Material Safety Data Sheet

MSDS Version Number	:	3.1
MSDS Effective Date	:	10.08.2011
MSDS Revisions	:	A vertical bar (|) in the left margin indicates an amendment from the previous version.
Uses and Restrictions	:	Advice in this document relates only to product as originally supplied. Other derivative chemicals will have different properties and hazards. Advice should be sought on their safe handling and use. Use for the manufacture of polyurethane products.
MSDS Distribution	:	The information in this document should be made available to all who may handle the product
Disclaimer	:	This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.