# **CARADOL SP37-25V**

Print Date 07.02.2025 Revision Date 07.02.2025 Version 0.0

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : CARADOL SP37-25V

Product code : U317P

Synonyms : Polyol

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the : Use for the manufacture of polyurethane products.

Substance/Mixture

Uses advised against : This product must not be used in applications other than those

listed in Section 1 without first seeking the advice of the

supplier.

This product must not be used in applications other than the

above without first seeking the advice of the supplier.

## 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier : Shell Trading (M.E.) Pvt. Ltd.

PO Box 16968 16968 Jebel Ali Unit.Arab Emir. : +971 4 331 6500

 Telephone
 : +971 4 331 6500

 Telefax
 : +971 4 332 1597

 Contact for Safety Data
 : sccmsds@shell.com

Sheet

## 1.4 Emergency telephone number

+ (65) 6542 9595 (Alert-SGS)

Other information : CARADOL is a trademark owned by Shell Trademark

Management B.V. and Shell Brands Inc. and used by affiliates

of Shell plc.

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

#### **GHS Classification**

Based on available data this substance / mixture does not meet the classification criteria.

#### 2.2 Label elements

# **CARADOL SP37-25V**

Print Date 07.02.2025 Revision Date 07.02.2025 Version 0.0

# **GHS-Labelling**

Hazard pictograms : No Hazard Symbol required

Signal word : No signal word

Hazard statements : PHYSICAL HAZARDS:

Not classified as a physical hazard under GHS criteria.

**HEALTH HAZARDS:** 

Not classified as a health hazard under GHS criteria.

**ENVIRONMENTAL HAZARDS:** 

Not classified as an environmental hazard under GHS criteria.

Precautionary statements : **Prevention:** 

No precautionary phrases.

Response:

No precautionary phrases.

Storage:

No precautionary phrases.

Disposal:

No precautionary phrases.

#### 2.3 Other hazards

### **SECTION 3: Composition/information on ingredients**

## 3.2 Mixtures

#### **Hazardous components**

Chemical name	CAS-No.	Classification	Concentration (% w/w)
Polyalkylene glycol	9082-00-2		70 - 80
Styrene-acrylonitrile polymer	57913-80-1		20 - 30

#### **SECTION 4: First aid measures**

### 4.1 Description of first aid measures

General advice : Not expected to be a health hazard when used under normal

conditions.

Protection of first-aiders : When administering first aid, ensure that you are wearing the

appropriate personal protective equipment according to the

incident, injury and surroundings.

If inhaled : No treatment necessary under normal conditions of use.

If symptoms persist, obtain medical advice.

				CARADOL SP37-25V
Prin	t Date 07.02.2025		Revision Date 07.02.2025	Version 0.0
In case	of skin contact	:	Remove contaminated clothing water and follow by washing w If persistent irritation occurs, of	ith soap if available.
In case	of eye contact	: Flush eye with copious quantities of water. Remove contact lenses, if present and easy to do. Continue rinsing. If persistent irritation occurs, obtain medical attention.		
If swallo	owed	:	In general no treatment is nece	essary unless large quantities

# 4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Not considered to be an inhalation hazard under normal

conditions of use.

Possible respiratory irritation signs and symptoms may include

a temporary burning sensation of the nose and throat,

coughing, and/or difficulty breathing.

No specific hazards under normal use conditions.

are swallowed, however, get medical advice.

Skin irritation signs and symptoms may include a burning

sensation, redness, or swelling.

Eye irritation signs and symptoms may include a burning sensation, redness, swelling, and/or blurred vision. Ingestion may result in nausea, vomiting and/or diarrhoea.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Call a doctor or poison control center for guidance.

Treat symptomatically. Following cases of gross overexposure, investigation of liver, kidney and eye function may be advisable. Records of such incidents should be maintained

for future reference.

### **SECTION 5: Firefighting measures**

### 5.1 Extinguishing media

Suitable extinguishing media : Large fires should only be fought by properly trained fire

fighters., Alcohol-resistant foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used

for small fires only.

Unsuitable extinguishing

media

: Do not use water in a jet.

#### 5.2 Special hazards arising from the substance or mixture

Specific hazards during

firefighting

: Will only burn if enveloped in a pre-existing fire. Hazardous

combustion products may include: Carbon dioxide

Unidentified organic and inorganic compounds. Toxic gases

Carbon monoxide.

	CAI	RADOL SP37-25V
Print Date 07.02.2025	Revision Date 07.02.2025	Version 0.0
5.3 Advice for firefighters		
Special protective equipment for firefighters	: Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).	
Specific extinguishing methods	: Standard procedure for chemical fires	
Further information	<ul> <li>Clear fire area of all non-emergency p</li> <li>All storage areas should be provided fighting facilities.</li> <li>Keep adjacent containers cool by spra</li> </ul>	with adequate fire

### **SECTION 6: Accidental release measures**

## 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions

Observe all relevant local and international regulations.

Avoid contact with skin, eyes and clothing.

Avoid inhaling vapour and/or mists.

Extinguish any naked flames. Do not smoke. Remove ignition

sources. Avoid sparks.

#### 6.2 Environmental precautions

Environmental precautions : Remove all possible sources of ignition in the surrounding

area.

Prevent from spreading or entering into drains, ditches or rivers by using sand, earth, or other appropriate barriers. Use appropriate containment to avoid environmental

contamination.

Ventilate contaminated area thoroughly.

#### 6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : For large liquid spills (> 1 drum), transfer by mechanical

means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely For small liquid spills (< 1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an

CARADOL S	P37-25V

Print Date 07.02.2025 Revision Date 07.02.2025 Version 0.0

appropriate absorbent material and dispose of safely. Remove

contaminated soil and dispose of safely.

Proper disposal should be evaluated based on regulatory status of this material (refer to Section 13), potential contamination from subsequent use and spillage, and regulations governing disposal in the local area.

#### 6.4 Reference to other sections

For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet., For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.

## **SECTION 7: Handling and storage**

General Precautions : Avoid breathing of or direct contact with material. Only use in

well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see

Section 8 of this Safety Data Sheet.

Use the information in this data sheet as input to a risk assessment of local circumstances to help determine

appropriate controls for safe handling, storage and disposal of

this material.

Ensure that all local regulations regarding handling and

storage facilities are followed.

#### 7.1 Precautions for safe handling

Advice on safe handling : In accordance with good industrial hygiene practices,

precautions should be taken to avoid breathing of material.

Use local exhaust extraction over processing area.

Avoid unintentional contact with isocyanates to prevent

uncontrolled polymerisation.

Avoid contact with skin, eyes and clothing.

Air-dry contaminated clothing in a well-ventilated area before

laundering.

Do not empty into drains. Handling Temperature:

Ambient.

When handling product in drums, safety footwear should be

worn and proper handling equipment should be used.

Extinguish any naked flames. Do not smoke. Remove ignition

sources. Avoid sparks.

Product Transfer : Lines should be purged with nitrogen before and after product

transfer. Keep containers closed when not in use.

#### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Refer to section 15 for any additional specific legislation covering the packaging and storage of this product.

	CARADOL	SP37-25V
Print Date 07.02.2025	Revision Date 07.02.2025	Version 0.0
Other data	Prevent all contact with water and with moist atmosphere. Tanks must be clean, dry and rust-free. Prevent ingress of water. Must be stored in a diked (bunded) well- ventilated area, away from sunlight, ignition sources and other sources of heat. Nitrogen blanket recommended for large tanks (capacity 100 m3 or higher). Drums should be stacked to a maximum of 3 high.	
Storage period	: 24 month(s)	
	Storage Temperature: Ambient.	
	Storage should be handled at temperatures suc viscosities are less than 500 cSt; typically at 25-should be fitted with heating coils in areas where temperatures are below the recommended prod temperatures. Heating coil skin temperatures shexceed 100 °C.	50 °C. Tanks the ambient uct handling
Packaging material	: <b>Suitable material:</b> Stainless steel.For container epoxy paint, zinc silicate paint. <b>Unsuitable material:</b> Copper.Copper alloys.	paints, use
7.3 Specific end use(s)		
Specific use(s)	: Not applicable	
	Ensure that all local regulations regarding handl storage facilities are followed.	ing and

# **SECTION 8: Exposure controls/personal protection**

### 8.1 Control parameters

**Occupational Exposure Limits** 

**Biological occupational exposure limits** 

No biological limit allocated.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Polyalkylene glycol : No DNEL value has been established.

**Monitoring Methods** 

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

# **CARADOL SP37-25V**

Print Date 07.02.2025 Revision Date 07.02.2025 Version 0.0

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA) , Germany http://www.dguv.de/inhalt/index.jsp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

## 8.2 Exposure controls

**Engineering measures**Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

Adequate ventilation to control airborne concentrations.

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

#### **General Information**

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

#### Personal protective equipment

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Eye protection : If material is handled such that it could be splashed into eyes,

protective eyewear is recommended.

Hand protection

Remarks : Where hand contact with the product may occur the use of

gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. Longer term protection: Nitrile rubber. Incidental contact/Splash protection: PVC, neoprene or nitrile rubber gloves For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the

	CA	RADOL SP37-25V		
Print Date 07.02.2025	Revision Date 07.02.2025	Version 0.0		
	same but recognize that suitable gloprotection may not be available and breakthrough time maybe acceptable maintenance and replacement regime thickness is not a good predictor of good chemical as it is dependent on the exployer material. Glove thickness shouthan 0.35 mm depending on the glove Suitability and durability of a glove is e.g. frequency and duration of contar glove material, dexterity. Always see suppliers. Contaminated gloves should be worn on clean hands. After us should be washed and dried thoroug perfumed moisturizer is recommended.	in this case a lower e so long as appropriate nes are followed. Glove glove resistance to a xact composition of the uld be typically greater we make and model. dependent on usage, act, chemical resistance of ek advice from glove uld be replaced. Personal e hand care. Gloves must using gloves, hands ghly. Application of a non-		
Skin and body protection	: Skin protection is not ordinarily requi work clothes. It is good practice to wear chemical i	•		
Respiratory protection	: No respiratory protection is ordinarily conditions of use. In accordance with good industrial hyprecautions should be taken to avoid	ygiene practices,		
Hygiene measures	: Wash hands before eating, drinking, toilet. Launder contaminated clothing			
Environmental exposure controls				
General advice	<ul> <li>Local guidelines on emission limits for must be observed for the discharge of vapour.</li> <li>Minimise release to the environment assessment must be made to ensure environmental legislation.</li> <li>Information on accidental release messection 6.</li> </ul>	of exhaust air containing  t. An environmental e compliance with local		

# **SECTION 9: Physical and chemical properties**

# 9.1 Information on basic physical and chemical properties

Appearance : Viscous liquid.

Colour : white
Odour : odourless

Odour Threshold : Data not available

# **CARADOL SP37-25V**

Print Date 07.02.2025 Revision Date 07.02.2025 Version 0.0

рΗ : Not applicable

Melting / freezing point : -18 °C Pour point -18 °C

Boiling point/boiling range Data not available Flash point

: Typical > 200 °C

Method: ASTM D93 (PMCC)

: Data not available Evaporation rate

Flammability

Flammability (solid, gas) : Data not available

Lower explosion limit and upper explosion limit / flammability limit

Upper explosion limit : Data not available Lower explosion limit : Data not available

Vapour pressure : Data not available (50 °C)

Relative vapour density : Data not available Relative density : Data not available Density : 1.020 kg/m3 (25 °C)

Method: ASTM D4052

Solubility(ies)

Water solubility : negligible

Partition coefficient: n-

octanol/water

: Data not available

Auto-ignition temperature : Data not available Decomposition temperature : Data not available

Viscosity

: Typical 2.000 mPa.s (20 °C) Viscosity, dynamic

Method: ASTM D445

Typical 50 mPa.s (> 100 °C)

Method: ASTM D445

Viscosity, kinematic : Data not available Explosive properties : No data available Oxidizing properties : Data not available

9/17 800001005691

# CARADOL SP37-25V

Print Date 07.02.2025 Revision Date 07.02.2025 Version 0.0

9.2 Other information

Surface tension : Data not available

Conductivity: > 10,000 pS/m

A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid, This material is not expected to be

a static accumulator.

Molecular weight : Data not available

# **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.

#### 10.2 Chemical stability

No hazardous reaction is expected when handled and stored according to provisions, Hygroscopic.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Polymerises exothermically with di-isocyanates at ambient

temperatures.

The reaction becomes progressively more vigorous and can be violent at higher temperatures if the miscibility of reaction partners is good or is supported by stirring or by the presence

of solvents.

Reacts with strong oxidising agents.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames, and sparks.

Product cannot ignite due to static electricity.

10.5 Incompatible materials

Materials to avoid : Avoid contact with isocyanates, copper and copper alloys,

zinc, strong oxidizing agents, and water.

10.6 Hazardous decomposition products

Hazardous decomposition

products

: Unknown toxic products may be formed.

### **SECTION 11: Toxicological information**

#### 11.1 Information on toxicological effects

# CARADOL SP37-25V

Print Date 07.02.2025 Revision Date 07.02.2025 Version 0.0

Basis for assessment : Information given is based on data obtained from similar

substances.

Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for

individual component(s).

Information on likely routes of :

exposure

Exposure may occur via inhalation, ingestion, skin absorption,

skin or eye contact, and accidental ingestion.

### **Acute toxicity**

## **Product:**

Acute oral toxicity : LD 50 : > 2.000 mg/kg

Remarks: Based on available data, the classification criteria

are not met.

Acute inhalation toxicity : Remarks: Based on available data, the classification criteria

are not met.

Acute dermal toxicity : LD 50 : > 2.000 mg/kg

Remarks: Low toxicity

Based on available data, the classification criteria are not met.

#### Skin corrosion/irritation

#### **Product:**

Remarks: Based on available data, the classification criteria are not met.

# Serious eye damage/eye irritation

### **Product:**

Remarks: Based on available data, the classification criteria are not met.

#### Respiratory or skin sensitisation

#### **Product:**

Remarks: Based on available data, the classification criteria are not met.

#### Germ cell mutagenicity

## **Product:**

: Remarks: Based on available data, the classification criteria

are not met.

# Carcinogenicity

#### **Product:**

# **CARADOL SP37-25V**

Print Date 07.02.2025 Revision Date 07.02.2025 Version 0.0

Remarks: Based on available data, the classification criteria are not met.

Material	GHS/CLP Carcinogenicity Classification
Polyalkylene glycol	No carcinogenicity classification.
Styrene-acrylonitrile polymer	No carcinogenicity classification.

### Reproductive toxicity

# **Product:**

Remarks: Based on available data, the classification criteria are not met.

# STOT - single exposure

### **Product:**

Remarks: Based on available data, the classification criteria are not met.

# STOT - repeated exposure

### **Product:**

Remarks: Based on available data, the classification criteria are not met.

# **Aspiration toxicity**

#### **Product:**

Not an aspiration hazard.

# **Further information**

### **Product:**

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

# **CARADOL SP37-25V**

Print Date 07.02.2025 Revision Date 07.02.2025 Version 0.0

# **SECTION 12: Ecological information**

## 12.1 Toxicity

Basis for assessment : Incomplete ecotoxicological data are available for this product.

> The information given below is based partly on a knowledge of the components and the ecotoxicology of similar products.

Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for

individual component(s).

**Product:** 

Toxicity to fish (Acute

toxicity)

: LC50 : > 100 mg/l

Remarks: Based on available data, the classification criteria

are not met.

Practically non toxic:

Toxicity to daphnia and other

aquatic invertebrates (Acute

toxicity)

: EC50 : > 100 mg/l

Remarks: Based on available data, the classification criteria

are not met.

Practically non toxic:

Toxicity to algae (Acute

toxicity)

: EC50: > 100 mg/l

Remarks: Practically non toxic:

Based on available data, the classification criteria are not met.

Toxicity to fish (Chronic

toxicity)

Toxicity to daphnia and other : Remarks: Data not available

aquatic invertebrates (Chronic toxicity)

Toxicity to bacteria (Acute

toxicity)

: Remarks: Data not available

: IC50 : > 100 mg/l

Remarks: Based on available data, the classification criteria

are not met.

Practically non toxic:

# 12.2 Persistence and degradability

#### **Product:**

Biodegradability : Remarks: Readily biodegradable.

No data available

### 12.3 Bioaccumulative potential

#### Product:

Bioaccumulation : Remarks: Does not bioaccumulate significantly.

**CARADOL SP37-25V** 

Print Date 07.02.2025 Revision Date 07.02.2025 Version 0.0

Partition coefficient: n-

octanol/water

: Remarks: Data not available

### 12.4 Mobility in soil

## **Product:**

Mobility : Remarks: If the product enters soil, one or more constituents

will or may be mobile and may contaminate groundwater.

#### 12.5 Results of PBT and vPvB assessment

No data available

#### 12.6 Other adverse effects

No data available

# **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Product : Recover or recycle if possible.

It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.

Do not dispose into the environment, in drains or in water

courses.

Waste product should not be allowed to contaminate soil or

water.

Disposal should be in accordance with applicable regional,

national, and local laws and regulations.

Local regulations may be more stringent than regional or

national requirements and must be complied with.

Contaminated packaging : Drain container thoroughly.

After draining, vent in a safe place away from sparks and fire.

Send to drum recoverer or metal reclaimer.

Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand.

Local legislation

# **SECTION 14: Transport information**

#### 14.1 UN number

ADR : Not regulated as a dangerous good

	CARADOL SP	37-25V
Print Date 07.02.2025	Revision Date 07.02.2025 Volume Volum	ersion 0.0
IMDG IATA	<ul><li>Not regulated as a dangerous good</li><li>Not regulated as a dangerous good</li></ul>	
14.2 Proper shipping name		
ADR IMDG IATA	<ul><li>Not regulated as a dangerous good</li><li>Not regulated as a dangerous good</li><li>Not regulated as a dangerous good</li></ul>	
14.3 Transport hazard class		
ADR IMDG IATA	<ul><li>Not regulated as a dangerous good</li><li>Not regulated as a dangerous good</li><li>Not regulated as a dangerous good</li></ul>	
14.4 Packing group		
IMDG IATA	<ul><li>Not regulated as a dangerous good</li><li>Not regulated as a dangerous good</li><li>Not regulated as a dangerous good</li></ul>	
14.5 Environmental hazards		
ADR IMDG	<ul><li>Not regulated as a dangerous good</li><li>Not regulated as a dangerous good</li></ul>	
14.6 Special precautions for user	3 3	
Remarks	: Special Precautions: Refer to Section 7, Handling & Sto for special precautions which a user needs to be aware needs to comply with in connection with transport.	
14.7 Maritime transport in bulk acco	ording to IMO instruments	
Pollution category Ship type Product name	<ul><li>: Y</li><li>: 3</li><li>: Acrylonitrile-Styrene Copolymer Dispersion in Polyether</li></ul>	Polyol
Additional Information	: This product may be transported under nitrogen blanket Nitrogen is an odourless and invisible gas. Exposure to nitrogen enriched atmospheres displaces available oxyg which may cause asphyxiation or death. Personnel mus observe strict safety precautions when involved with a confined space entry.  Transport in bulk according to Annex II of Marpol and th Code	gen t

# **SECTION 15: Regulatory information**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Other regulations : The regulatory information is not intended to be

comprehensive. Other regulations may apply to this material.

The components of this product are reported in the following inventories:

		CARADOL SP37-25V
Print Date 07.02.2025	Revision Date 07.02.2025	Version 0.0
TSCA AIIC DSL IECSC KECI NZIOC PICCS ENCS TCSI	<ul><li>Listed</li><li>Listed</li><li>Listed</li><li>Listed</li><li>Listed</li><li>Listed</li><li>Listed</li><li>Listed</li><li>Listed</li><li>Listed</li><li>Listed</li><li>Listed</li><li>Listed</li></ul>	

#### **SECTION 16: Other information**

Abbreviations and Acronyms : The standard abbreviations and acronyms used in this

document can be looked up in reference literature (e.g.

scientific dictionaries) and/or websites.

ACGIH = American Conference of Governmental Industrial

Hygienists

ADR = European Agreement concerning the International

Carriage of Dangerous Goods by Road

AICS = Australian Inventory of Chemical Substances ASTM = American Society for Testing and Materials

BEL = Biological exposure limits

BTEX = Benzene, Toluene, Ethylbenzene, Xylenes

CAS = Chemical Abstracts Service

CEFIC = European Chemical Industry Council CLP = Classification Packaging and Labelling

COC = Cleveland Open-Cup

DIN = Deutsches Institut fur Normung DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

DSL = Canada Domestic Substance List

EC = European Commission

EC50 = Effective Concentration fifty

ECETOC = European Center on Ecotoxicology and

**Toxicology Of Chemicals** 

ECHA = European Chemicals Agency

EINECS = The European Inventory of Existing Commercial

**Chemical Substances** 

EL50 = Effective Loading fifty

ENCS = Japanese Existing and New Chemical Substances

Inventory

EWC = European Waste Code

GHS = Globally Harmonised System of Classification and

# **CARADOL SP37-25V**

Print Date 07.02.2025 Revision Date 07.02.2025 Version 0.0

Labelling of Chemicals

IARC = International Agency for Research on Cancer

IATA = International Air Transport Association

IC50 = Inhibitory Concentration fifty

IL50 = Inhibitory Level fifty

IMDG = International Maritime Dangerous Goods

INV = Chinese Chemicals Inventory

IP346 = Institute of Petroleum test method N° 346 for the determination of polycyclic aromatics DMSO-extractables

KECI = Korea Existing Chemicals Inventory

LC50 = Lethal Concentration fifty LD50 = Lethal Dose fifty per cent.

LL/EL/IL = Lethal Loading/Effective Loading/Inhibitory loading

LL50 = Lethal Loading fifty

MARPOL = International Convention for the Prevention of

Pollution From Ships

NOEC/NOEL = No Observed Effect Concentration / No

Observed Effect Level

OE\_HPV = Occupational Exposure - High Production Volume

PBT = Persistent, Bioaccumulative and Toxic

PICCS = Philippine Inventory of Chemicals and Chemical

Substances

PNEC = Predicted No Effect Concentration

REACH = Registration Evaluation And Authorisation Of

Chemicals

RID = Regulations Relating to International Carriage of

Dangerous Goods by Rail SKIN\_DES = Skin Designation STEL = Short term exposure limit TRA = Targeted Risk Assessment

TSCA = US Toxic Substances Control Act

TWA = Time-Weighted Average

vPvB = very Persistent and very Bioaccumulative

## **Further information**

Training advice : Provide adequate information, instruction and training for

operators.

Other information : A vertical bar (|) in the left margin indicates an amendment

from the previous version.

Sources of key data used to

compile the Safety Data

Sheet

: The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU

IUCLID date base, EC 1272 regulation, etc).

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.