

SAFETY DATA SHEET

NEODOL 45-7

Version 5.0

Revision Date 26.03.2025

Print Date 02.04.2025

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Product name : NEODOL 45-7

Product code : V2459

CAS-No. : 68002-97-1

Synonyms : Alcohols, C14-15, ethoxylated

1.2 Identified relevant uses of the substance or mixture and restrictions on use

Recommended use of the chemical and restrictions on use

Recommended use : Use as a surfactant in various applications

Restrictions on use : This product must not be used in applications other than the above without first seeking the advice of the supplier.
This product must not be used in applications other than those listed in Section 1 without first seeking the advice of the supplier.

Other information : NEODOL is a trademark owned by Shell Trademark Management B.V. and Shell Brands Inc. and used by affiliates of Royal Dutch Shell plc.

1.3 Details of the supplier of the safety data sheet

Manufacturer or supplier's details

Manufacturer/Supplier : **Shell Chemicals Europe B.V.**
PO Box 2334
3000 CH Rotterdam
Netherlands

Telephone : +31 (0)10 441 5137 / +31 (0)10 441 5191

Telefax : +31 (0)20 716 8316 / +31 (0)20 713 9230

1.4 Emergency telephone number

Emergency telephone number : +44 (0) 1235 239 670 (NCEC) This telephone number is available 24 hours per day, 7 days per week 08 61555777 (Local Poison Centre)

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Acute toxicity (Oral) : Category 4

SAFETY DATA SHEET

NEODOL 45-7


Version 5.0

Revision Date 26.03.2025

Print Date 02.04.2025

Serious eye damage : Category 1
Short-term (acute) aquatic hazard : Category 1
Long-term (chronic) aquatic hazard : Category 2

2.2 Label elements

Hazard pictograms	:	
Signal word	:	Danger
Hazard statements	:	PHYSICAL HAZARDS: Not classified as a physical hazard according to CLP criteria. HEALTH HAZARDS: H302 Harmful if swallowed. H318 Causes serious eye damage. ENVIRONMENTAL HAZARDS: H400 Very toxic to aquatic life. H411 Toxic to aquatic life with long lasting effects.
Precautionary statements	:	Prevention: P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P273 Avoid release to the environment. Response: P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310 Immediately call a POISON CENTER/doctor. P391 Collect spillage. Storage: No precautionary phrases. Disposal: P501 Dispose of contents/ container to an approved waste disposal plant.

2.3 Other hazards

None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Substance

SAFETY DATA SHEET

NEODOL 45-7

Version 5.0

Revision Date 26.03.2025

Print Date 02.04.2025

3.1 Substances

Hazardous components

Chemical name	CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration (% w/w)
C14-15 Alcohol Ethoxylate	68002-97-1	Acute Tox. 4; H302 Eye Dam. 1; H318 Aquatic Acute 1; H400 Aquatic Chronic 2; H411	100

For explanation of abbreviations see section 16.

4. FIRST-AID MEASURES

4.1 Description of first aid measures

- General advice : Not expected to be a health hazard when used under normal conditions.
- If inhaled : No treatment necessary under normal conditions of use.
If symptoms persist, obtain medical advice.
- In case of skin contact : Remove contaminated clothing. Immediately flush skin with large amounts of water for at least 15 minutes, and follow by washing with soap and water if available. If needed, transport to the nearest medical facility for additional treatment.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses, if present and easy to do. Continue rinsing.
Transport to the nearest medical facility for additional treatment.
- If swallowed : Do not induce vomiting. If victim is alert, rinse mouth and drink 1/2 to 1 glass of water to help dilute the material. Do not give liquids to a drowsy, convulsing, or unconscious person.
Transport to nearest medical facility for additional treatment.

4.2 Protection of first-aiders

- Protection of first-aiders : When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.

4.3 Most important symptoms and effects, both acute and delayed

Most important symptoms and effects, both acute and delayed	: Not considered to be an inhalation hazard under normal conditions of use. Possible respiratory irritation signs and symptoms may include a temporary burning sensation of the nose and throat, coughing, and/or difficulty breathing. Skin irritation signs and symptoms may include a burning sensation, redness, swelling, and/or blisters. Corrosive to eyes. Contact can cause severe eye damage including chemical burns, pain, clouding of the eye surface, inflammation of the eye, and may result in permanent loss of vision. Swallowing of corrosive chemicals may cause immediate pain and burning in the mouth, throat, and stomach followed by vomiting and diarrhea. Burns and tearing of the esophagus and stomach are possible.
Notes to physician	: IMMEDIATE TREATMENT IS EXTREMELY IMPORTANT! Consult a Poison Control Centre for guidance. Treat symptomatically.

5. FIRE-FIGHTING MEASURES**5.1 Extinguishing media**

Suitable extinguishing media	: Alcohol-resistant foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
Unsuitable extinguishing media	: None

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting	: Carbon monoxide may be evolved if incomplete combustion occurs.
--------------------------------------	---

5.3 Recommendations for fire-fighters

Specific extinguishing methods	: Standard procedure for chemical fires. Clear fire area of all non-emergency personnel. Keep adjacent containers cool by spraying with water.
--------------------------------	--

Special protective equipment for firefighters : Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions :
Observe all relevant local and international regulations.
Notify authorities if any exposure to the general public or the environment occurs or is likely to occur.
Local authorities should be advised if significant spillages cannot be contained.
Avoid contact with spilled or released material. Immediately remove all contaminated clothing. For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet. For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.
Stay upwind and keep out of low areas.
Be ready for fire or possible exposure.

6.2 Environmental precautions

Environmental precautions : Prevent from spreading or entering into drains, ditches or rivers by using sand, earth, or other appropriate barriers.
Use appropriate containment to avoid environmental contamination.
Ventilate contaminated area thoroughly.

6.3 Methods and material for containment and cleaning up

Methods and materials for containment and cleaning up : For large liquid spills (> 1 drum), transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.
For small liquid spills (< 1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.

SAFETY DATA SHEET

NEODOL 45-7

Version 5.0

Revision Date 26.03.2025

Print Date 02.04.2025

6.4 Reference to other sections

For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet.,
For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

- | | |
|-------------------------|---|
| General Precautions | : Avoid breathing of or direct contact with material. Only use in well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet.
Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.
Ensure that all local regulations regarding handling and storage facilities are followed. |
| Advice on safe handling | : Avoid contact with skin, eyes and clothing.
Do not empty into drains. |
| Avoidance of contact | : Copper.
Copper alloys.
Strong oxidising agents.
Aluminum |
| Product Transfer | : Keep containers closed when not in use. Refer to guidance under Handling section. |

7.2 Conditions for safe storage, including any incompatibilities

- | | |
|-----------------------------|---|
| Conditions for safe storage | : Refer to section 15 for any additional specific legislation covering the packaging and storage of this product. |
| Other data | : Tanks should be fitted with heating coils in areas where the ambient temperatures are below the recommended product handling temperatures. Heating coil skin temperatures should not exceed 100 °C.
Bulk storage tanks should be diked (bunded).
Vapours from tanks should not be released to atmosphere.
Breathing losses during storage should be controlled by a suitable vapour treatment system.
Nitrogen blanket recommended for large tanks (capacity 100 m3 or higher).
Insulation (lagging) will minimize heat loss in areas of low ambient temperature.
Tanks should be fitted with heating coils in areas where ambient conditions can result in handling temperatures below the freezing point/pour point of the product. |

SAFETY DATA SHEET

NEODOL 45-7

Version 5.0

Revision Date 26.03.2025

Print Date 02.04.2025

Packaging material : Suitable material: Stainless steel., Epoxy resins, Polyester.
Unsuitable material: Aluminum, Copper., Copper alloys.

Container Advice : Containers, even those that have been emptied, can contain explosive vapours. Do not cut, drill, grind, weld or perform similar operations on or near containers.

7.3 Specific end use(s)

Specific use(s) : Use as a surfactant in various applications

Uses advised against : This product must not be used in applications other than the above without first seeking the advice of the supplier.
This product must not be used in applications other than those listed in Section 1 without first seeking the advice of the supplier.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Biological occupational exposure limits

No biological limit allocated.

8.2 Exposure controls

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods
<http://www.cdc.gov/niosh/>

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods
<http://www.osha.gov/>

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances
<http://www.hse.gov.uk/>

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA) , Germany
<http://www.dguv.de/inhalt/index.jsp>

L'Institut National de Recherche et de Sécurité, (INRS), France <http://www.inrs.fr/accueil>

Engineering measures : Adequate ventilation to control airborne concentrations below the exposure guidelines/limits.
Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.
Eye washes and showers for emergency use.
The level of protection and types of controls necessary will

vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

General Information

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

Do not ingest. If swallowed, then seek immediate medical assistance.

Personal protective equipment

Protective measures

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Respiratory protection : If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are unsuitable (e.g. airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. If air-filtering respirators are suitable for conditions of use: Select a filter suitable for the combination of organic gases and vapours and particles [Type A/Type P boiling point >65°C (149°F)].

Hand protection
Remarks

: Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. Longer term protection: Nitrile rubber gloves. Incidental contact/Splash protection: PVC or neoprene rubber gloves. For continuous contact we

recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

- Eye protection : Wear goggles for use against liquids and gas.
Wear full face shield if splashes are likely to occur.
- Skin and body protection : Skin protection is not required under normal conditions of use.
For prolonged or repeated exposures use impervious clothing over parts of the body subject to exposure.
If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to relevant Standard, and provide employee skin care programmes.
- Thermal hazards : Not applicable
- Hygiene measures : Wash hands before eating, drinking, smoking and using the toilet.
Launder contaminated clothing before re-use.

Environmental exposure controls

- General advice : Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour.
Minimise release to the environment. An environmental assessment must be made to ensure compliance with local environmental legislation.
Information on accidental release measures are to be found in section 6.

9. PHYSICAL AND CHEMICAL PROPERTIES**9.1 Information on basic physical and chemical properties**

- Appearance : Hazy, white liquid above 19.4°C/67°F.

SAFETY DATA SHEET

NEODOL 45-7

Version 5.0

Revision Date 26.03.2025

Print Date 02.04.2025

Colour	: Data not available
Odour	: mild
Odour Threshold	: Data not available
pH	: Data not available
Melting / freezing point	: 22 - 24 °C / 72 - 75 °F
Boiling point/boiling range	: 260 °C / 500 °F
Flash point	: 190 °C / 374 °F
Evaporation rate	: Data not available
Flammability (solid, gas)	: Not applicable
Upper explosion limit	: Data not available
Lower explosion limit	: Data not available
Vapour pressure	: 0,1 hPa (23,9 °C / 75,0 °F)
Relative vapour density	: 9,0
Relative density	: 0,969Method: ASTM D4052
Density	: 969 kg/m ³ (40 °C / 104 °F) Method: ASTM D4052
Solubility(ies)	
Water solubility	: 1 g/l Slight, may form gel.
Partition coefficient: n-octanol/water	: Data not available
Auto-ignition temperature	: Data not available
Decomposition temperature	: Data not available
Viscosity	
Viscosity, dynamic	: Not applicable (20 °C / 68 °F)
Viscosity, dynamic	50 mPa.s (38 °C / 100 °F)
Viscosity, kinematic	: Data not available
Particle size	: Data not available

9.2 Other information

Explosive properties	: Not applicable
Oxidizing properties	: Data not available

SAFETY DATA SHEET

NEODOL 45-7

Version 5.0

Revision Date 26.03.2025

Print Date 02.04.2025

Surface tension	: Data not available
Conductivity	: Electrical conductivity: > 10,000 pS/m A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid, This material is not expected to be a static accumulator.
Molecular weight	: Data not available

10. STABILITY AND REACTIVITY

10.1 Reactivity

Stable at normal ambient temperature and pressure., May oxidise in the presence of air.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : None known.

10.4 Conditions to avoid

Conditions to avoid : Extremes of temperature and direct sunlight.
Product cannot ignite due to static electricity.

10.5 Incompatible materials

Materials to avoid : Copper.
Copper alloys.
Strong oxidising agents.
Aluminum

10.6 Hazardous decomposition products

: None expected under normal use conditions.

11. TOXICOLOGICAL INFORMATION

SAFETY DATA SHEET

NEODOL 45-7

Version 5.0

Revision Date 26.03.2025

Print Date 02.04.2025

11.1 Information on toxicological effects

Basis for assessment : Information given is based on product testing, and/or similar products, and/or components.
Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

Information on likely routes of exposure : Exposure may occur via inhalation, ingestion, skin absorption, skin or eye contact, and accidental ingestion.

Acute toxicity

Components:

C14-15 Alcohol Ethoxylate:

Acute oral toxicity : LD50 Rat: > 300 - <= 2000 mg/kg
Remarks: Harmful if swallowed.

Acute inhalation toxicity : Remarks: Based on available data, the classification criteria are not met.

Acute dermal toxicity : LD50 Rabbit: > 2000 - <= 5000 mg/kg
Remarks: May be harmful in contact with skin.

Skin corrosion/irritation

Components:

C14-15 Alcohol Ethoxylate:

Remarks: Not irritating to skin.

Serious eye damage/eye irritation

Components:

C14-15 Alcohol Ethoxylate:

Remarks: Causes serious eye damage.

Respiratory or skin sensitisation

Components:

C14-15 Alcohol Ethoxylate:

Test Method: Skin sensitisation

Remarks: Not a sensitiser.

Based on available data, the classification criteria are not met.

Test Method: Respiratory sensitisation

Remarks: Not a sensitiser.

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

SAFETY DATA SHEET

NEODOL 45-7

Version 5.0

Revision Date 26.03.2025

Print Date 02.04.2025

Components:

C14-15 Alcohol Ethoxylate:

Remarks: Non mutagenic

Carcinogenicity

Components:

C14-15 Alcohol Ethoxylate:

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

Material	GHS/CLP Carcinogenicity Classification
C14-15 Alcohol Ethoxylate	No carcinogenicity classification.

Reproductive toxicity

Components:

C14-15 Alcohol Ethoxylate:

Remarks: Does not impair fertility., Not a developmental toxicant.

STOT - single exposure

Components:

C14-15 Alcohol Ethoxylate:

Remarks: Based on available data, the classification criteria are not met.

STOT - repeated exposure

Components:

C14-15 Alcohol Ethoxylate:

Remarks: Based on available data, the classification criteria are not met.

Aspiration toxicity

11.2 Information on other hazards

Components:

C14-15 Alcohol Ethoxylate:

Not an aspiration hazard.

Further information

Components:

C14-15 Alcohol Ethoxylate:

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

SAFETY DATA SHEET

NEODOL 45-7

Version 5.0

Revision Date 26.03.2025

Print Date 02.04.2025

12. ECOLOGICAL INFORMATION

Basis for assessment : Incomplete ecotoxicological data are available for this product. The information given below is based partly on a knowledge of the components and the ecotoxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

12.1 Toxicity

Components:

C14-15 Alcohol Ethoxylate :

Toxicity to fish (Acute toxicity) : Remarks: Very toxic.
LC/EC/IC50 < 1 mg/l

Toxicity to crustacean (Acute toxicity) : Remarks: Very toxic.
LC/EC/IC50 < 1 mg/l

Toxicity to algae/aquatic plants (Acute toxicity) : Remarks: Very toxic.
LC/EC/IC50 < 1 mg/l

M-Factor (Short-term (acute) aquatic hazard) : 1

Toxicity to microorganisms (Acute toxicity) : Remarks: LC/EC/IC50 > 100 mg/l
Practically non toxic:
Based on available data, the classification criteria are not met.

Toxicity to fish (Chronic toxicity) : Remarks: NOEC/NOEL > 0.1 - <=1.0 mg/l

Toxicity to crustacean(Chronic toxicity) : Remarks: NOEC/NOEL > 0.01 - <=0.1 mg/l

12.2 Persistence and degradability

Components:

C14-15 Alcohol Ethoxylate :

Biodegradability : Biodegradation: 80 %
Exposure time: 28 d
Method: OECD Test Guideline 301F
Remarks: Readily biodegradable.

12.3 Bioaccumulative potential

SAFETY DATA SHEET

NEODOL 45-7

Version 5.0

Revision Date 26.03.2025

Print Date 02.04.2025

Product:

Partition coefficient: n-octanol/water : Remarks: Data not available

Components:

C14-15 Alcohol Ethoxylate :

Bioaccumulation : Remarks: Bioaccumulation is unlikely to occur due to metabolism and excretion.
Data estimated using read-across from similar substances

12.4 Mobility in soil

Components:

C14-15 Alcohol Ethoxylate :

Mobility : Remarks: Dissolves in water., If the product enters soil, one or more constituents will or may be mobile and may contaminate groundwater.

12.5 Other adverse effects

No data available

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Waste from residues : Recover or recycle if possible.
It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.
Do not dispose into the environment, in drains or in water courses.
Waste product should not be allowed to contaminate soil or water.

Disposal should be in accordance with applicable regional, national, and local laws and regulations.
Local regulations may be more stringent than regional or national requirements and must be complied with.

Contaminated packaging : Drain container thoroughly.
After draining, vent in a safe place away from sparks and fire.

SAFETY DATA SHEET

NEODOL 45-7

Version 5.0

Revision Date 26.03.2025

Print Date 02.04.2025

Residues may cause an explosion hazard.
Do not puncture, cut, or weld uncleaned drums.
Send to drum recoverer or metal reclaimer.

14. TRANSPORT INFORMATION

14.1 UN number or ID number

ADR : 3082
IMDG : 3082
IATA : 3082

14.2 UN proper shipping name

ADR : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,
N.O.S.
(ALCOHOL C14-C15 POLY(7)ETHOXYLATE)
IMDG : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,
N.O.S.
(ALCOHOL C14-C15 POLY(7)ETHOXYLATE)
IATA : Environmentally hazardous substances, liquid, n.o.s.
(ALCOHOL C14-C15 POLY(7)ETHOXYLATE)

14.3 Transport hazard class(es)

ADR : 9
IMDG : 9
IATA : 9

14.4 Packing group

ADR
Packing group : III
Classification Code : M6
Hazard Identification Number : 90
Labels : 9
IMDG
Packing group : III
Labels : 9
IATA
Packing group : III
Labels : 9

14.5 Environmental hazards

ADR
Environmentally hazardous : yes
IMDG
Marine pollutant : yes

14.6 Special precautions for user

SAFETY DATA SHEET

NEODOL 45-7

Version 5.0

Revision Date 26.03.2025

Print Date 02.04.2025

Remarks : Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

14.7 Maritime transport in bulk according to IMO instruments

Pollution category : Y
Ship type : 2
Product name : Alcohol (C12-C16) poly (7-19) ethoxylates

Additional Information : This product may be transported under nitrogen blanketing. Nitrogen is an odourless and invisible gas. Exposure to nitrogen may cause asphyxiation or death. Personnel must observe strict safety precautions when involved with a confined space entry.

Transport in bulk according to Annex II of Marpol and the IBC Code

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

Other international regulations

The components of this product are reported in the following inventories:

DSL : Listed
IECSC : Listed
ENCS : Listed
TSCA : Listed
KECI : Listed
NZIoC : Listed
TCSI : Listed
AIRC : Listed
PICCS : Listed

16. OTHER INFORMATION

Full text of H-Statements

H302 Harmful if swallowed.
H318 Causes serious eye damage.
H400 Very toxic to aquatic life.
H411 Toxic to aquatic life with long lasting effects.

SAFETY DATA SHEET

NEODOL 45-7

Version 5.0

Revision Date 26.03.2025

Print Date 02.04.2025

Full text of other abbreviations

Acute Tox.	Acute toxicity
Aquatic Acute	Short-term (acute) aquatic hazard
Aquatic Chronic	Long-term (chronic) aquatic hazard
Eye Dam.	Serious eye damage

Abbreviations and Acronyms : The standard abbreviations and acronyms used in this document can be looked up in reference literature (e.g. scientific dictionaries) and/or websites.

Further information

Training advice : Provide adequate information, instruction and training for operators.

Other information : A vertical bar (|) in the left margin indicates an amendment from the previous version.

Sources of key data used to compile the Safety Data Sheet : The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID data base, EC 1272 regulation, etc).

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.