

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Ethylene oxide

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 28.03.2023 |
| 3.2 | 19.02.2024 | 800001000479 | Print Date 26.02.2024 |

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

| | |
|------------------------|--|
| Trade name | : Ethylene oxide |
| Product code | : U1111, U1114 |
| Registration number EU | : 01-2119432402-53-0011, 01-2119432402-53-0013 |
| Synonyms | : EO (Ethylene Oxide), Oxirane |
| CAS-No. | : 75-21-8 |

1.2 Relevant identified uses of the substance or mixture and uses advised against

| | |
|-----------------------------------|--|
| Use of the Sub- stance/Mixture | : Chemical intermediate. Please refer to section 16 and/or the annexes for the registered uses under REACH. |
| Uses advised against | : This product must not be used in applications other than the above without first seeking the advice of the supplier. |

1.3 Details of the supplier of the safety data sheet

| | |
|----------------------------------|---|
| Manufacturer/Supplier | : Shell Chemicals Europe B.V. PO Box 2334 3000 CH Rotterdam Netherlands |
| Telephone | : +31 (0)10 441 5137 / +31 (0)10 441 5191 |
| Telefax | : +31 (0)20 716 8316 / +31 (0)20 713 9230 |
| Contact for Safety Data Sheet | : sccmsds@shell.com |

1.4 Emergency telephone number

+44 (0) 1235 239 670 (This telephone number is available 24 hours per day, 7 days per week)
Instituto Nacional de Toxicologia: +34 91 562 04 20
+44 (0) 1235 239 670 (Este número de teléfono esta disponibles las 24 horas del día, 7 días de la semana)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

| | |
|-------------------------------------|---|
| Flammable gases, Category 1A | H220: Extremely flammable gas. |
| Chemically unstable gas, Category A | H230: May react explosively even in the absence of air. |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Ethylene oxide

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 28.03.2023 |
| 3.2 | 19.02.2024 | 800001000479 | Print Date 26.02.2024 |

| | |
|--|---|
| Gases under pressure, Liquefied gas | H280: Contains gas under pressure; may explode if heated. |
| Acute toxicity, Category 3, Oral | H301: Toxic if swallowed. |
| Skin corrosion, Category 1 | H314: Causes severe skin burns and eye damage. |
| Serious eye damage, Category 1 | H318: Causes serious eye damage. |
| Acute toxicity, Category 3, Inhalation | H331: Toxic if inhaled. |
| Specific target organ toxicity - single exposure, Category 3, Central nervous system | H336: May cause drowsiness or dizziness. |
| Specific target organ toxicity - single exposure, Category 3, Respiratory system | H335: May cause respiratory irritation. |
| Germ cell mutagenicity, Category 1B | H340: May cause genetic defects. |
| Carcinogenicity, Category 1B | H350: May cause cancer. |
| Reproductive toxicity, Category 1B | H360Fd: May damage fertility. Suspected of damaging the unborn child. |
| Specific target organ toxicity - repeated exposure, Category 1, Central nervous system | H372: Causes damage to organs through prolonged or repeated exposure. |

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements :

| | |
|-----------------|---|
| H220 | Extremely flammable gas. |
| H230 | May react explosively even in the absence of air. |
| H280 | Contains gas under pressure; may explode if heated. |
| HEALTH HAZARDS: | |
| H301 | Toxic if swallowed. |
| H314 | Causes severe skin burns and eye damage. |
| H318 | Causes serious eye damage. |
| H331 | Toxic if inhaled. |
| H335 | May cause respiratory irritation. |
| H336 | May cause drowsiness or dizziness. |
| H340 | May cause genetic defects. |
| H350 | May cause cancer. |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Ethylene oxide

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 28.03.2023 |
| 3.2 | 19.02.2024 | 800001000479 | Print Date 26.02.2024 |

H360Fd May damage fertility. Suspected of damaging the unborn child.

H372 Causes damage to organs (Central nervous system) through prolonged or repeated exposure.

ENVIRONMENTAL HAZARDS:

Not classified as environmental hazard according to CLP criteria.

Precautionary statements :

Prevention:

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P377 Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

P381 In case of leakage, eliminate all ignition sources.

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician.

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

2.3 Other hazards

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Even with proper grounding and bonding, this material can still accumulate an electrostatic charge.

If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur.

Dangerous polymerisation can occur on contact with highly catalytic surfaces.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Ethylene oxide

Version 3.2 Revision Date: 19.02.2024 SDS Number: 800001000479 Date of last issue: 28.03.2023
Print Date 26.02.2024

Highly reactive.
This material is shipped under pressure.
Exposure to rapidly expanding gases may cause frost burns to eyes and/or skin.
Liquid solutions of ethylene oxide cause serious chemical burns of the skin and eye lesions. The severity of injury will vary depending on the concentration and duration of skin contact. Concentrations of around 50% are the most dangerous, however a 1% solution of EO in water and gaseous EO dissolved in sweat can also cause damage to the skin. The onset of effects may be delayed for several hours.
Causes burns.

SECTION 3: Composition/information on ingredients

3.1 Substances

Components

| Chemical name | CAS-No. EC-No. | Concentration (% w/w) |
|----------------|----------------------|-----------------------|
| Ethylene Oxide | 75-21-8 200-849-9 | 100 |

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : DO NOT DELAY.
Keep victim calm. Obtain medical treatment immediately.
DO NOT attempt to rescue the victim unless proper respiratory protection is worn.
Take appropriate steps to avoid fire, explosion and inhalation hazards.
Contaminated leather articles including shoes cannot be decontaminated and should be destroyed to prevent reuse.
- Protection of first-aiders : When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.
- If inhaled : Call emergency number for your location / facility.
Remove to fresh air. Do not attempt to rescue the victim unless proper respiratory protection is worn. If the victim has difficulty breathing or tightness of the chest, is dizzy, vomiting, or unresponsive, give 100% oxygen with rescue breathing or Cardio-Pulmonary Resuscitation as required and transport to the nearest medical facility.
- In case of skin contact : DO NOT DELAY.
Call emergency number for your location / facility.
Remove contaminated clothing. Immediately flush skin with

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Ethylene oxide

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 28.03.2023 |
| 3.2 | 19.02.2024 | 800001000479 | Print Date 26.02.2024 |

large amounts of water for at least 15 minutes, and follow by washing with soap and water if available. If redness, swelling, pain and/or blisters occur, transport to the nearest medical facility for additional treatment.
All burns should receive medical attention.

In case of eye contact : Immediately flush eye(s) with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing.
Transport to the nearest medical facility for additional treatment.

If swallowed : Do not induce vomiting. If victim is alert, rinse mouth and drink 1/2 to 1 glass of water to help dilute the material. Do not give liquids to a drowsy, convulsing, or unconscious person. Transport to nearest medical facility for additional treatment. Rinse mouth.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Respiratory irritation signs and symptoms may include a temporary burning sensation of the nose and throat, coughing, and/or difficulty breathing.
Breathing of high vapour concentrations may cause central nervous system (CNS) depression resulting in dizziness, light-headedness, headache, nausea and loss of coordination. Continued inhalation may result in unconsciousness and death.
Corrosive to skin.
Contact with the skin can cause chemical burns, redness, swelling, and tissue damage.
Corrosive to eyes.
Contact can cause severe eye damage including chemical burns, pain, clouding of the eye surface, inflammation of the eye, and may result in permanent loss of vision.

Rapid release of gases which are liquids under pressure may cause frost burns of exposed tissues (skin, eye) due to evaporative cooling.
Peripheral nerve damage may be evidenced by impairment of motor function (incoordination, unsteady walk, or muscle weakness in the extremities, and/or loss of sensation in the arms and legs).

Other signs and symptoms of central nervous system (CNS) depression may include headache, nausea, and lack of coordination.
Symptoms may vary by the agent. Symptoms may extend to being locally corrosive to involving generalized systems including respiratory system, circulatory system, central nervous system (CNS), and may lead to death.
Burns and tearing of the esophagus and stomach are possible.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Ethylene oxide

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 28.03.2023 |
| 3.2 | 19.02.2024 | 800001000479 | Print Date 26.02.2024 |

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : IMMEDIATE TREATMENT IS EXTREMELY IMPORTANT!
Treat symptomatically.
Artificial respiration and/or oxygen may be necessary.
Call a doctor or poison control center for guidance.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Shut off supply. If not possible and no risk to surroundings, let the fire burn itself out.

Unsuitable extinguishing media : Do not use water in a jet.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : The vapour is heavier than air, spreads along the ground and distant ignition is possible.
Sustained fire attack on vessels may result in a Boiling Liquid Expanding Vapor Explosion (BLEVE).
Containers exposed to intense heat from fires should be cooled with large quantities of water.
Contents are under pressure and can explode when exposed to heat or flames.
As the vapours become lighter than air, the vapours may reach ignition sources at ground or elevated locations.

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear full protective clothing and self-contained breathing apparatus.

Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

Specific extinguishing methods : Standard procedure for chemical fires.

Further information : Clear fire area of all non-emergency personnel.
If the fire cannot be extinguished the only course of action is to evacuate immediately.
Large fires should only be fought by properly trained fire fighters.
Evacuate the area of all non-essential personnel.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Ethylene oxide

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 28.03.2023 |
| 3.2 | 19.02.2024 | 800001000479 | Print Date 26.02.2024 |

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : 6.1.1 For non emergency personnel:
Avoid contact with spilled or released material. For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet.
Isolate hazard area and deny entry to unnecessary or unprotected personnel.
Stay upwind and keep out of low areas.
Where there is a potential for direct exposure to the product use a gas tight suit.

6.1.2 For emergency responders:
Avoid contact with spilled or released material. For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet.
Isolate hazard area and deny entry to unnecessary or unprotected personnel.
Stay upwind and keep out of low areas.
Extinguish any naked flames. Do not smoke. Remove ignition sources. Avoid sparks.
Note - Since the danger of fire is so great, bunker gear worn over protective clothing is highly recommended.

6.2 Environmental precautions

Environmental precautions : Shut off leaks, if possible without personal risks. Remove all possible sources of ignition in the surrounding area and evacuate all personnel. Attempt to disperse the gas or to direct its flow to a safe location for example by using fog sprays. Take precautionary measures against static discharge. Ensure electrical continuity by bonding and grounding (earthing) all equipment. Monitor area with combustible gas meter.
Prevent from spreading or entering into waterways, sewers, basements or confined areas.
Use water spray barriers (curtains) to contain the toxic clouds.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Use water spray (fog) to reduce vapours or divert vapour cloud drift.
Do not use water in a jet.
Alcohol foam applied to surface of liquid pools may slow release of EO vapours into the atmosphere.

6.4 Reference to other sections

For personal protection see section 8., See Chapter 13 for information on disposal., Observe all relevant local regulations., Notify authorities if any exposure to the general public or the environment occurs or is likely to occur., Dike and contain spill water., Water dilution of at least 22:1 for open spaces or 100:1 for confined spaces is necessary to eliminate the fire hazard., Due to its high volatility, spilled liquid EO should either be allowed to evaporate or diluted with water as noted above., The vapour is

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Ethylene oxide

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 28.03.2023 |
| 3.2 | 19.02.2024 | 800001000479 | Print Date 26.02.2024 |

heavier than air, spreads along the ground and distant ignition is possible., Monitor area with combustible gas indicator., Run-off may cause a fire or explosion hazard., DOT recommends evacuating in all directions. For small spills the distance to evacuate is at least 200 feet; protect persons downwind to at least 0.1 miles during the day and 0.2 miles at night. For large spills the distance to evacuate is at least 400 feet; protect persons downwind to at least 0.2 miles during the day and 0.6 miles at night.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- | | |
|-------------------------|---|
| Technical measures | : Avoid breathing of or direct contact with material. Only use in well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material. Ensure that all local regulations regarding handling and storage facilities are followed. |
| Advice on safe handling | : Avoid exposure. Obtain special instructions before use. This product is intended for use in closed systems only. Ventilate workplace in such a way that the Occupational Exposure Limit (OEL) is not exceeded. The vapour is heavier than air, spreads along the ground and distant ignition is possible. Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment to reduce the risk. The vapours in the head space of the storage vessel may lie in the flammable/explosive range and hence may be flammable. Do NOT use compressed air for filling, discharging, or handling operations. |
| Product Transfer | : Refer to guidance under Handling section. Lines should be purged with nitrogen before and after product transfer. Refer to supplier for further product transfer instructions if required. |
| Hygiene measures | : Wash hands before eating, drinking, smoking and using the toilet. Launder contaminated clothing before re-use. |

7.2 Conditions for safe storage, including any incompatibilities

- | | |
|---|---|
| Requirements for storage areas and containers | : Refer to section 15 for any additional specific legislation covering the packaging and storage of this product. |
| Further information on storage stability | : Ethylene oxide (EO), an extremely flammable and toxic gas, and other hazardous vapours may evolve and collect in the headspace of storage tanks, transport vessels and other enclosed containers. Tanks must be specifically designed for use with this product. |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Ethylene oxide

Version 3.2 Revision Date: 19.02.2024 SDS Number: 800001000479 Date of last issue: 28.03.2023
Print Date 26.02.2024

- Tanks must be clean, dry and rust-free.
Keep container tightly closed.
Vapours from tanks should not be released to atmosphere.
Breathing losses during storage should be controlled by a suitable vapour treatment system.
Nitrogen blanket recommended.
Cleaning, inspection and maintenance of storage tanks is a specialist operation, which requires the implementation of strict procedures and precautions.
Keep away from flammables, oxidizing agents, and corrosives.
Storage Temperature:
30 °C / 86 °F maximum.
Potential exists for runaway reaction at elevated temperatures in the presence of strong bases and salts of strong bases.
Must be stored in a diked (bunded) well-ventilated area, away from sunlight, ignition sources and other sources of heat.
A reliable fixed sprinkler/deluge system should be installed.
- Packaging material : Suitable material: Stainless steel., Mild steel., Carbon steel
Unsuitable material: Compatibility should be checked with the manufacturer.
- Container Advice : Containers, even those that have been emptied, can contain explosive vapours. Do not cut, drill, grind, weld or perform similar operations on or near containers.

7.3 Specific end use(s)

- Specific use(s) : Please refer to section 16 and/or the annexes for the registered uses under REACH.
- Ensure that all local regulations regarding handling and storage facilities are followed.
See additional references that provide safe handling practices: American Petroleum Institute 2003 (Protection Against Ignitions Arising out of Static, Lightning and Stray Currents) or National Fire Protection Agency 77 (Recommended Practices on Static Electricity).
IEC/TS 60079-32-1: Electrostatic hazards, guidance

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

| Components | CAS-No. | Value type (Form of exposure) | Control parameters | Basis |
|--|---------|-------------------------------|--------------------------------|--------|
| Ethylene Oxide | 75-21-8 | VLA-ED | 1 ppm 1,8 mg/m ³ | ES VLA |
| Further information: Substances that are suspected to be toxic to human reproduction. Classification in category 1B is based primarily on the existence of | | | | |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Ethylene oxide

Version 3.2 Revision Date: 19.02.2024 SDS Number: 800001000479 Date of last issue: 28.03.2023
Print Date 26.02.2024

| | | | | |
|----------------|---|-----|--------------------|--|
| | data from animal studies., Suspected human carcinogen - based on on existing animal test results, Substances that are suspected to induce inheritable mutations in human germ cells, Skin | | | |
| Ethylene Oxide | | TWA | 1 ppm 1,8 mg/m3 | 2004/37/EC |
| | Further information: Skin, Carcinogens or mutagens | | | |
| Ethylene Oxide | | TWA | 1 ppm 1,8 mg/m3 | Shell Internal Standard (SIS) for 8-12 hour TWA. |

Biological occupational exposure limits

No biological limit allocated.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

| Substance name | End Use | Exposure routes | Potential health effects | Value |
|----------------|---------|-----------------|----------------------------|-----------|
| Ethylene Oxide | Workers | Inhalation | Acute local effects | 5 mg/m3 |
| Ethylene Oxide | Workers | Inhalation | Long-term systemic effects | 1,6 mg/m3 |

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

| Substance name | Environmental Compartment | Value |
|----------------|--|-------|
| Ethylene Oxide | | |
| Remarks: | Exposure assessments have not been presented for the environment therefore PNEC values not required. | |

8.2 Exposure controls

Engineering measures

Read in conjunction with the Exposure Scenario for your specific use contained in the Annex. The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

Use sealed systems as far as possible.

Adequate explosion-proof ventilation to control airborne concentrations below the exposure guidelines/limits.

Local exhaust ventilation is recommended.

The American Industrial Hygiene Association has established emergency response planning guidelines (ERPG) for ethylene oxide. These guidelines are estimates of concentration ranges which alone could reasonably anticipate observing adverse effects.

Ethylene Oxide ERPG-2, 50 ppm, is a maximum airborne concentration below which individuals could be exposed for up to 1 hour without experiencing mild transient health effects.

Ethylene Oxide ERPG-3, 500 ppm, is a maximum airborne concentration below which it is believed that individuals could be exposed for up to 1 hour without experiencing or developing life threatening health effects.

Firewater monitors and deluge systems are recommended.

Eye washes and showers for emergency use.

General Information:

Consider technical advances and process upgrades (including automation) for the elimination of releases. Minimise exposure using measures such as closed systems, dedicated facilities and suitable general/local exhaust ventilation. Drain down systems and clear transfer lines prior to

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Ethylene oxide

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 28.03.2023 |
| 3.2 | 19.02.2024 | 800001000479 | Print Date 26.02.2024 |

breaking containment. Clean/flush equipment, where possible, prior to maintenance. Where there is potential for exposure: restrict access to authorised persons; provide specific activity training to operators to minimise exposures; wear suitable gloves and coveralls to prevent skin contamination; wear respiratory protection when there is potential for inhalation; clear up spills immediately and dispose of wastes safely. Ensure safe systems of work or equivalent arrangements are in place to manage risks. Regularly inspect, test and maintain all control measures. Consider the need for risk based health surveillance.

Do not ingest. If swallowed, then seek immediate medical assistance

Items that cannot be decontaminated should be destroyed (see Chapter 13).

Personal protective equipment

Read in conjunction with the Exposure Scenario for your specific use contained in the Annex. The provided information is made in consideration of the PPE directive (Council Directive 89/686/EEC) and the CEN European Committee for Standardisation (CEN) standards.

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Eye protection : Wear goggles for use against liquids and gas, combined with face shield with chin guard.

Approved to EU Standard EN166.

Hand protection

Remarks : 4Htm (PE/EVAL) or butyl rubber gloves, First Responder chemical suit. Neoprene, Polyvinyl Chloride (PVC) or Vitontm are not recommended.
Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. Longer term protection: Butyl rubber. Incidental contact/Splash protection: Nitrile rubber gloves. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moistur-

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Ethylene oxide

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 28.03.2023 |
| 3.2 | 19.02.2024 | 800001000479 | Print Date 26.02.2024 |

izer is recommended.

Skin and body protection : Where risk of splashing or in spillage clean up, use chemical resistant one-piece overall with integral hood, chemical resistant knee length boots and chemical resistant gloves. Otherwise use chemical resistant apron and gauntlets.

Protective clothing approved to EU Standard EN14605.

Respiratory protection : If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are unsuitable (e.g. airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. If air-filtering respirators are suitable for conditions of use:

Select a filter suitable for organic gases and vapours [Type AX boiling point < 65°C (149°F)] meeting EN14387.

An approved respirator should be used when making or breaking connections to an ethylene oxide rail car or when sampling this material.

The odour threshold for ethylene oxide is above 250 ppm. This is much greater than the OSHA exposure limits. Therefore, do not depend on sense of smell for warning. If you smell ethylene oxide, you are in danger. Absence of odour, though, does not assure low enough exposure levels; its vapour may deaden the sense of smell.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

| | |
|------------------------------|--------------------------|
| Physical state | : Liquid under pressure. |
| Colour | : clear |
| Odour | : Ethereal, sweet |
| Odour Threshold | : Data not available |
| Melting point/freezing point | : -112 °C |
| Boiling point/boiling range | : 10,6 °C |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Ethylene oxide

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 28.03.2023 |
| 3.2 | 19.02.2024 | 800001000479 | Print Date 26.02.2024 |

Flammability

Flammability (solid, gas) : Extremely flammable.

Lower explosion limit and upper explosion limit / flammability limit

Upper explosion limit /
upper flammability limit : 99,99 %(V)

Lower explosion limit /
Lower flammability limit : 2,6 %(V)

Flash point : -57 °C

Auto-ignition temperature : 428 °C

Decomposition temperature
Decomposition temperature : Data not available

pH : Not applicable

Viscosity

Viscosity, dynamic : 0,41 mPa.s (0 °C)
Method: ASTM D445

Viscosity, kinematic : Data not available

Solubility(ies)

Water solubility : completely miscible

Solubility in other solvents : Data not available

Partition coefficient: n-
octanol/water : log Pow: -0,3

Vapour pressure : 144,6 kPa (20 °C)

Relative density : Data not available

Density : 898 kg/m³ (0 °C)
Method: ASTM D4052

Relative vapour density : ca. 1,5

Particle characteristics

Particle size : Data not available

9.2 Other information

Explosive properties : Not applicable

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Ethylene oxide

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 28.03.2023 |
| 3.2 | 19.02.2024 | 800001000479 | Print Date 26.02.2024 |

Oxidizing properties : Not applicable

Evaporation rate : Data not available

Conductivity : Electrical conductivity: > 10,000 pS/m

A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid, This material is not expected to be a static accumulator.

Surface tension : Data not available

Molecular weight : 44 g/mol

SECTION 10: Stability and reactivity

10.1 Reactivity

The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.

10.2 Chemical stability

Stable under normal conditions of use.

Pure EO or EO vapour mixed with air or inert gases can decompose explosively. The violence of the explosion depends on pressure, temperature and concentration; the form and energy of the ignition source, and the type of container.

Reacts exothermically with bases (eg caustic soda), ammonia, primary and secondary amines, alcohols, water and acids.

10.3 Possibility of hazardous reactions

Hazardous reactions : Data not available

10.4 Conditions to avoid

Conditions to avoid : Heat, flames, and sparks.
Temperatures above 30 °C / 86 °F.
Prevent vapour accumulation.

In certain circumstances product can ignite due to static electricity.

10.5 Incompatible materials

Materials to avoid : Avoid contamination with organic bases, strong acids, ammonia, copper, silver, magnesium and their salts, anhydrous chlorides of iron, tin and aluminium, and alkali metal hydroxides.

10.6 Hazardous decomposition products

Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids and gases including carbon monoxide, carbon dioxide, sulphur oxides and unidentified or-

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Ethylene oxide

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 28.03.2023 |
| 3.2 | 19.02.2024 | 800001000479 | Print Date 26.02.2024 |

ganic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure : Exposure may occur via inhalation, ingestion, skin absorption, skin or eye contact, and accidental ingestion.
This material penetrates the intact skin and eye rapidly as a liquid or mist, producing severe burns.

Acute toxicity

Components:

Ethylene Oxide:

| | |
|---------------------------|---|
| Acute oral toxicity | : LD 50 (Rat, male): > 50 - <= 300 mg/kg Method: Literature data Remarks: Toxic if swallowed. |
| Acute inhalation toxicity | : LC 50 (Rat, male): > 500 - <= 2500 ppm Exposure time: 4 h Test atmosphere: gas Method: Literature data Remarks: Toxic if inhaled. High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea; continued inhalation may result in unconsciousness and/or death. |
| Acute dermal toxicity | : Remarks: Based on available data, the classification criteria are not met. |

Skin corrosion/irritation

Components:

Ethylene Oxide:

| | |
|---------|--|
| Species | : Rabbit |
| Method | : Acceptable non-standard method. |
| Remarks | : Causes severe skin burns and eye damage. Liquid solutions of ethylene oxide cause serious chemical burns of the skin and eye lesions. The severity of injury will vary depending on the concentration and duration of skin contact. Rapid release of gases which are liquids under pressure may cause frost burns of exposed tissues (skin, eye) due to evaporative cooling. |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Ethylene oxide

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 28.03.2023 |
| 3.2 | 19.02.2024 | 800001000479 | Print Date 26.02.2024 |

Serious eye damage/eye irritation

Components:

Ethylene Oxide:

| | | |
|---------|---|----------------------------|
| Species | : | Rabbit |
| Method | : | Literature data |
| Remarks | : | Causes serious eye damage. |

Respiratory or skin sensitisation

Components:

Ethylene Oxide:

| | | |
|---------|---|---|
| Species | : | Guinea pig |
| Method | : | Literature data |
| Remarks | : | Based on available data, the classification criteria are not met. |

Germ cell mutagenicity

Components:

Ethylene Oxide:

| | | |
|-----------------------|---|--|
| Genotoxicity in vitro | : | Method: OECD Test Guideline 471 Remarks: May cause genetic defects. |
|-----------------------|---|--|

| | | |
|--|---|--|
| | : | Method: Literature data Remarks: May cause genetic defects. |
|--|---|--|

| | | |
|----------------------|---|---|
| Genotoxicity in vivo | : | Species: Mouse Application Route: Inhalation Method: Literature data Remarks: May cause genetic defects. |
|----------------------|---|---|

| | | |
|------------------------------------|---|----------------------------|
| Germ cell mutagenicity- Assessment | : | May cause genetic defects. |
|------------------------------------|---|----------------------------|

Carcinogenicity

Components:

Ethylene Oxide:

| | | |
|-------------------|---|----------------------|
| Species | : | Rat, male and female |
| Application Route | : | Inhalation |
| Method | : | Literature data |
| Remarks | : | May cause cancer. |

| | | |
|------------------------------|---|-------------------|
| Carcinogenicity - Assessment | : | May cause cancer. |
|------------------------------|---|-------------------|

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Ethylene oxide

Version 3.2 Revision Date: 19.02.2024 SDS Number: 800001000479 Date of last issue: 28.03.2023
Print Date 26.02.2024

| Material | GHS/CLP Carcinogenicity Classification |
|----------------|--|
| Ethylene Oxide | Carcinogenicity Category 1B |

| Material | Other Carcinogenicity Classification |
|----------------|---------------------------------------|
| Ethylene Oxide | IARC: Group 1: Carcinogenic to humans |

Reproductive toxicity

Components:

Ethylene Oxide:

Effects on fertility : Species: Rat
Sex: male and female
Application Route: Inhalation

Method: Literature data
Remarks: Based on available data, the classification criteria are not met., May impair fertility based on animal studies.

Reproductive toxicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

STOT - single exposure

Components:

Ethylene Oxide:

Exposure routes : Inhalation
Target Organs : Respiratory system
Remarks : May cause respiratory irritation.
High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea.

STOT - repeated exposure

Components:

Ethylene Oxide:

Exposure routes : Inhalation
Target Organs : Nervous system
Remarks : Causes damage to organs through prolonged or repeated exposure.

Repeated dose toxicity

Components:

Ethylene Oxide:

Species : Rat, male and female

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Ethylene oxide

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 28.03.2023 |
| 3.2 | 19.02.2024 | 800001000479 | Print Date 26.02.2024 |

| | | |
|-------------------|---|---|
| Application Route | : | Inhalation |
| Test atmosphere | : | vapour |
| Method | : | Test(s) equivalent or similar to OECD Test Guideline 453 |
| Target Organs | : | Nervous system |
| Remarks | : | Causes damage to organs through prolonged or repeated exposure. |

Aspiration toxicity

Components:

Ethylene Oxide:

Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

| | | |
|------------|---|---|
| Assessment | : | The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher. |
|------------|---|---|

Further information

Product:

| | | |
|---------|---|--|
| Remarks | : | Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s). |
|---------|---|--|

Components:

Ethylene Oxide:

| | | |
|---------|---|---|
| Remarks | : | Classifications by other authorities under varying regulatory frameworks may exist. |
|---------|---|---|

SECTION 12: Ecological information

12.1 Toxicity

Components:

Ethylene Oxide:

| | | |
|------------------|---|--|
| Toxicity to fish | : | LC50 (Pimephales promelas (fathead minnow)): 84 mg/l Exposure time: 96 h Method: Test(s) equivalent or similar to OECD Guideline 203 Remarks: Harmful LL/EL/IL50 >10 <= 100 mg/l |
|------------------|---|--|

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Ethylene oxide

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 28.03.2023 |
| 3.2 | 19.02.2024 | 800001000479 | Print Date 26.02.2024 |

| | |
|--|---|
| Toxicity to daphnia and other aquatic invertebrates | : LC50 (Daphnia magna (Water flea)): 137 - 300 mg/l Exposure time: 48 h Method: Test(s) equivalent or similar to OECD Guideline 202 Remarks: Practically non toxic: LC/EC/IC50 > 100 mg/l |
| Toxicity to algae/aquatic plants | : EC50 (Pseudokirchneriella subcapitata (algae)): 240 mg/l Exposure time: 96 h Method: Information given is based on data obtained from similar substances. Remarks: Practically non toxic: LC/EC/IC50 > 100 mg/l |
| Toxicity to microorganisms | : EC50 (Activated sludge, domestic waste): > 713 mg/l Exposure time: 3 h Method: OECD Test Guideline 209 Remarks: Practically non toxic: LC/EC/IC50 > 100 mg/l |
| Toxicity to fish (Chronic toxicity) | : Remarks: Data not available |
| Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) | : Remarks: Data not available |

12.2 Persistence and degradability

Components:

Ethylene Oxide:

| | |
|------------------|--|
| Biodegradability | : Biodegradation: 93 - 98 % Exposure time: 28 d Method: Information given is based on data obtained from similar substances. Remarks: Readily biodegradable. Rapidly hydrolyses in water and soil. |
|------------------|--|

12.3 Bioaccumulative potential

Components:

Ethylene Oxide:

| | |
|-----------------|--|
| Bioaccumulation | : Remarks: Does not have the potential to bioaccumulate significantly. |
|-----------------|--|

12.4 Mobility in soil

Components:

Ethylene Oxide:

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Ethylene oxide

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 28.03.2023 |
| 3.2 | 19.02.2024 | 800001000479 | Print Date 26.02.2024 |

| | | |
|----------|---|--|
| Mobility | : | Remarks: When released to air, transfers to soil or water by wet and dry deposition. |
|----------|---|--|

12.5 Results of PBT and vPvB assessment

Components:

Ethylene Oxide:

| | | |
|------------|---|---|
| Assessment | : | The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB.. |
|------------|---|---|

12.6 Endocrine disrupting properties

Product:

| | | |
|------------|---|---|
| Assessment | : | The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher. |
|------------|---|---|

12.7 Other adverse effects

Product:

| | | |
|-----------------------------------|---|--|
| Additional ecological information | : | Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s). |
|-----------------------------------|---|--|

SECTION 13: Disposal considerations

13.1 Waste treatment methods

| | | |
|------------------------|---|--|
| Product | : | Do not dispose into the environment, in drains or in water courses. Waste product should not be allowed to contaminate soil or water. Waste arising from a spillage or tank cleaning should be disposed of in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand. Disposal should be in accordance with applicable regional, national, and local laws and regulations. Local regulations may be more stringent than regional or national requirements and must be complied with. |
| Contaminated packaging | : | Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand. |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Ethylene oxide

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 28.03.2023 |
| 3.2 | 19.02.2024 | 800001000479 | Print Date 26.02.2024 |

SECTION 14: Transport information

14.1 UN number or ID number

| | | |
|------|---|------|
| ADR | : | 1040 |
| RID | : | 1040 |
| IMDG | : | 1040 |
| IATA | : | 1040 |

(Not permitted for transport)

14.2 UN proper shipping name

| | | |
|------|---|------------------------------|
| ADR | : | ETHYLENE OXIDE WITH NITROGEN |
| RID | : | ETHYLENE OXIDE WITH NITROGEN |
| IMDG | : | ETHYLENE OXIDE WITH NITROGEN |
| IATA | : | ETHYLENE OXIDE WITH NITROGEN |

14.3 Transport hazard class(es)

| | | |
|------|---|-----|
| ADR | : | 2 |
| RID | : | 2 |
| IMDG | : | 2.3 |
| IATA | : | 2.3 |

Not permitted for transport

14.4 Packing group

| | |
|------------------------------|------------------------------|
| ADR | |
| Packing group | : Not assigned by regulation |
| Classification Code | : 2TF |
| Hazard Identification Number | : 263 |
| Labels | : 2.3 (2.1) |
| RID | |
| Packing group | : Not assigned by regulation |
| Classification Code | : 2TF |
| Hazard Identification Number | : 263 |
| Labels | : 2.3 (2.1) |
| IMDG | |
| Packing group | : Not assigned by regulation |
| Labels | : 2.3 (2.1) |
| IATA | |
| Packing group | : Not Assigned |

14.5 Environmental hazards

| | |
|---------------------------|------|
| ADR | |
| Environmentally hazardous | : no |
| RID | |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Ethylene oxide

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 28.03.2023 |
| 3.2 | 19.02.2024 | 800001000479 | Print Date 26.02.2024 |

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

Remarks : Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

14.7 Maritime transport in bulk according to IMO instruments

| | |
|--------------------|------------------|
| Pollution category | : Not applicable |
| Ship type | : Not applicable |
| Product name | : Not applicable |

Additional Information : SHUNT WITH CARE (Label nr. 13 - for RID only) This product may be transported under nitrogen blanketing. Nitrogen is an odourless and invisible gas. Exposure to nitrogen may cause asphyxiation or death. Personnel must observe strict safety precautions when involved with a confined space entry.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - List of substances subject to authorisation (Annex XIV) : Product is not subject to Authorisation under REACH.

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. 20 Ethylene oxide

Other regulations:

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

Product is subject to El Real Decreto 840/2015, measures to control the risks inherent in serious accidents involving hazardous substances based on Seveso III directive (2012/18/EU).

The components of this product are reported in the following inventories:

AIIC : Listed

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Ethylene oxide

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 28.03.2023 |
| 3.2 | 19.02.2024 | 800001000479 | Print Date 26.02.2024 |

| | |
|-------|----------|
| DSL | : Listed |
| IECSC | : Listed |
| ENCS | : Listed |
| KECI | : Listed |
| NZIoC | : Listed |
| PICCS | : Listed |
| TSCA | : Listed |
| TCSI | : Listed |

15.2 Chemical safety assessment

A Chemical Safety Assessment has been carried out for this substance.

SECTION 16: Other information

Full text of other abbreviations

| | |
|------------------|---|
| 2004/37/EC | : Europe. Directive 2004/37/EC on the protection of workers from the risks related to exposure to carcinogens or mutagens at work |
| ES VLA | : Spain. Environmental Limits for exposure to Chemical agents - Table 1: Occupational Exposure Values |
| 2004/37/EC / TWA | : Long term exposure limit |
| ES VLA / VLA-ED | : Environmental Daily Limit Value |

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified;

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Ethylene oxide

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 28.03.2023 |
| 3.2 | 19.02.2024 | 800001000479 | Print Date 26.02.2024 |

NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECL - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Training advice : Provide adequate information, instruction and training for operators.

Other information : For Industry guidance and tools on REACH please visit the CEFIC website at <http://cefic.org/Industry-support>.
The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB.

A vertical bar (|) in the left margin indicates an amendment from the previous version.

This product is classified as R22/H302 Harmful if swallowed.
The same control advice applies to all uses of this product and is included in Section 8 of the SDS. An exposure scenario is not presented.

Sources of key data used to compile the Safety Data Sheet : The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID data base, EC 1272 regulation, etc).

Classification of the mixture:

| | |
|--------------------------|------|
| Flam. Gas 1A | H220 |
| Chem. Unst. Gas A | H230 |
| Press. Gas Liquefied gas | H280 |
| Acute Tox. 3 | H301 |
| Skin Corr. 1 | H314 |
| Eye Dam. 1 | H318 |
| Acute Tox. 3 | H331 |

Classification procedure:

| |
|--|
| On basis of test data. |
| On basis of test data. |
| On basis of test data. |
| Expert judgement and weight of evidence determination. |
| Expert judgement and weight of evidence determination. |
| Expert judgement and weight of evidence determination. |
| Expert judgement and weight of evidence determination. |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Ethylene oxide

| | | | |
|----------------|------------------------------|-----------------------------|---|
| Version 3.2 | Revision Date: 19.02.2024 | SDS Number: 800001000479 | Date of last issue: 28.03.2023 Print Date 26.02.2024 |
|----------------|------------------------------|-----------------------------|---|

| | | |
|-----------|--------|--|
| STOT SE 3 | H336 | Expert judgement and weight of evidence determination. |
| STOT SE 3 | H335 | Expert judgement and weight of evidence determination. |
| Muta. 1B | H340 | Expert judgement and weight of evidence determination. |
| Carc. 1B | H350 | Expert judgement and weight of evidence determination. |
| Repr. 1B | H360Fd | Expert judgement and weight of evidence determination. |
| STOT RE 1 | H372 | Expert judgement and weight of evidence determination. |

Identified Uses according to the Use Descriptor System

Uses - Worker

Title : Manufacture of substance
- Industrial

Uses - Worker

Title : Use as an intermediate
- Industrial

Uses - Worker

Title : Polymer production
- Industrial

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

ES / EN

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Ethylene oxide

Version 3.2 Revision Date: 19.02.2024 SDS Number: 800001000479 Date of last issue: 28.03.2023
Print Date 26.02.2024

Exposure Scenario - Worker

| | |
|-------------------------|---|
| 300000000703 | |
| SECTION 1 | EXPOSURE SCENARIO TITLE |
| Title | Manufacture of substance- Industrial |
| Use Descriptor | Sector of Use: SU3, SU8, SU9 Process Categories: PROC 1, PROC 2, PROC 3, PROC 8b Environmental Release Categories: ERC1 |
| Scope of process | Manufacture of the substance or use as a process chemical or extraction agent within closed or contained systems. Includes incidental exposures during recycling/ recovery, material transfers, storage, sampling, associated laboratory activities, maintenance and loading (including marine vessel/barge, road/rail car and bulk container). |

| | | |
|---|---|--|
| SECTION 2 | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES | |
| Additional Information | No exposure assessment presented for the environment. | |
| Section 2.1 | Control of Worker Exposure | |
| Product Characteristics | | |
| Physical form of product | Liquid, vapour pressure > 10 kPa at STP | |
| Concentration of the Substance in Mixture/Article | Covers use of substance/product up to 100% (unless stated differently)., | |
| Frequency and Duration of Use | | |
| Covers daily exposures up to 8 hours (unless stated differently). | | |
| Other Operational Conditions affecting Exposure | | |
| Assumes a good basic standard of occupational hygiene is implemented. | | |
| Contributing Scenarios | Risk Management Measures | |
| General measures (carcinogens). | Consider technical advances and process upgrades (including automation) for the elimination of releases. Minimise exposure using measures such as closed systems, dedicated facilities and suitable general/local exhaust ventilation. Drain down systems and clear transfer lines prior to breaking containment. Clean/flush equipment, where possible, prior to maintenance. Where there is potential for exposure: restrict access to authorised persons; provide specific activity training to operators to minimise exposures; wear suitable gloves and coveralls to prevent skin contamination; wear respiratory protection when its use is identified for certain contributing scenarios; clear up spills immediately and maintain all control measures. Consider the need for risk based health surveillance. | |
| General exposures (closed systems) | No other specific measures identified. | |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Ethylene oxide

Version 3.2 Revision Date: 19.02.2024 SDS Number: 800001000479 Date of last issue: 28.03.2023
Print Date 26.02.2024

| | |
|---|--|
| Process samplingProduct sampling. | Sample via a closed loop or other system to avoid exposure Wear a respirator conforming to EN140 with Type AX filter or better. |
| Bulk product storage | Store substance within a closed system. |
| Bulk transfersDedicated facility | Transfer via enclosed lines. Clear transfer lines prior to de-coupling. Wear a respirator conforming to EN140 with Type AX filter or better. |
| Equipment cleaning and maintenance | Drain down and flush system prior to equipment opening or maintenance. Wear a respirator conforming to EN140 with Type AX filter or better. |
| Section 2.2 | Control of Environmental Exposure |
| No exposure assessment presented for the environment. | |

| | |
|---|----------------------------|
| SECTION 3 | EXPOSURE ESTIMATION |
| Section 3.1 - Health | |
| The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated. | |

| |
|---|
| Section 3.2 -Environment |
| No exposure assessment presented for the environment. |

| | |
|---|--|
| SECTION 4 | GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO |
| Section 4.1 - Health | |
| Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. | |

| |
|---|
| Section 4.2 -Environment |
| No exposure assessment presented for the environment. |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Ethylene oxide

Version 3.2 Revision Date: 19.02.2024 SDS Number: 800001000479 Date of last issue: 28.03.2023
Print Date 26.02.2024

Exposure Scenario - Worker

| | |
|-------------------------|--|
| 300000000705 | |
| SECTION 1 | EXPOSURE SCENARIO TITLE |
| Title | Use as an intermediate- Industrial |
| Use Descriptor | Sector of Use: SU3, SU8, SU9 Process Categories: PROC 1, PROC 2, PROC 3, PROC 8b Environmental Release Categories: ERC6a |
| Scope of process | Use of substance as an intermediate within closed or contained systems (not related to Strictly Controlled Conditions). Includes incidental exposures during recycling/recovery, material transfers, storage, sampling, associated laboratory activities, maintenance and loading (including marine vessel/barge, road/rail car and bulk container). |

| | | |
|---|---|--|
| SECTION 2 | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES | |
| Additional Information | No exposure assessment presented for the environment. | |
| Section 2.1 | Control of Worker Exposure | |
| Product Characteristics | | |
| Physical form of product | Liquid, vapour pressure > 10 kPa at STP | |
| Concentration of the Substance in Mixture/Article | Covers use of substance/product up to 100% (unless stated differently)., | |
| Frequency and Duration of Use | | |
| Covers daily exposures up to 8 hours (unless stated differently). | | |
| Other Operational Conditions affecting Exposure | | |
| Assumes a good basic standard of occupational hygiene is implemented. | | |
| Contributing Scenarios | Risk Management Measures | |
| General measures (carcinogens). | Consider technical advances and process upgrades (including automation) for the elimination of releases. Minimise exposure using measures such as closed systems, dedicated facilities and suitable general/local exhaust ventilation. Drain down systems and clear transfer lines prior to breaking containment. Clean/flush equipment, where possible, prior to maintenance. Where there is potential for exposure: restrict access to authorised persons; provide specific activity training to operators to minimise exposures; wear suitable gloves and coveralls to prevent skin contamination; wear respiratory protection when its use is identified for certain contributing scenarios; clear up spills immediately and maintain all control measures. Consider the need for risk based health surveillance. | |
| General exposures (closed systems) | No other specific measures identified. | |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Ethylene oxide

Version 3.2 Revision Date: 19.02.2024 SDS Number: 800001000479 Date of last issue: 28.03.2023
Print Date 26.02.2024

| | |
|---|--|
| Process samplingProduct sampling. | Sample via a closed loop or other system to avoid exposure Wear a respirator conforming to EN140 with Type AX filter or better. |
| Bulk product storage | Store substance within a closed system. |
| Bulk transfersDedicated facility | Transfer via enclosed lines. Clear transfer lines prior to de-coupling. Wear a respirator conforming to EN140 with Type AX filter or better. |
| Equipment cleaning and maintenance | Drain down and flush system prior to equipment opening or maintenance. Wear a respirator conforming to EN140 with Type AX filter or better. |
| Section 2.2 | Control of Environmental Exposure |
| No exposure assessment presented for the environment. | |

| | |
|---|----------------------------|
| SECTION 3 | EXPOSURE ESTIMATION |
| Section 3.1 - Health | |
| The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated. | |

| |
|---|
| Section 3.2 -Environment |
| No exposure assessment presented for the environment. |

| | |
|---|--|
| SECTION 4 | GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO |
| Section 4.1 - Health | |
| Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. | |

| |
|---|
| Section 4.2 -Environment |
| No exposure assessment presented for the environment. |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Ethylene oxide

Version
3.2

Revision Date:
19.02.2024

SDS Number:
800001000479

Date of last issue: 28.03.2023
Print Date 26.02.2024

Exposure Scenario - Worker

300000000707

| SECTION 1 | EXPOSURE SCENARIO TITLE |
|------------------|---|
| Title | Polymer production- Industrial |
| Use Descriptor | Sector of Use: SU3, SU10 Process Categories: PROC 1, PROC 2, PROC 3, PROC 8b Environmental Release Categories: ERC 6C |
| Scope of process | Manufacture of polymers from monomers in continuous and batch processes. Including production, re-cycling and recovery, degassing, discharging, reactor maintenance and immediate polymer product formation (i.e. compounding, pelletisation, product off-gassing). |

| SECTION 2 | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES |
|---|---|
| Additional Information | No exposure assessment presented for the environment. |
| Section 2.1 | Control of Worker Exposure |
| Product Characteristics | |
| Physical form of product | Liquid, vapour pressure > 10 kPa at STP |
| Concentration of the Substance in Mixture/Article | Covers use of substance/product up to 100% (unless stated differently)., |
| Frequency and Duration of Use | |
| Covers daily exposures up to 8 hours (unless stated differently). | |
| Other Operational Conditions affecting Exposure | |
| Assumes a good basic standard of occupational hygiene is implemented. | |
| Contributing Scenarios | Risk Management Measures |
| General measures (carcinogens). | Consider technical advances and process upgrades (including automation) for the elimination of releases. Minimise exposure using measures such as closed systems, dedicated facilities and suitable general/local exhaust ventilation. Drain down systems and clear transfer lines prior to breaking containment. Clean/flush equipment, where possible, prior to maintenance. Where there is potential for exposure: restrict access to authorised persons; provide specific activity training to operators to minimise exposures; wear suitable gloves and coveralls to prevent skin contamination; wear respiratory protection when its use is identified for certain contributing scenarios; clear up spills immediately and maintain all control measures. Consider the need for risk based health surveillance. |
| General exposures (closed systems)Continuous process | No other specific measures identified. |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Ethylene oxide

Version 3.2 Revision Date: 19.02.2024 SDS Number: 800001000479 Date of last issue: 28.03.2023
Print Date 26.02.2024

| | |
|---|--|
| Use in contained batch processes | Handle substance within a closed system. |
| Process samplingProduct sampling. | Sample via a closed loop or other system to avoid exposure Wear a respirator conforming to EN140 with Type AX filter or better. |
| Bulk product storage | Store substance within a closed system. |
| Bulk transfersDedicated facility | Transfer via enclosed lines. Clear transfer lines prior to de-coupling. Wear a respirator conforming to EN140 with Type AX filter or better. |
| Equipment cleaning and maintenance | Drain down and flush system prior to equipment opening or maintenance. Wear a respirator conforming to EN140 with Type AX filter or better. |
| Section 2.2 | Control of Environmental Exposure |
| No exposure assessment presented for the environment. | |

| | |
|---|----------------------------|
| SECTION 3 | EXPOSURE ESTIMATION |
| Section 3.1 - Health | |
| The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated. | |

| |
|---|
| Section 3.2 -Environment |
| No exposure assessment presented for the environment. |

| | |
|---|--|
| SECTION 4 | GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO |
| Section 4.1 - Health | |
| Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. | |

| |
|---|
| Section 4.2 -Environment |
| No exposure assessment presented for the environment. |