

### 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

Material Name : CARADOL SP50-04

**Uses** : Use for the manufacture of polyurethane products.

Product Code : U318A

Supplier : SHELL EASTERN CHEMICALS (S)

A REGISTERED BUSINESS OF SHELL EASTERN

TRADING (PTE) LTD (UEN:198902087C)

The Metropolis Tower 1

9 North Buona Vista Drive, #07-01

Singapore 138588

Singapore

**Telephone** : +65 6384 8737 **Fax** : +65 6384 8454

**Emergency Telephone** 

Number

+ (65) 6542 9595 (Alert-SGS)

Other Information : CARADOL is a trademark owned by Shell Trademark

Management B.V. and Shell Brands Inc. and used by affiliates of

Royal Dutch Shell plc.

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

**Mixture Description** : Suspension of a solid polymeric material in a polyether polyol.

Synonyms : Polyol

**Hazardous Components** 

Chemical NameCASEINECSSymbol(s)R-phrase(s)Conc.Polyoxyalkylene9082-00-2NoneNone90.00 %

Triol

Polyurethane 66991-59-1 10.00 %

**Additional Information**: Refer to chapter 16 for full text of EC R-phrases.

# 3. HAZARDS IDENTIFICATION

**Health Hazards** : No specific hazards.

Safety Hazards : Not classified as flammable but will burn.

## 4. FIRST AID MEASURES

Inhalation : Remove to fresh air. If rapid recovery does not occur, transport

to nearest medical facility for additional treatment.

Skin Contact : Remove contaminated clothing. Flush exposed area with water

and follow by washing with soap if available.

1/7
Print Date 08.07.2014 000000001054
MSDS\_IN





Effective Date 22.03.2012

# **Material Safety Data Sheet**

**Eye Contact** : Flush eye with copious quantities of water. If persistent irritation

occurs, obtain medical attention.

Ingestion Wash out mouth with water and obtain medical attention.

Advice to Physician Treat symptomatically.

### 5. FIRE FIGHTING MEASURES

Clear fire area of all non-emergency personnel.

: Will only burn if enveloped in a pre-existing fire. Hazardous **Specific Hazards** 

combustion products may include: Carbon dioxide. Carbon monoxide. Unidentified organic and inorganic compounds. Toxic

products.

**Extinguishing Media** Large fires should only be fought by properly trained fire fighters.

> Alcohol-resistant foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small

apparatus.

**Unsuitable Extinguishing** 

Media

Do not use water in a jet.

**Protective Equipment for** 

Wear full protective clothing and self-contained breathing

**Firefighters** 

**Additional Advice** 

All storage areas should be provided with adequate fire fighting

facilities. Keep adjacent containers cool by spraying with water.

### 6. ACCIDENTAL RELEASE MEASURES

Observe all relevant local and international regulations. Avoid contact with spilled or released material. For guidance on selection of personal protective equipment see Chapter 8 of this Material Safety Data Sheet. See Chapter 13 for information on disposal.

Protective measures Avoid contact with spilled or released material. For guidance on

selection of personal protective equipment see Chapter 8 of this Material Safety Data Sheet. Avoid inhaling vapour and/or mists. Avoid contact with the skin. Prevent from spreading or entering into drains, ditches or rivers by using sand, earth, or other appropriate barriers. Use appropriate containment to avoid environmental contamination. Ventilate contaminated area

thoroughly.

**Clean Up Methods** For large liquid spills (> 1 drum), transfer by mechanical means

> such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely.

Remove contaminated soil and dispose of safely.

For small liquid spills (< 1 drum), transfer by mechanical means to a labelled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove

contaminated soil and dispose of safely.

Additional Advice Proper disposal should be evaluated based on regulatory status

of this material (refer to Section 13), potential contamination from subsequent use and spillage, and regulations governing

disposal in the local area.

2/7 Print Date 08.07.2014 00000001054



# 7. HANDLING AND STORAGE

**General Precautions** : Avoid breathing vapours or contact with material. Only use in

well ventilated areas. Wash thoroughly after handling. On guidance on selection of personal protective equipment see

Chapter 8 of this Material Safety Data Sheet. For

comprehensive advice on handling, product transfer, storage

and tank cleaning refer to the product supplier.

**Handling** : In accordance with good industrial hygiene practices,

precautions should be taken to avoid breathing of material. Use

local exhaust extraction over processing area. Avoid unintentional contact with isocyanates to prevent uncontrolled polymerisation. Avoid contact with skin, eyes, and clothing

polymerisation. Avoid contact with skin, eyes, and clothing. Air-dry contaminated clothing in a well-ventilated area before laundering. Do not empty into drains. Handling Temperature: Ambient. When handling product in drums, safety footwear should be worn and proper handling equipment should be used.

Storage : Prevent all contact with water and with moist atmosphere. Tanks

must be clean, dry and rust-free. Prevent ingress of water. Must be stored in a diked (bunded) well-ventilated area, away from sunlight, ignition sources and other sources of heat. Nitrogen blanket recommended for large tanks (capacity 100 m3 or higher). Drums should be stacked to a maximum of 3 high.

Maximum storage time: 12 months. Storage Temperature: Ambient.

Storage should be handled at temperatures such that viscosities are less than 500 cSt; typically at 25-50 °C. Tanks should be fitted with heating coils in areas where the ambient temperatures are below the recommended product handling temperatures. Heating coil skin temperatures should not exceed 100 °C.

Lines should be purged with nitrogen before and after product

transfer. Keep containers closed when not in use.

Unsuitable Materials : Copper. Copper alloys.

**Additional Information** : Ensure that all local regulations regarding handling and storage

facilities are followed. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and

disposal of this material.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

If the American Conference of Governmental Industrial Hygienists (ACGIH) value is provided on this document, it is provided for information only.

### **Occupational Exposure Limits**

None established.

**Product Transfer** 

**Exposure Controls**: Exhaust emission systems should be designed in accordance

with local conditions; the air should always be moved away from

3/7
Print Date 08.07.2014 000000001054



the source of vapour generation and the person working at this point. Adequate ventilation to control airborne concentrations.

Personal protective equipment (PPE) should meet

**Personal Protective** recommended national standards. Check with PPE suppliers. Equipment

**Respiratory Protection** No respiratory protection is ordinarily required under normal

conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of

material.

**Hand Protection** Where hand contact with the product may occur the use of

gloves approved to relevant standards (e.g. Europe: EN374, US: F739, AS/NZS:2161) made from the following materials may provide suitable chemical protection: Incidental contact/Splash protection: PVC. Neoprene rubber. Nitrile rubber. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Thin disposable gloves should be avoided for long

term use. When worn, use once and dispose.

Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a

non-perfumed moisturizer is recommended.

**Eye Protection** Chemical splash goggles (chemical monogoggles). Approved to

EU Standard EN166, AS/NZS:1337.

**Protective Clothing Monitoring Methods** 

Chemical and cold resistant gloves/gauntlets, boots, and apron. Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate. Examples of sources of recommended air monitoring methods are given below or contact supplier. Further

national methods may be available. National Institute of Occupational Safety and Health (NIOSH), USA: Manual of

Analytical Methods,

http://www.cdc.gov/niosh/nmam/nmammenu.html.

Occupational Safety and Health Administration (OSHA), USA:

Sampling and Analytical Methods

http://www.osha.gov/dts/sltc/methods/toc.html Health and Safety Executive (HSE), UK: Methods for the Determination of

Hazardous Substances,

http://www.hsl.gov.uk/publications/mdhs.aspx. Institut für Arbeitsschutz der Deutschen Gesetzlichen Unfallversicherung (IFA), http://www.dguv.de/ifa/de/index.jsp L'Institut National de

Recherche et de Securité, (INRS), France

http://www.inrs.fr/securite/hygiene securite travail.html.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

White Viscous liquid. Appearance

Odour Odourless

Flash point > 140 °C / 284 °F Explosion / Flammability : Data not available.

4/7 Print Date 08.07.2014 00000001054

Effective Date 22.03.2012





Version 1.2

# **Material Safety Data Sheet**

limits in air

: 1,020 kg/m3 at 25 °C / 77 °F Density

Water solubility Slightly soluble. Solubility in other solvents : Data not available.

Dynamic viscosity 2,500 mPa.s at 20 °C / 68 °F

### 10. STABILITY AND REACTIVITY

Stability Stable. Hygroscopic. Polymerises exothermically with

> di-isocyanates at ambient temperatures. The reaction becomes progressively more vigorous and can be violent at higher temperatures if the miscibility of reaction partners is good or is supported by stirring or by the presence of solvents. Reacts with

strong oxidising agents.

**Conditions to Avoid** : Heat, flames, and sparks.

Materials to Avoid : Avoid contact with isocyanates, copper and copper alloys, zinc,

strong oxidizing agents, and water.

**Hazardous** 

**Decomposition Products** 

: Unknown toxic products may be formed.

#### 11. TOXICOLOGICAL INFORMATION

**Basis for Assessment** Information given is based on product testing, and/or similar

products, and/or components.

Expected to be of low toxicity: LD50 >2000 mg/kg, Rat **Acute Oral Toxicity Acute Dermal Toxicity** Expected to be of low toxicity: LD50 >2000 mg/kg, Rat

Skin corrosion/irritation Expected to be non-irritating to skin. Serious eye Expected to be non-irritating to eyes.

damage/irritation

Respiratory Irritation Not expected to be a respiratory irritant. Sensitisation Not expected to be a skin sensitiser.

**Repeated Dose Toxicity** Not expected to be a hazard. Germ cell mutagenicity Not expected to be mutagenic. Carcinogenicity Not expected to be carcinogenic. Reproductive and Not expected to impair fertility. **Developmental Toxicity** 

Not expected to be a developmental toxicant.

# 12. ECOLOGICAL INFORMATION

**Acute Toxicity** 

Expected to have low toxicity: LC/EC/IC50 > 100 mg/l Fish Expected to have low toxicity: LC/EC/IC50 > 100 mg/l Aquatic crustacea Algae/aquatic plants Expected to have low toxicity: LC/EC/IC50 > 100 mg/l Microorganisms Expected to have low toxicity: LC/EC/IC50 > 100 mg/l

**Mobility** If product enters soil, one or more constituents will be mobile

and may contaminate groundwater.

Sinks in fresh water; may float or sink in seawater. Expected to be not readily biodegradable.

Persistence/degradability

Does not bioaccumulate significantly, MW > 1000. Bioaccumulation

Other Adverse Effects Small particles may have physical effects on aquatic and

terrestrial organisms.

5/7 Print Date 08.07.2014 00000001054 MSDS IN



Effective Date 22.03.2012

### 13. DISPOSAL CONSIDERATIONS

Material Disposal Recover or recycle if possible. It is the responsibility of the waste

> generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Do not dispose into the environment, in drains or in water courses. Waste product should not be allowed to contaminate

soil or water.

**Container Disposal** Drain container thoroughly. After draining, vent in a safe place

away from sparks and fire. Send to drum recoverer or metal

reclaimer.

**Local Legislation** Disposal should be in accordance with applicable regional,

> national, and local laws and regulations. Local regulations may be more stringent than regional or national requirements and

must be complied with.

### 14. TRANSPORT INFORMATION

# Land (as per ADR classification): Not regulated

This material is not classified as dangerous under ADR regulations.

### **IMDG**

This material is not classified as dangerous under IMDG regulations.

### IATA (Country variations may apply)

This material is either not classified as dangerous under IATA regulations or needs to follow country specific requirements.

### 15. REGULATORY INFORMATION

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

**EC** Classification Not classified as dangerous under EC criteria.

**Chemical Inventory Status** 

**EINECS** All components listed or

polymer exempt.

**AICS** All components listed or

polymer exempt.


### 16. OTHER INFORMATION

**Additional Information** For further information, contact your local Shell company or

agent.

6/7 Print Date 08.07.2014 00000001054

Version 1.2



Effective Date 22.03.2012

# **Material Safety Data Sheet**

R-phrase(s)

None None

MSDS Version Number : 1.2

MSDS Effective Date : 22.03.2012

**MSDS Revisions** : A vertical bar (|) in the left margin indicates an amendment from

the previous version.

**Uses and Restrictions** : Advice in this document relates only to product as originally

supplied. Other derivative chemicals will have different

properties and hazards. Advice should be sought on their safe

handling and use.
Use for the manufacture of polyurethane products.

MSDS Distribution : The information in this document should be made available to all

who may handle the product

**Disclaimer** : This information is based on our current knowledge and is

intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of

the product.

MSDS\_IN