

# SAFETY DATA SHEET

## Pentane 60/40

Version 3.2

Revision Date 2023.08.31

Print Date 2023.09.07

### 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Pentane 60/40

Product code : Q1125

Other means of identification : Pentane 60/40

#### Manufacturer or supplier's details

Supplier : SHELL EASTERN CHEMICALS (S)  
A REGISTERED BUSINESS OF SHELL EASTERN  
TRADING (PTE) LTD (UEN:198902087C)  
9 North Buona Vista Drive , #07-01  
The Metropolis Tower 1  
Singapore 138588  
Singapore

Telephone : +65 6384 8269

Telefax : +65 6384 8454

Contact for Safety Data  
Sheet :

Emergency telephone  
number : + (65) 6542 9595 (Alert-SGS)

#### Recommended use of the chemical and restrictions on use

Recommended use : Blowing agent

Restrictions on use : This product must not be used in applications other than the  
above without first seeking the advice of the supplier.

### 2. HAZARDS IDENTIFICATION

#### GHS Classification

Flammable liquids : Category 1  
Aspiration hazard : Category 1  
Specific target organ toxicity -  
single exposure : Category 3 (Narcotic effects)  
Short-term (acute) aquatic  
hazard : Category 2

#### GHS label elements

Hazard pictograms :



# SAFETY DATA SHEET

## Pentane 60/40

Version 3.2

Revision Date 2023.08.31

Print Date 2023.09.07

Signal word

: Danger

Hazard statements

: PHYSICAL HAZARDS:  
H224 Extremely flammable liquid and vapour.  
HEALTH HAZARDS:  
H304 May be fatal if swallowed and enters airways.  
H336 May cause drowsiness or dizziness.  
ENVIRONMENTAL HAZARDS:  
H401 Toxic to aquatic life.

Precautionary statements

:  
**Prevention:**  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P240 Ground/bond container and receiving equipment.  
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.  
P242 Use only non-sparking tools.  
P243 Take precautionary measures against static discharge.  
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.  
P271 Use only outdoors or in a well-ventilated area.  
P273 Avoid release to the environment.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  
  
**Response:**  
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.  
P370 + P378 In case of fire: Use appropriate media to extinguish.  
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.  
P331 Do NOT induce vomiting.  
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P312 Call a POISON CENTER/doctor if you feel unwell.  
  
**Storage:**  
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
P235 Keep cool.  
P405 Store locked up.  
  
**Disposal:**  
P501 Dispose of contents and container to appropriate waste site or reclaimer in accordance with local and national regulations.

Other hazards which do not result in classification

# SAFETY DATA SHEET

## Pentane 60/40

Version 3.2

Revision Date 2023.08.31

Print Date 2023.09.07

May form flammable/explosive vapour-air mixture. This material is a static accumulator. Even with proper grounding and bonding, this material can still accumulate an electrostatic charge. If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur. Repeated exposure may cause skin dryness or cracking.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

#### Hazardous components

Chemical name	Synonyms	CAS-No.	Classification	Concentration (% w/w)
pentane	pentane	109-66-0	Flam. Liq.1; H224 Asp. Tox.1; H304 STOT SE3; H336 Aquatic Acute2; H401	60
isopentane	2-methylbutane	78-78-4	Flam. Liq.1; H224 Asp. Tox.1; H304 STOT SE3; H336 Aquatic Acute2; H401	40

For explanation of abbreviations see section 16.

### 4. FIRST-AID MEASURES

General advice : Not expected to be a health hazard when used under normal conditions.

First aid measures for different exposure routes

If inhaled : Remove to fresh air. If rapid recovery does not occur, transport to nearest medical facility for additional treatment.

In case of skin contact : Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention.

In case of eye contact : Flush eye with copious quantities of water. Remove contact lenses, if present and easy to do. Continue rinsing. If persistent irritation occurs, obtain medical attention.

If swallowed : Call emergency number for your location / facility. If swallowed, do not induce vomiting: transport to nearest medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (38.3°C), shortness of breath, chest congestion or continued coughing or wheezing.

Most important symptoms : Breathing of high vapour concentrations may cause central

# SAFETY DATA SHEET

## Pentane 60/40

Version 3.2

Revision Date 2023.08.31

Print Date 2023.09.07

and effects, both acute and delayed

nervous system (CNS) depression resulting in dizziness, light-headedness, headache, nausea and loss of coordination. Continued inhalation may result in unconsciousness and death.

No specific hazards under normal use conditions.  
Skin irritation signs and symptoms may include a burning sensation, redness, or swelling.

No specific hazards under normal use conditions.  
Eye irritation signs and symptoms may include a burning sensation, redness, swelling, and/or blurred vision.

If material enters lungs, signs and symptoms may include coughing, choking, wheezing, difficulty in breathing, chest congestion, shortness of breath, and/or fever.  
If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (38.3°C), shortness of breath, chest congestion or continued coughing or wheezing.

Protection of first-aiders

: When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.

Notes to physician

: Call a doctor or poison control center for guidance.  
Potential for chemical pneumonitis.  
Treat symptomatically.

### 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

: Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

Unsuitable extinguishing media

: Do not use water in a jet.

Specific hazards during firefighting

: Clear fire area of all non-emergency personnel.  
Hazardous combustion products may include:  
A complex mixture of airborne solid and liquid particulates and gases (smoke).  
Carbon monoxide.  
Unidentified organic and inorganic compounds.  
Flammable vapours may be present even at temperatures below the flash point.  
The vapour is heavier than air, spreads along the ground and distant ignition is possible.  
Will float and can be reignited on surface water.

Specific extinguishing methods

: Standard procedure for chemical fires.  
Keep adjacent containers cool by spraying with water.

# SAFETY DATA SHEET

## Pentane 60/40

Version 3.2

Revision Date 2023.08.31

Print Date 2023.09.07

Special protective equipment for firefighters : Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Observe all relevant local and international regulations. Notify authorities if any exposure to the general public or the environment occurs or is likely to occur. Local authorities should be advised if significant spillages cannot be contained.

: Avoid contact with skin, eyes and clothing. Isolate hazard area and deny entry to unnecessary or unprotected personnel. Do not breathe fumes, vapour. Do not operate electrical equipment.

Environmental precautions : Shut off leaks, if possible without personal risks. Remove all possible sources of ignition in the surrounding area. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. Attempt to disperse the vapour or to direct its flow to a safe location for example by using fog sprays. Take precautionary measures against static discharge. Ensure electrical continuity by bonding and grounding (earthing) all equipment. Monitor area with combustible gas indicator.

Methods and materials for containment and cleaning up : For small liquid spills (< 1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely. For large liquid spills (> 1 drum), transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.

Ventilate contaminated area thoroughly. If contamination of site occurs remediation may require specialist advice.

Additional advice : For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet. For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.

# SAFETY DATA SHEET

## Pentane 60/40

Version 3.2

Revision Date 2023.08.31

Print Date 2023.09.07

### 7. HANDLING AND STORAGE

#### Handling

General Precautions : Avoid breathing of or direct contact with material. Only use in well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet.  
Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.  
Ensure that all local regulations regarding handling and storage facilities are followed.

Advice on safe handling : Avoid inhaling vapour and/or mists.  
Avoid contact with skin, eyes and clothing.  
Extinguish any naked flames. Do not smoke. Remove ignition sources. Avoid sparks.  
Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols.  
Bulk storage tanks should be diked (bunded).  
When using do not eat or drink.  
  
The vapour is heavier than air, spreads along the ground and distant ignition is possible.

Avoidance of contact : Strong oxidising agents.

Product Transfer : Even with proper grounding and bonding, this material can still accumulate an electrostatic charge. If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur. Be aware of handling operations that may give rise to additional hazards that result from the accumulation of static charges. These include but are not limited to pumping (especially turbulent flow), mixing, filtering, splash filling, cleaning and filling of tanks and containers, sampling, switch loading, gauging, vacuum truck operations, and mechanical movements. These activities may lead to static discharge e.g. spark formation. Restrict line velocity during pumping in order to avoid generation of electrostatic discharge ( $\leq 1$  m/s until fill pipe submerged to twice its diameter, then  $\leq 7$  m/s). Avoid splash filling. Do NOT use compressed air for filling, discharging, or handling operations.

Refer to guidance under Handling section.

#### Storage

Conditions for safe storage : Refer to section 15 for any additional specific legislation covering the packaging and storage of this product.

# SAFETY DATA SHEET

## Pentane 60/40

Version 3.2

Revision Date 2023.08.31

Print Date 2023.09.07

Other data

: Storage Temperature:  
Ambient.

Bulk storage tanks should be diked (bunded).  
Locate tanks away from heat and other sources of ignition.  
Cleaning, inspection and maintenance of storage tanks is a specialist operation, which requires the implementation of strict procedures and precautions.  
Must be stored in a diked (bunded) well- ventilated area, away from sunlight, ignition sources and other sources of heat.  
Keep away from aerosols, flammables, oxidizing agents, corrosives and from other flammable products which are not harmful or toxic to man or to the environment.  
Electrostatic charges will be generated during pumping.  
Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment to reduce the risk.  
The vapours in the head space of the storage vessel may lie in the flammable/explosive range and hence may be flammable.

Packaging material

: Suitable material: For containers, or container linings use mild steel, stainless steel., For container paints, use epoxy paint, zinc silicate paint.  
Unsuitable material: Avoid prolonged contact with natural, butyl or nitrile rubbers.

Container Advice

: Do not cut, drill, grind, weld or perform similar operations on or near containers.

Specific use(s)

: Not applicable

See additional references that provide safe handling practices for liquids that are determined to be static accumulators:  
American Petroleum Institute 2003 (Protection Against Ignitions Arising out of Static, Lightning and Stray Currents) or National Fire Protection Agency 77 (Recommended Practices on Static Electricity).  
IEC/TS 60079-32-1: Electrostatic hazards, guidance

### 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
pentane	109-66-0	TWA	600 ppm 1,770 mg/m3	TW OEL
pentane		STEL	750 ppm 1,770 mg/m3	TW OEL
pentane	109-66-0	TWA	1,000 ppm	OSHA Z-1

# SAFETY DATA SHEET

## Pentane 60/40

Version 3.2

Revision Date 2023.08.31

Print Date 2023.09.07

			2,950 mg/m3	
pentane		TWA	120 ppm 350 mg/m3	NIOSH REL
pentane		C	610 ppm 1,800 mg/m3	NIOSH REL
pentane		TWA	1,000 ppm	ACGIH
isopentane	78-78-4	TWA	1,000 ppm	ACGIH

### Biological occupational exposure limits

No biological limit allocated.

### Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods  
<http://www.cdc.gov/niosh/>

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods  
<http://www.osha.gov/>

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances  
<http://www.hse.gov.uk/>

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany  
<http://www.dguv.de/inhalt/index.jsp>

L'Institut National de Recherche et de Sécurité, (INRS), France <http://www.inrs.fr/accueil>

### Engineering measures

- : Use sealed systems as far as possible.
- Adequate explosion-proof ventilation to control airborne concentrations below the exposure guidelines/limits.
- Local exhaust ventilation is recommended.
- Eye washes and showers for emergency use.
- Firewater monitors and deluge systems are recommended.
- Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.
- The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances.
- Appropriate measures include:

#### General Information:

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping. Define procedures for safe handling and maintenance of controls. Educate and train workers in the hazards and control



# SAFETY DATA SHEET

## Pentane 60/40

Version 3.2

Revision Date 2023.08.31

Print Date 2023.09.07

measures relevant to normal activities associated with this product.  
Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.  
Drain down system prior to equipment break-in or maintenance.  
Retain drain downs in sealed storage pending disposal or for subsequent recycle.

### Personal protective equipment

#### Protective measures

Hygiene measures:

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

See also the following information:

Respiratory protection : If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are unsuitable (e.g. airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. If air-filtering respirators are suitable for conditions of use: Select a filter suitable for organic gases and vapours [Type AX boiling point  $\leq 65^{\circ}\text{C}$  ( $149^{\circ}\text{F}$ )].

Hand protection

Remarks

: Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. Longer term protection: Nitrile rubber gloves. Incidental contact/Splash protection: PVC or neoprene rubber gloves. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice

# SAFETY DATA SHEET

## Pentane 60/40

Version 3.2

Revision Date 2023.08.31

Print Date 2023.09.07

from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

- Eye protection : Wear goggles for use against liquids and gas.
- Skin and body protection : Skin protection is not required under normal conditions of use. For prolonged or repeated exposures use impervious clothing over parts of the body subject to exposure.
- If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to relevant Standard, and provide employee skin care programmes.
- Wear antistatic and flame-retardant clothing, if a local risk assessment deems it so.
- Thermal hazards : Not applicable
- Hygiene measures : Wash hands before eating, drinking, smoking and using the toilet.  
Launder contaminated clothing before re-use.  
Do not ingest. If swallowed, then seek immediate medical assistance.

### Environmental exposure controls

- General advice : Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour.  
Minimise release to the environment. An environmental assessment must be made to ensure compliance with local environmental legislation.  
Information on accidental release measures are to be found in section 6.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : Liquid.
- Colour : colourless
- Odour : Paraffinic
- Odour Threshold : Data not available
- pH : Not applicable
- Melting point/freezing point : -160.5 °C / -256.9 °F
- pour point : -150 °C / -238 °F
- Boiling point/boiling range : Typical 24 - 32 °C / 75 - 90 °F

# SAFETY DATA SHEET

## Pentane 60/40

Version 3.2

Revision Date 2023.08.31

Print Date 2023.09.07

Flash point	: Typical -57 °C / -71 °F Method: IP 170
Evaporation rate	: 1 Method: DIN 53170, di-ethyl ether=1  12 Method: ASTM D 3539, nBuAc=1
Flammability (solid, gas)	: Not applicable
Upper explosion limit	: 7.6 %(V)
Lower explosion limit	: 1.3 %(V)
Vapour pressure	: Typical 207 kPa (50 °C / 122 °F)  Typical 36 kPa (0 °C / 32 °F)  Typical 77 kPa (20 °C / 68 °F)
Relative vapour density	: 2.4
Relative density	: Data not available
Density	: Typical 624 kg/m3 (15 °C / 59 °F) Method: ASTM D4052
Solubility(ies)	
Water solubility	: 4.8 mg/l insoluble (20 °C / 68 °F)
Partition coefficient: n-octanol/water	: log Pow: 3.4
Auto-ignition temperature	: 468 °C / 874 °F Method: ASTM E-659
Auto-ignition temperature	370 °C / 698 °F Method: DIN 51794
Decomposition temperature	: Data not available
Viscosity	
Viscosity, dynamic	: Data not available
Viscosity, kinematic	: Typical 0.56 mm2/s (0 °C / 32 °F) Method: ASTM D445  Typical 0.32 mm2/s (25 °C / 77 °F)

# SAFETY DATA SHEET

## Pentane 60/40

Version 3.2

Revision Date 2023.08.31

Print Date 2023.09.07

Method: ASTM D445

Explosive properties	: Classification Code: Not classified
Oxidizing properties	: Not applicable
Surface tension	: Data not available
Conductivity	: Low conductivity: < 100 pS/m, The conductivity of this material makes it a static accumulator., A liquid is typically considered nonconductive if its conductivity is below 100 pS/m and is considered semi-conductive if its conductivity is below 10,000 pS/m., Whether a liquid is nonconductive or semi-conductive, the precautions are the same., A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid
Particle size	: Data not available
Molecular weight	: 72 g/mol

### 10. STABILITY AND REACTIVITY

Reactivity	: The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.
Chemical stability	: No hazardous reaction is expected when handled and stored according to provisions Stable under normal conditions of use.
Possibility of hazardous reactions	: Reacts with strong oxidising agents.
Conditions to avoid	: Avoid heat, sparks, open flames and other ignition sources.  In certain circumstances product can ignite due to static electricity.
Incompatible materials	: Strong oxidising agents.
Hazardous decomposition products	: Hazardous decomposition products are not expected to form during normal storage. Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids and gases including carbon monoxide, carbon dioxide, sulphur oxides and unidentified organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation.

# SAFETY DATA SHEET

## Pentane 60/40

Version 3.2

Revision Date 2023.08.31

Print Date 2023.09.07

### 11. TOXICOLOGICAL INFORMATION

- Basis for assessment : Information given is based on product testing, and/or similar products, and/or components.  
Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).
- Exposure routes : Exposure may occur via inhalation, ingestion, skin absorption, skin or eye contact, and accidental ingestion.
- Symptoms of Overexposure : Breathing of high vapour concentrations may cause central nervous system (CNS) depression resulting in dizziness, light-headedness, headache, nausea and loss of coordination. Continued inhalation may result in unconsciousness and death. No specific hazards under normal use conditions. Skin irritation signs and symptoms may include a burning sensation, redness, or swelling. No specific hazards under normal use conditions. Eye irritation signs and symptoms may include a burning sensation, redness, swelling, and/or blurred vision. If material enters lungs, signs and symptoms may include coughing, choking, wheezing, difficulty in breathing, chest congestion, shortness of breath, and/or fever. If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (38.3°C), shortness of breath, chest congestion or continued coughing or wheezing.

#### Acute toxicity

##### Product:

- Acute oral toxicity : LD50 Rat: > 5000 mg/kg  
Remarks: Low toxicity  
Based on available data, the classification criteria are not met.
- Acute inhalation toxicity : LC50 Rat: > 20 mg/l  
Exposure time: 4 h  
Remarks: Low toxicity  
High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea.
- Acute dermal toxicity :  
Remarks: Low toxicity  
Based on available data, the classification criteria are not met.

##### Components:

##### pentane:

- Acute oral toxicity : LD50 Rat, male and female: > 5,000 mg/kg  
Method: OECD Test Guideline 401  
Remarks: Based on available data, the classification criteria are not met.

# SAFETY DATA SHEET

## Pentane 60/40

Version 3.2

Revision Date 2023.08.31

Print Date 2023.09.07

Acute inhalation toxicity : LC50 Rat, male and female: > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: OECD Test Guideline 403  
Remarks: Based on available data, the classification criteria are not met.

### **isopentane:**

Acute oral toxicity : LD 50 Rat, male and female: > 5,000 mg/kg  
Method: OECD Test Guideline 401  
Remarks: Based on available data, the classification criteria are not met.

Acute inhalation toxicity : LD50 Rat, male and female: > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: OECD Test Guideline 403  
Remarks: Based on available data, the classification criteria are not met.

### **Skin corrosion/irritation**

#### **Product:**

Remarks: Not irritating to skin., Repeated exposure may cause skin dryness or cracking.

#### **Components:**

##### **pentane:**

Species: Rabbit  
Method: Test(s) equivalent or similar to OECD Test Guideline 404  
Remarks: Slightly irritating to skin., Insufficient to classify.

##### **isopentane:**

Species: Rabbit  
Method: Test(s) equivalent or similar to OECD Test Guideline 404  
Remarks: Slightly irritating., Insufficient to classify.

### **Serious eye damage/eye irritation**

#### **Product:**

Remarks: Not irritating to eye.

#### **Components:**

##### **pentane:**

Species: Rabbit  
Method: OECD Test Guideline 405  
Remarks: Slightly irritating., Insufficient to classify.

##### **isopentane:**

Species: Rabbit

# SAFETY DATA SHEET

## Pentane 60/40

Version 3.2

Revision Date 2023.08.31

Print Date 2023.09.07

Method: Test(s) equivalent or similar to OECD Test Guideline 405

Remarks: Slightly irritating., Insufficient to classify.

### Respiratory or skin sensitisation

#### Product:

Remarks: Not a sensitiser.

Based on available data, the classification criteria are not met.

#### Components:

##### **pentane:**

Species: Guinea pig

Method: OECD Test Guideline 406

Remarks: Based on available data, the classification criteria are not met.

##### **isopentane:**

Species: Guinea pig

Method: Test(s) equivalent or similar to OECD Test Guideline 406

Remarks: Based on available data, the classification criteria are not met.

### Chronic toxicity

### Germ cell mutagenicity

#### Product:

: Remarks: Not mutagenic.

#### Components:

##### **pentane:**

Genotoxicity in vitro

: Method: Test(s) equivalent or similar to OECD Guideline 471  
Remarks: Based on available data, the classification criteria are not met.

: Method: Directive 67/548/EEC, Annex V, B.10.  
Remarks: Based on available data, the classification criteria are not met.

: Test species: RatMethod: Directive 67/548/EEC, Annex V, B.12.  
Remarks: Based on available data, the classification criteria are not met.

##### **isopentane:**

Genotoxicity in vitro

: Method: Test(s) equivalent or similar to OECD Guideline 471  
Remarks: Based on available data, the classification criteria are not met.

: Method: Directive 67/548/EEC, Annex V, B.10.  
Remarks: Based on available data, the classification criteria are not met.

: Test species: RatMethod: Directive 67/548/EEC, Annex V, B.12.  
Remarks: Based on available data, the classification criteria are not met.

# SAFETY DATA SHEET

## Pentane 60/40

Version 3.2

Revision Date 2023.08.31

Print Date 2023.09.07

Germ cell mutagenicity-  
Assessment

are not met.  
: This product does not meet the criteria for classification in  
categories 1A/1B.

### Carcinogenicity

#### Product:

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

#### Components:

##### **isopentane:**

Carcinogenicity -  
Assessment

: This product does not meet the criteria for classification in  
categories 1A/1B.

Material	GHS/CLP Carcinogenicity Classification
pentane	No carcinogenicity classification.
isopentane	No carcinogenicity classification.

### Reproductive toxicity

#### **Product:**

:  
Remarks: Not a developmental toxicant., Does not impair  
fertility., Based on available data, the classification criteria are  
not met.

#### **Components:**

##### **pentane:**

: Species: Rat  
Sex: male and female  
Application Route: Inhalation

Method: Equivalent or similar to OECD Test Guideline 416  
Remarks: Based on available data, the classification criteria  
are not met.

Effects on foetal  
development

: Species: Rat, female  
Application Route: Oral  
Method: OECD Test Guideline 414  
Remarks: Based on available data, the classification criteria  
are not met.

##### **isopentane:**

Species: Rat  
Sex: male and female



# SAFETY DATA SHEET

## Pentane 60/40

Version 3.2

Revision Date 2023.08.31

Print Date 2023.09.07

Application Route: Inhalation

Method: Equivalent or similar to OECD Test Guideline 416  
Remarks: Based on available data, the classification criteria are not met.

Species: Rat, female  
Application Route: Oral  
Method: OECD Test Guideline 414  
Remarks: Based on available data, the classification criteria are not met.

Reproductive toxicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

### STOT - single exposure

#### Product:

Remarks: May cause drowsiness and dizziness., Inhalation of vapours or mists may cause irritation to the respiratory system.

#### Components:

##### **pentane:**

Exposure routes: Inhalation  
Target Organs: Central nervous system  
Remarks: May cause drowsiness or dizziness.

##### **isopentane:**

Exposure routes: Inhalation  
Target Organs: Central nervous system  
Remarks: May cause drowsiness or dizziness.

### STOT - repeated exposure

#### Product:

Remarks: Based on available data, the classification criteria are not met.

#### Components:

##### **pentane:**

Remarks: Based on available data, the classification criteria are not met.

##### **isopentane:**

Remarks: Based on available data, the classification criteria are not met., Low systemic toxicity on repeated exposure.

### Repeated dose toxicity

#### Components:

# SAFETY DATA SHEET

## Pentane 60/40

Version 3.2

Revision Date 2023.08.31

Print Date 2023.09.07

### **pentane:**

Rat, male and female:  
Application Route: Inhalation  
Test atmosphere: Gas  
Method: OECD Test Guideline 413  
Target Organs: No specific target organs noted

### **isopentane:**

Rat, male and female:  
Application Route: Inhalation  
Test atmosphere: Gas  
Method: Test(s) equivalent or similar to OECD Test Guideline 413  
Target Organs: No specific target organs noted

## Aspiration toxicity

### **Product:**

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

### **Components:**

#### **pentane:**

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

#### **isopentane:**

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

## Further information

### **Product:**

Remarks: Exposure to very high concentrations of similar materials has been associated with irregular heart rhythms and cardiac arrest., Classifications by other authorities under varying regulatory frameworks may exist.

### **Components:**

#### **pentane:**

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

#### **isopentane:**

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

---

## 12. ECOLOGICAL INFORMATION

Basis for assessment : Incomplete ecotoxicological data are available for this product.  
The information given below is based partly on a knowledge of

# SAFETY DATA SHEET

## Pentane 60/40

Version 3.2

Revision Date 2023.08.31

Print Date 2023.09.07

the components and the ecotoxicology of similar products.  
Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

### Ecotoxicity

#### Product:

Toxicity to fish (Acute toxicity) :  
Remarks: LL/EL/IL50 > 1 <= 10 mg/l  
Toxic

Toxicity to crustacean (Acute toxicity) :  
Remarks: Toxic  
LL/EL/IL50 > 1 <= 10 mg/l

Toxicity to algae/aquatic plants (Acute toxicity) :  
Remarks: LL/EL/IL50 >10 <= 100 mg/l  
Harmful

Toxicity to fish (Chronic toxicity) : Remarks: Data not available

Toxicity to crustacean (Chronic toxicity) : Remarks: Data not available

Toxicity to microorganisms (Acute toxicity) : Remarks: Data not available

#### Components:

##### **pentane :**

Toxicity to fish (Acute toxicity) : LC50 (Oncorhynchus mykiss (rainbow trout)): 4.26 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203  
Remarks: Toxic  
LL/EL/IL50 > 1 <= 10 mg/l

Toxicity to crustacean (Acute toxicity) : EC50 (Daphnia magna (Water flea)): 2.7 mg/l  
Exposure time: 48 h  
Method: Test(s) equivalent or similar to OECD Guideline 202  
Remarks: Toxic  
LL/EL/IL50 > 1 <= 10 mg/l

Toxicity to algae/aquatic plants (Acute toxicity) : EC50 (Scenedesmus capricornutum (fresh water algae)): 10.7 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
Remarks: Harmful  
LL/EL/IL50 >10 <= 100 mg/l

Toxicity to microorganisms (Acute toxicity) : NOEL (Tetrahymena pyriformis): 23.7 mg/l  
Exposure time: 48 h  
Method: Based on quantitative structure-activity relationship (QSAR) modelling  
Remarks: NOEC/NOEL >100 mg/l

# SAFETY DATA SHEET

## Pentane 60/40

Version 3.2

Revision Date 2023.08.31

Print Date 2023.09.07

Toxicity to fish (Chronic toxicity) : NOELR: 6.165 mg/l  
Exposure time: 28 d  
Species: Oncorhynchus mykiss (rainbow trout)  
Method: Based on quantitative structure-activity relationship (QSAR) modelling  
Remarks: NOEC/NOEL > 1.0 - <= 10 mg/l

Toxicity to crustacean(Chronic toxicity) : NOELR: 10.76 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Method: Based on quantitative structure-activity relationship (QSAR) modelling  
Remarks: no data available

### isopentane :

Toxicity to fish (Acute toxicity) : LC50 (Oncorhynchus mykiss (rainbow trout)): 4.26 mg/l  
Exposure time: 96 h  
Method: Information given is based on data obtained from similar substances.  
Remarks: Toxic  
LL/EL/IL50 > 1 <= 10 mg/l

Toxicity to crustacean (Acute toxicity) : EC50 (Daphnia magna (Water flea)): 4.2 mg/l  
Exposure time: 48 h  
Method: Test(s) equivalent or similar to OECD Guideline 301 F  
Remarks: Toxic  
LL/EL/IL50 > 1 <= 10 mg/l

Toxicity to algae/aquatic plants (Acute toxicity) : EL50 (Selenastrum capricornutum (green algae)): 25.12 mg/l  
Exposure time: 72 h  
Method: Based on quantitative structure-activity relationship (QSAR) modelling  
Remarks: Harmful  
LL/EL/IL50 >10 <= 100 mg/l

Toxicity to microorganisms (Acute toxicity) : EL50 (Tetrahymena pyriformis): 130.9 mg/l  
Exposure time: 48 h  
Method: Based on quantitative structure-activity relationship (QSAR) modelling  
Remarks: Practically non toxic:  
LL/EL/IL50 > 100 mg/l

Toxicity to fish (Chronic toxicity) : NOELR: 7.618 mg/l  
Exposure time: 28 d  
Species: Oncorhynchus mykiss (rainbow trout)  
Method: Based on quantitative structure-activity relationship (QSAR) modelling  
Remarks: NOEC/NOEL > 1.0 - <= 10 mg/l

Toxicity to crustacean(Chronic toxicity) : NOELR: 13.29 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Method: Based on quantitative structure-activity relationship

# SAFETY DATA SHEET

## Pentane 60/40

Version 3.2

Revision Date 2023.08.31

Print Date 2023.09.07

(QSAR) modelling

Remarks: NOEC/NOEL > 10 - <=100 mg/l

### Persistence and degradability

#### Product:

Biodegradability : Remarks: Readily biodegradable., Oxidises rapidly by photo-chemical reactions in air.

#### Components:

##### pentane :

Biodegradability : Biodegradation: 87 %  
Exposure time: 28 d  
Method: Test(s) equivalent or similar to OECD Guideline 301 F  
Remarks: Readily biodegradable.  
Oxidises rapidly by photo-chemical reactions in air.

##### isopentane :

Biodegradability : Biodegradation: 71 %  
Exposure time: 28 d  
Method: Test(s) equivalent or similar to OECD Guideline 301 F  
Remarks: Readily biodegradable.  
Oxidises rapidly by photo-chemical reactions in air.

### Bioaccumulative potential

#### Product:

Bioaccumulation : Remarks: Does not bioaccumulate significantly.

Partition coefficient: n-octanol/water : log Pow: 3.4

#### Components:

##### pentane :

Bioaccumulation : Species: Pimephales promelas (fathead minnow)  
Bioconcentration factor (BCF): 171  
Method: Based on quantitative structure-activity relationship (QSAR) modelling  
Remarks: Does not bioaccumulate significantly.

##### isopentane :

Bioaccumulation : Species: Pimephales promelas (fathead minnow)  
Bioconcentration factor (BCF): 171  
Method: Information given is based on data obtained from similar substances.  
Remarks: Does not bioaccumulate significantly.

### Mobility in soil

#### Product:

Mobility : Remarks: Floats on water., If the product enters soil, one or more constituents will or may be mobile and may contaminate

# SAFETY DATA SHEET

## Pentane 60/40

Version 3.2

Revision Date 2023.08.31

Print Date 2023.09.07

### **Components:**

#### **pentane :**

Mobility

groundwater.

: Remarks: Floats on water., If the product enters soil, one or more constituents will or may be mobile and may contaminate groundwater.

#### **isopentane :**

Mobility

: Remarks: Floats on water., If the product enters soil, one or more constituents will or may be mobile and may contaminate groundwater.

### **Other adverse effects**

#### **Product:**

Additional ecological information

: In view of the high rate of loss from solution, the product is unlikely to pose a significant hazard to aquatic life.

### **Components:**

#### **pentane :**

Results of PBT and vPvB assessment

: The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB.

Additional ecological information

: In view of the high rate of loss from solution, the product is unlikely to pose a significant hazard to aquatic life.

#### **isopentane :**

Results of PBT and vPvB assessment

: The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB.

Additional ecological information

: In view of the high rate of loss from solution, the product is unlikely to pose a significant hazard to aquatic life., Does not have ozone depletion potential.

## **13. DISPOSAL CONSIDERATIONS**

### **Disposal methods**

Waste from residues

: Recover or recycle if possible.  
It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.  
Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment.  
Do not dispose into the environment, in drains or in water courses.  
Do not dispose of tank water bottoms by allowing them to drain into the ground. This will result in soil and groundwater contamination.  
Waste arising from a spillage or tank cleaning should be disposed of in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand.

# SAFETY DATA SHEET

## Pentane 60/40

Version 3.2

Revision Date 2023.08.31

Print Date 2023.09.07

Waste, spills or used product is dangerous waste.

Disposal should be in accordance with applicable regional, national, and local laws and regulations.

Local regulations may be more stringent than regional or national requirements and must be complied with.

MARPOL - see International Convention for the Prevention of Pollution from Ships (MARPOL 73/78) which provides technical aspects at controlling pollutions from ships.

Contaminated packaging : Drain container thoroughly.  
After draining, vent in a safe place away from sparks and fire.  
Residues may cause an explosion hazard. Do not puncture, cut or weld uncleaned drums.  
Send to drum recoverer or metal reclaimer.  
Comply with any local recovery or waste disposal regulations.

### 14. TRANSPORT INFORMATION

#### International Regulations

##### ADR

UN number : 1265  
Proper shipping name : PENTANES  
Class : 3  
Packing group : I  
Labels : 3  
Hazard Identification Number : 33  
Environmentally hazardous : no

##### IATA-DGR

UN/ID No. : UN 1265  
Proper shipping name : PENTANES  
Class : 3  
Packing group : I  
Labels : 3

##### IMDG-Code

UN number : UN 1265  
Proper shipping name : PENTANES  
Class : 3  
Packing group : I  
Labels : 3  
Marine pollutant : no

#### Maritime transport in bulk according to IMO instruments

Pollution category : Y  
Ship type : 3  
Product name : Pentane (all isomers)

# SAFETY DATA SHEET

## Pentane 60/40

Version 3.2

Revision Date 2023.08.31

Print Date 2023.09.07

### Special precautions for user

- Remarks : Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.
- Additional Information** : This product may be transported under nitrogen blanketing. Nitrogen is an odourless and invisible gas. Exposure to nitrogen may cause asphyxiation or death. Personnel must observe strict safety precautions when involved with a confined space entry.

### 15. REGULATORY INFORMATION

#### National regulatory information

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

Occupational Safety and Health Act

Rules on hazard communication of dangerous and harmful materials.

Rules on public hazardous products and flammable pressurized gases installation and safety management.

Rules on road transport safety.

Toxic and Concerned Chemical Substances Control Act

Rules on organic solvent poison prevention.

Rules on pressurized gas labour safety.

Standards of Permissible Exposure Limits in Workplace

Standard on harm prevention of specific chemical substance.

Standards for the Storage, Cleanup, Handling and Disposal of Industrial Waste

#### Other international regulations

**The components of this product are reported in the following inventories:**

AIIC	: Listed
DSL	: Listed
IECSC	: Listed
ENCS	: Listed
KECI	: Listed
NZIoC	: Listed
PICCS	: Listed
TSCA	: Listed
TCSI	: Listed

### 16. OTHER INFORMATION

#### Full text of H-Statements

H224	Extremely flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.
H401	Toxic to aquatic life.

#### Full text of other abbreviations



# SAFETY DATA SHEET

## Pentane 60/40

Version 3.2

Revision Date 2023.08.31

Print Date 2023.09.07

Aquatic Acute	Short-term (acute) aquatic hazard
Asp. Tox.	Aspiration hazard
Flam. Liq.	Flammable liquids
STOT SE	Specific target organ toxicity - single exposure

### Abbreviations and Acronyms

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

### Further information

Training advice : Provide adequate information, instruction and training for operators.

Sources of key data used to compile the Safety Data Sheet : The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID data base, EC 1272 regulation, etc).

Revision Date : 2023.08.31

Organization that prepared the SDS : SHELL EASTERN CHEMICALS (S),  
A REGISTERED BUSINESS OF SHELL EASTERN,

# SAFETY DATA SHEET

## Pentane 60/40

Version 3.2

Revision Date 2023.08.31

Print Date 2023.09.07

TRADING (PTE) LTD (UEN:198902087C)

**Address** : The Metropolis Tower 1,  
9 North Buona Vista Drive , #07-01,  
Singapore 138588  
+65 6384 8737

**Person who prepared the SDS (Title)** : Varian Han (Product Steward)

**Signature**

: 

**Other information** : A vertical bar (|) in the left margin indicates an amendment from the previous version.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

TW / EN