GTL GS1927 HF

Print Date 17.02.2025 Revision Date 10.02.2025 Version 2.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : GTL GS1927 HF

Product code : Q6562

CAS-No. : 1809170-78-2

Synonyms: Hydrocarbons C11-C16, n-alkanes, isoalkanes, <2% aromatics,

Alkanes, C11-16 branched and linear

EC-No. : 942-085-5

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the : Solvent.

Substance/Mixture

Uses advised against : This product must not be used in applications other than the

above without first seeking the advice of the supplier.

This product must not be used in applications other than those

listed in Section 1 without first seeking the advice of the

supplier.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier : SHELL MARKETS (MIDDLE EAST) LIMITED

CHEMICALS PO Box 307

JEBEL ALI, DUBAI Unit.Arab Emir.

Telephone

Telefax

Contact for Safety Data

Sheet

1.4 Emergency telephone number

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

GHS Classification

Flammable liquids : Category 4
Aspiration hazard : Category 1

2.2 Label elements

1 / 24 800010024957 AE

GTL GS1927 HF

Print Date 17.02.2025 Revision Date 10.02.2025 Version 2.0

GHS-Labelling

Hazard pictograms

Signal word

PHYSICAL HAZARDS: Hazard statements

> H227 Combustible liquid. **HEALTH HAZARDS:**

H304 May be fatal if swallowed and enters airways.

ENVIRONMENTAL HAZARDS:

Not classified as an environmental hazard under GHS criteria.

: Prevention: Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames

and other ignition sources. No smoking. P243 Take action to prevent static discharges. P280 Wear protective gloves/ protective clothing/ eye

protection/ face protection.

Response:

P370 + P378 In case of fire: Use appropriate media to

extinguish.

P301 + P310 IF SWALLOWED: Immediately call a POISON

CENTER/doctor.

P331 Do NOT induce vomiting.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents and container to appropriate waste

site or reclaimer in accordance with local and national

regulations.

2.3 Other hazards

May form flammable/explosive vapour-air mixture.

This material is a static accumulator.

Even with proper grounding and bonding, this material can still accumulate an electrostatic charge. If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable airvapour mixtures can occur.

SECTION 3: Composition/information on ingredients

3.1 Substances

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
Alkanes, C11-C16-branched and linear	1809170-78-2	<=100

		GTL GS1927 HF
Print Date 17.02.2025	Revision Date 10.02.2025	Version 2.0

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Not expected to be a health hazard when used under normal

conditions.

Protection of first-aiders : When administering first aid, ensure that you are wearing the

appropriate personal protective equipment according to the

incident, injury and surroundings.

If inhaled : No treatment necessary under normal conditions of use.

If symptoms persist, obtain medical advice.

In case of skin contact : Remove contaminated clothing. Flush exposed area with

water and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention.

In case of eve contact : Flush eve with copious quantities of water.

Remove contact lenses, if present and easy to do. Continue

rinsina.

If persistent irritation occurs, obtain medical attention.

If swallowed : Call emergency number for your location / facility.

If swallowed, do not induce vomiting: transport to nearest medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (38.3°C), shortness of breath, chest congestion or continued coughing or wheezing.

4.2 Most important symptoms and effects, both acute and delayed

: Not considered to be an inhalation hazard under normal **Symptoms**

conditions of use.

Possible respiratory irritation signs and symptoms may include

a temporary burning sensation of the nose and throat,

coughing, and/or difficulty breathing.

No specific hazards under normal use conditions.

Skin irritation signs and symptoms may include a burning

sensation, redness, or swelling.

No specific hazards under normal use conditions.

Eye irritation signs and symptoms may include a burning sensation, redness, swelling, and/or blurred vision.

If material enters lungs, signs and symptoms may include

coughing, choking, wheezing, difficulty in breathing, chest

congestion, shortness of breath, and/or fever.

GTL GS1927 HF

Print Date 17.02.2025 Revision Date 10.02.2025 Version 2.0

If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (38.3°C), shortness of breath, chest congestion or continued coughing or wheezing.

Defatting dermatitis signs and symptoms may include a burning sensation and/or a dried/cracked appearance.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Call a doctor or poison control center for guidance.

Potential for chemical pneumonitis.

Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Foam, water spray or fog. Dry chemical powder, carbon

dioxide, sand or earth may be used for small fires only.

Unsuitable extinguishing

media

Do not use water in a jet.

5.2 Special hazards arising from the substance or mixture

Specific hazards during

firefighting

: Clear fire area of all non-emergency personnel. Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Flammable vapours may be present even at temperatures below the flash point. The vapour is heavier than air, spreads along the ground and distant ignition is possible. Will float and can be reignited on surface water.

5.3 Advice for firefighters

Special protective equipment

for firefighters

Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to

relevant Standards (e.g. Europe: EN469).

Specific extinguishing

methods

Further information

: Standard procedure for chemical fires.

: Keep adjacent containers cool by spraying with water.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions

Observe all relevant local and international regulations.

4 / 24 800010024957 AE

		GTL GS1927 HF
Print Date 17.02.2025	Revision Date 10.02.2025	Version 2.0
	Notify authorities if any exposure environment occurs or is likely to Local authorities should be advis cannot be contained. Avoid contact with skin, eyes and Isolate hazard area and deny enuprotected personnel. Do not breathe fumes, vapour. Do not operate electrical equipm	o occur. sed if significant spillages d clothing. try to unnecessary or

6.2 Environmental precautions

Environmental precautions

: Shut off leaks, if possible without personal risks. Remove all possible sources of ignition in the surrounding area. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. Attempt to disperse the vapour or to direct its flow to a safe location for example by using fog sprays. Take precautionary measures against static discharge. Ensure electrical continuity by bonding and grounding (earthing) all equipment.

Monitor area with combustible gas indicator.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up

: For small liquid spills (< 1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.

For large liquid spills (> 1 drum), transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely Ventilate contaminated area thoroughly.

If contamination of site occurs remediation may require

specialist advice.

6.4 Reference to other sections

For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet., For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.

SECTION 7: Handling and storage

General Precautions : Avoid breathing of or direct contact with material. Only use in

	GTL	. GS1927 HF
Print Date 17.02.2025	Revision Date 10.02.2025	Version 2.0
	well ventilated areas. Wash thoroughly after guidance on selection of personal protective Section 8 of this Safety Data Sheet. Use the information in this data sheet as input assessment of local circumstances to help deappropriate controls for safe handling, storage this material. Ensure that all local regulations regarding has storage facilities are followed.	equipment see ut to a risk etermine ue and disposal of
7.1 Precautions for safe handling		
Advice on safe handling	 Avoid inhaling vapour and/or mists. Avoid contact with skin, eyes and clothing. Extinguish any naked flames. Do not smoke. sources. Avoid sparks. Use local exhaust ventilation if there is risk o vapours, mists or aerosols. Bulk storage tanks should be diked (bunded) When using do not eat or drink. 	f inhalation of
	The vapour is heavier than air, spreads along distant ignition is possible.	g the ground and
Product Transfer	 Even with proper grounding and bonding, this accumulate an electrostatic charge. If sufficie allowed to accumulate, electrostatic discharge flammable air-vapour mixtures can occur. Be handling operations that may give rise to add that result from the accumulation of static chainclude but are not limited to pumping (espectiow), mixing, filtering, splash filling, cleaning tanks and containers, sampling, switch loading vacuum truck operations, and mechanical meactivities may lead to static discharge e.g. sp. Restrict line velocity during pumping in order generation of electrostatic discharge (≤ 1 m/s submerged to twice its diameter, then ≤ 7 m/filling. Do NOT use compressed air for filling, handling operations. 	ent charge is le and ignition of aware of litional hazards larges. These litional turbulent and filling of lang, gauging, lovements. These lark formation. to avoid suntil fill pipe s). Avoid splash
7.2 Conditions for safe storage, inc	eluding any incompatibilities	
Requirements for storage areas and containers	 Refer to section 15 for any additional specific covering the packaging and storage of this p 	•
Other data	: Storage Temperature: Ambient.	
	Bulk storage tanks should be diked (bunded) away from heat and other sources of ignition inspection and maintenance of storage tanks operation, which requires the implementation	. Cleaning, is a specialist

		GTL GS1927 HF
Print Date 17.02.2025	Revision Date 10.02.2025	Version 2.0
	procedures and precautions. Must be see (bunded) well- ventilated area, away from sources and other sources of heat. Keet flammables, oxidizing agents, corrosive flammable products which are not harm to the environment. Electrostatic chargeduring pumping. Electrostatic discharged Ensure electrical continuity by bonding (earthing) all equipment to reduce the rehead space of the storage vessel may flammable/explosive range and hence	om sunlight, ignition ep away from aerosols, es and from other nful or toxic to man or es will be generated e may cause fire. and grounding risk. The vapours in the lie in the
Packaging material	 Suitable material: For containers, or of mild steel, stainless steel. For container paint, zinc silicate paint. Unsuitable material: Avoid prolonged butyl or nitrile rubbers. 	r paints, use epoxy
Container Advice	: Do not cut, drill, grind, weld or perform near containers.	similar operations on or
7.3 Specific end use(s)		
Specific use(s)	: Not applicable	
	See additional references that provide for liquids that are determined to be sta American Petroleum Institute 2003 (Pro Ignitions Arising out of Static, Lightning National Fire Protection Agency 77 (Re on Static Electricity). IEC/TS 60079-32-1: Electrostatic haza	atic accumulators: otection Against g and Stray Currents) or ecommended Practices

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Aliphatic dearom. solvents 200 - 250		TWA	1.050 mg/m3	EU HSPA

Biological occupational exposure limits

No biological limit allocated.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

GTL GS1927 HF

Print Date 17.02.2025 Revision Date 10.02.2025 Version 2.0

Alkanes, C11-C16-branched and linear

: No DNEL value has been established.

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA) , Germany http://www.dquv.de/inhalt/index.isp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

8.2 Exposure controls

Engineering measures Use sealed systems as far as possible.

Adequate explosion-proof ventilation to control airborne concentrations below the exposure quidelines/limits.

Local exhaust ventilation is recommended.

Firewater monitors and deluge systems are recommended.

Eye washes and showers for emergency use.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

General Information

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

Personal protective equipment

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Eye protection : If material is handled such that it could be splashed into eyes,

protective eyewear is recommended.

GTL GS1927 HF

Print Date 17.02.2025

Revision Date 10.02.2025

Version 2.0

Hand protection

Remarks

: Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. Longer term protection: Nitrile rubber gloves. Incidental contact/Splash protection: PVC, neoprene or nitrile rubber gloves For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

Skin and body protection

Skin protection is not required under normal conditions of use. For prolonged or repeated exposures use impervious clothing over parts of the body subject to exposure. If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to relevant Standard, and provide employee skin care programmes.

Wear antistatic and flame-retardant clothing, if a local risk assessment deems it so.

Respiratory protection

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are unsuitable (e.g. airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter.

If air-filtering respirators are suitable for conditions of use:

GTL GS1927 HF

Print Date 17.02.2025 Revision Date 10.02.2025 Version 2.0

Select a filter suitable for organic gases and vapours [Type A

boiling point >65°C (149°F)].

Thermal hazards : Not applicable

Hygiene measures : Wash hands before eating, drinking, smoking and using the

> toilet. Launder contaminated clothing before re-use. Do not ingest. If swallowed, then seek immediate medical assistance.

Environmental exposure controls

General advice Local guidelines on emission limits for volatile substances

must be observed for the discharge of exhaust air containing

vapour.

Minimise release to the environment. An environmental assessment must be made to ensure compliance with local

environmental legislation.

Information on accidental release measures are to be found in

section 6.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour colourless Odour : odourless

Odour Threshold : Data not available

pΗ : Not applicable Melting point/freezing point : Data not available

Boiling point/boiling range 206 - 261 °C

Flash point $: > 78 \, ^{\circ}\text{C}$

Evaporation rate : Data not available

Flammability

Flammability (solid, gas) : Not applicable

Lower explosion limit and upper explosion limit / flammability limit

Upper explosion limit : 7 %(V)

Lower explosion limit : 0,5 %(V)

Vapour pressure : < 0,001 kPa (25 °C)

GTL GS1927 HF

Print Date 17.02.2025 Revision Date 10.02.2025 Version 2.0

Relative vapour density : Data not available

Relative density : < 0,8Method: ASTM D4052

Density : ca. 0,763 g/cm3 (15 °C)

Method: ASTM D4052

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

: log Pow: 4,5 - 7,0

Auto-ignition temperature : > 200 °C

Decomposition temperature : Data not available

Viscosity

Viscosity, dynamic : Data not available
Viscosity, kinematic : < 0,2 mm2/s (25 °C)

Method: ASTM D445

Explosive properties : Classification Code: Not classified.

Oxidizing properties : Data not available

9.2 Other information

Surface tension : Data not available

Conductivity: < 100 pS/m, The conductivity of this material

makes it a static accumulator., A liquid is typically considered nonconductive if its conductivity is below 100 pS/m and is considered semi-conductive if its conductivity is below 10,000 pS/m., Whether a liquid is nonconductive or semi-conductive, the precautions are the same., A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a

liquid

Molecular weight : Data not available

SECTION 10: Stability and reactivity

10.1 Reactivity

The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.

GTL GS1927 HF

Print Date 17.02.2025 Revision Date 10.02.2025 Version 2.0

10.2 Chemical stability

No hazardous reaction is expected when handled and stored according to provisions. Stable under normal conditions of use.

10.3 Possibility of hazardous reactions

Hazardous reactions : Reacts with strong oxidising agents.

10.4 Conditions to avoid

Conditions to avoid : Avoid heat, sparks, open flames and other ignition sources.

In certain circumstances product can ignite due to static

electricity.

10.5 Incompatible materials

Materials to avoid : Strong oxidising agents.

10.6 Hazardous decomposition products

Hazardous decomposition

products

: Hazardous decomposition products are not expected to form

during normal storage.

Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids and gases including carbon monoxide, carbon dioxide, sulphur oxides and unidentified organic compounds will be evolved when this

material undergoes combustion or thermal or oxidative

degradation.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Basis for assessment : Information given is based on data obtained from similar

substances.

Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for

individual component(s).

exposure

Information on likely routes of : Exposure may occur via inhalation, ingestion, skin absorption,

skin or eye contact, and accidental ingestion.

Acute toxicity

Product:

Acute oral toxicity : LD 50 Rat, male and female: > 5.000 mg/kg

Method: OECD Test Guideline 401

Remarks: Based on available data, the classification criteria

are not met.

Acute inhalation toxicity : LC 50 Rat, male and female: > 2 -<= 10 mg/l

GTL GS1927 HF

Print Date 17.02.2025 Revision Date 10.02.2025 Version 2.0

Exposure time: 4 h
Test atmosphere: vapour

Method: Test(s) equivalent or similar to OECD Test Guideline

403

Remarks: LC50 greater than near-saturated vapour

concentration.

Based on available data, the classification criteria are not met.

Acute dermal toxicity : LD 50 Rat, male and female: > 2.000 mg/kg

Method: Test(s) equivalent or similar to OECD Test Guideline

402

Remarks: Based on available data, the classification criteria

are not met.

Components:

Alkanes, C11-C16-branched and linear:

Acute oral toxicity : LD 50 Rat, male and female: > 5.000 mg/kg

Method: OECD Test Guideline 401

Remarks: Based on available data, the classification criteria

are not met.

Acute inhalation toxicity : LC 50 Rat, male and female: > 5 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Method: Test(s) equivalent or similar to OECD Test Guideline

403

Remarks: LC50 greater than near-saturated vapour

concentration.

Based on data from similar materials

Based on available data, the classification criteria are not met.

Acute dermal toxicity : LD 50 Rat, male and female: > 2.000 mg/kg

Method: Test(s) equivalent or similar to OECD Test Guideline

402

Remarks: Based on available data, the classification criteria

are not met.

Skin corrosion/irritation

Product:

Species: Rabbit

Method: Test(s) equivalent or similar to OECD Test Guideline 404

Remarks: Moderately irritating to skin (but insufficient to classify)., Prolonged/repeated contact

may cause defatting of the skin which can lead to dermatitis.

Components:

Alkanes, C11-C16-branched and linear:

Species: Rabbit

GTL GS1927 HF

 Print Date 17.02.2025
 Revision Date 10.02.2025
 Version 2.0

Method: Test(s) equivalent or similar to OECD Test Guideline 404

Remarks: Moderately irritating to skin (but insufficient to classify)., Prolonged/repeated contact

may cause defatting of the skin which can lead to dermatitis.

Serious eye damage/eye irritation

Product:

Species: Rabbit

Method: OECD Test Guideline 405

Remarks: Based on available data, the classification criteria are not met.

Components:

Alkanes, C11-C16-branched and linear:

Species: Rabbit

Method: OECD Test Guideline 405

Remarks: Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Product:

Species: Guinea pig

Method: OECD Test Guideline 406

Remarks: Based on available data, the classification criteria are not met.

Components:

Alkanes, C11-C16-branched and linear:

Species: Guinea pig

Method: OECD Test Guideline 406

Remarks: Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Product:

Genotoxicity in vitro : Method: Test(s) equivalent or similar to OECD Guideline 471
Remarks: Based on available data, the classification criteria

are not met.

: Method: Test(s) equivalent or similar to OECD Test Guideline

473

Remarks: Based on available data, the classification criteria

are not met.

: Method: Test(s) equivalent or similar to OECD Test Guideline

476

Remarks: Based on available data, the classification criteria

are not met.

: Test species: MouseMethod: Test(s) equivalent or similar to

OECD Test Guideline 474

Remarks: Based on available data, the classification criteria

are not met.

GTL GS1927 HF

Print Date 17.02.2025 Revision Date 10.02.2025 Version 2.0

Components:

Alkanes, C11-C16-branched and linear:

Genotoxicity in vitro : Method: Test(s) equivalent or similar to OECD Guideline 471

Remarks: Based on available data, the classification criteria

are not met.

: Method: Test(s) equivalent or similar to OECD Test Guideline

473

Remarks: Based on available data, the classification criteria

are not met.

Method: Test(s) equivalent or similar to OECD Test Guideline

476

Remarks: Based on available data, the classification criteria

are not met.

: Test species: MouseMethod: Test(s) equivalent or similar to

OECD Test Guideline 474

Remarks: Based on available data, the classification criteria

are not met.

Germ cell mutagenicity-

Assessment

This product does not meet the criteria for classification in

categories 1A/1B.

Carcinogenicity

Product:

Species: Rat, (male and female) Application Route: Inhalation

Method: Test(s) equivalent or similar to OECD Test Guideline 453

Remarks: Weight of evidence does not support classification as a carcinogen

Species: Mouse, (male and female)

Application Route: Inhalation

Method: Test(s) equivalent or similar to OECD Test Guideline 453

Remarks: Weight of evidence does not support classification as a carcinogen

Components:

Alkanes, C11-C16-branched and linear:

Species: Rat, (male and female) Application Route: Inhalation

Method: Test(s) equivalent or similar to OECD Test Guideline 453

Remarks: Weight of evidence does not support classification as a carcinogen

Species: Mouse, (male and female) Application Route: Inhalation

Method: Test(s) equivalent or similar to OECD Test Guideline 453

Remarks: Weight of evidence does not support classification as a carcinogen

Material	GHS/CLP Carcinogenicity Classification
	1

GTL GS1927 HF

Print Date 17.02.2025 Revision Date 10.02.2025 Version 2.0

Alkanes, C11-C16-branched No carcinogenicity classification. and linear

Reproductive toxicity

Product:

Species: Rat

Sex: male and female **Application Route: Oral**

Method: OECD Test Guideline 416

Remarks: Based on available data, the classification criteria

are not met.

Effects on foetal : Species: Rat, female development Application Route: Oral

Method: Test(s) equivalent or similar to OECD Test Guideline

Remarks: Based on available data, the classification criteria

are not met.

Species: Rat. female

Application Route: Inhalation

Method: Test(s) equivalent or similar to OECD Test Guideline

414

Remarks: Based on available data, the classification criteria

are not met.

Components:

Alkanes, C11-C16-branched and linear:

Species: Rat

Sex: male and female **Application Route: Oral**

Method: Test(s) equivalent or similar to OECD Test Guideline

Remarks: Based on available data, the classification criteria

are not met.

Effects on foetal : Species: Rat, female development Application Route: Oral

Method: Test(s) equivalent or similar to OECD Test Guideline

414

Remarks: Based on available data, the classification criteria

are not met.

Species: Rat, female

Application Route: Inhalation

Method: Test(s) equivalent or similar to OECD Test Guideline

GTL GS1927 HF

Print Date 17.02.2025 Revision Date 10.02.2025 Version 2.0

414

Remarks: Based on available data, the classification criteria

are not met.

Reproductive toxicity -

Assessment

: This product does not meet the criteria for classification in

categories 1A/1B.

STOT - single exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

Components:

Alkanes, C11-C16-branched and linear:

Remarks: Based on available data, the classification criteria are not met.

STOT - repeated exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

Components:

Alkanes, C11-C16-branched and linear:

Remarks: Based on available data, the classification criteria are not met.

Repeated dose toxicity

Product:

Rat, male and female: **Application Route: Oral**

Method: Test(s) equivalent or similar to OECD Test Guideline 408

Target Organs: No specific target organs noted

Rat, male and female: **Application Route: Inhalation** Test atmosphere: vapour

Method: Test(s) equivalent or similar to OECD Test Guideline 413

Target Organs: No specific target organs noted

Components:

Alkanes, C11-C16-branched and linear:

Rat. male and female: **Application Route: Oral**

Method: Test(s) equivalent or similar to OECD Test Guideline 408

Target Organs: No specific target organs noted

GTL GS1927 HF

Print Date 17.02.2025 Revision Date 10.02.2025 Version 2.0

Rat, male and female: Application Route: Inhalation Test atmosphere: vapour

Method: Test(s) equivalent or similar to OECD Test Guideline 413

Target Organs: No specific target organs noted

Aspiration toxicity

Product:

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

Components:

Alkanes, C11-C16-branched and linear:

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

Further information

Product:

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

Summary on evaluation of the CMR properties

Germ cell mutagenicity: This product does not meet the criteria for classification in

Assessment categories 1A/1B.

Carcinogenicity - : This product does not meet the criteria for classification in

Assessment categories 1A/1B.

Reproductive toxicity - : This product does not meet the criteria for classification in

Assessment categories 1A/1B.

Components:

Alkanes, C11-C16-branched and linear:

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

SECTION 12: Ecological information

12.1 Toxicity

GTL GS1927 HF				
Print Date 17.02.2025		Revision Date 10.02.2025	Version 2.0	
Basis for assessment	:	Incomplete ecotoxicological data are a The information given below is based the components and the ecotoxicology Unless indicated otherwise, the data p representative of the product as a who individual component(s).	partly on a knowledge of y of similar products.	
Product:				
Toxicity to fish (Acute toxicity)	:	LL50 (Oncorhynchus mykiss (rainbow Exposure time: 96 h Method: OECD Test Guideline 203 Remarks: Practically non toxic: LL/EL/IL50 > 100 mg/l	trout)): > 1.000 mg/l	
Toxicity to daphnia and other aquatic invertebrates (Acute toxicity)	:	EL50 (Daphnia magna (Water flea)): > Exposure time: 48 h Method: OECD Test Guideline 202 Remarks: Practically non toxic: LL/EL/IL50 > 100 mg/l	- 1.000 mg/l	
Toxicity to algae (Acute toxicity)	:	EL50 (Pseudokirchneriella subcapitata Exposure time: 72 h Method: OECD Test Guideline 201 Remarks: Practically non toxic: LL/EL/IL50 > 100 mg/l	a (algae)): > 1.000 mg/l	
Toxicity to fish (Chronic toxicity)	:	Remarks: Data not available		
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) Toxicity to bacteria (Acute	:	Remarks: Data not available		
toxicity)	•	Remarks: Data not available		

Components:

Alkanes, C11-C16-branched and linear:

Toxicity to fish (Acute : LL50 (Oncorhynchus mykiss (rainbow trout)): > 1.000 mg/l

toxicity) Exposure time: 96 h

Method: OECD Test Guideline 203 Remarks: Practically non toxic:

LL/EL/IL50 > 100 mg/l

Toxicity to daphnia and other : EL50 (Daphnia magna (Water flea)): > 1.000 mg/l

aquatic invertebrates (Acute Exposure time: 48 h

toxicity) Method: OECD Test Guideline 202

Remarks: Practically non toxic: LL/EL/IL50 > 100 mg/l

: EL50 (Pseudokirchneriella subcapitata (algae)): > 1.000 mg/l Toxicity to algae (Acute toxicity)

Exposure time: 72 h

Method: OECD Test Guideline 201

GTL GS1927 HF

Print Date 17.02.2025 Revision Date 10.02.2025 Version 2.0

Remarks: Practically non toxic:

LL/EL/IL50 > 100 mg/l

Toxicity to bacteria (Acute

toxicity)

Remarks: Data not available

Toxicity to fish (Chronic

toxicity)

: Remarks: Data not available

Toxicity to daphnia and other

aquatic invertebrates (Chronic toxicity)

: Remarks: Data not available

12.2 Persistence and degradability

Product:

Biodegradability : Biodegradation: 80 %

Exposure time: 28 d

Method: OECD Test Guideline 301F

Remarks: Readily biodegradable., Oxidises rapidly by photo-

chemical reactions in air.

Components:

Alkanes, C11-C16-branched and linear:

Biodegradability : Biodegradation: 80 %

Exposure time: 28 d

Method: OECD Test Guideline 301F

Remarks: Readily biodegradable., Oxidises rapidly by photo-

chemical reactions in air.

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: Has the potential to bioaccumulate.

Partition coefficient: n-

octanol/water

: log Pow: 4,5 - 7,0

Components:

Alkanes, C11-C16-branched and linear:

Bioaccumulation : Remarks: Has the potential to bioaccumulate.

12.4 Mobility in soil

Product:

Mobility : Remarks: Floats on water., If it enters soil, it will adsorb to soil

particles and will not be mobile.

Components:

Alkanes, C11-C16-branched and linear:

Mobility : Remarks: Floats on water., If it enters soil, it will adsorb to soil

particles and will not be mobile.

12.5 Results of PBT and vPvB assessment

Product:

Revision Date 10.02.2025

GTL GS1927 HF

Assessment : The substance does not fulfill all screening criteria for

persistence, bioaccumulation and toxicity and hence is not

Version 2.0

considered to be PBT or vPvB.

Components:

Alkanes, C11-C16-branched and linear:

Print Date 17.02.2025

Assessment : The substance does not fulfill all screening criteria for

persistence, bioaccumulation and toxicity and hence is not

considered to be PBT or vPvB.

12.6 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Recover or recycle if possible.

It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.

Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment. Do not dispose into the environment, in drains or in water courses.

Do not dispose of tank water bottoms by allowing them to drain into the ground. This will result in soil and groundwater contamination.

Waste arising from a spillage or tank cleaning should be disposed of in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand.

Waste, spills or used product is dangerous waste.

Disposal should be in accordance with applicable regional,

national, and local laws and regulations.

Local regulations may be more stringent than regional or national requirements and must be complied with.

MARPOL - see International Convention for the Prevention of Pollution from Ships (MARPOL 73/78) which provides

technical aspects at controlling pollutions from ships.

Contaminated packaging : Drain container thoroughly.

After draining, vent in a safe place away from sparks and fire. Residues may cause an explosion hazard. Do not puncture,

cut or weld uncleaned drums.

Send to drum recoverer or metal reclaimer.

Comply with any local recovery or waste disposal regulations.

GTL GS1927 HF

Print Date 17.02.2025 Revision Date 10.02.2025 Version 2.0

Local legislation

SECTION 14: Transport information

14.1 UN number

ADR : Not regulated as a dangerous good **IMDG** : Not regulated as a dangerous good : Not regulated as a dangerous good IATA

14.2 Proper shipping name

ADR : Not regulated as a dangerous good **IMDG** : Not regulated as a dangerous good IATA : Not regulated as a dangerous good

14.3 Transport hazard class

ADR : Not regulated as a dangerous good **IMDG** : Not regulated as a dangerous good **IATA** : Not regulated as a dangerous good

14.4 Packing group

ADR : Not regulated as a dangerous good **IMDG** Not regulated as a dangerous good IATA : Not regulated as a dangerous good

14.5 Environmental hazards

ADR : Not regulated as a dangerous good **IMDG** Not regulated as a dangerous good

14.6 Special precautions for user

Remarks : Special Precautions: Refer to Section 7, Handling & Storage,

for special precautions which a user needs to be aware of or

needs to comply with in connection with transport.

14.7 Maritime transport in bulk according to IMO instruments

MARPOL Annex 1 rules apply for bulk shipments by sea.

Additional Information : This product may be transported under nitrogen blanketing.

> Nitrogen is an odourless and invisible gas. Exposure to nitrogen may cause asphyxiation or death. Personnel must observe strict safety precautions when involved with a

confined space entry.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Volatile organic compounds : 20 %

GTL GS1927 HF

Print Date 17.02.2025 Revision Date 10.02.2025 Version 2.0

Other regulations : The regulatory information is not intended to be

comprehensive. Other regulations may apply to this material.

The components of this product are reported in the following inventories:

TSCA : Listed ENCS : Listed

SECTION 16: Other information

Abbreviations and Acronyms : The standard abbreviations and acronyms used in this document can be looked up in reference literature (e.g.

scientific dictionaries) and/or websites.

ACGIH = American Conference of Governmental Industrial

Hvaienists

ADR = European Agreement concerning the International

Carriage of Dangerous Goods by Road

AICS = Australian Inventory of Chemical Substances ASTM = American Society for Testing and Materials

BEL = Biological exposure limits

BTEX = Benzene, Toluene, Ethylbenzene, Xylenes

CAS = Chemical Abstracts Service

CEFIC = European Chemical Industry Council CLP = Classification Packaging and Labelling

COC = Cleveland Open-Cup

DIN = Deutsches Institut fur Normung DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level

DSL = Canada Domestic Substance List

EC = European Commission

EC50 = Effective Concentration fifty

ECETOC = European Center on Ecotoxicology and

Toxicology Of Chemicals

ECHA = European Chemicals Agency

EINECS = The European Inventory of Existing Commercial

Chemical Substances

EL50 = Effective Loading fifty

ENCS = Japanese Existing and New Chemical Substances

Inventory

EWC = European Waste Code

GHS = Globally Harmonised System of Classification and

Labelling of Chemicals

IARC = International Agency for Research on Cancer

IATA = International Air Transport Association

IC50 = Inhibitory Concentration fifty

IL50 = Inhibitory Level fifty

IMDG = International Maritime Dangerous Goods

INV = Chinese Chemicals Inventory

IP346 = Institute of Petroleum test method N° 346 for the

	G	TL GS1927 HF
Print Date 17.02.2025	Revision Date 10.02.2025	Version 2.0
	determination of polycyclic aromatics DM KECI = Korea Existing Chemicals Inventor LC50 = Lethal Concentration fifty LD50 = Lethal Dose fifty per cent. LL/EL/IL = Lethal Loading/Effective Load LL50 = Lethal Loading fifty MARPOL = International Convention for Pollution From Ships NOEC/NOEL = No Observed Effect Concobserved Effect Level OE_HPV = Occupational Exposure - Hig PBT = Persistent, Bioaccumulative and TPICCS = Philippine Inventory of Chemical Substances PNEC = Predicted No Effect Concentration REACH = Registration Evaluation And A Chemicals RID = Regulations Relating to Internation Dangerous Goods by Rail SKIN_DES = Skin Designation STEL = Short term exposure limit TRA = Targeted Risk Assessment TSCA = US Toxic Substances Control Act TWA = Time-Weighted Average vPvB = very Persistent and very Bioaccumulative control and the product of the prod	ding/Inhibitory loading the Prevention of centration / No th Production Volume Foxic als and Chemical on uthorisation Of hal Carriage of
Further information		
Training advice	 Provide adequate information, instruction operators. 	n and training for
Other information	: A vertical bar () in the left margin indicate from the previous version.	es an amendment
Sources of key data used to compile the Safety Data Sheet	: The quoted data are from, but not limited sources of information (e.g. toxicological Health Services, material suppliers' data, IUCLID date base, EC 1272 regulation, e	data from Shell , CONCAWE, EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.