

SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105

Ethylene Glycol Fiber Grade

Initial release date: 2009/07/10

Revision Date: 09.07.2024

Version 3.5

SDS Number: 800001000739

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Ethylene Glycol Fiber Grade

Product code : U1285

Registration number EU : 01-2119456816-28-0001, 01-2119456816-28-0002
CAS-No. : 107-21-1

Other means of identification : Dihydroxy ethane 1,2, Ethane diol 1,2, Ethylene Glycol, Glycol, MEG

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Chemical intermediate.

Recommended restrictions on use : This product must not be used in applications other than the above without first seeking the advice of the supplier., Do not use in the manufacture or preparation of foods or pharmaceuticals., Keep out of reach of children and pets., Do not use in theatrical fogs or other artificial smoke generator applications., Do not use in aircraft deicing applications.
This product must not be used in applications other than those listed in Section 1 without first seeking the advice of the supplier.

1.3 Details of the supplier of the safety data sheet

Company : **Shell Chemicals Europe B.V.**
PO Box 2334
3000 CH Rotterdam
Netherlands

Telephone : +31 (0)10 441 5137 / +31 (0)10 441 5191

Telefax : +31 (0)20 716 8316 / +31 (0)20 713 9230

E-mail address of person responsible for the SDS : sccmsds@shell.com

1.4 Emergency telephone number

Emergency telephone number : +44 (0) 1235 239 670 (This telephone number is available 24 hours per day, 7 days per week)
National Poison Counselling Centre (UZEM) – 114

SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105

Ethylene Glycol Fiber Grade

Initial release date: 2009/07/10

Revision Date: 09.07.2024

Version 3.5

SDS Number: 800001000739

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification T.R. SEA No 28848

Acute toxicity, Category 4

H302: Harmful if swallowed.

Specific target organ toxicity - repeated exposure, Category 2, Kidney

H373: May cause damage to organs through prolonged or repeated exposure.

2.2 Label elements

Labelling T.R. SEA No 28848

Hazard pictograms :



Signal word : Warning

Hazard statements :

H302
H373

PHYSICAL HAZARDS:

Not classified as a physical hazard under GHS criteria.

HEALTH HAZARDS:

Harmful if swallowed.

May cause damage to organs (Kidney) through prolonged or repeated exposure.

ENVIRONMENTAL HAZARDS:

Not classified as an environmental hazard under GHS criteria.

Precautionary statements : **Prevention:**

P260

Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

P264

Wash hands thoroughly after handling.

P270

Do not eat, drink or smoke when using this product.

Response:

P301 + P312

IF SWALLOWED: Call a POISON CENTER/ doctor if you feel unwell.

P330

Rinse mouth.

P314

Get medical advice/ attention if you feel unwell.

Storage:

No precautionary phrases.

Disposal:

P501

Dispose of contents/ container to an approved waste disposal plant.

SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105

Ethylene Glycol Fiber Grade

Initial release date: 2009/07/10

Revision Date: 09.07.2024

Version 3.5

SDS Number: 800001000739

2.3 Other hazards

Inhalation of vapours or mists may cause irritation to the respiratory system.

Slightly irritating to respiratory system.

Slightly irritating to the skin.

Slightly irritating to the eye.

Vapours may be irritating to the eye.

SECTION 3: Composition/information on ingredients

3.1 Substances

Substance name : 107-21-1

Hazardous components

Chemical name	CAS-No. EC-No. Registration number	T.R. SEA No 28848	Concentration (% w/w)
ethanediol	107-21-1 203-473-3	Acute Tox.4; H302 STOT RE2; H373	99 - 100

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Not expected to be a health hazard when used under normal conditions.

Protection of first-aiders : When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.

If inhaled : Remove to fresh air. If rapid recovery does not occur, transport to nearest medical facility for additional treatment.

In case of skin contact : Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available.
If persistent irritation occurs, obtain medical attention.

In case of eye contact : Flush eye with copious quantities of water.
Remove contact lenses, if present and easy to do. Continue rinsing.
If persistent irritation occurs, obtain medical attention.

If swallowed : If swallowed, do not induce vomiting: transport to nearest medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.
Rinse mouth.

SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105

Ethylene Glycol Fiber Grade

Initial release date: 2009/07/10

Revision Date: 09.07.2024

Version 3.5

SDS Number: 800001000739

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Kidney toxicity may be recognized by blood in the urine or increased or decreased urine flow. Other signs and symptoms can include nausea, vomiting, abdominal cramps, diarrhoea, lumbar pain shortly after ingestion, and possibly narcosis and death.
Not considered to be an inhalation hazard under normal conditions of use.
Respiratory irritation signs and symptoms may include a temporary burning sensation of the nose and throat, coughing, and/or difficulty breathing.
No specific hazards under normal use conditions.
Skin irritation signs and symptoms may include a burning sensation, redness, or swelling.
Eye irritation signs and symptoms may include a burning sensation, redness, swelling, and/or blurred vision.
Ingestion may result in nausea, vomiting and/or diarrhoea.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Call a doctor or poison control center for guidance.
Treat symptomatically.
May cause significant renal, respiratory, and CNS toxicity.
May cause significant acidosis.
The preferred treatment is immediate transportation to a medical facility and use of appropriate treatment including possible administration of activated charcoal, gastric lavage and or gastric aspiration. If none of the above are immediately available and a delay of more than one hour is anticipated before such medical attention can be obtained, induction of vomiting may be appropriate using IPECAC syrup (Contraindicated if there are any signs of CNS depression). This should be considered on a case by case basis following specialist advice.
Specific other treatments may include ethanol therapy, fomepizole, treatment of acidosis and haemodialysis. Seek specialist advice without delay.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

Unsuitable extinguishing media : Do not use water in a jet.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire- : Material will not burn unless preheated.

SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105

Ethylene Glycol Fiber Grade

Initial release date: 2009/07/10

Revision Date: 09.07.2024

Version 3.5

SDS Number: 800001000739

fighting

Carbon monoxide may be evolved if incomplete combustion occurs.

Containers exposed to intense heat from fires should be cooled with large quantities of water.

5.3 Advice for firefighters

Special protective equipment for firefighters

: Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

Specific extinguishing methods

: Standard procedure for chemical fires.

Further information

: Evacuate the area of all non-essential personnel. Keep adjacent containers cool by spraying with water.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions

: Observe all relevant local and international regulations. Notify authorities if any exposure to the general public or the environment occurs or is likely to occur. Local authorities should be advised if significant spillages cannot be contained. Avoid contact with skin, eyes and clothing.

6.2 Environmental precautions

Environmental precautions

: Prevent from spreading or entering into drains, ditches or rivers by using sand, earth, or other appropriate barriers. Use appropriate containment to avoid environmental contamination. Ventilate contaminated area thoroughly.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up

: Contain run-off from residue flush and dispose of properly. Soak up residue with an absorbent such as clay, sand or other suitable material.

For small liquid spills (< 1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.

For large liquid spills (> 1 drum), transfer by mechanical

SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105

Ethylene Glycol Fiber Grade

Initial release date: 2009/07/10

Revision Date: 09.07.2024

Version 3.5

SDS Number: 800001000739

means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely

6.4 Reference to other sections

For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet., For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- | | |
|-------------------------|---|
| Technical measures | : Avoid breathing of or direct contact with material. Only use in well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet.
Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.
Ensure that all local regulations regarding handling and storage facilities are followed. |
| Advice on safe handling | : Use local exhaust extraction over processing area.
Handle and open container with care in a well-ventilated area.
Do not empty into drains.
When handling product in drums, safety footwear should be worn and proper handling equipment should be used.
Handling Temperature:
Ambient. |
| Hygiene measures | : Wash hands before eating, drinking, smoking and using the toilet. Launder contaminated clothing before re-use. |

7.2 Conditions for safe storage, including any incompatibilities

- | | |
|---|---|
| Requirements for storage areas and containers | : Refer to section 15 for any additional specific legislation covering the packaging and storage of this product. |
| Other data | : Tanks must be clean, dry and rust-free. Keep container tightly closed. Must be stored in a diked (bunded) well- ventilated area, away from sunlight, ignition sources and other sources of heat. Cleaning, inspection and maintenance of storage tanks is a specialist operation, which requires the implementation of strict procedures and precautions. Drums should be stacked to a maximum of 3 high. Storage Temperature: Ambient. |

SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105

Ethylene Glycol Fiber Grade

Initial release date: 2009/07/10

Revision Date: 09.07.2024

Version 3.5

SDS Number: 800001000739

Packaging material : Suitable material: Stainless steel., Mild steel., Carbon steel
Unsuitable material: Data not available

7.3 Specific end use(s)

Specific use(s) : Please refer to section 16 and/or the annexes for the registered uses under REACH.

Ensure that all local regulations regarding handling and storage facilities are followed.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
ethanediol	107-21-1	TWA (8 Hour)	20 ppm 52 mg/m ³	TR OEL
Further information	A skin notation assigned to the OEL identifies the possibility of significant uptake through the skin.			
		STEL 15 min	40 ppm 104 mg/m ³	TR OEL
Further information	A skin notation assigned to the OEL identifies the possibility of significant uptake through the skin.			
		STEL	40 ppm 104 mg/m ³	2000/39/EC
Further information	Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	20 ppm 52 mg/m ³	2000/39/EC
Further information	Identifies the possibility of significant uptake through the skin, Indicative			

Biological occupational exposure limits

No biological limit allocated.

8.2 Exposure controls

Engineering measures

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

Adequate ventilation to control airborne concentrations.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

Eye washes and showers for emergency use.

General Information:

Always observe good personal hygiene measures, such as washing hands after handling the ma-

SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105

Ethylene Glycol Fiber Grade

Initial release date: 2009/07/10

Revision Date: 09.07.2024

Version 3.5

SDS Number: 800001000739

terial and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

Personal protective equipment

Eye protection : If material is handled such that it could be splashed into eyes, protective eyewear is recommended.

Hand protection

Remarks : Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. Longer term protection: Nitrile rubber gloves. Incidental contact/Splash protection: PVC or neoprene rubber gloves. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

Skin and body protection : Skin protection is not ordinarily required beyond standard work clothes.
It is good practice to wear chemical resistant gloves.

Respiratory protection : If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation.
Check with respiratory protective equipment suppliers.
Where air-filtering respirators are unsuitable (e.g. airborne

SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105

Ethylene Glycol Fiber Grade

Initial release date: 2009/07/10

Revision Date: 09.07.2024

Version 3.5

SDS Number: 800001000739

concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter.

If air-filtering respirators are suitable for conditions of use: Select a filter suitable for the combination of organic gases and vapours and particles [Type A/Type P boiling point >65°C (149°F)].

Protective measures : Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Thermal hazards : Not applicable

Environmental exposure controls

General advice : Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour.
Minimise release to the environment. An environmental assessment must be made to ensure compliance with local environmental legislation.
Information on accidental release measures are to be found in section 6.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : Slightly viscous liquid.

Colour : colourless

Odour : mild

Odour Threshold : Data not available

pH : Data not available

Melting / freezing point : -13 °C

Boiling point/boiling range : 196 - 200 °C

Flash point : 115 °C
Method: Pensky-Martens closed cup

Evaporation rate : 0,01
Method: ASTM D 3539, nBuAc=1

SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105

Ethylene Glycol Fiber Grade

Initial release date: 2009/07/10

Revision Date: 09.07.2024

Version 3.5

SDS Number: 800001000739

Flammability	
Flammability (solid, gas)	: Not applicable
Lower explosion limit and upper explosion limit / flammability limit	
Upper explosion limit	: 28 %(V)
Lower explosion limit	: 3,2 %(V)
Vapour pressure	: < 10 Pa (20 °C)
Relative vapour density	: 2,14 (Air = 1.0)
Relative density	: 1,1155 (20 °C) Method: ASTM D4052
Density	: 1.113 kg/m ³ (20 °C) Method: ASTM D4052
Solubility(ies)	
Water solubility	: completely soluble
Partition coefficient: n-octanol/water	: log Pow: -1,93 (20 °C)
Auto-ignition temperature	: 398 °C
Decomposition temperature	: Data not available
Viscosity	
Viscosity, dynamic	: 16,1 mPa.s (25 °C) Method: ASTM D445
Viscosity, kinematic	: 24,8 mm ² /s (20 °C) Method: ASTM D445
Explosive properties	: Not applicable
Oxidizing properties	: Data not available

9.2 Other information

Surface tension	: Data not available
Conductivity	: Electrical conductivity: > 10,000 pS/m

SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105

Ethylene Glycol Fiber Grade

Initial release date: 2009/07/10

Revision Date: 09.07.2024

Version 3.5

SDS Number: 800001000739

A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid, This material is not expected to be a static accumulator.

Molecular weight : 62 g/mol

SECTION 10: Stability and reactivity

10.1 Reactivity

The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.

10.2 Chemical stability

No hazardous reaction is expected when handled and stored according to provisions
Oxidises on contact with air.

10.3 Possibility of hazardous reactions

Hazardous reactions : None known.

10.4 Conditions to avoid

Conditions to avoid : Extremes of temperature and direct sunlight.

Product cannot ignite due to static electricity.

10.5 Incompatible materials

Materials to avoid : Strong oxidising agents.
Strong acids.
Strong bases.

10.6 Hazardous decomposition products

Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids and gases including carbon monoxide, carbon dioxide, sulphur oxides and unidentified organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Information on likely routes of exposure : Skin and eye contact are the primary routes of exposure although exposure may occur through inhalation or following accidental ingestion.

Acute toxicity

Components:
ethanediol:

SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105

Ethylene Glycol Fiber Grade

Initial release date: 2009/07/10

Revision Date: 09.07.2024

Version 3.5

SDS Number: 800001000739

- Acute oral toxicity : LD 50 (Rat, male and female): > 2.000 mg/kg
Method: Acceptable non-standard method.
Remarks: Harmful if swallowed.
There is a marked difference in acute oral toxicity between rodents and man, man being more susceptible than rodents.
The estimated fatal dose for man is 100 milliliters (1/2 cup).
This material has also been shown to be toxic and potentially lethal by ingestion to cats and dogs.
- Acute inhalation toxicity : LC 50 (Rat, male and female): > 2,5 mg/l
Exposure time: 6 h
Test atmosphere: Aerosol
Method: Literature data
Remarks: LC50 > 1.0 - <= 5.0 mg/l
LC50 greater than near-saturated vapour concentration.
Based on available data, the classification criteria are not met.
- Acute dermal toxicity : LD 50 (Mouse, male and female): > 2.000 mg/kg
Method: Literature data
Remarks: Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Components:

ethanediol:

Species: Rabbit

Method: Acceptable non-standard method.

Remarks: Slightly irritating to skin.

Insufficient to classify.

Serious eye damage/eye irritation

Components:

ethanediol:

Species: Rabbit

Method: Acceptable non-standard method.

Remarks: Slightly irritating to the eye.

Insufficient to classify.

Respiratory or skin sensitisation

Components:

ethanediol:

Species: Guinea pig

Method: Literature data

Remarks: Based on available data, the classification criteria are not met.

SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105

Ethylene Glycol Fiber Grade

Initial release date: 2009/07/10

Revision Date: 09.07.2024

Version 3.5

SDS Number: 800001000739

Germ cell mutagenicity

Components:

ethanediol:

- Genotoxicity in vitro : Method: OECD Test Guideline 471
Remarks: Based on data from similar materials
- : Method: Acceptable non-standard method.
Remarks: Based on data from similar materials
- : Method: Literature data
Remarks: Based on data from similar materials
- Genotoxicity in vivo : Species: Rat
Method: Literature data
Remarks: Based on available data, the classification criteria are not met.
- Germ cell mutagenicity- Assessment : This product does not meet the criteria for classification in categories 1A/1B.

Carcinogenicity

Components:

ethanediol:

Species: Mouse, (male and female)
Application Route: Oral
Method: Literature data
Remarks: Based on available data, the classification criteria are not met.

- Carcinogenicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

Material	SEA Carcinogenicity Classification
ethanediol	No carcinogenicity classification.

Reproductive toxicity

Components:

ethanediol:

- Effects on fertility : Species: Rat
Sex: male and female
Application Route: Oral
- Method: Literature data
Remarks: Based on available data, the classification criteria are not met.
- Effects on foetal development : Species: Rat, male and female
Application Route: Oral

SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105

Ethylene Glycol Fiber Grade

Initial release date: 2009/07/10

Revision Date: 09.07.2024

Version 3.5

SDS Number: 800001000739

Method: Literature data

Remarks: Based on available data, the classification criteria are not met.

Causes foetotoxicity in animals; considered to be secondary to maternal toxicity.

Reproductive toxicity - Assessment

: This product does not meet the criteria for classification in categories 1A/1B.

STOT - single exposure

Components:

ethanediol:

Remarks: Inhalation of vapours or mists may cause irritation to the respiratory system.

Based on available data, the classification criteria are not met.

Ingestion may cause drowsiness and dizziness.

STOT - repeated exposure

Components:

ethanediol:

Exposure routes: Oral

Target Organs: Kidney

Remarks: May cause damage to organs or organ systems through prolonged or repeated exposure.

Repeated dose toxicity

Components:

ethanediol:

Species: Rat, male

Application Route: Oral

Method: Test(s) equivalent or similar to OECD Test Guideline 408

Target Organs: Kidney

Aspiration toxicity

Components:

ethanediol:

Based on available data, the classification criteria are not met.

Further information

Product:

Remarks: Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

Components:

ethanediol:

SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105

Ethylene Glycol Fiber Grade

Initial release date: 2009/07/10

Revision Date: 09.07.2024

Version 3.5

SDS Number: 800001000739

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

SECTION 12: Ecological information

12.1 Toxicity

Components:

ethanediol:

- | | |
|--|---|
| Toxicity to fish (Acute toxicity) | : LC50 (Pimephales promelas (fathead minnow)): 72.860 mg/l
Exposure time: 96 h
Method: Other guideline method.
Remarks: Practically non toxic:
LC/EC/IC50 > 100 mg/l |
| Toxicity to daphnia and other aquatic invertebrates (Acute toxicity) | : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
Remarks: Practically non toxic:
LC/EC/IC50 > 100 mg/l |
| Toxicity to algae (Acute toxicity) | : EC50 (Pseudokirchneriella subcapitata (algae)): 6.500 - 13.000 mg/l
Exposure time: 96 h
Method: Other guideline method.
Remarks: Practically non toxic:
LC/EC/IC50 > 100 mg/l |
| Toxicity to bacteria (Acute toxicity) | : EC20 (Activated sludge, domestic waste): > 1.995 mg/l
Exposure time: 0,5 h
Method: Other guideline method.
Remarks: Practically non toxic:
LC/EC/IC50 > 100 mg/l |
| Toxicity to fish (Chronic toxicity) | : NOEC: 15.380 mg/l
Exposure time: 7 d
Species: Pimephales promelas (fathead minnow)
Method: Other guideline method.
Remarks: NOEC/NOEL > 100 mg/l |
| Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) | : NOEC: 8.590 mg/l
Exposure time: 7 d
Species: Chironomus sp. (midge)
Method: Other guideline method.
Remarks: NOEC/NOEL > 100 mg/l |

12.2 Persistence and degradability

Components:

ethanediol:

SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105

Ethylene Glycol Fiber Grade

Initial release date: 2009/07/10

Revision Date: 09.07.2024

Version 3.5

SDS Number: 800001000739

Biodegradability : Biodegradation: 90 - 100 %
Exposure time: 10 d
Method: OECD Test Guideline 301A
Remarks: Readily biodegradable.

12.3 Bioaccumulative potential

Components:

ethanediol:

Bioaccumulation : Remarks: Does not have the potential to bioaccumulate significantly.

12.4 Mobility in soil

Components:

ethanediol:

Mobility : Remarks: Disperses in water., If product enters soil, one or more constituents will be highly mobile and may contaminate groundwater.

12.5 Results of PBT and vPvB assessment

Components:

ethanediol:

Assessment : The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB..

12.6 Other adverse effects

Product:

Further information : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Additional ecological information : Remarks: Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

Components:

ethanediol:

Additional ecological information : Remarks: Does not have ozone depletion potential.

SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105

Ethylene Glycol Fiber Grade

Initial release date: 2009/07/10

Revision Date: 09.07.2024

Version 3.5

SDS Number: 800001000739

SECTION 13: Disposal considerations

13.1 Waste treatment methods

- Product
- : Recover or recycle if possible.
It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.
Remove all packaging for recovery or waste disposal.
Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment.
Do not dispose of tank water bottoms by allowing them to drain into the ground. This will result in soil and groundwater contamination.
Do not dispose into the environment, in drains or in water courses.
Waste arising from a spillage or tank cleaning should be disposed of in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand.
 - Disposal should be in accordance with applicable regional, national, and local laws and regulations.
Local regulations may be more stringent than regional or national requirements and must be complied with.
 - MARPOL - see International Convention for the Prevention of Pollution from Ships (MARPOL 73/78) which provides technical aspects at controlling pollutions from ships.
- Contaminated packaging
- : Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand.

SECTION 14: Transport information

14.1 UN number

- ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.2 UN proper shipping name

- ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.3 Transport hazard class(es)

SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105

Ethylene Glycol Fiber Grade

Initial release date: 2009/07/10

Revision Date: 09.07.2024

Version 3.5

SDS Number: 800001000739

ADR	: Not regulated as a dangerous good
RID	: Not regulated as a dangerous good
IMDG	: Not regulated as a dangerous good
IATA	: Not regulated as a dangerous good

14.4 Packing group

ADR	: Not regulated as a dangerous good
RID	: Not regulated as a dangerous good
IMDG	: Not regulated as a dangerous good
IATA	: Not regulated as a dangerous good

14.5 Environmental hazards

ADR	: Not regulated as a dangerous good
RID	: Not regulated as a dangerous good
IMDG	: Not regulated as a dangerous good

14.6 Special precautions for user

Remarks	: Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.
---------	--

14.7 Maritime transport in bulk according to IMO instruments

Pollution category	: Z
Ship type	: 3
Product name	: Ethylene glycol

Additional Information	: This product may be transported under nitrogen blanketing. Nitrogen is an odourless and invisible gas. Exposure to nitrogen enriched atmospheres displaces available oxygen which may cause asphyxiation or death. Personnel must observe strict safety precautions when involved with a confined space entry.
------------------------	--

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

KKDIK (30105 (Bis)) - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex 17)	: Conditions of restriction for the following entries should be considered: Entry number 3
--	--

Other regulations	: The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.
-------------------	---

Regulations on the health and safety precautions for chemicals in the workplace. Regulations on the fire protection of buildings. Regulations on the prevention of industrial accidents and the reduction of their effects.

SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105

Ethylene Glycol Fiber Grade

Initial release date: 2009/07/10

Revision Date: 09.07.2024

Version 3.5

SDS Number: 800001000739

The components of this product are reported in the following inventories:

DSL : Listed

IECSC : Listed

ENCS : Listed

KECI : Listed

NZIoC : Listed

PICCS : Listed

TSCA : Listed

TCSI : Listed

15.2 Chemical safety assessment

A Chemical Safety Assessment has been carried out for this substance.

SECTION 16: Other information

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Ef-

SAFETY DATA SHEET

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105

Ethylene Glycol Fiber Grade

Initial release date: 2009/07/10

Revision Date: 09.07.2024

Version 3.5

SDS Number: 800001000739

fect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Prepared by

Name : Eren Aktas

Certified Qualification date : 15.05.2024

Certificate number : TÜV/11.241.01

Expiry date : 15.05.2029

Further information

Training advice : Provide adequate information, instruction and training for operators.

Other information : A vertical bar (|) in the left margin indicates an amendment from the previous version.

Sources of key data used to compile the Safety Data Sheet : The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID data base, EC 1272 regulation, etc).

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

TR / EN