Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105

Methyl Isobutyl Carbinol

Initial release date: 2008/09/09 Revision Date: 14.11.2024

Version 3.0

SDS Number: 800001005658

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Methyl Isobutyl Carbinol

Product code : S1216

Registration number EU : 01-2119473979-13-0001

Synonyms : 1,3-dimethyl 1-butanol, 4-methylpentan-2-ol, Methyl Amyl

Alcohol, MIBC

CAS-No. : 108-11-2

Index-No. : 603-008-00-8

EC-No. : 203-551-7

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-: Solvent.

stance/Mixture

Recommended restrictions

This product must not be used in applications other than those on use

listed in Section 1 without first seeking the advice of the sup-

plier.

1.3 Details of the supplier of the safety data sheet

Company : Shell Chemicals Europe B.V.

> PO Box 2334 3000 CH Rotterdam

Netherlands

Telephone : +31 (0)10 441 5137 / +31 (0)10 441 5191

Telefax : +31 (0)20 716 8316 / +31 (0)20 713 9230

E-mail address of person responsible for the SDS

: sccmsds@shell.com

1.4 Emergency telephone number

Emergency telephone num-: +44 (0) 1235 239 670 (This telephone number is available 24

ber hours per day, 7 days per week)

National Poison Counselling Centre (UZEM) - 114

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105

Methyl Isobutyl Carbinol

Initial release date: 2008/09/09 Revision Date: 14.11.2024

Version 3.0

SDS Number: 800001005658

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification T.R. SEA No 28848

Flammable liquids, Category 3 H226: Flammable liquid and vapour.

Eye irritation, Category 2 H319: Causes serious eye irritation.

Specific target organ toxicity - single exposure, Category 3, Respiratory system

H335: May cause respiratory irritation.

2.2 Label elements

Labelling T.R. SEA No 28848

Hazard pictograms





Signal word : Warning

Hazard statements : PHYSICAL HAZARDS:

H226 Flammable liquid and vapour.

HEALTH HAZARDS:

H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
ENVIRONMENTAL HAZARDS:

Not classified as an environmental hazard

under GHS criteria.

Precautionary statements : Prevention:

P210 Keep away from heat/ sparks/ open flames/

hot surfaces. No smoking.

P280 Wear protective gloves/ protective clothing/

eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immedi-

ately all contaminated clothing. Rinse skin

with water/ shower.

P370 + P378 In case of fire: Use appropriate media to

extinguish.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with wa-

ter for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing.

Storage:

No precautionary phrases.

Disposal:

P501 Dispose of contents/ container to an ap-

proved waste disposal plant.

2 / 20 800001005658 TR

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105

Methyl Isobutyl Carbinol

Initial release date: 2008/09/09 Revision Date: 14.11.2024

Version 3.0

SDS Number: 800001005658

2.3 Other hazards

Vapours are heavier than air. Vapours may travel across the ground and reach remote ignition sources causing a flashback fire danger.

Even with proper grounding and bonding, this material can still accumulate an electrostatic charge.

If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur.

SECTION 3: Composition/information on ingredients

3.1 Substances

Substance name : Methyl Isobutyl Carbinol, 108-11-2

Index-No. : 603-008-00-8

Hazardous components

Chemical name	CAS-No. EC-No. Registration number	T.R. SEA No 28848	Concentration (% w/w)
4-methylpentan-2-ol	108-11-2 203-551-7	Flam. Liq.3; H226 Eye Irrit.2; H319 STOT SE3; H335	100

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : In general no treatment is necessary, however, obtain medical

advice.

Protection of first-aiders : When administering first aid, ensure that you are wearing the

appropriate personal protective equipment according to the

incident, injury and surroundings.

If inhaled : Remove to fresh air. If rapid recovery does not occur,

transport to nearest medical facility for additional treatment.

In case of skin contact : Remove contaminated clothing. Immediately flush skin with

large amounts of water for at least 15 minutes, and follow by washing with soap and water if available. If needed, transport

to the nearest medical facility for additional treatment.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses, if present and easy to do. Continue

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105

Methyl Isobutyl Carbinol

Initial release date: 2008/09/09 Revision Date: 14.11.2024

Version 3.0

SDS Number: 800001005658

rinsing.

Transport to the nearest medical facility for additional treat-

ment.

If swallowed : If swallowed, do not induce vomiting: transport to nearest

medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.

Rinse mouth.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Respiratory irritation signs and symptoms may include a tem-

porary burning sensation of the nose and throat, coughing,

and/or difficulty breathing.

Skin irritation signs and symptoms may include a burning sen-

sation, redness, or swelling.

Eye irritation signs and symptoms may include a burning sen-

sation, redness, swelling, and/or blurred vision.

Ingestion may result in nausea, vomiting and/or diarrhoea.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Call a doctor or poison control center for guidance.

Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam, water spray or fog. Dry chemical pow-

der, carbon dioxide, sand or earth may be used for small fires

only.

Unsuitable extinguishing

media

: None

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

: The vapour is heavier than air, spreads along the ground and

distant ignition is possible.

Carbon monoxide may be evolved if incomplete combustion

occurs.

5.3 Advice for firefighters

Special protective equipment

for firefighters

Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to

relevant Standards (e.g. Europe: EN469).

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105

Methyl Isobutyl Carbinol

Initial release date: 2008/09/09 Revision Date: 14.11.2024

Version 3.0

SDS Number: 800001005658

Specific extinguishing meth-

ods

: Standard procedure for chemical fires.

Further information

: Clear fire area of all non-emergency personnel. Keep adjacent containers cool by spraying with water.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Observe the relevant local and international regulations

Notify authorities if any exposure to the general public or the

environment occurs or is likely to occur.

Local authorities should be advised if significant spillages

cannot be contained.

The vapour is heavier than air, spreads along the ground and

distant ignition is possible.

Vapour may form an explosive mixture with air. Avoid contact with skin, eyes and clothing.

Isolate hazard area and deny entry to unnecessary or unpro-

tected personnel.

Stay upwind and keep out of low areas.

6.2 Environmental precautions

Environmental precautions

: Shut off leaks, if possible without personal risks. Remove all possible sources of ignition in the surrounding area. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. Attempt to disperse the vapour or to direct its flow to a safe location for example by using fog sprays. Take precautionary measures against static discharge. Ensure electrical continuity by bond-

ing and grounding (earthing) all equipment. Ventilate contaminated area thoroughly. Monitor area with combustible gas indicator.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : For large liquid spills (> 1 drum), transfer by mechanical

means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely For small liquid spills (< 1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove

contaminated soil and dispose of safely.

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105

Methyl Isobutyl Carbinol

Initial release date: 2008/09/09 Revision Date: 14.11.2024

Version 3.0

SDS Number: 800001005658

6.4 Reference to other sections

For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet., For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures : Avoid breathing of or direct contact with material. Only use in

well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see

Section 8 of this Safety Data Sheet.

Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this

material.

Ensure that all local regulations regarding handling and stor-

age facilities are followed.

Advice on safe handling : Avoid contact with skin, eyes and clothing.

Use local exhaust ventilation if there is risk of inhalation of

vapours, mists or aerosols.

Bulk storage tanks should be diked (bunded).

Extinguish any naked flames. Do not smoke. Remove ignition

sources. Avoid sparks.

Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment to

reduce the risk.

The vapours in the head space of the storage vessel may lie in the flammable/explosive range and hence may be flamma-

ble.

Properly dispose of any contaminated rags or cleaning mate-

rials in order to prevent fires.

Do NOT use compressed air for filling, discharging, or han-

dling operations.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

 The vapour is heavier than air. Beware of accumulation in pits and confined spaces. Refer to section 15 for any additional specific legislation covering the packaging and storage of this

product.

Packaging material : Suitable material: For containers, or container linings use mild

steel, stainless steel.

Unsuitable material: Natural, butyl, neoprene or nitrile rubbers.

7.3 Specific end use(s)

Specific use(s) : Please refer to section 16 and/or the annexes for the regis-

tered uses under REACH.

6 / 20 800001005658 TR

Prepared in accordance with the provisions of KKDIK Annex-2 Regu-

lation, 23.06.2017, No: 30105

Methyl Isobutyl Carbinol

Initial release date: 2008/09/09 Revision Date: 14.11.2024

Version 3.0

SDS Number: 800001005658

Ensure that all local regulations regarding handling and storage facilities are followed.

See additional references that provide safe handling practices: American Petroleum Institute 2003 (Protection Against Ignitions Arising out of Static, Lightning and Stray Currents) or National Fire Protection Agency 77 (Recommended Practices

on Static Electricity).

IEC/TS 60079-32-1: Electrostatic hazards, guidance

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form	Control parameters	Basis
		of exposure)		
4-methylpentan-2-	108-11-2	TWA (8 Hour)	25 ppm	TR OEL
ol			100 mg/m3	
Further information	A skin notation assigned to the OEL identifies the possibility of significant up-			
	take through the skin.			

Biological occupational exposure limits

No biological limit allocated.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

4-methylpentan-2-ol : End Use: Workers

Exposure routes: Inhalation

Potential health effects: Acute systemic effects

Value: 208 mg/m3 End Use: Workers

Exposure routes: Inhalation

Potential health effects: Acute local effects

Value: 104 mg/m3 End Use: Workers

Exposure routes: Inhalation

Potential health effects: Long-term systemic effects

Value: 83 mg/m3 End Use: Workers

Exposure routes: Inhalation

Potential health effects: Long-term local effects

Value: 83 mg/m3 End Use: Workers Exposure routes: Dermal

Potential health effects: Long-term systemic effects

Value: 11,8 mg/kg bw/day End Use: Consumers **Exposure routes: Inhalation**

Potential health effects: Acute systemic effects

Value: 155,2 mg/m3

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105

Methyl Isobutyl Carbinol

Initial release date: 2008/09/09 Revision Date: 14.11.2024

Version 3.0

SDS Number: 800001005658

End Use: Consumers Exposure routes: Inhalation

Potential health effects: Acute local effects

Value: 52,1 mg/m3 End Use: Consumers Exposure routes: Inhalation

Potential health effects: Long-term systemic effects

Value: 14,7 mg/m3 End Use: Consumers Exposure routes: Inhalation

Potential health effects: Long-term local effects

Value: 14,7 mg/m3 End Use: Consumers Exposure routes: Dermal

Potential health effects: Long-term systemic effects

Value: 4,2 mg/kg bw/day End Use: Consumers Exposure routes: Oral

Potential health effects: Long-term systemic effects

Value: 4,2 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

4-methylpentan-2-ol : Exposure assessments have not been presented for the envi-

ronment therefore PNEC values not required.

8.2 Exposure controls

Engineering measures

Use sealed systems as far as possible.

Adequate explosion-proof ventilation to control airborne concentrations below the exposure guidelines/limits.

Local exhaust ventilation is recommended.

Firewater monitors and deluge systems are recommended.

Eye washes and showers for emergency use.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

General Information:

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105

Methyl Isobutyl Carbinol

Initial release date: 2008/09/09 Revision Date: 14.11.2024

Version 3.0

SDS Number: 800001005658

Personal protective equipment

Eye protection : Wear goggles for use against liquids and gas.

Wear full face shield if splashes are likely to occur.

Hand protection

Remarks : Where hand contact with the product may occur the use of

gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. Longer term protection: Butyl rubber. Nitrile rubber. Incidental contact/Splash protection: PVC or neoprene rubber gloves. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

Skin and body protection

: Wear antistatic and flame-retardant clothing, if a local risk

assessment deems it so.

Skin protection is not required under normal conditions of use. For prolonged or repeated exposures use impervious clothing

over parts of the body subject to exposure.

If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to relevant Standard,

and provide employee skin care programmes.

Respiratory protection

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation.

Check with respiratory protective equipment suppliers. Where air-filtering respirators are unsuitable (e.g. airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus. Where air-filtering respirators are suitable, select an appropri-

ate combination of mask and filter.

If air-filtering respirators are suitable for conditions of use:

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105

Methyl Isobutyl Carbinol

Initial release date: 2008/09/09 Revision Date: 14.11.2024

Version 3.0

SDS Number: 800001005658

Select a filter suitable for organic gases and vapours [Type A

boiling point >65°C (149°F)].

Protective measures : Personal protective equipment (PPE) should meet recom-

mended national standards. Check with PPE suppliers.

Thermal hazards : Not applicable

Environmental exposure controls

General advice : Local guidelines on emission limits for volatile substances

must be observed for the discharge of exhaust air containing

vapour.

Minimise release to the environment. An environmental assessment must be made to ensure compliance with local envi-

ronmental legislation.

Information on accidental release measures are to be found in

section 6.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : Liquid.

Colour : clear

Odour : sweet

Odour Threshold : Data not available

pH : Data not available

Melting / freezing point : Data not available

Boiling point/boiling range : 130 - 133 °C

Flash point : 41 °C

Method: IP 170

Evaporation rate : 0,3

Method: ASTM D 3539, nBuAc=1

Flammability

Flammability (solid, gas) : Not applicable

Lower explosion limit and upper explosion limit / flammability limit

Upper explosion limit : upper flammability limit

5,5 %(V)

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105

Methyl Isobutyl Carbinol

Initial release date: 2008/09/09 Revision Date: 14.11.2024

Version 3.0

SDS Number: 800001005658

Lower explosion limit : Lower flammability limit

1 %(V)

Vapour pressure : 420 Pa (20 °C)

Relative vapour density : 3,5

Relative density : 0,81 (20 °C)

Method: ASTM D4052

Density : 806 - 808 kg/m3 (20 °C)

Method: ASTM D4052

Solubility(ies)

Water solubility : 16 g/l (20 °C)

Partition coefficient: n-

octanol/water

: log Pow: < 3

Auto-ignition temperature : 305 °C

Method: ASTM E-659

Decomposition temperature : Data not available

Viscosity

Viscosity, dynamic : 5,2 mPa.s (20 °C)

Method: ASTM D445

Viscosity, kinematic : Data not available

Explosive properties : Not applicable

Oxidizing properties : Data not available

9.2 Other information

Surface tension : 22,7 mN/m, 20 °C

Conductivity: > 10,000 pS/m

A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid, This material is not expected to be

a static accumulator.

Molecular weight : 102,18 g/mol

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105

Methyl Isobutyl Carbinol

Initial release date: 2008/09/09 Revision Date: 14.11.2024

Version 3.0

SDS Number: 800001005658

SECTION 10: Stability and reactivity

10.1 Reactivity

The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.

10.2 Chemical stability

No hazardous reaction is expected when handled and stored according to provisions

10.3 Possibility of hazardous reactions

Hazardous reactions : Reacts with strong oxidising agents.

10.4 Conditions to avoid

Conditions to avoid : Avoid heat, sparks, open flames and other ignition sources.

Prevent vapour accumulation.

In certain circumstances product can ignite due to static elec-

tricity.

10.5 Incompatible materials

Materials to avoid : Strong oxidising agents.

10.6 Hazardous decomposition products

Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids. liquids and gases including carbon monoxide, carbon dioxide, sulphur oxides and unidentified organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

exposure

Information on likely routes of : Inhalation is the primary route of exposure although absorption may occur through skin contact or following accidental

ingestion.

Acute toxicity

Product:

Acute oral toxicity : LD50 (Rat): > 2000 - <=5000 mg/kg

Remarks: May be harmful if swallowed.

Acute inhalation toxicity : (Rat): Remarks: Low toxicity by inhalation.

No deaths at highest tested dose.

Acute dermal toxicity : LD50 (Rabbit): > 2000 - <=5000 mg/kg

Remarks: May be harmful in contact with skin.

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105

Methyl Isobutyl Carbinol

Initial release date: 2008/09/09 Revision Date: 14.11.2024

Version 3.0

SDS Number: 800001005658

Skin corrosion/irritation

Product:

Remarks: Causes mild skin irritation.

Serious eye damage/eye irritation

Product:

Remarks: Causes serious eye irritation.

Respiratory or skin sensitisation

Product:

Remarks: Not a sensitiser.

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Product:

Genotoxicity in vivo : Remarks: No evidence of mutagenic activity.

Carcinogenicity

Product:

Remarks: Not a carcinogen.

Based on available data, the classification criteria are not met.

Material	SEA Carcinogenicity Classification
4-methylpentan-2-ol	No carcinogenicity classification.

Reproductive toxicity

Product:

Effects on fertility :

Remarks: Not a developmental toxicant.

Based on available data, the classification criteria are not met.

Does not impair fertility.

STOT - single exposure

Product:

Remarks: May cause respiratory irritation.

STOT - repeated exposure

Product:

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105

Methyl Isobutyl Carbinol

Initial release date: 2008/09/09 Revision Date: 14.11.2024

Version 3.0

SDS Number: 800001005658

Remarks: Based on available data, the classification criteria are not met.

Aspiration toxicity

Product:

Not an aspiration hazard., Based on available data, the classification criteria are not met.

Further information

Product:

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

Remarks: Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish (Acute toxici-

ty)

: Remarks: Practically non toxic:

LL/EL/IL50 > 100 mg/l

Toxicity to daphnia and other

aquatic invertebrates (Acute

toxicity)

: Remarks: Practically non toxic:

LL/EL/IL50 > 100 mg/l

Toxicity to algae (Acute tox-

icity)

: Remarks: Practically non toxic:

LL/EL/IL50 > 100 mg/l

Toxicity to fish (Chronic tox-

icity)

: Remarks: Data not available

Toxicity to daphnia and other aquatic invertebrates (Chron-

ic toxicity)

: Remarks: NOEC/NOEL > 10 - <=100 mg/l

Toxicity to bacteria (Acute

toxicity)

Remarks: Practically non toxic:

LL/EL/IL50 > 100 mg/l

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: Readily biodegradable.

Oxidises rapidly by photo-chemical reactions in air.

14 / 20 800001005658 TR

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105

Methyl Isobutyl Carbinol

Initial release date: 2008/09/09 Revision Date: 14.11.2024

Version 3.0

SDS Number: 800001005658

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: Does not bioaccumulate significantly.

12.4 Mobility in soil

Product:

Mobility : Remarks: Dissolves in water.

12.5 Results of PBT and vPvB assessment

Product:

Assessment : The substance does not fulfill all screening criteria for persis-

tence, bioaccumulation and toxicity and hence is not consid-

ered to be PBT or vPvB..

12.6 Other adverse effects

Product:

Further information : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

Additional ecological infor-

mation

Remarks: Unless indicated otherwise, the data presented is

representative of the product as a whole, rather than for indi-

vidual component(s).

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Recover or recycle if possible.

It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal meth-

ods in compliance with applicable regulations.

Do not dispose into the environment, in drains or in water

courses.

Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment. Waste, spills or used product is dangerous waste.

Disposal should be in accordance with applicable regional,

national, and local laws and regulations.

Local regulations may be more stringent than regional or na-

tional requirements and must be complied with.

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105

Methyl Isobutyl Carbinol

Initial release date: 2008/09/09 Revision Date: 14.11.2024

Version 3.0

SDS Number: 800001005658

MARPOL - see International Convention for the Prevention of Pollution from Ships (MARPOL 73/78) which provides tech-

nical aspects at controlling pollutions from ships.

Contaminated packaging Drain container thoroughly.

After draining, vent in a safe place away from sparks and fire.

Residues may cause an explosion hazard. Do not, puncture, cut, or weld uncleaned drums. Send to drum recoverer or metal reclaimer.

Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand. Disposal should be in accordance with applicable regional, national, and local laws and regulations.

Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand.

SECTION 14: Transport information

14.1 UN number

ADR : UN 2053 **RID** : UN 2053 **IMDG** : UN 2053 **IATA** : UN 2053

14.2 UN proper shipping name

: METHYL ISOBUTYL CARBINOL **ADR** RID : METHYL ISOBUTYL CARBINOL **IMDG** : METHYL ISOBUTYL CARBINOL

IATA : Methyl isobutyl carbinol

14.3 Transport hazard class(es)

ADR : 3 **RID** : 3 : 3 **IMDG** : 3 IATA

14.4 Packing group

ADR

Packing group : 111 Classification Code F1 Hazard Identification Number : 30

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105

Methyl Isobutyl Carbinol

Initial release date: 2008/09/09 Revision Date: 14.11.2024

Version 3.0

SDS Number: 800001005658

Labels : 3

RID

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

IMDG

Packing group : III Labels : 3

IATA

Packing group : III Labels : 3

14.5 Environmental hazards

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

Remarks : Special Precautions: Refer to Section 7, Handling & Storage,

for special precautions which a user needs to be aware of or

needs to comply with in connection with transport.

14.7 Maritime transport in bulk according to IMO instruments

Pollution category : Z

Ship type : 3; Must be Double Hulled Product name : Methyl amyl alcohol

Additional Information: This product may be transported under nitrogen blanketing.

Nitrogen is an odourless and invisible gas. Exposure to nitrogen enriched atmospheres displaces available oxygen which may cause asphyxiation or death. Personnel must observe strict safety precautions when involved with a confined space entry. Transport in bulk according to Annex II of Marpol and

the IBC Code

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

KKDIK (30105 (Bis)) - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex 17)

: Conditions of restriction for the following entries should be considered: Entry number 3

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105

Methyl Isobutyl Carbinol

Initial release date: 2008/09/09 Revision Date: 14.11.2024

Version 3.0

SDS Number: 800001005658

Other regulations : The regulatory information is not intended to be comprehen-

sive. Other regulations may apply to this material.

Regulations on the health and safety precautions for chemicals in the workplace. Regulations on the fire protection of buildings. Regulations on the prevention of industrial acci-

dents and the reduction of their effects.

The components of this product are reported in the following inventories:

DSL : Listed

IECSC : Listed

ENCS : Listed

KECI : Listed

PICCS : Listed

TSCA : Listed

TCSI : Listed

NZIoC : Listed

15.2 Chemical safety assessment

A Chemical Safety Assessment has been carried out for this substance.

SECTION 16: Other information

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good La-

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105

Methyl Isobutyl Carbinol

Initial release date: 2008/09/09 Revision Date: 14.11.2024

Version 3.0

SDS Number: 800001005658

boratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals: OECD - Organization for Economic Co-operation and Development: OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI -Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Prepared by

Name : Eren Aktas

Certified Qualification date : 15.05.2024

Certificate number : TÜV/11.241.01

Expiry date 15.05.2029

Further information

Training advice : Provide adequate information, instruction and training for op-

erators.

Other information : A vertical bar (|) in the left margin indicates an amendment

from the previous version.

Sources of key data used to compile the Safety Data

Sheet

: The guoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU

IUCLID date base, EC 1272 regulation, etc).

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105

Methyl Isobutyl Carbinol

Initial release date: 2008/09/09 Revision Date: 14.11.2024

Version 3.0

SDS Number: 800001005658

TR / EN