

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Propylene - Polymer Grade

Version	Revision Date:	SDS Number:	Date of last issue: 09.03.2023
2.2	28.01.2024	800001000816	Print Date 05.02.2024

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name	: Propylene - Polymer Grade
Product code	: X2121, X2125
Registration number EU	: 01-2119447103-50-0010, 01-2119447103-50-0012, 01-2119447103-50-0013, 01-2119447103-50-0014, 01-2119447103-50-0015, 01-2119447103-50-0142
CAS-No.	: 115-07-1
Other means of identification	: Propene

EC-No.	: 204-062-1
--------	-------------

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture	: Base chemical., Raw material for use in the chemical industry. Please refer to section 16 and/or the annexes for the registered uses under REACH.
Uses advised against	: This product must not be used in applications other than the above without first seeking the advice of the supplier.

#### 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier	: <b>Shell Chemicals Europe B.V.</b> PO Box 2334 3000 CH Rotterdam Netherlands
Telephone	: +31 (0)10 441 5137 / +31 (0)10 441 5191
Telefax	: +31 (0)20 716 8316 / +31 (0)20 713 9230
Contact for Safety Data Sheet	: sccmsds@shell.com

#### 1.4 Emergency telephone number

+44 (0) 1235 239 670 (24/7)

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Flammable gases, Category 1A	H220: Extremely flammable gas.
Gases under pressure, Compressed gas	H280: Contains gas under pressure; may explode if heated.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Propylene - Polymer Grade

Version	Revision Date:	SDS Number:	Date of last issue: 09.03.2023
2.2	28.01.2024	800001000816	Print Date 05.02.2024

### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements :  
H220 Extremely flammable gas.  
H280 Contains gas under pressure; may explode if heated.  
HEALTH HAZARDS:  
Not classified as a health hazard under CLP criteria.  
ENVIRONMENTAL HAZARDS:  
Not classified as environmental hazard according to CLP criteria.

Precautionary statements : **Prevention:**  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P243 Take action to prevent static discharges.  
**Response:**  
P377 Leaking gas fire: Do not extinguish, unless leak can be stopped safely.  
P381 In case of leakage, eliminate all ignition sources.  
**Storage:**  
P410 + P403 Protect from sunlight. Store in a well-ventilated place.  
**Disposal:**  
No precautionary phrases.

### 2.3 Other hazards

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

High gas concentrations will displace available air; unconsciousness and death may occur suddenly from lack of oxygen.  
Vapours may cause drowsiness and dizziness.  
Electrostatic charges may be generated during pumping. Electrostatic discharge may cause fire.  
Vapours are heavier than air. Vapours may travel across the ground and reach remote ignition sources causing a flashback fire danger.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Propylene - Polymer Grade

Version 2.2      Revision Date: 28.01.2024      SDS Number: 800001000816      Date of last issue: 09.03.2023  
Print Date 05.02.2024

May form flammable/explosive vapour-air mixture.  
This material is shipped under pressure.

### SECTION 3: Composition/information on ingredients

#### 3.1 Substances

##### Components

Chemical name	CAS-No. EC-No.	Concentration (% w/w)
propylene	115-07-1 204-062-1	> 99,5

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General advice : Not expected to be a health hazard when used under normal conditions.
- Protection of first-aiders : When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.
- If inhaled : Call emergency number for your location / facility.  
Remove to fresh air. Do not attempt to rescue the victim unless proper respiratory protection is worn. If the victim has difficulty breathing or tightness of the chest, is dizzy, vomiting, or unresponsive, give 100% oxygen with rescue breathing or Cardio-Pulmonary Resuscitation as required and transport to the nearest medical facility.
- In case of skin contact : Slowly warm the exposed area by rinsing with warm water.  
Transport to the nearest medical facility for additional treatment.
- In case of eye contact : Slowly warm the exposed area by rinsing with warm water.  
Transport to the nearest medical facility for additional treatment.
- If swallowed : In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.

#### 4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Respiratory irritation signs and symptoms may include a temporary burning sensation of the nose and throat, coughing, and/or difficulty breathing.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Propylene - Polymer Grade

Version 2.2	Revision Date: 28.01.2024	SDS Number: 800001000816	Date of last issue: 09.03.2023 Print Date 05.02.2024
----------------	------------------------------	-----------------------------	---

Breathing of high vapour concentrations may cause central nervous system (CNS) depression resulting in dizziness, light-headedness, headache, nausea and loss of coordination. Continued inhalation may result in unconsciousness and death.

Rapid release of gases which are liquids under pressure may cause frost burns of exposed tissues (skin, eye) due to evaporative cooling.

No specific hazards under normal use conditions.  
Ingestion may result in nausea, vomiting and/or diarrhoea.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : IMMEDIATE TREATMENT IS EXTREMELY IMPORTANT!  
Artificial respiration and/or oxygen may be necessary.  
Call a doctor or poison control center for guidance.  
Treat symptomatically.  
Potential for cardiac sensitisation, particularly in abuse situations. Hypoxia or negative inotropes may enhance these effects. Consider: oxygen therapy.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Shut off supply. If not possible and no risk to surroundings, let the fire burn itself out.

Unsuitable extinguishing media : Do not use water in a jet.

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Sustained fire attack on vessels may result in a Boiling Liquid Expanding Vapor Explosion (BLEVE).  
The vapour is heavier than air, spreads along the ground and distant ignition is possible.  
Contents are under pressure and can explode when exposed to heat or flames.  
As the vapours become lighter than air, the vapours may reach ignition sources at ground or elevated locations.

### 5.3 Advice for firefighters

Special protective equipment for firefighters : Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

Specific extinguishing meth- : Standard procedure for chemical fires.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Propylene - Polymer Grade

Version	Revision Date:	SDS Number:	Date of last issue: 09.03.2023
2.2	28.01.2024	800001000816	Print Date 05.02.2024

ods

Further information : Clear fire area of all non-emergency personnel.  
Keep adjacent containers cool by spraying with water.

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Observe the relevant local and international regulations  
Risk of explosion. Inform the emergency services if liquid enters surface water drains.  
Notify authorities if any exposure to the general public or the environment occurs or is likely to occur.  
Local authorities should be advised if significant spillages cannot be contained.  
6.1.1 For non emergency personnel:  
Avoid contact with skin, eyes and clothing.  
Isolate hazard area and deny entry to unnecessary or unprotected personnel.  
Do not breathe fumes, vapour.  
Do not operate electrical equipment.  
6.1.2 For emergency responders:  
Avoid contact with skin, eyes and clothing.  
Isolate hazard area and deny entry to unnecessary or unprotected personnel.  
Do not breathe fumes, vapour.  
Do not operate electrical equipment.

#### 6.2 Environmental precautions

Environmental precautions : Shut off leaks, if possible without personal risks. Remove all possible sources of ignition in the surrounding area and evacuate all personnel. Attempt to disperse the gas or to direct its flow to a safe location for example by using fog sprays. Take precautionary measures against static discharge. Ensure electrical continuity by bonding and grounding (earthing) all equipment. Monitor area with combustible gas meter.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Allow to evaporate.  
Attempt to disperse the vapour or to direct its flow to a safe location, for example by using fog sprays. Otherwise treat as for small spillage.

#### 6.4 Reference to other sections

For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet., Risk of explosion. Inform the emergency services if liquid enters surface water drains., For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet., Vapour may form an explosive mixture with air.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Propylene - Polymer Grade

Version	Revision Date:	SDS Number:	Date of last issue: 09.03.2023
2.2	28.01.2024	800001000816	Print Date 05.02.2024

---

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

- |                         |   |
|-------------------------|---|
| Technical measures      | : Avoid breathing of or direct contact with material. Only use in well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet.<br>Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.  |
| Advice on safe handling | : Extinguish any naked flames. Do not smoke. Remove ignition sources. Avoid sparks.<br>Avoid inhaling vapour and/or mists.<br>Avoid contact with skin, eyes and clothing.<br>Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols.<br>Bulk storage tanks should be diked (bunded).<br>Properly dispose of any contaminated rags or cleaning materials in order to prevent fires.<br>Even with proper grounding and bonding, this material can still accumulate an electrostatic charge.<br>If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur.<br>Be aware of handling operations that may give rise to additional hazards that result from the accumulation of static charges.<br>These include but are not limited to pumping (especially turbulent flow), mixing, filtering, splash filling, cleaning and filling of tanks and containers, sampling, switch loading, gauging, vacuum truck operations, and mechanical movements.<br>These activities may lead to static discharge e.g. spark formation.<br>Restrict line velocity during pumping in order to avoid generation of electrostatic discharge ( $\leq 1$ m/s until fill pipe submerged to twice its diameter, then $\leq 7$ m/s). Avoid splash filling.<br>Do NOT use compressed air for filling, discharging, or handling operations.<br>The vapour is heavier than air. Beware of accumulation in pits and confined spaces. |
| Product Transfer        | : Refer to guidance under Handling section.   |
| Hygiene measures        | : Wash hands before eating, drinking, smoking and using the toilet. Launder contaminated clothing before re-use.  |

#### 7.2 Conditions for safe storage, including any incompatibilities

- |  |   |
|--|---|
| Further information on storage stability | : Keep away from aerosols, flammables, oxidizing agents, corrosives and from products harmful or toxic to man or to the |
|--|---|

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Propylene - Polymer Grade

Version 2.2      Revision Date: 28.01.2024      SDS Number: 800001000816      Date of last issue: 09.03.2023  
Print Date 05.02.2024

environment.

Must be stored in a diked (bunded) well-ventilated area, away from sunlight, ignition sources and other sources of heat.

Vapours from tanks should not be released to atmosphere.

Breathing losses during storage should be controlled by a suitable vapour treatment system.

Electrostatic charges will be generated during pumping.

Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment to reduce the risk.

The vapours in the head space of the storage vessel may lie in the flammable/explosive range and hence may be flammable.

Packaging material : Suitable material: For containers, or container linings use mild steel, stainless steel.

Container Advice : Containers, even those that have been emptied, can contain explosive vapours. Do not cut, drill, grind, weld or perform similar operations on or near containers.

### 7.3 Specific end use(s)

Specific use(s) : Please refer to section 16 and/or the annexes for the registered uses under REACH.

Ensure that all local regulations regarding handling and storage facilities are followed.

See additional references that provide safe handling practices for liquids that are determined to be static accumulators: American Petroleum Institute 2003 (Protection Against Ignitions Arising out of Static, Lightning and Stray Currents) or National Fire Protection Agency 77 (Recommended Practices on Static Electricity).

IEC/TS 60079-32-1: Electrostatic hazards, guidance

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
propylene	115-07-1	NDS	2.000 mg/m <sup>3</sup>	PL OEL
propylene		NDSch	8.600 mg/m <sup>3</sup>	PL OEL

#### Biological occupational exposure limits

No biological limit allocated.

**Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:**

**Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:**

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Propylene - Polymer Grade

Version 2.2      Revision Date: 28.01.2024      SDS Number: 800001000816      Date of last issue: 09.03.2023  
Print Date 05.02.2024

Substance name	Environmental Compartment	Value
propylene		
Remarks:	Exposure assessments have not been presented for the environment therefore PNEC values not required.	

### 8.2 Exposure controls

#### Engineering measures

Read in conjunction with the Exposure Scenario for your specific use contained in the Annex.  
Use sealed systems as far as possible.

Adequate explosion-proof ventilation to control airborne concentrations below the exposure guidelines/limits.

Local exhaust ventilation is recommended.

Firewater monitors and deluge systems are recommended.

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

#### General Information:

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Purge system prior to equipment break-in or maintenance.

#### Personal protective equipment

Read in conjunction with the Exposure Scenario for your specific use contained in the Annex.

The provided information is made in consideration of the PPE directive (Council Directive 89/686/EEC) and the CEN European Committee for Standardisation (CEN) standards.

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Eye protection : Wear goggles for use against liquids and gas, combined with face shield with chin guard.

Approved to EU Standard EN166.

Hand protection

Remarks : Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. Neoprene rubber. If contact with liquefied product is possible or anticipated, gloves should be thermally insulated to prevent cold burns. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes



# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Propylene - Polymer Grade

Version 2.2	Revision Date: 28.01.2024	SDS Number: 800001000816	Date of last issue: 09.03.2023 Print Date 05.02.2024
----------------	------------------------------	-----------------------------	---

where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

Skin and body protection : Chemical and cryogenic gloves/gauntlets, boots, and apron. Wear antistatic and flame-retardant clothing.

Respiratory protection : If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are unsuitable (e.g. airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus. If air-filtering respirators are suitable for conditions of use: Where air-filtering respirators are suitable, select an appropriate combination of mask and filter.

Select a filter suitable for combined particulate/organic gases and vapours [Type AX/Type P boiling point < 65°C (149°F)] meeting EN14387 and EN143.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state	: Liquid under pressure.
Colour	: colourless
Odour	: Faint
Odour Threshold	: Typical 67 ppm
Melting point/freezing point	: -185,2 °C

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Propylene - Polymer Grade

Version	Revision Date:	SDS Number:	Date of last issue: 09.03.2023
2.2	28.01.2024	800001000816	Print Date 05.02.2024

---

Boiling point/boiling range : -47,7 °C

### Flammability

Flammability (solid, gas) : Flammable gas.

### Lower explosion limit and upper explosion limit / flammability limit

Upper explosion limit /  
upper flammability limit : 11 %(V)

Lower explosion limit /  
Lower flammability limit : 2 %(V)

Flash point : -108 °C  
Method: No information available.

Auto-ignition temperature : 455 °C

Decomposition temperature  
Decomposition temperature : Data not available

pH : Data not available

Viscosity  
Viscosity, dynamic : 0,01 mPa.s (0 °C)  
Method: ASTM D445

Viscosity, kinematic : Data not available

Solubility(ies)  
Water solubility : 260 mg/l (40 °C)  
380 mg/l (22 °C)  
930 g/l (0 °C)

Partition coefficient: n-  
octanol/water : log Pow: 1,77

Vapour pressure : 600 kPa (0 °C)

Relative density : 0,58 (0 °C)  
Method: ASTM D4052

Density : 610 kg/m<sup>3</sup> (0 °C)  
Method: ASTM D4052

Relative vapour density : 1,5 (0 °C)

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Propylene - Polymer Grade

Version	Revision Date:	SDS Number:	Date of last issue: 09.03.2023
2.2	28.01.2024	800001000816	Print Date 05.02.2024

### Particle characteristics

Particle size : Data not available

### 9.2 Other information

Explosive properties : no data available

Oxidizing properties : Data not available

Evaporation rate : Data not available

Conductivity : Low conductivity: < 100 pS/m

The conductivity of this material makes it a static accumulator. A liquid is typically considered nonconductive if its conductivity is below 100 pS/m and is considered semi-conductive if its conductivity is below 10,000 pS/m. Whether a liquid is nonconductive or semi-conductive, the precautions are the same. A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid

Surface tension : 17,5 mN/m, -50 °C

Molecular weight : 42 g/mol

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.

### 10.2 Chemical stability

Stable under normal conditions of use.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Reacts violently with strong oxidising agents.  
Polymerisation may occur at elevated temperatures.

### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames, and sparks.  
Exposure to air.  
In certain circumstances product can ignite due to static electricity.

### 10.5 Incompatible materials

Materials to avoid : Strong oxidising agents.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Propylene - Polymer Grade

Version	Revision Date:	SDS Number:	Date of last issue: 09.03.2023
2.2	28.01.2024	800001000816	Print Date 05.02.2024

### 10.6 Hazardous decomposition products

Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids and gases including carbon monoxide, carbon dioxide, sulphur oxides and unidentified organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation.

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure : Inhalation is the primary route of exposure.

#### Acute toxicity

##### Components:

##### **propylene:**

Acute oral toxicity : Remarks: Not applicable

Acute inhalation toxicity : LC50 (Rat): > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: gas  
Remarks: Low toxicity by inhalation.  
High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea; continued inhalation may result in unconsciousness and/or death.

Acute dermal toxicity : Remarks: Not applicable

#### Skin corrosion/irritation

##### Components:

##### **propylene:**

Remarks : Not irritating to skin.

#### Serious eye damage/eye irritation

##### Components:

##### **propylene:**

Remarks : Not irritating to eye.

#### Respiratory or skin sensitisation

##### Components:

##### **propylene:**

Remarks : Not a sensitiser.  
Based on available data, the classification criteria are not met.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Propylene - Polymer Grade

Version 2.2      Revision Date: 28.01.2024      SDS Number: 800001000816      Date of last issue: 09.03.2023  
Print Date 05.02.2024

### Germ cell mutagenicity

#### Components:

##### propylene:

Genotoxicity in vivo : Remarks: Non mutagenic

Germ cell mutagenicity- Assessment : This product does not meet the criteria for classification in categories 1A/1B.

### Carcinogenicity

#### Components:

##### propylene:

Remarks : Not a carcinogen.  
Based on available data, the classification criteria are not met.

Carcinogenicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

Material	GHS/CLP Carcinogenicity Classification
propylene	No carcinogenicity classification.

Material	Other Carcinogenicity Classification
propylene	IARC: Group 3: Not classifiable as to its carcinogenicity to humans

### Reproductive toxicity

#### Components:

##### propylene:

Effects on fertility : Remarks: Does not impair fertility., Not a developmental toxicant.

Reproductive toxicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

### STOT - single exposure

#### Components:

##### propylene:

Remarks : Not a respiratory irritant

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Propylene - Polymer Grade

Version	Revision Date:	SDS Number:	Date of last issue: 09.03.2023
2.2	28.01.2024	800001000816	Print Date 05.02.2024

### STOT - repeated exposure

#### Components:

##### propylene:

Remarks : Low systemic toxicity on repeated exposure.

### Aspiration toxicity

#### Components:

##### propylene:

Not an aspiration hazard., Based on available data, the classification criteria are not met.

## 11.2 Information on other hazards

### Endocrine disrupting properties

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### Further information

#### Product:

Remarks : Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

#### Components:

##### propylene:

Remarks : High gas concentrations will displace available air; unconsciousness and death may occur suddenly from lack of oxygen.  
Rapid release of gases which are liquids under pressure may cause frost burns of exposed tissues (skin, eye) due to evaporative cooling.  
Exposure to very high concentrations of similar materials has been associated with irregular heart rhythms and cardiac arrest.

Remarks : Classifications by other authorities under varying regulatory frameworks may exist.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Propylene - Polymer Grade

Version	Revision Date:	SDS Number:	Date of last issue: 09.03.2023
2.2	28.01.2024	800001000816	Print Date 05.02.2024

### SECTION 12: Ecological information

#### 12.1 Toxicity

##### Components:

##### **propylene:**

Toxicity to fish	:	Remarks: Based on available data, the classification criteria are not met.
Toxicity to daphnia and other aquatic invertebrates	:	Remarks: Based on available data, the classification criteria are not met.
Toxicity to algae/aquatic plants	:	Remarks: Based on available data, the classification criteria are not met.
Toxicity to microorganisms	:	Remarks: Based on available data, the classification criteria are not met.
Toxicity to fish (Chronic toxicity)	:	Remarks: Based on available data, the classification criteria are not met.
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	Remarks: Based on available data, the classification criteria are not met.

#### 12.2 Persistence and degradability

##### Product:

Biodegradability	:	Remarks: Inherently biodegradable. Oxidises rapidly by photo-chemical reactions in air. Not Persistent per IMO criteria. International Oil Pollution Compensation (IOPC) Fund definition: "A non-persistent oil is oil, which, at the time of shipment, consists of hydrocarbon fractions, (a) at least 50% of which, by volume, distills at a temperature of 340°C (645°F) and (b) at least 95% of which, by volume, distills at a temperature of 370°C (700°F) when tested by the ASTM Method D-86/78 or any subsequent revision thereof."
------------------	---	--

##### Components:

##### **propylene:**

Biodegradability	:	Remarks: Inherently biodegradable. Oxidises rapidly by photo-chemical reactions in air. Not Persistent per IMO criteria. International Oil Pollution Compensation (IOPC) Fund definition: "A non-persistent oil is oil, which, at the time of shipment, consists of hydrocarbon fractions, (a) at least 50% of which, by volume, distills at a temperature of 340°C (645°F) and (b) at least 95% of
------------------	---	---

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Propylene - Polymer Grade

Version	Revision Date:	SDS Number:	Date of last issue: 09.03.2023
2.2	28.01.2024	800001000816	Print Date 05.02.2024

---

which, by volume, distils at a temperature of 370°C (700°F) when tested by the ASTM Method D-86/78 or any subsequent revision thereof."

### 12.3 Bioaccumulative potential

#### Components:

##### **propylene:**

Bioaccumulation : Remarks: Does not bioaccumulate significantly.

### 12.4 Mobility in soil

#### Components:

##### **propylene:**

Mobility : Remarks: Because of their extreme volatility, air is the only environmental compartment that hydrocarbon gases will be found.

### 12.5 Results of PBT and vPvB assessment

#### Components:

##### **propylene:**

Assessment : The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB..

### 12.6 Endocrine disrupting properties

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### 12.7 Other adverse effects

#### Product:

Additional ecological information : Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

#### Components:

##### **propylene:**

Additional ecological information : Physical properties indicate that hydrocarbon gases will rapidly volatilise from the aquatic environment and that acute and chronic effects would not be observed in practice.  
In view of the high rate of loss from solution, the product is unlikely



# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Propylene - Polymer Grade

Version	Revision Date:	SDS Number:	Date of last issue: 09.03.2023
2.2	28.01.2024	800001000816	Print Date 05.02.2024

---

to pose a significant hazard to aquatic life.

---

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

Product : Recover or recycle if possible.  
It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.

Do not dispose into the environment, in drains or in water courses.  
Waste product should not be allowed to contaminate soil or water.

Disposal should be in accordance with applicable regional, national, and local laws and regulations.  
Local regulations may be more stringent than regional or national requirements and must be complied with.

MARPOL - see International Convention for the Prevention of Pollution from Ships (MARPOL 73/78) which provides technical aspects at controlling pollutions from ships.

Contaminated packaging : Data not available

---

### SECTION 14: Transport information

#### 14.1 UN number or ID number

ADN	: 1077
ADR	: 1077
RID	: 1077
IMDG	: 1077
IATA	: 1077

#### 14.2 UN proper shipping name

ADN	: PROPYLENE
ADR	: PROPYLENE
RID	: PROPYLENE
IMDG	: PROPYLENE
IATA	: PROPYLENE

#### 14.3 Transport hazard class(es)

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Propylene - Polymer Grade

Version	Revision Date:	SDS Number:	Date of last issue: 09.03.2023
2.2	28.01.2024	800001000816	Print Date 05.02.2024

---

<b>ADN</b>	: 2
<b>ADR</b>	: 2
<b>RID</b>	: 2
<b>IMDG</b>	: 2.1
<b>IATA</b>	: 2.1

### 14.4 Packing group

<b>ADN</b>	
Packing group	: Not Assigned
Classification Code	: 2F
Labels	: 2.1
<b>ADR</b>	
Packing group	: Not assigned by regulation
Classification Code	: 2F
Hazard Identification Number	: 23
Labels	: 2.1
<b>RID</b>	
Packing group	: Not assigned by regulation
Classification Code	: 2F
Hazard Identification Number	: 23
Labels	: 2.1
<b>IMDG</b>	
Packing group	: Not assigned by regulation
Labels	: 2.1
<b>IATA</b>	
Packing group	: Not Assigned
Labels	: 2.1

### 14.5 Environmental hazards

<b>ADN</b>	
Environmentally hazardous	: no
<b>ADR</b>	
Environmentally hazardous	: no
<b>RID</b>	
Environmentally hazardous	: no
<b>IMDG</b>	
Marine pollutant	: no

### 14.6 Special precautions for user

Remarks	: Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.
---------	--

### 14.7 Maritime transport in bulk according to IMO instruments

Ship type	: 2G/2PG
Product name	: Propylene

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Propylene - Polymer Grade

Version	Revision Date:	SDS Number:	Date of last issue: 09.03.2023
2.2	28.01.2024	800001000816	Print Date 05.02.2024

**Additional Information** : Transport in bulk according to the IGC code

Transport in bulk according to the IGC code

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)

: Not applicable

REACH - List of substances subject to authorisation (Annex XIV)

: Product is not subject to Authorisation under REACH.

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).

: This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

18

Liquefied flammable gases (including LPG) and natural gas

#### Other regulations:

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

Act of 25 February 2011 on chemical substances and their mixtures (Dz.U. 2011 nr 63 poz. 322).

Ordinance of the Minister of Health of 12 January 2015 concerning the criteria and procedures for classification of chemical substances and their mixtures (Dz.U. 2015 poz. 208).

Regulation of the Minister of Labor and Social Policy of 6th June 2014 concerning the highest allowable concentrations and levels of agents harmful for health in the workplace (Dz.U. 2018 poz. 1286).

Regulations of the Minister of Economy, Labor and Social Policy of 21 December 2005 concerning the basic requirements for personal protective equipment (Dz.U. 2005 nr 259 poz. 2173).

Ordinance of the Minister of Health of 9 September 2016 on the health and safety of workers related to chemical agents at work (Dz.U. 2016 poz. 1488).

Regulation of the Minister of Health of 2nd February 2011 concerning tests and measurement of agents harmful for health in the workplace (Dz.U. 2011 nr 33 poz. 166).

Regulation of the Minister of Health of 20 April 2012 on the labelling of packaging of dangerous substances and mixtures of dangerous substances and mixtures (Dz.U. 2011 nr 33 poz. 166).

Act of 14 December 2012 on Waste (Dz.U. 2013 poz. 21).

Act of 13 June 2013 on packaging and packaging waste (Dz.U. 2013 poz. 888).

Regulation of the Minister of Environment of 9 December 2014 on the Waste Catalog (Dz.U.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Propylene - Polymer Grade

Version	Revision Date:	SDS Number:	Date of last issue: 09.03.2023
2.2	28.01.2024	800001000816	Print Date 05.02.2024

2014 poz. 1923).

Act of 19 August 2011 on the carriage of dangerous goods (Dz.U. 2011 nr 227 poz. 1367).

Product is subject to types and quantities of dangerous substances with an increased risk of developing a major industrial accident (ROZPORZĄDZENIE MINISTRA ROZWOJU z dnia 29 stycznia 2016 r. w sprawie rodzajów i ilości znajdujących się w zakładzie substancji niebezpiecznych, decydujących o zaliczeniu zakładu do zakładu o zwiększonym lub dużym ryzyku wystąpienia poważnej awarii przemysłowej) based on Seveso III directive (2012/18/EU).

Product is subject to the Regulation of the Minister of Development of 29 January 2016 on the types and quantities of hazardous substances present in the establishment, determining the establishment's count as an establishment with an increased or high risk of a major industrial accident (Dz.U. 2016 poz. 138), based on Seveso III directive (2012/18/EU).

### The components of this product are reported in the following inventories:

AIIC : Listed

DSL : Listed

IECSC : Listed

ENCS : Listed

KECI : Listed

NZIoC : Listed

PICCS : Listed

TSCA : Listed

TCSI : Listed

### 15.2 Chemical safety assessment

A Chemical Safety Assessment has been carried out for this substance.

## SECTION 16: Other information

### Full text of other abbreviations

PL OEL : Ordinance of the Minister of Family, Labour and Social Policy of 12 June 2018 concerning the highest allowable concentrations and levels of the agents harmful for health in the workplace (Dz.U 2018 pos 1286, with later amendments)

PL OEL / NDS : Maximal Admissible Concentration

PL OEL / NDSch : Maximal Admissible Temporary Concentration

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Propylene - Polymer Grade

Version	Revision Date:	SDS Number:	Date of last issue: 09.03.2023
2.2	28.01.2024	800001000816	Print Date 05.02.2024

Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECL - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

Training advice : Provide adequate information, instruction and training for operators.

Other information : For Industry guidance and tools on REACH please visit the CEFIC website at <http://cefic.org/Industry-support>.  
The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB.

A vertical bar (|) in the left margin indicates an amendment from the previous version.

Sources of key data used to compile the Safety Data Sheet : The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID data base, EC 1272 regulation, etc).

### Classification of the mixture:

Flam. Gas 1A H220

### Classification procedure:

On basis of test data.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Propylene - Polymer Grade

Version	Revision Date:	SDS Number:	Date of last issue: 09.03.2023
2.2	28.01.2024	800001000816	Print Date 05.02.2024

---

Press. Gas Compr. Gas	H280	On basis of test data.
-----------------------	------	------------------------

### Identified Uses according to the Use Descriptor System

#### Uses - Worker

Title	:	Manufacture of substance- Industrial
-------	---	--------------------------------------

#### Uses - Worker

Title	:	Distribution of substance- Industrial
-------	---	---------------------------------------

#### Uses - Worker

Title	:	Use as an intermediate- Industrial
-------	---	------------------------------------

#### Uses - Worker

Title	:	Polymer production- Industrial
-------	---	--------------------------------

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

PL / EN

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Propylene - Polymer Grade

Version 2.2      Revision Date: 28.01.2024      SDS Number: 800001000816      Date of last issue: 09.03.2023  
Print Date 05.02.2024

### Exposure Scenario - Worker

<b>300000010077</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Manufacture of substance- Industrial
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU3, SU8, SU9 <b>Process Categories:</b> PROC1, PROC2, PROC3, PROC8a, PROC8b, PROC15 <b>Environmental Release Categories:</b> ERC1, ERC4
<b>Scope of process</b>	Manufacture of the substance or use as a process chemical or extraction agent. Includes recycling/ recovery, material transfers, storage, maintenance and loading (including marine vessel/barge, road/rail car and bulk container), sampling and associated laboratory activities.

SECTION 2		OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Section 2.1		Control of Worker Exposure	
Product Characteristics			
Physical form of product		Gas/liquefied gas	
Concentration of the Substance in Mixture/Article		Covers use of substance/product up to 100% (unless stated differently).,	
Frequency and Duration of Use			
Covers daily exposures up to 8 hours (unless stated differently).			
Other Operational Conditions affecting Exposure			
Assumes a good basic standard of occupational hygiene is implemented.			
Contributing Scenarios		Risk Management Measures	
General measures (Flammable gas)		Risks from the physicochemical hazards of substances, such as flammability or explosiveness can be controlled by implementing risk management measures at the workplace. It is recommended to follow the ATEX Directive 2014/34/EU and its subsequent updates. Based on the implementation of a selection of handling and storage risk management measures for the identified uses, the risk can be regarded as controlled to an acceptable level Use in contained systems. Avoid ignition sources – No smoking. Handle in well-ventilated area to prevent formation of explosive atmosphere. Use equipment and protective systems approved for flammable substances. Restrict line velocity during pumping to avoid generation of electrostatic discharge. Ground/bond container and receiving equipment. Use non-sparking tools. Comply with relevant EU/national regulations.	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Propylene - Polymer Grade

Version  
2.2

Revision Date:  
28.01.2024

SDS Number:  
800001000816

Date of last issue: 09.03.2023  
Print Date 05.02.2024

	Review Safety Data Sheet for additional advice.
<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Not applicable.	
<b>Frequency and Duration of Use</b>	
Not applicable.	
<b>Environmental factors not influenced by risk management</b>	
Not applicable.	
<b>Other Operational Conditions affecting Environmental Exposure</b>	
Not applicable.	
<b>Technical conditions and measures at process level (source) to prevent release</b>	
Not applicable.	
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>	
Not applicable.	
<b>Organisational measures to prevent/limit release from site</b>	
Not applicable.	
<b>Conditions and Measures related to municipal sewage treatment plant</b>	
Not applicable.	
<b>Conditions and Measures related to external treatment of waste for disposal</b>	
Not applicable.	
<b>Conditions and measures related to external recovery of waste</b>	
Not applicable.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
Risk Management Measures are based on qualitative risk characterisation.	

<b>Section 3.2 -Environment</b>	
Not applicable.	

<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
<b>Section 4.1 - Health</b>	
Not applicable.	

<b>Section 4.2 -Environment</b>	
Not applicable.	



# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Propylene - Polymer Grade

Version 2.2      Revision Date: 28.01.2024      SDS Number: 800001000816      Date of last issue: 09.03.2023  
Print Date 05.02.2024

### Exposure Scenario - Worker

<b>300000010078</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Distribution of substance- Industrial
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU3, SU8, SU9 <b>Process Categories:</b> PROC1, PROC2, PROC3, PROC8a, PROC8b, PROC9, PROC15 <b>Environmental Release Categories:</b> ERC1, ERC2, ERC3, ERC4, ERC5, ERC6a, ERC6b, ERC6c, ERC6d, ERC7
<b>Scope of process</b>	Loading (including marine vessel/barge, rail/road car and IBC loading) and repacking (including drums and small packs) of substance, including its sampling, storage, unloading distribution and associated laboratory activities.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Section 2.1	Control of Worker Exposure	
Product Characteristics		
Physical form of product	Gas/liquefied gas	
Concentration of the Substance in Mixture/Article	Covers use of substance/product up to 100% (unless stated differently).,	
Frequency and Duration of Use		
Covers daily exposures up to 8 hours (unless stated differently).		
Other Operational Conditions affecting Exposure		
Assumes a good basic standard of occupational hygiene is implemented.		
Contributing Scenarios	Risk Management Measures	
General measures (Flammable gas)	<p>Risks from the physicochemical hazards of substances, such as flammability or explosiveness can be controlled by implementing risk management measures at the workplace. It is recommended to follow the ATEX Directive 2014/34/EU and its subsequent updates.</p> <p>Based on the implementation of a selection of handling and storage risk management measures for the identified uses, the risk can be regarded as controlled to an acceptable level.</p> <p>Use in contained systems.</p> <p>Avoid ignition sources – No smoking.</p> <p>Handle in well-ventilated area to prevent formation of explosive atmosphere.</p> <p>Use equipment and protective systems approved for flammable substances.</p> <p>Restrict line velocity during pumping to avoid generation of electrostatic discharge.</p> <p>Ground/bond container and receiving equipment.</p> <p>Use non-sparking tools.</p> <p>Comply with relevant EU/national regulations.</p>	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Propylene - Polymer Grade

Version  
2.2

Revision Date:  
28.01.2024

SDS Number:  
800001000816

Date of last issue: 09.03.2023  
Print Date 05.02.2024

	Review Safety Data Sheet for additional advice.
<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Not applicable.	
<b>Frequency and Duration of Use</b>	
Not applicable.	
<b>Environmental factors not influenced by risk management</b>	
Not applicable.	
<b>Other Operational Conditions affecting Environmental Exposure</b>	
Not applicable.	
<b>Technical conditions and measures at process level (source) to prevent release</b>	
Not applicable.	
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>	
Not applicable.	
<b>Organisational measures to prevent/limit release from site</b>	
Not applicable.	
<b>Conditions and Measures related to municipal sewage treatment plant</b>	
Not applicable.	
<b>Conditions and Measures related to external treatment of waste for disposal</b>	
Not applicable.	
<b>Conditions and measures related to external recovery of waste</b>	
Not applicable.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
Risk Management Measures are based on qualitative risk characterisation.	

<b>Section 3.2 -Environment</b>	
Not applicable.	

<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
<b>Section 4.1 - Health</b>	
Not applicable.	

<b>Section 4.2 -Environment</b>	
Not applicable.	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Propylene - Polymer Grade

Version 2.2      Revision Date: 28.01.2024      SDS Number: 800001000816      Date of last issue: 09.03.2023  
Print Date 05.02.2024

### Exposure Scenario - Worker

<b>300000010079</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Use as an intermediate- Industrial
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU3, SU8, SU9 <b>Process Categories:</b> PROC1, PROC2, PROC3, PROC8a, PROC8b, PROC15 <b>Environmental Release Categories:</b> ERC6a
<b>Scope of process</b>	Use of substance as an intermediate (not related to Strictly Controlled Conditions). Includes recycling/ recovery, material transfers, storage, sampling, associated laboratory activities, maintenance and loading (including marine vessel/barge, road/rail car and bulk container).

SECTION 2		OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Section 2.1		Control of Worker Exposure	
Product Characteristics			
Physical form of product		Gas/liquefied gas	
Concentration of the Substance in Mixture/Article		Covers use of substance/product up to 100% (unless stated differently).,	
Frequency and Duration of Use			
Covers daily exposures up to 8 hours (unless stated differently).			
Other Operational Conditions affecting Exposure			
Assumes a good basic standard of occupational hygiene is implemented.			
Contributing Scenarios		Risk Management Measures	
General measures (Flammable gas)		Risks from the physicochemical hazards of substances, such as flammability or explosiveness can be controlled by implementing risk management measures at the workplace. It is recommended to follow the ATEX Directive 2014/34/EU and its subsequent updates. Based on the implementation of a selection of handling and storage risk management measures for the identified uses, the risk can be regarded as controlled to an acceptable level. Use in contained systems. Avoid ignition sources – No smoking. Handle in well-ventilated area to prevent formation of explosive atmosphere. Use equipment and protective systems approved for flammable substances. Restrict line velocity during pumping to avoid generation of electrostatic discharge. Ground/bond container and receiving equipment. Use non-sparking tools. Comply with relevant EU/national regulations.	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Propylene - Polymer Grade

Version  
2.2

Revision Date:  
28.01.2024

SDS Number:  
800001000816

Date of last issue: 09.03.2023  
Print Date 05.02.2024

	Review Safety Data Sheet for additional advice.
<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Not applicable.	
<b>Frequency and Duration of Use</b>	
Not applicable.	
<b>Environmental factors not influenced by risk management</b>	
Not applicable.	
<b>Other Operational Conditions affecting Environmental Exposure</b>	
Not applicable.	
<b>Technical conditions and measures at process level (source) to prevent release</b>	
Not applicable.	
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>	
Not applicable.	
<b>Organisational measures to prevent/limit release from site</b>	
Not applicable.	
<b>Conditions and Measures related to municipal sewage treatment plant</b>	
Not applicable.	
<b>Conditions and Measures related to external treatment of waste for disposal</b>	
Not applicable.	
<b>Conditions and measures related to external recovery of waste</b>	
Not applicable.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
Risk Management Measures are based on qualitative risk characterisation.	

<b>Section 3.2 -Environment</b>	
Not applicable.	

<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
<b>Section 4.1 - Health</b>	
Not applicable.	

<b>Section 4.2 -Environment</b>	
Not applicable.	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Propylene - Polymer Grade

Version 2.2      Revision Date: 28.01.2024      SDS Number: 800001000816      Date of last issue: 09.03.2023  
Print Date 05.02.2024

### Exposure Scenario - Worker

<b>300000010080</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Polymer production- Industrial
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU3, SU10 <b>Process Categories:</b> PROC1, PROC2, PROC3, PROC4, PROC5, PROC6, PROC8a, PROC8b, PROC14 <b>Environmental Release Categories:</b> ERC6c
<b>Scope of process</b>	Manufacture of polymers from monomers in continuous and batch processes. Including production, re-cycling and recovery, degassing, discharging, reactor maintenance and immediate polymer product formation (i.e. compounding, pelletisation, product off-gassing).

SECTION 2		OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Section 2.1		Control of Worker Exposure	
Product Characteristics			
Physical form of product		Gas/liquefied gas	
Concentration of the Substance in Mixture/Article		Covers use of substance/product up to 100% (unless stated differently).,	
Frequency and Duration of Use			
Covers daily exposures up to 8 hours (unless stated differently).			
Other Operational Conditions affecting Exposure			
Assumes a good basic standard of occupational hygiene is implemented.			
Contributing Scenarios		Risk Management Measures	
General measures (Flammable gas)		Risks from the physicochemical hazards of substances, such as flammability or explosiveness can be controlled by implementing risk management measures at the workplace. It is recommended to follow the ATEX Directive 2014/34/EU and its subsequent updates. Based on the implementation of a selection of handling and storage risk management measures for the identified uses, the risk can be regarded as controlled to an acceptable level. Use in contained systems. Avoid ignition sources – No smoking. Handle in well-ventilated area to prevent formation of explosive atmosphere. Use equipment and protective systems approved for flammable substances. Restrict line velocity during pumping to avoid generation of electrostatic discharge. Ground/bond container and receiving equipment. Use non-sparking tools. Comply with relevant EU/national regulations.	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Propylene - Polymer Grade

Version  
2.2

Revision Date:  
28.01.2024

SDS Number:  
800001000816

Date of last issue: 09.03.2023  
Print Date 05.02.2024

	Review Safety Data Sheet for additional advice.
<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Not applicable.	
<b>Frequency and Duration of Use</b>	
Not applicable.	
<b>Environmental factors not influenced by risk management</b>	
Not applicable.	
<b>Other Operational Conditions affecting Environmental Exposure</b>	
Not applicable.	
<b>Technical conditions and measures at process level (source) to prevent release</b>	
Not applicable.	
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>	
Not applicable.	
<b>Organisational measures to prevent/limit release from site</b>	
Not applicable.	
<b>Conditions and Measures related to municipal sewage treatment plant</b>	
Not applicable.	
<b>Conditions and Measures related to external treatment of waste for disposal</b>	
Not applicable.	
<b>Conditions and measures related to external recovery of waste</b>	
Not applicable.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
Risk Management Measures are based on qualitative risk characterisation.	

<b>Section 3.2 -Environment</b>	
Not applicable.	

<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
<b>Section 4.1 - Health</b>	
Not applicable.	

<b>Section 4.2 -Environment</b>	
Not applicable.	