In accordance with Occupational Safety and Health Act's Standard of Classification and Labelling of Chemical Substances and MSDS

CARADOL SC56-18S

Version 1.5 Revision Date 2024.02.15 Print Date 2024.02.22

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : CARADOL SC56-18S

Product code : U312Y

Synonyms : Polyol CAS-No. : 9082-00-2

Recommended use of the chemical and restrictions on use

Recommended use : Use for the manufacture of polyurethane products., To be

evaluated on a case by case basis depending on specific

customer application.

Restrictions on use : This product must not be used in applications other than the

above without first seeking the advice of the supplier.

Manufacturer or supplier's details

Supplier :

SHELL EASTERN CHEMICALS (S)

A REGISTERED BUSINESS OF SHELL EASTERN

TRADING (PTE) LTD (UEN:198902087C)

9 North Buona Vista Drive, #07-01

The Metropolis Tower 1 Singapore 138588

Singapore

Telephone : +65 6384 8269 Telefax : +65 6384 8454

Contact for Safety Data

Sheet

: sccmsds@shell.com

Emergency telephone

number

: + (65) 6542 9595 (Alert-SGS)

Other information : CARADOL is a trademark owned by Shell Trademark

Management B.V. and Shell Brands Inc. and used by affiliates

of Shell plc.

2. HAZARDS IDENTIFICATION

GHS Classification

Based on available data this substance / mixture does not meet the classification criteria.

GHS label elements

Hazard pictograms : No Hazard Symbol required

Signal word : No signal word

1 / 17 800010031340 KR

In accordance with Occupational Safety and Health Act's Standard of Classification and Labelling of Chemical Substances and MSDS

CARADOL SC56-18S

Version 1.5 Revision Date 2024.02.15 Print Date 2024.02.22

Hazard statements : PHYSICAL HAZARDS:

Not classified as a physical hazard under GHS criteria.

HEALTH HAZARDS:

Not classified as a health hazard under GHS criteria.

ENVIRONMENTAL HAZARDS:

Not classified as an environmental hazard under GHS criteria.

Precautionary statements

Prevention:

No precautionary phrases.

Response:

No precautionary phrases.

Storage:

No precautionary phrases.

Disposal:

No precautionary phrases.

Other hazards which do not result in classification

None known.

NFPA Rating (Health, Fire, : 0, 1, 0

Reactivity)

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Substance

Components

Chemical name	Common Name	CAS-No.	Concentration (% w/w)
Polyalkylene glycol	PAG	9082-00-2	100

Further information

Contains:

Chemical name	Identification number	Concentration (% w/w)
Benzenamine, N- phenyl-, reaction products with 2,4,4- trimethylpentene	68411-46-1	0.1 - 0.2

In accordance with Occupational Safety and Health Act's Standard of Classification and Labelling of Chemical Substances and MSDS

CARADOL SC56-18S

/ersion 1.5	Revision Date 2024.02.15	Print Date 2024.02.22
. FIRST-AID MEASURES		
General advice	Not expected to be a health haza conditions.	rd when used under normal
In case of eye contact	Flush eye with copious quantities Remove contact lenses, if presen rinsing. If persistent irritation occurs, obta	at and easy to do. Continue
In case of skin contact	Remove contaminated clothing. F water and follow by washing with If persistent irritation occurs, obta	soap if available.
If inhaled	No treatment necessary under no If symptoms persist, obtain medic	
If swallowed	In general no treatment is necess are swallowed, however, get med	
Most important symptoms and effects, both acute and delayed	Not considered to be an inhalation conditions of use. Possible respiratory irritation sign a temporary burning sensation of coughing, and/or difficulty breathin No specific hazards under norma Skin irritation signs and symptom sensation, redness, or swelling. Eye irritation signs and symptoms sensation, redness, swelling, and Ingestion may result in nausea, version of the sense o	as and symptoms may include the nose and throat, ng. Il use conditions. Is may include a burning Is may include a burning If or blurred vision.
Protection of first-aiders	When administering first aid, ensuappropriate personal protective eincident, injury and surroundings.	quipment according to the
Notes to physician	Call a doctor or poison control ce Treat symptomatically. Following exposure, investigation of liver, ki be advisable. Records of such inc for future reference.	cases of gross over- idney and eye function may

5. FIRE-FIGHTING MEASURES

Suitable and unsuitable extinguishing media

Suitable extinguishing media : Large fires should only be fought by properly trained fire

fighters.

Alcohol-resistant foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small

fires only.

3 / 17 800010031340 KR

In accordance with Occupational Safety and Health Act's Standard of Classification and Labelling of Chemical Substances and MSDS

CARADOL SC56-18S

Version 1.5 Revision Date 2024.02.15 Print Date 2024.02.22

Unsuitable extinguishing

media

: Do not use water in a jet.

Specific hazards during

firefighting

: Will only burn if enveloped in a pre-existing fire.

Hazardous combustion products may include: Carbon dioxide

Unidentified organic and inorganic compounds.

Toxic gases Carbon monoxide.

Specific extinguishing

methods

: Standard procedure for chemical fires.

Clear fire area of all non-emergency personnel.

All storage areas should be provided with adequate fire

fighting facilities.

Keep adjacent containers cool by spraying with water.

Special protective equipment

for firefighters

: Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to

relevant Standards (e.g. Europe: EN469).

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

: Observe all relevant local and international regulations.

: Avoid contact with skin, eyes and clothing.

Avoid inhaling vapour and/or mists.

Extinguish any naked flames. Do not smoke. Remove ignition

sources. Avoid sparks.

Environmental precautions

Remove all possible sources of ignition in the surrounding

area.

Prevent from spreading or entering into drains, ditches or rivers by using sand, earth, or other appropriate barriers. Use appropriate containment to avoid environmental

contamination.

Ventilate contaminated area thoroughly.

Methods and materials for containment and cleaning up

: For large liquid spills (> 1 drum), transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely For small liquid spills (< 1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.

4 / 17 800010031340

KR

In accordance with Occupational Safety and Health Act's Standard of Classification and Labelling of Chemical Substances and MSDS

CARADOL SC56-18S

Version 1.5 Revision Date 2024.02.15 Print Date 2024.02.22

Proper disposal should be evaluated based on regulatory status of this material (refer to Section 13), potential contamination from subsequent use and spillage, and regulations governing disposal in the local area.

Additional advice : For guidance on selection of personal protective equipment

see Section 8 of this Safety Data Sheet.

For guidance on disposal of spilled material see Section 13 of

this Safety Data Sheet.

7. HANDLING AND STORAGE

General Precautions : Avoid breathing of or direct contact with material. Only use in

well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see

Section 8 of this Safety Data Sheet.

Use the information in this data sheet as input to a risk assessment of local circumstances to help determine

appropriate controls for safe handling, storage and disposal of

this material.

Ensure that all local regulations regarding handling and

storage facilities are followed.

Advice on safe handling : In accordance with good industrial hygiene practices,

precautions should be taken to avoid breathing of material.

Use local exhaust extraction over processing area. Avoid unintentional contact with isocyanates to prevent

uncontrolled polymerisation.

Avoid contact with skin, eyes and clothing.

Air-dry contaminated clothing in a well-ventilated area before

laundering.

Do not empty into drains. Handling Temperature:

Ambient.

When handling product in drums, safety footwear should be

worn and proper handling equipment should be used.

Extinguish any naked flames. Do not smoke. Remove ignition

sources. Avoid sparks.

Avoidance of contact : Avoid contact with isocyanates, copper and copper alloys,

zinc, strong oxidizing agents, and water.

Product Transfer : Lines should be purged with nitrogen before and after product

transfer. Keep containers closed when not in use.

Safe storage methods (including conditions to be avoided)

Conditions for safe storage : Refer to section 15 for any additional specific legislation

covering the packaging and storage of this product.

Storage period : 24 month(s)

In accordance with Occupational Safety and Health Act's Standard of Classification and Labelling of Chemical Substances and MSDS

CARADOL SC56-18S

Version 1.5 Revision Date 2024.02.15 Print Date 2024.02.22 Other data : Prevent all contact with water and with moist atmosphere. Tanks must be clean, dry and rust-free. Prevent ingress of water. Must be stored in a diked (bunded) well- ventilated area, away from sunlight, ignition sources and other sources of heat. Nitrogen blanket recommended for large tanks (capacity 100 m3 or higher). Drums should be stacked to a maximum of 3 high. Storage Temperature: Ambient. Storage should be handled at temperatures such that viscosities are less than 500 cSt; typically at 25-50 °C. Tanks should be fitted with heating coils in areas where the ambient temperatures are below the recommended product handling temperatures. Heating coil skin temperatures should not exceed 100 °C. : Suitable material: Stainless steel., For container paints, use Packaging material epoxy paint, zinc silicate paint. Unsuitable material: Copper., Copper alloys. Specific use(s) : Not applicable Ensure that all local regulations regarding handling and

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Components with workplace control parameters

Biological occupational exposure limits

No biological limit allocated.

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

storage facilities are followed.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

In accordance with Occupational Safety and Health Act's Standard of Classification and Labelling of Chemical Substances and MSDS

CARADOL SC56-18S

Version 1.5 Revision Date 2024.02.15 Print Date 2024.02.22

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany http://www.dguv.de/inhalt/index.jsp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

Engineering measures

: Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated. Adequate ventilation to control airborne concentrations. The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

General Information:

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or

maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

Personal protective equipment

Protective measures

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Respiratory protection : No respiratory protection is ordinarily required under normal

conditions of use.

In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material.

Eye protection : If material is handled such that it could be splashed into eyes,

protective eyewear is recommended.

Hand protection

Remarks : Where hand contact with the product may occur the use of

gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. Longer term protection: Nitrile rubber. Incidental contact/Splash protection: PVC, neoprene

In accordance with Occupational Safety and Health Act's Standard of Classification and Labelling of Chemical Substances and MSDS

CARADOL SC56-18S

Version 1.5 Revision Date 2024.02.15 Print Date 2024.02.22

or nitrile rubber gloves For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-

perfumed moisturizer is recommended.

Skin and body protection : Skin protection is not ordinarily required beyond standard

work clothes.

It is good practice to wear chemical resistant gloves.

Hygiene measures : Wash hands before eating, drinking, smoking and using the

toilet

Launder contaminated clothing before re-use.

Environmental exposure controls

General advice : Local guidelines on emission limits for volatile substances

must be observed for the discharge of exhaust air containing

/apour.

Minimise release to the environment. An environmental assessment must be made to ensure compliance with local

environmental legislation.

Information on accidental release measures are to be found in

section 6.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Liquid.

Colour : Clear colourless

Odour : odourless

Odour Threshold : Data not available

pH : ca. 7

Melting / freezing point : Data not available Boiling point/boiling range : $> 285 \, ^{\circ}\text{C} / > 545 \, ^{\circ}\text{F}$ Flash point : $> 237 \, ^{\circ}\text{C} / > 459 \, ^{\circ}\text{F}$

In accordance with Occupational Safety and Health Act's Standard of Classification and Labelling of Chemical Substances and MSDS

CARADOL SC56-18S

Version 1.5 Revision Date 2024.02.15 Print Date 2024.02.22

Method: ASTM D93 (PMCC)

Evaporation rate : Data not available Flammability (solid, gas) : Not applicable

Upper/Lower explosion limit

Upper explosion limit : Data not available Lower explosion limit : Data not available

Vapour pressure : < 10 hPa

Solubility(ies)

Water solubility : Data not available Relative vapour density : Data not available

Relative density : 1.02Method: ASTM D4052

: Typical 1,017 kg/m3 (20 °C / 68 °F) Density

Method: ASTM D4052

Partition coefficient: n-

octanol/water

: log Pow: 1.1 - 4.8

Auto-ignition temperature : Data not available Decomposition temperature : Data not available

Viscosity

Typical 600 mPa.s (25 °C / 77 °F) Viscosity, dynamic

Method: ASTM D445

: 260 mm2/s (40 °C / 104 °F) Viscosity, kinematic

Method: ASTM D445

Explosive properties : Not applicable Oxidizing properties : Data not available

Surface tension : Data not available

Conductivity : Electrical conductivity: > 10,000 pS/m

> A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid, This material is not expected to be

a static accumulator.

Particle size : Data not available

Data not available

In accordance with Occupational Safety and Health Act's Standard of Classification and Labelling of Chemical Substances and MSDS

CARADOL SC56-18S

Version 1.5 Revision Date 2024.02.15 Print Date 2024.02.22

Molecular weight : 3,000 g/mol

10. STABILITY AND REACTIVITY

Chemical stability and possibility of hazardous reactions:

The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph. No hazardous reaction is expected when handled and

stored according to provisions, Hygroscopic. Polymerises exothermically with di-isocyanates at

ambient temperatures.

The reaction becomes progressively more vigorous and can be violent at higher temperatures if the miscibility of reaction partners is good or is supported by stirring or by

the presence of solvents.

Reacts with strong oxidising agents.

Conditions to avoid : Heat, flames, and sparks.

Product cannot ignite due to static electricity.

Incompatible materials : Avoid contact with isocyanates, copper and copper alloys,

zinc, strong oxidizing agents, and water.

Hazardous decomposition

products

: Unknown toxic products may be formed.

11. TOXICOLOGICAL INFORMATION

Basis for assessment : Information given is based on data obtained from similar

substances.

Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for

individual component(s).

exposure

Information on likely routes of : Exposure may occur via inhalation, ingestion, skin absorption,

skin or eye contact, and accidental ingestion.

Health hazard information

Acute toxicity

Product:

Acute oral toxicity : LD 50 : > 2,000 mg/kg

Remarks: Based on available data, the classification criteria

are not met.

In accordance with Occupational Safety and Health Act's Standard of Classification and Labelling of Chemical Substances and MSDS

CARADOL SC56-18S

Version 1.5 Revision Date 2024.02.15 Print Date 2024.02.22

Acute inhalation toxicity : Remarks: Based on available data, the classification criteria

are not met.

Acute dermal toxicity : LD 50 : > 2,000 mg/kg

Remarks: Low toxicity

Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Product:

Remarks: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Product:

Remarks: Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Product:

Remarks: Based on available data, the classification criteria are not met.

Carcinogenicity

Product:

Remarks: Based on available data, the classification criteria are not met.

Material	GHS/CLP Carcinogenicity Classification
Polyalkylene glycol	No carcinogenicity classification.

Germ cell mutagenicity

Product:

 Remarks: Based on available data, the classification criteria are not met.

Reproductive toxicity

Product:

Remarks: May impair fertility at doses which produce other toxic effects.

STOT - single exposure

Product:

In accordance with Occupational Safety and Health Act's Standard of Classification and Labelling of Chemical Substances and MSDS

CARADOL SC56-18S

Version 1.5 Revision Date 2024.02.15 Print Date 2024.02.22

Remarks: Based on available data, the classification criteria are not met.

STOT - repeated exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

Aspiration toxicity

Product:

Not an aspiration hazard.

Further information

Product:

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

12. ECOLOGICAL INFORMATION

Basis for assessment : Incomplete ecotoxicological data are available for this product.

The information given below is based partly on a knowledge of the components and the ecotoxicology of similar products.

Unless indicated otherwise, the data presented is

representative of the product as a whole, rather than for

individual component(s).

Ecotoxicity

Product:

Toxicity to fish (Acute : LC50 : > 100 mg/l

toxicity) Remarks: Based of

Remarks: Based on available data, the classification criteria

are not met.

Practically non toxic:

Toxicity to crustacean (Acute

toxicity)

: EC50 : > 100 mg/l

Remarks: Based on available data, the classification criteria

are not met.

Practically non toxic:

Toxicity to algae/aquatic plants (Acute toxicity)

: EC50 : > 100 mg/l

toxicity) Remarks: Practically non toxic:

Based on available data, the classification criteria are not met.

Toxicity to fish (Chronic

toxicity)

: Remarks: Data not available

Toxicity to crustacean

: Remarks: Data not available

(Chronic toxicity)

: IC50 : > 100 mg/l

Toxicity to microorganisms (Acute toxicity)

Remarks: Based on available data, the classification criteria

12 / 17 800010031340 KR

In accordance with Occupational Safety and Health Act's Standard of Classification and Labelling of Chemical Substances and MSDS

CARADOL SC56-18S

Version 1.5 Revision Date 2024.02.15 Print Date 2024.02.22

are not met.

Practically non toxic:

Persistence and degradability

Product:

Biodegradability : Remarks: Readily biodegradable.

Bioaccumulative potential

Product:

Bioaccumulation : Remarks: Does not bioaccumulate significantly.

Partition coefficient: n-

octanol/water

: log Pow: 1.1 - 4.8

Mobility in soil

Product:

Mobility : Remarks: If the product enters soil, one or more constituents

will or may be mobile and may contaminate groundwater.

Other adverse effects

no data available

13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Recover or recycle if possible.

It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.

Do not dispose into the environment, in drains or in water

Waste product should not be allowed to contaminate soil or

water.

Disposal should be in accordance with applicable regional,

national, and local laws and regulations.

Local regulations may be more stringent than regional or national requirements and must be complied with.

Contaminated packaging : Drain container thoroughly.

After draining, vent in a safe place away from sparks and fire.

Send to drum recoverer or metal reclaimer.

Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand.

13 / 17 800010031340 KR

In accordance with Occupational Safety and Health Act's Standard of Classification and Labelling of Chemical Substances and MSDS

CARADOL SC56-18S

Version 1.5 Revision Date 2024.02.15 Print Date 2024.02.22

Disposal considerations

Dispose of in accordance with local regulations.

14. TRANSPORT INFORMATION

National Regulations

Refer to section 15 for specific national regulation.

International Regulations

ADR

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Maritime transport in bulk according to IMO instruments

: Z Pollution category Ship type 3

Product name Glycerol, propoxylated and ethoxylated

Special precautions for user

Remarks : Special Precautions: Refer to Section 7, Handling & Storage,

for special precautions which a user needs to be aware of or

needs to comply with in connection with transport.

Additional Information : This product may be transported under nitrogen blanketing.

> Nitrogen is an odourless and invisible gas. Exposure to nitrogen enriched atmospheres displaces available oxygen which may cause asphyxiation or death. Personnel must observe strict safety precautions when involved with a

confined space entry.

15. REGULATORY INFORMATION

National regulatory information

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

INDUSTRY SAFETY & HEALTH ACT:	Hazardous substances prohibited from manufacturing, etc., Not applicable
	Hazardous substances subject to authorization, Not applicable

In accordance with Occupational Safety and Health Act's Standard of Classification and Labelling of Chemical Substances and MSDS

CARADOL SC56-18S

ersion 1.5	Revision Date 2024.02.15	Print Date 2024.02.22
	Hazardous subst	tances subject to control, Not
	Substances esta applicable	blished for exposure limits, Not
	Hazardous factor permissible limit,	r subject to keep below Not applicable
		ors Subject to Working nitoring, Not applicable
	Hazardous Factor Examination, No	ors Subject to Special Medical t applicable
CHEMICALS CONTROL ACT:	Toxic chemical s	substances, Not applicable
	Authorization che applicable	emical substances, Not
	Restricted chemi	cal substances, Not applicable
	Prohibited chemi	cal substances, Not applicable
	Accident precaut applicable	ion chemical substance, Not
DANGEROUS GOODS SAFE CO ACT:	Category 4 Dang	ication of dangerous material:, gerous Goods (Flammable 1 petroleum chemicals
WASTES MANAGEMENT ACT:		e 4/5/24/25 of Disposal

Other requirements in domestic and other countries

The components of this product are reported in the following inventories:

DSL : Listed

IECSC : Listed

ENCS : Listed

KECI : Listed

NZIoC : Listed

In accordance with Occupational Safety and Health Act's Standard of Classification and Labelling of Chemical Substances and MSDS

CARADOL SC56-18S

Version 1.5 Revision Date 2024.02.15 Print Date 2024.02.22

PICCS : Listed

TSCA : Listed

TCSI : Listed

16. OTHER INFORMATION

Abbreviations and Acronyms

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 -Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC -New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG -Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Further information

Training advice : Provide adequate information, instruction and training for

operators.

Sources of key data used to compile the Safety Data

Sheet

The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU

IUCLID date base, EC 1272 regulation, etc).

In accordance with Occupational Safety and Health Act's Standard of Classification and Labelling of Chemical Substances and MSDS

CARADOL SC56-18S

Version 1.5 Revision Date 2024.02.15 Print Date 2024.02.22

Issuing date : 2017.11.14

Revision number and date

Number of Revision : 1.5

Revision Date : 2024.02.15

Other information : A vertical bar (|) in the left margin indicates an amendment

from the previous version.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

KR / EN