According to EC No 1907/2006 as amended as at the date of this SDS

# **C** Ethylene

Version Revision Date: SDS Number: Date of last issue: 29.03.2023

2.3 12.02.2024 800010047427 Print Date 19.02.2024

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : C Ethylene Product code : X3602

Registration number EU : 01-2119462827-27-0005, 01-2119462827-27-0006, 01-

2119462827-27-0008

CAS-No. : 74-85-1

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Base chemical.

stance/Mixture Please refer to section 16 and/or the annexes for the regis-

tered uses under REACH.

Uses advised against : This product must not be used in applications other than the

above without first seeking the advice of the supplier.

#### 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier : Shell Chemicals Europe B.V.

PO Box 2334

3000 CH Rotterdam

Netherlands

Telephone : +31 (0)10 441 5137 / +31 (0)10 441 5191 Telefax : +31 (0)20 716 8316 / +31 (0)20 713 9230

Contact for Safety Data : sccmsds@shell.com

Sheet

#### 1.4 Emergency telephone number

+44 (0) 1235 239 670

National Poison Information Centre (NVIC): Tel. nr. +31(0)88 755 8000 (24 hrs a day and 7

days a week).

Only for the purpose of informing medical personnel.

#### **SECTION 2: Hazards identification**

### 2.1 Classification of the substance or mixture

#### Classification (REGULATION (EC) No 1272/2008)

Flammable gases, Category 1A H220: Extremely flammable gas.

Gases under pressure, Compressed gas H280: Contains gas under pressure; may explode if

heated.

Specific target organ toxicity - single ex- H336: May cause drowsiness or dizziness.

According to EC No 1907/2006 as amended as at the date of this SDS

# **C** Ethylene

Version Revision Date: SDS Number: Date of last issue: 29.03.2023

2.3 12.02.2024 800010047427 Print Date 19.02.2024

posure, Category 3, Narcotic effects

#### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms







Signal word : Danger

Hazard statements : PHYSICAL HAZARDS:

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

**HEALTH HAZARDS:** 

H336 May cause drowsiness or dizziness.

ENVIRONMENTAL HAZARDS:

Not classified as environmental hazard according to

CLP criteria.

Precautionary statements : Prevention:

P210 Keep away from heat/ sparks/ open flames/ hot surfac-

es. No smoking.

P243 Take precautionary measures against static discharge. P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

Response:

P377 Leaking gas fire: Do not extinguish, unless leak can be

stopped safely.

P381 Eliminate all ignition sources if safe to do so.

P304 + P340 IF INHALED: Remove person to fresh air and

keep comfortable for breathing.

Storage:

P410 + P403 Protect from sunlight. Store in a well-ventilated

place.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

#### 2.3 Other hazards

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

According to EC No 1907/2006 as amended as at the date of this SDS

# **C** Ethylene

Version Revision Date: SDS Number: Date of last issue: 29.03.2023

2.3 12.02.2024 800010047427 Print Date 19.02.2024

May form flammable/explosive vapour-air mixture.

This material is a static accumulator.

Even with proper grounding and bonding, this material can still accumulate an electrostatic charge.

If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable airvapour mixtures can occur.

This material is shipped under pressure.

High gas concentrations will displace available air; unconsciousness and death may occur suddenly from lack of oxygen.

Rapid release of gases which are liquids under pressure may cause frost burns of exposed tissues (skin, eye) due to evaporative cooling.

#### **SECTION 3: Composition/information on ingredients**

#### 3.1 Substances

#### Components

Chemical name	CAS-No.	Concentration (% w/w)
	EC-No.	, , ,
ethylene	74-85-1	>= 99,9
-	200-815-3	

#### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

General advice : Not expected to be a health hazard when used under normal

conditions.

Protection of first-aiders : When administering first aid, ensure that you are wearing the

appropriate personal protective equipment according to the

incident, injury and surroundings.

If inhaled : Remove to fresh air. If rapid recovery does not occur,

transport to nearest medical facility for additional treatment.

In case of skin contact : Slowly warm the exposed area by rinsing with warm water.

Transport to the nearest medical facility for additional treat-

ment.

In case of eye contact : Slowly warm the exposed area by rinsing with warm water.

Transport to the nearest medical facility for additional treat-

ment.

If swallowed : In general no treatment is necessary unless large quantities

are swallowed, however, get medical advice.

According to EC No 1907/2006 as amended as at the date of this SDS

# **C** Ethylene

Version Revision Date: SDS Number: Date of last issue: 29.03.2023

2.3 12.02.2024 800010047427 Print Date 19.02.2024

#### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Breathing of high vapour concentrations may cause central

nervous system (CNS) depression resulting in dizziness, light-headedness, headache, nausea and loss of coordination. Continued inhalation may result in unconsciousness and

death.

Rapid release of gases which are liquids under pressure may cause frost burns of exposed tissues (skin, eye) due to evapo-

rative cooling.

No specific hazards under normal use conditions.

Ingestion may result in nausea, vomiting and/or diarrhoea.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : IMMEDIATE TREATMENT IS EXTREMELY IMPORTANT!

Call a doctor or poison control center for guidance.

Treat symptomatically.

Potential for cardiac sensitisation, particularly in abuse situations. Hypoxia or negative inotropes may enhance these ef-

fects. Consider: oxygen therapy.

### **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

Suitable extinguishing media : Shut off supply. If not possible and no risk to surroundings, let

the fire burn itself out.

Unsuitable extinguishing

media

Data not available

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

Sustained fire attack on vessels may result in a Boiling Liquid

Expanding Vapor Explosion (BLEVE).

Contents are under pressure and can explode when exposed

to heat or flames.

As the vapours become lighter than air, the vapours may reach ignition sources at ground or elevated locations.

#### 5.3 Advice for firefighters

Special protective equipment :

for firefighters

Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to

relevant Standards (e.g. Europe: EN469).

Specific extinguishing meth-

ods

Standard procedure for chemical fires.

According to EC No 1907/2006 as amended as at the date of this SDS

# **C** Ethylene

Version Revision Date: SDS Number: Date of last issue: 29.03.2023

2.3 12.02.2024 800010047427 Print Date 19.02.2024

Further information : Clear fire area of all non-emergency personnel.

Keep adjacent containers cool by spraying with water.

#### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Observe the relevant local and international regulations

Notify authorities if any exposure to the general public or the

environment occurs or is likely to occur.

Local authorities should be advised if significant spillages

cannot be contained.

6.1.1 For non emergency personnel: Avoid contact with skin, eyes and clothing.

Isolate hazard area and deny entry to unnecessary or unpro-

tected personnel.

Do not breathe fumes, vapour. Do not operate electrical equipment. 6.1.2 For emergency responders:

Avoid contact with skin, eyes and clothing.

Isolate hazard area and deny entry to unnecessary or unpro-

tected personnel.

Do not breathe fumes, vapour.

Do not operate electrical equipment.

#### 6.2 Environmental precautions

Environmental precautions : Shut off leaks, if possible without personal risks. Remove all

possible sources of ignition in the surrounding area and evacuate all personnel. Attempt to disperse the gas or to direct its flow to a safe location for example by using fog sprays. Take precautionary measures against static discharge. Ensure electrical continuity by bonding and grounding (earthing) all equipment. Monitor area with combustible gas meter.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Allow to evaporate.

Attempt to disperse the vapour or to direct its flow to a safe location, for example by using fog sprays. Otherwise treat as

for small spillage.

### 6.4 Reference to other sections

For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet., Vapour may form an explosive mixture with air., For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.

#### **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

According to EC No 1907/2006 as amended as at the date of this SDS

# C Ethylene

Version Revision Date: SDS Number: Date of last issue: 29.03.2023

2.3 12.02.2024 800010047427 Print Date 19.02.2024

Technical measures : Avoid breathing of or direct contact with material. Only use in

well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see

Section 8 of this Safety Data Sheet.

Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this

material.

Advice on safe handling : This product is intended for use in closed systems only.

Extinguish any naked flames. Do not smoke. Remove ignition

sources. Avoid sparks.

Avoid inhaling vapour and/or mists.

Avoid contact with skin, eyes and clothing.

Use local exhaust ventilation if there is risk of inhalation of

vapours, mists or aerosols.

Bulk storage tanks should be diked (bunded).

Properly dispose of any contaminated rags or cleaning mate-

rials in order to prevent fires.

Even with proper grounding and bonding, this material can still

accumulate an electrostatic charge.

If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can oc-

cur.

Be aware of handling operations that may give rise to additional hazards that result from the accumulation of static

charges.

These include but are not limited to pumping (especially turbulent flow), mixing, filtering, splash filling, cleaning and filling of tanks and containers, sampling, switch loading, gauging, vac-

uum truck operations, and mechanical movements.

These activities may lead to static discharge e.g. spark for-

mation.

Restrict line velocity during pumping in order to avoid generation of electrostatic discharge (≤ 1 m/s until fill pipe submerged to twice its diameter, then ≤ 7 m/s). Avoid splash filling. Do NOT use compressed air for filling, discharging, or han-

dling operations.

Product Transfer : Refer to guidance under Handling section.

Hygiene measures : Wash hands before eating, drinking, smoking and using the

toilet. Launder contaminated clothing before re-use.

#### 7.2 Conditions for safe storage, including any incompatibilities

Further information on storage stability

Vapours from tanks should not be released to atmosphere. Breathing losses during storage should be controlled by a

suitable vapour treatment system.

Electrostatic charges will be generated during pumping. Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment to

reduce the risk.

According to EC No 1907/2006 as amended as at the date of this SDS

# **C** Ethylene

Version Revision Date: SDS Number: Date of last issue: 29.03.2023

2.3 12.02.2024 800010047427 Print Date 19.02.2024

The vapours in the head space of the storage vessel may lie in the flammable/explosive range and hence may be flamma-

ble.

Must be stored in a diked (bunded) well- ventilated area, away from sunlight, ignition sources and other sources of heat. Keep away from aerosols, flammables, oxidizing agents, corrosives and from products harmful or toxic to man or to the

environment.

Packaging material : Suitable material: For containers, or container linings use mild

steel, stainless steel.

7.3 Specific end use(s)

Specific use(s) : Please refer to section 16 and/or the annexes for the regis-

tered uses under REACH.

Ensure that all local regulations regarding handling and stor-

age facilities are followed.

See additional references that provide safe handling practices for liquids that are determined to be static accumulators: American Petroleum Institute 2003 (Protection Against Ignitions Arising out of Static, Lightning and Stray Currents) or National Fire Protection Agency 77 (Recommended Practices

on Static Electricity).

IEC/TS 60079-32-1: Electrostatic hazards, guidance

### **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

#### **Biological occupational exposure limits**

No biological limit allocated.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

#### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name		Environmental Compartment	Value
ethylene			
Remarks:	Exposure assessments have not been presented for the environment therefore PNEC values not required.		

#### 8.2 Exposure controls

#### **Engineering measures**

Use sealed systems as far as possible.

Adequate explosion-proof ventilation to control airborne concentrations below the exposure guidelines/limits.

Local exhaust ventilation is recommended.

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

According to EC No 1907/2006 as amended as at the date of this SDS

# **C** Ethylene

Version Revision Date: SDS Number: Date of last issue: 29.03.2023

2.3 12.02.2024 800010047427 Print Date 19.02.2024

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or for subsequent recycle.

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

#### Personal protective equipment

Read in conjunction with the Exposure Scenario for your specific use contained in the Annex. The provided information is made in consideration of the PPE directive (Council Directive 89/686/EEC) and the CEN European Committee for Standardisation (CEN) standards.

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Eye protection : Wear safety glasses and face shield (preferably with a chin

guard) if splashes are likely to occur.

Approved to EU Standard EN166.

Hand protection

Remarks : If contact with liquefied product is possible or anticipated,

gloves should be thermally insulated to prevent cold burns. Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. Neoprene rubber. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is

recommended.

According to EC No 1907/2006 as amended as at the date of this SDS

# **C** Ethylene

Version Revision Date: SDS Number: Date of last issue: 29.03.2023

2.3 12.02.2024 800010047427 Print Date 19.02.2024

Skin and body protection : Chemical and cryogenic gloves/gauntlets, boots, and apron.

Wear antistatic and flame-retardant clothing, if a local risk

assessment deems it so.

Respiratory protection : If engineering controls do not maintain airborne concentra-

tions to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are unsuitable (e.g. airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing appa-

ratus.

Where respiratory protective equipment is required, use a

full-face mask.

If air-filtering respirators are suitable for conditions of use:

Select a filter suitable for combined particulate/organic gases and vapours [Type AX/Type P boiling point < 65°C (149°F)]

meeting EN14387 and EN143.

# **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Physical state : Gas at Standard Temperature and Pressure.

Colour : colourless

Odour : Data not available

Odour Threshold : 270 - 600 ppm

Melting point/freezing point : -169,2 °C

Boiling point/boiling range : -103,7 °C

Flammability

Flammability (solid, gas) : Flammable gas.

Lower explosion limit and upper explosion limit / flammability limit

Upper explosion limit /

upper flammability limit

36 %(V)

Lower explosion limit / Lower flammability limit

: 2,7 %(V)

Flash point

: -136 °C

Auto-ignition temperature : 450 °C

According to EC No 1907/2006 as amended as at the date of this SDS

# C Ethylene

SDS Number: Date of last issue: 29.03.2023 Version Revision Date:

2.3 12.02.2024 800010047427 Print Date 19.02.2024

Decomposition temperature

Decomposition tempera-Data not available

ture

рH Not applicable

Viscosity

Viscosity, dynamic Data not available

Viscosity, kinematic Data not available

Solubility(ies)

Water solubility 131 mg/l (25 °C)

Solubility in other solvents Data not available

Partition coefficient: n-

log Pow: 1,13 octanol/water

Method: Literature data.

Vapour pressure 4.275 kPa (1,9 °C)

0,568 (-104 °C) Relative density

Method: ASTM D4052

Density 568 kg/m3 (-104 °C)

Method: ASTM D4052

Relative vapour density 0,975 (0 °C)

9.2 Other information

Explosive properties no data available

Oxidizing properties Data not available

Evaporation rate Data not available

Conductivity Low conductivity: < 100 pS/m, The conductivity of this material

> makes it a static accumulator., A liquid is typically considered nonconductive if its conductivity is below 100 pS/m and is considered semi-conductive if its conductivity is below 10,000 pS/m., Whether a liquid is nonconductive or semi-conductive, the precautions are the same., A number of factors, for example liquid temperature, presence of contaminants, and antistatic additives can greatly influence the conductivity of a lig-

uid

Surface tension Data not available

Molecular weight 28 g/mol

According to EC No 1907/2006 as amended as at the date of this SDS

# **C** Ethylene

Version Revision Date: SDS Number: Date of last issue: 29.03.2023

2.3 12.02.2024 800010047427 Print Date 19.02.2024

### **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.

### 10.2 Chemical stability

No hazardous reaction is expected when handled and stored according to provisions

Reacts violently with strong oxidising agents.

Reacts violently with hydrochloric acid, hydrogen bromide and nitrogen oxides.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : Polymerisation may occur at elevated temperatures.

#### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames, and sparks.

Exposure to air.

In certain circumstances product can ignite due to static elec-

tricity.

#### 10.5 Incompatible materials

Materials to avoid : Strong oxidising agents.

Hydrochloric acid, hydrogen bromide and nitrogen oxides.

### 10.6 Hazardous decomposition products

Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids and gases including carbon monoxide, carbon dioxide, sulphur oxides and unidentified organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation.

### **SECTION 11: Toxicological information**

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of : Inhalation is the primary route of exposure.

exposure

#### **Acute toxicity**

### **Components:**

#### ethylene:

Acute inhalation toxicity : LC 50 (Rat, male): > 20000 ppm

Exposure time: 4 h Test atmosphere: gas Method: Literature data

Remarks: Based on available data, the classification criteria

are not met.

High gas concentrations will displace available air; uncon-

According to EC No 1907/2006 as amended as at the date of this SDS

# **C** Ethylene

Version Revision Date: SDS Number: Date of last issue: 29.03.2023

2.3 12.02.2024 800010047427 Print Date 19.02.2024

sciousness and death may occur suddenly from lack of oxy-

gen.

Skin corrosion/irritation

**Components:** 

ethylene:

Remarks : Rapid release of gases which are liquids under pressure may

cause frost burns of exposed tissues (skin, eye) due to evapo-

rative cooling.

Serious eye damage/eye irritation

**Components:** 

ethylene:

Remarks : Rapid release of gases which are liquids under pressure may

cause frost burns of exposed tissues (skin, eye) due to evapo-

rative cooling.

Germ cell mutagenicity

**Components:** 

ethylene:

Genotoxicity in vitro : Method: Test(s) equivalent or similar to OECD Guideline 471

Remarks: Based on available data, the classification criteria

are not met.

Method: OECD Test Guideline 473

Remarks: Based on available data, the classification criteria

are not met.

Genotoxicity in vivo : Species: Rat

Method: Test(s) equivalent or similar to OECD Test Guideline

4/4

Remarks: Based on available data, the classification criteria

are not met.

Germ cell mutagenicity- As-

sessment

This product does not meet the criteria for classification in

categories 1A/1B.

Carcinogenicity

**Components:** 

ethylene:

Species : Rat, male and female

Application Route : Inhalation

Method : Test(s) equivalent or similar to OECD Test Guideline 453

According to EC No 1907/2006 as amended as at the date of this SDS

# **C** Ethylene

Version Revision Date: SDS Number: Date of last issue: 29.03.2023

2.3 12.02.2024 800010047427 Print Date 19.02.2024

Remarks : Based on available data, the classification criteria are not met.

Carcinogenicity - Assess-

ment

This product does not meet the criteria for classification in

categories 1A/1B.

Material	GHS/CLP Carcinogenicity Classification
ethylene	No carcinogenicity classification.

Material	Other Carcinogenicity Classification
ethylene	IARC: Group 3: Not classifiable as to its carcinogenicity to humans

#### Reproductive toxicity

### **Components:**

ethylene:

Effects on fertility : Species: Rat

Sex: male and female

Application Route: Inhalation

Method: OECD Test Guideline 421

Remarks: Based on available data, the classification criteria

are not met.

Reproductive toxicity - As-

sessment

This product does not meet the criteria for classification in

categories 1A/1B.

#### STOT - single exposure

# **Components:**

ethylene:

Remarks : May cause drowsiness or dizziness.

High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea.

#### STOT - repeated exposure

#### **Components:**

ethylene:

Remarks : Based on available data, the classification criteria are not met.

According to EC No 1907/2006 as amended as at the date of this SDS

# **C** Ethylene

Version Revision Date: SDS Number: Date of last issue: 29.03.2023

2.3 12.02.2024 800010047427 Print Date 19.02.2024

### Repeated dose toxicity

#### **Components:**

#### ethylene:

Species : Rat, male and female

Application Route : Inhalation

Test atmosphere : Gas

Method : OECD Test Guideline 413
Target Organs : No specific target organs noted

Symptoms : Strain-dependent, Subacute rhinitis, Nasal lesions Remarks : Treatment-related but slight and not considered adverse.

# **Aspiration toxicity**

#### **Components:**

# ethylene:

Based on available data, the classification criteria are not met.

#### 11.2 Information on other hazards

#### **Endocrine disrupting properties**

# **Product:**

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

### **Further information**

**Product:** 

Remarks : Unless indicated otherwise, the data presented is representa-

tive of the product as a whole, rather than for individual com-

ponent(s).

# Components:

ethylene:

Remarks : Classifications by other authorities under varying regulatory

frameworks may exist.

According to EC No 1907/2006 as amended as at the date of this SDS

# **C** Ethylene

Version Revision Date: SDS Number: Date of last issue: 29.03.2023

2.3 12.02.2024 800010047427 Print Date 19.02.2024

# **SECTION 12: Ecological information**

# 12.1 Toxicity

# **Components:**

ethylene:

Toxicity to fish : LC50 : 126,012 mg/l

Exposure time: 96 h

Method: Based on quantitative structure-activity relationship

(QSAR) modelling

Remarks: Practically non toxic: LL/EL/IL50 > 100 mg/l

Toxicity to daphnia and other :

aquatic invertebrates

Remarks: Practically non toxic:

LL/EL/IL50 > 100 mg/l

Toxicity to algae/aquatic plants : Remarks: Practically non toxic:

LL/EL/IL50 > 100 mg/l

Toxicity to microorganisms

Remarks: Data not available

Toxicity to fish (Chronic tox-

icity)

Remarks: Data not available

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

ic toxicity)

Remarks: Data not available

#### 12.2 Persistence and degradability

#### Components:

ethylene:

Biodegradability : Biodegradation: 50 %

Exposure time: 2,9 d

Method: Based on quantitative structure-activity relationship

(QSAR) modelling

Remarks: Readily biodegradable.

#### 12.3 Bioaccumulative potential

# **Components:**

ethylene:

Bioaccumulation : Remarks: Does not bioaccumulate significantly.

According to EC No 1907/2006 as amended as at the date of this SDS

# **C** Ethylene

Version Revision Date: SDS Number: Date of last issue: 29.03.2023

2.3 12.02.2024 800010047427 Print Date 19.02.2024

### 12.4 Mobility in soil

#### **Components:**

ethylene:

Mobility : Remarks: Because of their extreme volatility, air is the only

environmental compartment that hydrocarbon gases will be

found.

#### 12.5 Results of PBT and vPvB assessment

#### **Components:**

ethylene:

Assessment : The substance does not fulfill all screening criteria for persis-

tence, bioaccumulation and toxicity and hence is not consid-

ered to be PBT or vPvB..

#### 12.6 Endocrine disrupting properties

**Product:** 

Assessment : The substance/mixture does not contain components considered to

have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# 12.7 Other adverse effects

**Product:** 

Additional ecological infor-

mation

: Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

**Components:** 

ethylene:

Additional ecological infor-

mation

In view of the high rate of loss from solution, the product is unlikely

to pose a significant hazard to aquatic life.

#### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Product : Recover or recycle if possible.

It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal meth-

ods in compliance with applicable regulations.

Do not dispose into the environment, in drains or in water

courses.

According to EC No 1907/2006 as amended as at the date of this SDS

# **C** Ethylene

Version Revision Date: SDS Number: Date of last issue: 29.03.2023 2.3 12.02.2024 800010047427 Print Date 19.02.2024

Waste product should not be allowed to contaminate soil or

water.

Local regulations may be more stringent than regional or na-

tional requirements and must be complied with.

Contaminated packaging : Disposal should be in accordance with applicable regional,

national, and local laws and regulations.

### **SECTION 14: Transport information**

14.1 UN number or ID number

ADN : 1038
ADR : 1038
RID : 1038
IMDG : 1038
IATA : 1038

(Not permitted for transport)

14.2 UN proper shipping name

ADN : ETHYLENE, REFRIGERATED LIQUID
ADR : ETHYLENE, REFRIGERATED LIQUID
RID : ETHYLENE, REFRIGERATED LIQUID
IMDG : ETHYLENE, REFRIGERATED LIQUID

IATA : ETHYLENE, REFRIGERATED LIQUID

14.3 Transport hazard class(es)

ADN : 2
ADR : 2
RID : 2
IMDG : 2.1
IATA : 2.1

Not permitted for transport

14.4 Packing group

**ADN** 

Packing group : Not Assigned

Classification Code : 3F Labels : 2.1

CDNI Inland Water Waste

Agreement

: NST 3303 Ethylene

ADR

Packing group : Not assigned by regulation

According to EC No 1907/2006 as amended as at the date of this SDS

# **C** Ethylene

Version Revision Date: SDS Number: Date of last issue: 29.03.2023

2.3 12.02.2024 800010047427 Print Date 19.02.2024

Classification Code : 3F Hazard Identification Number : 223 Labels : 2.1

**RID** 

Packing group : Not assigned by regulation

Classification Code : 3F Hazard Identification Number : 223 Labels : 2.1

**IMDG** 

Packing group : Not assigned by regulation

Labels : 2.1

**IATA** 

Packing group : Not Assigned

Labels : 2.1

14.5 Environmental hazards

**ADN** 

Environmentally hazardous : no

**ADR** 

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

Remarks : Special Precautions: Refer to Section 7, Handling & Storage,

for special precautions which a user needs to be aware of or

needs to comply with in connection with transport.

14.7 Maritime transport in bulk according to IMO instruments

Ship type : 2G Ethylene Carrier

Product name : Ethylene

**SECTION 15: Regulatory information** 

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - List of substances subject to authorisation

(Annex XIV)

: Product is not subject to Authorisation under REACH.

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

: This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH),

Article 57).

According to EC No 1907/2006 as amended as at the date of this SDS

# C Ethylene

Version Revision Date: SDS Number: Date of last issue: 29.03.2023

2.3 12.02.2024 800010047427 Print Date 19.02.2024

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Liquefied flammable gases (including LPG) and natural gas

#### Other regulations:

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

18

Product is subject to Major accident risk decision 2015 (BRZO+) based on Seveso III directive (2012/18/EU).

# The components of this product are reported in the following inventories:

AIIC : Listed

DSL : Listed

IECSC : Listed

ENCS : Listed

KECI : Listed

NZIoC : Listed

PICCS : Listed

TCSI : Listed

TSCA : Listed

# 15.2 Chemical safety assessment

A Chemical Safety Assessment was performed for all substances of this product.

#### **SECTION 16: Other information**

#### Full text of other abbreviations

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration as-

According to EC No 1907/2006 as amended as at the date of this SDS

# **C** Ethylene

Version Revision Date: SDS Number: Date of last issue: 29.03.2023

2.3 12.02.2024 800010047427 Print Date 19.02.2024

sociated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI -Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

#### **Further information**

Training advice : Provide adequate information, instruction and training for op-

erators.

Other information : This product is not classified for human health or environmen-

tal hazards. An exposure scenario is not required.

For Industry guidance and tools on REACH please visit the

CEFIC website at http://cefic.org/Industry-support.

The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not consid-

ered to be PBT or vPvB.

A vertical bar (|) in the left margin indicates an amendment

from the previous version.

Sources of key data used to compile the Safety Data

Sheet

The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU

IUCLID date base, EC 1272 regulation, etc).

# Identified Uses according to the Use Descriptor System Uses - Worker

Title : - Industrial

Manufacture of substance Use as an intermediate Distribution of substance Use in functional fluids Use in polymer production

According to EC No 1907/2006 as amended as at the date of this SDS

# **C** Ethylene

Version Revision Date: SDS Number: Date of last issue: 29.03.2023

2.3 12.02.2024 800010047427 Print Date 19.02.2024

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

NL / EN