

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Light Olefin Feed

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Print Date: 09/03/2022 |
| 9.0 | 06/08/2018 | 800001011426 | Date of last issue: 06/08/2018 |

SECTION 1. IDENTIFICATION

Product name : Light Olefin Feed

Product code : X2259, X2500

Manufacturer or supplier's details

Company : **Shell Chemical LP**
PO Box 576
HOUSTON TX 77001
USA

SDS Request : 1-800-240-6737
Customer Service : 1-855-697-4355

Emergency telephone number

Chemtrec Domestic (24 hr) : 1-800-424-9300
Chemtrec International (24 hr) : 1-703-527-3887

Recommended use of the chemical and restrictions on use

Recommended use : Base chemical., For industrial use only.

Restrictions on use : This product must not be used in applications other than those listed in Section 1 without first seeking the advice of the supplier.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

| | |
|---|--------------------------------------|
| Flammable liquids | : Category 3 |
| Aspiration hazard | : Category 1 |
| Acute toxicity (Inhalation) | : Category 4 |
| Skin irritation | : Category 2 |
| Carcinogenicity | : Category 2 |
| Specific target organ toxicity - repeated exposure | : Category 2 (Blood, thymus, Liver.) |
| Chronic aquatic toxicity | : Category 2 |

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Light Olefin Feed

Version
9.0

Revision Date:
06/08/2018

SDS Number:
800001011426

Print Date: 09/03/2022
Date of last issue: 06/08/2018

GHS label elements

Hazard pictograms

:



Signal word

:

Danger

Hazard statements

:

PHYSICAL HAZARDS:
H226 Flammable liquid and vapour.
HEALTH HAZARDS:
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H332 Harmful if inhaled.
H373 May cause damage to organs (Blood, Liver, thymus) through prolonged or repeated exposure.
H351 Suspected of causing cancer.
ENVIRONMENTAL HAZARDS:
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

:

Prevention:

P201 + P202 Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P264 Wash hands thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Light Olefin Feed

Version
9.0

Revision Date:
06/08/2018

SDS Number:
800001011426

Print Date: 09/03/2022
Date of last issue: 06/08/2018

P314 Get medical advice/ attention if you feel unwell.
P321 Specific treatment (see supplemental first aid instructions on this label).
P331 Do NOT induce vomiting.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.
P370 + P378 In case of fire: Use appropriate media to extinguish.
P391 Collect spillage.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Disposal:

P501 Dispose of contents and container to appropriate waste site or reclaimer in accordance with local and national regulations.

Other hazards which do not result in classification

May ignite on surfaces at temperatures above auto-ignition temperature.
Vapour in the headspace of tanks and containers may ignite and explode at temperatures exceeding auto-ignition temperature, where vapour concentrations are within the flammability range.
This material is a static accumulator.
Even with proper grounding and bonding, this material can still accumulate an electrostatic charge.
If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur.
This product is intended for use in closed systems only.
The classification of this material is based on OSHA HCS 2012 criteria.
Hydrogen sulphide (H₂S), an extremely flammable and toxic gas, and other hazardous vapours may evolve and collect in the headspace of storage tanks, transport vessels and other enclosed containers.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous components

| Chemical name | Synonyms | CAS-No. | Concentration (% w/w) |
|------------------------------------|------------------------------------|------------|-----------------------|
| Gas oils (petroleum), light vacuum | Gas oils (petroleum), light vacuum | 64741-58-8 | <= 100 |

Hydrogen sulphide may be present both in the liquid and the vapour. Composition is complex and varies with the source of the crude oil and the contributing process plants at that time.

SECTION 4. FIRST-AID MEASURES

General advice : Vapourisation of H₂S that has been trapped in clothing can be dangerous to rescuers. Maintain respiratory protection to

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Light Olefin Feed

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Print Date: 09/03/2022 |
| 9.0 | 06/08/2018 | 800001011426 | Date of last issue: 06/08/2018 |

-
- | | |
|---|---|
| | <p>avoid contamination from the victim to rescuer. Mechanical ventilation should be used to resuscitate if at all possible.</p> |
| If inhaled | <p>: Call emergency number for your location / facility. Remove to fresh air. Do not attempt to rescue the victim unless proper respiratory protection is worn. If the victim has difficulty breathing or tightness of the chest, is dizzy, vomiting, or unresponsive, give 100% oxygen with rescue breathing or Cardio-Pulmonary Resuscitation as required and transport to the nearest medical facility.</p> <p>Respiratory irritation signs and symptoms may include a temporary burning sensation of the nose and throat, coughing, and/or difficulty breathing.</p> |
| In case of skin contact | <p>: Remove contaminated clothing. Immediately flush skin with large amounts of water for at least 15 minutes, and follow by washing with soap and water if available. If redness, swelling, pain and/or blisters occur, transport to the nearest medical facility for additional treatment.</p> <p>When using high pressure equipment, injection of product under the skin can occur. If high pressure injuries occur, the casualty should be sent immediately to a hospital. Do not wait for symptoms to develop.</p> <p>Obtain medical attention even in the absence of apparent wounds.</p> |
| In case of eye contact | <p>: Immediately flush eye(s) with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>Transport to the nearest medical facility for additional treatment.</p> <p>Eye irritation signs and symptoms may include a burning sensation, redness, swelling, and/or blurred vision.</p> |
| If swallowed | <p>: Call emergency number for your location / facility.</p> <p>If swallowed, do not induce vomiting: transport to nearest medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.</p> <p>If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (38.3°C), shortness of breath, chest congestion or continued coughing or wheezing.</p> |
| Most important symptoms and effects, both acute and delayed | <p>: If material enters lungs, signs and symptoms may include coughing, choking, wheezing, difficulty in breathing, chest congestion, shortness of breath, and/or fever.</p> <p>If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (38.3°C), shortness of breath, chest congestion or continued coughing or wheezing.</p> <p>Respiratory irritation signs and symptoms may include a tem-</p> |

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Light Olefin Feed

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Print Date: 09/03/2022 |
| 9.0 | 06/08/2018 | 800001011426 | Date of last issue: 06/08/2018 |

porary burning sensation of the nose and throat, coughing, and/or difficulty breathing.
Skin irritation signs and symptoms may include a burning sensation, redness, swelling, and/or blisters.
No specific hazards under normal use conditions.
Eye irritation signs and symptoms may include a burning sensation, redness, swelling, and/or blurred vision.

Protection of first-aiders : When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.

Indication of any immediate medical attention and special treatment needed : Call a doctor or poison control center for guidance.
Potential for chemical pneumonitis.
Treat symptomatically.

Hydrogen sulphide (H₂S) - CNS asphyxiant. May cause rhinitis, bronchitis and occasionally pulmonary oedema after severe exposure. CONSIDER: Oxygen therapy. Consult a Poison Control Center for guidance.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

Unsuitable extinguishing media : Do not use water in a jet.
Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam.

Specific hazards during fire-fighting : Hazardous combustion products may include:
A complex mixture of airborne solid and liquid particulates and gases (smoke).
Oxides of sulphur.
Unidentified organic and inorganic compounds.
Carbon monoxide may be evolved if incomplete combustion occurs.
Will float and can be reignited on surface water.
Flammable vapours may be present even at temperatures below the flash point.
The vapour is heavier than air, spreads along the ground and distant ignition is possible.

Specific extinguishing methods : Use water spray to cool unopened containers.

Further information : Keep adjacent containers cool by spraying with water.
If possible remove containers from the danger zone.
If the fire cannot be extinguished the only course of action is to evacuate immediately.
Contain residual material at affected sites to prevent material from entering drains (sewers), ditches, and waterways.

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Light Olefin Feed

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Print Date: 09/03/2022 |
| 9.0 | 06/08/2018 | 800001011426 | Date of last issue: 06/08/2018 |

Special protective equipment for firefighters : Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Do not breathe fumes, vapour.
Do not operate electrical equipment.
Shut off leaks, if possible without personal risks. Remove all possible sources of ignition in the surrounding area and evacuate all personnel. Attempt to disperse the gas or to direct its flow to a safe location for example by using fog sprays. Take precautionary measures against static discharge. Ensure electrical continuity by bonding and grounding (earthing) all equipment. Monitor area with combustible gas meter.

Environmental precautions : Take measures to minimise the effects on groundwater.
Contain residual material at affected sites to prevent material from entering drains (sewers), ditches, and waterways.
Prevent from spreading or entering into drains, ditches or rivers by using sand, earth, or other appropriate barriers.

Methods and materials for containment and cleaning up : Take precautionary measures against static discharges.
For small liquid spills (< 1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.
For large liquid spills (> 1 drum), transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.
Prevent from spreading or entering into drains, ditches or rivers by using sand, earth, or other appropriate barriers.

Avoid contact with skin, eyes and clothing.
Evacuate the area of all non-essential personnel.
Ventilate contaminated area thoroughly.
Take precautionary measures against static discharges.
Observe all relevant local and international regulations.

Additional advice : For guidance on selection of personal protective equipment see Chapter 8 of this Safety Data Sheet.
Notify authorities if any exposure to the general public or the environment occurs or is likely to occur.
For guidance on disposal of spilled material see Chapter 13 of

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Light Olefin Feed

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Print Date: 09/03/2022 |
| 9.0 | 06/08/2018 | 800001011426 | Date of last issue: 06/08/2018 |

this Safety Data Sheet.

Local authorities should be advised if significant spillages cannot be contained.

Maritime spillages should be dealt with using a Shipboard Oil Pollution Emergency Plan (SOPEP), as required by MARPOL Annex 1 Regulation 26.

This material is covered by EPA's Comprehensive Environmental Response, Compensation and Liability Act (CERCLA) Petroleum Exclusion. Therefore, releases to the environment may not be reportable under CERCLA.

U.S. regulations may require reporting releases of this material to the environment which exceed the reportable quantity (refer to Chapter 15) to the National Response Center at (800) 424-8802.

Under Section 311 of the Clean Water Act (CWA) this material is considered an oil. As such, spills into surface waters must be reported to the National Response Center at (800) 424-8802.

SECTION 7. HANDLING AND STORAGE

Technical measures : Avoid breathing of or direct contact with material. Only use in well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see Chapter 8 of this Safety Data Sheet.

Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.

Air-dry contaminated clothing in a well-ventilated area before laundering.

Prevent spillages.

Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols.

Never siphon by mouth.

Contaminated leather articles including shoes cannot be decontaminated and should be destroyed to prevent reuse.

Advice on safe handling : Ensure that all local regulations regarding handling and storage facilities are followed.

Avoid inhaling vapour and/or mists.

Avoid prolonged or repeated contact with skin.

When using do not eat or drink.

Extinguish any naked flames. Do not smoke. Remove ignition sources. Avoid sparks.

Earth all equipment.

Properly dispose of any contaminated rags or cleaning materials in order to prevent fires.

Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols.

The inherent toxic and olfactory (sense of smell) fatiguing

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Light Olefin Feed

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Print Date: 09/03/2022 |
| 9.0 | 06/08/2018 | 800001011426 | Date of last issue: 06/08/2018 |

properties of hydrogen sulphide require that air monitoring alarms be used if concentrations are expected to reach harmful levels such as in enclosed spaces, heated transport vessels and spill or leak situations. If the air concentration exceeds 10 ppm, the area should be evacuated unless respiratory protection is in use.

Avoidance of contact : Strong oxidising agents.

Product Transfer : Avoid splash filling Wait 2 minutes after tank filling (for tanks such as those on road tanker vehicles) before opening hatches or manholes. Wait 30 minutes after tank filling (for large storage tanks) before opening hatches or manholes. Keep containers closed when not in use. Contamination resulting from product transfer may give rise to light hydrocarbon vapour in the headspace of tanks that have previously contained gasoline. This vapour may explode if there is a source of ignition. Partly filled containers present a greater hazard than those that are full, therefore handling, transfer and sampling activities need special care. Even with proper grounding and bonding, this material can still accumulate an electrostatic charge. If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur. Be aware of handling operations that may give rise to additional hazards that result from the accumulation of static charges. These include but are not limited to pumping (especially turbulent flow), mixing, filtering, splash filling, cleaning and filling of tanks and containers, sampling, switch loading, gauging, vacuum truck operations, and mechanical movements. These activities may lead to static discharge e.g. spark formation. Restrict line velocity during pumping in order to avoid generation of electrostatic discharge (≤ 1 m/s until fill pipe submerged to twice its diameter, then ≤ 7 m/s). Avoid splash filling. Do NOT use compressed air for filling, discharging, or handling operations.

Further information on storage stability : Drum and small container storage:
Drums should be stacked to a maximum of 3 high.
Use properly labeled and closable containers.
Tank storage:
Tanks must be specifically designed for use with this product.
Bulk storage tanks should be diked (bunded).
Locate tanks away from heat and other sources of ignition.
Must be stored in a diked (bunded) well-ventilated area, away from sunlight, ignition sources and other sources of heat.
Vapours from tanks should not be released to atmosphere.
Breathing losses during storage should be controlled by a suitable vapour treatment system.
The vapour is heavier than air. Beware of accumulation in pits and confined spaces.
Keep container tightly closed and in a cool, well-ventilated place.
Keep in a cool place.

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Light Olefin Feed

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Print Date: 09/03/2022 |
| 9.0 | 06/08/2018 | 800001011426 | Date of last issue: 06/08/2018 |

Electrostatic charges will be generated during pumping. Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment to reduce the risk.
The vapours in the head space of the storage vessel may lie in the flammable/explosive range and hence may be flammable.
Refer to section 15 for any additional specific legislation covering the packaging and storage of this product.

- Packaging material : Suitable material: For containers, or container linings use mild steel, stainless steel.
Unsuitable material: Some synthetic materials may be unsuitable for containers or container linings depending on the material specification and intended use. Examples of materials to avoid are: natural rubber (NR), nitrile rubber (NBR), ethylene propylene rubber (EPDM), polymethyl methacrylate (PMMA), polystyrene, polyvinyl chloride (PVC), polyisobutylene., Compatibility should be checked with the manufacturer.
- Container Advice : Do not cut, drill, grind, weld or perform similar operations on or near containers. Containers, even those that have been emptied, can contain explosive vapours.
- Specific use(s) : Not applicable.

See additional references that provide safe handling practices for liquids that are determined to be static accumulators: American Petroleum Institute 2003 (Protection Against Ignitions Arising out of Static, Lightning and Stray Currents) or National Fire Protection Agency 77 (Recommended Practices on Static Electricity).
IEC/TS 60079-32-1: Electrostatic hazards, guidance

SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Components with workplace control parameters

Contains no substances with occupational exposure limit values.

Biological occupational exposure limits

No biological limit allocated.

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.
Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.
Examples of sources of recommended exposure measurement methods are given below or con-

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Light Olefin Feed

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Print Date: 09/03/2022 |
| 9.0 | 06/08/2018 | 800001011426 | Date of last issue: 06/08/2018 |

tact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods <http://www.cdc.gov/niosh/>

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods <http://www.osha.gov/>

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances <http://www.hse.gov.uk/>

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany <http://www.dguv.de/inhalt/index.jsp>

L'Institut National de Recherche et de Sécurité, (INRS), France <http://www.inrs.fr/accueil>

Engineering measures : The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:
Use sealed systems as far as possible.
Firewater monitors and deluge systems are recommended.
Adequate ventilation to control airborne concentrations below the exposure guidelines/limits.
Local exhaust ventilation is recommended.
Eye washes and showers for emergency use.

General Information:

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.
Define procedures for safe handling and maintenance of controls.
Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.
Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.
Drain down system prior to equipment break-in or maintenance.
Retain drain downs in sealed storage pending disposal or for subsequent recycle.
Do not ingest. If swallowed then seek immediate medical assistance

Personal protective equipment

Respiratory protection : If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers.

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Light Olefin Feed

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Print Date: 09/03/2022 |
| 9.0 | 06/08/2018 | 800001011426 | Date of last issue: 06/08/2018 |

Where air-filtering respirators are unsuitable (e.g. airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus.

Where air-filtering respirators are suitable, select an appropriate combination of mask and filter.

Select a filter suitable for the combination of organic gases and vapours [Type A/Type P boiling point >65°C (149°F)].

Hand protection Remarks

: Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. When prolonged or frequent repeated contact occurs. Nitrile rubber. For incidental contact/splash protection Neoprene, PVC gloves may be suitable. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same, but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

Eye protection

: If material is handled such that it could be splashed into eyes, protective eyewear is recommended.
If a local risk assessment deems it so then chemical splash goggles may not be required and safety glasses may provide adequate eye protection.

Skin and body protection

: Wear chemical resistant gloves/gauntlets and boots. Where risk of splashing, also wear an apron.

Protective measures

: Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Environmental exposure controls

General advice

: Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour.
Minimise release to the environment. An environmental as-

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Light Olefin Feed

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Print Date: 09/03/2022 |
| 9.0 | 06/08/2018 | 800001011426 | Date of last issue: 06/08/2018 |

assessment must be made to ensure compliance with local environmental legislation.
Information on accidental release measures are to be found in section 6.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

| | | |
|--|---|---|
| Appearance | : | Clear, bright liquid. |
| Colour | : | Brown to black |
| Odour | : | Hydrocarbon |
| Odour Threshold | : | Data not available |
| pH | : | Not applicable |
| Melting point/freezing point | : | Data not available |
| Boiling point/boiling range | : | -20.0 - 220.0 °C / -4.0 - 428.0 °F |
| Flash point | : | < -7 °C / 19 °F |
| Evaporation rate | : | Data not available |
| Flammability (solid, gas) | : | Not applicable |
| Upper explosion limit / upper flammability limit | : | 6 %(V) 7.5 %(V) not determined |
| Lower explosion limit / Lower flammability limit | : | 0.6 %(V) |
| Vapour pressure | : | Data not available |
| Relative vapour density | : | Data not available |
| Relative density | : | Data not available |
| Density | : | 800 - 910 kg/m ³ (15 °C / 59 °F) |
| Solubility(ies) | | |
| Water solubility | : | 0.05 g/l negligible |
| Solubility in other solvents | : | Data not available |
| Partition coefficient: n-octanol/water | : | log Pow: ca. 2 - 15 |
| | | Data not available |

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Light Olefin Feed

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Print Date: 09/03/2022 |
| 9.0 | 06/08/2018 | 800001011426 | Date of last issue: 06/08/2018 |

| | | |
|---------------------------|---|---|
| Auto-ignition temperature | : | Data not available |
| Decomposition temperature | : | no data available |
| Viscosity | | |
| Viscosity, dynamic | : | Data not available |
| Viscosity, kinematic | : | 2.5 - 11 mm ² /s (40 °C / 104 °F) |
| Explosive properties | : | Classification Code: NOT CLASS: Not classified |
| Oxidizing properties | : | Not applicable |
| Surface tension | : | Data not available |
| Conductivity | : | Low conductivity: < 100 pS/m, The conductivity of this material makes it a static accumulator., A liquid is typically considered nonconductive if its conductivity is below 100 pS/m and is considered semi-conductive if its conductivity is below 10,000 pS/m., Whether a liquid is nonconductive or semiconductive, the precautions are the same., A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid |
| Molecular weight | : | Data not available |

SECTION 10. STABILITY AND REACTIVITY

| | | |
|------------------------------------|---|--|
| Reactivity | : | The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph. |
| Chemical stability | : | Stable under normal use conditions. |
| Possibility of hazardous reactions | : | No hazardous reaction is expected when handled and stored according to provisions |
| Conditions to avoid | : | Avoid heat, sparks, open flames and other ignition sources. In certain circumstances product can ignite due to static electricity. |
| Incompatible materials | : | Strong oxidising agents. |
| Hazardous decomposition products | : | Hazardous decomposition products are not expected to form during normal storage. Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids and gases including carbon monoxide, carbon dioxide, sulphur oxides and unidentified organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation. |

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR
1910.1200

Light Olefin Feed

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Print Date: 09/03/2022 |
| 9.0 | 06/08/2018 | 800001011426 | Date of last issue: 06/08/2018 |

SECTION 11. TOXICOLOGICAL INFORMATION

Basis for assessment : Information given is based on product data, a knowledge of the components and the toxicology of similar products.
Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

Information on likely routes of exposure

Skin and eye contact are the primary routes of exposure although exposure may occur through inhalation or following accidental ingestion.

Acute toxicity

Product:

Acute oral toxicity : LD50 Oral (rat): > 5,000 mg/kg
Remarks: Low toxicity:

Acute inhalation toxicity : LC 50 (rat): > 1 - <=5 mg/l
Exposure time: 4 h
Remarks: Harmful if inhaled.
High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea; continued inhalation may result in unconsciousness and/or death.

Acute dermal toxicity : LD 50 (Rabbit): > 2,000 mg/kg
Remarks: Low toxicity:

Skin corrosion/irritation

Product:

Remarks: Irritating to skin.

Serious eye damage/eye irritation

Product:

Remarks: Slightly irritating to the eye., Based on available data, the classification criteria are not met.

Remarks: Irritating to eyes. (Hydrogen Sulfide)

Respiratory or skin sensitisation

Product:

Remarks: Not a sensitiser.

Based on available data, the classification criteria are not met.

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Light Olefin Feed

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Print Date: 09/03/2022 |
| 9.0 | 06/08/2018 | 800001011426 | Date of last issue: 06/08/2018 |

Germ cell mutagenicity

Product:

: Remarks: Positive in in-vitro, but negative in in-vivo mutagenicity assays.

Carcinogenicity

Product:

Remarks: Limited evidence of carcinogenic effect, Repeated skin contact has resulted in irritation and skin cancer in animals.

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Product:

: Remarks: Not a developmental toxicant., Based on available data, the classification criteria are not met., Does not impair fertility.

STOT - single exposure

Product:

Remarks: Inhalation of vapours or mists may cause irritation to the respiratory system., High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea; continued inhalation may result in unconsciousness and/or death.

Remarks: Inhalation of vapours or mists may cause irritation to the respiratory system., Contains hydrogen sulphide.

STOT - repeated exposure

Product:

Target Organs: Blood, thymus, Liver

Remarks: May cause damage to organs or organ systems through prolonged or repeated exposure.

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Light Olefin Feed

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Print Date: 09/03/2022 |
| 9.0 | 06/08/2018 | 800001011426 | Date of last issue: 06/08/2018 |

Aspiration toxicity

Product:

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

Further information

Product:

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

Remarks: H₂S has a broad range of effects dependent on the airborne concentration and length of exposure: 0.02 ppm odour threshold, smell of rotten eggs; 10 ppm eye and respiratory tract irritation; 100 ppm coughing, headache, dizziness, nausea, eye irritation, loss of sense of smell in minutes; 200 ppm potential for pulmonary oedema after >20-30 minutes; 500 ppm loss of consciousness after short exposures, potential for respiratory arrest; >1000ppm immediate loss of consciousness, may lead rapidly to death, prompt cardiopulmonary resuscitation may be required. Do not depend on sense of smell for warning. H₂S causes rapid olfactory fatigue (deadens sense of smell). There is no evidence that H₂S will accumulate in the body tissue after repeated exposure.

SECTION 12. ECOLOGICAL INFORMATION

Basis for assessment : Information given is based on a knowledge of the components and the ecotoxicology of similar products.
Fuels are typically made from blending several refinery streams. Ecotoxicological studies have been carried out on a variety of hydrocarbon blends and streams but not those containing additives.
Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

Ecotoxicity

Product:

| | | |
|--|---|---|
| Toxicity to fish (Acute toxicity) | : | Remarks: LL/EL/IL50 > 1 <= 10 mg/l Toxic |
| Toxicity to daphnia and other aquatic invertebrates (Acute toxicity) | : | Remarks: LL/EL/IL50 > 1 <= 10 mg/l Toxic |
| Toxicity to algae (Acute toxicity) | : | Remarks: LL/EL/IL50 > 1 <= 10 mg/l Toxic |
| Toxicity to fish (Chronic toxicity) | : | Remarks: NOEC/NOEL > 0.01 - <=0.1 mg/l |

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR
1910.1200

Light Olefin Feed

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Print Date: 09/03/2022 |
| 9.0 | 06/08/2018 | 800001011426 | Date of last issue: 06/08/2018 |

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : Remarks: NOEC/NOEL > 0.1 - <=1.0 mg/l

Toxicity to microorganisms (Acute toxicity) : Remarks: LL/EL/IL50 > 100 mg/l
Practically non toxic:
Based on available data, the classification criteria are not met.

Persistence and degradability

Product:

Biodegradability : Remarks: Readily biodegradable.

Bioaccumulative potential

Product:

Bioaccumulation : Remarks: Contains constituents with the potential to bioaccumulate.

Mobility in soil

Product:

Mobility : Remarks: Partly evaporates from water or soil surfaces, but a significant proportion will remain after one day.
If product enters soil, one or more constituents will be mobile and may contaminate groundwater.
Large volumes may penetrate soil and could contaminate groundwater.
Floats on water.

Other adverse effects

Product:

Additional ecological information : Films formed on water may affect oxygen transfer and damage organisms.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Recover or recycle if possible.
It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.
Do not dispose into the environment, in drains or in water courses
Do not dispose of tank water bottoms by allowing them to drain into the ground.
Waste arising from a spillage or tank cleaning should be dis-

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Light Olefin Feed

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Print Date: 09/03/2022 |
| 9.0 | 06/08/2018 | 800001011426 | Date of last issue: 06/08/2018 |

posed of in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand.

Contaminated packaging : After draining, vent in a safe place away from sparks and fire. Residues may cause an explosion hazard. Drain container thoroughly. Do not puncture, cut, or weld uncleaned drums. Send to drum recoverer or metal reclaimer. Do not pollute the soil, water or environment with the waste container.

SECTION 14. TRANSPORT INFORMATION

National Regulations

US Department of Transportation Classification (49 CFR Parts 171-180)

| | |
|----------------------|---------------------------------|
| UN/ID/NA number | : UN 1268 |
| Proper shipping name | : Petroleum distillates, n.o.s. |
| Class | : 3 |
| Packing group | : I |
| Labels | : 3 |
| ERG Code | : 128 |
| Marine pollutant | : no |
| Remarks | : Oil |

International Regulations

IATA-DGR

| | |
|----------------------|---------------------------------|
| UN/ID No. | : UN 1268 |
| Proper shipping name | : Petroleum distillates, n.o.s. |
| Class | : 3 |
| Packing group | : I |
| Labels | : 3 |

IMDG-Code

| | |
|----------------------|---|
| UN number | : UN 1268 |
| Proper shipping name | : PETROLEUM DISTILLATES, N.O.S. (Gas oils (petroleum), light vacuum) |
| Class | : 3 |
| Packing group | : I |
| Labels | : 3 |
| Marine pollutant | : yes |

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied. MARPOL Annex 1 rules apply for bulk shipments by sea.

Special precautions for user

Remarks : Special Precautions: Refer to Chapter 7, Handling & Storage, for special precautions which a user needs to be aware of or

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Light Olefin Feed

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Print Date: 09/03/2022 |
| 9.0 | 06/08/2018 | 800001011426 | Date of last issue: 06/08/2018 |

needs to comply with in connection with transport.

Additional Information : This material is an 'OIL' under 49 CFR Part 130 when transported in a container of 3500 gallon capacity or greater.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

*: This material does not contain any components with a CERCLA RQ.
Shell classifies this material as an "oil" under the CERCLA Petroleum Exclusion, therefore releases to the environment are not reportable under CERCLA.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
Aspiration hazard
Acute toxicity (any route of exposure)
Skin corrosion or irritation
Carcinogenicity
Specific target organ toxicity (single or repeated exposure)

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Water Act

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

US State Regulations

California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

Other regulations:

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

IARC has classified diesel exhaust emissions as a Class 1 carcinogen - carcinogenic to humans. Steps should be taken to prevent personal exposure to diesel exhaust emissions.

SECTION 16. OTHER INFORMATION

Further information

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR
1910.1200

Light Olefin Feed

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Print Date: 09/03/2022 |
| 9.0 | 06/08/2018 | 800001011426 | Date of last issue: 06/08/2018 |

NFPA Rating (Health, Fire, Reactivity) 2, 2, 0

Full text of other abbreviations

Abbreviations and Acronyms : The standard abbreviations and acronyms used in this document can be looked up in reference literature (e.g. scientific dictionaries) and/or websites.

ACGIH = American Conference of Governmental Industrial Hygienists
ADR = European Agreement concerning the International Carriage of Dangerous Goods by Road
AICS = Australian Inventory of Chemical Substances
ASTM = American Society for Testing and Materials
BEL = Biological exposure limits
BTEX = Benzene, Toluene, Ethylbenzene, Xylenes
CAS = Chemical Abstracts Service
CEFIC = European Chemical Industry Council
CLP = Classification Packaging and Labelling
COC = Cleveland Open-Cup
DIN = Deutsches Institut für Normung
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
DSL = Canada Domestic Substance List
EC = European Commission
EC50 = Effective Concentration fifty
ECETOC = European Center on Ecotoxicology and Toxicology Of Chemicals
ECHA = European Chemicals Agency
EINECS = The European Inventory of Existing Commercial Chemical Substances
EL50 = Effective Loading fifty
ENCS = Japanese Existing and New Chemical Substances Inventory
EWC = European Waste Code
GHS = Globally Harmonised System of Classification and Labelling of Chemicals
IARC = International Agency for Research on Cancer
IATA = International Air Transport Association
IC50 = Inhibitory Concentration fifty
IL50 = Inhibitory Level fifty
IMDG = International Maritime Dangerous Goods
INV = Chinese Chemicals Inventory
IP346 = Institute of Petroleum test method N° 346 for the determination of polycyclic aromatics DMSO-extractables
KECI = Korea Existing Chemicals Inventory
LC50 = Lethal Concentration fifty
LD50 = Lethal Dose fifty per cent.
LL/EL/IL = Lethal Loading/Effective Loading/Inhibitory loading
LL50 = Lethal Loading fifty
MARPOL = International Convention for the Prevention of Pollution From Ships
NOEC/NOEL = No Observed Effect Concentration / No Ob-

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR
1910.1200

Light Olefin Feed

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Print Date: 09/03/2022 |
| 9.0 | 06/08/2018 | 800001011426 | Date of last issue: 06/08/2018 |

served Effect Level
OE_HPVS = Occupational Exposure - High Production Volume
PBT = Persistent, Bioaccumulative and Toxic
PICCS = Philippine Inventory of Chemicals and Chemical
Substances
PNEC = Predicted No Effect Concentration
REACH = Registration Evaluation And Authorisation Of
Chemicals
RID = Regulations Relating to International Carriage of Dan-
gerous Goods by Rail
SKIN_DES = Skin Designation
STEL = Short term exposure limit
TRA = Targeted Risk Assessment
TSCA = US Toxic Substances Control Act
TWA = Time-Weighted Average
vPvB = very Persistent and very Bioaccumulative

This product is intended for use in closed systems only.

Due to a change in detail in Section 15, this document has been released as a significant change.

Revision Date : 06/08/2018

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN