According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Isopropyl alcohol-cosmetic

Product code : S1114

Registration number EU : 01-2119457558-25-0001, 01-2119457558-25-0002 Synonyms : 2-propanol, Dimethyl carbinol, IPA C+, IPSC, Isopropanol

CAS-No. : 67-63-0

EC-No. : 200-661-7

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Solvent.

stance/Mixture Please refer to section 16 and/or the annexes for the regis-

tered uses under REACH.

Uses advised against : This product must not be used in applications other than the

above without first seeking the advice of the supplier.

This product must not be used in applications other than those listed in Section 1 without first seeking the advice of the sup-

plier.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier : Shell Chemicals Europe B.V.

PO Box 2334 3000 CH Rotterdam

Netherlands

Telephone : +31 (0)10 441 5137 / +31 (0)10 441 5191 Telefax : +31 (0)20 716 8316 / +31 (0)20 713 9230

Contact for Safety Data : sccmsds@shell.com

Sheet

1.4 Emergency telephone number

+44 (0) 1235 239 670

National Poison Information Centre (NVIC): Tel. nr. +31(0)88 755 8000 (24 hrs a day and 7

days a week).

Only for the purpose of informing medical personnel.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 2 H225: Highly flammable liquid and vapour.

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

Eye irritation, Category 2 H319: Causes serious eye irritation.

Specific target organ toxicity - single exposure, Category 3, Inhalation, Narcotic

effects , Oral H336: May cause drowsiness or dizziness.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :





Signal word : Danger

Hazard statements : PHYSICAL HAZARDS:

H225 Highly flammable liquid and vapour.

HEALTH HAZARDS:

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

ENVIRONMENTAL HAZARDS:

Not classified as environmental hazard according to

CLP criteria.

Precautionary statements : Prevention:

P210 Keep away from heat, hot surfaces, sparks, open

flames and other ignition sources. No smoking. P243 Take action to prevent static discharges.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice/

attention.

P304 + P340 IF INHALED: Remove person to fresh air and

keep comfortable for breathing.

Storage:

No precautionary phrases.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

2.3 Other hazards

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Vapours are heavier than air. Vapours may travel across the ground and reach remote ignition sources causing a flashback fire danger.

Even with proper grounding and bonding, this material can still accumulate an electrostatic charge.

If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable airvapour mixtures can occur.

Slightly irritating to respiratory system.

SECTION 3: Composition/information on ingredients

3.1 Substances

Components

Chemical name	CAS-No. EC-No.	Concentration (% w/w)
Isopropyl alcohol	67-63-0 200-661-7	<= 100

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Not expected to be a health hazard when used under normal

conditions.

Protection of first-aiders : When administering first aid, ensure that you are wearing the

appropriate personal protective equipment according to the

incident, injury and surroundings.

If inhaled : Remove to fresh air. If rapid recovery does not occur,

transport to nearest medical facility for additional treatment.

In case of skin contact : Remove contaminated clothing. Flush exposed area with wa-

ter and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses, if present and easy to do. Continue

rinsing.

Transport to the nearest medical facility for additional treat-

ment.

If swallowed : If swallowed, do not induce vomiting: transport to nearest

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (38.3°C), shortness of breath, chest congestion or continued coughing or wheezing.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Breathing of high vapour concentrations may cause central

nervous system (CNS) depression resulting in dizziness, lightheadedness, headache, nausea and loss of coordination. Continued inhalation may result in unconsciousness and

death.

No specific hazards under normal use conditions.

Skin irritation signs and symptoms may include a burning sen-

sation, redness, or swelling.

Eye irritation signs and symptoms may include a burning sen-

sation, redness, swelling, and/or blurred vision.

If material enters lungs, signs and symptoms may include coughing, choking, wheezing, difficulty in breathing, chest

congestion, shortness of breath, and/or fever.

If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (38.3°C), shortness of breath, chest congestion or continued coughing or wheezing.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : IMMEDIATE TREATMENT IS EXTREMELY IMPORTANT!

Call a doctor or poison control center for guidance.

Potential for chemical pneumonitis.

Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam, water spray or fog. Dry chemical pow-

der, carbon dioxide, sand or earth may be used for small fires

only.

Unsuitable extinguishing

media

None

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

The vapour is heavier than air, spreads along the ground and distant ignition is possible.

Carbon monoxide may be evolved if incomplete combustion

occurs.

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

5.3 Advice for firefighters

Special protective equipment :

for firefighters

Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to

relevant Standards (e.g. Europe: EN469).

Specific extinguishing meth-

ods

Standard procedure for chemical fires.

Further information : Clear fire area of all non-emergency personnel.

Keep adjacent containers cool by spraying with water.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Observe the relevant local and international regulations

Notify authorities if any exposure to the general public or the

environment occurs or is likely to occur.

Local authorities should be advised if significant spillages

cannot be contained.

The vapour is heavier than air, spreads along the ground and

distant ignition is possible.

Vapour may form an explosive mixture with air.

6.1.1 For non emergency personnel:
Avoid contact with skin, eyes and clothing.

Isolate hazard area and deny entry to unnecessary or unpro-

tected personnel.

Stay upwind and keep out of low areas. 6.1.2 For emergency responders:

Avoid contact with skin, eyes and clothing.

Isolate hazard area and deny entry to unnecessary or unpro-

tected personnel.

Stay upwind and keep out of low areas.

6.2 Environmental precautions

Environmental precautions

Shut off leaks, if possible without personal risks. Remove all possible sources of ignition in the surrounding area. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. Attempt to disperse the vapour or to direct its flow to a safe location for example by using fog sprays. Take precautionary measures against static discharge. Ensure electrical continuity by bond-

ing and grounding (earthing) all equipment. Ventilate contaminated area thoroughly. Monitor area with combustible gas indicator.

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : For large liquid spills (> 1 drum), transfer by mechanical

means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely For small liquid spills (< 1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove

contaminated soil and dispose of safely.

6.4 Reference to other sections

For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet., For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures : Avoid breathing of or direct contact with material. Only use in

well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see

Section 8 of this Safety Data Sheet.

Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this

material.

Ensure that all local regulations regarding handling and stor-

age facilities are followed.

Advice on safe handling : Avoid contact with skin, eyes and clothing.

Use local exhaust ventilation if there is risk of inhalation of

vapours, mists or aerosols.

Bulk storage tanks should be diked (bunded).

Extinguish any naked flames. Do not smoke. Remove ignition

sources. Avoid sparks.

Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment to

reduce the risk.

The vapours in the head space of the storage vessel may lie in the flammable/explosive range and hence may be flamma-

ble.

Properly dispose of any contaminated rags or cleaning mate-

rials in order to prevent fires.

Do NOT use compressed air for filling, discharging, or han-

dling operations.

Product Transfer : Refer to guidance under Handling section.

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: The vapour is heavier than air. Beware of accumulation in pits and confined spaces. Refer to section 15 for any additional specific legislation covering the packaging and storage of this

product.

Packaging material : Suitable material: For containers, or container linings use mild

steel, stainless steel.

Unsuitable material: Natural, butyl, neoprene or nitrile rubbers.

Container Advice : Containers, even those that have been emptied, can contain

explosive vapours. Do not cut, drill, grind, weld or perform

similar operations on or near containers.

7.3 Specific end use(s)

Specific use(s) : Please refer to section 16 and/or the annexes for the regis-

tered uses under REACH.

Ensure that all local regulations regarding handling and stor-

age facilities are followed.

See additional references that provide safe handling practices: American Petroleum Institute 2003 (Protection Against Ignitions Arising out of Static, Lightning and Stray Currents) or National Fire Protection Agency 77 (Recommended Practices

on Static Electricity).

IEC/TS 60079-32-1: Electrostatic hazards, guidance

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Biological occupational exposure limits

No biological limit allocated.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Isopropyl alcohol	Workers	Dermal	Long-term systemic effects	888 mg/kg bw/day
Isopropyl alcohol	Workers	Inhalation	Long-term systemic effects	500 mg/m3
Isopropyl alcohol	Consumers	Dermal	Long-term systemic effects	319 mg/kg bw/day
Isopropyl alcohol	Consumers	Inhalation	Long-term systemic effects	89 mg/m3
Isopropyl alcohol	Consumers	Oral	Long-term systemic effects	26 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name Er	nvironmental Compartment	Value
-------------------	--------------------------	-------

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

Isopropyl alcohol		
Remarks:	Exposure assessments have not been presented for the environment	
	therefore PNEC values not required.	

8.2 Exposure controls

Engineering measures

Read in conjunction with the Exposure Scenario for your specific use contained in the Annex. Read in conjunction with the Exposure Scenario for your specific use contained in the Annex. Use sealed systems as far as possible.

Adequate explosion-proof ventilation to control airborne concentrations below the exposure guidelines/limits.

Local exhaust ventilation is recommended.

Firewater monitors and deluge systems are recommended.

Eye washes and showers for emergency use.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

General Information:

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

Personal protective equipment

Read in conjunction with the Exposure Scenario for your specific use contained in the Annex.

Read in conjunction with the Exposure Scenario for your specific use contained in the Annex. The provided information is made in consideration of the PPE directive (Council Directive 89/686/EEC) and the CEN European Committee for Standardisation (CEN) standards.

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Eye protection : Wear goggles for use against liquids and gas.

Wear full face shield if splashes are likely to occur.

Approved to EU Standard EN166.

Hand protection

Remarks : Where hand contact with the product may occur the use of

gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

suitable chemical protection. Longer term protection: Butyl rubber. Nitrile rubber. Incidental contact/Splash protection: PVC or neoprene rubber gloves. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

Skin and body protection

Wear antistatic and flame-retardant clothing, if a local risk assessment deems it so.

Skin protection is not required under normal conditions of

For prolonged or repeated exposures use impervious clothing over parts of the body subject to exposure.

If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to relevant Standard, and provide employee skin care programmes.

Protective clothing approved to EU Standard EN14605.

Respiratory protection

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are unsuitable (e.g. airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus

Where air-filtering respirators are suitable, select an appropriate combination of mask and filter.

If air-filtering respirators are suitable for conditions of use: Select a filter suitable for organic gases and vapours [Type A boiling point > 65°C (149°F)] meeting EN14387.

Thermal hazards : Not applicable

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : Liquid.

Colour : clear

Odour : characteristic

Odour Threshold : Data not available

Melting / freezing point : -88 °C

Boiling point/boiling range : 82 - 83 °C

Flammability

Flammability (solid, gas) : Not applicable

Lower explosion limit and upper explosion limit / flammability limit

Upper explosion limit / : upper flammability limit

upper flammability limit 12 %(V)

Lower explosion limit / : Lower flammability limit

Lower flammability limit 2 %(V)

Flash point : 12 °C

Method: IP 170

Auto-ignition temperature : 425 °C

Method: ASTM E-659

Decomposition temperature

Decomposition tempera: Not applicable

ture

pH : Not applicable

Viscosity

Viscosity, dynamic : 2,43 mPa.s (20 °C)

Method: ASTM D445

Viscosity, kinematic : Data not available

Solubility(ies)

Water solubility : completely miscible

Solubility in other solvents : Readily soluble in various organic solvents.

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

Partition coefficient: n-

octanol/water

: log Pow: 0,05

Vapour pressure : 6.020 Pa

Relative density : 0,78 - 0,79 (20 °C)

Method: ASTM D4052

Density : 785 - 786 kg/m3 (20 °C)

Method: ASTM D4052

Relative vapour density : 2 (20 °C)

Particle characteristics

Particle size : Data not available

9.2 Other information

Explosive properties : Not applicable

Oxidizing properties : Data not available

Evaporation rate : 1,5

Method: ASTM D 3539, nBuAc=1

11

Method: DIN 53170, di-ethyl ether=1

Conductivity: > 10,000 pS/m

A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid, This material is not expected to be

a static accumulator.

Surface tension : 22,7 mN/m, 20 °C

Molecular weight : 60,1 g/mol

SECTION 10: Stability and reactivity

10.1 Reactivity

The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.

10.2 Chemical stability

No hazardous reaction is expected when handled and stored according to provisions

10.3 Possibility of hazardous reactions

Hazardous reactions : Reacts with strong oxidising agents.

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

10.4 Conditions to avoid

Conditions to avoid : Avoid heat, sparks, open flames and other ignition sources.

Prevent vapour accumulation.

In certain circumstances product can ignite due to static elec-

tricity.

10.5 Incompatible materials

Materials to avoid : Strong oxidising agents.

10.6 Hazardous decomposition products

Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids and gases including carbon monoxide, carbon dioxide, sulphur oxides and unidentified organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of : Exposure may occur via inhalation, ingestion, skin absorption,

exposure skin or eye contact, and accidental ingestion.

Acute toxicity

Components:

Isopropyl alcohol:

Acute oral toxicity : LD50 (Rat): > 5000 mg/kg

Remarks: Low toxicity

Acute inhalation toxicity : LC50 (Rat, male and female): > 10000 ppm

Exposure time: 6 h

Method: Test(s) equivalent or similar to OECD Test Guideline

403

Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcot-

ic effects.

Remarks: Low toxicity by inhalation.

Acute dermal toxicity : LD50 (Rabbit): > 5000 mg/kg

Remarks: Low toxicity

Skin corrosion/irritation

Components:

Isopropyl alcohol:

Remarks : Not irritating to skin.

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

Serious eye damage/eye irritation

Components:

Isopropyl alcohol:

Species : Rabbit Exposure time : 24 h

Method : Test(s) equivalent or similar to OECD Test Guideline 405

Remarks : Irritating to eyes.

Species : Rabbit Exposure time : 48 h

Method : Test(s) equivalent or similar to OECD Test Guideline 405

Remarks : Irritating to eyes.

Species : Rabbit Exposure time : 72 h

Method : Test(s) equivalent or similar to OECD Test Guideline 405

Remarks : Irritating to eyes.

Respiratory or skin sensitisation

Components:

Isopropyl alcohol:

Species : Guinea pig
Method : Buehler Test
Result : negative

Remarks : Not a sensitiser.

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Components:

Isopropyl alcohol:

Genotoxicity in vitro : Remarks: Based on available data, the classification criteria

are not met.

Genotoxicity in vivo : Remarks: Not mutagenic.

Germ cell mutagenicity- As-

sessment

This product does not meet the criteria for classification in

categories 1A/1B.

Carcinogenicity

Components:

Isopropyl alcohol:

Remarks : Not a carcinogen.

Carcinogenicity - Assess- : This product does not meet the criteria for classification in

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

ment categories 1A/1B.

Material	GHS/CLP Carcinogenicity Classification
Isopropyl alcohol	No carcinogenicity classification.

Material	Other Carcinogenicity Classification
Isopropyl alcohol	IARC: Group 3: Not classifiable as to its carcinogenicity to humans

Reproductive toxicity

Components:

Isopropyl alcohol:

Effects on fertility

Remarks: Does not impair fertility., Not a developmental toxicant., Based on available data, the classification criteria are

not met.

Reproductive toxicity - As-

sessment

This product does not meet the criteria for classification in

categories 1A/1B.

STOT - single exposure

Components:

Isopropyl alcohol:

Remarks : May cause drowsiness and dizziness.

STOT - repeated exposure

Components:

Isopropyl alcohol:

Remarks : Kidney: caused kidney effects in male rats which are not con-

sidered relevant to humans

Aspiration toxicity

Components:

Isopropyl alcohol:

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Date of last issue: 09.03.2023 Version Revision Date: SDS Number:

Print Date 16.10.2024 2.2 09.10.2024 800001006805

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment The substance/mixture does not contain components consid-

> ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

Further information

Product:

Remarks Unless indicated otherwise, the data presented is representa-

tive of the product as a whole, rather than for individual com-

ponent(s).

Components:

Isopropyl alcohol:

Remarks Exposure may enhance the toxicity of other materials.

Classifications by other authorities under varying regulatory

frameworks may exist.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Isopropyl alcohol:

Toxicity to fish Remarks: Practically non toxic:

LL/EL/IL50 > 100 mg/l

aquatic invertebrates

Toxicity to daphnia and other : Remarks: Practically non toxic:

LL/EL/IL50 > 100 mg/l

Toxicity to algae/aquatic plants : Remarks: Practically non toxic:

LL/EL/IL50 > 100 mg/l

Toxicity to microorganisms

Remarks: Practically non toxic:

LL/EL/IL50 > 100 mg/l

Toxicity to fish (Chronic tox-

icity)

Remarks: Data not available

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

Remarks: Data not available

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

ic toxicity)

12.2 Persistence and degradability

Components:

Isopropyl alcohol:

Biodegradability : Remarks: Readily biodegradable.

Oxidises rapidly by photo-chemical reactions in air.

12.3 Bioaccumulative potential

Components:

Isopropyl alcohol:

Bioaccumulation : Remarks: Does not bioaccumulate significantly.

12.4 Mobility in soil

Components:

Isopropyl alcohol:

Mobility : Remarks: Dissolves in water., If the product enters soil, one or

more constituents will or may be mobile and may contaminate

groundwater.

12.5 Results of PBT and vPvB assessment

Components:

Isopropyl alcohol:

Assessment : The substance does not fulfill all screening criteria for persis-

tence, bioaccumulation and toxicity and hence is not consid-

ered to be PBT or vPvB..

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to

have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological infor-

mation

Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

Components:

Isopropyl alcohol:

Additional ecological infor-

mation

: Does not have ozone depletion potential.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Recover or recycle if possible.

It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.

Do not dispose into the environment, in drains or in water

courses.

Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment. Waste, spills or used product is dangerous waste.

Disposal should be in accordance with applicable regional,

national, and local laws and regulations.

Local regulations may be more stringent than regional or na-

tional requirements and must be complied with.

MARPOL - see International Convention for the Prevention of Pollution from Ships (MARPOL 73/78) which provides tech-

nical aspects at controlling pollutions from ships.

Contaminated packaging : Drain container thoroughly.

After draining, vent in a safe place away from sparks and fire.

Residues may cause an explosion hazard. Do not, puncture, cut, or weld uncleaned drums. Send to drum recoverer or metal reclaimer.

Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand.

SECTION 14: Transport information

14.1 UN number or ID number

ADN : 1219
ADR : 1219
RID : 1219
IMDG : 1219
IATA : 1219

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

SDS Number: Date of last issue: 09.03.2023 Version Revision Date:

09.10.2024 800001006805 Print Date 16.10.2024 2.2

14.2 UN proper shipping name

ADN : ISOPROPANOL **ADR** : ISOPROPANOL **RID ISOPROPANOL IMDG ISOPROPANOL**

IATA : ISOPROPANOL

14.3 Transport hazard class(es)

ADN : 3 **ADR** 3 **RID** 3 **IMDG** 3 **IATA** : 3

14.4 Packing group

ADN

Packing group : 11 : F1 Classification Code Labels : 3

: NST 8192 Isopropyl alcohol

CDNI Inland Water Waste

Agreement

ADR

Packing group Ш Classification Code F1 Hazard Identification Number : 33 Labels 3

RID

Ш Packing group Classification Code F1 Hazard Identification Number : 33 Labels

IMDG

Packing group Ш Labels 3

IATA

Packing group : II Labels : 3

14.5 Environmental hazards

ADN

Environmentally hazardous : no

ADR

Environmentally hazardous no

Environmentally hazardous no

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

IMDG

Marine pollutant : no

14.6 Special precautions for user

Remarks : Special Precautions: Refer to Section 7, Handling & Storage,

for special precautions which a user needs to be aware of or

needs to comply with in connection with transport.

14.7 Maritime transport in bulk according to IMO instruments

Pollution category : Z

Ship type : IBC Chapter 18 cargo, must be double hulled

Product name : Isopropyl alcohol

Additional Information: This product may be transported under nitrogen blanketing.

Nitrogen is an odourless and invisible gas. Exposure to nitrogen may cause asphyxiation or death. Personnel must observe strict safety precautions when involved with a confined

space entry.

Transport in bulk according to Annex II of Marpol and the IBC

Code

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - List of substances subject to authorisation

(Annex XIV)

: Product is not subject to Authorisation under REACH.

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

: This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH),

Article 57).

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P5c

FLAMMABLE LIQUIDS

Other regulations:

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

Product is subject to Major accident risk decision 2015 (BRZO+) based on Seveso III directive (2012/18/EU).

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

The components of this product are reported in the following inventories:

AIIC : Listed

DSL : Listed

IECSC : Listed

ENCS : Listed

KECI : Listed

NZIoC : Listed

PICCS : Listed

TSCA : Listed

TCSI : Listed

15.2 Chemical safety assessment

A Chemical Safety Assessment has been carried out for this substance.

SECTION 16: Other information

Full text of other abbreviations

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA -European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergencv Schedule: ENCS - Existing and New Chemical Substances (Japan): ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice: IARC - International Agency for Research on Cancer: IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic sub-

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

stance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Training advice : Provide adequate information, instruction and training for op-

erators.

Other information : For Industry guidance and tools on REACH please visit the

CEFIC website at http://cefic.org/Industry-support.

The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not consid-

ered to be PBT or vPvB.

A vertical bar (|) in the left margin indicates an amendment

from the previous version.

Sources of key data used to compile the Safety Data

Sheet

The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU

IUCLID date base, EC 1272 regulation, etc).

Classification of the mixture: Classification procedure:

Flam. Liq. 2 H225 On basis of test data.

Eye Irrit. 2 H319 Expert judgement and weight of evi-

dence determination.

STOT SE 3 H336 Expert judgement and weight of evi-

dence determination.

Identified Uses according to the Use Descriptor System

Uses - Worker

Title : Water treatment chemicals

- Professional

Uses - Worker

Title : Water treatment chemicals

- Industrial

Uses - Worker

Title : Use in laboratories

- Professional

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

Uses - Worker

Title : Use in laboratories

- Industrial

Uses - Worker

Title : De-icing and anti-icing applications

- Professional

Uses - Worker

Title : Functional Fluids

- Professional

Uses - Worker

Title : Functional Fluids

- Industrial

Uses - Worker

Title : Use as a fuel

- Professional

Uses - Worker

Title : Use as a fuel

- Industrial

Uses - Worker

Title : Use in Agrochemicals uses

- Professional

Uses - Worker

Title : Use as binders and release agents

- Professional

Uses - Worker

Title : Use as binders and release agents

- Industrial

Uses - Worker

Title : Metal working fluids / rolling oils

- Professional

Uses - Worker

Title : Metal working fluids / rolling oils

Industrial

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

Uses - Worker

Title : Lubricants

- Professional

Uses - Worker

Title : Lubricants

- Industrial

Uses - Worker

Title : Use in Cleaning Agents

- Professional

Uses - Worker

Title : Use in Cleaning Agents

- Industrial

Uses - Worker

Title : Uses in Coatings

- Professional

Uses - Worker

Title : Uses in Coatings

- Industrial

Uses - Worker

Title : Formulation & (re)packing of substances and mixtures

- Industrial

Uses - Worker

Title : Distribution of substance

- Industrial

Uses - Worker

Title : Use as an intermediate

- Industrial

Uses - Worker

Title : Manufacture of substance

- Industrial

Identified Uses according to the Use Descriptor System

Uses - Consumer

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

Title : Use in coatings

- Consumer

Uses - Consumer

Title : Use in Cleaning Agents

- Consumer

Uses - Consumer

Title : Lubricants

- Consumer

Uses - Consumer

Title : Use in agrochemicals

- Consumer

Uses - Consumer

Title : Use as a fuel

- Consumer

Uses - Consumer

Title : Functional Fluids

- Consumer

Uses - Consumer

Title : Use in de-icing and anti-icing fluids

- Consumer

Uses - Consumer

Title : Other Consumer Uses

- Consumer

Uses - Consumer

Title : Water treatment chemicals

- Consumer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

NL / EN

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

Exposure Scenario - Worker

30000000313	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Water treatment chemicals- Professional
Use Descriptor	Sector of Use: SU22 Process Categories: PROC1, PROC3, PROC4, PROC8a, PROC8b, PROC13 Environmental Release Categories: ERC8f
Scope of process	Covers the use of the substance for the treatment of water in open and closed systems.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
Additional Information	No exposure assessment presented for the environment.
Section 2.1	Control of Worker Exposure
Product Characteristics	
Physical form of product	Liquid, vapour pressure 0.5 - 10 kPa at STP
Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100%., Unless stated otherwise.,
Frequency and Duration of	Use
Covers daily exposures up to	8 hours (unless stated differently).
Other Operational Condition	ns affecting Exposure
	in 20°C above ambient temperature (unless stated differently).
Assumes a good basic standa	ard of occupational hygiene is implemented.
Contributing Scenarios	Risk Management Measures
General measures (eye irritants).	Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands.
Bulk transfersDedicated facilityPROC8b	Clear transfer lines prior to de-coupling.
Drum/batch transfer- sPROC8b	Use drum pumps or carefully pour from container.
General exposures (closed systems)Use in contained batch processesPROC3	No other specific measures identified.
General exposures (open systems)PROC4	No other specific measures identified.
ManualPouring from small containersPROC13	Carefully pour from containers.
Equipment cleaning and maintenancePROC8a	Retain drain downs in sealed storage pending disposal or for subsequent recycle.

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

Section 2.2	Control of Environmental Exposure	
No exposure assessment pre	sented for the environment.	

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise	
indicated.	

Section 3.2 - Environment

No exposure assessment presented for the environment.

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	
Measures/Operational Condit Where other Risk Manageme	expected to exceed the DN(M)EL when the Risk Management tions outlined in Section 2 are implemented. In the Measures of the Me

Section 4.2 -Environment

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

Exposure Scenario - Worker

30000000312	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Water treatment chemicals- Industrial
Use Descriptor	Sector of Use: SU3 Process Categories: PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC13 Environmental Release Categories: ERC3, ERC4
Scope of process	Covers the use of the substance for the treatment of water at industrial facilities in open and closed systems.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
Additional Information	No exposure assessment presented for the environment.
Section 2.1	Control of Worker Exposure
Product Characteristics	
Physical form of product	Liquid, vapour pressure 0.5 - 10 kPa at STP
Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100%., Unless stated otherwise.,
Frequency and Duration of	Use
	o 8 hours (unless stated differently).
Other Operational Condition	
	an 20°C above ambient temperature (unless stated differently).
Assumes a good basic stand	dard of occupational hygiene is implemented.
Contributing Scenarios	Risk Management Measures
General measures (eye	Use suitable eye protection.
irritants).	Avoid direct eye contact with product, also via contamination on hands.
Bulk transfers(closed systems)PROC2	Clear transfer lines prior to de-coupling.
Drum/batch transfersDedicated facilityPROC8b	Use drum pumps or carefully pour from container.
General exposures (closed systems)Use in contained batch processesPROC3	No other specific measures identified.
General exposures (open systems)PROC4	No other specific measures identified.
ManualPouring from small containersPROC13	Carefully pour from containers.
	Retain drain downs in sealed storage pending disposal or for
Equipment cleaning and maintenancePROC8a	subsequent recycle.

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

Section 2.2	Control of Environmental Exposure	
No exposure assessment presented for the environment.		

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise	
indicated.	

Section 3.2 - Environment

No exposure assessment presented for the environment.

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	
Measures/Operational Condit Where other Risk Manageme	expected to exceed the DN(M)EL when the Risk Management tions outlined in Section 2 are implemented. ent Measures/Operational Conditions are adopted, then users managed to at least equivalent levels.

Section 4.2 -Environment

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

Exposure Scenario - Worker

Expedit edenario Treritor	
30000000311	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Use in laboratories- Professional
Use Descriptor	Sector of Use: SU22 Process Categories: PROC10, PROC15 Environmental Release Categories: ERC8a
Scope of process	Use of small quantities within laboratory settings, including material transfers and equipment cleaning.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Additional Information	No exposure assessment presented for the environment.	
Section 2.1	Control of Worker Exposure	
Product Characteristics		
Physical form of product	Liquid, vapour pressure 0.5 - 10 kPa at STP	
Concentration of the Sub-	Covers percentage substance in the product up to 100%.,	
stance in Mixture/Article	Unless stated otherwise.,	
Frequency and Duration of	Use	
Covers daily exposures up to	o 8 hours (unless stated differently).	
Other Operational Condition		
Assumes use at not more that	Assumes use at not more than 20°C above ambient temperature (unless stated differently).	
Assumes a good basic standard of occupational hygiene is implemented.		
Contributing Scenarios	Risk Management Measures	
General measures (eye	Use suitable eye protection.	
irritants).	Avoid direct eye contact with product, also via contamination	
,	on hands.	
Laboratory activitiesPROC15	No other specific measures identified.	
CleaningPROC10	No other specific measures identified.	
Section 2.2	Control of Environmental Exposure	

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	

Section 3.2 - Environment

No exposure assessment presented for the environment.

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

SECTION 4 GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO

Section 4.1 - Health

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 - Environment

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

Exposure Scenario - Worker

30000000310	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Use in laboratories- Industrial
Use Descriptor	Sector of Use: SU3 Process Categories: PROC10, PROC15 Environmental Release Categories: ERC2, ERC4
Scope of process	Use of the substance within laboratory settings, including material transfers and equipment cleaning.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
Additional Information	No exposure assessment presented for the environment.
Section 2.1	Control of Worker Exposure
Product Characteristics	
Physical form of product	Liquid, vapour pressure 0.5 - 10 kPa at STP
Concentration of the Sub-	Covers percentage substance in the product up to 100%.,
stance in Mixture/Article	Unless stated otherwise.,
Frequency and Duration of	
Other Operational Condition	8 hours (unless stated differently).
-	<u> </u>
Assumes use at not more than 20°C above ambient temperature (unless stated differently).	
Assumes a good basic stand	ard of occupational hygiene is implemented.
Contributing Scenarios	Risk Management Measures
General measures (eye	Use suitable eye protection.
irritants).	Avoid direct eye contact with product, also via contamination
,	on hands.
Laboratory activi-	No other specific measures identified.
tiesPROC15	,
CleaningPROC10	No other specific measures identified.
Section 2.2	Control of Environmental Exposure

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise	
indicated.	

Section 3.2 - Environment

No exposure assessment presented for the environment.

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

SECTION 4 GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO

Section 4.1 - Health

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 - Environment

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

Exposure Scenario - Worker

Expedit Contains Tronton	
30000000306	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	De-icing and anti-icing applications- Professional
Use Descriptor	Sector of Use: SU22 Process Categories: PROC1, PROC2, PROC8a, PROC8b, PROC11 Environmental Release Categories: ERC8d
Scope of process	Ice prevention and de-icing of vehicles, aircraft and other equipment by spraying.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
Additional Information	No exposure assessment presented for the environment.
Section 2.1	Control of Worker Exposure
Product Characteristics	
Physical form of product	Liquid, vapour pressure 0.5 - 10 kPa at STP
Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100%., Unless stated otherwise.,
Frequency and Duration o	f Use
Covers daily exposures up to	o 8 hours (unless stated differently).
Other Operational Condition	
	an 20°C above ambient temperature (unless stated differently).
Assumes a good basic stand	dard of occupational hygiene is implemented.
Contributing Scenarios	Risk Management Measures
General measures (eye	Use suitable eye protection.
irritants).	Avoid direct eye contact with product, also via contamination on hands.
Bulk transfersDedicated facilityPROC8b	Clear transfer lines prior to de-coupling.
Drum/batch transfer- sPROC8b	No other specific measures identified.
Spraying/ fogging by machine applicationPROC11	Ensure operation is undertaken outdoors. Avoid carrying out activities involving exposure for more than 1 hour. Stay upwind/ keep distance from source.
Ad hoc manual application via trigger sprays, dipping, etc.PROC11	Ensure operation is undertaken outdoors. Avoid carrying out activities involving exposure for more than 1 hour. Stay upwind/ keep distance from source.
Equipment cleaning and	No other specific measures identified.

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

maintenancePROC8a	
Storage.PROC1PROC2	Store substance within a closed system.
Section 2.2	Control of Environmental Exposure
No exposure assessment presented for the environment.	

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
The ECETOC TRA tool has be indicated.	peen used to estimate workplace exposures unless otherwise

Section 3.2 - Environment

No exposure assessment presented for the environment.

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	
Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management	
Measures/Operational Condi	tions outlined in Section 2 are implemented.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 -Environment No exposure assessment presented for the environment.

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

Exposure Scenario - Worker

30000000305	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Functional Fluids- Professional
Use Descriptor	Sector of Use: SU22 Process Categories: PROC1, PROC2, PROC3, PROC8a, PROC9, PROC20 Environmental Release Categories: ERC9a, ERC9b
Scope of process	Use as functional fluids e.g. cable oils, transfer oils, coolants, insulators, refrigerants, hydraulic fluids in professional equipment including maintenance and related material transfers.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
Additional Information	No exposure assessment presented for the environment.
Section 2.1	Control of Worker Exposure
Product Characteristics	
Physical form of product	Liquid, vapour pressure 0.5 - 10 kPa at STP
Concentration of the Sub-	Covers percentage substance in the product up to 100%.,
stance in Mixture/Article	Unless stated otherwise.,
Frequency and Duration of	Use
Covers daily exposures up to	8 hours (unless stated differently).
Other Operational Condition	ns affecting Exposure
Assumes use at not more that	an 20°C above ambient temperature (unless stated differently).
Assumes a good basic stand	lard of occupational hygiene is implemented.

Contributing Scenarios Risk Management Measures General measures (eye irri-Use suitable eye protection. Avoid direct eye contact with product, also via contamination tants). on hands. Drum/batch transfersPROC8a No other specific measures identified. Transfer from/pouring from con-No other specific measures identified. tainersPROC9 ManualFilling of arti-Carefully pour from containers. cles/equipmentPROC9 Use of sealed items containing No other specific measures identified. functional fluids e.g. transfer oils, hydraulic fluids, refrigerants.PROC20 General exposures (closed No other specific measures identified. systems)PROC1PROC2PROC3 Remanufacture of reject arti-No other specific measures identified. clesPROC9

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

maintenancePROC8a Storage.PROC1PROC2	Store substance within a closed system.
Section 2.2 Co	ontrol of Environmental Exposure

No exposure assessment presented for the environment.

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
The ECETOC TRA tool has be indicated.	peen used to estimate workplace exposures unless otherwise

Section 3.2 - Environment No exposure assessment presented for the environment.

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	
Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management	
Measures/Operational Conditions outlined in Section 2 are implemented.	
Whore other Dick Me	programment Measures/Operational Conditions are adopted, then upors

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 -Environment
No exposure assessment presented for the environment.

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

Exposure Scenario - Worker

30000000303	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Functional Fluids- Industrial
Use Descriptor	Sector of Use: SU3 Process Categories: PROC1, PROC2, PROC4, PROC8a, PROC9, PROC8b Environmental Release Categories: ERC7
Scope of process	Use as functional fluids e.g. cable oils, transfer oils, coolants, insulators, refrigerants, hydraulic fluids in industrial equipment including maintenance and related material transfers.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Additional Information	No exposure assessment presented for the environment.	
Section 2.1	Control of Worker Exposure	
Product Characteristics		
Physical form of product	Liquid, vapour pressure 0.5 - 10 kPa at STP	
Concentration of the Sub-	Covers percentage substance in the product up to 100%.,	
stance in Mixture/Article	Unless stated otherwise.,	
Frequency and Duration of Use		
Covers daily exposures up to	o 8 hours (unless stated differently).	
Other Operational Condition	ons affecting Exposure	

Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.

Contributing Scenarios	Risk Management Measures
General measures (eye irritants).	Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands.
Bulk transfers(closed systems)PROC1PROC2	Clear transfer lines prior to de-coupling.
Drum/batch transfersDedicated facilityPROC8b	No other specific measures identified.
Filling of arti- cles/equipmentUse of closed filling equip- ment.PROC9	No other specific measures identified.
ManualFilling of articles/equipmentPROC8a	Carefully pour from containers.
Use of sealed items containing functional fluids e.g. transfer oils, hydraulic fluids, refrigerants.PROC2	No other specific measures identified.

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

General exposures (open systems)PROC4	No other specific measures identified.	
Equipment cleaning and maintenancePROC8a	Retain drain downs in sealed storage pending disposal or for subsequent recycle.	
Storage.PROC1PROC2	Store substance within a closed system.	
Section 2.2	Control of Environmental Exposure	
No exposure assessment presented for the environment.		

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

Section 3.2 - Environment

No exposure assessment presented for the environment.

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE
	EXPOSURE SCENARIO
Section 4.1 - Health	

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 - Environment

No exposure assessment presented for the environment.

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Date of last issue: 09.03.2023 Version Revision Date: SDS Number:

2.2 09.10.2024 800001006805 Print Date 16.10.2024

Exposure Scenario - Worker

30000000302	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Use as a fuel- Professional
Use Descriptor	Sector of Use: SU22 Process Categories: PROC1, PROC2, PROC3, PROC8a, PROC8b, PROC16 Environmental Release Categories: ERC9a, ERC9b
Scope of process	Covers the use as a fuel (or fuel additive) and includes activities associated with its transfer, use, equipment maintenance and handling of waste.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Additional Information	No exposure assessment presented for the environment.	
Section 2.1	Control of Worker Exposure	
Product Characteristics		
Physical form of product	Liquid, vapour pressure 0.5 - 10 kPa at S	TP
Concentration of the Substance in Mixture/Article	Covers percentage substance in the proc Unless stated otherwise.,	luct up to 100%.,
Frequency and Duration of Use		
Covers daily exposures up to 8 hours (unless stated differently).		
Other Operational Conditions affecting Exposure		
Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.		

0 1 11 11 0	
Contributing Scenarios	Risk Management Measures
General measures (eye irritants).	Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands.
Bulk transfersDedicated facili-	Transfer via enclosed lines.
tyPROC8b	Clear transfer lines prior to de-coupling.
Drum/batch transfersDedicate facilityPROC8b	ed Avoid spillage when withdrawing pump.
Refueling.Dedicated facili- tyPROC8b	Avoid spillage when withdrawing pump.
Use as a fuel(closed systems)PROC16	No other specific measures identified.
General exposures (closed systems)PROC1PROC2PRO	No other specific measures identified.
Equipment cleaning and maintenancePROC8a	Retain drain downs in sealed storage pending disposal or for subsequent recycle.

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

Storage.PROC1 Store substance within a closed system.

Section 2.2 Control of Environmental Exposure

No exposure assessment presented for the environment.

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise	
indicated.	

Section 3.2 - Environment

No exposure assessment presented for the environment.

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO	
Section 4.1 - Health		
Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management		
Measures/Operational Conditions outlined in Section 2 are implemented.		
Where other Risk Management Measures/Operational Conditions are adopted, then users		
should ensure that risks are managed to at least equivalent levels.		

Section 4.2 - Environment

No exposure assessment presented for the environment.

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

Exposure Scenario - Worker

30000000301	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Use as a fuel- Industrial
Use Descriptor	Sector of Use: SU3 Process Categories: PROC1, PROC2, PROC3, PROC8a, PROC8b, PROC16 Environmental Release Categories: ERC7
Scope of process	Covers the use as a fuel (or fuel additive) and includes activities associated with its transfer, use, equipment maintenance and handling of waste.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Additional Information	No exposure assessment presented for the environment.	
Section 2.1	Control of Worker Exposure	
Product Characteristics		
Physical form of product	Liquid, vapour pressure 0.5 - 10 kPa at STP	
Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100%., Unless stated otherwise.,	
Frequency and Duration of Use		
Covers daily exposures up to 8 hours (unless stated differently).		
Other Operational Conditions affecting Exposure		
Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.		

Contributing Scenarios Risk Management Measures General measures (eye irri-Use suitable eye protection. Avoid direct eye contact with product, also via contamination tants). on hands. Bulk transfersDedicated facili-Transfer via enclosed lines. tyPROC8b Clear transfer lines prior to de-coupling. Drum/batch transfersDedicated Use drum pumps or carefully pour from container. facilityPROC8b General exposures (closed No other specific measures identified. systems)PROC1PROC2PROC3 Use as a fuel(closed sys-No other specific measures identified. tems)PROC16 Equipment cleaning and Drain down system prior to equipment opening or maintemaintenancePROC8a Retain drain downs in sealed storage pending disposal or for subsequent recycle.

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

Storage.PROC1PROC2 Store substance within a closed system.

Section 2.2 Control of Environmental Exposure

No exposure assessment presented for the environment.

SECTION 3 EXPOSURE ESTIMATION

Section 3.1 - Health

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

Section 3.2 - Environment

No exposure assessment presented for the environment.

SECTION 4

GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO

Section 4.1 - Health

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.

Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 - Environment

No exposure assessment presented for the environment.

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

Exposure Scenario - Worker

30000000300	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Use in Agrochemicals uses- Professional
Use Descriptor	Sector of Use: SU22 Process Categories: PROC1, PROC2, PROC4, PROC8a, PROC8b, PROC11, PROC13 Environmental Release Categories: ERC8a, ERC8d
Scope of process	Use as an agrochemical excipient for application by manual or machine spraying, smokes and fogging; including equipment clean-downs and disposal.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
Additional Information	No exposure assessment presented for the environment.
Section 2.1	Control of Worker Exposure
Product Characteristics	
Physical form of product	Liquid, vapour pressure 0.5 - 10 kPa at STP
Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100%., Unless stated otherwise.,
Frequency and Duration o	f Use
Covers daily exposures up t	o 8 hours (unless stated differently).
Other Operational Condition	ons affecting Exposure
Assumes use at not more th	an 20°C above ambient temperature (unless stated differently).

Assumes a good basic standard of occupational hygiene is implemented.

Contributing Scenarios	Risk Management Measures
General measures (eye irritants).	Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands.
Transfer from/pouring from containersPROC8b	No other specific measures identified.
Mixing operations (open systems)PROC4	No other specific measures identified.
Spraying/ fogging by man- ual applicationPROC11	Limit the substance content in the product to 25 %. Avoid carrying out activities involving exposure for more than 4 hours
Spraying/ fogging by machine applicationPROC11	Apply within a vented cab supplied with filtered air under positive pressure and with a protection factor of >20.
Ad hoc manual application via trigger sprays, dipping, etc.PROC13	No other specific measures identified.

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

Equipment cleaning and maintenancePROC8a	Retain drain downs in sealed storage pending disposal or for subsequent recycle.
Storage.PROC1PROC2	Store substance within a closed system.
Section 2.2	Control of Environmental Exposure
No exposure assessment presented for the environment.	

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
The ECETOC TRA tool has indicated.	been used to estimate workplace exposures unless otherwise

Section 3.2 -Environment No exposure assessment presented for the environment.

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO	
Section 4.1 - Health		
Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management		
Measures/Operational Conditions outlined in Section 2 are implemented.		
Where other Risk Management Measures/Operational Conditions are adopted, then users		
should ensure that risks are managed to at least equivalent levels.		

Section 4.2 -Environment	
No exposure assessment presented for the environment.	

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Date of last issue: 09.03.2023 Version Revision Date: SDS Number:

2.2 09.10.2024 800001006805 Print Date 16.10.2024

Exposure Scenario - Worker

Exposure occinario - W	OT ICC
30000000299	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Use as binders and release agents- Professional
Use Descriptor	Sector of Use: SU22 Process Categories: PROC 1, PROC 2, PROC 3, PROC 4, PROC 6, PROC 8a, PROC 8b, PROC 10, PROC 11, PROC 14 Environmental Release Categories: ERC8a, ERC8d
Scope of process	Covers the use as binders and release agents including material transfers, mixing, application by spraying, brushing, and handling of waste.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Additional Information	No exposure assessment presented for the environment.	
Section 2.1	Control of Worker Exposure	
Product Characteristics	Product Characteristics	
Physical form of product	Liquid, vapour pressure 0.5 - 10 kPa at STP	
Concentration of the Sub-	Covers percentage substance in the product up to 100%.,	
stance in Mixture/Article	Unless stated otherwise.,	
Frequency and Duration of Use		
Covers daily exposures up to 8 hours (unless stated differently).		
Other Operational Conditions affecting Exposure		
Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.		

Contributing Scenarios	Risk Management Measures
General measures (eye irritants).	Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands.
Bulk transfers(closed systems)PROC1PROC2PROC3	No other specific measures identified.
Drum/batch transfer- sPROC8aPROC8b	No other specific measures identified.
Mixing operations (open systems)PROC4	No other specific measures identified.
Mixing operations (closed sys tems)PROC3	- No other specific measures identified.
Mold formingPROC14	No other specific measures identified.
Casting operations(open systems)elevated temperature-PROC6	Provide extraction ventilation at points where emissions occur.

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

MachineSprayingPROC11	Carry out in a vented booth or extracted enclosure. Segregate the activity away from other operations.
Roller, spreader, flow applicationPROC10	No other specific measures identified.
ManualSprayingPROC11	Carry out in a vented booth or extracted enclosure. , or: Wear a respirator conforming to EN140 with Type A/P2 filter or better. Segregate the activity away from other operations.
Storage.PROC1PROC2	Store substance within a closed system.

	Section 2.2	Control of Environmental Exposure	
No exposure assessment presented for the environment.			

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise	
indicated.	

Section 3.2 -Environment No exposure assessment presented for the environment.

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 -Environment	
No exposure assessment presented for the environment.	

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Date of last issue: 09.03.2023 Version Revision Date: SDS Number:

2.2 09.10.2024 800001006805 Print Date 16.10.2024

Exposure Scenario - Worker

Exposure occinatio Worker	
30000000298	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Use as binders and release agents- Industrial
Use Descriptor	Sector of Use: SU3 Process Categories: PROC1, PROC2, PROC3, PROC4, PROC6, PROC7, PROC8a, PROC8b, PROC10, PROC13, PROC14 Environmental Release Categories: ERC4
Scope of process	Covers the use as binders and release agents including material transfers, mixing, application (including spraying and brushing), mould forming and casting, and handling of waste.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Additional Information	No exposure assessment presented for the environment.	
Section 2.1	Control of Worker Exposure	
Product Characteristics		
Physical form of product	Liquid, vapour pressure 0.5 - 10 kPa at STP	
Concentration of the Sub-	Covers percentage substance in the product up to 100%.,	
stance in Mixture/Article	Unless stated otherwise.,	
Frequency and Duration of Use		
Covers daily exposures up to	o 8 hours (unless stated differently).	
Other Operational Conditions affecting Exposure		
Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.		

Contributing Scenarios	Risk Management Measures
General measures (eye irritants).	Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands.
Bulk transfers(closed systems)PROC1PROC2PROC3	Clear transfer lines prior to de-coupling.
Drum/batch transfer- sPROC8aPROC8b	No other specific measures identified.
Mixing operations (closed systems)PROC3	No other specific measures identified.
Mixing operations (open systems)PROC4	No other specific measures identified.
Mold formingPROC14	No other specific measures identified.
Casting operations(open systems)elevated temperature- PROC6	Provide extraction ventilation at points where emissions occur.

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

Treatment by dipping and pouringPROC13	No other specific measures identified.
Spraying (automatic/robotic)PROC7	Minimise exposure by partial enclosure of the operation or equipment and provide extract ventilation at openings.
SprayingManualPROC7	Carry out in a vented booth or extracted enclosure.
Equipment cleaning and maintenancePROC8a	No other specific measures identified.
Storage.PROC1PROC2	Store substance within a closed system.

Section 2.2	Control of Environmental Exposure	
No exposure assessment presented for the environment.		

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise	
indicated.	

Section 3.2 - Environment

No exposure assessment presented for the environment.

No exposure assessment presented for the environment.

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 -Environment

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

Exposure Scenario - Worker

30000000297	0000000297	
SECTION 1	EXPOSURE SCENARIO TITLE	
Title	Metal working fluids / rolling oils- Professional	
Use Descriptor	Sector of Use: SU22 Process Categories: PROC1, PROC2, PROC3, PROC5, PROC8a, PROC8b, PROC9, PROC10, PROC11, PROC13, PROC17 Environmental Release Categories: ERC8a, ERC8d	
Scope of process	Covers the use in formulated MWFs including transfer operations, open and contained cutting/machining activities, automated and manual application of corrosion protections, draining and working on contaminated/ reject articles, and disposal of waste oils.	

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Additional Information	No exposure assessment presented for the environment.	
Section 2.1	Control of Worker Exposure	
Product Characteristics		
Physical form of product	Liquid, vapour pressure 0.5 - 10 kPa at STP	
Concentration of the Sub- stance in Mixture/Article	Covers percentage substance in the product up to 100%., Unless stated otherwise.,	
Frequency and Duration of Use		
Covers daily exposures up to	Covers daily exposures up to 8 hours (unless stated differently).	
Other Operational Conditions affecting Exposure		

Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.

Contributing Scenarios	Risk Management Measures

General measures (eye irritants).	Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands.
General exposures (closed systems)PROC1PROC2PROC3	No other specific measures identified.
Bulk transfersDedicated facilityPROC8b	Clear transfer lines prior to de-coupling.
Filling/ preparation of equipment from drums or contain- ers.PROC5PROC8aPROC8bPROC9	No other specific measures identified.
Product sampling.PROC8b	No other specific measures identified.
Metal machining operationsPROC17	Provide extraction ventilation at points where emissions occur.

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

Roller, spreader, flow applicationPROC10	No other specific measures identified.
SprayingPROC11	Carry out in a vented booth or extracted enclosure. , or: Wear a respirator conforming to EN140 with Type A/P2 filter or better.
Treatment by dipping and pouringPROC13	Allow time for product to drain from workpiece. No other specific measures identified.
Equipment cleaning and maintenance-PROC8aPROC8b	Retain drain downs in sealed storage pending disposal or for subsequent recycle. No other specific measures identified.
Storage.PROC1PROC2	Handle substance within a closed system.

Section 2.2	Control of Environmental Exposure	
No exposure assessment presented for the environment.		

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise	
indicated.	

Section 3.2 - Environment

No exposure assessment presented for the environment.

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	
Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management	

Measures/Operational Conditions outlined in Section 2 are implemented.
Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 -Environment No exposure assessment presented for the environment.

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Date of last issue: 09.03.2023 Version Revision Date: SDS Number:

2.2 09.10.2024 800001006805 Print Date 16.10.2024

Exposure Scenario - Worker

Exposure occinato - Worker		
30000000296		
SECTION 1	EXPOSURE SCENARIO TITLE	
Title	Metal working fluids / rolling oils- Industrial	
Use Descriptor	Sector of Use: SU3	
	Process Categories: PROC1, PROC2, PROC3, PROC4,	
	PROC5, PROC7, PROC8a, PROC8b, PROC9, PROC10,	
	PROC13, PROC17	
	Environmental Release Categories: ERC4	
	_	
Scope of process	Covers the use in formulated MWFs/rolling oils including transfer operations, rolling and annealing activities, cutting/machining activities, automated and manual application of corrosion protections (including brushing, dipping and spraying), equipment maintenance, draining and disposal of waste oils.	

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Additional Information	No exposure assessment presented for the environment.	
Section 2.1	Control of Worker Exposure	
Product Characteristics		
Physical form of product	Liquid, vapour pressure 0.5 - 10 kPa at STP	
Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100%., Unless stated otherwise.,	
Frequency and Duration of Use		
Covers daily exposures up to 8 hours (unless stated differently).		
Other Operational Conditions affecting Exposure		
Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.		

Contributing Scenarios	Ris	k Management Measures
General measures (eye irritar	nts).	Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands.
General exposures (closed sy tems)PROC1PROC2PROC3		No other specific measures identified.
General exposures (open systems)PROC4	3-	No other specific measures identified.
Bulk transfersDrum/batch tranfersPROC5PROC8bPROC9	าร-	No other specific measures identified.
Product sampling.PROC8b		No other specific measures identified.
Metal machining operationsPROC17		No other specific measures identified.

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

Treatment by dipping and pour-ingPROC13	No other specific measures identified.
SprayingPROC7	Minimise exposure by partial enclosure of the operation or equipment and provide extract ventilation at openings.
Manual applications e.g. brushing, rollingPROC10	No other specific measures identified.
Automated metal roll- ing/formingelevated tempera- tureUse in contained sys- temsPROC2	No other specific measures identified.
Semi-automated metal roll- ing/formingelevated tempera- turePROC17	Automate activity where possible. No other specific measures identified.
Equipment cleaning and maintenancePROC8aPROC8b	Retain drain downs in sealed storage pending disposal or for subsequent recycle.
Storage.PROC1PROC2	Store substance within a closed system.

Section 2.2	Control of Environmental Exposure
No exposure assessment pre	sented for the environment.

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise	
indicated.	

Section 3.2 -Environment

No exposure assessment presented for the environment.

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 -Environment
No exposure assessment presented for the environment.

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

Exposure Scenario - Worker

30000000295		
SECTION 1	EXPOSURE SCENARIO TITLE	
Title	Lubricants- Professional	
Use Descriptor	Sector of Use: SU22 Process Categories: PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC9, PROC10, PROC11, PROC13, PROC17, PROC18, PROC20 Environmental Release Categories: ERC8a, ERC8d, ERC9a, ERC9b	
Scope of process	Covers the use of formulated lubricants in closed and open systems including transfer operations, operation of engines and similar articles, reworking on reject articles, equipment maintenance and disposal of waste oil.	

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Additional Information	No exposure assessment presented for the environment.	
Section 2.1	Control of Worker Exposure	
Product Characteristics		
Physical form of product	Liquid, vapour pressure 0.5 - 10 kPa at STP	
Concentration of the Substance in Mixture/Article		
Frequency and Duration of Use		
Covers daily exposures up t	Covers daily exposures up to 8 hours (unless stated differently).	
Other Operational Conditions affecting Exposure		
_		

Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.

S .		1 75 1	
Contributing Scenarios	Risk M	anagement Measures	
General measures (eye irritan	ts).	Use suitable eye protection. Avoid direct eye contact with product, also via contami tion on hands.	na-
General exposures (closed systems)PROC1PROC2PROC3	S-	No other specific measures identified.	
Operation of equipment containengine oils and similar.PROC2		No other specific measures identified.	
General exposures (open systems)PROC4		No other specific measures identified.	
Bulk transfersDedicated facilityPROC8b		No other specific measures identified.	
Filling/ preparation of equipme from drums or containers.PROC8aPROC8b	ent	No other specific measures identified.	

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

Operation and lubrication of high energy open equipmentIn-doorPROC17PROC18	Restrict area of openings to equipment.
doorPROC1/PROC18	Provide extraction ventilation at points where emissions occur.
Operation and lubrication of high energy open equipmentOut-doorPROC17PROC18	No other specific measures identified.
Maintenance and machine set upelevated temperaturePROC8b	Provide extract ventilation to emission points when contact with warm (>50 Degrees C) lubricant is likely.
Maintenance of small itemselevated temperatureCovers percentage sub-	Avoid carrying out activities involving exposure for more than 4 hours
stance in the product up to 5%.PROC8a	Retain drain downs in sealed storage pending disposal or for subsequent recycle.
Engine lubricant servicePROC9	No other specific measures identified.
Manual applications e.g. brushing, rollingPROC10	No other specific measures identified.
SprayingPROC11	Minimise exposure by partial enclosure of the operation or equipment and provide extract ventilation at openings. , or:
	Wear a respirator conforming to EN140 with Type A/P2 filter or better.
Treatment by dipping and pour- ingPROC13	Minimise exposure by partial enclosure of the operation or equipment and provide extract ventilation at openings. , or:
	Provide a good standard of controlled ventilation (10 to 15 air changes per hour). Allow time for product to drain from workpiece.
Storage.PROC1PROC2	Store substance within a closed system.

Section 2.2	Control of Environmental Exposure	
No exposure assessment presented for the environment.		

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
The ECETOC TRA tool has b indicated.	een used to estimate workplace exposures unless otherwise

Section 3.2 -Environment	
No exposure assessment presented for the environment.	

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	
Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management	

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

Measures/Operational Conditions outlined in Section 2 are implemented.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

should chould that how are managed to at least equivalent levels.

Section 4.2 - Environment

No exposure assessment presented for the environment.

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

Exposure Scenario - Worker

30000000294		
SECTION 1	EXPOSURE SCENARIO TITLE	
Title	Lubricants- Industrial	
Use Descriptor	Sector of Use: SU3 Process Categories: PROC1, PROC2, PROC3, PROC4, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC17, PROC18 Environmental Release Categories: ERC7, ERC4	
Scope of process	Covers the use of formulated lubricants in closed and open systems including transfer operations, operation of machinery/engines and similar articles, reworking on reject articles, equipment maintenance and disposal of wastes.	

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Additional Information	No exposure assessment presented for the environment.	
Section 2.1	Control of Worker Exposure	
Product Characteristics		
Physical form of product	Liquid, vapour pressure 0.5 - 10 kPa at STP	
Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100%., Unless stated otherwise.,	
Frequency and Duration o	f Use	
Covers daily exposures up to	o 8 hours (unless stated differently).	
Other Operational Condition	ons affecting Exposure	
	an 20°C above ambient temperature (unless stated differently).	

Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.

Contributing Scenarios	Risk Management Measures
General measures (eye irritants).	Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands.
General exposures (closed systems)PROC1PROC2PROC	No other specific measures identified.
General exposures (open systems)PROC4	No other specific measures identified.
Bulk transfersDedicated facilityPROC8b	Clear transfer lines prior to de-coupling.
Filling/ preparation of equipme from drums or containers.PROC8aPROC8b	nt No other specific measures identified.
Initial factory fill of equip- mentPROC9	No other specific measures identified.
Operation and lubrication of	Provide extraction ventilation at points where emissions oc-

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

high energy open equip- mentPROC17PROC18	cur. Restrict area of openings to equipment.
Manual applications e.g. brushing, rollingPROC10	No other specific measures identified.
Treatment by dipping and pour-ingPROC13	No other specific measures identified.
SprayingPROC7	Minimise exposure by partial enclosure of the operation or equipment and provide extract ventilation at openings.
Maintenance (of larger plant items) and machine set up-PROC8b	No other specific measures identified.
Maintenance of small itemsPROC8a	No other specific measures identified.
Storage.PROC1PROC2	Store substance within a closed system.

Section 2.2	Control of Environmental Exposure
No exposure assessment pre	sented for the environment.

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
The ECETOC TRA tool has be indicated.	peen used to estimate workplace exposures unless otherwise

Section 3.2 - Environment

No exposure assessment presented for the environment.

SECTION 4	EXPOSURE SCENARIO
Section 4.1 - Health	
Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.	

Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 -Environment	
No exposure assessment presented for the environment.	

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

Exposure Scenario - Worker

30000000278	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Use in Cleaning Agents- Professional
Use Descriptor	Sector of Use: SU22 Process Categories: PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC10, PROC11, PROC13 Environmental Release Categories: ERC8a, ERC8d
Scope of process	Covers the use as a component of cleaning products including pouring/unloading from drums or containers; and exposures during mixing/diluting in the preparatory phase and cleaning activities (including spraying, brushing, dipping, wiping automated and by hand).

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES		
Additional Information	No exposure assessment presented for the environment.		
Section 2.1	Control of Worker Exposure		
Product Characteristics			
Physical form of product	Liquid, vapour pressure 0.5 - 10 kPa at STP		
Concentration of the Sub-	Covers percentage substance in the product up to 100%.,		
stance in Mixture/Article	Unless stated otherwise.,		
Frequency and Duration o	f Use		
Covers daily exposures up to 8 hours (unless stated differently).			
Other Operational Condition	ons affecting Exposure		
Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.			

Contributing Scenarios	Risk Manage	ement Measures	
General measures (eye irritar	nts).	Use suitable eye protection. Avoid direct eye contact with product, also via cotamination on hands.	on-
Filling/ preparation of equipm drums or containers.PROC8b		No other specific measures identified.	
Automated process with (semi) closed systems.Use in contained systemsPROC2PROC3		No other specific measures identified.	
Semi Automated process. (e. tomatic application of floor ca maintenance products)PROC	re and	No other specific measures identified.	
Filling/ preparation of equipm drums or containers.PROC8a		No other specific measures identified.	
ManualSurfacesCleaningDipp sion and pouringPROC13	oing, immer-	No other specific measures identified.	

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

Cleaning with low-pressure washers-	No other specific measures identified.
Rolling, Brushingno sprayingPROC10	
Cleaning with high pressure washers-	Provide a good standard of controlled ventilation
SprayingIndoorPROC11	(10 to 15 air changes per hour).
Cleaning with high pressure washers-	Limit the substance content in the product to 1 %.
SprayingOutdoorPROC11	, or:
	Avoid carrying out activities involving exposure for
	more than 15 minutes.
Manual Confess Classics Constitute DDCC40	No other constitues and identified
ManualSurfacesCleaningSprayingPROC10	No other specific measures identified.
Ad hoc manual application via trigger	No other specific measures identified.
sprays, dipping, etc.Rolling, Brush-	, , , , , , , , , , , , , , , , , , ,
ingPROC10	
Application of cleaning products in closed	No other specific measures identified.
systemsOutdoorPROC4	·
Cleaning of medical devicesPROC4	No other specific measures identified.
-	
Storage.PROC1	Store substance within a closed system.

Section 2.2	Control of Environmental Exposure
No exposure assessment pre	sented for the environment.

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise	

indicated.

Section 3.2 - Environment

No exposure assessment presented for the environment.

	SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO	
	Section 4.1 - Health		
Ī	Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management		
	Measures/Operational Conditions outlined in Section 2 are implemented.		

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 -Environment	
No exposure assessment presented for the environment	

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

Exposure Scenario - Worker

30000000277	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Use in Cleaning Agents- Industrial
Use Descriptor	Sector of Use: SU3 Process Categories: PROC1, PROC2, PROC3, PROC4, PROC7, PROC8a, PROC8b, PROC10, PROC13 Environmental Release Categories: ERC4
Scope of process	Covers the use as a component of cleaning products including transfer from storage, pouring/unloading from drums or containers. Exposures during mixing/diluting in the preparatory phase and cleaning activities (including spraying, brushing, dipping, wiping, automated and by hand), related equipment cleaning and maintenance.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Additional Information	No exposure assessment presented for the environment.	
Section 2.1	Control of Worker Exposure	
Product Characteristics		
Physical form of product	Liquid, vapour pressure 0.5 - 10 kPa at STP	
Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100%., Unless stated otherwise.,	
Frequency and Duration of	f Use	
Covers daily exposures up to 8 hours (unless stated differently).		
Other Operational Conditi	ons affecting Exposure	
Accumes use at not more th	an 20°C above ambient temperature (unless stated differently)	

Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.

Contributing Scenarios	Risk Management Measures
General measures (eye irritants).	Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands.
Bulk transfersPROC8a	Clear transfer lines prior to de-coupling.
Automated process with (semi) closed systems.Use in contained systemsPROC2	No other specific measures identified.
Application of cleaning products in closed systemsPROC2	No other specific measures identified.
Filling/ preparation of equipment from drums or	No other specific measures identified.

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

containers.PROC8b		
Use in contained batch processesPROC4	No other specific measures identified.	
Degreasing small objects in cleaning stationPROC13	No other specific measures identified.	
Cleaning with low-pressure washersPROC10	No other specific measures identified.	
Cleaning with high pressure washersPROC7	Provide a good standard of controlled ventilation (10 to 15 air changes per hour).	
ManualSurfacesCleaningno sprayingPROC10	No other specific measures identified.	
Storage.PROC1	Store substance within a closed system.	
Section 2.2	Control of Environmental Exposure	
No exposure assessment presented for the environment.		

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
The ECETOC TRA tool has b	peen used to estimate workplace exposures unless otherwise

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

Section 3.2 - Environment

No exposure assessment presented for the environment.

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO	
Section 4.1 - Health		
Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.		

Section 4.2 - Environment

No exposure assessment presented for the environment.

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

Exposure Scenario - Worker

Exposure deciratio - Worker		
30000000276		
SECTION 1	EXPOSURE SCENARIO TITLE	
Title	Uses in Coatings- Professional	
Use Descriptor	Sector of Use: SU22	
	Process Categories: PROC1, PROC2, PROC3, PROC4,	
	PROC5, PROC8a, PROC8b, PROC10, PROC11, PROC13,	
	PROC15, PROC19	
	Environmental Release Categories: ERC8a, ERC8d	
Scope of process	Covers the use in coatings (paints, inks, adhesives, etc) including exposures during use (including materials receipt, storage, preparation and transfer from bulk and semi-bulk, application by spray, roller, brush, spreader by hand or similar methods, and film formation), and equipment cleaning, maintenance and associated laboratory activities.	

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
Additional Information	No exposure assessment presented for the environment.
Section 2.1	Control of Worker Exposure
Product Characteristics	
Physical form of product	Liquid, vapour pressure 0.5 - 10 kPa at STP
Concentration of the Substance in Mixture/Article Covers percentage substance in the product up to 100%., Unless stated otherwise.,	
Frequency and Duration o	f Use
Covers daily exposures up to 8 hours (unless stated differently).	
Other Operational Condition	ons affecting Exposure
	nan 20°C above ambient temperature (unless stated differently).

Assumes a good basic standard of occupational hygiene is implemented.

Contributing Scenarios	Risk	Management Measures	
General measures (eye irritar	nts).	Use suitable eye protection. Avoid direct eye contact with product, also via contaminati on hands.	ion
General exposures (closed sy tems)PROC1PROC2PROC3		No other specific measures identified.	
Filling/ preparation of equipment from drums or containers.Use contained systemsPROC2		No other specific measures identified.	
General exposures (open systems)PROC4	;-	No other specific measures identified.	
Preparation of material for ap cationUse in contained batch processesPROC3	•	No other specific measures identified.	

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

Coation 2.2	Control of Environmental Expenses
Hand application - fingerpaints pastels, adhesives PROC19	No other specific measures identified.
Laboratory activitiesPROC15	No other specific measures identified.
Dipping, immersion and pouringPROC13	No other specific measures identified.
ManualSprayingOutdoorPRO0	Wear a respirator conforming to EN140 with Type A filter or better.
ManualSprayingIndoorPROC1	1 Carry out in a vented booth or extracted enclosure.
Roller, spreader, flow applicationPROC10	No other specific measures identified.
Material transfersDrum/batch transfersPROC8aPROC8b	No other specific measures identified.
Preparation of material for app cationIndoorPROC5	li- No other specific measures identified.
Film formation - air dryingln-doorPROC4	No other specific measures identified.
Film formation - air dry- ingOutdoorPROC4	No other specific measures identified.

Section 2.2	Control of Environmental Exposure	
No exposure assessment presented for the environment.		

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise	

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

Section 3.2 -Environment No exposure assessment presented for the environment.

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE
	EXPOSURE SCENARIO
Section 4.1 - Health	
Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management	
Measures/Operational Conditions outlined in Section 2 are implemented.	
Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.	

Section 4.2 -Environment
No exposure assessment presented for the environment.

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

Exposure Scenario - Worker

30000000275	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Uses in Coatings- Industrial
Use Descriptor	Sector of Use: SU3 Process Categories: PROC1, PROC2, PROC3, PROC4, PROC5, PROC7, PROC8a, PROC8b, PROC10, PROC13, PROC15 Environmental Release Categories: ERC4
Scope of process	Covers the use in coatings (paints, inks, adhesives, etc) including exposures during use (including materials receipt, storage, preparation and transfer from bulk and semi-bulk, application by spray, roller, spreader, dip, flow, fluidised bed on production lines and film formation) and equipment cleaning, maintenance and associated laboratory activities.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Additional Information	No exposure assessment presented for the environment.	
Section 2.1	Control of Worker Exposure	
Product Characteristics		
Physical form of product	Liquid, vapour pressure 0.5 - 10 kPa at STP	
Concentration of the Sub-	Covers percentage substance in the product up to 100%.,	
stance in Mixture/Article	Unless stated otherwise.,	
Frequency and Duration of Use		
Covers daily exposures up to 8 hours (unless stated differently).		
Other Operational Conditions affecting Exposure		
Assumes use at not more than 20°C above ambient temperature (unless stated differently).		

Assumes a good basic standard of occupational hygiene is implemented.

Contributing Scenarios	Risk Management Measures	
General measures (eye irritar	ts). Use suitable eye protection. Avoid direct eye contact with product, also via contamition on hands.	na-
General exposures (closed sy tems)PROC1PROC2	No other specific measures identified.	
General exposures (open systems)PROC4	No other specific measures identified.	
Film formation - force drying, ing and other technologies. Us contained systems PROC2	· ·	
Mixing operations (closed systems)General exposures (closystems)PROC3		

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

Film formation - air dryingPROC4	No other specific measures identified.
Preparation of material for applicationMixing operations (open systems)PROC5	No other specific measures identified.
Spraying (automatic/robotic)PROC7	Carry out in a vented booth or extracted enclosure.
ManualSprayingPROC7	Provide a good standard of controlled ventilation (10 to 15 air changes per hour).
Roller, spreader, flow applicationPROC10	No other specific measures identified.
Dipping, immersion and pouringPROC13	No other specific measures identified.
Laboratory activitiesPROC15	No other specific measures identified.
Material transfersDrum/batch transfersTransfer from/pouring from containersPROC8aPROC8bPROC9	No other specific measures identified.
Production or preparation or articles by tabletting, compression, extrusion or pelletisationPROC14	No other specific measures identified.

Section 2.2	Control of Environmental Exposure	
No exposure assessment presented for the environment.		

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise	

indicated.

Section 3.2 - Environment

No exposure assessment presented for the environment.

	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	
Predicted exposures are not expected to exceed the DN(M)FL when the Risk Management	

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users

should ensure that risks are managed to at least equivalent levels.

Section 4.2 -Environment	
No exposure assessment presented for the environment.	

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

Exposure Scenario - Worker

30000000274	30000000274	
SECTION 1	EXPOSURE SCENARIO TITLE	
Title	Formulation & (re)packing of substances and mixtures- Industrial	
Use Descriptor	Sector of Use: SU3, SU10 Process Categories: PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9, PROC14, PROC15 Environmental Release Categories: ERC2	
Scope of process	Formulation, packing and re-packing of the substance and its mixtures in batch or continuous operations, including storage, materials transfers, mixing, tabletting, compression, pelletisation, extrusion, large and small scale packing, sampling, maintenance and associated laboratory activities.	

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Additional Information	No exposure assessment presented for the environment.	
Section 2.1	Control of Worker Exposure	
Product Characteristics		
Physical form of product	Liquid, vapour pressure 0.5 - 10 kPa at STP	
Concentration of the Sub-	tration of the Sub- Covers percentage substance in the product up to 100%.,	
stance in Mixture/Article	Unless stated otherwise.,	
Frequency and Duration of Use		
Covers daily exposures up to	o 8 hours (unless stated differently).	
Other Operational Conditions affecting Exposure		

Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.

Contributing Scenarios F	Risk Management Measures
General measures (eye irritants).	Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands.
General exposures (closed systems)PROC1PROC2PROC3	No other specific measures identified. 3
General exposures (open systems)PROC4	No other specific measures identified.
Batch processes at elevated temperaturesPROC3	No other specific measures identified.
Process samplingPROC3	No other specific measures identified.
Laboratory activitiesPROC15	No other specific measures identified.
Bulk transfersPROC8b	No other specific measures identified.

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

Storage.PROC2	Store substance within a closed system.
Equipment cleaning and maintenancePROC8a	Drain down system prior to equipment opening or maintenance. Retain drain downs in sealed storage pending disposal or for subsequent recycle.
Drum and small package fill-ingPROC9	No other specific measures identified.
articles by tabletting, compression, extrusion or pelletisationPROC14	·
Production or preparation or	No other specific measures identified.
Drum/batch transfersPROC8k	No other specific measures identified.
ManualTransfer from/pouring from containersPROC8a	No other specific measures identified.
Mixing operations (open systems)PROC5	No other specific measures identified.

Section 2.2	Control of Environmental Exposure	
No exposure assessment pre	sented for the environment.	

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise	
indicated.	

-		

Section 3.2 - Environment
No exposure assessment presented for the environment.

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	
Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management	
Measures/Operational Conditions outlined in Section 2 are implemented.	
Where other Risk Management Measures/Operational Conditions are adopted, then users	
should ensure that risks are managed to at least equivalent levels.	

Section 4.2 -Environment	
	No exposure assessment presented for the environment.

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

Exposure Scenario - Worker

30000000273	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Distribution of substance- Industrial
Use Descriptor	Sector of Use: SU3, SU8, SU9 Process Categories: PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC9, PROC15 Environmental Release Categories: ERC1, ERC2, ERC3, ERC4, ERC5, ERC6a, ERC7
Scope of process	Loading (including marine vessel/barge, rail/road car and IBC loading) and repacking (including drums and small packs) of substance, including its sampling, storage, unloading distribution and associated laboratory activities.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Additional Information	No exposure assessment presented for the environment.	
Section 2.1	Control of Worker Exposure	
Product Characteristics		
Physical form of product	Liquid, vapour pressure 0.5 - 10 kPa at STP	
Concentration of the Sub-	Covers percentage substance in the product up to 100%.,	
stance in Mixture/Article	Unless stated otherwise.,	
Frequency and Duration of	of Use	
Covers daily exposures up t	to 8 hours (unless stated differently).	
Other Operational Conditi	ons affecting Exposure	
Assumes use at not more th	nan 20°C above ambient temperature (unless stated differently)	

Assumes use at not more than 20°C above ambient temperature (unless stated differently).

Assumes a good basic standard of occupational hygiene is implemented.

Contributing Scenarios	Risk Management Measures
General measures (eye irritants).	Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands.
General exposures (closed systems)PROC1PROC2PROC	No other specific measures identified.
General exposures (open systems)PROC4	No other specific measures identified.
Process samplingPROC3	No other specific measures identified.
Laboratory activitiesPROC15	No other specific measures identified.
Bulk transfers(open systems)PROC8b	No other specific measures identified.
Bulk transfers(closed systems)PROC8b	No other specific measures identified.

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

Drum and small package fill-ingPROC9	No other specific measures identified.
Equipment cleaning and maintenancePROC8a	Drain down system prior to equipment opening or maintenance. Retain drain downs in sealed storage pending disposal or for subsequent recycle.
Storage.PROC2	Store substance within a closed system.

Section 2.2	Control of Environmental Exposure	
No exposure assessment presented for the environment.		

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
The ECETOC TRA tool has be indicated.	een used to estimate workplace exposures unless otherwise

Section 3.2 -Environment

No exposure assessment presented for the environment.

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	
Prodicted exposures are not exposted to exceed the DN/M/EL when the Rick Management	

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 - Environment

No exposure assessment presented for the environment.

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

Exposure Scenario - Worker

30000000272	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Use as an intermediate- Industrial
Use Descriptor	Sector of Use: SU3, SU8, SU9 Process Categories: PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC15 Environmental Release Categories: ERC6a
Scope of process	Use of substance as an intermediate (not related to Strictly Controlled Conditions). Includes recycling/ recovery, material transfers, storage, sampling, associated laboratory activities, maintenance and loading (including marine vessel/barge, road/rail car and bulk container).

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Additional Information	No exposure assessment presented for the environment.	
Section 2.1	Control of Worker Exposure	
Product Characteristics		
Physical form of product	Liquid, vapour pressure 0.5 - 10 kPa at STP	
Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100%., Unless stated otherwise.,	
Frequency and Duration o	f Use	
Covers daily exposures up t	o 8 hours (unless stated differently).	
Other Operational Condition	ons affecting Exposure	
	an 20°C above ambient temperature (unless stated differently).	

Assumes a good basic standard of occupational hygiene is implemented.

Contributing Scenarios R	sk Management Measures
General measures (eye irritants).	Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands.
General exposures (closed systems)PROC1PROC2PROC3	No other specific measures identified.
General exposures (open systems)PROC4	No other specific measures identified.
Process samplingPROC8a	No other specific measures identified.
Laboratory activitiesPROC15	No other specific measures identified.
Bulk transfers(open systems)PROC8b	No other specific measures identified.
Bulk transfers(closed systems)PROC8b	No other specific measures identified.

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

Equipment cleaning and maintenancePROC8a	Drain down system prior to equipment opening or maintenance. Retain drain downs in sealed storage pending disposal or for subsequent recycle.	
Storage.	Store substance within a closed system.	
Section 2.2	Control of Environmental Exposure	
No exposure assessment pres	ented for the environment.	

SECTION 3	EXPOSURE ESTIMATION	
Section 3.1 - Health		
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise		
indicated		

indicated.

Section 3.2 -Environment

No exposure assessment presented for the environment.

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 -Environment

No exposure assessment presented for the environment.

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

Exposure Scenario - Worker

30000000271		
SECTION 1	EXPOSURE SCENARIO TITLE	
Title	Manufacture of substance- Industrial	
Use Descriptor	Sector of Use: SU3, SU8, SU9 Process Categories: PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC15 Environmental Release Categories: ERC1, ERC4	
Scope of process	Manufacture of the substance or use as a process chemical or extraction agent. Includes recycling/ recovery, material transfers, storage, maintenance and loading (including marine vessel/barge, road/rail car and bulk container), sampling and associated laboratory activities.	

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
Additional Information	No exposure assessment presented for the environment.
Section 2.1	Control of Worker Exposure
Product Characteristics	
Physical form of product	Liquid, vapour pressure 0.5 - 10 kPa at STP
Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100%., Unless stated otherwise.,
Frequency and Duration o	f Use
Covers daily exposures up t	o 8 hours (unless stated differently).
Other Operational Condition	ons affecting Exposure
	an 20°C above ambient temperature (unless stated differently).

Assumes a good basic standard of occupational hygiene is implemented.

Contributing Scenarios R	sk Management Measures
General measures (eye irritants).	Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands.
General exposures (closed systems)PROC1PROC2PROC3	No other specific measures identified.
General exposures (open systems)PROC4	No other specific measures identified.
Process samplingPROC8b	No other specific measures identified.
Laboratory activitiesPROC15	No other specific measures identified.
Bulk transfers(open systems)PROC8b	No other specific measures identified.
Bulk transfers(closed systems)PROC8b	No other specific measures identified.

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

Equipment cleaning and maintenancePROC8a	Drain down system prior to equipment opening or maintenance. Retain drain downs in sealed storage pending disposal or for subsequent recycle.
Storage.PROC2	Store substance within a closed system.
Section 2.2	Control of Environmental Exposure
No exposure assessment pre	esented for the environment.

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise	

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

Section 3.2 - Environment

No exposure assessment presented for the environment.

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 -Environment

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

Exposure Scenario - Consumer

30000001013	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Use in coatings - Consumer
Use Descriptor	Sector of Use: SU21 Product Categories: PC1, PC4, PC8 (excipient only), PC9a, PC9b, PC9c, PC15, PC18, PC23, PC31, PC34 Environmental Release Categories: ERC8a, ERC8d
Scope of process	Covers the use in coatings (paints, inks, adhesives, etc) including exposures during use (including product transfer and preparation, application by brush, spray by hand or similar methods) and equipment cleaning.

OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES		ND RISK MANAGEMENT
Additional Information	No exposure assessment presente	ed for the environment.
Section 2.1	Control of Consumer Exposure	
Product Characteristics	•	
Physical form of product	Liquid, vapour pressure > 10 Pa at	STP
Concentration of the Substance in Mixture/Article	Unless stated otherwise.	
	Covers concentration up to (%): 10	00 %
Amounts Used		
Unless stated otherwise.		
for each use event, covers amount up to (g): 13.800		13.800
covers skin contact area (cm2): 857,5		857,5
Frequency and Duration o	f Use	
Unless stated otherwise.		
covers use up to (times/day	of use):	1
Exposure (hours/event): 6		6
Other Operational Condition	ons affecting Exposure	
Unless stated otherwise	_	_

Unless stated otherwise.

Covers use at ambient temperatures.

Covers use in room size of 20m3

Product Categories	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
Adhesives, sealants Glues, hobby use.	Covers concentrations up to 50 %
	covers use up to 365 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 35,73 cm2
	For each use event, covers amount up to 9 g
	Covers use in room size of 20 m3

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

	for each use event Covers exposure up to 4 hours/event
Adhesives, sealants Glues	Covers concentrations up to 50 %
DIY-use (carpet glue, tile	Service concentrations up to 60 %
glue, wood parquet glue).	
gido, wood parquet gido).	covers use up to 1 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 110,00 cm2
	For each use event, covers amount up to 6.390 g
	Covers use in room size of 20 m3
	for each use event Covers exposure up to 6,00 hours/event
Adhesives, sealants Glue	Covers concentrations up to 50 %
from spray.	
	covers use up to 6 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 35,73 cm2
	For each use event, covers amount up to 85,05 g
	Covers use in room size of 20 m3
	for each use event Covers exposure up to 4,00 hours/event
Adhesives, sealants Sealants.	Covers concentrations up to 50 %
	covers use up to 365 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 35,73 cm2
	For each use event, covers amount up to 75 g
	Covers use in room size of 20 m3
	for each use event Covers exposure up to 1,00 hours/event
Anti-Freeze and de-icing products Washing car win-	Covers concentrations up to 50 %
dow.	covers use up to 265 day/year
	covers use up to 365 day/year
	covers use up to 1 times/day of use
	For each use event, covers amount up to 0,5 g
	Covers use in a one car garage (34 m3) under typical ventilation.
	Covers use in room size of 34 m3
	for each use event Covers exposure up to 0,02 hours/event
Anti-Freeze and de-icing products Pouring into radiator.	Covers concentrations up to 50 %
	covers use up to 365 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 428,00 cm2
	For each use event, covers amount up to 2.000 g
	Covers use in a one car garage (34 m3) under typical ventila-
	tion.
	Covers use in room size of 34 m3
	for each use event Covers exposure up to 0,17 hours/event
Anti-Freeze and de-icing	Covers concentrations up to 50 %
products Lock de-icer.	Ouvers concentrations up to 30 /0
products Lock de-icer.	covers use up to 365 day/year
	covers use up to 365 day/year
	covers use up to 1 times/day of use

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

	covers skin contact area up to (cm2): 214,40 cm2
	For each use event, covers amount up to 4 g
	Covers use in a one car garage (34 m3) under typical ventilation.
	Covers use in room size of 34 m3
	for each use event Covers exposure up to 0,25 hours/event
Biocidal products (e.g. Dis- infectants, pest control) (excipient only). Laundry and dish washing products.	Covers concentrations up to 50 %
	covers use up to 365 day/year
	Covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 857,50 cm2
	For each use event, covers amount up to 15 g
	Covers use in room size of 20 m3
	for each use event Covers exposure up to 0,50 hours/event
Biocidal products (e.g. Dis- infectants, pest control) (excipient only). Cleaners, liquids (all purpose clean- ers, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners).	Covers concentrations up to 50 %
	covers use up to 128 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 857,50 cm2
	For each use event, covers amount up to 27 g
	Covers use in room size of 20 m3
	for each use event Covers exposure up to 0,33 hours/event
Biocidal products (e.g. Dis- infectants, pest control) (excipient only). Cleaners, trigger sprays (all purpose cleaners,sanitary products, glass cleaners).	Covers concentrations up to 50 %
	covers use up to 128 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 428,00 cm2
	For each use event, covers amount up to 35 g
	Covers use in room size of 20 m3
	for each use event Covers exposure up to 0,17 hours/event
Coatings and paints, thin- ners, paint removers Sol- vent rich, high solid, water borne paint.	Covers concentrations up to 27,5 %
	covers use up to 6 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 428,75 cm2
	For each use event, covers amount up to 744 g
	Covers use in room size of 20 m3

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

	for each use event Covers exposure up to 2,20 hours/event
Coatings and paints, thin-	Covers concentrations up to 50 %
ners, paint removers Aero-	
sol spray can.	
	covers use up to 2 day/year
	covers use up to 1 times/day of use
	For each use event, covers amount up to 215 g
	Covers use in a one car garage (34 m3) under typical ventila-
	tion.
	Covers use in room size of 34 m3
	for each use event Covers exposure up to 0,33 hours/event
Coatings and paints, thin-	Covers concentrations up to 50 %
ners, paint removers Re-	'
movers (paint-, glue-, wall	
paper-, sealant-remover).	
	covers use up to 3 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 857,50 cm2
	for each use event, covers amount up to (g): 491 g
	Covers use in room size of 20 m3
	for each use event Covers exposure up to 2,00 hours/event
Fillers, Putties Fillers and	Covers concentrations up to 50 %
putty.	·
	covers use up to 12 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 35,73 cm2
	For each use event, covers amount up to 85 g
	Covers use in room size of 20 m3
	for each use event Covers exposure up to 4,00 hours/event
Fillers, Putties Plasters and	Covers concentrations up to 2 %
floor equalizers.	·
	covers use up to 12 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 857,50 cm2
	For each use event, covers amount up to 13.800 g
	Covers use in room size of 20 m3
	for each use event Covers exposure up to 2,00 hours/event
Fillers, Putties Modelling clay.	Covers concentrations up to 10 %
•	covers use up to 365 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 254,40 cm2
	For each use event, assumes swallowed amount of 1 g
	Covers use in room size of 20 m3
Finger paints	Covers concentrations up to 15 %
·	covers use up to 365 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 254,40 cm2
	For each use event, assumes swallowed amount of 1,35 g Covers use in room size of 20 m3

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

ment products Solvent rich,	
high solid, water borne paint.	
panti	covers use up to 6 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 428,75 cm2
	For each use event, covers amount up to 744 g
	Covers use in room size of 20 m3
	for each use event Covers exposure up to 2,20 hours/event
Non-metal-surface treat-	Covers concentrations up to 50 %
ment products Aerosol	
spray can.	according to 2 day/year
	covers use up to 2 day/year
	covers use up to 1 times/day of use
	For each use event, covers amount up to 215 g
	Covers use in a one car garage (34 m3) under typical ventilation.
	Covers use in room size of 34 m3
	for each use event Covers exposure up to 0,33 hours/event
Non-metal-surface treat-	Covers concentrations up to 50 %
ment products Removers	·
(paint-, glue-, wall paper-,	
sealant-remover).	
	covers use up to 3 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 857,50 cm2
	For each use event, covers amount up to 491 g
	Covers use in room size of 20 m3
	for each use event Covers exposure up to 2,00 hours/event
Ink and toners Inks and toners.	Covers concentrations up to 50 %
	covers use up to 365 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 71,40 cm2
	For each use event, covers amount up to 40 g
	Covers use in room size of 20 m3
	for each use event Covers exposure up to 2,20 hours/event
Leather tanning, dye, finishing, impregnation and care products Polishes, wax /	Covers concentrations up to 50 %
cream (floor, furniture, shoes).	
011000j.	covers use up to 29 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 430,00 cm2
	For each use event, covers amount up to 56 g
	Covers use in room size of 20 m3
	for each use event Covers exposure up to 1,23 hours/event
Leather tanning, dye, finish-	Covers concentrations up to 50 %
ing, impregnation and care	
products Polishes, spray	

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

(furniture, shoes).	
(1.00.00.00.00.00.00.00.00.00.00.00.00.00	covers use up to 8 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 430,00 cm2
	for each use event, covers amount up to (g): 56 g
	Covers use in room size of 20 m3
	for each use event Covers exposure up to 0,33 hours/event
Lubricants, greases, re-	Covers concentrations up to 100 %
lease products Liquids.	γ
	covers use up to 4 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 468,00 cm2
	For each use event, covers amount up to 2.200 g
	Covers use in a one car garage (34 m3) under typical ventila-
	tion.
	Covers use in room size of 34 m3
	for each use event Covers exposure up to 0,17 hours/event
Lubricants, greases, re-	Covers concentrations up to 20 %
lease products Pastes.	·
•	covers use up to 10 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 468,00 cm2
	For each use event, covers amount up to 34 g
	Covers use in room size of 20 m3
Lubricants, greases, re-	Covers concentrations up to 50 %
lease products Sprays.	·
	covers use up to 6 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 428,75 cm2
	For each use event, covers amount up to 73 g
	Covers use in room size of 20 m3
	for each use event Covers exposure up to 0,17 hours/event
Polishes and wax blends Polishes, wax / cream (floor, furniture, shoes).	Covers concentrations up to 50 %
(11001, Turniture, Silves).	covers use up to 20 day/year
	covers use up to 29 day/year covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 430,00 cm2
	For each use event, covers amount up to 142 g
	Covers use in room size of 20 m3
	for each use event Covers exposure up to 1,23 hours/event
Polishes and wax blends	Covers concentrations up to 50 %
Polishes, spray (furniture, shoes).	, in the second
	covers use up to 8 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 430,00 cm2
	For each use event, covers amount up to 35 g
	Covers use in room size of 20 m3
	for each use event Covers exposure up to 0,33 hours/event
Textile dyes, finishing and	Covers concentrations up to 10 %

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

impregnating products; including bleaches and other processing aids	
	covers use up to 365 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 857,50 cm2
	For each use event, covers amount up to 115 g
	Covers use in room size of 20 m3
	for each use event Covers exposure up to 1,00 hours/event

Section 2.2	Control of Environmental Exposure	
No exposure assessment pre	sented for the environment.	

	SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health The ECETOC TRA tool has been used to estimate consumer exposures unless othe indicated.		
		een used to estimate consumer exposures unless otherwise

Section 3.2 - Environment

No exposure assessment presented for the environment.

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE
	EXPOSURE SCENARIO
Section 4.1 - Health	

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 -Environment	
No exposure assessment presented for the environment	

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

Exposure Scenario - Consumer

30000001015	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Use in Cleaning Agents - Consumer
Use Descriptor	Sector of Use: SU21 Product Categories: PC3, PC4, PC8 (excipient only), PC9a, PC24, PC35, PC38 Environmental Release Categories: ERC8a, ERC8d
Scope of process	Covers general exposures to consumers arising from the use of household products sold as washing and cleaning products, aerosols, coatings, de-icers, lubricants and air care products.

SECTION 2	OPERATIONAL CONDITIONS AND RI MEASURES	SK MANAGEMENT	
Additional Information	No exposure assessment presented for	the environment.	
Section 2.1	Control of Consumer Exposure		
Product Characteristics			
Physical form of product	Liquid, vapour pressure > 10 Pa at STP		
Concentration of the Substance in Mixture/Article	Unless stated otherwise.		
	Covers concentration up to (%): 100 %		
Amounts Used			
Unless stated otherwise.			
for each use event, covers amount up to (g): 13.800		13.800	
covers skin contact area (cm2):		857,5	
Frequency and Duration of Use			
Unless stated otherwise.	Unless stated otherwise.		
covers use up to (times/day of use):		1	
Exposure (hours/event): 4		4	
Other Operational Condition	Other Operational Conditions affecting Exposure		
Unless stated otherwise.			

Covers use at ambient temperatures.

Covers use in room size of 20m3

Product Categories	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
Air care products Air care, instant action (aerosol sprays).	Covers concentrations up to 50 %
	covers use up to 365 day/year
	covers use up to 4 times/day of use
	for each use event, covers amount up to (g): 0,1 g
	Covers use in room size of 20 m3

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

	for each use event Covers exposure up to 0,25 hours/event
Air care products Air care,	Covers use under typical household ventilation.
continuous action (solid and	урган на постана на по
liquid).	
	Covers concentrations up to 100 %
	covers use up to 365 day/year
	covers use up to 2 times/day of use
	covers skin contact area up to (cm2): 35,70 cm2
	For each use event, covers amount up to 12 g
	Covers use in room size of 20 m3
	for each use event Covers exposure up to 12 hours/event
Anti-Freeze and de-icing	Covers concentrations up to 50 %
products Washing car window.	Covers concentrations up to 30 %
dow.	covers use up to 365 day/year
	covers use up to 1 times/day of use
	For each use event, covers amount up to 0,5 g
	Covers use in a one car garage (34 m3) under typical ventila-
	tion.
	Covers use in room size of 34 m3
	for each use event Covers exposure up to 0,02 hours/event
Anti-Freeze and de-icing	Covers concentrations up to 50 %
products Pouring into radiator.	Covers concentrations up to 50 %
	covers use up to 365 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 428,00 cm2
	For each use event, covers amount up to 2.000 g
	Covers use in a one car garage (34 m3) under typical ventila-
	tion.
	Covers use in room size of 34 m3
	for each use event Covers exposure up to 0,17 hours/event
Anti-Freeze and de-icing products Lock de-icer.	Covers concentrations up to 50 %
products book de loci.	covers use up to 365 day/year
	covers use up to 1 times/day of use
	covers use up to 1 times/day of use covers skin contact area up to (cm2): 214,40 cm2
	For each use event, covers amount up to 4 g
	Covers use in a one car garage (34 m3) under typical ventila-
	tion.
	Covers use in room size of 34 m3
Pionidal products (a a Dia	for each use event Covers exposure up to 0,25 hours/event Covers concentrations up to 50 %
Biocidal products (e.g. Dis- infectants, pest control) (excipient only). Laundry	Covers concentrations up to 50 %
and dish washing products.	povers use up to 265 day/yeer
	covers use up to 365 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 857,50 cm2
	For each use event, covers amount up to 15 g
	Covers use in room size of 20 m3

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

	for each use event Covers expenses up to 0.50 hours/event
Dissidal products (s. p.:-	for each use event Covers exposure up to 0,50 hours/event
Biocidal products (e.g. Dis-	Covers concentrations up to 50 %
infectants, pest control)	
(excipient only). Cleaners,	
liquids (all purpose clean-	
ers, sanitary products, floor	
cleaners, glass cleaners, carpet cleaners, metal	
cleaners).	
cleariers).	covers use up to 128 day/year
	covers use up to 125 day/year covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 857,50 cm2
	For each use event, covers amount up to 27 g
	Covers use in room size of 20 m3
Piocidal products (a.e. Die	for each use event Covers exposure up to 0,33 hours/event
Biocidal products (e.g. Dis- infectants, pest control)	Covers concentrations up to 50 %
(excipient only). Cleaners,	
trigger sprays (all purpose	
cleaners, sanitary products,	
glass cleaners).	
glass cleariers).	covers use up to 128 day/year
	covers use up to 125 day/year
	covers skin contact area up to (cm2): 428,00 cm2
	For each use event, covers amount up to 35 g
	Covers use in room size of 20 m3
	for each use event Covers exposure up to 0,17 hours/event
Coatings and paints, thin-	Covers concentrations up to 50 %
ners, paint removers Wa-	Covers concentrations up to 30 %
terborne latex wall paint.	
terserrie latex wan panta	covers use up to 4 day/year
	Covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 428,75 cm2
	For each use event, covers amount up to 2.760 g
	Covers use in room size of 20 m3
	for each use event Covers exposure up to 2,20 hours/event
Coatings and paints, thin-	Covers concentrations up to 27,5 %
ners, paint removers Sol-	201010 0011001111 attion 3 ap to 21,0 /0
vent rich, high solid, water	
borne paint.	
	covers use up to 6 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 428,75 cm2
	For each use event, covers amount up to 744 g
	Covers use in room size of 20 m3
	for each use event Covers exposure up to 2,20 hours/event
Coatings and paints, thin-	Covers concentrations up to 50 %
ners, paint removers Aero-	OUTUS CONCONTINUIONS UP to 30 /0
sol spray can.	
oc. opiay our.	covers use up to 2 day/year
	covers use up to 1 times/day of use
	1 00 voto abo ap to 1 timos/day of abo

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

	For each use event covers amount up to 215 a
	For each use event, covers amount up to 215 g
	Covers use in a one car garage (34 m3) under typical ventilation.
	Covers use in room size of 34 m3
	for each use event Covers exposure up to 0,33 hours/event
Coatings and paints, thin-	Covers concentrations up to 50 %
ners, paint removers Re-	
movers (paint-, glue-, wall	
paper-, sealant-remover).	and the contract of the contra
	covers use up to 3 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 857,50 cm2
	For each use event, covers amount up to 491 g
	Covers use in room size of 20 m3
	for each use event Covers exposure up to 2,00 hours/event
Lubricants, greases, re-	Covers concentrations up to 100 %
lease products Liquids.	
	covers use up to 4 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 468,00 cm2
	For each use event, covers amount up to 2.200 g
	Covers use in a one car garage (34 m3) under typical ventila-
	tion.
	Covers use in room size of 34 m3
	for each use event Covers exposure up to 0,17 hours/event
Lubricants, greases, re-	Covers concentrations up to 20 %
lease products Pastes.	
	covers use up to 10 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 468,00 cm2
	For each use event, covers amount up to 34 g
	Covers use in room size of 20 m3
Lubricants, greases, re-	Covers concentrations up to 50 %
lease products Sprays.	·
	covers use up to 6 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 428,75 cm2
	For each use event, covers amount up to 73 g
	Covers use in room size of 20 m3
	for each use event Covers exposure up to 0,17 hours/event
Washing and cleaning	Covers concentrations up to 70 %
products (including solvent	COTOLO CONCONTIGUIONO AP 10 10 /0
based products) Laundry	
and dish washing products.	
and dion washing products.	covers use up to 365 day/year
	Covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 857,50 cm2
	For each use event, covers amount up to 15 g
	Covers use in room size of 20 m3
Machine and describe	for each use event Covers exposure up to 0,50 hours/event
Washing and cleaning	Covers concentrations up to 70 %

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09.03.2023

 2.2
 09.10.2024
 800001006805
 Print Date 16.10.2024

products (including solvent based products) Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners). covers use up to 128 day/year covers use up to 1 times/day of use covers skin contact area up to (cm2): 857,50 cm2 For each use event, covers amount up to 27 g Covers use in room size of 20 m3 for each use event Covers exposure up to 0,33 hours/event Washing and cleaning Covers concentrations up to 70 % products (including solvent based products) Cleaners, trigger sprays (all purpose cleaners, sanitary products, glass cleaners). covers use up to 128 day/year covers use up to 1 times/day of use covers skin contact area up to (cm2): 428,00 cm2 For each use event, covers amount up to 35 g Covers use in room size of 20 m3 for each use event Covers exposure up to 0,17 hours/event Welding and soldering Covers concentrations up to 50 % products (with flux coatings or flux cores.), flux products covers use up to 365 day/year covers use up to 1 times/day of use For each use event, covers amount up to 12 g Covers use in room size of 20 m3 for each use event Covers exposure up to 1,00 hours/event

Se	ection 2.2	Control of Environmental Exposure	
No exposure assessment presented for the environment.			

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
The ECETOC TRA tool has been used to estimate consumer exposures unless otherwise indicated.	

Section 3.2 -Environment
No exposure assessment presented for the environment.

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO	
Section 4.1 - Health		
Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management		

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

Measures/Operational Conditions outlined in Section 2 are implemented.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

should charte that hake are managed to at least equivalent levels.

Section 4.2 - Environment

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

Exposure Scenario - Consumer

30000001017		
SECTION 1	EXPOSURE SCENARIO TITLE	
Title	Lubricants - Consumer	
Use Descriptor	Sector of Use: SU21 Product Categories: PC1, PC24, PC31 Environmental Release Categories: ERC8a, ERC8d, ERC9a, ERC9b	
Scope of process	Covers the consumer use of formulated lubricants in closed and open systems including transfer operations, application, operation of engines and similar articles, equipment maintenance and disposal of waste oil.	

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Additional Information	No exposure assessment presented for the environment.	
Section 2.1	Control of Consumer Exposu	re
Product Characteristics	· ·	
Physical form of product	Liquid, vapour pressure > 10 Pa	ı
Concentration of the Substance in Mixture/Article	Unless stated otherwise.	
	Covers concentration up to (%):	100 %
Amounts Used		
Unless stated otherwise.		
for each use event, covers amount up to (g):		6.390
covers skin contact area (cm2):		468
Frequency and Duration o	f Use	
Unless stated otherwise.		
covers use up to (times/day of use):		1
Exposure (hours/event):		6
Other Operational Condition	ons affecting Exposure	
Unless stated otherwise		

Unless stated otherwise.

Covers use at ambient temperatures.

Covers use in room size of 20m3

Product Categories	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Adhesives, sealants Glues, hobby use.	Covers concentrations up to 30 %	
	covers use up to 365 day/year	
	covers use up to 1 times/day of use	
	covers skin contact area up to (cm2): 35,73 cm2	
	For each use event, covers amount up to 9 g	
	Covers use in room size of 20 m3	

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

	for each use event Covers exposure up to 4 hours/event		
Adhesives, sealants Glues	Covers concentrations up to 30 %		
DIY-use (carpet glue, tile	Govern concentrations up to 30 //		
glue, wood parquet glue).			
<u> </u>	covers use up to 1 day/year		
	covers use up to 1 times/day of use		
	covers skin contact area up to (cm2): 110,00 cm2		
	For each use event, covers amount up to 6.390 g		
	Covers use in room size of 20 m3		
	for each use event Covers exposure up to 6,00 hours/event		
Adhesives, sealants Glue from spray.	Covers concentrations up to 30 %		
	covers use up to 6 day/year		
	covers use up to 1 times/day of use		
	covers skin contact area up to (cm2): 35,73 cm2		
	For each use event, covers amount up to 85,05 g		
	Covers use in room size of 20 m3		
	for each use event Covers exposure up to 4,00 hours/event		
Adhesives, sealants Sealants.	Covers concentrations up to 30 %		
4.1.6.	covers use up to 365 day/year		
	covers use up to 1 times/day of use		
	covers skin contact area up to (cm2): 35,73 cm2		
	For each use event, covers amount up to 75 g		
	Covers use in room size of 20 m3		
	for each use event Covers exposure up to 1,00 hours/event		
Lubricants, greases, re-	Covers concentrations up to 100 %		
lease products Liquids.			
	covers use up to 4 day/year		
	covers use up to 1 times/day of use		
	covers skin contact area up to (cm2): 468,00 cm2		
	For each use event, covers amount up to 2.200 g		
	Covers use in a one car garage (34 m3) under typical ventilation.		
	Covers use in room size of 34 m3		
	for each use event Covers exposure up to 0,17 hours/event		
Lubricants, greases, re- lease products Pastes.	Covers concentrations up to 20 %		
	covers use up to 10 day/year		
	covers use up to 1 times/day of use		
	covers skin contact area up to (cm2): 468,00 cm2		
	For each use event, covers amount up to 34 g		
	Covers use in room size of 20 m3		
Lubricants, greases, release products Sprays.	Covers concentrations up to 50 %		
	covers use up to 6 day/year		
	covers use up to 1 times/day of use		
	covers skin contact area up to (cm2): 428,75 cm2		
	For each use event, covers amount up to 73 g		
_	Covers use in room size of 20 m3		
	for each use event Covers exposure up to 0,17 hours/event		

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

Polishes and wax blends Polishes, wax / cream (floor, furniture, shoes).	Covers concentrations up to 50 %	
	covers use up to 29 day/year	
	covers use up to 1 times/day of use	
	covers skin contact area up to (cm2): 430,00 cm2	
	For each use event, covers amount up to 142 g	
	Covers use in room size of 20 m3	
	for each use event Covers exposure up to 1,23 hours/event	
Polishes and wax blends Polishes, spray (furniture, shoes).	Covers concentrations up to 50 %	
	covers use up to 8 day/year	
	covers use up to 1 times/day of use	
	covers skin contact area up to (cm2): 430,00 cm2	
	For each use event, covers amount up to 35 g	
	Covers use in room size of 20 m3	
	for each use event Covers exposure up to 0,33 hours/event	

Section 2.2 Control of Environmental Exposure		
No exposure assessment presented for the environment.		

SECTION 3	EXPOSURE ESTIMATION	
Section 3.1 - Health		
TI FORTOO TDA (II I I I I I I I I I I I I I I I I I		

The ECETOC TRA tool has been used to estimate consumer exposures unless otherwise indicated.

Section 3.2 - Environment

No exposure assessment presented for the environment.

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users

should ensure that risks are managed to at least equivalent levels.

Section 4.2 -Environment

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

Exposure Scenario - Consumer

Exposure occinario oc	7.104.1101
30000001019	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Use in agrochemicals - Consumer
Use Descriptor	Sector of Use: SU21 Product Categories: PC12, PC27 Environmental Release Categories: ERC8a, ERC8d
Scope of process	Covers the consumer use in agrochemicals in liquid and solid forms.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Additional Information	No exposure assessment presented for the environment.	
Section 2.1	Control of Consumer Exposure	
Product Characteristics		
Physical form of product	Liquid, vapour pressure > 10 Pa at STP	
Concentration of the Substance in Mixture/Article	Unless stated otherwise.	
	Covers concentration up to (%): 50 %	
Amounts Used		
Unless stated otherwise.		
for each use event, covers amount up to (g):		50
covers skin contact area (cm2):		857,50
Frequency and Duration of	f Use	·
Unless stated otherwise.		
covers use up to (times/day of use):		0
Other Operational Condition	one affecting Evnosure	•

Other Operational Conditions affecting Exposure

Unless stated otherwise.

Covers use at ambient temperatures.

Covers use in room size of 20m3

Product Categories	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
Fertilizers	Covers concentrations up to 50 %
	covers use up to 365 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 857,50 cm2
	For each use event, assumes swallowed amount of 0,3 g
	Covers use in room size of 20 m3
Plant protection products	Covers concentrations up to 50 %
	covers use up to 365 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 857,50 cm2

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

For each use event, assumes swallowed amount of 0,3 g
Covers use in room size of 20 m3

Section 2.2	Control of Environmental Exposure	
No exposure assessment pre	sented for the environment.	

	SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health		
	The ECETOC TRA tool has been used to estimate consumer exposures unless otherwise indicated.	

Section 3.2 -Environment

No exposure assessment presented for the environment.

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE
	EXPOSURE SCENARIO
Section 4.1 Health	

Section 4.1 - Health

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 - Environment

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

Exposure Scenario - Consumer

30000001021		
SECTION 1	EXPOSURE SCENARIO TITLE	
Title	Use as a fuel - Consumer	
Use Descriptor	Sector of Use: SU21 Product Categories: PC13 Environmental Release Categories: ERC9a, ERC9b	
Scope of process	Covers consumer uses in liquid fuels.	

SECTION 2	OPERATIONAL CONDITIONS A MEASURES	AND RISK MANAGEMENT
Additional Information	No exposure assessment presen	ted for the environment.
Section 2.1	Control of Consumer Exposure	•
Product Characteristics		
Physical form of product	Liquid, vapour pressure > 10 Pa	at STP
Concentration of the Substance in Mixture/Article	Unless stated otherwise.	
	Covers concentration up to (%):	100 %
Amounts Used		
Unless stated otherwise.		
for each use event, covers amount up to (g):		37.500
covers skin contact area (cm2):		420
Frequency and Duration of	f Use	•
Unless stated otherwise.		
covers use up to (times/day of use): 0,143		0,143
Exposure (hours/event): 2		2
Other Operational Conditi	one offecting Evnecure	•

Other Operational Conditions affecting Exposure

Unless stated otherwise.

Covers use at ambient temperatures.

Covers use in room size of 20m3

Product Categories	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
Fuels Liquid: Automotive Refuelling.	Covers concentrations up to 100 %
	covers use up to 52 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 210,00 cm2
	For each use event, covers amount up to 37.500 g
	Covers outdoor use.
	Covers use in room size of 100 m3
	for each use event Covers exposure up to 0,05 hours/event
Fuels Liquid Scooter Refu-	Covers concentrations up to 100 %

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

elling.	
Ciling.	covers use up to 52 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 210,00 cm2
	For each use event, covers amount up to 3.750 g
	Covers outdoor use.
	Covers use in room size of 100 m3
	for each use event Covers exposure up to 0,03 hours/event
Fuels Liquid, Garden	Covers concentrations up to 100 %
Equipment - Use.	, in the second
	covers use up to 26 day/year
	covers use up to 1 times/day of use
	For each use event, covers amount up to 750 g
	Covers outdoor use.
	Covers use in room size of 100 m3
	for each use event Covers exposure up to 2,00 hours/event
Fuels Liquid: Garden Equipment - Refuelling.	Covers concentrations up to 100 %
	covers use up to 26 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 420,00 cm2
	For each use event, covers amount up to 750 g
	Covers use in a one car garage (34 m3) under typical ventilation.
	Covers use in room size of 34 m3
	for each use event Covers exposure up to 0,03 hours/event
Fuels Liquid: Home space	Covers concentrations up to 100 %
heater fuel.	·
	covers use up to 26 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 420,00 cm2
	For each use event, covers amount up to 750 g
	Covers use in room size of 20 m3
	for each use event Covers exposure up to 8,00 hours/event
Fuels Liquid: Lamp oil.	Covers concentrations up to 100 %
	covers use up to 52 day/year
	Covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 210,00 cm2
	For each use event, covers amount up to 100 g
	Covers use in room size of 20 m3
	for each use event Covers exposure up to 0,01 hours/event

Section 2.2	Control of Environmental Exposure	
No exposure assessment pre-	sented for the environment.	

SECTION 3	EXPOSURE ESTIMATION	
Section 3.1 - Health		
The ECETOC TRA tool has I indicated.	been used to estimate consumer exposures unless otherwise	

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

Section 3.2 - Environment

No exposure assessment presented for the environment.

SECTION 4 GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO

Section 4.1 - Health

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 - Environment

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

Exposure Scenario - Consumer

30000001023	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Functional Fluids - Consumer
Use Descriptor	Sector of Use: SU21 Product Categories: PC16, PC17 Environmental Release Categories: ERC9a, ERC9b
Scope of process	Use of sealed items containing functional fluids e.g. transfer oils, hydraulic fluids, refrigerants.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES		
Additional Information	No exposure assessment presented for the environment.		
Section 2.1	Control of Consumer Exposure	Control of Consumer Exposure	
Product Characteristics			
Physical form of product	Liquid, vapour pressure > 10 Pa at ST	P	
Concentration of the Substance in Mixture/Article	Unless stated otherwise.		
	Covers concentration up to (%): 100 %)	
Amounts Used			
Unless stated otherwise.			
for each use event, covers amount up to (g):		2.200	
covers skin contact area (cm2):		468	
Frequency and Duration o	f Use		
Unless stated otherwise.			
covers use up to (times/day of use):		0,010	
Exposure (hours/event):		0,167	
Other Operational Condition	ons affecting Exposure		

Other Operational Conditions affecting Exposure

Unless stated otherwise.

Covers use at ambient temperatures.

Covers use in room size of 20m3

Product Categories	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
Heat transfer fluids Liquids.	Covers concentrations up to 100 %
	covers use up to 4 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 468,00 cm2
	For each use event, assumes swallowed amount of 2.200 g
	Covers use in a one car garage (34 m3) under typical ventila-
	tion.
	Covers use in room size of 34 m3
	for each use event Covers exposure up to 0,17 hours/event

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

Hydraulic fluids Liquids.	Covers concentrations up to 100 %
	covers use up to 4 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 468,00 cm2
	For each use event, covers amount up to 2.200 g
	Covers use in a one car garage (34 m3) under typical ventila-
	tion.
	Covers use in room size of 34 m3
	for each use event Covers exposure up to 0,17 hours/event

Section 2.2	Control of Environmental Exposure	
No exposure assessment presented for the environment.		

SECTION 3	EXPOSURE ESTIMATION	
Section 3.1 - Health		
The ECETOC TRA tool has been used to estimate consumer exposures unless otherwise		
indicated.		

Section 3.2 - Environment

No exposure assessment presented for the environment.

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 -Environment No exposure assessment presented for the environment.

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

Exposure Scenario - Consumer

30000001024		
SECTION 1	EXPOSURE SCENARIO TITLE	
Title	Use in de-icing and anti-icing fluids - Consumer	
Use Descriptor	Sector of Use: SU21 Product Categories: PC4 Environmental Release Categories: ERC8d	
Scope of process	De-icing of vehicles and similar equipment by spraying.	

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Additional Information	No exposure assessment presented for the environment.	
Section 2.1	Control of Consumer Exposure	
Product Characteristics		
Physical form of product	Liquid, vapour pressure > 10 Pa	a at STP
Concentration of the Substance in Mixture/Article	Unless stated otherwise.	
	Covers concentration up to (%):	: 40 %
Amounts Used		
Unless stated otherwise.		
for each use event, covers amount up to (g):		2.000
covers skin contact area (cm2):		428
Frequency and Duration of	f Use	•
Unless stated otherwise.		
covers use up to (times/day of use):		1
Covers exposure up to (hours/event): 0,25		0,25
Other Operational Conditi	one offecting Evacure	·

Other Operational Conditions affecting Exposure

Unless stated otherwise.

Covers use at ambient temperatures.

Covers use in room size of 20m3

Product Categories	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
Anti-Freeze and de-icing products Washing car window.	Covers concentrations up to 20 %
	covers use up to 365 day/year
	covers use up to 1 times/day of use
	For each use event, covers amount up to 0,5 g
	Covers use in a one car garage (34 m3) under typical ventilation.
	Covers use in room size of 34 m3
	for each use event Covers exposure up to 0,02 hours/event
Anti-Freeze and de-icing	Covers concentrations up to 20 %

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

products Pouring into radia-	
tor.	
	covers use up to 365 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 428,00 cm2
	For each use event, covers amount up to 2.000 g
	Covers use in a one car garage (34 m3) under typical ventila-
	tion.
	Covers use in room size of 34 m3
	for each use event Covers exposure up to 0,17 hours/event
Anti-Freeze and de-icing	Covers concentrations up to 50 %
products Lock de-icer.	
	covers use up to 365 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 214,40 cm2
	For each use event, covers amount up to 4 g
	Covers use in a one car garage (34 m3) under typical ventila-
	tion.
	Covers use in room size of 34 m3
	for each use event Covers exposure up to 0,25 hours/event

Section 2.2	Control of Environmental Exposure	
No exposure assessment presented for the environment.		

SECTION 3	EXPOSURE ESTIMATION	
Section 3.1 - Health		
The ECETOC TRA tool has been used to estimate consumer exposures unless otherwise		

indicated.

Section 3.2 - Environment

No exposure assessment presented for the environment.

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO	
Section 4.1 - Health		
Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management		
Measures/Operational Conditions outlined in Section 2 are implemented.		
Where other Disk Management Massures (Operational Conditions are adopted they users		

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 -Environment
No exposure assessment presented for the environment.

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

Exposure Scenario - Consumer

30000001025		
SECTION 1	EXPOSURE SCENARIO TITLE	
Title	Other Consumer Uses - Consumer	
Use Descriptor	Sector of Use: SU21 Product Categories: PC28, PC39 Environmental Release Categories: ERC8a, ERC8d	
Scope of process	Consumer uses e.g. as a carrier in cosmetics/personal care products, perfumes and fragrances. Note: For cosmetic and personal care products, risk assessment only required for the environment under REACH as human health is covered by alternative legislation.	

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Additional Information	No exposure assessment presented for human health.	
	No exposure assessment presented for the environment.	
Section 2.1	Control of Consumer Exposure	
Product Characteristics		
Product Categories	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
No exposure assessment presented for human health.	

Section 3.2 -Environment

SECTION 4 GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO	
Section 4.1 - Health	
No exposure assessment presented for human health.	

Section 4.2 -Environment	
No exposure assessment presented for the environment.	

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

Exposure Scenario - Consumer

30000001026		
SECTION 1	EXPOSURE SCENARIO TITLE	
Title	Water treatment chemicals - Consumer	
Use Descriptor	Sector of Use: SU21 Product Categories: PC36, PC37 Environmental Release Categories: ERC8f	
Scope of process	Covers the use of the substance for the treatment of water in open and closed systems.	

SECTION 2	OPERATIONAL CONDITIONS AN MEASURES	ND RISK MANAGEMENT
Additional Information	No exposure assessment presente	ed for the environment.
Section 2.1	Control of Consumer Exposure	
Product Characteristics		
Physical form of product	Liquid, vapour pressure > 10 Pa	
Concentration of the Substance in Mixture/Article	Unless stated otherwise.	
	Covers concentration up to (%): 20	0 %
Amounts Used		
Unless stated otherwise.		
for each use event, covers amount up to (g):		10
covers skin contact area (cm2): 6.600		6.600
Frequency and Duration of Use		
Unless stated otherwise.		
covers use up to (times/day	covers use up to (times/day of use):	
Other Operational Conditions affecting Exposure		

Other Operational Conditions affecting Exposure

Unless stated otherwise.

Covers use at ambient temperatures.

Covers use in room size of 20m3

Product Categories	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Water softeners	Covers concentrations up to 20 %	
	covers use up to 365 day/year	
	covers use up to 1 times/day of use	
	covers skin contact area up to (cm2): 6.600 cm2	
	For each use event, assumes swallowed amount of 0,02 mg	
	For each use event, covers amount up to 10 g	
	Covers use in room size of 20 m3	
Water treatment chemicals	Covers concentrations up to 20 %	
	covers use up to 365 day/year	
_	covers use up to 1 times/day of use	

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 09.03.2023

2.2 09.10.2024 800001006805 Print Date 16.10.2024

covers skin contact area up to (cm2): 6.600 cm2
For each use event, assumes swallowed amount of 0,15 mg
For each use event, covers amount up to 10 g
Covers use in room size of 20 m3

Section 2.2	Control of Environmental Exposure	
No exposure assessment presented for the environment.		

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
The ECETOC TDA tool bee b	son used to estimate concumer exposures unless otherwise

The ECETOC TRA tool has been used to estimate consumer exposures unless otherwise indicated.

Section 3.2 - Environment

No exposure assessment presented for the environment.

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE
	EXPOSURE SCENARIO

Section 4.1 - Health

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 - Environment