

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR
1910.1200

Ethyl Proxitol Acetate

Version	Revision Date:	SDS Number:	Print Date: 12/01/2023
3.1	11/24/2023	800001000220	Date of last issue: 04/26/2018

SECTION 1. IDENTIFICATION

Product name : Ethyl Proxitol Acetate

Product code : U5149

CAS-No. : 98516-30-4

Manufacturer or supplier's details

Company : **Shell Chemical LP**
PO Box 576
HOUSTON TX 77001
USA

SDS Request : 1-800-240-6737

Customer Service : 1-855-697-4355

Emergency telephone number

Chemtrec Domestic (24 hr) : 1-800-424-9300

Chemtrec International (24 hr) : 1-703-527-3887

Recommended use of the chemical and restrictions on use

Recommended use : Speciality solvent.

Restrictions on use : This product must not be used in applications other than the above without first seeking the advice of the supplier.

Other information : PROXITOL is a registered trademark of Shell trademark Management BV.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids : Category 3

Specific target organ toxicity : Category 3 (Narcotic effects)
- single exposure

GHS label elements

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Ethyl Proxitol Acetate

Version
3.1

Revision Date:
11/24/2023

SDS Number:
800001000220

Print Date: 12/01/2023
Date of last issue: 04/26/2018

Hazard pictograms

:



Signal word

:

Warning

Hazard statements

:

PHYSICAL HAZARDS:
H226 Flammable liquid and vapour.
HEALTH HAZARDS:
H336 May cause drowsiness or dizziness.
ENVIRONMENTAL HAZARDS:
Not classified as an environmental hazard under GHS criteria.

Precautionary statements

:

Prevention:

P210 Keep away from heat/ sparks/ open flames/ hot surfaces.
No smoking.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P370 + P378 In case of fire: Use appropriate media to extinguish.
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312 Call a POISON CENTER/ doctor if you feel unwell.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P235 Keep cool.
P405 Store locked up.

Disposal:

P501 Dispose of contents and container to appropriate waste site or reclaimer in accordance with local and national regulations.

Other hazards which do not result in classification

Even with proper grounding and bonding, this material can still accumulate an electrostatic charge.

If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur.

The classification of this material is based on OSHA HCS 2012 criteria.

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR
1910.1200

Ethyl Proxitol Acetate

Version
3.1

Revision Date:
11/24/2023

SDS Number:
800001000220

Print Date: 12/01/2023
Date of last issue: 04/26/2018

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Substance

Hazardous components

Chemical name	Synonyms	CAS-No.	Concentration (% w/w)
Propanol, 1(or 2)-ethoxy-, acetate	Ethoxypropyl acetates (isomer)	98516-30-4	<= 100

SECTION 4. FIRST-AID MEASURES

- General advice : Not expected to be a health hazard when used under normal conditions.
- If inhaled : Remove to fresh air. If rapid recovery does not occur, transport to nearest medical facility for additional treatment.
- In case of skin contact : Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available.
If persistent irritation occurs, obtain medical attention.
- In case of eye contact : Flush eye with copious quantities of water.
Remove contact lenses, if present and easy to do. Continue rinsing.
If persistent irritation occurs, obtain medical attention.
- If swallowed : In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.
- Most important symptoms and effects, both acute and delayed : Breathing of high vapour concentrations may cause central nervous system (CNS) depression resulting in dizziness, light-headedness, headache, nausea and loss of coordination.
Continued inhalation may result in unconsciousness and death.
No specific hazards under normal use conditions.
Skin irritation signs and symptoms may include a burning sensation, redness, or swelling.
No specific hazards under normal use conditions.
Eye irritation signs and symptoms may include a burning sensation, redness, swelling, and/or blurred vision.
No specific hazards under normal use conditions.
Ingestion may result in nausea, vomiting and/or diarrhoea.
- Protection of first-aiders : When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.
- Indication of any immediate medical attention and special treatment needed : Call a doctor or poison control center for guidance.
Treat symptomatically.

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR
1910.1200

Ethyl Proxitol Acetate

Version
3.1

Revision Date:
11/24/2023

SDS Number:
800001000220

Print Date: 12/01/2023
Date of last issue: 04/26/2018

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Alcohol-resistant foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
- Unsuitable extinguishing media : None
- Specific hazards during fire-fighting : The vapour is heavier than air, spreads along the ground and distant ignition is possible.
Carbon monoxide may be evolved if incomplete combustion occurs.
- Specific extinguishing methods : Standard procedure for chemical fires.
- Further information : Clear fire area of all non-emergency personnel.
Keep adjacent containers cool by spraying with water.
- Special protective equipment for firefighters : Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Observe the relevant local and international regulations
Notify authorities if any exposure to the general public or the environment occurs or is likely to occur.
Local authorities should be advised if significant spillages cannot be contained.
The vapour is heavier than air, spreads along the ground and distant ignition is possible.
Vapour may form an explosive mixture with air.
Avoid contact with skin, eyes and clothing.
Isolate hazard area and deny entry to unnecessary or unprotected personnel.
Stay upwind and keep out of low areas.
- Environmental precautions : Shut off leaks, if possible without personal risks. Remove all possible sources of ignition in the surrounding area. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. Attempt to disperse the vapour or to direct its flow to a safe location for example by using fog sprays. Take precautionary measures against static discharge. Ensure electrical continuity by bonding and grounding (earthing) all equipment.

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Ethyl Proxitol Acetate

Version
3.1

Revision Date:
11/24/2023

SDS Number:
800001000220

Print Date: 12/01/2023
Date of last issue: 04/26/2018

Ventilate contaminated area thoroughly.
Monitor area with combustible gas indicator.

Methods and materials for containment and cleaning up : For large liquid spills (> 1 drum), transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.
For small liquid spills (< 1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.

Additional advice : For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet.
For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.

U.S. regulations may require reporting releases of this material to the environment which exceed the reportable quantity (refer to Section 15) to the National Response Center at (800) 424-8802.

SECTION 7. HANDLING AND STORAGE

Technical measures : Avoid breathing of or direct contact with material. Only use in well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet.
Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.
Ensure that all local regulations regarding handling and storage facilities are followed.

Advice on safe handling : Avoid contact with skin, eyes and clothing.
Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols.
Bulk storage tanks should be diked (bunded).
Extinguish any naked flames. Do not smoke. Remove ignition sources. Avoid sparks.
Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment to reduce the risk.
The vapours in the head space of the storage vessel may lie in the flammable/explosive range and hence may be flammable.
Properly dispose of any contaminated rags or cleaning materials in order to prevent fires.

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Ethyl Proxitol Acetate

Version
3.1

Revision Date:
11/24/2023

SDS Number:
800001000220

Print Date: 12/01/2023
Date of last issue: 04/26/2018

	Do NOT use compressed air for filling, discharging, or handling operations.
Avoidance of contact	: Strong oxidising agents.
Product Transfer	: Refer to guidance under Handling section.
Conditions for safe storage	: The vapour is heavier than air. Beware of accumulation in pits and confined spaces. Refer to section 15 for any additional specific legislation covering the packaging and storage of this product.
Packaging material	: Suitable material: For containers, or container linings use mild steel, stainless steel. Unsuitable material: Natural, butyl, neoprene or nitrile rubbers.
Container Advice	: Containers, even those that have been emptied, can contain explosive vapours. Do not cut, drill, grind, weld or perform similar operations on or near containers.
Specific use(s)	: Not applicable
	Ensure that all local regulations regarding handling and storage facilities are followed. See additional references that provide safe handling practices: American Petroleum Institute 2003 (Protection Against Ignitions Arising out of Static, Lightning and Stray Currents) or National Fire Protection Agency 77 (Recommended Practices on Static Electricity). IEC/TS 60079-32-1: Electrostatic hazards, guidance

SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Components with workplace control parameters

Contains no substances with occupational exposure limit values.

Biological occupational exposure limits

No biological limit allocated.

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate. Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory. Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available. National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods <http://www.cdc.gov/niosh/> Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Ethyl Proxitol Acetate

Version
3.1

Revision Date:
11/24/2023

SDS Number:
800001000220

Print Date: 12/01/2023
Date of last issue: 04/26/2018

<http://www.osha.gov/>

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances <http://www.hse.gov.uk/>

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany

<http://www.dguv.de/inhalt/index.jsp>

L'Institut National de Recherche et de Sécurité, (INRS), France <http://www.inrs.fr/accueil>

Engineering measures

: The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:
Use sealed systems as far as possible.
Adequate explosion-proof ventilation to control airborne concentrations below the exposure guidelines/limits.
Local exhaust ventilation is recommended.
Firewater monitors and deluge systems are recommended.
Eye washes and showers for emergency use.
Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

General Information:

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.
Define procedures for safe handling and maintenance of controls.
Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.
Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.
Drain down system prior to equipment break-in or maintenance.
Retain drain downs in sealed storage pending disposal or subsequent recycle.

Personal protective equipment

Respiratory protection

: If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are unsuitable (e.g. airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. If air-filtering respirators are suitable for conditions of use:

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Ethyl Proxitol Acetate

Version
3.1

Revision Date:
11/24/2023

SDS Number:
800001000220

Print Date: 12/01/2023
Date of last issue: 04/26/2018

Select a filter suitable for organic gases and vapours [Type A boiling point >65°C (149°F)].

Respirator selection, use and maintenance should be in accordance with the requirements of the OSHA Respiratory Protection Standard, 29 CFR 1910.134.

Hand protection Remarks

: Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. Longer term protection: butyl-rubber Nitrile rubber gloves.
Incidental contact/Splash protection: Nitrile rubber gloves.
For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

Eye protection

: If material is handled such that it could be splashed into eyes, protective eyewear is recommended.

Skin and body protection

: Skin protection is not required under normal conditions of use.
For prolonged or repeated exposures use impervious clothing over parts of the body subject to exposure.
If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to relevant Standard, and provide employee skin care programmes.
Wear antistatic and flame-retardant clothing, if a local risk assessment deems it so.

Protective measures

: Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Environmental exposure controls

General advice

: Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Ethyl Proxitol Acetate

Version
3.1

Revision Date:
11/24/2023

SDS Number:
800001000220

Print Date: 12/01/2023
Date of last issue: 04/26/2018

vapour.

Minimise release to the environment. An environmental assessment must be made to ensure compliance with local environmental legislation.

Information on accidental release measures are to be found in section 6.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: Liquid.
Colour	: colourless
Odour	: characteristic
Odour Threshold	: Data not available
pH	: Not applicable
Melting / freezing point	: -89 °C / -128 °F
Boiling point/boiling range	: 158 - 160 °C / 316 - 320 °F
Flash point	: 53 °C / 127 °F
Evaporation rate	: Data not available
Flammability	
Flammability (solid, gas)	: Data not available
Lower explosion limit and upper explosion limit / flammability limit	
Upper explosion limit / upper flammability limit	: 9.8 %(V)
Lower explosion limit / Lower flammability limit	: 1 %(V)
Vapour pressure	: 2.3 hPa (20 °C / 68 °F)
Relative vapour density	: Data not available
Relative density	: Data not available
Density	: 0.941 g/cm ³ (20 °C / 68 °F) Method: ASTM D4052
Solubility(ies)	
Water solubility	: 69.6 g/l (20 °C / 68 °F))
Partition coefficient: n-octanol/water	: log Pow: 0.76

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Ethyl Proxitol Acetate

Version
3.1

Revision Date:
11/24/2023

SDS Number:
800001000220

Print Date: 12/01/2023
Date of last issue: 04/26/2018

Auto-ignition temperature	:	325 °C / 617 °F
Decomposition temperature	:	Data not available
Viscosity		
Viscosity, dynamic	:	Data not available
Viscosity, kinematic	:	1.33 mm ² /s (40 °C / 104 °F)
		Method: ASTM D445
Explosive properties	:	Not applicable
Oxidizing properties	:	Data not available
Surface tension	:	39.1 mN/m, 20 °C / 68 °F
Conductivity	:	Electrical conductivity: > 10,000 pS/m
		A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid, This material is not expected to be a static accumulator.
Molecular weight	:	146.2 g/mol
Particle size	:	Data not available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.
Chemical stability	:	No hazardous reaction is expected when handled and stored according to provisions
Possibility of hazardous reactions	:	Reacts with strong oxidising agents.
Conditions to avoid	:	Avoid heat, sparks, open flames and other ignition sources. Prevent vapour accumulation. In certain circumstances product can ignite due to static electricity.
Incompatible materials	:	Strong oxidising agents.
Hazardous decomposition products	:	Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids and gases including carbon monoxide, carbon dioxide, sulphur oxides and unidentified organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation.

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR
1910.1200

Ethyl Proxitol Acetate

Version
3.1

Revision Date:
11/24/2023

SDS Number:
800001000220

Print Date: 12/01/2023
Date of last issue: 04/26/2018

SECTION 11. TOXICOLOGICAL INFORMATION

Basis for assessment : Information given is based on product testing, and/or similar products, and/or components.
Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

Information on likely routes of exposure

Exposure may occur via inhalation, ingestion, skin absorption, skin or eye contact, and accidental ingestion.

Acute toxicity

Components:

Propanol, 1(or 2)-ethoxy-, acetate:

Acute oral toxicity : LD 50 (Rat): > 5000 mg/kg
Remarks: Low toxicity

Acute inhalation toxicity : Remarks: Low toxicity by inhalation.
LC50 greater than near-saturated vapour concentration.

Acute dermal toxicity : LD 50 (Rabbit): > 5000 mg/kg
Remarks: Low toxicity

Skin corrosion/irritation

Components:

Propanol, 1(or 2)-ethoxy-, acetate:

Remarks: Not irritating to skin.

Serious eye damage/eye irritation

Components:

Propanol, 1(or 2)-ethoxy-, acetate:

Remarks: Not irritating to eye.

Respiratory or skin sensitisation

Components:

Propanol, 1(or 2)-ethoxy-, acetate:

Remarks: Not a sensitizer. Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Components:

Propanol, 1(or 2)-ethoxy-, acetate:

Genotoxicity in vivo : Remarks: Not mutagenic.

Carcinogenicity

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR
1910.1200

Ethyl Proxitol Acetate

Version
3.1

Revision Date:
11/24/2023

SDS Number:
800001000220

Print Date: 12/01/2023
Date of last issue: 04/26/2018

Components:

Propanol, 1(or 2)-ethoxy-, acetate:

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Components:

Propanol, 1(or 2)-ethoxy-, acetate:

Effects on fertility :

Remarks: Not a developmental toxicant.
Based on available data, the classification criteria are not met.
Does not impair fertility.

STOT - single exposure

Components:

Propanol, 1(or 2)-ethoxy-, acetate:

Remarks: May cause drowsiness and dizziness.

STOT - repeated exposure

Components:

Propanol, 1(or 2)-ethoxy-, acetate:

Remarks: Based on available data, the classification criteria are not met.

Aspiration toxicity

Components:

Propanol, 1(or 2)-ethoxy-, acetate:

Not an aspiration hazard.

Further information

Components:

Propanol, 1(or 2)-ethoxy-, acetate:

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR
1910.1200

Ethyl Proxitol Acetate

Version
3.1

Revision Date:
11/24/2023

SDS Number:
800001000220

Print Date: 12/01/2023
Date of last issue: 04/26/2018

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

SECTION 12. ECOLOGICAL INFORMATION

Basis for assessment : Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).
Incomplete ecotoxicological data are available for this product.
The information given below is based partly on a knowledge of the components and the ecotoxicology of similar products.

Ecotoxicity

Components:

Propanol, 1(or 2)-ethoxy-, acetate:

Toxicity to fish (Acute toxicity) : Remarks: Practically non toxic:
LC/EC/IC50 > 100 mg/l

Toxicity to daphnia and other aquatic invertebrates (Acute toxicity) : Remarks: Practically non toxic:
LC/EC/IC50 > 100 mg/l

Toxicity to algae (Acute toxicity) : Remarks: Practically non toxic:
LC/EC/IC50 > 100 mg/l

Toxicity to fish (Chronic toxicity) : Remarks: NOEC/NOEL > 10 - <=100 mg/l

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : Remarks: NOEC/NOEL > 100 mg/l

Toxicity to microorganisms (Acute toxicity) : Remarks: LC/EC/IC50 > 100 mg/l
Practically non toxic:
Based on available data, the classification criteria are not met.

Persistence and degradability

Components:

Propanol, 1(or 2)-ethoxy-, acetate:

Biodegradability : Remarks: Readily biodegradable.

Bioaccumulative potential

Components:

Propanol, 1(or 2)-ethoxy-, acetate:

Bioaccumulation : Remarks: Does not bioaccumulate significantly.

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Ethyl Proxitol Acetate

Version
3.1

Revision Date:
11/24/2023

SDS Number:
800001000220

Print Date: 12/01/2023
Date of last issue: 04/26/2018

Mobility in soil

Components:

Propanol, 1(or 2)-ethoxy-, acetate:

Mobility : Remarks: If the product enters soil, one or more constituents will or may be mobile and may contaminate groundwater.
Dissolves in water.

Other adverse effects

no data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Recover or recycle if possible.
It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.
Do not dispose into the environment, in drains or in water courses.
Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment.
Waste, spills or used product is dangerous waste.

Disposal should be in accordance with applicable regional, national, and local laws and regulations.
Local regulations may be more stringent than regional or national requirements and must be complied with.

MARPOL - see International Convention for the Prevention of Pollution from Ships (MARPOL 73/78) which provides technical aspects at controlling pollutions from ships.

Contaminated packaging : Drain container thoroughly.
After draining, vent in a safe place away from sparks and fire.
Residues may cause an explosion hazard.
Do not, puncture, cut, or weld uncleaned drums.
Send to drum recoverer or metal reclaimer.

Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand.

SECTION 14. TRANSPORT INFORMATION

National Regulations

US Department of Transportation Classification (49 CFR Parts 171-180)

UN/ID/NA number : UN 3272
Proper shipping name : ESTERS, N.O.S.

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR
1910.1200

Ethyl Proxitol Acetate

Version	Revision Date:	SDS Number:	Print Date: 12/01/2023
3.1	11/24/2023	800001000220	Date of last issue: 04/26/2018

Class	: 3
Packing group	: III
Labels	: 3
ERG Code	: 127
Marine pollutant	: no

International Regulations

IATA-DGR

UN/ID No.	: UN 3272
Proper shipping name	: ESTERS, N.O.S. (2-ethoxy-1-methylethyl acetate)
Class	: 3
Packing group	: III
Labels	: 3

IMDG-Code

UN number	: UN 3272
Proper shipping name	: ESTERS, N.O.S. (2-ethoxy-1-methylethyl acetate)
Class	: 3
Packing group	: III
Labels	: 3
Marine pollutant	: no

Maritime transport in bulk according to IMO instruments

Pollution category	: Z
Ship type	: 3
Product name	: Propylene glycol methyl ether acetate

Special precautions for user

Remarks	: Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.
---------	--

Additional Information	: This product may be transported under nitrogen blanketing. Nitrogen is an odourless and invisible gas. Exposure to nitrogen may cause asphyxiation or death. Personnel must observe strict safety precautions when involved with a confined space entry. Transport in bulk according to Annex II of Marpol and the IBC Code
-------------------------------	--

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

*: This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Ethyl Proxitol Acetate

Version
3.1

Revision Date:
11/24/2023

SDS Number:
800001000220

Print Date: 12/01/2023
Date of last issue: 04/26/2018

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
Specific target organ toxicity (single or repeated exposure)

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Water Act

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

US State Regulations

California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

Other regulations:

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

The components of this product are reported in the following inventories:

IECSC	: Listed
ENCS	: Listed
KECI	: Listed
NZIoC	: Listed
TSCA	: Listed
DSL	: Listed
PICCS	: Listed
TCSI	: Listed

SECTION 16. OTHER INFORMATION

Further information

NFPA Rating (Health, Fire, Reactivity) 0, 2, 0

Full text of other abbreviations

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR
1910.1200

Ethyl Proxitol Acetate

Version
3.1

Revision Date:
11/24/2023

SDS Number:
800001000220

Print Date: 12/01/2023
Date of last issue: 04/26/2018

Abbreviations and Acronyms : The standard abbreviations and acronyms used in this document can be looked up in reference literature (e.g. scientific dictionaries) and/or websites.

ACGIH = American Conference of Governmental Industrial Hygienists

ADR = European Agreement concerning the International Carriage of Dangerous Goods by Road

AICS = Australian Inventory of Chemical Substances

ASTM = American Society for Testing and Materials

BEL = Biological exposure limits

BTEX = Benzene, Toluene, Ethylbenzene, Xylenes

CAS = Chemical Abstracts Service

CEFIC = European Chemical Industry Council

CLP = Classification Packaging and Labelling

COC = Cleveland Open-Cup

DIN = Deutsches Institut für Normung

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

DSL = Canada Domestic Substance List

EC = European Commission

EC50 = Effective Concentration fifty

ECETOC = European Center on Ecotoxicology and Toxicology Of Chemicals

ECHA = European Chemicals Agency

EINECS = The European Inventory of Existing Commercial Chemical Substances

EL50 = Effective Loading fifty

ENCS = Japanese Existing and New Chemical Substances Inventory

EWC = European Waste Code

GHS = Globally Harmonised System of Classification and Labelling of Chemicals

IARC = International Agency for Research on Cancer

IATA = International Air Transport Association

IC50 = Inhibitory Concentration fifty

IL50 = Inhibitory Level fifty

IMDG = International Maritime Dangerous Goods

INV = Chinese Chemicals Inventory

IP346 = Institute of Petroleum test method N° 346 for the determination of polycyclic aromatics DMSO-extractables

KECI = Korea Existing Chemicals Inventory

LC50 = Lethal Concentration fifty

LD50 = Lethal Dose fifty per cent.

LL/EL/IL = Lethal Loading/Effective Loading/Inhibitory loading

LL50 = Lethal Loading fifty

MARPOL = International Convention for the Prevention of Pollution From Ships

NOEC/NOEL = No Observed Effect Concentration / No Observed Effect Level

OE_HP = Occupational Exposure - High Production Volume

PBT = Persistent, Bioaccumulative and Toxic

PICCS = Philippine Inventory of Chemicals and Chemical Substances

PNEC = Predicted No Effect Concentration

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR
1910.1200

Ethyl Proxitol Acetate

Version
3.1

Revision Date:
11/24/2023

SDS Number:
800001000220

Print Date: 12/01/2023
Date of last issue: 04/26/2018

REACH = Registration Evaluation And Authorisation Of
Chemicals
RID = Regulations Relating to International Carriage of Dan-
gerous Goods by Rail
SKIN_DES = Skin Designation
STEL = Short term exposure limit
TRA = Targeted Risk Assessment
TSCA = US Toxic Substances Control Act
TWA = Time-Weighted Average
vPvB = very Persistent and very Bioaccumulative

A vertical bar (|) in the left margin indicates an amendment from the previous version.

Sources of key data used to compile the Safety Data Sheet : The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID data base, EC 1272 regulation, etc).

Revision Date : 11/24/2023

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN