According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 45

Version Revision Date: SDS Number: Date of last issue: 17.11.2023

5.0 29.04.2024 800001001064 Print Date 06.05.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : NEODOL 45 Product code : V2456

Registration number EU : 01-2119486413-36-0001

CAS-No. : 120944-67-4

EC-No. : 931-287-9

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Use in detergent manufacture.

stance/Mixture Please refer to section 16 and/or the annexes for the regis-

tered uses under REACH.

Uses advised against : This product must not be used in applications other than the

above without first seeking the advice of the supplier.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier : Shell Chemicals Europe B.V.

PO Box 2334

3000 CH Rotterdam

Netherlands

Telephone : +31 (0)10 441 5137 / +31 (0)10 441 5191 Telefax : +31 (0)20 716 8316 / +31 (0)20 713 9230

Contact for Safety Data : sccmsds@shell.com

Sheet

1.4 Emergency telephone number

+44 (0) 1235 239 670 (This telephone number is available 24 hours per day, 7 days per

week)

Giftnotruf (Berlin): +49 (0) 30 3068 6700

Other information : NEODOL is a trademark owned by Shell Trademark Man-

agement B.V. and Shell Brands Inc. and used by affiliates of

Royal Dutch Shell plc.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Short-term (acute) aquatic hazard, Cate-

H400: Very toxic to aquatic life.

gory 1

Long-term (chronic) aquatic hazard, Cat-H410: Very toxic to aquatic life with long lasting

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 45

Version Revision Date: SDS Number: Date of last issue: 17.11.2023

5.0 29.04.2024 800001001064 Print Date 06.05.2024

egory 1 effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms

Signal word : Warning

Hazard statements : PHYSICAL HAZARDS:

Not classified as a physical hazard according to CLP

criteria.

HEALTH HAZARDS:

Not classified as a health hazard under CLP criteria.

ENVIRONMENTAL HAZARDS:

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

Supplemental Hazard

Statements

EUH066

Repeated exposure may cause skin dryness or

cracking.

Precautionary statements : Prevention:

P273 Avoid release to the environment.

Response:

P391 Collect spillage.

Storage:

No precautionary phrases.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

2.3 Other hazards

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 45

Version Revision Date: SDS Number: Date of last issue: 17.11.2023

5.0 29.04.2024 800001001064 Print Date 06.05.2024

SECTION 3: Composition/information on ingredients

3.1 Substances

Components

Chemical name	CAS-No. EC-No.	Concentration (% w/w)
Alcohols, C14-15-branched and linear	Not Assigned 931-287-9	<= 100

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Not expected to be a health hazard when used under normal

conditions.

Protection of first-aiders : When administering first aid, ensure that you are wearing the

appropriate personal protective equipment according to the

incident, injury and surroundings.

If inhaled : No treatment necessary under normal conditions of use. If

symptoms persist, obtain medical advice.

In case of skin contact : Remove contaminated clothing. Flush exposed area with wa-

ter and follow by washing with soap if available.

If persistent irritation occurs, obtain medical attention.

In case of eye contact : Flush eye with copious quantities of water.

Remove contact lenses, if present and easy to do. Continue

rinsing.

If persistent irritation occurs, obtain medical attention.

If swallowed : In general no treatment is necessary unless large quantities

are swallowed, however, get medical advice.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Not considered to be an inhalation hazard under normal con-

ditions of use.

Possible respiratory irritation signs and symptoms may include a temporary burning sensation of the nose and throat, cough-

ing, and/or difficulty breathing.

Defatting dermatitis signs and symptoms may include a burn-

ing sensation and/or a dried/cracked appearance.

No specific hazards under normal use conditions.

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 45

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 17.11.2023

 5.0
 29.04.2024
 800001001064
 Print Date 06.05.2024

Eye irritation signs and symptoms may include a burning sen-

sation, redness, swelling, and/or blurred vision.

No specific hazards under normal use conditions.

Ingestion may result in nausea, vomiting and/or diarrhoea.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Call a doctor or poison control center for guidance.

Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam, water spray or fog. Dry chemical pow-

der, carbon dioxide, sand or earth may be used for small fires

only.

Unsuitable extinguishing

media

Do not use water in a jet.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

Carbon monoxide may be evolved if incomplete combustion

occurs.

Will float and can be reignited on surface water.

The vapour is heavier than air, spreads along the ground and

distant ignition is possible.

5.3 Advice for firefighters

Special protective equipment:

for firefighters

Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to

relevant Standards (e.g. Europe: EN469).

Specific extinguishing meth-

ods

Standard procedure for chemical fires.

Further information : Clear fire area of all non-emergency personnel.

Keep adjacent containers cool by spraying with water.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions

Observe all relevant local and international regulations. Notify authorities if any exposure to the general public or the

environment occurs or is likely to occur.

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 45

Date of last issue: 17.11.2023 Version Revision Date: SDS Number:

5.0 29.04.2024 800001001064 Print Date 06.05.2024

> Local authorities should be advised if significant spillages cannot be contained.

6.1.1 For non emergency personnel:

Avoid contact with spilled or released material. Immediately remove all contaminated clothing. For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet. For guidance on disposal of spilled material see

Section 13 of this Safety Data Sheet. Stay upwind and keep out of low areas. Be ready for fire or possible exposure. 6.1.2 For emergency responders:

Avoid contact with spilled or released material. Immediately remove all contaminated clothing. For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet. For guidance on disposal of spilled material see

Section 13 of this Safety Data Sheet. Stay upwind and keep out of low areas. Be ready for fire or possible exposure.

6.2 Environmental precautions

Environmental precautions Prevent from spreading or entering into drains, ditches or riv-

ers by using sand, earth, or other appropriate barriers.

Use appropriate containment to avoid environmental contami-

nation.

Ventilate contaminated area thoroughly.

6.3 Methods and material for containment and cleaning up

For large liquid spills (> 1 drum), transfer by mechanical Methods for cleaning up

means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely For small liquid spills (< 1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove

contaminated soil and dispose of safely.

6.4 Reference to other sections

For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet., For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures Avoid breathing of or direct contact with material. Only use in

well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see

Section 8 of this Safety Data Sheet.

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 45

Version Revision Date: SDS Number: Date of last issue: 17.11.2023 5.0 29.04.2024 800001001064 Print Date 06.05.2024

Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this

material.

Ensure that all local regulations regarding handling and stor-

age facilities are followed.

Advice on safe handling : Avoid contact with skin, eyes and clothing.

Do not empty into drains.

Sudden Release of Pressure Hazard

Product Transfer : Keep containers closed when not in use. Do not use com-

pressed air for filling discharge or handling.

Hygiene measures : Wash hands before eating, drinking, smoking and using the

toilet. Launder contaminated clothing before re-use.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Refer to section 15 for any additional specific legislation cov-

ering the packaging and storage of this product.

Storage class (TRGS 510) : 10, Combustible liquids

Further information on stor-

age stability

Bulk storage tanks should be diked (bunded).

Vapours from tanks should not be released to atmosphere. Breathing losses during storage should be controlled by a

suitable vapour treatment system.

Nitrogen blanket recommended for large tanks (capacity 100

m3 or higher).

Insulation (lagging) will minimize heat loss in areas of low

ambient temperature.

Tanks should be fitted with heating coils in areas where ambient conditions can result in handling temperatures below the

freezing point/pour point of the product.

Packaging material : Suitable material: Stainless steel., Epoxy resins, Polyester.

Unsuitable material: Aluminum, Copper., Copper alloys.

Container Advice : Containers, even those that have been emptied, can contain

explosive vapours. Do not cut, drill, grind, weld or perform

similar operations on or near containers.

7.3 Specific end use(s)

Specific use(s) : Please refer to section 16 and/or the annexes for the regis-

tered uses under REACH.

Ensure that all local regulations regarding handling and stor-

age facilities are followed.

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 45

Version Revision Date: SDS Number: Date of last issue: 17.11.2023

5.0 29.04.2024 800001001064 Print Date 06.05.2024

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Biological occupational exposure limits

No biological limit allocated.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Remarks:	No DNEL value has been established.
----------	-------------------------------------

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name		Environmental Compartment	Value
Remarks:	Exposure assessments have not been presented for the environment		environment
	therefore	PNEC values not required.	

8.2 Exposure controls

Engineering measures

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

Adequate ventilation to control airborne concentrations.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

Eye washes and showers for emergency use.

General Information:

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

Personal protective equipment

Read in conjunction with the Exposure Scenario for your specific use contained in the Annex. The provided information is made in consideration of the PPE directive (Council Directive 89/686/EEC) and the CEN European Committee for Standardisation (CEN) standards.

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Eye protection : If material is handled such that it could be splashed into eyes,

protective eyewear is recommended. Approved to EU Standard EN166.

Hand protection

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 45

Date of last issue: 17.11.2023 Version Revision Date: SDS Number:

5.0 29.04.2024 800001001064 Print Date 06.05.2024

Remarks

Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. Longer term protection: Nitrile rubber gloves. Incidental contact/Splash protection: PVC or neoprene rubber gloves. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

Skin and body protection

Skin protection is not ordinarily required beyond standard work clothes.

It is good practice to wear chemical resistant gloves. Protective clothing approved to EU Standard EN14605.

Respiratory protection

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are unsuitable (e.g. airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing appa-

Where air-filtering respirators are suitable, select an appropriate combination of mask and filter.

If air-filtering respirators are suitable for conditions of use: Select a filter suitable for the combination of organic gases and vapours and particles meeting EN14387 and EN143 [Filter type A/P for use against certain organic gases and vapours with a boiling point >65°C (149°F) and for use

against particles].

Thermal hazards : Not applicable

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 45

Version Revision Date: SDS Number: Date of last issue: 17.11.2023

5.0 29.04.2024 800001001064 Print Date 06.05.2024

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : Waxy solid at 20 °C.

Colour : white

Odour : mild

Odour Threshold : Data not available

Melting / freezing point : 29 - 36 °C

Boiling point/boiling range : 289 °C (1013,0 hPa)

Flammability

Flammability (solid, gas) : Not classified as flammable but will burn.

Lower explosion limit and upper explosion limit / flammability limit

Upper explosion limit /

upper flammability limit

Data not available

Lower explosion limit /

Lower flammability limit

Data not available

Flash point : 157 °C

Method: ASTM D93 (PMCC)

Auto-ignition temperature : Data not available

Decomposition temperature

Decomposition tempera-

ture

Data not available

pH : Not applicable

Viscosity

Viscosity, dynamic : 14 mPa.s (40 °C)

Method: ASTM D445

50 mPa.s (35 °C) Method: ASTM D445

Viscosity, kinematic : 18 mm2/s (40 °C)

Method: ASTM D445

Solubility(ies)

Water solubility : ca. 0,2 mg/l negligible (25 °C)

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 45

Version Revision Date: SDS Number: Date of last issue: 17.11.2023

5.0 29.04.2024 800001001064 Print Date 06.05.2024

Partition coefficient: n-

octanol/water

: log Pow: 6 - 6,2

Vapour pressure : < 0,05 hPa (25 °C)

Relative density : 0,824 (38 °C)

Method: ASTM D4052

Density : 823 kg/m3 (40 °C)

Method: ASTM D4052

Relative vapour density : 7,5

Particle characteristics

Particle size : Data not available

9.2 Other information

Explosive properties : Not applicable

Oxidizing properties : Data not available

Evaporation rate : Data not available

Conductivity: > 10,000 pS/m

A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid, This material is not expected to be

a static accumulator.

Surface tension : Data not available

Molecular weight : 218 - 224 g/mol

SECTION 10: Stability and reactivity

10.1 Reactivity

Stable at normal ambient temperature and pressure. May oxidise in the presence of air.

10.2 Chemical stability

The product is chemically stable. Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : None known.

10.4 Conditions to avoid

Conditions to avoid : Extremes of temperature and direct sunlight.

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 45

SDS Number: Date of last issue: 17.11.2023 Version Revision Date:

5.0 29.04.2024 800001001064 Print Date 06.05.2024

10.5 Incompatible materials

Materials to avoid Copper.

Copper alloys.

Strong oxidising agents.

Aluminum

10.6 Hazardous decomposition products

None expected under normal use conditions.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of: exposure

Exposure may occur via inhalation, ingestion, skin absorption,

skin or eye contact, and accidental ingestion.

Acute toxicity

Components:

Alcohols, C14-15-branched and linear:

Acute oral toxicity Remarks: LD50 >5000 mg/kg

Low toxicity

Remarks: Low toxicity if inhaled. Acute inhalation toxicity

Based on available data, the classification criteria are not met.

Acute dermal toxicity Remarks: LD50 > 5000 mg/kg

Low toxicity

Skin corrosion/irritation

Components:

Alcohols, C14-15-branched and linear:

Remarks : Not irritating to skin.

Serious eye damage/eye irritation

Components:

Alcohols, C14-15-branched and linear:

Remarks : Not irritating to eye.

Respiratory or skin sensitisation

Components:

Alcohols, C14-15-branched and linear:

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 45

Version Revision Date: SDS Number: Date of last issue: 17.11.2023

5.0 29.04.2024 800001001064 Print Date 06.05.2024

Remarks : Not a sensitiser.

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Components:

Alcohols, C14-15-branched and linear:

Genotoxicity in vivo : Remarks: Non mutagenic

Germ cell mutagenicity- As-

sessment

This product does not meet the criteria for classification in

categories 1A/1B.

Carcinogenicity

Components:

Alcohols, C14-15-branched and linear:

Remarks : Not a carcinogen

Based on available data, the classification criteria are not met.

Carcinogenicity - Assess-

ment

This product does not meet the criteria for classification in

categories 1A/1B.

Material	GHS/CLP Carcinogenicity Classification
Alcohols, C14-15-branched and linear	No carcinogenicity classification.

Reproductive toxicity

Components:

Alcohols, C14-15-branched and linear:

Effects on fertility :

Remarks: Data not available

Reproductive toxicity - As-

sessment

This product does not meet the criteria for classification in

categories 1A/1B.

STOT - single exposure

Components:

Alcohols, C14-15-branched and linear:

Remarks : Based on available data, the classification criteria are not met.

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 45

SDS Number: Date of last issue: 17.11.2023 Version Revision Date:

5.0 29.04.2024 800001001064 Print Date 06.05.2024

STOT - repeated exposure

Components:

Alcohols, C14-15-branched and linear:

Based on available data, the classification criteria are not met. Remarks

Aspiration toxicity

Components:

Alcohols, C14-15-branched and linear:

Not an aspiration hazard., Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

Further information

Product:

Remarks Unless indicated otherwise, the data presented is representa-

tive of the product as a whole, rather than for individual com-

ponent(s).

Components:

Alcohols, C14-15-branched and linear:

Remarks Classifications by other authorities under varying regulatory

frameworks may exist.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Alcohols, C14-15-branched and linear:

Toxicity to fish : Remarks: No toxicity at the limit of solubility

aquatic invertebrates

Toxicity to daphnia and other : Remarks: No toxicity at the limit of solubility

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 45

Version Revision Date: SDS Number: Date of last issue: 17.11.2023

5.0 29.04.2024 800001001064 Print Date 06.05.2024

Toxicity to algae/aquatic plants : Remarks: LC/EC/IC50 < 1 mg/l

Toxicity to microorganisms :

Remarks: Data not available

Toxicity to fish (Chronic tox-

icity)

Remarks: Data not available

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

ic toxicity)

Remarks: Data not available

12.2 Persistence and degradability

Components:

Alcohols, C14-15-branched and linear:

Biodegradability : Remarks: Readily biodegradable.

12.3 Bioaccumulative potential

Components:

Alcohols, C14-15-branched and linear:

Bioaccumulation : Remarks: Has the potential to bioaccumulate.

Log Kow > =4

12.4 Mobility in soil

Components:

Alcohols, C14-15-branched and linear:

Mobility : Remarks: Floats on water., Adsorbs to soil and has low mobili-

ty

12.5 Results of PBT and vPvB assessment

Components:

Alcohols, C14-15-branched and linear:

Assessment : The substance does not fulfill all screening criteria for persis-

tence, bioaccumulation and toxicity and hence is not consid-

ered to be PBT or vPvB..

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to

have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 45

Version Revision Date: SDS Number: Date of last issue: 17.11.2023

5.0 29.04.2024 800001001064 Print Date 06.05.2024

12.7 Other adverse effects

Product:

Additional ecological infor-

mation

Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Recover or recycle if possible.

It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal meth-

ods in compliance with applicable regulations.

Do not dispose into the environment, in drains or in water

courses.

Waste product should not be allowed to contaminate soil or

water.

Disposal should be in accordance with applicable regional,

national, and local laws and regulations.

Local regulations may be more stringent than regional or na-

tional requirements and must be complied with.

Contaminated packaging : Drain container thoroughly.

After draining, vent in a safe place away from sparks and fire.

Residues may cause an explosion hazard. Do not puncture, cut, or weld uncleaned drums. Send to drum recoverer or metal reclaimer.

SECTION 14: Transport information

14.1 UN number or ID number

ADN : 3082
ADR : 3082
RID : 3082
IMDG : 3082
IATA : 3082

14.2 UN proper shipping name

ADN : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(C12-C15 ALCOHOL)

ADR : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 45

Version Revision Date: SDS Number: Date of last issue: 17.11.2023

5.0 29.04.2024 800001001064 Print Date 06.05.2024

(C12-C15 ALCOHOL)

RID : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(C12-C15 ALCOHOL)

IMDG : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(C12-C15 ALCOHOL)

IATA : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(C12-C15 ALCOHOL)

14.3 Transport hazard class(es)

ADN : 9
ADR : 9
RID : 9
IMDG : 9
IATA : 9

14.4 Packing group

ADN

Packing group : III
Classification Code : M6
Labels : 9 (N2, F)

CDNI Inland Water Waste : NST 8969 Chemicals

Agreement

ADR

Packing group : III
Classification Code : M6
Hazard Identification Number : 90
Labels : 9

RID

Packing group : III
Classification Code : M6
Hazard Identification Number : 90
Labels : 9

IMDG

Packing group : III Labels : 9

IATA

Packing group : III Labels : 9

14.5 Environmental hazards

ADN

Environmentally hazardous : yes

ADR

Environmentally hazardous : yes

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 45

Version Revision Date: SDS Number: Date of last issue: 17.11.2023

29.04.2024 800001001064 Print Date 06.05.2024 5.0

RID

Environmentally hazardous : yes

IMDG

Marine pollutant yes

14.6 Special precautions for user

Remarks Special Precautions: Refer to Section 7, Handling & Storage,

for special precautions which a user needs to be aware of or

needs to comply with in connection with transport.

14.7 Maritime transport in bulk according to IMO instruments

Pollution category : Y Ship type

Product name : Alcohols (C13+)

Additional Information : This product may be transported under nitrogen blanketing.

> Nitrogen is an odourless and invisible gas. Exposure to nitrogen enriched atmospheres displaces available oxygen which may cause asphyxiation or death. Personnel must observe strict safety precautions when involved with a confined space

Transport in bulk according to Annex II of Marpol and the IBC

Code

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances.

mixtures and articles (Annex XVII)

: Not applicable

REACH - List of substances subject to authorisation

(Annex XIV)

: Product is not subject to Authorisa-

tion under REACH.

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH),

Article 57).

Water hazard class (Germa-

ny)

WGK 2 obviously hazardous to water

Remarks: Code Number: 8061, Classification according to

AwSV

Other regulations:

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 45

Version Revision Date: SDS Number: Date of last issue: 17.11.2023

5.0 29.04.2024 800001001064 Print Date 06.05.2024

Product is subject to Stoerfallverordnung (12. BlmSchV) based on Seveso III directive (2012/18/EU).

The components of this product are reported in the following inventories:

DSL : Listed

IECSC : Listed

KECI : Listed

NZIoC : Listed

PICCS : Listed

TSCA : Listed

TCSI : Listed

AIIC : Listed

ENCS : Listed

15.2 Chemical safety assessment

A Chemical Safety Assessment has been carried out for this substance.

SECTION 16: Other information

Full text of other abbreviations

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways: ADR - Agreement concerning the International Carriage of Dangerous Goods by Road: AIIC - Australian Inventory of Industrial Chemicals: ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA -European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association: IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - Interna-

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 45

Version Revision Date: SDS Number: Date of last issue: 17.11.2023

5.0 29.04.2024 800001001064 Print Date 06.05.2024

tional Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Training advice : Provide adequate information, instruction and training for op-

erators.

Other information : For Industry guidance and tools on REACH please visit the

CEFIC website at http://cefic.org/Industry-support.

The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not consid-

ered to be PBT or vPvB.

A vertical bar (|) in the left margin indicates an amendment

from the previous version.

Sources of key data used to compile the Safety Data

Sheet

The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU

IUCLID date base, EC 1272 regulation, etc).

Identified Uses according to the Use Descriptor System

Uses - Worker

Title : Manufacture of substance

- Industrial

Uses - Worker

Title : Use as an intermediate

- Industrial

Uses - Worker

Title : Formulation & (re)packing of substances and mixtures

- Industrial

Uses - Worker

Title : Uses in Coatings

- Industrial

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 45

Version Revision Date: SDS Number: Date of last issue: 17.11.2023

5.0 29.04.2024 800001001064 Print Date 06.05.2024

Uses - Worker

Title : Uses in Coatings

- Professional

Uses - Worker

Title : Use in Cleaning Agents

- Industrial

Uses - Worker

Title : Use in Cleaning Agents

- Professional

Uses - Worker

Title : Metal working fluids / rolling oils

- Industrial

Uses - Worker

Title : Metal working fluids / rolling oils

- Professional

Identified Uses according to the Use Descriptor System

Uses - Consumer

Title : Uses in Coatings

- Consumer

Uses - Consumer

Title : Use in Cleaning Agents

- Consumer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

DE / EN

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 45

Version Revision Date: SDS Number: Date of last issue: 17.11.2023

5.0 29.04.2024 800001001064 Print Date 06.05.2024

Exposure Scenario - Worker

Exposure Scenario - Worker	
30000000622	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Manufacture of substance- Industrial
Use Descriptor	Sector of Use: SU3, SU8, SU9 Process Categories: PROC 1, PROC 2, PROC 3, PROC 4, PROC 8a, PROC 8b, PROC 15 Environmental Release Categories: ERC1
Scope of process	Manufacture of the substance or use as a process chemical or extraction agent. Includes recycling/ recovery, material transfers, storage, maintenance and loading (including marine vessel/barge, road/rail car and bulk container), sampling and associated laboratory activities.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Additional Information	No exposure assessment presented for human health.	
Section 2.1	Control of Worker Exposure	
Product Characteristics		
Contributing Scenarios	Risk Management Measures	
Section 2.2	Control of Environmental Exposure	
Substance is complex UVCE	3.	
Alcohol.		
Readily biodegradable.		
Amounts Used		
Fraction of EU tonnage used		
Regional use tonnage (tonne		
Fraction of Regional tonnage	•	
Annual site tonnage (tonnes/year):		13,900
Maximum daily site tonnage (kg/day):		4,63E+04
Frequency and Duration o	f Use	
Continuous release.		
Emission Days (days/year):		300
	influenced by risk management	T
Local freshwater dilution fac		10
Local marine water dilution f		100
	ons affecting Environmental Exposure	
	process (initial release prior to RMM):	
RMM):	ter from process (initial release prior to	
	process (initial release prior to RMM):	
	measures at process level (source) to p	prevent release
	ess sites thus conservative process re-	
lease estimates used.		
Technical onsite condition	s and measures to reduce or limit disc	harges, air emis-

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 45

Version Revision Date: SDS Number: Date of last issue: 17.11.2023

5.0 29.04.2024 800001001064 Print Date 06.05.2024

sions and releases to soil	1
Risk from environmental exposure is driven by soil.	
Prevent discharge of undissolved substance to or recover from onsite	
wastewater.	
If discharging to domestic sewage treatment plant, no secondary	
wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	0
Treat onsite wastewater (prior to receiving water discharge) to provide	99
the required removal efficiency of >= (%)	
If discharging to domestic sewage treatment plant, no secondary	0
wastewater treatment required.	
Organisational measures to prevent/limit release from site	
Do not apply industrial sludge to natural soils.	
Sludge should be incinerated, contained or reclaimed.	
Conditions and Measures related to municipal sewage treatment p	lant
Estimated substance removal from wastewater via domestic sewage	99
treatment (%)	
Total efficiency of removal from wastewater after onsite and offsite	99
(domestic treatment plant) RMMs (%)	
Assumed domestic sewage treatment plant flow (m3/d)	10.000
Maximum allowable site tonnage (MSafe) based on release following	
total wastewater treatment removal (kg/d)	
Conditions and Measures related to external treatment of waste for	r disposal
During manufacturing no waste of the substance is generated.	
· · · · · · · · · · · · · · · · · · ·	
Conditions and measures related to external recovery of waste	
During manufacturing no waste of the substance is generated.	

SECTION 3	EXPOSURE ESTIMATION	
Section 3.1 - Health		
No exposure assessment pre	No exposure assessment presented for human health.	

Section 3.2 -Environment	
Used EUSES model.	

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO	
Section 4.1 - Health		
No exposure assessment presented for human health.		

Section 4.2 - Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 45

Version Revision Date: SDS Number: Date of last issue: 17.11.2023

5.0 29.04.2024 800001001064 Print Date 06.05.2024

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required.

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 45

Version Revision Date: SDS Number: Date of last issue: 17.11.2023

5.0 29.04.2024 800001001064 Print Date 06.05.2024

Exposure Scenario - Worker

30000000623	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Use as an intermediate- Industrial
Use Descriptor	Sector of Use: SU3, SU8, SU9 Process Categories: PROC 1, PROC 2, PROC 3, PROC 4, PROC 8a, PROC 8b, PROC 15 Environmental Release Categories: ERC6a
Scope of process	Use of substance as an intermediate (not related to Strictly Controlled Conditions). Includes recycling/ recovery, material transfers, storage, sampling, associated laboratory activities, maintenance and loading (including marine vessel/barge, road/rail car and bulk container).

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Additional Information	No exposure assessment presented for human health.	
Section 2.1	Control of Worker Exposure	
Product Characteristics		
Contributing Scenarios	Risk Management Measures	
Section 2.2	Control of Environmental Exposure	
Substance is complex UVCB		
Alcohol.		
Readily biodegradable.		
Amounts Used		
Fraction of EU tonnage used	in region:	
Regional use tonnage (tonne		
Fraction of Regional tonnage		
Annual site tonnage (tonnes/year):		1,870
Maximum daily site tonnage (kg/day):		6,233
Frequency and Duration of	Use	
Continuous release.		
Emission Days (days/year):		300
	influenced by risk management	
Local freshwater dilution fact		10
Local marine water dilution fa		100
	ns affecting Environmental Exposure	
	rocess (initial release prior to RMM):	3,80E-05
Release fraction to wastewater from process (initial release prior to RMM):		0,007
	process (initial release prior to RMM):	
	neasures at process level (source) to p	revent release
Common practices vary acrollease estimates used.	ss sites thus conservative process re-	
Technical onsite condition	s and measures to reduce or limit disc	harges, air emis-

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 45

Version Revision Date: SDS Number: Date of last issue: 17.11.2023

5.0 29.04.2024 800001001064 Print Date 06.05.2024

sions and releases to soil	
Risk from environmental exposure is driven by marine water.	
Prevent discharge of undissolved substance to or recover from onsite	
wastewater.	
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	0
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)	99
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	0
Organisational measures to prevent/limit release from site	
Do not apply industrial sludge to natural soils.	
Sludge should be incinerated, contained or reclaimed.	
Conditions and Measures related to municipal sewage treatment p	lant
Estimated substance removal from wastewater via domestic sewage treatment (%)	99
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	99
Assumed domestic sewage treatment plant flow (m3/d)	10.000
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	
Conditions and Measures related to external treatment of waste fo	r disposal
External treatment and disposal of waste should comply with applicable regulations.	· ·
This substance is consumed during use and no waste of substance is g	generated.
Conditions and measures related to external recovery of waste	
External recovery and recycling of waste should comply with applicable regulations.	
This substance is consumed during use and no waste of substance is g	roporated

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
No exposure assessment pre	sented for human health.

Section 3.2 -Environment	
Used EUSES model.	

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	
No exposure assessment presented for human health.	

Section 4.2 -Environment
Guidance is based on assumed operating conditions which may not be applicable to all

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 45

Version Revision Date: SDS Number: Date of last issue: 17.11.2023

5.0 29.04.2024 800001001064 Print Date 06.05.2024

sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required.

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 45

Version Revision Date: SDS Number: Date of last issue: 17.11.2023

5.0 29.04.2024 800001001064 Print Date 06.05.2024

Exposure Scenario - Worker

Exposure Scenario - Worker	
30000000624	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Formulation & (re)packing of substances and mixtures- Industrial
Use Descriptor	Sector of Use: SU3, SU10 Process Categories: PROC 1, PROC 2, PROC 3, PROC 4, PROC 5, PROC 8a, PROC 8b, PROC 9, PROC 14, PROC 15 Environmental Release Categories: ERC2
Scope of process	Formulation, packing and re-packing of the substance and its mixtures in batch or continuous operations, including storage, materials transfers, mixing, tabletting, compression, pelletisation, extrusion, large and small scale packing, sampling, maintenance and associated laboratory activities.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Additional Information	No exposure assessment presented for	r human health.
Section 2.1	Control of Worker Exposure	
Product Characteristics		
Contributing Scenarios	Risk Management Measures	
Section 2.2	Control of Environmental Exposure	
Substance is complex UVCB		
Alcohol.		
Readily biodegradable.		
Amounts Used		
Fraction of EU tonnage used		
Regional use tonnage (tonne		
Fraction of Regional tonnage		
Annual site tonnage (tonnes/year): 200		200
Maximum daily site tonnage (kg/day): 666,7		666,7
Frequency and Duration of	Use	
Continuous release.		
Emission Days (days/year):		300
	influenced by risk management	
Local freshwater dilution fact		10
Local marine water dilution fa		100
	ns affecting Environmental Exposure	1000504
	rocess (initial release prior to RMM):	3,60E-04
Release fraction to wastewater from process (initial release prior to		2,00E-05
RMM):	anne de Caritiel and anne anima to DAMA	
	process (initial release prior to RMM):	wayyant valaasa
	neasures at process level (source) to p	prevent release
lease estimates used.	ss sites thus conservative process re-	
lease estimates used.		

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 45

Version Revision Date: SDS Number: Date of last issue: 17.11.2023

5.0 29.04.2024 800001001064 Print Date 06.05.2024

Technical onsite conditions and measures to reduce or limit discharges and releases to soil	arges, air emis-
Risk from environmental exposure is driven by marine water.	
Prevent discharge of undissolved substance to or recover from onsite wastewater.	
If discharging to domestic sewage treatment plant, no secondary	
wastewater treatment required. Treat air emission to provide a typical removal efficiency of (%)	0
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)	99
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	0
Organisational measures to prevent/limit release from site	
Sludge should be incinerated, contained or reclaimed.	
Conditions and Measures related to municipal sewage treatment p	lant
Estimated substance removal from wastewater via domestic sewage treatment (%)	99
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	99
Assumed domestic sewage treatment plant flow (m3/d)	10.000
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	
Conditions and Measures related to external treatment of waste for	r disposal
External treatment and disposal of waste should comply with applicable regulations.	local and/or regional
Conditions and measures related to external recovery of waste	
External recovery and recycling of waste should comply with applicable regulations.	local and/or regional

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
No exposure assessment presented for human health.	

Section 3.2 -Environment	
Used EUSES model.	

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	
No exposure assessment presented for human health.	

Section 4.2 -Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 45

Version Revision Date: SDS Number: Date of last issue: 17.11.2023

5.0 29.04.2024 800001001064 Print Date 06.05.2024

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required.

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 45

Version Revision Date: SDS Number: Date of last issue: 17.11.2023

5.0 29.04.2024 800001001064 Print Date 06.05.2024

Exposure Scenario - Worker

30000000625	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Uses in Coatings- Industrial
Use Descriptor	Sector of Use: SU3 Process Categories: PROC 1, PROC 2, PROC 3, PROC 4, PROC 5, PROC 7, PROC 8a, PROC 8b, PROC 10, PROC 13, PROC 15 Environmental Release Categories: ERC4
Scope of process	Covers the use in coatings (paints, inks, adhesives, etc) including exposures during use (including materials receipt, storage, preparation and transfer from bulk and semi-bulk, application by spray, roller, spreader, dip, flow, fluidised bed on production lines and film formation) and equipment cleaning, maintenance and associated laboratory activities.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Additional Information	No exposure assessment presented for	human health.
Section 2.1	Control of Worker Exposure	
Product Characteristics		
Contributing Scenarios	Risk Management Measures	
Section 2.2	Control of Environmental Exposure	
Substance is complex UVCB	•	
Alcohol.		
Readily biodegradable.		
Amounts Used		
Fraction of EU tonnage used	in region:	7,500
Regional use tonnage (tonne	s/year):	
Fraction of Regional tonnage	used locally:	
Annual site tonnage (tonnes/year):		0,029
Maximum daily site tonnage (kg/day):		0,1
Frequency and Duration of	Use	
Continuous release.		
Emission Days (days/year):		300
	influenced by risk management	
Local freshwater dilution fact	or:	10
Local marine water dilution factor:		100
	ns affecting Environmental Exposure	
Release fraction to air from process (initial release prior to RMM):		0,03
Release fraction to wastewat RMM):	er from process (initial release prior to	0,03
	process (initial release prior to RMM):	
	neasures at process level (source) to p	revent release
Common practices vary acro-	ss sites thus conservative process re-	

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 45

Version Revision Date: SDS Number: Date of last issue: 17.11.2023

5.0 29.04.2024 800001001064 Print Date 06.05.2024

lease estimates used.	
Technical onsite conditions and measures to reduce or limit disch	arges, air emis-
sions and releases to soil	
Risk from environmental exposure is driven by marine water.	
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	0
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)	99
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	0
Organisational measures to prevent/limit release from site	
Sludge should be incinerated, contained or reclaimed.	
Conditions and Measures related to municipal sewage treatment p	lant
Estimated substance removal from wastewater via domestic sewage treatment (%)	99
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	99
Assumed domestic sewage treatment plant flow (m3/d)	2.000
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	
Conditions and Measures related to external treatment of waste fo	r disposal
External treatment and disposal of waste should comply with applicable regulations.	
Conditions and measures related to external recovery of waste	
External recovery and recycling of waste should comply with applicable regulations.	local and/or regional

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
No exposure assessment pre	sented for human health.

Section 3.2 -Environment	
Used EUSES model.	

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO	
Section 4.1 - Health		
No exposure assessment pre	No exposure assessment presented for human health.	

Section 4.2 - Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technolo-

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 45

Version Revision Date: SDS Number: Date of last issue: 17.11.2023

5.0 29.04.2024 800001001064 Print Date 06.05.2024

gies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required.

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 45

Version Revision Date: SDS Number: Date of last issue: 17.11.2023

5.0 29.04.2024 800001001064 Print Date 06.05.2024

Exposure Scenario - Worker

30000000626	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Uses in Coatings- Professional
Use Descriptor	Sector of Use: SU22 Process Categories: PROC 1, PROC 2, PROC 3, PROC 4, PROC 5, PROC 8a, PROC 8b, PROC 10, PROC 11, PROC 13, PROC 15, PROC 19 Environmental Release Categories: ERC8a, ERC8d
Scope of process	Covers the use in coatings (paints, inks, adhesives, etc) including exposures during use (including materials receipt, storage, preparation and transfer from bulk and semi-bulk, application by spray, roller, brush, spreader by hand or similar methods, and film formation), and equipment cleaning, maintenance and associated laboratory activities.

SECTION 2	OPERATIONAL CONDITIONS AND RI MEASURES	SK MANAGEMENT
Additional Information	No exposure assessment presented for	human health.
Section 2.1	Control of Worker Exposure	
Product Characteristics		
Contributing Scenarios	Risk Management Measures	
Section 2.2	Control of Environmental Exposure	
Substance is complex UVCB.		
Alcohol.		
Readily biodegradable.		
Amounts Used		
Fraction of EU tonnage used		
Regional use tonnage (tonne	s/year):	
Fraction of Regional tonnage		
Annual site tonnage (tonnes/year):		0,87
Maximum daily site tonnage (kg/day):		2,9
Frequency and Duration of	Use	
Continuous release.		
Emission Days (days/year):		300
	nfluenced by risk management	
Local freshwater dilution factor		10
Local marine water dilution factor:		100
	ns affecting Environmental Exposure	1
Release fraction to air from process (initial release prior to RMM):		0,01
Release fraction to wastewate RMM):	er from process (initial release prior to	0,01
	process (initial release prior to RMM):	
	neasures at process level (source) to p	revent release
Common practices vary acros	ss sites thus conservative process re-	

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 45

Version Revision Date: SDS Number: Date of last issue: 17.11.2023

5.0 29.04.2024 800001001064 Print Date 06.05.2024

leans actimates used	1
lease estimates used. Technical onsite conditions and measures to reduce or limit discharge.	arge air emie-
sions and releases to soil	arges, an enns-
Risk from environmental exposure is driven by marine water.	
If discharging to domestic sewage treatment plant, no secondary	
wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	0
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)	99
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	0
Organisational measures to prevent/limit release from site	
Sludge should be incinerated, contained or reclaimed.	
Conditions and Measures related to municipal sewage treatment p	lant
Estimated substance removal from wastewater via domestic sewage	99
treatment (%)	
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	99
Assumed domestic sewage treatment plant flow (m3/d)	2.000
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	
Conditions and Measures related to external treatment of waste for	r disposal
External treatment and disposal of waste should comply with applicable regulations.	local and/or regional
Conditions and measures related to external recovery of waste	
External recovery and recycling of waste should comply with applicable local and/or regional regulations.	

SECTION 3	EXPOSURE ESTIMATION	
Section 3.1 - Health		
No exposure assessment pre	No exposure assessment presented for human health.	

Section 3.2 -Environment	
Used EUSES model.	

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE
	EXPOSURE SCENARIO
Section 4.1 - Health	
No exposure assessment pre	sented for human health.

Section 4.2 - Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technolo-

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 45

Version Revision Date: SDS Number: Date of last issue: 17.11.2023

5.0 29.04.2024 800001001064 Print Date 06.05.2024

gies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required.

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 45

Version Revision Date: SDS Number: Date of last issue: 17.11.2023

5.0 29.04.2024 800001001064 Print Date 06.05.2024

Exposure Scenario - Worker

30000000628	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Use in Cleaning Agents- Industrial
Use Descriptor	Sector of Use: SU3 Process Categories: PROC 1, PROC 2, PROC 3, PROC 4, PROC 7, PROC 8a, PROC 8b, PROC 10, PROC 13 Environmental Release Categories: ERC4
Scope of process	Covers the use as a component of cleaning products including transfer from storage, pouring/unloading from drums or containers. Exposures during mixing/diluting in the preparatory phase and cleaning activities (including spraying, brushing, dipping, wiping, automated and by hand), related equipment cleaning and maintenance.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Additional Information	No exposure assessment presented for human health.	
Section 2.1	Control of Worker Exposure	
Product Characteristics		
Contributing Scenarios	Risk Management Measures	
Section 2.2	Control of Environmental Exposure	
Substance is complex UVCE	3.	
Alcohol.		
Readily biodegradable.		
Amounts Used		
Fraction of EU tonnage used in region:		
Regional use tonnage (tonnes/year):		
Fraction of Regional tonnage	e used locally:	
Annual site tonnage (tonnes/year):		0,96
Maximum daily site tonnage (kg/day):		4,36
Frequency and Duration of	f Use	
Continuous release.		
Emission Days (days/year):		220
	influenced by risk management	
Local freshwater dilution factor:		10
Local marine water dilution factor:		100
	ons affecting Environmental Exposure	
Release fraction to air from process (initial release prior to RMM):		0
Release fraction to wastewater from process (initial release prior to		1
RMM):	(1.11.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1	
	process (initial release prior to RMM):	
	measures at process level (source) to p	prevent release
Common practices vary across sites thus conservative process re- lease estimates used.		

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 45

Version Revision Date: SDS Number: Date of last issue: 17.11.2023

5.0 29.04.2024 800001001064 Print Date 06.05.2024

sions and releases to soil Risk from environmental exposure is driven by marine water.		
If discharging to domestic sewage treatment plant, no secondary		
wastewater treatment required.		
Treat air emission to provide a typical removal efficiency of (%)	0	
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)	99	
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	0	
Organisational measures to prevent/limit release from site		
Sludge should be incinerated, contained or reclaimed.		
Conditions and Measures related to municipal sewage treatment plant		
Estimated substance removal from wastewater via domestic sewage treatment (%)	99	
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	99	
Assumed domestic sewage treatment plant flow (m3/d)	2.000	
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)		
Conditions and Measures related to external treatment of waste fo	r disposal	
External treatment and disposal of waste should comply with applicable	local and/or regional	
regulations.		
Conditions and measures related to external recovery of waste		
External recovery and recycling of waste should comply with applicable local and/or regional regulations.		

SECTION 3	EXPOSURE ESTIMATION	
Section 3.1 - Health		
No exposure assessment presented for human health.		

Section 3.2 -Environment	
Used EUSES model.	

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO	
Section 4.1 - Health		
No exposure assessment presented for human health.		

Section 4.2 - Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 45

Version Revision Date: SDS Number: Date of last issue: 17.11.2023

5.0 29.04.2024 800001001064 Print Date 06.05.2024

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 45

Version Revision Date: SDS Number: Date of last issue: 17.11.2023

5.0 29.04.2024 800001001064 Print Date 06.05.2024

Exposure Scenario - Worker

30000000629	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Use in Cleaning Agents- Professional
Use Descriptor	Sector of Use: SU22 Process Categories: PROC 1, PROC 2, PROC 3, PROC 4, PROC 8a, PROC 8b, PROC 10, PROC 11, PROC 13 Environmental Release Categories: ERC8a, ERC8d
Scope of process	Covers the use as a component of cleaning products including pouring/unloading from drums or containers; and exposures during mixing/diluting in the preparatory phase and cleaning activities (including spraying, brushing, dipping, wiping automated and by hand).

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Additional Information	No exposure assessment presented for human health.	
Section 2.1	Control of Worker Exposure	
Product Characteristics		
Contributing Scenarios	Risk Management Measures	
Section 2.2	Control of Environmental Exposure	
Substance is complex UVC	B.	
Alcohol.		
Readily biodegradable.		
Amounts Used		
Fraction of EU tonnage use	d in region:	
Regional use tonnage (tonn	es/year):	
Fraction of Regional tonnag	e used locally:	
Annual site tonnage (tonnes/year):		0,52
Maximum daily site tonnage	e (kg/day):	1,42
Frequency and Duration of	of Use	
Continuous release.		
Emission Days (days/year):		365
	t influenced by risk management	
Local freshwater dilution fac		10
Local marine water dilution		100
	ons affecting Environmental Exposure	
Release fraction to air from process (initial release prior to RMM):		0
RMM):	ater from process (initial release prior to	1
Release fraction to soil from	process (initial release prior to RMM):	
	measures at process level (source) to p	prevent release
Common practices vary acr lease estimates used.	oss sites thus conservative process re-	
Technical onsite conditio	ns and measures to reduce or limit disc	harges, air emis-

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 45

Version Revision Date: SDS Number: Date of last issue: 17.11.2023

5.0 29.04.2024 800001001064 Print Date 06.05.2024

sions and releases to soil		
Risk from environmental exposure is driven by freshwater.		
If discharging to domestic sewage treatment plant, no secondary		
wastewater treatment required.		
Treat air emission to provide a typical removal efficiency of (%)	0	
Treat onsite wastewater (prior to receiving water discharge) to provide	99	
the required removal efficiency of >= (%)		
If discharging to domestic sewage treatment plant, no secondary	0	
wastewater treatment required.		
Organisational measures to prevent/limit release from site		
Sludge should be incinerated, contained or reclaimed.		
Conditions and Measures related to municipal sewage treatment p		
Estimated substance removal from wastewater via domestic sewage	99	
treatment (%)		
Total efficiency of removal from wastewater after onsite and offsite	99	
(domestic treatment plant) RMMs (%)		
Assumed domestic sewage treatment plant flow (m3/d)	2.000	
Maximum allowable site tonnage (MSafe) based on release following		
total wastewater treatment removal (kg/d)		
Conditions and Measures related to external treatment of waste for disposal		
External treatment and disposal of waste should comply with applicable local and/or regional		
regulations.		
Conditions and measures related to external recovery of waste		
External recovery and recycling of waste should comply with applicable local and/or regional		
regulations.		

SECTION 3	EXPOSURE ESTIMATION	
Section 3.1 - Health		
No exposure assessment presented for human health.		

Section 3.2 -Environment	
Used EUSES model.	

SECTION 4 GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO		
Section 4.1 - Health		
No exposure assessment presented for human health.		

Section 4.2 - Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 45

Version Revision Date: SDS Number: Date of last issue: 17.11.2023

5.0 29.04.2024 800001001064 Print Date 06.05.2024

or in combination.

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 45

Version Revision Date: SDS Number: Date of last issue: 17.11.2023

5.0 29.04.2024 800001001064 Print Date 06.05.2024

Exposure Scenario - Worker

Exposure Scenario - we	OI NEI
30000000632	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Metal working fluids / rolling oils- Industrial
Use Descriptor	Sector of Use: SU3 Process Categories: PROC 1, PROC 2, PROC 3, PROC 4, PROC 5, PROC 7, PROC 8a, PROC 8b, PROC 9, PROC 10, PROC 13, PROC 17 Environmental Release Categories: ERC4
Scope of process	Covers the use in formulated MWFs/rolling oils including transfer operations, rolling and annealing activities, cutting/machining activities, automated and manual application of corrosion protections (including brushing, dipping and spraying), equipment maintenance, draining and disposal of waste oils.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Additional Information	No exposure assessment presented for human health.	
Section 2.1	Control of Worker Exposure	
Product Characteristics		
Contributing Scenarios	Risk Management Measures	
Section 2.2	Control of Environmental Exposure	
Substance is complex UVCB.		
Alcohol.		
Readily biodegradable.		
Amounts Used		
Fraction of EU tonnage used	in region:	
Regional use tonnage (tonne		
Fraction of Regional tonnage		
Annual site tonnage (tonnes/		7,5
Maximum daily site tonnage (kg/day):		25
Frequency and Duration of	Use	
Continuous release.		
Emission Days (days/year):		300
	nfluenced by risk management	T-
Local freshwater dilution factor		10
Local marine water dilution factor:		100
	ns affecting Environmental Exposure	T-
Release fraction to air from process (initial release prior to RMM):		9,60E-03
Release fraction to wastewate RMM):	er from process (initial release prior to	2,08E-07
	process (initial release prior to RMM):	
	neasures at process level (source) to p	revent release
Common practices vary acros	ss sites thus conservative process re-	

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 45

Version Revision Date: SDS Number: Date of last issue: 17.11.2023

5.0 29.04.2024 800001001064 Print Date 06.05.2024

	1
lease estimates used.	
Technical onsite conditions and measures to reduce or limit disch	arges, air emis-
sions and releases to soil	1
Risk from environmental exposure is driven by marine water.	
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	0
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)	99
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	0
Organisational measures to prevent/limit release from site	
Sludge should be incinerated, contained or reclaimed.	
Conditions and Measures related to municipal sewage treatment p	lant
Estimated substance removal from wastewater via domestic sewage treatment (%)	99
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	99
Assumed domestic sewage treatment plant flow (m3/d)	2.000
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	
Conditions and Measures related to external treatment of waste for	r disposal
External treatment and disposal of waste should comply with applicable regulations.	local and/or regional
Conditions and measures related to external recovery of waste	
External recovery and recycling of waste should comply with applicable regulations.	local and/or regional

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
No exposure assessment presented for human health.	

Section 3.2 -Environment	
Used EUSES model.	

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE
	EXPOSURE SCENARIO
Section 4.1 - Health	
No exposure assessment presented for human health.	

Section 4.2 - Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technolo-

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 45

Version Revision Date: SDS Number: Date of last issue: 17.11.2023

5.0 29.04.2024 800001001064 Print Date 06.05.2024

gies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 45

Version Revision Date: SDS Number: Date of last issue: 17.11.2023

5.0 29.04.2024 800001001064 Print Date 06.05.2024

Exposure Scenario - Worker

30000000633	O I I I I I I I I I I I I I I I I I I I
SECTION 1 Title	EXPOSURE SCENARIO TITLE Metal working fluids / rolling oils- Professional
Use Descriptor	Sector of Use: SU22 Process Categories: PROC 1, PROC 2, PROC 3, PROC 5, PROC 8a, PROC 8b, PROC 9, PROC 10, PROC 11, PROC 13, PROC 17 Environmental Release Categories: ERC8a, ERC8d
Scope of process	Covers the use in formulated MWFs including transfer operations, open and contained cutting/machining activities, automated and manual application of corrosion protections, draining and working on contaminated/reject articles, and disposal of waste oils.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Additional Information	No exposure assessment presented for	r human health.
Section 2.1	Control of Worker Exposure	
Product Characteristics		
Contributing Scenarios	Risk Management Measures	
Section 2.2	Control of Environmental Exposure	
Substance is complex UVC	3.	
Alcohol.		
Readily biodegradable.		
Amounts Used		
Fraction of EU tonnage used	d in region:	
Regional use tonnage (tonne	es/year):	
Fraction of Regional tonnage	e used locally:	
Annual site tonnage (tonnes/year): 7,5		7,5
Maximum daily site tonnage (kg/day):		25
Frequency and Duration o	f Use	
Continuous release.		
Emission Days (days/year):		365
	influenced by risk management	
Local freshwater dilution fac		10
Local marine water dilution f		100
	ons affecting Environmental Exposure	
	process (initial release prior to RMM):	9,60E-03
Release fraction to wastewater from process (initial release prior to		2,08E-07
RMM):	7	
	process (initial release prior to RMM):	<u> </u>
	measures at process level (source) to p	prevent release
	oss sites thus conservative process re-	
lease estimates used.		

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 45

Version Revision Date: SDS Number: Date of last issue: 17.11.2023

5.0 29.04.2024 800001001064 Print Date 06.05.2024

Risk from environmental exposure is driven by marine water.	
If discharging to domestic sewage treatment plant, no secondary	
wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	0
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)	99
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	0
Organisational measures to prevent/limit release from site	
Sludge should be incinerated, contained or reclaimed.	
Conditions and Measures related to municipal sewage treatment p	lant
Estimated substance removal from wastewater via domestic sewage treatment (%)	99
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	99
Assumed domestic sewage treatment plant flow (m3/d)	2.000
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	
Conditions and Measures related to external treatment of waste fo	r disposal
External treatment and disposal of waste should comply with applicable	local and/or regional
regulations.	
Conditions and measures related to external recovery of waste	
External recovery and recycling of waste should comply with applicable regulations.	local and/or regional

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
No exposure assessment presented for human health.	

Section 3.2 -Environment	
Used EUSES model.	

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	
No exposure assessment presented for human health.	

Section 4.2 - Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 45

Version Revision Date: SDS Number: Date of last issue: 17.11.2023

5.0 29.04.2024 800001001064 Print Date 06.05.2024

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 45

Version Revision Date: SDS Number: Date of last issue: 17.11.2023

5.0 29.04.2024 800001001064 Print Date 06.05.2024

Exposure Scenario - Consumer

30000001085	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Uses in Coatings - Consumer
Use Descriptor	Sector of Use: SU21 Product Categories: PC1, PC4, PC8 (excipient only), PC9a, PC9b, PC9c, PC15, PC18, PC23, PC24, PC31, PC34 Environmental Release Categories: ERC8a, ERC8d
Scope of process	Covers the use in coatings (paints, inks, adhesives, etc) including exposures during use (including product transfer and preparation, application by brush, spray by hand or similar methods) and equipment cleaning.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
Additional Information	No exposure assessment presented for human health.
Section 2.1	Control of Consumer Exposure
Product Characteristics	
Product Categories	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES

Section 2.2	Control of Environmental Exposure	
Substance is complex UVCB.		
Alcohol.		
Readily biodegradable.		
Amounts Used		
Fraction of EU tonnage used	in region:	
Regional use tonnage (tonne	s/year):	
Fraction of Regional tonnage used locally:		
Annual site tonnage (tonnes/year):		0,87
Maximum daily site tonnage (kg/day):		2,9
Frequency and Duration of	Use	
Continuous release.		
Emission Days (days/year):		300
	influenced by risk management	
Local freshwater dilution factor	or:	10
Local marine water dilution factor:		100
	ns affecting Environmental Exposure	
	rocess (initial release prior to RMM):	0,01
Release fraction to wastewater from process (initial release prior to		0,01
RMM):		
Release fraction to soil from process (initial release prior to RMM):		
Conditions and Measures related to municipal sewage treatment plant		olant
	osure is driven by marine water.	
Estimated substance remova	I from wastewater via domestic sewage	99

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 45

Version Revision Date: SDS Number: Date of last issue: 17.11.2023

5.0 29.04.2024 800001001064 Print Date 06.05.2024

treatment (%)	
Assumed domestic sewage treatment plant flow (m3/d)	2.000
Maximum allowable site tonnage (MSafe) based on release following	
total wastewater treatment removal (kg/d)	

Conditions and Measures related to external treatment of waste for disposal

External treatment and disposal of waste should comply with applicable local and/or regional regulations.

Conditions and measures related to external recovery of waste

External recovery and recycling of waste should comply with applicable local and/or regional regulations.

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
No exposure assessment presented for human health.	

Section 3.2 - Environment

Used EUSES model.

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	
No exposure assessment presented for human health.	

Section 4.2 - Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 45

Version Revision Date: SDS Number: Date of last issue: 17.11.2023

5.0 29.04.2024 800001001064 Print Date 06.05.2024

Exposure Scenario - Consumer

30000001086	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Use in Cleaning Agents - Consumer
Use Descriptor	Sector of Use: SU21 Product Categories: PC3, PC4, PC8 (excipient only), PC9a, PC9b, PC9c, PC24, PC35, PC38 Environmental Release Categories: ERC8a, ERC8d
Scope of process	Covers general exposures to consumers arising from the use of household products sold as washing and cleaning products, aerosols, coatings, de-icers, lubricants and air care products.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
Additional Information	No exposure assessment presented for human health.
Section 2.1	Control of Consumer Exposure
Product Characteristics	
Product Categories	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES

Section 2.2	Control of Environmental Exposure	
Substance is complex UVCB.		
Alcohol.		
Readily biodegradable.		
Amounts Used		
Fraction of EU tonnage used	in region:	
Regional use tonnage (tonne	es/year):	
Fraction of Regional tonnage		
Annual site tonnage (tonnes/year):		0,28
Maximum daily site tonnage		0,78
Frequency and Duration of	Use	
Continuous release.		
Emission Days (days/year):		365
	influenced by risk management	
Local freshwater dilution fact		10
Local marine water dilution factor:		100
	ns affecting Environmental Exposure	T
	rocess (initial release prior to RMM):	0
Release fraction to wastewater from process (initial release prior to		1
RMM):		
Release fraction to soil from process (initial release prior to RMM):		
Conditions and Measures related to municipal sewage treatment plant		plant
	osure is driven by freshwater.	
Estimated substance remova	al from wastewater via domestic sewage	99

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 45

Version Revision Date: SDS Number: Date of last issue: 17.11.2023

5.0 29.04.2024 800001001064 Print Date 06.05.2024

treatment (%)	
Assumed domestic sewage treatment plant flow (m3/d)	2.000
Maximum allowable site tonnage (MSafe) based on release following	
total wastewater treatment removal (kg/d)	

Conditions and Measures related to external treatment of waste for disposal

External treatment and disposal of waste should comply with applicable local and/or regional regulations.

Conditions and measures related to external recovery of waste

External recovery and recycling of waste should comply with applicable local and/or regional regulations.

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
No exposure assessment presented for human health.	

Section 3.2 - Environment

Used EUSES model.

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	
No exposure assessment presented for human health.	

Section 4.2 - Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.