According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## **NEODOL 135**

Version Revision Date: SDS Number: Print Date: 01/30/2025

5.0 01/23/2025 800001012062 Date of last issue: 07/18/2024

#### **SECTION 1. IDENTIFICATION**

: NEODOL 135 Product name

Product code V2483, V2501

#### Manufacturer or supplier's details

: Shell Chemical LP Company

PO Box 576

HOUSTON TX 77001

USA

SDS Request : 1-800-240-6737

**Customer Service** : 1-855-697-4355

**Emergency telephone number** 

Chemtrec Domestic (24 hr) : 1-800-424-9300

Chemtrec International (24

hr)

: 1-703-527-3887

### Recommended use of the chemical and restrictions on use

Recommended use

Feedstock for detergent derivative manufacture.

Restrictions on use This product must not be used in applications other than those

listed in Section 1 without first seeking the advice of the sup-

plier.

This product must not be used in applications other than the above without first seeking the advice of the supplier.

Other information NEODOL is a registered trademark of SHELL.

## **SECTION 2. HAZARDS IDENTIFICATION**

# GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR

1910.1200)

Skin irritation Category 2

Eye irritation Category 2

Short-term (acute) aquatic

hazard

Category 1

Long-term (chronic) aquatic Category 1

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## **NEODOL 135**

Version Revision Date: SDS Number: Print Date: 01/30/2025

5.0 01/23/2025 800001012062 Date of last issue: 07/18/2024

hazard

**GHS label elements** 

Hazard pictograms





Signal word : Warning

Hazard statements : PHYSICAL HAZARDS:

Not classified as a physical hazard under GHS criteria.

HEALTH HAZARDS:
H315 Causes skin irritation.
H319 Causes serious eye irritation.
ENVIRONMENTAL HAZARDS:
H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements : Prevention:

P264 Wash skin thoroughly after handling. P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protection/

face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing.

P321 Specific treatment (see .? on this label).

P332 + P313 If skin irritation occurs: Get medical attention. P337 + P313 If eye irritation persists: Get medical attention. P362 Take off contaminated clothing and wash before reuse.

P391 Collect spillage.

Storage:

No precautionary phrases.

Disposal:

P501 Dispose of contents and container to appropriate waste site or reclaimer in accordance with local and national regula-

tions.

Other hazards which do not result in classification

Repeated exposure may cause skin dryness or cracking.

The classification of this material is based on OSHA HCS 2012 criteria.

### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## **NEODOL 135**

Version Revision Date: SDS Number: Print Date: 01/30/2025 5.0 01/23/2025 800001012062 Date of last issue: 07/18/2024

#### **Hazardous components**

Chemical name	Synonyms	CAS-No.	Concentration (% w/w)
tridecan-1-ol	tridecan-1-ol	112-70-9	>= 35 - <= 50
Pentadecanol, branched and linear	Pentadecanol, branched and linear	90480-71-0	>= 35 - <= 50
Undecan-1-ol	undecan-1-ol	112-42-5	>= 10 - <= 18

#### **SECTION 4. FIRST-AID MEASURES**

General advice : Not expected to be a health hazard when used under normal

conditions.

If inhaled : No treatment necessary under normal conditions of use.

If symptoms persist, obtain medical advice.

In case of skin contact : Remove contaminated clothing. Immediately flush skin with

large amounts of water for at least 15 minutes, and follow by washing with soap and water if available. If redness, swelling, pain and/or blisters occur, transport to the nearest medical

facility for additional treatment.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses, if present and easy to do. Continue

rinsing.

Transport to the nearest medical facility for additional treat-

ment.

If swallowed : In general no treatment is necessary unless large quantities

are swallowed, however, get medical advice.

Most important symptoms and effects, both acute and

delayed

Not considered to be an inhalation hazard under normal con-

ditions of use.

Possible respiratory irritation signs and symptoms may include a temporary burning sensation of the nose and throat, cough-

ing, and/or difficulty breathing.

Skin irritation signs and symptoms may include a burning sen-

sation, redness, swelling, and/or blisters.

Eye irritation signs and symptoms may include a burning sen-

sation, redness, swelling, and/or blurred vision.

Ingestion may result in nausea, vomiting and/or diarrhoea.

Protection of first-aiders : When administering first aid, ensure that you are wearing the

appropriate personal protective equipment according to the

incident, injury and surroundings.

Indication of any immediate medical attention and special

medical attention and special treatment needed

Call a doctor or poison control center for guidance.

Treat symptomatically.

IMMEDIATE TREATMENT IS EXTREMELY IMPORTANT!

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## **NEODOL 135**

Version Revision Date: SDS Number: Print Date: 01/30/2025

5.0 01/23/2025 800001012062 Date of last issue: 07/18/2024

#### **SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media : Alcohol-resistant foam, water spray or fog. Dry chemical pow-

der, carbon dioxide, sand or earth may be used for small fires

only.

Unsuitable extinguishing

media

Do not use water in a jet.

Specific hazards during fire-

fighting

Carbon monoxide may be evolved if incomplete combustion

occurs

Will float and can be reignited on surface water.

The vapour is heavier than air, spreads along the ground and

distant ignition is possible.

Specific extinguishing meth-

ods

Standard procedure for chemical fires.

Further information Clear fire area of all non-emergency personnel.

Keep adjacent containers cool by spraying with water.

Special protective equipment :

for firefighters

Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if

large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to

relevant Standards (e.g. Europe: EN469).

## **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protec: : tive equipment and emer-

gency procedures

Observe all relevant local and international regulations. Notify authorities if any exposure to the general public or the

environment occurs or is likely to occur.

Local authorities should be advised if significant spillages

cannot be contained.

Avoid contact with spilled or released material. Immediately remove all contaminated clothing. For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet. For guidance on disposal of spilled material see

Section 13 of this Safety Data Sheet. Stay upwind and keep out of low areas. Be ready for fire or possible exposure.

Prevent from spreading or entering into drains, ditches or riv-Environmental precautions

ers by using sand, earth, or other appropriate barriers.

Use appropriate containment to avoid environmental contami-

nation.

Ventilate contaminated area thoroughly.

Methods and materials for containment and cleaning up For large liquid spills (> 1 drum), transfer by mechanical means such as vacuum truck to a salvage tank for recovery or

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## **NEODOL 135**

Version Revision Date: SDS Number: Print Date: 01/30/2025 5.0 01/23/2025 800001012062 Date of last issue: 07/18/2024

safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely For small liquid spills (< 1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.

Additional advice : For guidance on selection of personal protective equipment

see Section 8 of this Safety Data Sheet.

For guidance on disposal of spilled material see Section 13 of

this Safety Data Sheet.

U.S. regulations may require reporting releases of this material to the environment which exceed the reportable quantity (refer to Section 15) to the National Response Center at (800) 424-8802.

#### **SECTION 7. HANDLING AND STORAGE**

Technical measures : Avoid breathing of or direct contact with material. Only use in

well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see

Section 8 of this Safety Data Sheet.

Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this

material.

Ensure that all local regulations regarding handling and stor-

age facilities are followed.

Advice on safe handling : Avoid contact with skin, eyes and clothing.

Do not empty into drains.

Sudden Release of Pressure Hazard

Avoidance of contact : Copper.

Copper alloys.

Strong oxidising agents.

Aluminum

Product Transfer : Keep containers closed when not in use. Do not use com-

pressed air for filling discharge or handling.

Conditions for safe storage : Refer to section 15 for any additional specific legislation cov-

ering the packaging and storage of this product.

Further information on stor-

age stability

Bulk storage tanks should be diked (bunded).

Vapours from tanks should not be released to atmosphere. Breathing losses during storage should be controlled by a

suitable vapour treatment system.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## **NEODOL 135**

 Version
 Revision Date:
 SDS Number:
 Print Date: 01/30/2025

 5.0
 01/23/2025
 800001012062
 Date of last issue: 07/18/2024

Nitrogen blanket recommended for large tanks (capacity 100

m3 or higher).

Insulation (lagging) will minimize heat loss in areas of low

ambient temperature.

Tanks should be fitted with heating coils in areas where ambient conditions can result in handling temperatures below the

freezing point/pour point of the product.

Packaging material : Suitable material: Stainless steel., Epoxy resins, Polyester.

Unsuitable material: Aluminum, Copper., Copper alloys.

Container Advice : Containers, even those that have been emptied, can contain

explosive vapours. Do not cut, drill, grind, weld or perform

similar operations on or near containers.

Specific use(s) : Not applicable

Ensure that all local regulations regarding handling and stor-

age facilities are followed.

#### SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

#### Components with workplace control parameters

Contains no substances with occupational exposure limit values.

#### **Biological occupational exposure limits**

No biological limit allocated.

## **Monitoring Methods**

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA) , Germany http://www.dguv.de/inhalt/index.jsp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

Engineering measures : The level of protection and types of controls necessary will

vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances.

Appropriate measures include:

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## **NEODOL 135**

Version Revision Date: SDS Number: Print Date: 01/30/2025

5.0 01/23/2025 800001012062 Date of last issue: 07/18/2024

Adequate ventilation to control airborne concentrations. Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated. Eye washes and showers for emergency use.

#### General Information:

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

## Personal protective equipment

Respiratory protection

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are unsuitable (e.g. airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus.

Where air-filtering respirators are suitable, select an appropriate combination of mask and filter.

If air-filtering respirators are suitable for conditions of use: Select a filter suitable for the combination of organic gases and vapours and particles [Type A/Type P boiling point >65°C (149°F)].

Respirator selection, use and maintenance should be in accordance with the requirements of the OSHA Respiratory Protection Standard, 29 CFR 1910.134.

Hand protection Remarks

Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. Longer term protection: Nitrile rubber gloves. Incidental contact/Splash protection: PVC or neoprene rubber gloves. For continuous contact we recom-

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## **NEODOL 135**

Version Revision Date: SDS Number: Print Date: 01/30/2025 5.0 01/23/2025 800001012062 Date of last issue: 07/18/2024

> mend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

Eye protection : If material is handled such that it could be splashed into eyes,

protective eyewear is recommended.

Skin and body protection : Skin protection is not ordinarily required beyond standard

work clothes.

It is good practice to wear chemical resistant gloves.

Protective measures : Personal protective equipment (PPE) should meet recom-

mended national standards. Check with PPE suppliers.

Thermal hazards : Not applicable

Hygiene measures : Wash hands before eating, drinking, smoking and using the

toilet.

Launder contaminated clothing before re-use.

#### **Environmental exposure controls**

General advice : Local guidelines on emission limits for volatile substances

must be observed for the discharge of exhaust air containing

vapour.

Minimise release to the environment. An environmental assessment must be made to ensure compliance with local envi-

ronmental legislation.

Information on accidental release measures are to be found in

section 6.

## **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : Semi-solid at room temperature.

Colour : colourless

Odour : mild

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## **NEODOL 135**

Version Revision Date: SDS Number: Print Date: 01/30/2025

5.0 01/23/2025 800001012062 Date of last issue: 07/18/2024

Odour Threshold Data not available

рΗ Data not available

Melting / freezing point : ca. 24 - 36 °C / 75 - 97 °F

ca. 24 °C / 75 °F pour point

260 - 293 °C / 500 - 559 °F Boiling point/boiling range

143 °C / 289 °F Flash point

Evaporation rate Data not available

Flammability

Flammability (solid, gas) Data not available

Lower explosion limit and upper explosion limit / flammability limit

Upper explosion limit / up- : Data not available

per flammability limit

Lower explosion limit / Lower flammability limit : Data not available

Vapour pressure : < 0.01 hPa (25 °C / 77 °F)

Relative vapour density : Data not available

Relative density : 0.83 (25 °C / 77 °F)

Method: ASTM D4052

822 kg/m3 (40 °C / 104 °F) Density

Method: ASTM D4052

Solubility(ies)

ca. 20 mg/l (25 °C / 77 °F Water solubility

Solubility in other solvents : Data not available

Partition coefficient: n-

octanol/water

log Pow: ca. 4.72 - 6.2

Auto-ignition temperature Data not available

Decomposition temperature Data not available

Viscosity

12.4 mPa.s (40 °C / 104 °F) Viscosity, dynamic

Method: ASTM D445

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## **NEODOL 135**

Version Revision Date: SDS Number: Print Date: 01/30/2025

5.0 01/23/2025 800001012062 Date of last issue: 07/18/2024

50 mPa.s (35 °C / 95 °F)

Method: ASTM D445

Viscosity, kinematic : 15 mm2/s (40 °C / 104 °F)

Method: ASTM D445

Explosive properties : Not applicable

Oxidizing properties : Data not available

Surface tension : Data not available

Conductivity: > 10,000 pS/m

A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid, This material is not expected to be

a static accumulator.

Molecular weight : 203 - 210 g/mol

Particle size : Data not available

#### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : Stable at normal ambient temperature and pressure.

May oxidise in the presence of air.

Chemical stability : The product is chemically stable.

Stable under normal conditions.

Possibility of hazardous reac-

tions

None known.

Conditions to avoid : Extremes of temperature and direct sunlight.

Incompatible materials : Copper.

Copper alloys.

Strong oxidising agents.

Aluminum

Hazardous decomposition

products

None expected under normal use conditions.

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

Basis for assessment : Information given is based on product testing, and/or similar

products, and/or components. Information given is based on product testing, and/or similar products, and/or components. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual com-

ponent(s).

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## **NEODOL 135**

Version Revision Date: SDS Number: Print Date: 01/30/2025 5.0 01/23/2025 800001012062 Date of last issue: 07/18/2024

#### Information on likely routes of exposure

Exposure may occur via inhalation, ingestion, skin absorption, skin or eye contact, and accidental ingestion.

## **Acute toxicity**

**Product:** 

Acute oral toxicity : LD50 (Rat): 4,750 mg/kg >

Remarks: Low toxicity

Acute inhalation toxicity : Remarks: Low toxicity if inhaled.

Based on available data, the classification criteria are not met.

Acute dermal toxicity : LD50 (Rabbit): 5,000 mg/kg>

Remarks: Low toxicity

**Components:** 

tridecan-1-ol:

Acute oral toxicity : LD50 (Rat): > 4750 mg/kg

Remarks: Low toxicity

Acute inhalation toxicity : Remarks: Low toxicity if inhaled.

Based on available data, the classification criteria are not met.

Acute dermal toxicity : LD50 (Rabbit): > 5000 mg/kg

Remarks: Low toxicity

Pentadecanol, branched and linear:

Acute oral toxicity : Remarks: no data available

Acute inhalation toxicity : Remarks: no data available

Acute dermal toxicity : Remarks: no data available

Undecan-1-ol:

Acute oral toxicity : LD50 (Rat): > 5000 mg/kg

Remarks: Low toxicity

Acute inhalation toxicity : Remarks: Low toxicity

Based on available data, the classification criteria are not met.

Acute dermal toxicity : LD50 (Rabbit): > 5000 mg/kg

Remarks: Low toxicity

#### Skin corrosion/irritation

**Product:** 

Remarks: Causes skin irritation.

**Components:** 

tridecan-1-ol:

Remarks: Causes skin irritation.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## **NEODOL 135**

Version Revision Date: SDS Number: Print Date: 01/30/2025

5.0 01/23/2025 800001012062 Date of last issue: 07/18/2024

#### Pentadecanol, branched and linear:

Remarks: no data available

Undecan-1-ol:

Remarks: Causes mild skin irritation.

## Serious eye damage/eye irritation

#### **Product:**

Remarks: Causes serious eye irritation.

#### **Components:**

tridecan-1-ol:

Remarks: Causes serious eye irritation.

## Pentadecanol, branched and linear:

Remarks: no data available

Undecan-1-ol:

Remarks: Causes serious eye irritation.

## Respiratory or skin sensitisation

### **Product:**

Remarks: Not a sensitiser.

Based on available data, the classification criteria are not met.

## **Components:**

tridecan-1-ol:

Remarks: Not a sensitiser. Based on available data, the classification criteria are not met.

#### Pentadecanol, branched and linear:

Remarks: no data available

Undecan-1-ol:

Remarks: Not a sensitiser. Based on available data, the classification criteria are not met.

#### Germ cell mutagenicity

**Product:** 

Genotoxicity in vivo : Remarks: Non mutagenic

Components: tridecan-1-ol:

Genotoxicity in vivo : Remarks: Non mutagenic

### Pentadecanol, branched and linear:

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## **NEODOL 135**

Version Revision Date: SDS Number: Print Date: 01/30/2025

5.0 01/23/2025 800001012062 Date of last issue: 07/18/2024

Genotoxicity in vivo : Remarks: no data available

Undecan-1-ol:

Genotoxicity in vivo : Remarks: No evidence of mutagenic activity.

## Carcinogenicity

#### **Product:**

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

### **Components:**

#### tridecan-1-ol:

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

#### Pentadecanol, branched and linear:

Remarks: no data available

#### Undecan-1-ol:

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

## Reproductive toxicity

### **Product:**

Effects on fertility :

Remarks: Not a developmental toxicant., Based on available data, the classification criteria are not met., Does not impair

fertility.

## **Components:**

tridecan-1-ol:

Effects on fertility

Remarks: Not a developmental toxicant.

Based on available data, the classification criteria are not met.

Does not impair fertility.

#### Pentadecanol, branched and linear:

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## **NEODOL 135**

Version Revision Date: SDS Number: Print Date: 01/30/2025

5.0 01/23/2025 800001012062 Date of last issue: 07/18/2024

Effects on fertility

Remarks: Data not available

Undecan-1-ol:

Effects on fertility

Remarks: Not a developmental toxicant.

Based on available data, the classification criteria are not met.

Does not impair fertility.

## STOT - single exposure

#### **Product:**

Remarks: Based on available data, the classification criteria are not met.

### Components:

#### tridecan-1-ol:

Remarks: Based on available data, the classification criteria are not met.

#### Pentadecanol, branched and linear:

Remarks: no data available

## Undecan-1-ol:

Remarks: Based on available data, the classification criteria are not met.

#### STOT - repeated exposure

### **Product:**

Remarks: Based on available data, the classification criteria are not met.

## **Components:**

#### tridecan-1-ol:

Remarks: Based on available data, the classification criteria are not met.

### Pentadecanol, branched and linear:

Remarks: Based on available data, the classification criteria are not met.

#### Undecan-1-ol:

Remarks: Based on available data, the classification criteria are not met.

#### **Aspiration toxicity**

### **Product:**

Not an aspiration hazard.

### **Components:**

## tridecan-1-ol:

Not an aspiration hazard.

### Pentadecanol, branched and linear:

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## **NEODOL 135**

Version Revision Date: SDS Number: Print Date: 01/30/2025

5.0 01/23/2025 800001012062 Date of last issue: 07/18/2024

Not an aspiration hazard.

#### Undecan-1-ol:

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

#### **Further information**

#### **Product:**

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

#### **Components:**

#### tridecan-1-ol:

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

#### Pentadecanol, branched and linear:

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

#### Undecan-1-ol:

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

#### **SECTION 12. ECOLOGICAL INFORMATION**

Basis for assessment : Incomplete ecotoxicological data are available for this product.

> The information given below is based partly on a knowledge of the components and the ecotoxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).Incomplete ecotoxicological data are available for this product. The information given below is based partly on a knowledge of the components and the ecotoxicology of similar

products.

#### **Ecotoxicity**

#### **Product:**

Toxicity to fish (Acute toxici-

Remarks: Toxic ty)

LC/EC/IC50 >1 - <=10 mg/l

Toxicity to daphnia and other :

aquatic invertebrates (Acute

toxicity)

Remarks: Very toxic. LC/EC/IC50 < 1 mg/l

Toxicity to algae (Acute tox-

icity)

Remarks: Very toxic. LC/EC/IC50 < 1 mg/l

Toxicity to fish (Chronic tox-Remarks: NOEC/NOEL > 0.01 - <=0.1 mg/l

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## **NEODOL 135**

Version **Revision Date:** SDS Number: Print Date: 01/30/2025

5.0 01/23/2025 800001012062 Date of last issue: 07/18/2024

icity)

Toxicity to daphnia and other : Remarks: NOEC/NOEL > 0.1 - <=1.0 mg/l

aquatic invertebrates (Chron-

ic toxicity)

Toxicity to microorganisms Remarks: Practically non toxic:

(Acute toxicity) LC/EC/IC50 > 100 mg/l

Components:

tridecan-1-ol:

Toxicity to fish (Acute toxici-Remarks: Toxic

LC/EC/IC50 >1 - <=10 mg/l ty)

1

Toxicity to daphnia and other : aquatic invertebrates (Acute

toxicity)

Remarks: Very toxic. LC/EC/IC50 < 1 mg/l

Toxicity to algae (Acute tox-

icity)

Remarks: Very toxic. LC/EC/IC50 < 1 mg/l

M-Factor (Acute aquatic tox-

icity)

Toxicity to fish (Chronic toxicity)

Remarks: NOEC/NOEL > 0.01 - <=0.1 mg/l

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

ic toxicity)

Remarks: NOEC/NOEL > 0.1 - <=1.0 mg/l

Toxicity to microorganisms

(Acute toxicity)

Remarks: Practically non toxic:

LC/EC/IC50 > 100 mg/l

Undecan-1-ol:

Toxicity to fish (Acute toxici-

ty)

Remarks: LC/EC/IC50 >1 - <=10 mg/l

Toxic

Toxicity to daphnia and other : aquatic invertebrates (Acute

toxicity)

Remarks: Very toxic. LC/EC/IC50 < 1 mg/l

Toxicity to algae (Acute tox-

icity)

Remarks: LC/EC/IC50 >1 - <=10 mg/l

Toxic

M-Factor (Acute aquatic tox-

icity)

Toxicity to fish (Chronic tox-

icity)

Remarks: Data not available

Toxicity to daphnia and other : Remarks: NOEC/NOEL > 0.01 - <=0.1 mg/l

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## **NEODOL 135**

Version Revision Date: SDS Number: Print Date: 01/30/2025

5.0 01/23/2025 800001012062 Date of last issue: 07/18/2024

aquatic invertebrates (Chron-

ic toxicity)

Toxicity to microorganisms

(Acute toxicity)

Remarks: LC/EC/IC50 > 100 mg/l

Practically non toxic:

Based on available data, the classification criteria are not met.

### Persistence and degradability

**Product:** 

Biodegradability : Remarks: Taking into consideration the properties of several

components, the product is estimated to be biodegradable

according to OECD classification.

Remarks: Readily biodegradable.

**Components:** 

tridecan-1-ol:

Biodegradability : Remarks: Readily biodegradable.

Undecan-1-ol:

Biodegradability : Remarks: Readily biodegradable.

Oxidises rapidly by photo-chemical reactions in air.

**Bioaccumulative potential** 

**Product:** 

Bioaccumulation : Remarks: Based on data from similar materials

Remarks: Bioaccumulation is unlikely to occur due to metabo-

lism and excretion.

**Components:** 

tridecan-1-ol:

Bioaccumulation : Remarks: Bioaccumulation is unlikely to occur due to metabo-

lism and excretion.

Undecan-1-ol:

Bioaccumulation : Remarks: Bioaccumulation is unlikely to occur due to metabo-

lism and excretion.

Mobility in soil

**Product:** 

Mobility : Remarks: Floats on water.

If it enters soil, it will adsorb to soil particles and will not be

mobile.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## **NEODOL 135**

Version Revision Date: SDS Number: Print Date: 01/30/2025 5.0 01/23/2025 800001012062 Date of last issue: 07/18/2024

Remarks: Adsorbs to soil and has low mobility

**Components:** 

tridecan-1-ol:

Mobility : Remarks: Floats on water.

If it enters soil, it will adsorb to soil particles and will not be

mobile.

Undecan-1-ol:

Mobility : Remarks: Floats on water.

If product enters soil, it will be highly mobile and may contam-

inate groundwater.

Other adverse effects

no data available

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

### **Disposal methods**

Waste from residues : Recover or recycle if possible.

It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal meth-

ods in compliance with applicable regulations.

Do not dispose into the environment, in drains or in water

courses.

Waste product should not be allowed to contaminate soil or

water.

Disposal should be in accordance with applicable regional,

national, and local laws and regulations.

Local regulations may be more stringent than regional or na-

tional requirements and must be complied with.

Contaminated packaging : Drain container thoroughly.

After draining, vent in a safe place away from sparks and fire.

Residues may cause an explosion hazard. Do not puncture, cut, or weld uncleaned drums. Send to drum recoverer or metal reclaimer.

### **SECTION 14. TRANSPORT INFORMATION**

### **National Regulations**

## **US Department of Transportation Classification (49 CFR Parts 171-180)**

Not regulated as a dangerous good

### **International Regulations**

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## **NEODOL 135**

Version Revision Date: SDS Number: Print Date: 01/30/2025 5.0 01/23/2025 800001012062 Date of last issue: 07/18/2024

IATA-DGR

UN/ID No. : UN 3082

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(Alcohols C14-15, 1-Undecanol)

Class : 9
Packing group : III
Labels : 9

**IMDG-Code** 

UN number : UN 3082

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(Alcohols C14-15, 1-Undecanol)

Class : 9
Packing group : III
Labels : 9
Marine pollutant : yes

## Maritime transport in bulk according to IMO instruments

Pollution category : Y
Ship type : 2

Product name : NEODOL 135 (contains Undecyl Alcohol)

#### Special precautions for user

Remarks : Special Precautions: Refer to Section 7, Handling & Storage,

for special precautions which a user needs to be aware of or

needs to comply with in connection with transport.

**Additional Information**: This product may be transported under nitrogen blanketing.

Nitrogen is an odourless and invisible gas. Exposure to nitrogen enriched atmospheres displaces available oxygen which may cause asphyxiation or death. Personnel must observe strict safety precautions when involved with a confined space

entry

Transport in bulk according to Annex II of Marpol and the IBC

Code

### **SECTION 15. REGULATORY INFORMATION**

#### **EPCRA - Emergency Planning and Community Right-to-Know Act**

\*: This material does not contain any components with a CERCLA RQ.

## SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

#### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Skin corrosion or irritation

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## **NEODOL 135**

Version Revision Date: SDS Number: Print Date: 01/30/2025 5.0 01/23/2025 800001012062 Date of last issue: 07/18/2024

Serious eye damage or eye irritation

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

#### **Clean Water Act**

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

## **US State Regulations**

### California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

### Other regulations:

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

### The components of this product are reported in the following inventories:

AIIC : Listed

DSL : Listed

IECSC : Listed

ENCS : Listed

TSCA : Listed

EINECS : Listed

KECI : Listed

### **SECTION 16. OTHER INFORMATION**

#### **Further information**

NFPA Rating (Health, Fire, Reac- 2, 1, 0 tivity)

#### Full text of other abbreviations

Abbreviations and Acronyms : The standard abbreviations and acronyms used in this docu-

ment can be looked up in reference literature (e.g. scientific

dictionaries) and/or websites.

ACGIH = American Conference of Governmental Industrial

Hygienists

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## **NEODOL 135**

Version Revision Date: SDS Number: Print Date: 01/30/2025 5.0 01/23/2025 800001012062 Date of last issue: 07/18/2024

ADR = European Agreement concerning the International

Carriage of Dangerous Goods by Road

AICS = Australian Inventory of Chemical Substances ASTM = American Society for Testing and Materials

BEL = Biological exposure limits

BTEX = Benzene, Toluene, Ethylbenzene, Xylenes

CAS = Chemical Abstracts Service

CEFIC = European Chemical Industry Council CLP = Classification Packaging and Labelling

COC = Cleveland Open-Cup

DIN = Deutsches Institut für Normung

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

DSL = Canada Domestic Substance List

EC = European Commission

EC50 = Effective Concentration fifty

ECETOC = European Center on Ecotoxicology and Toxicology Of Chemicals

ECHA = European Chemicals Agency

EINECS = The European Inventory of Existing Commercial

**Chemical Substances** 

EL50 = Effective Loading fifty

ENCS = Japanese Existing and New Chemical Substances Inventory

EWC = European Waste Code

GHS = Globally Harmonised System of Classification and Labelling of Chemicals

IARC = International Agency for Research on Cancer

IATA = International Air Transport Association

IC50 = Inhibitory Concentration fifty

IL50 = Inhibitory Level fifty

IMDG = International Maritime Dangerous Goods

INV = Chinese Chemicals Inventory

IP346 = Institute of Petroleum test method N° 346 for the determination of polycyclic aromatics DMSO-extractables

KECI = Korea Existing Chemicals Inventory

LC50 = Lethal Concentration fifty

LD50 = Lethal Dose fifty per cent.

LL/EL/IL = Lethal Loading/Effective Loading/Inhibitory loading

LL50 = Lethal Loading fifty

MARPOL = International Convention for the Prevention of Pollution From Ships

NOEC/NOEL = No Observed Effect Concentration / No Observed Effect Level

OE HPV = Occupational Exposure - High Production Volume

PBT = Persistent, Bioaccumulative and Toxic

PICCS = Philippine Inventory of Chemicals and Chemical Substances

PNEC = Predicted No Effect Concentration

REACH = Registration Evaluation And Authorisation Of Chemicals

RID = Regulations Relating to International Carriage of Dangerous Goods by Rail

SKIN\_DES = Skin Designation

STEL = Short term exposure limit

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## **NEODOL 135**

Version Revision Date: SDS Number: Print Date: 01/30/2025

5.0 01/23/2025 800001012062 Date of last issue: 07/18/2024

TRA = Targeted Risk Assessment

TSCA = US Toxic Substances Control Act

TWA = Time-Weighted Average

vPvB = very Persistent and very Bioaccumulative

A vertical bar (|) in the left margin indicates an amendment from the previous version.

Sources of key data used to compile the Safety Data

Sheet

The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU

IUCLID date base, EC 1272 regulation, etc).

Revision Date : 01/23/2025

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN