The content and format of this safety data sheet is in accordance with ABNT NBR 14725:2023 requirements.

NEODOL 135

Version 4.1 Revision Date 09.05.2025 Print Date 17.05.2025

SECTION 1. IDENTIFICATION

Product name : NEODOL 135

Product code : V2483, V2501

Manufacturer or supplier's details

Manufacturer/Supplier : Shell CAPSA

Av. Roque Saenz Peña 788

Buenos Aires, 1383

Argentina

Telephone : (+54 11) 4130-2168

Telefax : (+54 11) 4130-2180

Contact for Safety Data Sheet :

Emergency telephone number : Locais: (+11 15) 4970-7391 / 4970-7390 / 5062-6601 / 4973-

7368; Internacionais: (+54 911) 4970-7391 / 4970-7390 /

5062/6601 / 4973-7

Recommended use of the chemical and restrictions on use

Recommended use : Feedstock for detergent derivative manufacture.

Restrictions on use : This product must not be used in applications other than the

above without first seeking the advice of the supplier.

This product must not be used in applications other than those listed in Section 1 without first seeking the advice of the suppli-

er.

Other information : NEODOL is a trademark owned by Shell Trademark Man-

agement B.V. and Shell Brands Inc. and used by affiliates of

Royal Dutch Shell plc.

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Skin irritation : Category 2

Skin corrosion/irritation : Category 2

Short-term (acute) aquatic

hazard

: Category 1

Long-term (chronic) aquatic

hazard

: Category 1

The content and format of this safety data sheet is in accordance with ABNT NBR 14725:2023 requirements.

NEODOL 135

Version 4.1 Revision Date 09.05.2025 Print Date 17.05.2025

GHS label elements

Hazard pictograms





Signal word : Warning

Hazard statements : PHYSICAL HAZARDS:

Not classified as a physical hazard under GHS criteria.

HEALTH HAZARDS:
H315 Causes skin irritation.
H319 Causes serious eye irritation.

H319 Causes serious eye irritation ENVIRONMENTAL HAZARDS: H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**

P264 Wash skin thoroughly after handling. P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protec-

tion/ face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

P321 Specific treatment (see supplemental first aid instructions

on this label).

P332 + P313 If skin irritation occurs: Get medical advice/ atten-

tion.

P337 + P313 If eye irritation persists: Get medical advice/ at-

tention.

P362 + P364 Take off contaminated clothing and wash it before

reuse.

P391 Collect spillage.

Storage:

No precautionary phrases.

Disposal:

P501 Dispose of contents and container to appropriate waste site or reclaimer in accordance with local and national regula-

tions.

Other hazards which do not result in classification

Repeated exposure may cause skin dryness or cracking.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

The content and format of this safety data sheet is in accordance with ABNT NBR 14725:2023 requirements.

NEODOL 135

Version 4.1 Revision Date 09.05.2025 Print Date 17.05.2025

Hazardous components

| Chemical name | CAS-No. | Classification | Concentration (% w/w) |
|-----------------------------------|------------|---|-----------------------|
| tridecan-1-ol | 112-70-9 | Asp. Tox.2; H305 Skin Irrit.2; H315 Eye Irrit.2; H319 Aquatic Acute1; H400 Aquatic Chronic1; H410 | >= 35 - <= 50 |
| Pentadecanol, branched and linear | 90480-71-0 | Aquatic ChronicH410 | >= 35 - <= 50 |
| Undecan-1-ol | 112-42-5 | Skin Irrit.3; H316 Eye Irrit.2; H319 Asp. Tox.2; H305 Aquatic Acute1; H400 Aquatic Chronic2; H411 | >= 10 - <= 18 |

For explanation of abbreviations see section 16.

SECTION 4. FIRST-AID MEASURES

| General advice | Not expected to be a health hazard when used under normal |
|----------------|---|
| General advice | Not expected to be a fleath flazard when used under floring |

conditions.

If inhaled No treatment necessary under normal conditions of use.

If symptoms persist, obtain medical advice.

In case of skin contact Remove contaminated clothing. Immediately flush skin with

> large amounts of water for at least 15 minutes, and follow by washing with soap and water if available. If redness, swelling, pain and/or blisters occur, transport to the nearest medical

facility for additional treatment.

In case of eye contact Immediately flush eye(s) with plenty of water.

Remove contact lenses, if present and easy to do. Continue

rinsing.

Transport to the nearest medical facility for additional treat-

ment.

If swallowed : If swallowed, do not induce vomiting: transport to nearest

medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (38.3°C), shortness of breath, chest congestion or continued coughing or wheezing.

Most important symptoms and effects, both acute and delayed

Not considered to be an inhalation hazard under normal conditions of use.

Possible respiratory irritation signs and symptoms may include a temporary burning sensation of the nose and throat, cough-

ing, and/or difficulty breathing.

Skin irritation signs and symptoms may include a burning sen-

sation, redness, swelling, and/or blisters.

Eye irritation signs and symptoms may include a burning sen-

sation, redness, swelling, and/or blurred vision.

The content and format of this safety data sheet is in accordance with ABNT NBR 14725:2023 requirements.

NEODOL 135

Version 4.1 Revision Date 09.05.2025 Print Date 17.05.2025

If material enters lungs, signs and symptoms may include coughing, choking, wheezing, difficulty in breathing, chest

congestion, shortness of breath, and/or fever.

If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (38.3°C), shortness of breath, chest congestion or continued coughing or wheezing.

Protection of first-aiders : When administering first aid, ensure that you are wearing the

appropriate personal protective equipment according to the

incident, injury and surroundings.

Notes to physician : Call a doctor or poison control center for guidance.

Treat symptomatically.

IMMEDIATE TREATMENT IS EXTREMELY IMPORTANT!

Potential for chemical pneumonitis.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Alcohol-resistant foam, water spray or fog. Dry chemical pow-

der, carbon dioxide, sand or earth may be used for small fires

only.

Unsuitable extinguishing

media

: Do not use water in a jet.

Specific hazards during fire-

fighting

: Carbon monoxide may be evolved if incomplete combustion

occurs.

Will float and can be reignited on surface water.

The vapour is heavier than air, spreads along the ground and

distant ignition is possible.

Specific extinguishing meth-

ods

Standard procedure for chemical fires.

Clear fire area of all non-emergency personnel. Keep adjacent containers cool by spraying with water.

Special protective equipment

for firefighters

Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained

Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to

relevant Standards (e.g. Europe: EN469).

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emer-

gency procedures

Observe all relevant local and international regulations.

Notify authorities if any exposure to the general public or the

environment occurs or is likely to occur.

Local authorities should be advised if significant spillages

cannot be contained.

The content and format of this safety data sheet is in accordance with ABNT NBR 14725:2023 requirements.

NEODOL 135

Version 4.1 Revision Date 09.05.2025 Print Date 17.05.2025

Avoid contact with spilled or released material. Immediately remove all contaminated clothing. For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet. For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.

Stay upwind and keep out of low areas. Be ready for fire or possible exposure.

Environmental precautions : Prevent from spreading or entering into drains, ditches or riv-

ers by using sand, earth, or other appropriate barriers.
Use appropriate containment to avoid environmental contami-

nation.

Ventilate contaminated area thoroughly.

Methods and materials for containment and cleaning up

For large liquid spills (> 1 drum), transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely For small liquid spills (< 1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove

contaminated soil and dispose of safely.

Additional advice : For guidance on selection of personal protective equipment

see Section 8 of this Safety Data Sheet.

For guidance on disposal of spilled material see Section 13 of

this Safety Data Sheet.

SECTION 7. HANDLING AND STORAGE

General Precautions : Avoid breathing of or direct contact with material. Only use in

well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see

Section 8 of this Safety Data Sheet.

Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this

material.

Ensure that all local regulations regarding handling and stor-

age facilities are followed.

Advice on safe handling : Avoid contact with skin, eyes and clothing.

Do not empty into drains.

Sudden Release of Pressure Hazard

Avoidance of contact : Copper.

Copper alloys.

Strong oxidising agents.

Aluminum

The content and format of this safety data sheet is in accordance with ABNT NBR 14725:2023 requirements.

NEODOL 135

| /ersion 4.1 | Revision Date 09.05.2025 | Print Date 17.05.2025 |
|-----------------------------|---|---|
| Product Transfer | : Keep containers closed when pressed air for filling discharge | |
| Storage | | |
| Conditions for safe storage | Refer to section 15 for any addering the packaging and storage | |
| Other data | m3 or higher). Insulation (lagging) will minimi ambient temperature. Tanks should be fitted with he | t be released to atmosphere. ge should be controlled by a em. ed for large tanks (capacity 100 ze heat loss in areas of low ating coils in areas where ambinding temperatures below the |
| Packaging material | : Suitable material: Stainless ste Unsuitable material: Aluminum | |
| Container Advice | Containers, even those that has explosive vapours. Do not cut, similar operations on or near of | |
| Specific use(s) | : Not applicable | |
| | Ensure that all local regulation age facilities are followed. | s regarding handling and stor- |
| | | |

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Contains no substances with occupational exposure limit values. Contains no components with occupational exposure limit values.

Biological occupational exposure limits

No biological limit allocated.

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

The content and format of this safety data sheet is in accordance with ABNT NBR 14725:2023 requirements.

NEODOL 135

Version 4.1 Revision Date 09.05.2025 Print Date 17.05.2025

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany http://www.douv.de/inhalt/index.isp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

Engineering measures

: The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

Adequate ventilation to control airborne concentrations. Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated. Eye washes and showers for emergency use.

General Information

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

Personal protective equipment

Respiratory protection

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are unsuitable (e.g. airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus.

Where air-filtering respirators are suitable, select an appropriate combination of mask and filter.

If air-filtering respirators are suitable for conditions of use: Select a filter suitable for the combination of organic gases and vapours and particles [Type A/Type P boiling point >65°C (149°F)].

The content and format of this safety data sheet is in accordance with ABNT NBR 14725:2023 requirements.

NEODOL 135

Version 4.1 Revision Date 09.05.2025 Print Date 17.05.2025

Hand protection Remarks

: Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. Longer term protection: Nitrile rubber gloves. Incidental contact/Splash protection: PVC or neoprene rubber gloves. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

Eye protection : If material is handled such that it could be splashed into eyes,

protective eyewear is recommended.

Skin and body protection : Skin protection is not ordinarily required beyond standard

work clothes.

It is good practice to wear chemical resistant gloves.

Thermal hazards : Not applicable

Protective measures : Personal protective equipment (PPE) should meet recom-

mended national standards. Check with PPE suppliers.

Environmental exposure controls

General advice : Local guidelines on emission limits for volatile substances

must be observed for the discharge of exhaust air containing

vapour.

Minimise release to the environment. An environmental assessment must be made to ensure compliance with local envi-

ronmental legislation.

Information on accidental release measures are to be found in

section 6.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

The content and format of this safety data sheet is in accordance with ABNT NBR 14725:2023 requirements.

NEODOL 135

Version 4.1 Revision Date 09.05.2025 Print Date 17.05.2025

Appearance : Semi-solid at room temperature.

Colour : colourless

Odour : mild

Odour Threshold : Data not available

pH : Data not available

Melting / freezing point : ca. 24 - 36 $^{\circ}$ C / 75 - 97 $^{\circ}$ F

Pour point ca. 24 °C / 75 °F

Boiling point/boiling range : 260 - 293 °C / 500 - 559 °F

Flash point : 143 °C / 289 °F

Evaporation rate : Data not available

Flammability

Flammability (solid, gas) : Data not available

Lower explosion limit and upper explosion limit / flammability limit

Upper explosion limit : Data not available

Lower explosion limit : Data not available

Vapour pressure : < 0.01 hPa (25 °C / 77 °F)

Relative vapour density : Data not available

Relative density : 0.83 (25 °C / 77 °F)

Method: ASTM D4052

Density : 822 kg/m3 (40 °C / 104 °F)Method: ASTM D4052

Solubility(ies)

Water solubility : ca. 20 mg/l (25 °C / 77 °F

)

Solubility in other solvents : Data not available

Partition coefficient: n-

octanol/water

: log Pow: ca. 4.72 - 6.2

Auto-ignition temperature : Data not available

Decomposition temperature : Data not available

Viscosity

Viscosity, dynamic : 12.4 mPa.s (40 °C / 104 °F)

Method: ASTM D445

9 / 20 800001012062 BR

The content and format of this safety data sheet is in accordance with ABNT NBR 14725:2023 requirements.

NEODOL 135

Version 4.1 Revision Date 09.05.2025 Print Date 17.05.2025

50 mPa.s (35 °C / 95 °F) Method: ASTM D445

Viscosity, kinematic : 15 mm2/s (40 °C / 104 °F)

Method: ASTM D445

Explosive properties : Not applicable

Oxidizing properties : Data not available

Surface tension : Data not available

Conductivity: > 10,000 pS/m

A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid, This material is not expected to be

a static accumulator.

Molecular weight : 203 - 210 g/mol

Particle characteristics

Particle size : Data not available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Stable at normal ambient temperature and pressure.

May oxidise in the presence of air.

Chemical stability : The product is chemically stable.

Stable under normal conditions.

Possibility of hazardous reac-

tions

: None known.

Conditions to avoid : Extremes of temperature and direct sunlight.

Incompatible materials : Copper.

Copper alloys.

Strong oxidising agents.

Aluminum

Hazardous decomposition

products

: None expected under normal use conditions.

SECTION 11. TOXICOLOGICAL INFORMATION

Basis for assessment : Information given is based on product testing, and/or similar

products, and/or components.Information given is based on product testing, and/or similar products, and/or components. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual com-

ponent(s).

The content and format of this safety data sheet is in accordance with ABNT NBR 14725:2023 requirements.

NEODOL 135

Version 4.1 Revision Date 09.05.2025 Print Date 17.05.2025

exposure

Information on likely routes of : Exposure may occur via inhalation, ingestion, skin absorption,

skin or eye contact, and accidental ingestion.

Acute toxicity

Product:

Acute oral toxicity : LD50 (Rat): 4,750 mg/kg >

Remarks: Low toxicity

: Remarks: Low toxicity if inhaled. Acute inhalation toxicity

Based on available data, the classification criteria are not met.

Acute dermal toxicity : LD50 (Rabbit): 5,000 mg/kg>

Remarks: Low toxicity

Components:

tridecan-1-ol:

Acute oral toxicity : LD50 (Rat): > 4750 mg/kg

Remarks: Low toxicity

Acute inhalation toxicity : Remarks: Low toxicity if inhaled.

Based on available data, the classification criteria are not met.

: LD50 (Rabbit): > 5000 mg/kg Acute dermal toxicity

Remarks: Low toxicity

Pentadecanol, branched and linear:

Acute oral toxicity : Remarks: No data available

Acute inhalation toxicity : Remarks: No data available

Acute dermal toxicity : Remarks: No data available

Undecan-1-ol:

Acute oral toxicity : LD50 (Rat): > 5000 mg/kg

Remarks: Low toxicity

Acute inhalation toxicity : Remarks: Low toxicity

Based on available data, the classification criteria are not met.

Acute dermal toxicity : LD50 (Rabbit): > 5000 mg/kg

Remarks: Low toxicity

Skin corrosion/irritation

Product:

Remarks: Causes skin irritation.

Components:

tridecan-1-ol:

Remarks: Causes skin irritation.

The content and format of this safety data sheet is in accordance with ABNT NBR 14725:2023 requirements.

NEODOL 135

Version 4.1 Revision Date 09.05.2025 Print Date 17.05.2025

Pentadecanol, branched and linear:

Remarks: No data available

Undecan-1-ol:

Remarks: Causes mild skin irritation.

Serious eye damage/eye irritation

Product:

Remarks: Causes serious eye irritation.

Components:

tridecan-1-ol:

Remarks: Causes serious eye irritation.

Pentadecanol, branched and linear:

Remarks: No data available

Undecan-1-ol:

Remarks: Causes serious eye irritation.

Respiratory or skin sensitisation

Product:

Remarks: Not a sensitiser.

Based on available data, the classification criteria are not met.

Components:

tridecan-1-ol:

Remarks: Not a sensitiser.

Based on available data, the classification criteria are not met.

Pentadecanol, branched and linear:

Remarks: No data available

Undecan-1-ol:

Remarks: Not a sensitiser.

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Product:

Genotoxicity in vivo : Remarks: Non mutagenic

Components:

tridecan-1-ol:

Genotoxicity in vivo : Remarks: Non mutagenic

Pentadecanol, branched and linear:

Genotoxicity in vivo : Remarks: No data available

The content and format of this safety data sheet is in accordance with ABNT NBR 14725:2023 requirements.

NEODOL 135

Version 4.1 Revision Date 09.05.2025 Print Date 17.05.2025

Undecan-1-ol:

Genotoxicity in vivo : Remarks: No evidence of mutagenic activity.

Carcinogenicity

Product:

Remarks: Not a carcinogen.

Based on available data, the classification criteria are not met.

Components:

tridecan-1-ol:

Remarks: Not a carcinogen.

Based on available data, the classification criteria are not met.

Pentadecanol, branched and linear:

Remarks: No data available

Undecan-1-ol:

Remarks: Not a carcinogen.

Based on available data, the classification criteria are not met.

| Material | GHS/CLP Carcinogenicity Classification |
|-----------------------------------|--|
| tridecan-1-ol | No carcinogenicity classification. |
| Pentadecanol, branched and linear | No carcinogenicity classification. |
| Undecan-1-ol | No carcinogenicity classification. |

Reproductive toxicity

Product:

Effects on fertility

Remarks: Not a developmental toxicant.

Based on available data, the classification criteria are not met.

Does not impair fertility.

STOT - single exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

Components:

tridecan-1-ol:

Remarks: Based on available data, the classification criteria are not met.

Pentadecanol, branched and linear:

Remarks: No data available

Undecan-1-ol:

Remarks: Based on available data, the classification criteria are not met.

The content and format of this safety data sheet is in accordance with ABNT NBR 14725:2023 requirements.

NEODOL 135

Version 4.1

Revision Date 09.05.2025

Print Date 17.05.2025

STOT - repeated exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

Components:

tridecan-1-ol:

Remarks: Based on available data, the classification criteria are not met.

Pentadecanol, branched and linear:

Remarks: Based on available data, the classification criteria are not met.

Undecan-1-ol:

Remarks: Based on available data, the classification criteria are not met.

Aspiration toxicity

Product:

Remarks: Based on available data, the classification criteria are not met.

Not an aspiration hazard.

Components:

tridecan-1-ol:

Not an aspiration hazard.

Pentadecanol, branched and linear:

Not an aspiration hazard.

Undecan-1-ol:

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

Further information

Product:

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

Components:

tridecan-1-ol:

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

Pentadecanol, branched and linear:

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

Undecan-1-ol:

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

The content and format of this safety data sheet is in accordance with ABNT NBR 14725:2023 requirements.

NEODOL 135

Version 4.1 Revision Date 09.05.2025 Print Date 17.05.2025

SECTION 12. ECOLOGICAL INFORMATION

Basis for assessment : Incomplete ecotoxicological data are available for this product.

The information given below is based partly on a knowledge of the components and the ecotoxicology of similar products.Incomplete ecotoxicological data are available for this product. The information given below is based partly on a knowledge of the components and the ecotoxicology of similar

products.

Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual com-

ponent(s).

Ecotoxicity

Product:

Toxicity to fish (Acute toxici-

ty)

Remarks: Toxic

LC/EC/IC50 >1 - <=10 mg/l

Toxicity to crustacean (Acute

toxicity)

Remarks: Very toxic. LC/EC/IC50 < 1 mg/l

Toxicity to algae/aquatic

plants (Acute toxicity)

Remarks: Very toxic.

LC/EC/IC50 < 1 mg/l

Toxicity to fish (Chronic tox-

icity)

: Remarks: NOEC/NOEL > 0.01 - <=0.1 mg/l

Toxicity to crustacean

(Chronic toxicity)

: Remarks: NOEC/NOEL > 0.1 - <=1.0 mg/l

Toxicity to microorganisms

(Acute toxicity)

Remarks: Practically non toxic:

LC/EC/IC50 > 100 mg/l

Components:

tridecan-1-ol:

Toxicity to fish (Acute toxici-

: Remarks: Toxic

LC/EC/IC50 >1 - <=10 mg/l

Toxicity to crustacean (Acute

toxicity)

Remarks: Very toxic. LC/EC/IC50 < 1 mg/l

Toxicity to algae/aquatic plants (Acute toxicity)

: Remarks: Very toxic. LC/EC/IC50 < 1 mg/l

M-Factor (Acute aquatic tox-

icity)

: 1

Toxicity to fish (Chronic tox-

icity)

: Remarks: NOEC/NOEL > 0.01 - <=0.1 mg/l

15 / 20 800001012062 BR

The content and format of this safety data sheet is in accordance with ABNT NBR 14725:2023 requirements.

NEODOL 135

Version 4.1 Revision Date 09.05.2025 Print Date 17.05.2025

Toxicity to crustacean(Chronic toxicity) : Remarks: NOEC/NOEL > 0.1 - <=1.0 mg/l

Toxicity to bacteria

: Remarks: Practically non toxic:

LC/EC/IC50 > 100 mg/l

Undecan-1-ol:

Toxicity to fish (Acute toxici-

ty)

: Remarks: LC/EC/IC50 >1 - <=10 mg/l

Toxic

Toxicity to crustacean (Acute

toxicity)

: Remarks: Very toxic. LC/EC/IC50 < 1 mg/l

Toxicity to algae/aquatic

plants (Acute toxicity)

: Remarks: LC/EC/IC50 >1 - <=10 mg/l

Toxic

M-Factor (Acute aquatic tox-

icity)

: 1

Toxicity to fish (Chronic tox-

icity)

: Remarks: Data not available

Toxicity to crustacean(Chronic toxicity) Toxicity to bacteria : Remarks: NOEC/NOEL > 0.01 - <=0.1 mg/l

: Remarks: LC/EC/IC50 > 100 mg/l Practically non toxic:

Based on available data, the classification criteria are not met.

Persistence and degradability

Product:

Biodegradability : Remarks: Taking into consideration the properties of several

components, the product is estimated to be biodegradable

according to OECD classification.

Remarks: Readily biodegradable.

Components:

tridecan-1-ol:

Biodegradability : Remarks: Readily biodegradable.

Undecan-1-ol:

Biodegradability : Remarks: Readily biodegradable.

Oxidises rapidly by photo-chemical reactions in air.

Bioaccumulative potential

Product:

Bioaccumulation : Remarks: Based on data from similar materials

Remarks: Bioaccumulation is unlikely to occur due to metabo-

lism and excretion.

The content and format of this safety data sheet is in accordance with ABNT NBR 14725:2023 requirements.

NEODOL 135

Version 4.1 Revision Date 09.05.2025 Print Date 17.05.2025

Partition coefficient: n-

octanol/water

: log Pow: ca. 4.72 - 6.2

Components:

tridecan-1-ol:

Bioaccumulation : Remarks: Bioaccumulation is unlikely to occur due to metabo-

lism and excretion.

Undecan-1-ol:

Bioaccumulation : Remarks: Bioaccumulation is unlikely to occur due to metabo-

lism and excretion.

Mobility in soil

Product:

Mobility : Remarks: Floats on water.

If it enters soil, it will adsorb to soil particles and will not be

mobile.

Remarks: Adsorbs to soil and has low mobility

Components:

tridecan-1-ol:

Mobility : Remarks: Floats on water.

If it enters soil, it will adsorb to soil particles and will not be

mobile.

Undecan-1-ol:

Mobility : Remarks: Floats on water.

If product enters soil, it will be highly mobile and may contam-

inate groundwater.

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Recover or recycle if possible.

It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal meth-

ods in compliance with applicable regulations.

Do not dispose into the environment, in drains or in water

courses.

Waste product should not be allowed to contaminate soil or

water.

Disposal should be in accordance with applicable regional,

national, and local laws and regulations.

Local regulations may be more stringent than regional or na-

The content and format of this safety data sheet is in accordance with ABNT NBR 14725:2023 requirements.

NEODOL 135

Version 4.1 Revision Date 09.05.2025 Print Date 17.05.2025

tional requirements and must be complied with.

Contaminated packaging : Drain container thoroughly.

After draining, vent in a safe place away from sparks and fire.

Residues may cause an explosion hazard. Do not puncture, cut, or weld uncleaned drums. Send to drum recoverer or metal reclaimer.

SECTION 14. TRANSPORT INFORMATION

ANTT

UN number : 3082

Proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(Alcohols C14-15, 1-Undecanol)

Class : 9 Packing group Ш Labels 9 Hazard Identification Number : 90 Environmentally hazardous : no

International Regulations

IATA-DGR

UN/ID No. : UN 3082

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

(Alcohols C14-15, 1-Undecanol)

Class : 9 : III Packing group Labels : 9

IMDG-Code

UN number : UN 3082

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(Alcohols C14-15, 1-Undecanol)

: 9 Class Packing group : 111 Labels 9 Marine pollutant : yes

Maritime transport in bulk according to IMO instruments

: Y Pollution category Ship type 2

Product name NEODOL 135 (contains Undecyl Alcohol)

Special precautions for user

Remarks : Special Precautions: Refer to Section 7, Handling & Storage,

for special precautions which a user needs to be aware of or

needs to comply with in connection with transport.

The content and format of this safety data sheet is in accordance with ABNT NBR 14725:2023 requirements.

NEODOL 135

Version 4.1 Revision Date 09.05.2025 Print Date 17.05.2025

Additional Information

: This product may be transported under nitrogen blanketing. Nitrogen is an odourless and invisible gas. Exposure to nitrogen enriched atmospheres displaces available oxygen which may cause asphyxiation or death. Personnel must observe strict safety precautions when involved with a confined space

Transport in bulk according to Annex II of Marpol and the IBC

Code

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

The components of this product are reported in the following inventories:

AIIC : Listed

DSL : Listed

IECSC : Listed

ENCS : Listed

TSCA : Listed

EINECS : Listed

KECI : Listed

SECTION 16. OTHER INFORMATION

Full text of H-Statements

H305 May be harmful if swallowed and enters airways.

Causes skin irritation. H315 Causes mild skin irritation. H316 Causes serious eye irritation. H319 Very toxic to aquatic life. H400

Very toxic to aquatic life with long lasting effects. H410 H411 Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Aquatic Acute Short-term (acute) aquatic hazard Aquatic Chronic Long-term (chronic) aquatic hazard

Asp. Tox. Aspiration hazard Eve Irrit. Eve irritation Skin irritation Skin Irrit.

Abbreviations and Acronyms : The standard abbreviations and acronyms used in this docu-

The content and format of this safety data sheet is in accordance with ABNT NBR 14725:2023 requirements.

NEODOL 135

Version 4.1 Revision Date 09.05.2025 Print Date 17.05.2025

ment can be looked up in reference literature (e.g. scientific dictionaries) and/or websites.

Further information

Training advice : Provide adequate information, instruction and training for op-

erators.

Other information : A vertical bar (|) in the left margin indicates an amendment

from the previous version.

There has been a decrease in the Health Hazard classification

of this product in section 2.

Sources of key data used to compile the Safety Data

Sheet

: The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU

IUCLID date base, EC 1272 regulation, etc).

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.