

# SAFETY DATA SHEET

**ShellSol D 100**

Print Date 29.11.2023

Revision Date 22.11.2023

Version 2.3

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Trade name	: ShellSol D 100
Product code	: Q7732
CAS-No.	: 64742-47-8
Synonyms	: Hydrocarbons, C13-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture	: Industrial Solvent.
Uses advised against	: This product must not be used in applications other than the above without first seeking the advice of the supplier.

### 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier	: <b>SHELL MARKETS (MIDDLE EAST) LIMITED</b> CHEMICALS PO Box 307 JEBEL ALI, DUBAI Unit.Arab Emir.
Telephone	:
Telefax	:
Contact for Safety Data Sheet	:

### 1.4 Emergency telephone number

Other information	: SHELLSOL is a trademark owned by Shell Trademark Management B.V. and Shell Brands Inc. and used by affiliates of Shell plc.
-------------------	---

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

#### GHS Classification

Aspiration hazard	: Category 1
Skin irritation	: Category 3

### 2.2 Label elements

# SAFETY DATA SHEET

**ShellSol D 100**

Print Date 29.11.2023

Revision Date 22.11.2023

Version 2.3

## GHS-Labeling

Hazard pictograms

:



Signal word

: Danger

Hazard statements

: **PHYSICAL HAZARDS:**  
Not classified as a physical hazard under GHS criteria.  
**HEALTH HAZARDS:**  
H304 May be fatal if swallowed and enters airways.  
H316 Causes mild skin irritation.  
**ENVIRONMENTAL HAZARDS:**  
Not classified as an environmental hazard under GHS criteria.

Precautionary statements

: **Prevention:**  
P243 Take precautionary measures against static discharge.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  
**Response:**  
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.  
P331 Do NOT induce vomiting.  
P332 + P313 If skin irritation occurs: Get medical advice/ attention.  
**Storage:**  
P405 Store locked up.  
**Disposal:**  
P501 Dispose of contents and container to appropriate waste site or reclaimer in accordance with local and national regulations.

## 2.3 Other hazards

May form flammable/explosive vapour-air mixture.  
This material is a static accumulator.  
Even with proper grounding and bonding, this material can still accumulate an electrostatic charge.  
If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur.

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

#### Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
Distillates (petroleum), hydro- treated light; Kerosine — unspecified	64742-47-8	100

# SAFETY DATA SHEET

**ShellSol D 100**

Print Date 29.11.2023

Revision Date 22.11.2023

Version 2.3

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- |                            |  |
|----------------------------|--|
| General advice             | : Not expected to be a health hazard when used under normal conditions.  |
| Protection of first-aiders | : When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.  |
| If inhaled                 | : No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.   |
| In case of skin contact    | : Remove contaminated clothing. Immediately flush skin with large amounts of water for at least 15 minutes, and follow by washing with soap and water if available. If redness, swelling, pain and/or blisters occur, transport to the nearest medical facility for additional treatment.  |
| In case of eye contact     | : Flush eye with copious quantities of water.<br>Remove contact lenses, if present and easy to do. Continue rinsing.<br>If persistent irritation occurs, obtain medical attention.   |
| If swallowed               | : Call emergency number for your location / facility.<br>If swallowed, do not induce vomiting: transport to nearest medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.<br>If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (38.3°C), shortness of breath, chest congestion or continued coughing or wheezing. |

### 4.2 Most important symptoms and effects, both acute and delayed

- |          |   |
|----------|---|
| Symptoms | : Not considered to be an inhalation hazard under normal conditions of use.<br>Possible respiratory irritation signs and symptoms may include a temporary burning sensation of the nose and throat, coughing, and/or difficulty breathing.<br><br>Skin irritation signs and symptoms may include a burning sensation, redness, or swelling.<br><br>No specific hazards under normal use conditions.<br>Eye irritation signs and symptoms may include a burning sensation, redness, swelling, and/or blurred vision.<br><br>If material enters lungs, signs and symptoms may include coughing, choking, wheezing, difficulty in breathing, chest |
|----------|---|

# SAFETY DATA SHEET

**ShellSol D 100**

Print Date 29.11.2023

Revision Date 22.11.2023

Version 2.3

congestion, shortness of breath, and/or fever.  
If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (38.3°C), shortness of breath, chest congestion or continued coughing or wheezing.

Defatting dermatitis signs and symptoms may include a burning sensation and/or a dried/cracked appearance.

## 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Call a doctor or poison control center for guidance.  
Potential for chemical pneumonitis.  
Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.  
Unsuitable extinguishing media : Do not use water in a jet.

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Clear fire area of all non-emergency personnel. Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Flammable vapours may be present even at temperatures below the flash point. The vapour is heavier than air, spreads along the ground and distant ignition is possible. Will float and can be reignited on surface water.

### 5.3 Advice for firefighters

Special protective equipment for firefighters : Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).  
Specific extinguishing methods : Standard procedure for chemical fires.  
Further information : Keep adjacent containers cool by spraying with water.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Observe all relevant local and international regulations.

# SAFETY DATA SHEET

**ShellSol D 100**

Print Date 29.11.2023

Revision Date 22.11.2023

Version 2.3

Notify authorities if any exposure to the general public or the environment occurs or is likely to occur.

Local authorities should be advised if significant spillages cannot be contained.

Avoid contact with skin, eyes and clothing.

Isolate hazard area and deny entry to unnecessary or unprotected personnel.

Do not breathe fumes, vapour.

Do not operate electrical equipment.

## 6.2 Environmental precautions

- Environmental precautions : Shut off leaks, if possible without personal risks. Remove all possible sources of ignition in the surrounding area. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. Attempt to disperse the vapour or to direct its flow to a safe location for example by using fog sprays. Take precautionary measures against static discharge. Ensure electrical continuity by bonding and grounding (earthing) all equipment.  
Monitor area with combustible gas indicator.

## 6.3 Methods and materials for containment and cleaning up

- Methods for cleaning up : For small liquid spills (< 1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.  
For large liquid spills (> 1 drum), transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.  
Ventilate contaminated area thoroughly.  
If contamination of site occurs remediation may require specialist advice.

## 6.4 Reference to other sections

For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet.,  
For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.

## SECTION 7: Handling and storage

- General Precautions : Avoid breathing of or direct contact with material. Only use in

# SAFETY DATA SHEET

**ShellSol D 100**

Print Date 29.11.2023

Revision Date 22.11.2023

Version 2.3

well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet.

Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.

Ensure that all local regulations regarding handling and storage facilities are followed.

## 7.1 Precautions for safe handling

Advice on safe handling

- : Avoid inhaling vapour and/or mists.
- Avoid contact with skin, eyes and clothing.
- Extinguish any naked flames. Do not smoke. Remove ignition sources. Avoid sparks.
- Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols.
- Bulk storage tanks should be diked (bunded).
- When using do not eat or drink.

The vapour is heavier than air, spreads along the ground and distant ignition is possible.

Product Transfer

- : Even with proper grounding and bonding, this material can still accumulate an electrostatic charge. If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur. Be aware of handling operations that may give rise to additional hazards that result from the accumulation of static charges. These include but are not limited to pumping (especially turbulent flow), mixing, filtering, splash filling, cleaning and filling of tanks and containers, sampling, switch loading, gauging, vacuum truck operations, and mechanical movements. These activities may lead to static discharge e.g. spark formation. Restrict line velocity during pumping in order to avoid generation of electrostatic discharge ( $\leq 1$  m/s until fill pipe submerged to twice its diameter, then  $\leq 7$  m/s). Avoid splash filling. Do NOT use compressed air for filling, discharging, or handling operations.

Refer to guidance under Handling section.

## 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

- : Refer to section 15 for any additional specific legislation covering the packaging and storage of this product.

Other data

- : Storage Temperature: Ambient.

Bulk storage tanks should be diked (bunded). Locate tanks away from heat and other sources of ignition. Cleaning, inspection and maintenance of storage tanks is a specialist operation, which requires the implementation of strict

# SAFETY DATA SHEET

**ShellSol D 100**

Print Date 29.11.2023

Revision Date 22.11.2023

Version 2.3

procedures and precautions. Must be stored in a diked (bunded) well- ventilated area, away from sunlight, ignition sources and other sources of heat. Keep away from aerosols, flammables, oxidizing agents, corrosives and from other flammable products which are not harmful or toxic to man or to the environment. Electrostatic charges will be generated during pumping. Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment to reduce the risk. The vapours in the head space of the storage vessel may lie in the flammable/explosive range and hence may be flammable.

- Packaging material : **Suitable material:** For containers, or container linings use mild steel, stainless steel. For container paints, use epoxy paint, zinc silicate paint.  
**Unsuitable material:** Avoid prolonged contact with natural, butyl or nitrile rubbers.
- Container Advice : Do not cut, drill, grind, weld or perform similar operations on or near containers.

## 7.3 Specific end use(s)

- Specific use(s) : Not applicable

See additional references that provide safe handling practices for liquids that are determined to be static accumulators: American Petroleum Institute 2003 (Protection Against Ignitions Arising out of Static, Lightning and Stray Currents) or National Fire Protection Agency 77 (Recommended Practices on Static Electricity).  
IEC/TS 60079-32-1: Electrostatic hazards, guidance

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Aliphatic dearom. solvents 200 - 250		TWA	1.050 mg/m <sup>3</sup>	EU HSPA

#### Biological occupational exposure limits

No biological limit allocated.

#### Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general

# SAFETY DATA SHEET

**ShellSol D 100**

Print Date 29.11.2023

Revision Date 22.11.2023

Version 2.3

workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods  
<http://www.cdc.gov/niosh/>

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods  
<http://www.osha.gov/>

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances  
<http://www.hse.gov.uk/>

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA) , Germany  
<http://www.dguv.de/inhalt/index.jsp>

L'Institut National de Recherche et de Sécurité, (INRS), France <http://www.inrs.fr/accueil>

## 8.2 Exposure controls

**Engineering measures** The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

Use sealed systems as far as possible.

Adequate explosion-proof ventilation to control airborne concentrations below the exposure guidelines/limits.

Local exhaust ventilation is recommended.

Firewater monitors and deluge systems are recommended.

Eye washes and showers for emergency use.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

### General Information:

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned.

Practice good housekeeping.

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

### Personal protective equipment

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Eye protection : If material is handled such that it could be splashed into eyes, protective eyewear is recommended.

Hand protection



# SAFETY DATA SHEET

**ShellSol D 100**

Print Date 29.11.2023

Revision Date 22.11.2023

Version 2.3

## Remarks

- : Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. Longer term protection: butyl-rubber Nitrile rubber gloves.

Incidental contact/Splash protection: Nitrile rubber gloves. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

## Skin and body protection

- : Skin protection is not required under normal conditions of use. For prolonged or repeated exposures use impervious clothing over parts of the body subject to exposure. If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to relevant Standard, and provide employee skin care programmes.

Wear antistatic and flame-retardant clothing, if a local risk assessment deems it so.

## Respiratory protection

- : If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are unsuitable (e.g. airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. If air-filtering respirators are suitable for conditions of use: Select a filter suitable for organic gases and vapours [Type A

# SAFETY DATA SHEET

**ShellSol D 100**

Print Date 29.11.2023

Revision Date 22.11.2023

Version 2.3

boiling point >65°C (149°F)].

Hygiene measures : Wash hands before eating, drinking, smoking and using the toilet. Launder contaminated clothing before re-use. Do not ingest. If swallowed, then seek immediate medical assistance.

## Environmental exposure controls

General advice : Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour.  
Minimise release to the environment. An environmental assessment must be made to ensure compliance with local environmental legislation.  
Information on accidental release measures are to be found in section 6.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Appearance : Liquid.

Colour : colourless

Odour : Paraffinic

Odour Threshold : Data not available

pH : Not applicable

Melting / freezing point : < -30 °C

Boiling point/boiling range : Typical 238 - 257 °C

Flash point : Typical 105 °C  
Method: ASTM D-93 / PMCC

Evaporation rate : 0,01  
Method: ASTM D 3539, nBuAc=1

3.900  
Method: DIN 53170, di-ethyl ether=1

Flammability

Flammability (solid, gas) : Data not available

Lower explosion limit and upper explosion limit / flammability limit

Upper explosion limit : 5,5 %(V)

Lower explosion limit : 0,5 %(V)

# SAFETY DATA SHEET

**ShellSol D 100**

Print Date 29.11.2023

Revision Date 22.11.2023

Version 2.3

Vapour pressure : &lt; 4 Pa (20 °C)

&lt; 1 Pa (0 °C)

Relative vapour density : Data not available

Relative density : Data not available

Density : Typical 797 kg/m<sup>3</sup> (15 °C)  
Method: ASTM D4052**Solubility(ies)**

Water solubility : insoluble

Partition coefficient: n-octanol/water : log Pow: 7 - 8,7

Auto-ignition temperature : 232 °C Method: ASTM E-659

215 °C Method: DIN 51794

Decomposition temperature : Data not available

**Viscosity**

Viscosity, dynamic : Data not available

Viscosity, kinematic : Typical 3,2 mm<sup>2</sup>/s (25 °C)  
Method: ASTM D445

Explosive properties : Not classified

Oxidizing properties : Data not available

**9.2 Other information**

Surface tension : Typical 38 mN/m, 20 °C, ASTM D-971

Conductivity : Low conductivity: &lt; 100 pS/m

The conductivity of this material makes it a static accumulator. A liquid is typically considered nonconductive if its conductivity is below 100 pS/m and is considered semi-conductive if its conductivity is below 10,000 pS/m. Whether a liquid is nonconductive or semi-conductive, the precautions are the same. A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid

Molecular weight : 206 g/mol

---

**SECTION 10: Stability and reactivity****10.1 Reactivity**

The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.

**10.2 Chemical stability**

No hazardous reaction is expected when handled and stored according to provisions, Stable under normal conditions of use.

**10.3 Possibility of hazardous reactions**

Hazardous reactions : Reacts with strong oxidising agents.

**10.4 Conditions to avoid**

Conditions to avoid : Avoid heat, sparks, open flames and other ignition sources.

In certain circumstances product can ignite due to static electricity.

**10.5 Incompatible materials**

Materials to avoid : Strong oxidising agents.

**10.6 Hazardous decomposition products**

Hazardous decomposition products : Hazardous decomposition products are not expected to form during normal storage.

Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids and gases including carbon monoxide, carbon dioxide, sulphur oxides and unidentified organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation.

---

**SECTION 11: Toxicological information****11.1 Information on toxicological effects**

Basis for assessment : Information given is based on product testing, and/or similar products, and/or components.

Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

Information on likely routes of exposure : Exposure may occur via inhalation, ingestion, skin absorption, skin or eye contact, and accidental ingestion.

# SAFETY DATA SHEET

**ShellSol D 100**

Print Date 29.11.2023

Revision Date 22.11.2023

Version 2.3

## Acute toxicity

### Components:

#### **Distillates (petroleum), hydro- treated light; Kerosine — unspecified:**

Acute oral toxicity : LD50 Rat: > 5000 mg/kg  
Remarks: Low toxicity

Acute inhalation toxicity : Rat: Exposure time: 4 hrs  
Remarks: Low toxicity by inhalation.  
LC50 greater than near-saturated vapour concentration.

Acute dermal toxicity : LD50 Rabbit: > 2000 mg/kg  
Remarks: Low toxicity

## Skin corrosion/irritation

### Components:

#### **Distillates (petroleum), hydro- treated light; Kerosine — unspecified:**

Remarks: Causes mild skin irritation., Prolonged/repeated contact may cause defatting of the skin which can lead to dermatitis.

## Serious eye damage/eye irritation

### Components:

#### **Distillates (petroleum), hydro- treated light; Kerosine — unspecified:**

Remarks: Not irritating to eye.

## Respiratory or skin sensitisation

### Components:

#### **Distillates (petroleum), hydro- treated light; Kerosine — unspecified:**

Remarks: Not a sensitiser., Based on available data, the classification criteria are not met.

## Germ cell mutagenicity

### Components:

#### **Distillates (petroleum), hydro- treated light; Kerosine — unspecified:**

: Remarks: Not mutagenic.

## Carcinogenicity

### Components:

#### **Distillates (petroleum), hydro- treated light; Kerosine — unspecified:**

Remarks: Repeated exposure causes skin tumour promotion in experimental animals., Not a carcinogen., Based on available data, the classification criteria are not met.

# SAFETY DATA SHEET

**ShellSol D 100**

Print Date 29.11.2023

Revision Date 22.11.2023

Version 2.3

Material	GHS/CLP Carcinogenicity Classification
Distillates (petroleum), hydro-treated light; Kerosine — unspecified	No carcinogenicity classification.

## Reproductive toxicity

### Components:

**Distillates (petroleum), hydro- treated light; Kerosine — unspecified:**

Remarks: Not a developmental toxicant., Based on available data, the classification criteria are not met., Does not impair fertility.

## STOT - single exposure

### Components:

**Distillates (petroleum), hydro- treated light; Kerosine — unspecified:**

Remarks: Based on available data, the classification criteria are not met.

## STOT - repeated exposure

### Components:

**Distillates (petroleum), hydro- treated light; Kerosine — unspecified:**

Remarks: Kidney: caused kidney effects in male rats which are not considered relevant to humans

## Aspiration toxicity

### Components:

**Distillates (petroleum), hydro- treated light; Kerosine — unspecified:**

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

## Further information

### Components:

**Distillates (petroleum), hydro- treated light; Kerosine — unspecified:**

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

# SAFETY DATA SHEET

**ShellSol D 100**

Print Date 29.11.2023

Revision Date 22.11.2023

Version 2.3

## SECTION 12: Ecological information

### 12.1 Toxicity

Basis for assessment : Incomplete ecotoxicological data are available for this product. The information given below is based partly on a knowledge of the components and the ecotoxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

#### Components:

**Distillates (petroleum), hydro- treated light; Kerosine — unspecified :**

Toxicity to fish (Acute toxicity) : Remarks: LC/EC/IC50 > 100 mg/l  
Practically non toxic:  
Based on available data, the classification criteria are not met.

Toxicity to daphnia and other aquatic invertebrates (Acute toxicity) : Remarks: LC/EC/IC50 > 100 mg/l  
Practically non toxic:  
Based on available data, the classification criteria are not met.

Toxicity to algae (Acute toxicity) : Remarks: LC/EC/IC50 > 100 mg/l  
Practically non toxic:  
Based on available data, the classification criteria are not met.

Toxicity to bacteria (Acute toxicity) :  
Remarks: LC/EC/IC50 > 100 mg/l  
Practically non toxic:  
Based on available data, the classification criteria are not met.

Toxicity to fish (Chronic toxicity) : Remarks: Data not available

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : Remarks: Data not available

### 12.2 Persistence and degradability

#### Components:

**Distillates (petroleum), hydro- treated light; Kerosine — unspecified :**

Biodegradability : Remarks: Readily biodegradable., Oxidises rapidly by photo-chemical reactions in air.

### 12.3 Bioaccumulative potential

#### Product:

Partition coefficient: n-octanol/water : log Pow: 7 - 8,7

#### Components:

# SAFETY DATA SHEET

**ShellSol D 100**

Print Date 29.11.2023

Revision Date 22.11.2023

Version 2.3

**Distillates (petroleum), hydro- treated light; Kerosine — unspecified :**

Bioaccumulation

: Remarks: Has the potential to bioaccumulate.

## 12.4 Mobility in soil

**Components:**

**Distillates (petroleum), hydro- treated light; Kerosine — unspecified :**

Mobility

: Remarks: Floats on water., If it enters soil, it will adsorb to soil particles and will not be mobile.

## 12.5 Results of PBT and vPvB assessment

no data available

## 12.6 Other adverse effects

**Components:**

**Distillates (petroleum), hydro- treated light; Kerosine — unspecified :**

Additional ecological  
information

: In view of the high rate of loss from solution, the product is unlikely to pose a significant hazard to aquatic life.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product

: Recover or recycle if possible.

It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.

Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment.

Do not dispose into the environment, in drains or in water courses.

Do not dispose of tank water bottoms by allowing them to drain into the ground. This will result in soil and groundwater contamination.

Waste arising from a spillage or tank cleaning should be disposed of in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand.

Waste, spills or used product is dangerous waste.

Disposal should be in accordance with applicable regional, national, and local laws and regulations.

Local regulations may be more stringent than regional or national requirements and must be complied with.

MARPOL - see International Convention for the Prevention of Pollution from Ships (MARPOL 73/78) which provides



# SAFETY DATA SHEET

**ShellSol D 100**

Print Date 29.11.2023

Revision Date 22.11.2023

Version 2.3

technical aspects at controlling pollutions from ships.

Contaminated packaging : Drain container thoroughly.  
After draining, vent in a safe place away from sparks and fire.  
Residues may cause an explosion hazard. Do not puncture,  
cut or weld uncleaned drums.  
Send to drum recoverer or metal reclaimer.  
Comply with any local recovery or waste disposal regulations.

Local legislation

## SECTION 14: Transport information

### 14.1 UN number

ADR : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good  
IATA : Not regulated as a dangerous good

### 14.2 Proper shipping name

ADR : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good  
IATA : Not regulated as a dangerous good

### 14.3 Transport hazard class

ADR : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good  
IATA : Not regulated as a dangerous good

### 14.4 Packing group

ADR : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good  
IATA : Not regulated as a dangerous good

### 14.5 Environmental hazards

ADR : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good

### 14.6 Special precautions for user

Remarks : Special Precautions: Refer to Section 7, Handling & Storage,  
for special precautions which a user needs to be aware of or  
needs to comply with in connection with transport.

### 14.7 Maritime transport in bulk according to IMO instruments

MARPOL Annex 1 rules apply for bulk shipments by sea.

**Additional Information** : This product may be transported under nitrogen blanketing.  
Nitrogen is an odourless and invisible gas. Exposure to  
nitrogen may cause asphyxiation or death. Personnel must  
observe strict safety precautions when involved with a  
confined space entry.

# SAFETY DATA SHEET

**ShellSol D 100**

Print Date 29.11.2023

Revision Date 22.11.2023

Version 2.3

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Volatile organic compounds : 0 %

Other regulations : The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

#### The components of this product are reported in the following inventories:

AIIC	: Listed
DSL	: Listed
IECSC	: Listed
KECI	: Listed
PICCS	: Listed
TSCA	: Listed
NZIoC	: Listed
TCSI	: Listed

## SECTION 16: Other information

Abbreviations and Acronyms : The standard abbreviations and acronyms used in this document can be looked up in reference literature (e.g. scientific dictionaries) and/or websites.

ACGIH = American Conference of Governmental Industrial Hygienists

ADR = European Agreement concerning the International Carriage of Dangerous Goods by Road

AICS = Australian Inventory of Chemical Substances

ASTM = American Society for Testing and Materials

BEL = Biological exposure limits

BTEX = Benzene, Toluene, Ethylbenzene, Xylenes

CAS = Chemical Abstracts Service

CEFIC = European Chemical Industry Council

CLP = Classification Packaging and Labelling

COC = Cleveland Open-Cup

DIN = Deutsches Institut für Normung

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

DSL = Canada Domestic Substance List

EC = European Commission

EC50 = Effective Concentration fifty

ECETOC = European Center on Ecotoxicology and

# SAFETY DATA SHEET

**ShellSol D 100**

Print Date 29.11.2023

Revision Date 22.11.2023

Version 2.3

Toxicology Of Chemicals  
ECHA = European Chemicals Agency  
EINECS = The European Inventory of Existing Commercial Chemical Substances  
EL50 = Effective Loading fifty  
ENCS = Japanese Existing and New Chemical Substances Inventory  
EWC = European Waste Code  
GHS = Globally Harmonised System of Classification and Labelling of Chemicals  
IARC = International Agency for Research on Cancer  
IATA = International Air Transport Association  
IC50 = Inhibitory Concentration fifty  
IL50 = Inhibitory Level fifty  
IMDG = International Maritime Dangerous Goods  
INV = Chinese Chemicals Inventory  
IP346 = Institute of Petroleum test method N° 346 for the determination of polycyclic aromatics DMSO-extractables  
KECI = Korea Existing Chemicals Inventory  
LC50 = Lethal Concentration fifty  
LD50 = Lethal Dose fifty per cent.  
LL/EL/IL = Lethal Loading/Effective Loading/Inhibitory loading  
LL50 = Lethal Loading fifty  
MARPOL = International Convention for the Prevention of Pollution From Ships  
NOEC/NOEL = No Observed Effect Concentration / No Observed Effect Level  
OE\_HP V = Occupational Exposure - High Production Volume  
PBT = Persistent, Bioaccumulative and Toxic  
PICCS = Philippine Inventory of Chemicals and Chemical Substances  
PNEC = Predicted No Effect Concentration  
REACH = Registration Evaluation And Authorisation Of Chemicals  
RID = Regulations Relating to International Carriage of Dangerous Goods by Rail  
SKIN\_DES = Skin Designation  
STEL = Short term exposure limit  
TRA = Targeted Risk Assessment  
TSCA = US Toxic Substances Control Act  
TWA = Time-Weighted Average  
vPvB = very Persistent and very Bioaccumulative

## Further information

- Training advice : Provide adequate information, instruction and training for operators.
- Other information : A vertical bar (|) in the left margin indicates an amendment from the previous version.
- Sources of key data used to compile the Safety Data : The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell

# SAFETY DATA SHEET

**ShellSol D 100**

Print Date 29.11.2023

Revision Date 22.11.2023

Version 2.3

Sheet

Health Services, material suppliers' data, CONCAWE, EU  
IUCLID data base, EC 1272 regulation, etc).

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.