CARADOL ED260-02

Print Date 19.05.2023 Revision Date 19.05.2023 Version 1.3

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : CARADOL ED260-02

Product code : U1740 CAS-No. : 25322-69-4

Synonyms : Polyol

EC-No. : 500-039-8

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the : Use for the manufacture of polyurethane products.

Substance/Mixture

Uses advised against : This product must not be used in applications other than the

above without first seeking the advice of the supplier.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier : Shell Trading (M.E.) Pvt. Ltd.

PO Box 16968 16968 Jebel Ali Unit.Arab Emir. : +971 4 331 6500

 Telephone
 : +971 4 331 6500

 Telefax
 : +971 4 332 1597

 Contact for Safety Data
 : sccmsds@shell.com

Sheet

1.4 Emergency telephone number

+ (65) 6542 9595 (Alert-SGS)

Other information : CARADOL is a trademark owned by Shell Trademark

Management B.V. and Shell Brands Inc. and used by affiliates

of Royal Dutch Shell plc.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

GHS Classification

Based on available data this substance / mixture does not meet the classification criteria.

2.2 Label elements

GHS-Labelling

1 / 20 800001004915 AE

CARADOL ED260-02

Print Date 19.05.2023 Revision Date 19.05.2023 Version 1.3

Hazard pictograms : No Hazard Symbol required

Signal word : No signal word

Hazard statements : PHYSICAL HAZARDS:

Not classified as a physical hazard under GHS criteria.

HEALTH HAZARDS:

Not classified as a health hazard under GHS criteria.

ENVIRONMENTAL HAZARDS:

Not classified as an environmental hazard under GHS criteria.

Precautionary statements : **Prevention:**

No precautionary phrases.

Response:

No precautionary phrases.

Storage:

No precautionary phrases.

Disposal:

No precautionary phrases.

2.3 Other hazards

SECTION 3: Composition/information on ingredients

3.1 Substances

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
Polypropylene glycol	25322-69-4	<= 100

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Not expected to be a health hazard when used under normal

conditions.

Protection of first-aiders : When administering first aid, ensure that you are wearing the

appropriate personal protective equipment according to the

incident, injury and surroundings.

If inhaled : No treatment necessary under normal conditions of use.

If symptoms persist, obtain medical advice.

In case of skin contact : Remove contaminated clothing. Flush exposed area with

water and follow by washing with soap if available.

If persistent irritation occurs, obtain medical attention.

Print Date 19.05.2023 Revision Date 19.05.2023 Version 1.3

In case of eye contact : Flush eye with copious quantities of water. Remove contact lenses, if present and easy to do. Continue rinsing. If persistent irritation occurs, obtain medical attention.

If swallowed : In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Not considered to be an inhalation hazard under normal

conditions of use.

Possible respiratory irritation signs and symptoms may include

a temporary burning sensation of the nose and throat,

coughing, and/or difficulty breathing.

No specific hazards under normal use conditions.

Skin irritation signs and symptoms may include a burning

sensation, redness, or swelling.

Eye irritation signs and symptoms may include a burning sensation, redness, swelling, and/or blurred vision.

Ingestion may result in nausea, vomiting and/or diarrhoea.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Call a doctor or poison control center for guidance.

Treat symptomatically. Following cases of gross overexposure, investigation of liver, kidney and eye function may be advisable. Records of such incidents should be maintained

for future reference.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Large fires should only be fought by properly trained fire

fighters., Alcohol-resistant foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used

for small fires only.

Unsuitable extinguishing

media

: Do not use water in a jet.

5.2 Special hazards arising from the substance or mixture

Specific hazards during

firefighting

: Will only burn if enveloped in a pre-existing fire. Hazardous

combustion products may include: Carbon dioxide

Unidentified organic and inorganic compounds. Toxic gases

Carbon monoxide.

5.3 Advice for firefighters

Special protective equipment

for firefighters

: Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if

large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in

a confined space. Select fire fighter's clothing approved to

SAFFTY DATA SHFFT

	CAF	RADOL ED260-02
Print Date 19.05.2023	Revision Date 19.05.2023	Version 1.3
Specific extinguishing methods Further information	relevant Standards (e.g. Europe: ENd: Standard procedure for chemical firest: Clear fire area of all non-emergency particles All storage areas should be provided fighting facilities. Keep adjacent containers cool by spre	s. oersonnel. with adequate fire

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Observe all relevant local and international regulations.

Avoid contact with skin, eyes and clothing.

Avoid inhaling vapour and/or mists.

Extinguish any naked flames. Do not smoke. Remove ignition

sources. Avoid sparks.

6.2 Environmental precautions

Environmental precautions : Remove all possible sources of ignition in the surrounding

Prevent from spreading or entering into drains, ditches or rivers by using sand, earth, or other appropriate barriers. Use appropriate containment to avoid environmental

contamination.

Ventilate contaminated area thoroughly.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : For large liquid spills (> 1 drum), transfer by mechanical

> means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely For small liquid spills (< 1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an

> appropriate absorbent material and dispose of safely. Remove

contaminated soil and dispose of safely.

Proper disposal should be evaluated based on regulatory status of this material (refer to Section 13), potential contamination from subsequent use and spillage, and regulations governing disposal in the local area.

6.4 Reference to other sections

SAFFTY DATA SHFFT

CARADOL ED260-02

Print Date 19.05.2023 **Revision Date 19.05.2023** Version 1.3

For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet., For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.

SECTION 7: Handling and storage

General Precautions : Avoid breathing of or direct contact with material. Only use in

well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see

Section 8 of this Safety Data Sheet.

Use the information in this data sheet as input to a risk assessment of local circumstances to help determine

appropriate controls for safe handling, storage and disposal of

this material.

Ensure that all local regulations regarding handling and

storage facilities are followed.

7.1 Precautions for safe handling

Advice on safe handling : In accordance with good industrial hygiene practices.

precautions should be taken to avoid breathing of material.

Use local exhaust extraction over processing area. Avoid unintentional contact with isocvanates to prevent

uncontrolled polymerisation.

Avoid contact with skin, eyes and clothing.

Air-dry contaminated clothing in a well-ventilated area before

laundering.

Do not empty into drains. Handling Temperature:

Ambient.

When handling product in drums, safety footwear should be worn and proper handling equipment should be used.

Extinguish any naked flames. Do not smoke. Remove ignition

sources. Avoid sparks.

Product Transfer : Lines should be purged with nitrogen before and after product

transfer. Keep containers closed when not in use.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Refer to section 15 for any additional specific legislation covering the packaging and storage of this product.

Other data : Prevent all contact with water and with moist atmosphere.

> Tanks must be clean, dry and rust-free. Prevent ingress of water. Must be stored in a diked (bunded) well- ventilated area, away from sunlight, ignition sources and other sources of heat. Nitrogen blanket recommended for large tanks (capacity 100 m3 or higher). Drums should be stacked to a

maximum of 3 high.

Storage period : 24 month(s)

Storage Temperature: Ambient.

	CAR	RADOL ED260-02
Print Date 19.05.2023	Revision Date 19.05.2023	Version 1.3
	Storage should be handled at temperativiscosities are less than 500 cSt; typic should be fitted with heating coils in attemperatures are below the recomme temperatures. Heating coil skin temperatures are below the recomme temperatures.	cally at 25-50 °C. Tanks reas where the ambient nded product handling
Packaging material	 Suitable material: Stainless steel. For epoxy paint, zinc silicate paint. Unsuitable material: Copper. Copper 	•
7.3 Specific end use(s)		
Specific use(s)	: Not applicable	
	Ensure that all local regulations regard storage facilities are followed.	ding handling and

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Biological occupational exposure limits

No biological limit allocated.

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA) , Germany http://www.dquv.de/inhalt/index.isp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

8.2 Exposure controls

Engineering measures Where material is heated, sprayed or mist formed, there is greater potential

CARADOL ED260-02

Print Date 19.05.2023

Revision Date 19.05.2023

Version 1.3

for airborne concentrations to be generated.

Adequate ventilation to control airborne concentrations.

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

General Information:

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

Personal protective equipment

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Eye protection : If material is handled such that it could be splashed into eyes,

protective eyewear is recommended.

Hand protection

Remarks : Where hand contact with the product may occur the use of

gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. Longer term protection: Nitrile rubber. Incidental contact/Splash protection: PVC, neoprene or nitrile rubber gloves For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-

perfumed moisturizer is recommended.

Revision Date 19.05.2023

CARADOL ED260-02

Skin and body protection : Skin protection is not ordinarily required beyond standard

work clothes.

It is good practice to wear chemical resistant gloves.

Respiratory protection : No respiratory protection is ordinarily required under normal

conditions of use.

In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material.

Version 1.3

Hygiene measures : Wash hands before eating, drinking, smoking and using the

toilet. Launder contaminated clothing before re-use.

Environmental exposure controls

Print Date 19.05.2023

General advice : Local guidelines on emission limits for volatile substances

must be observed for the discharge of exhaust air containing

vapour.

Minimise release to the environment. An environmental assessment must be made to ensure compliance with local

environmental legislation.

Information on accidental release measures are to be found in

section 6.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : Liquid.

Colour : Clear colourless

Odour : odourless
Odour Threshold : Not relevant
pH : Not applicable
Melting point/freezing point : Data not available

Boiling point/boiling range : 288 °C

Flash point : Typical > 140 °C

Method: ASTM D93 (PMCC)

Evaporation rate : Data not available

Flammability

Flammability (solid, gas) : Not applicable

Lower explosion limit and upper explosion limit / flammability limit

Upper explosion limit : Data not available

Lower explosion limit : Data not available

CARADOL ED260-02

Print Date 19.05.2023 Revision Date 19.05.2023 Version 1.3

Vapour pressure : 0,0008 hPa (20 °C)

Relative vapour density : Data not available
Relative density : Data not available

Density : Typical 1.008 kg/m3 (20 °C)

Method: ASTM D4052

Solubility(ies)

Water solubility : Miscible.

Partition coefficient: n-

octanol/water

: log Pow: 0,01 (25 °C)

Auto-ignition temperature : 305 °C

Decomposition temperature : > 270 °C

Viscosity

Viscosity, dynamic : Typical 70 mPa.s (25 °C)

Method: ASTM D445

Viscosity, kinematic : Data not available

Explosive properties : Not classified

Oxidizing properties : Not applicable

9.2 Other information

Surface tension : 63,6 mN/m

Conductivity: > 10,000 pS/m, A number of factors,

for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity

of a liquid, This material is not expected to be a static

accumulator.

Molecular weight : Data not available

SECTION 10: Stability and reactivity

10.1 Reactivity

The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.

10.2 Chemical stability

No hazardous reaction is expected when handled and stored according to provisions, Hygroscopic.

CARADOL ED260-02

Print Date 19.05.2023 **Revision Date 19.05.2023** Version 1.3

10.3 Possibility of hazardous reactions

Hazardous reactions : Polymerises exothermically with di-isocyanates at ambient

temperatures.

The reaction becomes progressively more vigorous and can be violent at higher temperatures if the miscibility of reaction partners is good or is supported by stirring or by the presence

of solvents.

Reacts with strong oxidising agents.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames, and sparks.

Product cannot ignite due to static electricity.

10.5 Incompatible materials

: Avoid contact with isocyanates, copper and copper alloys, Materials to avoid

zinc, strong oxidizing agents, and water.

10.6 Hazardous decomposition products

Hazardous decomposition

products

: Unknown toxic products may be formed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Basis for assessment : Information given is based on data obtained from similar

substances.

Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for

individual component(s).

exposure

Information on likely routes of : Exposure may occur via inhalation, ingestion, skin absorption,

skin or eye contact, and accidental ingestion.

Acute toxicity

Product:

Acute oral toxicity : LD 50 : > 2.000 mg/kg

Remarks: Based on available data, the classification criteria

are not met.

Acute inhalation toxicity : Remarks: Based on available data, the classification criteria

are not met.

Acute dermal toxicity : LD 50 : > 2.000 mg/kg

Remarks: Low toxicity

Based on available data, the classification criteria are not met.

CARADOL ED260-02

Print Date 19.05.2023 **Revision Date 19.05.2023** Version 1.3

Components:

Polypropylene glycol:

Acute oral toxicity : LD 50 Rat, male and female: > 5.000 mg/kg

Method: OECD Test Guideline 401

Remarks: Based on available data, the classification criteria

are not met.

Acute inhalation toxicity : LD50 Rat, male and female: > 20 mg/l

> Exposure time: 4 h Test atmosphere: vapour

Method: OECD Test Guideline 403

Remarks: Based on available data, the classification criteria

are not met.

Acute dermal toxicity : LD 50 : > 2.000 mg/kg

Remarks: Low toxicity

Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Product:

Remarks: Based on available data, the classification criteria are not met.

Components:

Polypropylene glycol:

Species: Rabbit

Method: Test(s) equivalent or similar to OECD Test Guideline 404

Remarks: Slightly irritating to skin., Insufficient to classify., Based on available data, the

classification criteria are not met.

Serious eye damage/eye irritation

Product:

Remarks: Based on available data, the classification criteria are not met.

Components:

Polypropylene glycol:

Species: Rabbit

Method: OECD Test Guideline 405

Remarks: Slightly irritating to the eye., Insufficient to classify., Based on available data, the

classification criteria are not met.

Respiratory or skin sensitisation

Product:

Remarks: Based on available data, the classification criteria are not met.

CARADOL ED260-02

Print Date 19.05.2023 **Revision Date 19.05.2023** Version 1.3

Components:

Polypropylene alycol:

Species: Guinea pig

Method: OECD Test Guideline 406

Remarks: Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Product:

: Remarks: Based on available data, the classification criteria are not met.

Components:

Polypropylene glycol:

Genotoxicity in vitro

- : Method: Test(s) equivalent or similar to OECD Guideline 471 Remarks: Based on available data, the classification criteria are not met.
- : Method: Test(s) equivalent or similar to OECD Guideline 471 Remarks: Based on available data, the classification criteria are not met.
- : Method: Directive 67/548/EEC, Annex V, B.10. Remarks: Based on available data, the classification criteria are not met.
- : Method: Directive 67/548/EEC, Annex V, B.10. Remarks: Based on available data, the classification criteria are not met.
- : Test species: RatMethod: Directive 67/548/EEC, Annex V,

Remarks: Based on available data, the classification criteria are not met.

Carcinogenicity

Product:

Remarks: Based on available data, the classification criteria are not met.

Components:

Polypropylene glycol:

Remarks: Based on available data, the classification criteria are not met.

Material	GHS/CLP Carcinogenicity Classification
Polypropylene glycol	No carcinogenicity classification.

CARADOL ED260-02

Print Date 19.05.2023 Revision Date 19.05.2023 Version 1.3

Reproductive toxicity

Product:

Remarks: Based on available data, the classification criteria

are not met.

Components:

Polypropylene glycol:

Species: Rat

Sex: male and female

Application Route: Inhalation

Method: Equivalent or similar to OECD Test Guideline 416 Remarks: Based on available data, the classification criteria

are not met.

Effects on foetal : Species: Rat, female development Application Route: Oral

Method: OECD Test Guideline 414

Remarks: Based on available data, the classification criteria

are not met.

STOT - single exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

Components:

Polypropylene glycol:

Exposure routes: Inhalation

Target Organs: Central nervous system

Remarks: May cause drowsiness or dizziness., Based on available data, the classification

criteria are not met.

STOT - repeated exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

Components:

Polypropylene glycol:

Remarks: Based on available data, the classification criteria are not met.

Repeated dose toxicity

CARADOL ED260-02

Print Date 19.05.2023 **Revision Date 19.05.2023** Version 1.3

Components:

Polypropylene alycol:

Rat, male and female: **Application Route: Inhalation** Test atmosphere: Gas

Method: OECD Test Guideline 413

Target Organs: No specific target organs noted

Aspiration toxicity

Product:

Not an aspiration hazard.

Components:

Polypropylene glycol:

Not an aspiration hazard.

Further information

Product:

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

Components:

Polypropylene glycol:

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

SECTION 12: Ecological information

12.1 Toxicity

Basis for assessment : Incomplete ecotoxicological data are available for this product.

> The information given below is based partly on a knowledge of the components and the ecotoxicology of similar products.

Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for

individual component(s).

Product:

Toxicity to fish (Acute

toxicity)

: LC50: > 100 mg/l

Remarks: Based on available data, the classification criteria

are not met.

Practically non toxic:

		CARADOL ED260-02
Print Date 19.05.2023	Revision Date 19.05.2023	Version 1.3

Toxicity to daphnia and other

aquatic invertebrates (Acute

toxicity)

: EC50 : > 100 mg/l

Remarks: Based on available data, the classification criteria

are not met.

Practically non toxic:

Toxicity to algae (Acute

toxicity)

: EC50 : > 100 mg/l

Remarks: Practically non toxic:

Based on available data, the classification criteria are not met.

Toxicity to fish (Chronic

toxicity)

: Remarks: Data not available

Toxicity to daphnia and other aquatic invertebrates

(Chronic toxicity)

: Remarks: Data not available

Toxicity to bacteria (Acute

toxicity)

: IC50 : > 100 mg/l

Remarks: Based on available data, the classification criteria

are not met.

Practically non toxic:

Components:

Polypropylene glycol:

Toxicity to fish (Acute

toxicity)

: LC50 (Danio rerio (zebra fish)): > 100 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Remarks: Based on available data, the classification criteria

are not met.

Toxicity to daphnia and other aquatic invertebrates (Acute

toxicity)

: EC50 (Daphnia magna (Water flea)): > 105.8 mg/l

Exposure time: 48 h

Remarks: Based on available data, the classification criteria

are not met.

Toxicity to algae (Acute

toxicity)

: EC50 (Desmodesmus subspicatus (green algae)): > 100 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 202

Remarks: Based on available data, the classification criteria

are not met.

Toxicity to bacteria (Acute

toxicity)

: EC50 (Activated sludge, domestic waste): > 1.000 mg/l

Exposure time: 3 h

Method: OECD Test Guideline 209

Remarks: Based on available data, the classification criteria

are not met.

Toxicity to fish (Chronic

toxicity)

: Remarks: Data not available

Toxicity to daphnia and other

aquatic invertebrates (Chronic toxicity)

: NOEC: > 10 mg/l Exposure time: 21 d

> Species: Daphnia magna (Water flea) Method: OECD Test Guideline 211

CARADOL ED260-02

Print Date 19.05.2023 Revision Date 19.05.2023 Version 1.3

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: Readily biodegradable.

Components:

Polypropylene glycol:

Biodegradation: 86,6 %

Exposure time: 28 d

Method: OECD Test Guideline 301F Remarks: Readily biodegradable.

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: Does not bioaccumulate significantly.

Partition coefficient: n-

octanol/water

: log Pow: 0,01 (25 °C)

Components:

Polypropylene glycol:

Bioaccumulation : Remarks: Does not bioaccumulate significantly.

12.4 Mobility in soil

Product:

Mobility : Remarks: If the product enters soil, one or more constituents

will or may be mobile and may contaminate groundwater.

Components:

Polypropylene glycol:

Mobility : Remarks: If product enters soil, it will be highly mobile and

may contaminate groundwater., Dissolves in water.

: Remarks: If the product enters soil, one or more constituents will or may be mobile and may contaminate groundwater.

12.5 Results of PBT and vPvB assessment

Components:

Polypropylene glycol:

Assessment : The substance does not fulfill all screening criteria for

persistence, bioaccumulation and toxicity and hence is not

considered to be PBT or vPvB.

12.6 Other adverse effects

no data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

	CARA	NDOL ED260-02
Print Date 19.05.2023	Revision Date 19.05.2023	Version 1.3
Product	: Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.	
	Do not dispose into the environment, in courses. Waste product should not be allowed to water.	
	Disposal should be in accordance with a national, and local laws and regulations. Local regulations may be more stringent national requirements and must be comp	than regional or
Contaminated packaging	: Drain container thoroughly. After draining, vent in a safe place away Send to drum recoverer or metal reclaim Dispose in accordance with prevailing re to a recognized collector or contractor. the collector or contractor should be esta	ner. egulations, preferably The competence of
Local legislation		

SECTION 14: Transport information

14.1 UN number

ADR : Not regulated as a dangerous good **IMDG** : Not regulated as a dangerous good **IATA** : Not regulated as a dangerous good

14.2 Proper shipping name

ADR : Not regulated as a dangerous good **IMDG** : Not regulated as a dangerous good **IATA** : Not regulated as a dangerous good

14.3 Transport hazard class

ADR : Not regulated as a dangerous good **IMDG** : Not regulated as a dangerous good **IATA** : Not regulated as a dangerous good

14.4 Packing group

ADR : Not regulated as a dangerous good **IMDG** Not regulated as a dangerous good IATA : Not regulated as a dangerous good

14.5 Environmental hazards

ADR : Not regulated as a dangerous good **IMDG** Not regulated as a dangerous good

14.6 Special precautions for user

Remarks : Special Precautions: Refer to Section 7, Handling & Storage,

SAFFTY DATA SHFFT

CARADOL ED260-02

Print Date 19.05.2023 **Revision Date 19.05.2023** Version 1.3

for special precautions which a user needs to be aware of or

needs to comply with in connection with transport.

14.7 Maritime transport in bulk according to IMO instruments

Ζ Pollution category 3 Ship type

Polypropylene Glycol Product name

Additional Information : This product may be transported under nitrogen blanketing.

> Nitrogen is an odourless and invisible gas. Exposure to nitrogen enriched atmospheres displaces available oxygen which may cause asphyxiation or death. Personnel must observe strict safety precautions when involved with a

confined space entry.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Other regulations : The regulatory information is not intended to be

comprehensive. Other regulations may apply to this material.

The components of this product are reported in the following inventories:

AIIC : Listed DSL : Listed **IECSC** : Listed **ENCS** Listed KECI : Listed NZIoC : Listed **PICCS** : Listed **TSCA** : Listed **TCSI** : Listed

SECTION 16: Other information

Abbreviations and Acronyms : The standard abbreviations and acronyms used in this

document can be looked up in reference literature (e.g.

scientific dictionaries) and/or websites.

ACGIH = American Conference of Governmental Industrial

Hygienists

ADR = European Agreement concerning the International

Carriage of Dangerous Goods by Road

AICS = Australian Inventory of Chemical Substances ASTM = American Society for Testing and Materials

BEL = Biological exposure limits

CARADOL ED260-02

Version 1.3

Print Date 19.05.2023 Revision Date 19.05.2023

BTEX = Benzene, Toluene, Ethylbenzene, Xylenes

CAS = Chemical Abstracts Service

CEFIC = European Chemical Industry Council

CLP = Classification Packaging and Labelling

COC = Cleveland Open-Cup

DIN = Deutsches Institut fur Normung

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

DSL = Canada Domestic Substance List

EC = European Commission

EC50 = Effective Concentration fifty

ECETOC = European Center on Ecotoxicology and

Toxicology Of Chemicals

ECHA = European Chemicals Agency

EINECS = The European Inventory of Existing Commercial

Chemical Substances

EL50 = Effective Loading fifty

ENCS = Japanese Existing and New Chemical Substances Inventory

EWC = European Waste Code

GHS = Globally Harmonised System of Classification and

Labelling of Chemicals

IARC = International Agency for Research on Cancer

IATA = International Air Transport Association

IC50 = Inhibitory Concentration fifty

IL50 = Inhibitory Level fifty

IMDG = International Maritime Dangerous Goods

INV = Chinese Chemicals Inventory

IP346 = Institute of Petroleum test method N° 346 for the determination of polycyclic aromatics DMSO-extractables

KECI = Korea Existing Chemicals Inventory

LC50 = Lethal Concentration fifty

LD50 = Lethal Dose fifty per cent.

LL/EL/IL = Lethal Loading/Effective Loading/Inhibitory loading

LL50 = Lethal Loading fifty

MARPOL = International Convention for the Prevention of

Pollution From Ships

NOEC/NOEL = No Observed Effect Concentration / No

Observed Effect Level

OE HPV = Occupational Exposure - High Production Volume

PBT = Persistent, Bioaccumulative and Toxic

PICCS = Philippine Inventory of Chemicals and Chemical

Substances

PNEC = Predicted No Effect Concentration

REACH = Registration Evaluation And Authorisation Of

Chemicals

RID = Regulations Relating to International Carriage of

Dangerous Goods by Rail

SKIN_DES = Skin Designation

STEL = Short term exposure limit

TRA = Targeted Risk Assessment

TSCA = US Toxic Substances Control Act

TWA = Time-Weighted Average

	CARA	ADOL ED260-02
Print Date 19.05.2023	Revision Date 19.05.2023	Version 1.3
	vPvB = very Persistent and very Bioacc	umulative
Further information		
Training advice	: Provide adequate information, instructio operators.	n and training for
Other information	: A vertical bar () in the left margin indica from the previous version.	tes an amendment
Sources of key data used to compile the Safety Data Sheet	: The quoted data are from, but not limited sources of information (e.g. toxicological Health Services, material suppliers' data IUCLID date base, EC 1272 regulation,	ll data from Shell a, CONCAWE, EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.