

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name	: Risella X 409
Product code	: Q6566
Registration number	: 01-2120081657-46-0000
Synonyms	: Hydrocarbons C15-C19, n-alkanes, isoalkanes, <2% aromatics
CAS-No.	: 1437281-01-0
EC-No.	: 940-730-5

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture	: Solvent. Please refer to Ch16 and/or the annexes for the registered uses under REACH.
Uses advised against	: This product must not be used in applications other than the above without first seeking the advice of the supplier.

#### 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier	: <b>Shell Chemicals Europe B.V.</b> PO Box 2334 3000 CH Rotterdam Netherlands
Telephone	: +31 (0)10 441 5137 / +31 (0)10 441 5191
Telefax	: +31 (0)20 716 8316 / +31 (0)20 713 9230
Email Contact for Safety Data Sheet	: sccmsds@shell.com

#### 1.4 Emergency telephone number

+44 (0) 1235 239 670 (This telephone number is available 24 hours per day, 7 days per week)

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Aspiration hazard, Category 1

H304: May be fatal if swallowed and enters airways.

#### 2.2 Label elements

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms

:



Signal word

: Danger

Hazard statements

:

H304

PHYSICAL HAZARDS:

Not classified as a physical hazard according to CLP criteria.

HEALTH HAZARDS:

May be fatal if swallowed and enters airways.

ENVIRONMENTAL HAZARDS:

Not classified as environmental hazard according to CLP criteria.

Supplemental Hazard Statements

: EUH066

Repeated exposure may cause skin dryness or cracking.

Precautionary statements

: **Prevention:**

P243

**Response:**

P301 + P310

P331

**Storage:**

P405

**Disposal:**

P501

Take action to prevent static discharges.

IF SWALLOWED: Immediately call a POISON CENTER/ doctor.  
Do NOT induce vomiting.

Store locked up.

Dispose of contents/ container to an approved waste disposal plant.

### 2.3 Other hazards

The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB.

May form flammable/explosive vapour-air mixture.

This material is a static accumulator.

Even with proper grounding and bonding, this material can still accumulate an electrostatic charge.

If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur.

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

#### Hazardous components

Chemical name	CAS-No. EC-No.	Concentration (% w/w)
---------------	-------------------	-----------------------

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

Alkanes, C15-19-branched  
and linear

1437281-01-0  
940-730-5

<= 100

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General advice : Not expected to be a health hazard when used under normal conditions.
- Protection of first-aiders : When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.
- If inhaled : No treatment necessary under normal conditions of use.  
If symptoms persist, obtain medical advice.
- In case of skin contact : Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available.  
If persistent irritation occurs, obtain medical attention.
- In case of eye contact : Flush eye with copious quantities of water.  
Remove contact lenses, if present and easy to do. Continue rinsing.  
If persistent irritation occurs, obtain medical attention.
- If swallowed : Call emergency number for your location / facility.  
If swallowed, do not induce vomiting: transport to nearest medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.  
If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (38.3°C), shortness of breath, chest congestion or continued coughing or wheezing.

#### 4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Not considered to be an inhalation hazard under normal conditions of use.  
Possible respiratory irritation signs and symptoms may include a temporary burning sensation of the nose and throat, coughing, and/or difficulty breathing.
- No specific hazards under normal use conditions.  
Skin irritation signs and symptoms may include a burning sensation, redness, or swelling.
- No specific hazards under normal use conditions.  
Eye irritation signs and symptoms may include a burning sensation, redness, swelling, and/or blurred vision.
- If material enters lungs, signs and symptoms may include

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

coughing, choking, wheezing, difficulty in breathing, chest congestion, shortness of breath, and/or fever.  
If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (38.3°C), shortness of breath, chest congestion or continued coughing or wheezing.

Defatting dermatitis signs and symptoms may include a burning sensation and/or a dried/cracked appearance.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Call a doctor or poison control center for guidance.  
Potential for chemical pneumonitis.  
Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.  
Unsuitable extinguishing media : Do not use water in a jet.

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Clear fire area of all non-emergency personnel. Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Flammable vapours may be present even at temperatures below the flash point. The vapour is heavier than air, spreads along the ground and distant ignition is possible. Will float and can be reignited on surface water.

### 5.3 Advice for firefighters

Special protective equipment for firefighters : Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).  
Specific extinguishing methods : Standard procedure for chemical fires.  
Further information : Keep adjacent containers cool by spraying with water.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

- Personal precautions :
- Observe all relevant local and international regulations.
  - Notify authorities if any exposure to the general public or the environment occurs or is likely to occur.
  - Local authorities should be advised if significant spillages cannot be contained.
  - 6.1.1 For non emergency personnel:
    - Avoid contact with skin, eyes and clothing.
    - Isolate hazard area and deny entry to unnecessary or unprotected personnel.
    - Do not breathe fumes, vapour.
    - Do not operate electrical equipment.
  - 6.1.2 For emergency responders:
    - Avoid contact with skin, eyes and clothing.
    - Isolate hazard area and deny entry to unnecessary or unprotected personnel.
    - Do not breathe fumes, vapour.
    - Do not operate electrical equipment.

### 6.2 Environmental precautions

- Environmental precautions :
- Shut off leaks, if possible without personal risks. Remove all possible sources of ignition in the surrounding area. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. Attempt to disperse the vapour or to direct its flow to a safe location for example by using fog sprays. Take precautionary measures against static discharge. Ensure electrical continuity by bonding and grounding (earthing) all equipment.
  - Monitor area with combustible gas indicator.

### 6.3 Methods and materials for containment and cleaning up

- Methods for cleaning up :
- For small liquid spills (< 1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.
  - For large liquid spills (> 1 drum), transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.
  - Ventilate contaminated area thoroughly.
  - If contamination of site occurs remediation may require specialist advice.

### 6.4 Reference to other sections

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet.,  
For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.

### SECTION 7: Handling and storage

General Precautions : Avoid breathing of or direct contact with material. Only use in well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet.  
Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.  
Ensure that all local regulations regarding handling and storage facilities are followed.

#### 7.1 Precautions for safe handling

Advice on safe handling : Avoid inhaling vapour and/or mists.  
Avoid contact with skin, eyes and clothing.  
Extinguish any naked flames. Do not smoke. Remove ignition sources. Avoid sparks.  
Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols.  
Bulk storage tanks should be diked (bunded).  
When using do not eat or drink.

The vapour is heavier than air, spreads along the ground and distant ignition is possible.

Product Transfer : Even with proper grounding and bonding, this material can still accumulate an electrostatic charge. If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur. Be aware of handling operations that may give rise to additional hazards that result from the accumulation of static charges. These include but are not limited to pumping (especially turbulent flow), mixing, filtering, splash filling, cleaning and filling of tanks and containers, sampling, switch loading, gauging, vacuum truck operations, and mechanical movements. These activities may lead to static discharge e.g. spark formation. Restrict line velocity during pumping in order to avoid generation of electrostatic discharge ( $\leq 1$  m/s until fill pipe submerged to twice its diameter, then  $\leq 7$  m/s). Avoid splash filling. Do NOT use compressed air for filling, discharging, or handling operations.

Refer to guidance under Handling section.

#### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Refer to section 15 for any additional specific legislation covering the packaging and storage of this product.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

Other data : Storage Temperature: Ambient.

Bulk storage tanks should be diked (bunded). Locate tanks away from heat and other sources of ignition. Cleaning, inspection and maintenance of storage tanks is a specialist operation, which requires the implementation of strict procedures and precautions. Must be stored in a diked (bunded) well-ventilated area, away from sunlight, ignition sources and other sources of heat. Keep away from aerosols, flammables, oxidizing agents, corrosives and from other flammable products which are not harmful or toxic to man or to the environment. Electrostatic charges will be generated during pumping. Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment to reduce the risk. The vapours in the head space of the storage vessel may lie in the flammable/explosive range and hence may be flammable.

Packaging material : Suitable material: For containers, or container linings use mild steel, stainless steel., For container paints, use epoxy paint, zinc silicate paint.  
Unsuitable material: Avoid prolonged contact with natural, butyl or nitrile rubbers.

Container Advice : Do not cut, drill, grind, weld or perform similar operations on or near containers.

### 7.3 Specific end use(s)

Specific use(s) : Please refer to Ch16 and/or the annexes for the registered uses under REACH.

See additional references that provide safe handling practices for liquids that are determined to be static accumulators: American Petroleum Institute 2003 (Protection Against Ignitions Arising out of Static, Lightning and Stray Currents) or National Fire Protection Agency 77 (Recommended Practices on Static Electricity).  
IEC/TS 60079-32-1: Electrostatic hazards, guidance

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
------------	---------	-------------------------------	--------------------	-------

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

Aliphatic dearom. solvents 200 - 250		TWA	1.050 mg/m3	EU HSPA
---	--	-----	-------------	---------

### Biological occupational exposure limits

No biological limit allocated.

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Alkanes, C15-19-branched and linear : No DNEL value has been established.

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Alkanes, C15-19-branched and linear : Substance is a hydrocarbon with a complex, unknown or variable composition. Conventional methods of deriving PNECs are not appropriate and it is not possible to identify a single representative PNEC for such substances.

### Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods  
<http://www.cdc.gov/niosh/>

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods  
<http://www.osha.gov/>

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances  
<http://www.hse.gov.uk/>

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA) , Germany  
<http://www.dguv.de/inhalt/index.jsp>

L'Institut National de Recherche et de Sécurité, (INRS), France <http://www.inrs.fr/accueil>

## 8.2 Exposure controls

**Engineering measures** Read in conjunction with the Exposure Scenario for your specific use contained in the Annex.

Use sealed systems as far as possible.

Adequate explosion-proof ventilation to control airborne concentrations below the exposure guidelines/limits.

Local exhaust ventilation is recommended.

Firewater monitors and deluge systems are recommended.

Eye washes and showers for emergency use.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

General Information:

Always observe good personal hygiene measures, such as washing hands after handling the material



# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned.

Practice good housekeeping.

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

### Personal protective equipment

Read in conjunction with the Exposure Scenario for your specific use contained in the Annex.

The provided information is made in consideration of the PPE directive (Council Directive 89/686/EEC) and the CEN European Committee for Standardisation (CEN) standards.

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Eye protection : If material is handled such that it could be splashed into eyes, protective eyewear is recommended.  
Approved to EU Standard EN166.

Hand protection

Remarks : Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. Longer term protection: Nitrile rubber gloves. Incidental contact/Splash protection: PVC, neoprene or nitrile rubber gloves For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

Skin and body protection : Skin protection is not required under normal conditions of use.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

For prolonged or repeated exposures use impervious clothing over parts of the body subject to exposure.  
If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to relevant Standard, and provide employee skin care programmes.

Protective clothing approved to EU Standard EN14605.

Wear antistatic and flame-retardant clothing, if a local risk assessment deems it so.

Respiratory protection : If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are unsuitable (e.g. airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. If air-filtering respirators are suitable for conditions of use: Select a filter suitable for organic gases and vapours [Type A boiling point > 65°C (149°F)] meeting EN14387.

Hygiene measures : Wash hands before eating, drinking, smoking and using the toilet. Launder contaminated clothing before re-use. Do not ingest. If swallowed, then seek immediate medical assistance.

### Environmental exposure controls

General advice : Read in conjunction with the Exposure Scenario for your specific use contained in the Annex. Take appropriate measures to fulfil the requirements of relevant environmental protection legislation. Avoid contamination of the environment by following advice given in Section 6. If necessary, prevent undissolved material from being discharged to waste water. Waste water should be treated in a municipal or industrial waste water treatment plant before discharge to surface water. Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour. Minimise release to the environment. An environmental assessment must be made to ensure compliance with local environmental legislation. Information on accidental release measures are to be found in section 6.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

Appearance	: liquid
Colour	: colourless
Odour	: Hydrocarbon
Odour Threshold	: Data not available
pH	: Data not available
Melting / freezing point	: Data not available
Boiling point/boiling range	: 260 - 320 °C
Flash point	: 128,5 °C
Flammability (solid, gas)	: Data not available
Upper explosion limit	: 7 %(V)
Lower explosion limit	: 0,5 %(V)
Vapour pressure	: Data not available
Relative vapour density	: Data not available
Relative density	: < 0,8
Density	: < 800 kg/m <sup>3</sup> (15 °C)
Solubility(ies)	
Water solubility	: insoluble
Partition coefficient: n-octanol/water	: log Pow: > 7
Auto-ignition temperature	: > 200 °C
Decomposition temperature	: Data not available
Viscosity	
Viscosity, dynamic	: Data not available
Viscosity, kinematic	: 3,3 mm <sup>2</sup> /s (40 °C)
Explosive properties	: Not classified
Oxidizing properties	: Not applicable

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

### 9.2 Other information

Surface tension	: Data not available
Conductivity	: Low conductivity: < 100 pS/m, The conductivity of this material makes it a static accumulator., A liquid is typically considered nonconductive if its conductivity is below 100 pS/m and is considered semi-conductive if its conductivity is below 10,000 pS/m., Whether a liquid is nonconductive or semi-conductive, the precautions are the same., A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid
Molecular weight	: Data not available

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.

### 10.2 Chemical stability

No hazardous reaction is expected when handled and stored according to provisions, Stable under normal conditions of use.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Reacts with strong oxidising agents.

### 10.4 Conditions to avoid

Conditions to avoid : Avoid heat, sparks, open flames and other ignition sources.  
  
In certain circumstances product can ignite due to static electricity.

### 10.5 Incompatible materials

Materials to avoid : Strong oxidising agents.

### 10.6 Hazardous decomposition products

Hazardous decomposition products : Hazardous decomposition products are not expected to form during normal storage.  
Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids and gases including carbon monoxide, carbon dioxide, sulphur oxides and unidentified organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

### SECTION 11: Toxicological information

#### 11.1 Information on toxicological effects

Basis for assessment : Information given is based on product testing, and/or similar products, and/or components.

Information on likely routes of exposure : Exposure may occur via inhalation, ingestion, skin absorption, skin or eye contact, and accidental ingestion.

#### Acute toxicity

##### Product:

Acute oral toxicity : LD50 Rat: > 5000 mg/kg  
Remarks: Low toxicity:  
Based on available data, the classification criteria are not met.

Acute inhalation toxicity : Remarks: LC50 greater than near-saturated vapour concentration.  
Low toxicity:  
Based on available data, the classification criteria are not met.

Acute dermal toxicity : LD50 Rabbit: > 2000 mg/kg  
Remarks: Low toxicity:  
Based on available data, the classification criteria are not met.

#### Skin corrosion/irritation

##### Product:

Remarks: Prolonged/repeated contact may cause defatting of the skin which can lead to dermatitis., Not irritating to skin.

#### Serious eye damage/eye irritation

##### Product:

Remarks: Not irritating to eye.

#### Respiratory or skin sensitisation

##### Product:

Remarks: Not a sensitiser., Based on available data, the classification criteria are not met.

#### Germ cell mutagenicity

##### Product:

: Remarks: Non mutagenic

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

### Carcinogenicity

#### Product:

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

Material	GHS/CLP Carcinogenicity Classification
Alkanes, C15-19-branched and linear	No carcinogenicity classification.

### Reproductive toxicity

#### Product:

:

Remarks: Not a developmental toxicant., Based on available data, the classification criteria are not met., Does not impair fertility.

### STOT - single exposure

#### Product:

Remarks: Based on available data, the classification criteria are not met.

### STOT - repeated exposure

#### Product:

Remarks: Based on available data, the classification criteria are not met.

### Aspiration toxicity

#### Product:

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

### Further information

#### Product:

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

#### **Summary on evaluation of the CMR properties**

Germ cell mutagenicity-  
Assessment : This product does not meet the criteria for classification in categories 1A/1B.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

Carcinogenicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

Reproductive toxicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

## SECTION 12: Ecological information

### 12.1 Toxicity

Basis for assessment : Incomplete ecotoxicological data are available for this product. The information given below is based partly on a knowledge of the components and the ecotoxicology of similar products.

#### **Product:**

Toxicity to fish (Acute toxicity) : LL50 : > 100 mg/l  
Remarks: Practically non toxic:  
Based on available data, the classification criteria are not met.

Toxicity to crustacean (Acute toxicity) : EL50 : > 100 mg/l  
Remarks: Practically non toxic:  
Based on available data, the classification criteria are not met.

Toxicity to algae/aquatic plants (Acute toxicity) : EL50 : > 100 mg/l  
Remarks: Practically non toxic:  
Based on available data, the classification criteria are not met.

Toxicity to fish (Chronic toxicity) : Remarks: Data not available

Toxicity to crustacean (Chronic toxicity) : Remarks: Data not available

Toxicity to microorganisms (Acute toxicity) : IC50 : > 100 mg/l  
Remarks: Practically non toxic:  
Based on available data, the classification criteria are not met.

### 12.2 Persistence and degradability

#### **Product:**

Biodegradability : Remarks: Oxidises rapidly by photo-chemical reactions in air., Readily biodegradable.

### 12.3 Bioaccumulative potential

#### **Product:**

Bioaccumulation : Remarks: Has the potential to bioaccumulate.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

Partition coefficient: n-octanol/water : log Pow: > 7

### 12.4 Mobility in soil

#### Product:

Mobility : Remarks: Floats on water., If it enters soil, it will adsorb to soil particles and will not be mobile.

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB.

### 12.6 Other adverse effects

#### Product:

Additional ecological information : Physical properties indicate that hydrocarbon gases will rapidly volatilise from the aquatic environment and that acute and chronic effects would not be observed in practice., Does not have ozone depletion potential.

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : Recover or recycle if possible.  
It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.  
Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment.  
Do not dispose into the environment, in drains or in water courses  
Do not dispose of tank water bottoms by allowing them to drain into the ground. This will result in soil and groundwater contamination.  
Waste arising from a spillage or tank cleaning should be disposed of in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand.

Waste, spills or used product is dangerous waste.

Disposal should be in accordance with applicable regional, national, and local laws and regulations.  
Local regulations may be more stringent than regional or national requirements and must be complied with.



# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

MARPOL - see International Convention for the Prevention of Pollution from Ships (MARPOL 73/78) which provides technical aspects at controlling pollutions from ships.

Contaminated packaging : Drain container thoroughly.  
After draining, vent in a safe place away from sparks and fire.  
Residues may cause an explosion hazard. Do not puncture, cut or weld uncleaned drums.  
Send to drum recoverer or metal reclaimer.  
Comply with any local recovery or waste disposal regulations.

### SECTION 14: Transport information

#### 14.1 UN number

ADR : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good  
IATA : Not regulated as a dangerous good

#### 14.2 Proper shipping name

ADR : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good  
IATA : Not regulated as a dangerous good

#### 14.3 Transport hazard class

ADR : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good  
IATA : Not regulated as a dangerous good

#### 14.4 Packing group

ADR : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good  
IATA : Not regulated as a dangerous good

#### 14.5 Environmental hazards

ADR : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good

#### 14.6 Special precautions for user

Remarks : Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

#### 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied. MARPOL Annex 1 rules apply for bulk shipments by sea.

**Additional Information** : This product may be transported under nitrogen blanketing. Nitrogen is an odourless and invisible gas. Exposure to nitrogen enriched atmospheres displaces available oxygen which may cause asphyxiation or death. Personnel must observe strict safety precautions when involved with a

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

confined space entry.

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - List of substances subject to authorisation (Annex XIV) : Product is not subject to Authorisation under REACH.

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).

Other regulations : The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), annex XIV.

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), annex XVII.

Directive 2004/37/EC on the protection of workers from the risks related to exposure to carcinogens or mutagens at work and its amendments.

Directive 1994/33/EC on the protection of young people at work and its amendments.

Council Directive 92/85/EEC on the introduction of measures to encourage improvements in the safety and health at work of pregnant workers and workers who have recently given birth or are breastfeeding and its amendments.

#### The components of this product are reported in the following inventories:

DSL	: Listed
ENCS	: Listed
KECI	: Listed
TSCA	: Listed
PICCS	: Notified with Restrictions.
IECSC	: Notified with Restrictions.

#### 15.2 Chemical safety assessment

A Chemical Safety Assessment has been carried out for this substance.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

### SECTION 16: Other information

#### Full text of other abbreviations

Asp. Tox.                      Aspiration hazard

Abbreviations and Acronyms : The standard abbreviations and acronyms used in this document can be looked up in reference literature (e.g. scientific dictionaries) and/or websites.

ACGIH = American Conference of Governmental Industrial Hygienists

ADR = European Agreement concerning the International Carriage of Dangerous Goods by Road

AICS = Australian Inventory of Chemical Substances

ASTM = American Society for Testing and Materials

BEL = Biological exposure limits

BTEX = Benzene, Toluene, Ethylbenzene, Xylenes

CAS = Chemical Abstracts Service

CEFIC = European Chemical Industry Council

CLP = Classification Packaging and Labelling

COC = Cleveland Open-Cup

DIN = Deutsches Institut für Normung

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

DSL = Canada Domestic Substance List

EC = European Commission

EC50 = Effective Concentration fifty

ECETOC = European Center on Ecotoxicology and Toxicology Of Chemicals

ECHA = European Chemicals Agency

EINECS = The European Inventory of Existing Commercial Chemical Substances

EL50 = Effective Loading fifty

ENCS = Japanese Existing and New Chemical Substances Inventory

EWC = European Waste Code

GHS = Globally Harmonised System of Classification and Labelling of Chemicals

IARC = International Agency for Research on Cancer

IATA = International Air Transport Association

IC50 = Inhibitory Concentration fifty

IL50 = Inhibitory Level fifty

IMDG = International Maritime Dangerous Goods

INV = Chinese Chemicals Inventory

IP346 = Institute of Petroleum test method N° 346 for the determination of polycyclic aromatics DMSO-extractables

KECI = Korea Existing Chemicals Inventory

LC50 = Lethal Concentration fifty

LD50 = Lethal Dose fifty per cent.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

LL/EL/IL = Lethal Loading/Effective Loading/Inhibitory loading  
LL50 = Lethal Loading fifty  
MARPOL = International Convention for the Prevention of Pollution From Ships  
NOEC/NOEL = No Observed Effect Concentration / No Observed Effect Level  
OE\_HPVS = Occupational Exposure - High Production Volume  
PBT = Persistent, Bioaccumulative and Toxic  
PICCS = Philippine Inventory of Chemicals and Chemical Substances  
PNEC = Predicted No Effect Concentration  
REACH = Registration Evaluation And Authorisation Of Chemicals  
RID = Regulations Relating to International Carriage of Dangerous Goods by Rail  
SKIN\_DES = Skin Designation  
STEL = Short term exposure limit  
TRA = Targeted Risk Assessment  
TSCA = US Toxic Substances Control Act  
TWA = Time-Weighted Average  
vPvB = very Persistent and very Bioaccumulative

### Further information

Training advice : Provide adequate information, instruction and training for operators.

Other information : For Industry guidance and tools on REACH please visit the CEFIC website at <http://cefic.org/Industry-support>.  
The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB.

A vertical bar (|) in the left margin indicates an amendment from the previous version.

Sources of key data used to compile the Safety Data Sheet : The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID data base, EC 1272 regulation, etc).

### Identified Uses according to the Use Descriptor System

#### Uses - Worker

Title : Manufacture of substance- Industrial

#### Uses - Worker

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

Title	:	Use as an intermediate- Industrial
<b>Uses - Worker</b>		
Title	:	Distribution of substance- Industrial
<b>Uses - Worker</b>		
Title	:	Formulation & (re)packing of substances and mixtures- Industrial
<b>Uses - Worker</b>		
Title	:	Uses in Coatings- Industrial
<b>Uses - Worker</b>		
Title	:	Uses in Coatings- Professional
<b>Uses - Worker</b>		
Title	:	Use in Cleaning Agents- Industrial
<b>Uses - Worker</b>		
Title	:	Use in Cleaning Agents- Professional
<b>Uses - Worker</b>		
Title	:	Use in Oil and Gas field drilling and production operations- Industrial
<b>Uses - Worker</b>		
Title	:	Use in Oil and Gas field drilling and production operations- Professional
<b>Uses - Worker</b>		
Title	:	Lubricants- Industrial
<b>Uses - Worker</b>		
Title	:	Lubricants- ProfessionalLow Environmental ReleaseHigh Environmental Release
<b>Uses - Worker</b>		
Title	:	Metal working fluids / rolling oils- Industrial
<b>Uses - Worker</b>		
Title	:	Metal working fluids / rolling oils- ProfessionalHigh Environmental Release
<b>Uses - Worker</b>		
Title	:	Use as binders and release agents- Industrial
<b>Uses - Worker</b>		
Title	:	Use as binders and release agents- Professional
<b>Uses - Worker</b>		
Title	:	Use in Agrochemicals uses- Professional
<b>Uses - Worker</b>		

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

Title : Use as a fuel- Industrial

### Uses - Worker

Title : Use as a fuel- Professional

### Uses - Worker

Title : Functional Fluids- Industrial

### Uses - Worker

Title : Functional Fluids- Professional

### Uses - Worker

Title : Road and construction applications- Professional

### Uses - Worker

Title : Use in laboratories- Industrial

### Uses - Worker

Title : Use in laboratories- Professional

### Uses - Worker

Title : Use in explosives- Professional

### Uses - Worker

Title : Rubber production and processing- Industrial

### Uses - Worker

Title : Polymer processing- Industrial

### Uses - Worker

Title : Polymer processing- Professional

### Uses - Worker

Title : Water treatment chemicals- Industrial

### Uses - Worker

Title : Water treatment chemicals- Professional

### Uses - Worker

Title : Mining chemicals- Industrial

### Identified Uses according to the Use Descriptor System

#### Uses - Consumer

Title : Uses in Coatings  
- Consumer

#### Uses - Consumer

Title : Use in Cleaning Agents  
- Consumer

#### Uses - Consumer

Title : Lubricants

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

- Consumer  
Low Environmental Release  
High Environmental Release

### Uses - Consumer

Title : Use as a fuel  
- Consumer

### Uses - Consumer

Title : Functional Fluids  
- Consumer

### Uses - Consumer

Title : Other Consumer Uses  
- Consumer

### Uses - Consumer

Title : Water treatment chemicals  
- Consumer

### Uses - Consumer

Title : Use in Agrochemicals uses  
- Consumer

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

### Exposure Scenario - Worker

<b>300000010600</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Manufacture of substance- Industrial
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU3, SU8, SU9 <b>Process Categories:</b> PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC15 <b>Environmental Release Categories:</b> ERC1, ERC4, ESVOC SpERC 1.1.v1
<b>Scope of process</b>	Manufacture of the substance or use as a process chemical or extraction agent. Includes recycling/ recovery, material transfers, storage, maintenance and loading (including marine vessel/barge, road/rail car and bulk container), sampling and associated laboratory activities.

<b>SECTION 2</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
------------------	--

<b>Section 2.1</b>	<b>Control of Worker Exposure</b>
<b>Product Characteristics</b>	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100%., Unless stated otherwise.,
<b>Frequency and Duration of Use</b>	
Covers daily exposures up to 8 hours (unless stated differently).	
<b>Other Operational Conditions affecting Exposure</b>	
Operation is carried out at elevated temperature (> 20°C above ambient temperature). Assumes a good basic standard of occupational hygiene is implemented.	

<b>Contributing Scenarios</b>	<b>Risk Management Measures</b>
General measures (Aspiration)	The H304 hazard statement (May be fatal if swallowed and enters airways) relates to potential for aspiration, a non-quantifiable hazard determined by physico-chemical properties (i.e. viscosity) that can occur during ingestion and also if it is vomited following ingestion. A DNEL cannot be derived. Risks from the physicochemical hazards of substances can be controlled by implementing risk management measures. For substances classified as H304, the following measures need to be implemented to control the aspiration hazard. Do not ingest. If swallowed, then seek immediate medical assistance

<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Not applicable.	



# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
Not applicable. Risk Management Measures are based on qualitative risk characterisation.	
<b>Section 3.2 -Environment</b>	
Not applicable.	
<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
<b>Section 4.1 - Health</b>	
Not applicable.	
<b>Section 4.2 -Environment</b>	
Not applicable.	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

### Exposure Scenario - Worker

<b>300000010634</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Use as an intermediate- Industrial
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU3, SU8, SU9 <b>Process Categories:</b> PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC15 <b>Environmental Release Categories:</b> ERC6a, ESVOC SpERC 6.1a.v1
<b>Scope of process</b>	Use of substance as an intermediate (not related to Strictly Controlled Conditions). Includes recycling/ recovery, material transfers, storage, sampling, associated laboratory activities, maintenance and loading (including marine vessel/barge, road/rail car and bulk container).

<b>SECTION 2</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
------------------	--

<b>Section 2.1</b>	<b>Control of Worker Exposure</b>
<b>Product Characteristics</b>	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100%., Unless stated otherwise.,
<b>Frequency and Duration of Use</b>	
Covers daily exposures up to 8 hours (unless stated differently).	
<b>Other Operational Conditions affecting Exposure</b>	
Operation is carried out at elevated temperature (> 20°C above ambient temperature). Assumes a good basic standard of occupational hygiene is implemented.	

<b>Contributing Scenarios</b>	<b>Risk Management Measures</b>
General measures (Aspiration)	The H304 hazard statement (May be fatal if swallowed and enters airways) relates to potential for aspiration, a non-quantifiable hazard determined by physico-chemical properties (i.e. viscosity) that can occur during ingestion and also if it is vomited following ingestion. A DNEL cannot be derived. Risks from the physicochemical hazards of substances can be controlled by implementing risk management measures. For substances classified as H304, the following measures need to be implemented to control the aspiration hazard. Do not ingest. If swallowed, then seek immediate medical assistance

<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Not applicable.	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
Not applicable. Risk Management Measures are based on qualitative risk characterisation.	
<b>Section 3.2 -Environment</b>	
Not applicable.	
<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
<b>Section 4.1 - Health</b>	
Not applicable.	
<b>Section 4.2 -Environment</b>	
Not applicable.	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

### Exposure Scenario - Worker

<b>300000010601</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Distribution of substance- Industrial
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU3, SU8, SU9 <b>Process Categories:</b> PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC9, PROC15 <b>Environmental Release Categories:</b> ERC1, ERC2, ERC3, ERC4, ERC5, ERC6a, ERC6b, ERC6c, ERC6d, ERC7, ESVOC SpERC 1.1b.v1
<b>Scope of process</b>	Loading (including marine vessel/barge, rail/road car and IBC loading) and repacking (including drums and small packs) of substance, including its sampling, storage, unloading distribution and associated laboratory activities.

<b>SECTION 2</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
------------------	--

<b>Section 2.1</b>	<b>Control of Worker Exposure</b>
<b>Product Characteristics</b>	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100%., Unless stated otherwise.,
<b>Frequency and Duration of Use</b>	
Covers daily exposures up to 8 hours (unless stated differently).	
<b>Other Operational Conditions affecting Exposure</b>	
Operation is carried out at elevated temperature (> 20°C above ambient temperature). Assumes a good basic standard of occupational hygiene is implemented.	

<b>Contributing Scenarios</b>	<b>Risk Management Measures</b>
General measures (Aspiration)	The H304 hazard statement (May be fatal if swallowed and enters airways) relates to potential for aspiration, a non-quantifiable hazard determined by physico-chemical properties (i.e. viscosity) that can occur during ingestion and also if it is vomited following ingestion. A DNEL cannot be derived. Risks from the physicochemical hazards of substances can be controlled by implementing risk management measures. For substances classified as H304, the following measures need to be implemented to control the aspiration hazard. Do not ingest. If swallowed, then seek immediate medical assistance

<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Not applicable.	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
Not applicable. Risk Management Measures are based on qualitative risk characterisation.	
<b>Section 3.2 -Environment</b>	
Not applicable.	
<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
<b>Section 4.1 - Health</b>	
Not applicable.	
<b>Section 4.2 -Environment</b>	
Not applicable.	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

### Exposure Scenario - Worker

<b>300000010602</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Formulation & (re)packing of substances and mixtures-Industrial
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU3, SU10 <b>Process Categories:</b> PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9, PROC14, PROC15 <b>Environmental Release Categories:</b> ERC2, ESVOC SpERC 2.2.v1
<b>Scope of process</b>	Formulation, packing and re-packing of the substance and its mixtures in batch or continuous operations, including storage, materials transfers, mixing, tableting, compression, pelletisation, extrusion, large and small scale packing, sampling, maintenance and associated laboratory activities.

<b>SECTION 2</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
------------------	--

<b>Section 2.1</b>	<b>Control of Worker Exposure</b>
<b>Product Characteristics</b>	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100%., Unless stated otherwise.,
<b>Frequency and Duration of Use</b>	
Covers daily exposures up to 8 hours (unless stated differently).	
<b>Other Operational Conditions affecting Exposure</b>	
Operation is carried out at elevated temperature (> 20°C above ambient temperature). Assumes a good basic standard of occupational hygiene is implemented.	

<b>Contributing Scenarios</b>	<b>Risk Management Measures</b>
General measures (Aspiration)	The H304 hazard statement (May be fatal if swallowed and enters airways) relates to potential for aspiration, a non-quantifiable hazard determined by physico-chemical properties (i.e. viscosity) that can occur during ingestion and also if it is vomited following ingestion. A DNEL cannot be derived. Risks from the physicochemical hazards of substances can be controlled by implementing risk management measures. For substances classified as H304, the following measures need to be implemented to control the aspiration hazard. Do not ingest. If swallowed, then seek immediate medical assistance

<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
--------------------	--

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

Not applicable.	
-----------------	--

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
------------------	----------------------------

<b>Section 3.1 - Health</b>
-----------------------------

Not applicable.

Risk Management Measures are based on qualitative risk characterisation.

<b>Section 3.2 -Environment</b>
---------------------------------

Not applicable.

<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
------------------	--

<b>Section 4.1 - Health</b>
-----------------------------

Not applicable.

<b>Section 4.2 -Environment</b>
---------------------------------

Not applicable.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

### Exposure Scenario - Worker

<b>300000010603</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Uses in Coatings- Industrial
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU3 <b>Process Categories:</b> PROC1, PROC2, PROC3, PROC4, PROC5, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC14, PROC15 <b>Environmental Release Categories:</b> ERC4, ESVOC SpERC 4.3a.v1
<b>Scope of process</b>	Covers the use in coatings (paints, inks, adhesives, etc) including exposures during use (including materials receipt, storage, preparation and transfer from bulk and semi-bulk, application by spray, roller, spreader, dip, flow, fluidised bed on production lines and film formation) and equipment cleaning, maintenance and associated laboratory activities.

<b>SECTION 2</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
------------------	--

<b>Section 2.1</b>	<b>Control of Worker Exposure</b>
<b>Product Characteristics</b>	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100%., Unless stated otherwise.,
<b>Frequency and Duration of Use</b>	
Covers daily exposures up to 8 hours (unless stated differently).	
<b>Other Operational Conditions affecting Exposure</b>	
Operation is carried out at elevated temperature (> 20°C above ambient temperature). Assumes a good basic standard of occupational hygiene is implemented.	

<b>Contributing Scenarios</b>	<b>Risk Management Measures</b>
General measures (Aspiration)	The H304 hazard statement (May be fatal if swallowed and enters airways) relates to potential for aspiration, a non-quantifiable hazard determined by physico-chemical properties (i.e. viscosity) that can occur during ingestion and also if it is vomited following ingestion. A DNEL cannot be derived. Risks from the physicochemical hazards of substances can be controlled by implementing risk management measures. For substances classified as H304, the following measures need to be implemented to control the aspiration hazard. Do not ingest. If swallowed, then seek immediate medical assistance



# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Not applicable.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
Not applicable. Risk Management Measures are based on qualitative risk characterisation.	

<b>Section 3.2 -Environment</b>
Not applicable.

<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
<b>Section 4.1 - Health</b>	
Not applicable.	

<b>Section 4.2 -Environment</b>
Not applicable.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

### Exposure Scenario - Worker

<b>300000010604</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Uses in Coatings- Professional
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU22 <b>Process Categories:</b> PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC10, PROC11, PROC13, PROC15, PROC19 <b>Environmental Release Categories:</b> ERC8a, ERC8d, ESVOC SpERC 8.3b.v1
<b>Scope of process</b>	Covers the use in coatings (paints, inks, adhesives, etc) including exposures during use (including materials receipt, storage, preparation and transfer from bulk and semi-bulk, application by spray, roller, brush, spreader by hand or similar methods, and film formation), and equipment cleaning, maintenance and associated laboratory activities.

<b>SECTION 2</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
------------------	--

<b>Section 2.1</b>	<b>Control of Worker Exposure</b>
<b>Product Characteristics</b>	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100%., Unless stated otherwise.,
<b>Frequency and Duration of Use</b>	
Covers daily exposures up to 8 hours (unless stated differently).	
<b>Other Operational Conditions affecting Exposure</b>	
Operation is carried out at elevated temperature (> 20°C above ambient temperature). Assumes a good basic standard of occupational hygiene is implemented.	

<b>Contributing Scenarios</b>	<b>Risk Management Measures</b>
General measures (Aspiration)	<p>The H304 hazard statement (May be fatal if swallowed and enters airways) relates to potential for aspiration, a non-quantifiable hazard determined by physico-chemical properties (i.e. viscosity) that can occur during ingestion and also if it is vomited following ingestion. A DNEL cannot be derived. Risks from the physicochemical hazards of substances can be controlled by implementing risk management measures. For substances classified as H304, the following measures need to be implemented to control the aspiration hazard.</p> <p>Do not ingest. If swallowed, then seek immediate medical assistance</p>

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Not applicable.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
Not applicable. Risk Management Measures are based on qualitative risk characterisation.	

<b>Section 3.2 -Environment</b>
Not applicable.

<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
<b>Section 4.1 - Health</b>	
Not applicable.	

<b>Section 4.2 -Environment</b>
Not applicable.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

### Exposure Scenario - Worker

<b>300000010605</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Use in Cleaning Agents- Industrial
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU3 <b>Process Categories:</b> PROC1, PROC2, PROC3, PROC4, PROC7, PROC8a, PROC8b, PROC10, PROC13 <b>Environmental Release Categories:</b> ERC4, ESVOC SpERC 4.4a.v1
<b>Scope of process</b>	Covers the use as a component of cleaning products including transfer from storage, pouring/unloading from drums or containers. Exposures during mixing/diluting in the preparatory phase and cleaning activities (including spraying, brushing, dipping, wiping, automated and by hand), related equipment cleaning and maintenance.

<b>SECTION 2</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
------------------	--

<b>Section 2.1</b>	<b>Control of Worker Exposure</b>
<b>Product Characteristics</b>	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100%., Unless stated otherwise.,
<b>Frequency and Duration of Use</b>	
Covers daily exposures up to 8 hours (unless stated differently).	
<b>Other Operational Conditions affecting Exposure</b>	
Operation is carried out at elevated temperature (> 20°C above ambient temperature). Assumes a good basic standard of occupational hygiene is implemented.	

<b>Contributing Scenarios</b>	<b>Risk Management Measures</b>
General measures (Aspiration)	The H304 hazard statement (May be fatal if swallowed and enters airways) relates to potential for aspiration, a non-quantifiable hazard determined by physico-chemical properties (i.e. viscosity) that can occur during ingestion and also if it is vomited following ingestion. A DNEL cannot be derived. Risks from the physicochemical hazards of substances can be controlled by implementing risk management measures. For substances classified as H304, the following measures need to be implemented to control the aspiration hazard. Do not ingest. If swallowed, then seek immediate medical assistance

<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
--------------------	--

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

Not applicable.

### SECTION 3

### EXPOSURE ESTIMATION

#### Section 3.1 - Health

Not applicable.

Risk Management Measures are based on qualitative risk characterisation.

#### Section 3.2 -Environment

Not applicable.

### SECTION 4

### GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO

#### Section 4.1 - Health

Not applicable.

#### Section 4.2 -Environment

Not applicable.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

### Exposure Scenario - Worker

<b>300000010606</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Use in Cleaning Agents- Professional
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU22 <b>Process Categories:</b> PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC10, PROC11, PROC13, PROC19 <b>Environmental Release Categories:</b> ERC8a, ERC8d, ESVOC SpERC 8.4b.v1
<b>Scope of process</b>	Covers the use as a component of cleaning products including pouring/unloading from drums or containers; and exposures during mixing/diluting in the preparatory phase and cleaning activities (including spraying, brushing, dipping, wiping automated and by hand).

<b>SECTION 2</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
------------------	--

<b>Section 2.1</b>	<b>Control of Worker Exposure</b>
<b>Product Characteristics</b>	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100%., Unless stated otherwise.,
<b>Frequency and Duration of Use</b>	
Covers daily exposures up to 8 hours (unless stated differently).	
<b>Other Operational Conditions affecting Exposure</b>	
Operation is carried out at elevated temperature (> 20°C above ambient temperature). Assumes a good basic standard of occupational hygiene is implemented.	

<b>Contributing Scenarios</b>	<b>Risk Management Measures</b>
General measures (Aspiration)	The H304 hazard statement (May be fatal if swallowed and enters airways) relates to potential for aspiration, a non-quantifiable hazard determined by physico-chemical properties (i.e. viscosity) that can occur during ingestion and also if it is vomited following ingestion. A DNEL cannot be derived. Risks from the physicochemical hazards of substances can be controlled by implementing risk management measures. For substances classified as H304, the following measures need to be implemented to control the aspiration hazard. Do not ingest. If swallowed, then seek immediate medical assistance

<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Not applicable.	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
Not applicable. Risk Management Measures are based on qualitative risk characterisation.	
<b>Section 3.2 -Environment</b>	
Not applicable.	
<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
<b>Section 4.1 - Health</b>	
Not applicable.	
<b>Section 4.2 -Environment</b>	
Not applicable.	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

### Exposure Scenario - Worker

<b>300000010632</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Use in Oil and Gas field drilling and production operations-Industrial
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU3 <b>Process Categories:</b> PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b <b>Environmental Release Categories:</b> ERC4, ESVOC SpERC 4.5a.v1
<b>Scope of process</b>	Oil field well drilling and production operations (including drilling muds and well cleaning) including material transfers, on-site formulation, well head operations, shaker room activities and related maintenance.

<b>SECTION 2</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
------------------	--

<b>Section 2.1</b>	<b>Control of Worker Exposure</b>
<b>Product Characteristics</b>	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100%., Unless stated otherwise.,
<b>Frequency and Duration of Use</b>	
Covers daily exposures up to 8 hours (unless stated differently).	
<b>Other Operational Conditions affecting Exposure</b>	
Operation is carried out at elevated temperature (> 20°C above ambient temperature). Assumes a good basic standard of occupational hygiene is implemented.	

<b>Contributing Scenarios</b>	<b>Risk Management Measures</b>
General measures (Aspiration)	The H304 hazard statement (May be fatal if swallowed and enters airways) relates to potential for aspiration, a non-quantifiable hazard determined by physico-chemical properties (i.e. viscosity) that can occur during ingestion and also if it is vomited following ingestion. A DNEL cannot be derived. Risks from the physicochemical hazards of substances can be controlled by implementing risk management measures. For substances classified as H304, the following measures need to be implemented to control the aspiration hazard. Do not ingest. If swallowed, then seek immediate medical assistance

<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Not applicable.	



# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
Not applicable. Risk Management Measures are based on qualitative risk characterisation.	
<b>Section 3.2 -Environment</b>	
Not applicable.	
<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
<b>Section 4.1 - Health</b>	
Not applicable.	
<b>Section 4.2 -Environment</b>	
Not applicable.	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

### Exposure Scenario - Worker

<b>300000010635</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Use in Oil and Gas field drilling and production operations-Professional
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU22 <b>Process Categories:</b> PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b <b>Environmental Release Categories:</b> ERC8d, ESVOC SpERC 8.5b.v1
<b>Scope of process</b>	Oil field well drilling operations (including drilling muds and well cleaning) including material transfers, on-site formulation, well head operations, shaker room activities and related maintenance.

<b>SECTION 2</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
------------------	--

<b>Section 2.1</b>	<b>Control of Worker Exposure</b>
<b>Product Characteristics</b>	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100%., Unless stated otherwise.,
<b>Frequency and Duration of Use</b>	
Covers daily exposures up to 8 hours (unless stated differently).	
<b>Other Operational Conditions affecting Exposure</b>	
Operation is carried out at elevated temperature (> 20°C above ambient temperature). Assumes a good basic standard of occupational hygiene is implemented.	

<b>Contributing Scenarios</b>	<b>Risk Management Measures</b>
General measures (Aspiration)	The H304 hazard statement (May be fatal if swallowed and enters airways) relates to potential for aspiration, a non-quantifiable hazard determined by physico-chemical properties (i.e. viscosity) that can occur during ingestion and also if it is vomited following ingestion. A DNEL cannot be derived. Risks from the physicochemical hazards of substances can be controlled by implementing risk management measures. For substances classified as H304, the following measures need to be implemented to control the aspiration hazard. Do not ingest. If swallowed, then seek immediate medical assistance

<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Not applicable.	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
Not applicable. Risk Management Measures are based on qualitative risk characterisation.	
<b>Section 3.2 -Environment</b>	
Not applicable.	
<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
<b>Section 4.1 - Health</b>	
Not applicable.	
<b>Section 4.2 -Environment</b>	
Not applicable.	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

### Exposure Scenario - Worker

<b>300000010609</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Lubricants- Industrial
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU3 <b>Process Categories:</b> PROC1, PROC2, PROC3, PROC4, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC17, PROC18 <b>Environmental Release Categories:</b> ERC4, ERC7, ESVOC SpERC 4.6a.v1
<b>Scope of process</b>	Covers the use of formulated lubricants in closed and open systems including transfer operations, operation of machinery/engines and similar articles, reworking on reject articles, equipment maintenance and disposal of wastes.

<b>SECTION 2</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
------------------	--

<b>Section 2.1</b>	<b>Control of Worker Exposure</b>
<b>Product Characteristics</b>	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100%., Unless stated otherwise.,
<b>Frequency and Duration of Use</b>	
Covers daily exposures up to 8 hours (unless stated differently).	
<b>Other Operational Conditions affecting Exposure</b>	
Operation is carried out at elevated temperature (> 20°C above ambient temperature). Assumes a good basic standard of occupational hygiene is implemented.	

<b>Contributing Scenarios</b>	<b>Risk Management Measures</b>
General measures (Aspiration)	The H304 hazard statement (May be fatal if swallowed and enters airways) relates to potential for aspiration, a non-quantifiable hazard determined by physico-chemical properties (i.e. viscosity) that can occur during ingestion and also if it is vomited following ingestion. A DNEL cannot be derived. Risks from the physicochemical hazards of substances can be controlled by implementing risk management measures. For substances classified as H304, the following measures need to be implemented to control the aspiration hazard. Do not ingest. If swallowed, then seek immediate medical assistance

<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Not applicable.	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
Not applicable. Risk Management Measures are based on qualitative risk characterisation.	
<b>Section 3.2 -Environment</b>	
Not applicable.	
<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
<b>Section 4.1 - Health</b>	
Not applicable.	
<b>Section 4.2 -Environment</b>	
Not applicable.	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

### Exposure Scenario - Worker

<b>300000010610</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Lubricants- ProfessionalLow Environmental ReleaseHigh Environmental Release
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU22 <b>Process Categories:</b> PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC9, PROC10, PROC11, PROC13, PROC17, PROC18, PROC20 <b>Environmental Release Categories:</b> ERC8a, ERC8d, ERC9a, ERC9b, ESVOC SpERC 8.6c.v1, ESVOC SpERC 9.6b.v1
<b>Scope of process</b>	Covers the use of formulated lubricants in closed and open systems including transfer operations, operation of engines and similar articles, reworking on reject articles, equipment maintenance and disposal of waste oil.

<b>SECTION 2</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
------------------	--

<b>Section 2.1</b>	<b>Control of Worker Exposure</b>
<b>Product Characteristics</b>	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100%., Unless stated otherwise.,
<b>Frequency and Duration of Use</b>	
Covers daily exposures up to 8 hours (unless stated differently).	
<b>Other Operational Conditions affecting Exposure</b>	
Operation is carried out at elevated temperature (> 20°C above ambient temperature). Assumes a good basic standard of occupational hygiene is implemented.	

<b>Contributing Scenarios</b>	<b>Risk Management Measures</b>
General measures (Aspiration)	The H304 hazard statement (May be fatal if swallowed and enters airways) relates to potential for aspiration, a non-quantifiable hazard determined by physico-chemical properties (i.e. viscosity) that can occur during ingestion and also if it is vomited following ingestion. A DNEL cannot be derived. Risks from the physicochemical hazards of substances can be controlled by implementing risk management measures. For substances classified as H304, the following measures need to be implemented to control the aspiration hazard. Do not ingest. If swallowed, then seek immediate medical assistance

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Not applicable.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
Not applicable. Risk Management Measures are based on qualitative risk characterisation.	

<b>Section 3.2 -Environment</b>	
Not applicable.	

<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
<b>Section 4.1 - Health</b>	
Not applicable.	

<b>Section 4.2 -Environment</b>	
Not applicable.	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

### Exposure Scenario - Worker

<b>300000010612</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Metal working fluids / rolling oils- Industrial
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU3 <b>Process Categories:</b> PROC1, PROC2, PROC3, PROC4, PROC5, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC17 <b>Environmental Release Categories:</b> ERC4, ESVOC SpERC 4.7a.v1
<b>Scope of process</b>	Covers the use in formulated MWFs/rolling oils including transfer operations, rolling and annealing activities, cutting/machining activities, automated and manual application of corrosion protections (including brushing, dipping and spraying), equipment maintenance, draining and disposal of waste oils.

<b>SECTION 2</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
------------------	--

<b>Section 2.1</b>	<b>Control of Worker Exposure</b>
<b>Product Characteristics</b>	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100%., Unless stated otherwise.,
<b>Frequency and Duration of Use</b>	
Covers daily exposures up to 8 hours (unless stated differently).	
<b>Other Operational Conditions affecting Exposure</b>	
Operation is carried out at elevated temperature (> 20°C above ambient temperature). Assumes a good basic standard of occupational hygiene is implemented.	

<b>Contributing Scenarios</b>	<b>Risk Management Measures</b>
General measures (Aspiration)	The H304 hazard statement (May be fatal if swallowed and enters airways) relates to potential for aspiration, a non-quantifiable hazard determined by physico-chemical properties (i.e. viscosity) that can occur during ingestion and also if it is vomited following ingestion. A DNEL cannot be derived. Risks from the physicochemical hazards of substances can be controlled by implementing risk management measures. For substances classified as H304, the following measures need to be implemented to control the aspiration hazard. Do not ingest. If swallowed, then seek immediate medical assistance



# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Not applicable.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
Not applicable. Risk Management Measures are based on qualitative risk characterisation.	

<b>Section 3.2 -Environment</b>	
Not applicable.	

<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
<b>Section 4.1 - Health</b>	
Not applicable.	

<b>Section 4.2 -Environment</b>	
Not applicable.	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

### Exposure Scenario - Worker

<b>300000010613</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Metal working fluids / rolling oils- ProfessionalHigh Environmental Release
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU22 <b>Process Categories:</b> PROC1, PROC2, PROC3, PROC5, PROC8a, PROC8b, PROC9, PROC10, PROC11, PROC13, PROC17 <b>Environmental Release Categories:</b> ERC8a, ERC8d, ESVOC SpERC 8.7c.v1
<b>Scope of process</b>	Covers the use in formulated MWFs including transfer operations, open and contained cutting/machining activities, automated and manual application of corrosion protections, draining and working on contaminated/ reject articles, and disposal of waste oils.

<b>SECTION 2</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
------------------	--

<b>Section 2.1</b>	<b>Control of Worker Exposure</b>
<b>Product Characteristics</b>	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100%., Unless stated otherwise.,
<b>Frequency and Duration of Use</b>	
Covers daily exposures up to 8 hours (unless stated differently).	
<b>Other Operational Conditions affecting Exposure</b>	
Operation is carried out at elevated temperature (> 20°C above ambient temperature). Assumes a good basic standard of occupational hygiene is implemented.	

<b>Contributing Scenarios</b>	<b>Risk Management Measures</b>
General measures (Aspiration)	The H304 hazard statement (May be fatal if swallowed and enters airways) relates to potential for aspiration, a non-quantifiable hazard determined by physico-chemical properties (i.e. viscosity) that can occur during ingestion and also if it is vomited following ingestion. A DNEL cannot be derived. Risks from the physicochemical hazards of substances can be controlled by implementing risk management measures. For substances classified as H304, the following measures need to be implemented to control the aspiration hazard. Do not ingest. If swallowed, then seek immediate medical assistance

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Not applicable.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
Not applicable. Risk Management Measures are based on qualitative risk characterisation.	

<b>Section 3.2 -Environment</b>
Not applicable.

<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
<b>Section 4.1 - Health</b>	
Not applicable.	

<b>Section 4.2 -Environment</b>
Not applicable.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

### Exposure Scenario - Worker

<b>300000010614</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Use as binders and release agents- Industrial
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU3 <b>Process Categories:</b> PROC1, PROC2, PROC3, PROC4, PROC6, PROC7, PROC8a, PROC8b, PROC10, PROC13, PROC14 <b>Environmental Release Categories:</b> ERC4, ESVOC SpERC 4.10a.v1
<b>Scope of process</b>	Covers the use as binders and release agents including material transfers, mixing, application (including spraying and brushing), mould forming and casting, and handling of waste.

<b>SECTION 2</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
------------------	--

<b>Section 2.1</b>	<b>Control of Worker Exposure</b>
<b>Product Characteristics</b>	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100%., Unless stated otherwise.,
<b>Frequency and Duration of Use</b>	
Covers daily exposures up to 8 hours (unless stated differently).	
<b>Other Operational Conditions affecting Exposure</b>	
Operation is carried out at elevated temperature (> 20°C above ambient temperature). Assumes a good basic standard of occupational hygiene is implemented.	

<b>Contributing Scenarios</b>	<b>Risk Management Measures</b>
General measures (Aspiration)	The H304 hazard statement (May be fatal if swallowed and enters airways) relates to potential for aspiration, a non-quantifiable hazard determined by physico-chemical properties (i.e. viscosity) that can occur during ingestion and also if it is vomited following ingestion. A DNEL cannot be derived. Risks from the physicochemical hazards of substances can be controlled by implementing risk management measures. For substances classified as H304, the following measures need to be implemented to control the aspiration hazard. Do not ingest. If swallowed, then seek immediate medical assistance

<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Not applicable.	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
Not applicable. Risk Management Measures are based on qualitative risk characterisation.	
<b>Section 3.2 -Environment</b>	
Not applicable.	
<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
<b>Section 4.1 - Health</b>	
Not applicable.	
<b>Section 4.2 -Environment</b>	
Not applicable.	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

### Exposure Scenario - Worker

<b>300000010615</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Use as binders and release agents- Professional
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU22 <b>Process Categories:</b> PROC1, PROC2, PROC3, PROC4, PROC6, PROC8a, PROC8b, PROC10, PROC11, PROC14 <b>Environmental Release Categories:</b> ERC8a, ERC8d, ESVOC SpERC 8.10b.v1
<b>Scope of process</b>	Covers the use as binders and release agents including material transfers, mixing, application by spraying, brushing, and handling of waste.

<b>SECTION 2</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
------------------	--

<b>Section 2.1</b>	<b>Control of Worker Exposure</b>
<b>Product Characteristics</b>	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100%., Unless stated otherwise.,
<b>Frequency and Duration of Use</b>	
Covers daily exposures up to 8 hours (unless stated differently).	
<b>Other Operational Conditions affecting Exposure</b>	
Operation is carried out at elevated temperature (> 20°C above ambient temperature). Assumes a good basic standard of occupational hygiene is implemented.	

<b>Contributing Scenarios</b>	<b>Risk Management Measures</b>
General measures (Aspiration)	The H304 hazard statement (May be fatal if swallowed and enters airways) relates to potential for aspiration, a non-quantifiable hazard determined by physico-chemical properties (i.e. viscosity) that can occur during ingestion and also if it is vomited following ingestion. A DNEL cannot be derived. Risks from the physicochemical hazards of substances can be controlled by implementing risk management measures. For substances classified as H304, the following measures need to be implemented to control the aspiration hazard. Do not ingest. If swallowed, then seek immediate medical assistance

<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Not applicable.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
------------------	----------------------------

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

### Section 3.1 - Health

Not applicable.

Risk Management Measures are based on qualitative risk characterisation.

### Section 3.2 -Environment

Not applicable.

## SECTION 4

### GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO

#### Section 4.1 - Health

Not applicable.

#### Section 4.2 -Environment

Not applicable.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

### Exposure Scenario - Worker

<b>300000010616</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Use in Agrochemicals uses- Professional
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU22 <b>Process Categories:</b> PROC1, PROC2, PROC4, PROC8a, PROC8b, PROC11, PROC13 <b>Environmental Release Categories:</b> ERC8a, ERC8d, ESVOC SpERC 8.11a.v1
<b>Scope of process</b>	Use as an agrochemical excipient for application by manual or machine spraying, smokes and fogging; including equipment clean-downs and disposal.

<b>SECTION 2</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
------------------	--

<b>Section 2.1</b>	<b>Control of Worker Exposure</b>
<b>Product Characteristics</b>	

<b>Contributing Scenarios</b>	<b>Risk Management Measures</b>
General measures (Aspiration)	The H304 hazard statement (May be fatal if swallowed and enters airways) relates to potential for aspiration, a non-quantifiable hazard determined by physico-chemical properties (i.e. viscosity) that can occur during ingestion and also if it is vomited following ingestion. A DNEL cannot be derived. Risks from the physicochemical hazards of substances can be controlled by implementing risk management measures. For substances classified as H304, the following measures need to be implemented to control the aspiration hazard. Do not ingest. If swallowed, then seek immediate medical assistance

<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Not applicable.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
Not applicable. Risk Management Measures are based on qualitative risk characterisation.	

<b>Section 3.2 -Environment</b>	
Not applicable.	



# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
<b>Section 4.1 - Health</b>	
Not applicable.	
<b>Section 4.2 -Environment</b>	
Not applicable.	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

### Exposure Scenario - Worker

<b>300000010618</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Use as a fuel- Industrial
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU3 <b>Process Categories:</b> PROC1, PROC2, PROC3, PROC8a, PROC8b, PROC16 <b>Environmental Release Categories:</b> ERC7, ESVOC SpERC 7.12a.v1
<b>Scope of process</b>	Covers the use as a fuel (or fuel additive) and includes activities associated with its transfer, use, equipment maintenance and handling of waste.

<b>SECTION 2</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
------------------	--

<b>Section 2.1</b>	<b>Control of Worker Exposure</b>
<b>Product Characteristics</b>	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100%., Unless stated otherwise.,
<b>Frequency and Duration of Use</b>	
Covers daily exposures up to 8 hours (unless stated differently).	
<b>Other Operational Conditions affecting Exposure</b>	
Operation is carried out at elevated temperature (> 20°C above ambient temperature). Assumes a good basic standard of occupational hygiene is implemented.	

<b>Contributing Scenarios</b>	<b>Risk Management Measures</b>
General measures (Aspiration)	The H304 hazard statement (May be fatal if swallowed and enters airways) relates to potential for aspiration, a non-quantifiable hazard determined by physico-chemical properties (i.e. viscosity) that can occur during ingestion and also if it is vomited following ingestion. A DNEL cannot be derived. Risks from the physicochemical hazards of substances can be controlled by implementing risk management measures. For substances classified as H304, the following measures need to be implemented to control the aspiration hazard. Do not ingest. If swallowed, then seek immediate medical assistance

<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Not applicable.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
------------------	----------------------------

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

### Section 3.1 - Health

Not applicable.

Risk Management Measures are based on qualitative risk characterisation.

### Section 3.2 -Environment

Not applicable.

### SECTION 4

#### GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO

### Section 4.1 - Health

Not applicable.

### Section 4.2 -Environment

Not applicable.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

### Exposure Scenario - Worker

<b>300000010619</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Use as a fuel- Professional
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU22 <b>Process Categories:</b> PROC1, PROC2, PROC3, PROC8a, PROC8b, PROC16 <b>Environmental Release Categories:</b> ERC9a, ERC9b, ESVOC SpERC 9.12b.v1
<b>Scope of process</b>	Covers the use as a fuel (or fuel additive) and includes activities associated with its transfer, use, equipment maintenance and handling of waste.

<b>SECTION 2</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
------------------	--

<b>Section 2.1</b>	<b>Control of Worker Exposure</b>
<b>Product Characteristics</b>	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100%., Unless stated otherwise.,
<b>Frequency and Duration of Use</b>	
Covers daily exposures up to 8 hours (unless stated differently).	
<b>Other Operational Conditions affecting Exposure</b>	
Operation is carried out at elevated temperature (> 20°C above ambient temperature). Assumes a good basic standard of occupational hygiene is implemented.	

<b>Contributing Scenarios</b>	<b>Risk Management Measures</b>
General measures (Aspiration)	The H304 hazard statement (May be fatal if swallowed and enters airways) relates to potential for aspiration, a non-quantifiable hazard determined by physico-chemical properties (i.e. viscosity) that can occur during ingestion and also if it is vomited following ingestion. A DNEL cannot be derived. Risks from the physicochemical hazards of substances can be controlled by implementing risk management measures. For substances classified as H304, the following measures need to be implemented to control the aspiration hazard. Do not ingest. If swallowed, then seek immediate medical assistance

<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Not applicable.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
------------------	----------------------------

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

### Section 3.1 - Health

Not applicable.

Risk Management Measures are based on qualitative risk characterisation.

### Section 3.2 -Environment

Not applicable.

## SECTION 4

### GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO

#### Section 4.1 - Health

Not applicable.

#### Section 4.2 -Environment

Not applicable.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

### Exposure Scenario - Worker

300000010621

SECTION 1	EXPOSURE SCENARIO TITLE
Title	Functional Fluids- Industrial
Use Descriptor	<b>Sector of Use:</b> SU3 <b>Process Categories:</b> PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC9 <b>Environmental Release Categories:</b> ERC7, ESVOC SpERC 7.13a.v1
Scope of process	Use as functional fluids e.g. cable oils, transfer oils, coolants, insulators, refrigerants, hydraulic fluids in industrial equipment including maintenance and related material transfers.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
-----------	---

Section 2.1	Control of Worker Exposure
<b>Product Characteristics</b>	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100%., Unless stated otherwise.,
<b>Frequency and Duration of Use</b>	
Covers daily exposures up to 8 hours (unless stated differently).	
<b>Other Operational Conditions affecting Exposure</b>	
Operation is carried out at elevated temperature (> 20°C above ambient temperature). Assumes a good basic standard of occupational hygiene is implemented.	

Contributing Scenarios	Risk Management Measures
General measures (Aspiration)	The H304 hazard statement (May be fatal if swallowed and enters airways) relates to potential for aspiration, a non-quantifiable hazard determined by physico-chemical properties (i.e. viscosity) that can occur during ingestion and also if it is vomited following ingestion. A DNEL cannot be derived. Risks from the physicochemical hazards of substances can be controlled by implementing risk management measures. For substances classified as H304, the following measures need to be implemented to control the aspiration hazard. Do not ingest. If swallowed, then seek immediate medical assistance

Section 2.2	Control of Environmental Exposure
Not applicable.	

SECTION 3	EXPOSURE ESTIMATION
-----------	---------------------

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

### Section 3.1 - Health

Not applicable.

Risk Management Measures are based on qualitative risk characterisation.

### Section 3.2 -Environment

Not applicable.

## SECTION 4

### GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO

#### Section 4.1 - Health

Not applicable.

#### Section 4.2 -Environment

Not applicable.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

### Exposure Scenario - Worker

<b>300000010622</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Functional Fluids- Professional
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU22 <b>Process Categories:</b> PROC1, PROC2, PROC3, PROC8a, PROC9, PROC20 <b>Environmental Release Categories:</b> ERC9a, ERC9b, ESVOC SpERC 9.13b.v1
<b>Scope of process</b>	Use as functional fluids e.g. cable oils, transfer oils, coolants, insulators, refrigerants, hydraulic fluids in professional equipment including maintenance and related material transfers.

<b>SECTION 2</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
------------------	--

<b>Section 2.1</b>	<b>Control of Worker Exposure</b>
<b>Product Characteristics</b>	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100%., Unless stated otherwise.,
<b>Frequency and Duration of Use</b>	
Covers daily exposures up to 8 hours (unless stated differently).	
<b>Other Operational Conditions affecting Exposure</b>	
Operation is carried out at elevated temperature (> 20°C above ambient temperature). Assumes a good basic standard of occupational hygiene is implemented.	

<b>Contributing Scenarios</b>	<b>Risk Management Measures</b>
General measures (Aspiration)	The H304 hazard statement (May be fatal if swallowed and enters airways) relates to potential for aspiration, a non-quantifiable hazard determined by physico-chemical properties (i.e. viscosity) that can occur during ingestion and also if it is vomited following ingestion. A DNEL cannot be derived. Risks from the physicochemical hazards of substances can be controlled by implementing risk management measures. For substances classified as H304, the following measures need to be implemented to control the aspiration hazard. Do not ingest. If swallowed, then seek immediate medical assistance

<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Not applicable.	



# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
Not applicable. Risk Management Measures are based on qualitative risk characterisation.	
<b>Section 3.2 -Environment</b>	
Not applicable.	
<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
<b>Section 4.1 - Health</b>	
Not applicable.	
<b>Section 4.2 -Environment</b>	
Not applicable.	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

### Exposure Scenario - Worker

<b>300000010623</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Road and construction applications- Professional
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU22 <b>Process Categories:</b> PROC1, PROC2, PROC8a, PROC8b, PROC9, PROC10, PROC11, PROC13 <b>Environmental Release Categories:</b> ERC8d, ERC8f, ESVOC SpERC 8.15.v1
<b>Scope of process</b>	Application of surface coatings and binders in road and construction activities, including paving uses, manual mastic and in the application of roofing and water-proofing membranes.

<b>SECTION 2</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
------------------	--

<b>Section 2.1</b>	<b>Control of Worker Exposure</b>
<b>Product Characteristics</b>	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100%., Unless stated otherwise.,
<b>Frequency and Duration of Use</b>	
Covers daily exposures up to 8 hours (unless stated differently).	
<b>Other Operational Conditions affecting Exposure</b>	
Operation is carried out at elevated temperature (> 20°C above ambient temperature). Assumes a good basic standard of occupational hygiene is implemented.	

<b>Contributing Scenarios</b>	<b>Risk Management Measures</b>
General measures (Aspiration)	The H304 hazard statement (May be fatal if swallowed and enters airways) relates to potential for aspiration, a non-quantifiable hazard determined by physico-chemical properties (i.e. viscosity) that can occur during ingestion and also if it is vomited following ingestion. A DNEL cannot be derived. Risks from the physicochemical hazards of substances can be controlled by implementing risk management measures. For substances classified as H304, the following measures need to be implemented to control the aspiration hazard. Do not ingest. If swallowed, then seek immediate medical assistance

<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Not applicable.	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
Not applicable. Risk Management Measures are based on qualitative risk characterisation.	
<b>Section 3.2 -Environment</b>	
Not applicable.	
<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
<b>Section 4.1 - Health</b>	
Not applicable.	
<b>Section 4.2 -Environment</b>	
Not applicable.	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

### Exposure Scenario - Worker

<b>300000010625</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Use in laboratories- Industrial
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU3 <b>Process Categories:</b> PROC15 <b>Environmental Release Categories:</b> ERC2, ERC4
<b>Scope of process</b>	Use of the substance within laboratory settings, including material transfers and equipment cleaning.

<b>SECTION 2</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
------------------	--

<b>Section 2.1</b>	<b>Control of Worker Exposure</b>
<b>Product Characteristics</b>	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100%., Unless stated otherwise.,
<b>Frequency and Duration of Use</b>	
Covers daily exposures up to 8 hours (unless stated differently).	
<b>Other Operational Conditions affecting Exposure</b>	
Operation is carried out at elevated temperature (> 20°C above ambient temperature). Assumes a good basic standard of occupational hygiene is implemented.	

<b>Contributing Scenarios</b>	<b>Risk Management Measures</b>
General measures (Aspiration)	The H304 hazard statement (May be fatal if swallowed and enters airways) relates to potential for aspiration, a non-quantifiable hazard determined by physico-chemical properties (i.e. viscosity) that can occur during ingestion and also if it is vomited following ingestion. A DNEL cannot be derived. Risks from the physicochemical hazards of substances can be controlled by implementing risk management measures. For substances classified as H304, the following measures need to be implemented to control the aspiration hazard. Do not ingest. If swallowed, then seek immediate medical assistance

<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Not applicable.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
Not applicable.	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

Risk Management Measures are based on qualitative risk characterisation.

### Section 3.2 -Environment

Not applicable.

### SECTION 4

#### GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO

### Section 4.1 - Health

Not applicable.

### Section 4.2 -Environment

Not applicable.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

### Exposure Scenario - Worker

<b>300000010626</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Use in laboratories- Professional
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU22 <b>Process Categories:</b> PROC15 <b>Environmental Release Categories:</b> ERC8a, ESVOC SpERC 8.17.v1
<b>Scope of process</b>	Use of small quantities within laboratory settings, including material transfers and equipment cleaning.

<b>SECTION 2</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
------------------	--

<b>Section 2.1</b>	<b>Control of Worker Exposure</b>
<b>Product Characteristics</b>	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100%., Unless stated otherwise.,
<b>Frequency and Duration of Use</b>	
Covers daily exposures up to 8 hours (unless stated differently).	
<b>Other Operational Conditions affecting Exposure</b>	
Operation is carried out at elevated temperature (> 20°C above ambient temperature). Assumes a good basic standard of occupational hygiene is implemented.	

<b>Contributing Scenarios</b>	<b>Risk Management Measures</b>
General measures (Aspiration)	The H304 hazard statement (May be fatal if swallowed and enters airways) relates to potential for aspiration, a non-quantifiable hazard determined by physico-chemical properties (i.e. viscosity) that can occur during ingestion and also if it is vomited following ingestion. A DNEL cannot be derived. Risks from the physicochemical hazards of substances can be controlled by implementing risk management measures. For substances classified as H304, the following measures need to be implemented to control the aspiration hazard. Do not ingest. If swallowed, then seek immediate medical assistance

<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Not applicable.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

Not applicable.  
Risk Management Measures are based on qualitative risk characterisation.

### Section 3.2 -Environment

Not applicable.

### SECTION 4

#### GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO

#### Section 4.1 - Health

Not applicable.

#### Section 4.2 -Environment

Not applicable.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

### Exposure Scenario - Worker

<b>300000010637</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Use in explosives- Professional
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU22 <b>Process Categories:</b> PROC1, PROC3, PROC5, PROC8a, PROC8b <b>Environmental Release Categories:</b> ERC8e
<b>Scope of process</b>	Covers exposures arising from the manufacture and use of slurry explosives (including materials transfer, mixing and charging) and equipment cleaning.

<b>SECTION 2</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
------------------	--

<b>Section 2.1</b>	<b>Control of Worker Exposure</b>
<b>Product Characteristics</b>	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100%., Unless stated otherwise.,
<b>Frequency and Duration of Use</b>	
Covers daily exposures up to 8 hours (unless stated differently).	
<b>Other Operational Conditions affecting Exposure</b>	
Operation is carried out at elevated temperature (> 20°C above ambient temperature). Assumes a good basic standard of occupational hygiene is implemented.	

<b>Contributing Scenarios</b>	<b>Risk Management Measures</b>
General measures (Aspiration)	The H304 hazard statement (May be fatal if swallowed and enters airways) relates to potential for aspiration, a non-quantifiable hazard determined by physico-chemical properties (i.e. viscosity) that can occur during ingestion and also if it is vomited following ingestion. A DNEL cannot be derived. Risks from the physicochemical hazards of substances can be controlled by implementing risk management measures. For substances classified as H304, the following measures need to be implemented to control the aspiration hazard. Do not ingest. If swallowed, then seek immediate medical assistance

<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Not applicable.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
------------------	----------------------------



# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

### Section 3.1 - Health

Not applicable.

Risk Management Measures are based on qualitative risk characterisation.

### Section 3.2 -Environment

Not applicable.

### SECTION 4

#### GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO

### Section 4.1 - Health

Not applicable.

### Section 4.2 -Environment

Not applicable.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

### Exposure Scenario - Worker

<b>300000010627</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Rubber production and processing- Industrial
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU3, SU10 <b>Process Categories:</b> PROC1, PROC2, PROC3, PROC4, PROC5, PROC6, PROC7, PROC8a, PROC8b, PROC9, PROC13, PROC14, PROC15, PROC21 <b>Environmental Release Categories:</b> ERC1, ERC4, ERC6d, ESVOC SpERC 4.19.v1
<b>Scope of process</b>	Manufacture of tyres and general rubber articles, including processing of raw (uncured) rubber, handling and mixing of rubber additives, vulcanising, cooling and finishing.

<b>SECTION 2</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
------------------	--

<b>Section 2.1</b>	<b>Control of Worker Exposure</b>
<b>Product Characteristics</b>	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100%., Unless stated otherwise.,
<b>Frequency and Duration of Use</b>	
Covers daily exposures up to 8 hours (unless stated differently).	
<b>Other Operational Conditions affecting Exposure</b>	
Operation is carried out at elevated temperature (> 20°C above ambient temperature). Assumes a good basic standard of occupational hygiene is implemented.	

<b>Contributing Scenarios</b>	<b>Risk Management Measures</b>
General measures (Aspiration)	The H304 hazard statement (May be fatal if swallowed and enters airways) relates to potential for aspiration, a non-quantifiable hazard determined by physico-chemical properties (i.e. viscosity) that can occur during ingestion and also if it is vomited following ingestion. A DNEL cannot be derived. Risks from the physicochemical hazards of substances can be controlled by implementing risk management measures. For substances classified as H304, the following measures need to be implemented to control the aspiration hazard. Do not ingest. If swallowed, then seek immediate medical assistance

<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Not applicable.	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
Not applicable. Risk Management Measures are based on qualitative risk characterisation.	
<b>Section 3.2 -Environment</b>	
Not applicable.	
<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
<b>Section 4.1 - Health</b>	
Not applicable.	
<b>Section 4.2 -Environment</b>	
Not applicable.	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

### Exposure Scenario - Worker

<b>300000010628</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Polymer processing- Industrial
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU10 <b>Process Categories:</b> PROC1, PROC2, PROC3, PROC4, PROC5, PROC6, PROC8a, PROC8b, PROC9, PROC13, PROC14, PROC21 <b>Environmental Release Categories:</b> ERC4, ESVOC SpERC 4.21a.v1
<b>Scope of process</b>	Processing of formulated polymers including material transfers, additives handling (e.g. pigments, stabilisers, fillers, plasticisers, etc.), moulding, curing and forming activities, material re-works, storage and associated maintenance.

<b>SECTION 2</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
------------------	--

<b>Section 2.1</b>	<b>Control of Worker Exposure</b>
<b>Product Characteristics</b>	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100%., Unless stated otherwise.,
<b>Frequency and Duration of Use</b>	
Covers daily exposures up to 8 hours (unless stated differently).	
<b>Other Operational Conditions affecting Exposure</b>	
Operation is carried out at elevated temperature (> 20°C above ambient temperature). Assumes a good basic standard of occupational hygiene is implemented.	

<b>Contributing Scenarios</b>	<b>Risk Management Measures</b>
General measures (Aspiration)	The H304 hazard statement (May be fatal if swallowed and enters airways) relates to potential for aspiration, a non-quantifiable hazard determined by physico-chemical properties (i.e. viscosity) that can occur during ingestion and also if it is vomited following ingestion. A DNEL cannot be derived. Risks from the physicochemical hazards of substances can be controlled by implementing risk management measures. For substances classified as H304, the following measures need to be implemented to control the aspiration hazard. Do not ingest. If swallowed, then seek immediate medical assistance

<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Not applicable.	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
Not applicable. Risk Management Measures are based on qualitative risk characterisation.	
<b>Section 3.2 -Environment</b>	
Not applicable.	
<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
<b>Section 4.1 - Health</b>	
Not applicable.	
<b>Section 4.2 -Environment</b>	
Not applicable.	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

### Exposure Scenario - Worker

<b>300000010629</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Polymer processing- Professional
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU22 <b>Process Categories:</b> PROC1, PROC2, PROC6, PROC8a, PROC8b, PROC14, PROC21 <b>Environmental Release Categories:</b> ERC8a, ERC8d, ESVOC SpERC 8.21b.v1
<b>Scope of process</b>	Processing of formulated polymers including material transfers, moulding and forming activities, material re-works and associated maintenance.

<b>SECTION 2</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
------------------	--

<b>Section 2.1</b>	<b>Control of Worker Exposure</b>
<b>Product Characteristics</b>	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100%., Unless stated otherwise.,
<b>Frequency and Duration of Use</b>	
Covers daily exposures up to 8 hours (unless stated differently).	
<b>Other Operational Conditions affecting Exposure</b>	
Operation is carried out at elevated temperature (> 20°C above ambient temperature). Assumes a good basic standard of occupational hygiene is implemented.	

<b>Contributing Scenarios</b>	<b>Risk Management Measures</b>
General measures (Aspiration)	The H304 hazard statement (May be fatal if swallowed and enters airways) relates to potential for aspiration, a non-quantifiable hazard determined by physico-chemical properties (i.e. viscosity) that can occur during ingestion and also if it is vomited following ingestion. A DNEL cannot be derived. Risks from the physicochemical hazards of substances can be controlled by implementing risk management measures. For substances classified as H304, the following measures need to be implemented to control the aspiration hazard. Do not ingest. If swallowed, then seek immediate medical assistance

<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Not applicable.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
------------------	----------------------------

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

### Section 3.1 - Health

Not applicable.

Risk Management Measures are based on qualitative risk characterisation.

### Section 3.2 -Environment

Not applicable.

### SECTION 4

#### GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO

### Section 4.1 - Health

Not applicable.

### Section 4.2 -Environment

Not applicable.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

### Exposure Scenario - Worker

<b>300000010630</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Water treatment chemicals- Industrial
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU3 <b>Process Categories:</b> PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC13 <b>Environmental Release Categories:</b> ERC3, ERC4, ESVOC SpERC 3.22a.v1
<b>Scope of process</b>	Covers the use of the substance for the treatment of water in open and closed systems.

<b>SECTION 2</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
------------------	--

<b>Section 2.1</b>	<b>Control of Worker Exposure</b>
<b>Product Characteristics</b>	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100%., Unless stated otherwise.,
<b>Frequency and Duration of Use</b>	
Covers daily exposures up to 8 hours (unless stated differently).	
<b>Other Operational Conditions affecting Exposure</b>	
Operation is carried out at elevated temperature (> 20°C above ambient temperature). Assumes a good basic standard of occupational hygiene is implemented.	

<b>Contributing Scenarios</b>	<b>Risk Management Measures</b>
General measures (Aspiration)	The H304 hazard statement (May be fatal if swallowed and enters airways) relates to potential for aspiration, a non-quantifiable hazard determined by physico-chemical properties (i.e. viscosity) that can occur during ingestion and also if it is vomited following ingestion. A DNEL cannot be derived. Risks from the physicochemical hazards of substances can be controlled by implementing risk management measures. For substances classified as H304, the following measures need to be implemented to control the aspiration hazard. Do not ingest. If swallowed, then seek immediate medical assistance

<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Not applicable.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
------------------	----------------------------



# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

### Section 3.1 - Health

Not applicable.

Risk Management Measures are based on qualitative risk characterisation.

### Section 3.2 -Environment

Not applicable.

### SECTION 4

### GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO

#### Section 4.1 - Health

Not applicable.

#### Section 4.2 -Environment

Not applicable.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

### Exposure Scenario - Worker

<b>300000010631</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Water treatment chemicals- Professional
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU22 <b>Process Categories:</b> PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC13 <b>Environmental Release Categories:</b> ERC8f, ESVOC SpERC 8.22b.v1
<b>Scope of process</b>	Covers the use of the substance for the treatment of water in open and closed systems.

<b>SECTION 2</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
------------------	--

<b>Section 2.1</b>	<b>Control of Worker Exposure</b>
<b>Product Characteristics</b>	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100%., Unless stated otherwise.,
<b>Frequency and Duration of Use</b>	
Covers daily exposures up to 8 hours (unless stated differently).	
<b>Other Operational Conditions affecting Exposure</b>	
Operation is carried out at elevated temperature (> 20°C above ambient temperature). Assumes a good basic standard of occupational hygiene is implemented.	

<b>Contributing Scenarios</b>	<b>Risk Management Measures</b>
General measures (Aspiration)	The H304 hazard statement (May be fatal if swallowed and enters airways) relates to potential for aspiration, a non-quantifiable hazard determined by physico-chemical properties (i.e. viscosity) that can occur during ingestion and also if it is vomited following ingestion. A DNEL cannot be derived. Risks from the physicochemical hazards of substances can be controlled by implementing risk management measures. For substances classified as H304, the following measures need to be implemented to control the aspiration hazard. Do not ingest. If swallowed, then seek immediate medical assistance

<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Not applicable.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
------------------	----------------------------

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

### Section 3.1 - Health

Not applicable.

Risk Management Measures are based on qualitative risk characterisation.

### Section 3.2 -Environment

Not applicable.

### SECTION 4

#### GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO

### Section 4.1 - Health

Not applicable.

### Section 4.2 -Environment

Not applicable.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

### Exposure Scenario - Worker

<b>300000010633</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Mining chemicals- Industrial
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU3 <b>Process Categories:</b> PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9 <b>Environmental Release Categories:</b> ERC4, ESVOC SpERC 4.23.v1
<b>Scope of process</b>	Covers the use of the substance in extraction processes at mining operations, including material transfers, winning and separation activities, and substance recovery and disposal.

<b>SECTION 2</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
------------------	--

<b>Section 2.1</b>	<b>Control of Worker Exposure</b>
<b>Product Characteristics</b>	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100%., Unless stated otherwise.,
<b>Frequency and Duration of Use</b>	
Covers daily exposures up to 8 hours (unless stated differently).	
<b>Other Operational Conditions affecting Exposure</b>	
Operation is carried out at elevated temperature (> 20°C above ambient temperature). Assumes a good basic standard of occupational hygiene is implemented.	

<b>Contributing Scenarios</b>	<b>Risk Management Measures</b>
General measures (Aspiration)	The H304 hazard statement (May be fatal if swallowed and enters airways) relates to potential for aspiration, a non-quantifiable hazard determined by physico-chemical properties (i.e. viscosity) that can occur during ingestion and also if it is vomited following ingestion. A DNEL cannot be derived. Risks from the physicochemical hazards of substances can be controlled by implementing risk management measures. For substances classified as H304, the following measures need to be implemented to control the aspiration hazard. Do not ingest. If swallowed, then seek immediate medical assistance

<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Not applicable.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
------------------	----------------------------

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

### Section 3.1 - Health

Not applicable.

Risk Management Measures are based on qualitative risk characterisation.

### Section 3.2 -Environment

Not applicable.

### SECTION 4

#### GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO

### Section 4.1 - Health

Not applicable.

### Section 4.2 -Environment

Not applicable.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

### Exposure Scenario - Consumer

<b>300000010607</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Uses in Coatings - Consumer
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU21 <b>Product Categories:</b> PC1, PC4, PC8 (excipient only), PC9a, PC9b, PC9c, PC15, PC18, PC23, PC24, PC31, PC34 <b>Environmental Release Categories:</b> ERC8a, ERC8d, ESVOC SpERC 8.3c.v1
<b>Scope of process</b>	Covers the use in coatings (paints, inks, adhesives, etc) including exposures during use (including product transfer and preparation, application by brush, spray by hand or similar methods) and equipment cleaning.

<b>SECTION 2</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
------------------	--

<b>Section 2.1</b>	<b>Control of Consumer Exposure</b>
<b>Product Characteristics</b>	

<b>Product Categories</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
General measures (Aspiration)	The H304 hazard statement (May be fatal if swallowed and enters airways) relates to potential for aspiration, a non-quantifiable hazard determined by physico-chemical properties (i.e. viscosity) that can occur during ingestion and also if it is vomited following ingestion. A DNEL cannot be derived. Risks from the physicochemical hazards of substances can be controlled by implementing risk management measures. For substances classified as H304, the following measures need to be implemented to control the aspiration hazard. Do not ingest. If swallowed, then seek immediate medical assistance

<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Not applicable.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
Not applicable. Risk Management Measures are based on qualitative risk characterisation.	

<b>Section 3.2 -Environment</b>	
Not applicable.	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
<b>Section 4.1 - Health</b>	
Not applicable.	
<b>Section 4.2 -Environment</b>	
Not applicable.	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

### Exposure Scenario - Consumer

<b>300000010608</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Use in Cleaning Agents - Consumer
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU21 <b>Product Categories:</b> PC3, PC4, PC8 (excipient only), PC9a, PC9b, PC9c, PC24, PC35, PC38 <b>Environmental Release Categories:</b> ERC8a, ERC8d, ESVOC SpERC 8.4c.v1
<b>Scope of process</b>	Covers general exposures to consumers arising from the use of household products sold as washing and cleaning products, aerosols, coatings, de-icers, lubricants and air care products.

<b>SECTION 2</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
------------------	--

<b>Section 2.1</b>	<b>Control of Consumer Exposure</b>
<b>Product Characteristics</b>	

<b>Product Categories</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
General measures (Aspiration)	The H304 hazard statement (May be fatal if swallowed and enters airways) relates to potential for aspiration, a non-quantifiable hazard determined by physico-chemical properties (i.e. viscosity) that can occur during ingestion and also if it is vomited following ingestion. A DNEL cannot be derived. Risks from the physicochemical hazards of substances can be controlled by implementing risk management measures. For substances classified as H304, the following measures need to be implemented to control the aspiration hazard. Do not ingest. If swallowed, then seek immediate medical assistance

<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Not applicable.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
Not applicable. Risk Management Measures are based on qualitative risk characterisation.	

<b>Section 3.2 -Environment</b>	
Not applicable.	



# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
<b>Section 4.1 - Health</b>	
Not applicable.	
<b>Section 4.2 -Environment</b>	
Not applicable.	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

### Exposure Scenario - Consumer

<b>300000010611</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Lubricants - Consumer Low Environmental Release High Environmental Release
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU21 <b>Product Categories:</b> PC1, PC24, PC31 <b>Environmental Release Categories:</b> ERC8a, ERC8d, ERC9a, ERC9b, ESVOC SpERC 8.6e.v1, ESVOC SpERC 9.6d.v1
<b>Scope of process</b>	Covers the consumer use of formulated lubricants in closed and open systems including transfer operations, application, operation of engines and similar articles, equipment maintenance and disposal of waste oil.

<b>SECTION 2</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
------------------	--

<b>Section 2.1</b>	<b>Control of Consumer Exposure</b>
<b>Product Characteristics</b>	

<b>Product Categories</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
General measures (Aspiration)	The H304 hazard statement (May be fatal if swallowed and enters airways) relates to potential for aspiration, a non-quantifiable hazard determined by physico-chemical properties (i.e. viscosity) that can occur during ingestion and also if it is vomited following ingestion. A DNEL cannot be derived. Risks from the physicochemical hazards of substances can be controlled by implementing risk management measures. For substances classified as H304, the following measures need to be implemented to control the aspiration hazard. Do not ingest. If swallowed, then seek immediate medical assistance

<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Not applicable.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
Not applicable. Risk Management Measures are based on qualitative risk characterisation.	

<b>Section 3.2 -Environment</b>	
Not applicable.	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
<b>Section 4.1 - Health</b>	
Not applicable.	
<b>Section 4.2 -Environment</b>	
Not applicable.	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

### Exposure Scenario - Consumer

<b>300000010620</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Use as a fuel - Consumer
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU21 <b>Product Categories:</b> PC13 <b>Environmental Release Categories:</b> ERC9a, ERC9b, ESVOC SpERC 9.12c.v1
<b>Scope of process</b>	Covers consumer uses in liquid fuels.

<b>SECTION 2</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
------------------	--

<b>Section 2.1</b>	<b>Control of Consumer Exposure</b>
<b>Product Characteristics</b>	

<b>Product Categories</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
General measures (Aspiration)	The H304 hazard statement (May be fatal if swallowed and enters airways) relates to potential for aspiration, a non-quantifiable hazard determined by physico-chemical properties (i.e. viscosity) that can occur during ingestion and also if it is vomited following ingestion. A DNEL cannot be derived. Risks from the physicochemical hazards of substances can be controlled by implementing risk management measures. For substances classified as H304, the following measures need to be implemented to control the aspiration hazard. Do not ingest. If swallowed, then seek immediate medical assistance

<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Not applicable.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
Not applicable. Risk Management Measures are based on qualitative risk characterisation.	

<b>Section 3.2 -Environment</b>	
Not applicable.	

<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
<b>Section 4.1 - Health</b>	
Not applicable.	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

--

<b>Section 4.2 -Environment</b>
---------------------------------

Not applicable.
-----------------

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

### Exposure Scenario - Consumer

<b>300000010636</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Functional Fluids - Consumer
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU21 <b>Product Categories:</b> PC16, PC17 <b>Environmental Release Categories:</b> ERC9a, ERC9b, ESVOC SpERC 9.13c.v1
<b>Scope of process</b>	Use of sealed items containing functional fluids e.g. transfer oils, hydraulic fluids, refrigerants.

<b>SECTION 2</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
------------------	--

<b>Section 2.1</b>	<b>Control of Consumer Exposure</b>
<b>Product Characteristics</b>	

<b>Product Categories</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
General measures (Aspiration)	The H304 hazard statement (May be fatal if swallowed and enters airways) relates to potential for aspiration, a non-quantifiable hazard determined by physico-chemical properties (i.e. viscosity) that can occur during ingestion and also if it is vomited following ingestion. A DNEL cannot be derived. Risks from the physicochemical hazards of substances can be controlled by implementing risk management measures. For substances classified as H304, the following measures need to be implemented to control the aspiration hazard. Do not ingest. If swallowed, then seek immediate medical assistance

<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Not applicable.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
Not applicable. Risk Management Measures are based on qualitative risk characterisation.	

<b>Section 3.2 -Environment</b>	
Not applicable.	

<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
<b>Section 4.1 - Health</b>	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

Not applicable.

### Section 4.2 -Environment

Not applicable.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

### Exposure Scenario - Consumer

<b>300000010624</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Other Consumer Uses - Consumer
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU21 <b>Product Categories:</b> PC28, PC39 <b>Environmental Release Categories:</b> ERC8a, ERC8d, ESVOC SpERC 8.16.v1
<b>Scope of process</b>	Consumer uses e.g. as a carrier in cosmetics/personal care products, perfumes and fragrances. Note: For cosmetic and personal care products, risk assessment only required for the environment under REACH as human health is covered by alternative legislation.

<b>SECTION 2</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
------------------	--

<b>Section 2.1</b>	<b>Control of Consumer Exposure</b>
<b>Product Characteristics</b>	

<b>Product Categories</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
General measures (Aspiration)	The H304 hazard statement (May be fatal if swallowed and enters airways) relates to potential for aspiration, a non-quantifiable hazard determined by physico-chemical properties (i.e. viscosity) that can occur during ingestion and also if it is vomited following ingestion. A DNEL cannot be derived. Risks from the physicochemical hazards of substances can be controlled by implementing risk management measures. For substances classified as H304, the following measures need to be implemented to control the aspiration hazard. Do not ingest. If swallowed, then seek immediate medical assistance

<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Not applicable.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
Not applicable. Risk Management Measures are based on qualitative risk characterisation.	

<b>Section 3.2 -Environment</b>	
Not applicable.	



# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
<b>Section 4.1 - Health</b>	
Not applicable.	
<b>Section 4.2 -Environment</b>	
Not applicable.	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

### Exposure Scenario - Consumer

<b>300000010638</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Water treatment chemicals - Consumer
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU21 <b>Product Categories:</b> PC36, PC37 <b>Environmental Release Categories:</b> ERC8f, ESVOC SpERC 8.22c.v1
<b>Scope of process</b>	Covers the use of the substance for the treatment of water in open and closed systems.

<b>SECTION 2</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
------------------	--

<b>Section 2.1</b>	<b>Control of Consumer Exposure</b>
<b>Product Characteristics</b>	

<b>Product Categories</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
General measures (Aspiration)	The H304 hazard statement (May be fatal if swallowed and enters airways) relates to potential for aspiration, a non-quantifiable hazard determined by physico-chemical properties (i.e. viscosity) that can occur during ingestion and also if it is vomited following ingestion. A DNEL cannot be derived. Risks from the physicochemical hazards of substances can be controlled by implementing risk management measures. For substances classified as H304, the following measures need to be implemented to control the aspiration hazard. Do not ingest. If swallowed, then seek immediate medical assistance

<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Not applicable.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
Not applicable. Risk Management Measures are based on qualitative risk characterisation.	

<b>Section 3.2 -Environment</b>	
Not applicable.	

<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
<b>Section 4.1 - Health</b>	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

Not applicable.

### Section 4.2 -Environment

Not applicable.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

### Exposure Scenario - Consumer

<b>300000010617</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Use in Agrochemicals uses - Consumer
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU21 <b>Product Categories:</b> PC8 (excipient only), PC12, PC27 <b>Environmental Release Categories:</b> ERC8a, ERC8d, ESVOC SpERC 8.11b.v1
<b>Scope of process</b>	Covers the consumer use in agrochemicals in liquid and solid forms.

<b>SECTION 2</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
------------------	--

<b>Section 2.1</b>	<b>Control of Consumer Exposure</b>
<b>Product Characteristics</b>	

<b>Product Categories</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
General measures (Aspiration)	The H304 hazard statement (May be fatal if swallowed and enters airways) relates to potential for aspiration, a non-quantifiable hazard determined by physico-chemical properties (i.e. viscosity) that can occur during ingestion and also if it is vomited following ingestion. A DNEL cannot be derived. Risks from the physicochemical hazards of substances can be controlled by implementing risk management measures. For substances classified as H304, the following measures need to be implemented to control the aspiration hazard. Do not ingest. If swallowed, then seek immediate medical assistance

<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Not applicable.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
Not applicable. Risk Management Measures are based on qualitative risk characterisation.	

<b>Section 3.2 -Environment</b>	
Not applicable.	

<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
<b>Section 4.1 - Health</b>	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 409

Version 1.3

Revision Date 29.03.2021

Print Date 29.08.2022

Not applicable.

### Section 4.2 -Environment

Not applicable.