

# SAFETY DATA SHEET

## BC AE-9A

Version 1.0

Revision Date 07.06.2024

Print Date 15.06.2024

### 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : BC AE-9A  
Product code : V2778  
Synonyms : Alcohols, C12-C14, ethoxylated  
CAS-No. : 68439-50-9

#### Manufacturer or supplier's details

Supplier : SHELL EASTERN CHEMICALS (S)  
A REGISTERED BUSINESS OF SHELL EASTERN  
TRADING (PTE) LTD (UEN:198902087C)  
9 North Buona Vista Drive , #07-01  
The Metropolis Tower 1  
Singapore 138588  
Singapore  
Telephone : +65 6384 8269  
Telefax : +65 6384 8454  
Contact for Safety Data :  
Sheet  
Emergency telephone : +800 2537 8747 ( ALERT SGS- toll Free) or +65 6542 9595  
number (ALERT SGS)

#### Recommended use of the chemical and restrictions on use

Recommended use : Use in detergent manufacture.  
Restrictions on use : This product must not be used in applications other than the  
above without first seeking the advice of the supplier.

### 2. HAZARDS IDENTIFICATION

#### GHS Classification

Acute toxicity (Oral) : Category 4  
Acute toxicity (Dermal) : Category 5  
Serious eye damage : Category 1  
Short-term (acute) aquatic : Category 2  
hazard  
Long-term (chronic) aquatic : Category 3  
hazard

#### GHS label elements

# SAFETY DATA SHEET

## BC AE-9A

Version 1.0

Revision Date 07.06.2024

Print Date 15.06.2024

Hazard pictograms

:



Signal word

:

Danger

Hazard statements

:

**PHYSICAL HAZARDS:**  
Not classified as a physical hazard under GHS criteria.  
**HEALTH HAZARDS:**  
H302 Harmful if swallowed.  
H313 May be harmful in contact with skin.  
H318 Causes serious eye damage.  
**ENVIRONMENTAL HAZARDS:**  
H401 Toxic to aquatic life.  
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

:

**Prevention:**

P264 Wash hands thoroughly after handling.  
P270 Do not eat, drink or smoke when using this product.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  
P273 Avoid release to the environment.

**Response:**

P301 + P312 IF SWALLOWED: Call a POISON CENTER/ doctor if you feel unwell.  
P330 Rinse mouth.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P310 Immediately call a POISON CENTER/ doctor.

**Storage:**

No precautionary phrases.

**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

**Other hazards which do not result in classification**

Repeated exposure may cause skin dryness or cracking.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture

: Substance

Hazardous components

# SAFETY DATA SHEET

## BC AE-9A

Version 1.0

Revision Date 07.06.2024

Print Date 15.06.2024

Chemical name	CAS-No.	Classification	Concentration (% w/w)
Alcohols, C12-14, ethoxylated	68439-50-9	Acute Tox.4; H302 Acute Tox.5; H313 Eye Dam.1; H318 Aquatic Acute2; H401 Aquatic Chronic3; H412	<= 100

For explanation of abbreviations see section 16.

### 4. FIRST-AID MEASURES

- General advice : Not expected to be a health hazard when used under normal conditions.
- If inhaled : No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.
- In case of skin contact : Remove contaminated clothing. Immediately flush skin with large amounts of water for at least 15 minutes, and follow by washing with soap and water if available. If needed, transport to the nearest medical facility for additional treatment.
- In case of eye contact : Immediately flush eye(s) with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Transport to the nearest medical facility for additional treatment.
- If swallowed : Do not induce vomiting. If victim is alert, rinse mouth and drink 1/2 to 1 glass of water to help dilute the material. Do not give liquids to a drowsy, convulsing, or unconscious person. Transport to nearest medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.
- Most important symptoms and effects, both acute and delayed : Not considered to be an inhalation hazard under normal conditions of use. Possible respiratory irritation signs and symptoms may include a temporary burning sensation of the nose and throat, coughing, and/or difficulty breathing.
- Skin irritation signs and symptoms may include a burning sensation, redness, swelling, and/or blisters.

# SAFETY DATA SHEET

## BC AE-9A

Version 1.0

Revision Date 07.06.2024

Print Date 15.06.2024

Corrosive to eyes.

Contact can cause severe eye damage including chemical burns, pain, clouding of the eye surface, inflammation of the eye, and may result in permanent loss of vision.

Swallowing of corrosive chemicals may cause immediate pain and burning in the mouth, throat, and stomach followed by vomiting and diarrhea.

Burns and tearing of the esophagus and stomach are possible.  
Ingestion may result in nausea, vomiting and/or diarrhoea.

Defatting dermatitis signs and symptoms may include a burning sensation and/or a dried/cracked appearance.

Protection of first-aiders : When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.

Notes to physician : IMMEDIATE TREATMENT IS EXTREMELY IMPORTANT!  
Call a doctor or poison control center for guidance.  
Potential for chemical pneumonitis.  
Treat symptomatically.

### 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Alcohol-resistant foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

Unsuitable extinguishing media : None

Specific hazards during firefighting : Carbon monoxide may be evolved if incomplete combustion occurs.

Specific extinguishing methods : Standard procedure for chemical fires.  
Clear fire area of all non-emergency personnel.  
Keep adjacent containers cool by spraying with water.

Special protective equipment for firefighters : Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

# SAFETY DATA SHEET

## BC AE-9A

Version 1.0

Revision Date 07.06.2024

Print Date 15.06.2024

### 6. ACCIDENTAL RELEASE MEASURES

- |   |   |   |
|---|---|---|
| Personal precautions, protective equipment and emergency procedures | : | <p>Observe all relevant local and international regulations. Notify authorities if any exposure to the general public or the environment occurs or is likely to occur. Local authorities should be advised if significant spillages cannot be contained.</p> <p>Avoid contact with spilled or released material. Immediately remove all contaminated clothing. For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet. For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet. Stay upwind and keep out of low areas. Be ready for fire or possible exposure.</p>                                |
| Environmental precautions   | : | <p>Prevent from spreading or entering into drains, ditches or rivers by using sand, earth, or other appropriate barriers. Use appropriate containment to avoid environmental contamination. Ventilate contaminated area thoroughly.</p>   |
| Methods and materials for containment and cleaning up               | : | <p>For large liquid spills (&gt; 1 drum), transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely. For small liquid spills (&lt; 1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.</p> |
| Additional advice   | : | <p>For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet. For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.</p>   |

### 7. HANDLING AND STORAGE

- |                     |   |   |
|---------------------|---|---|
| General Precautions | : | <p>Avoid breathing of or direct contact with material. Only use in well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material. Ensure that all local regulations regarding handling and</p> |
|---------------------|---|---|

# SAFETY DATA SHEET

## BC AE-9A

Version 1.0

Revision Date 07.06.2024

Print Date 15.06.2024

storage facilities are followed.

- Advice on safe handling : Avoid contact with skin, eyes and clothing.  
Do not empty into drains.
- Avoidance of contact : Copper.  
Copper alloys.  
Strong oxidising agents.  
Aluminum
- Product Transfer : Keep containers closed when not in use. Refer to guidance under Handling section.

### Storage

- Conditions for safe storage : Refer to section 15 for any additional specific legislation covering the packaging and storage of this product.
- Other data : Tanks should be fitted with heating coils in areas where the ambient temperatures are below the recommended product handling temperatures. Heating coil skin temperatures should not exceed 100 °C.  
Bulk storage tanks should be diked (bunded).  
Vapours from tanks should not be released to atmosphere.  
Breathing losses during storage should be controlled by a suitable vapour treatment system.  
Nitrogen blanket recommended for large tanks (capacity 100 m3 or higher).  
Insulation (lagging) will minimize heat loss in areas of low ambient temperature.  
Tanks should be fitted with heating coils in areas where ambient conditions can result in handling temperatures below the freezing point/pour point of the product.
- Packaging material : Suitable material: Stainless steel., Epoxy resins, Polyester.  
Unsuitable material: Aluminum, Copper., Copper alloys.
- Container Advice : Containers, even those that have been emptied, can contain explosive vapours. Do not cut, drill, grind, weld or perform similar operations on or near containers.
- Specific use(s) : Not applicable
- Ensure that all local regulations regarding handling and storage facilities are followed.

## 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

### Components with workplace control parameters

### Biological occupational exposure limits

# SAFETY DATA SHEET

## BC AE-9A

Version 1.0

Revision Date 07.06.2024

Print Date 15.06.2024

No biological limit allocated.

### Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods  
<http://www.cdc.gov/niosh/>

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods  
<http://www.osha.gov/>

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances  
<http://www.hse.gov.uk/>

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA) , Germany  
<http://www.dguv.de/inhalt/index.jsp>

L'Institut National de Recherche et de Sécurité, (INRS), France <http://www.inrs.fr/accueil>

### Engineering measures

: Adequate ventilation to control airborne concentrations below the exposure guidelines/limits.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated. Eye washes and showers for emergency use.

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

#### General Information:

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

Do not ingest. If swallowed, then seek immediate medical assistance.

### Personal protective equipment

# SAFETY DATA SHEET

## BC AE-9A

Version 1.0

Revision Date 07.06.2024

Print Date 15.06.2024

### Protective measures

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Respiratory protection : If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are unsuitable (e.g. airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. If air-filtering respirators are suitable for conditions of use: Select a filter suitable for the combination of organic gases and vapours and particles [Type A/Type P boiling point >65°C (149°F)].

Hand protection  
Remarks

: Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. Longer term protection: Nitrile rubber gloves. Incidental contact/Splash protection: PVC or neoprene rubber gloves. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

Eye protection : Wear goggles for use against liquids and gas. Wear full face shield if splashes are likely to occur.

Skin and body protection : Skin protection is not required under normal conditions of use. For prolonged or repeated exposures use impervious clothing over parts of the body subject to exposure. If repeated and/or prolonged skin exposure to the substance



# SAFETY DATA SHEET

## BC AE-9A

Version 1.0

Revision Date 07.06.2024

Print Date 15.06.2024

is likely, then wear suitable gloves tested to relevant Standard, and provide employee skin care programmes.

Thermal hazards : Not applicable

Hygiene measures : Wash hands before eating, drinking, smoking and using the toilet.  
Laundry contaminated clothing before re-use.

### Environmental exposure controls

General advice : Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour.  
Minimise release to the environment. An environmental assessment must be made to ensure compliance with local environmental legislation.  
Information on accidental release measures are to be found in section 6.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : solid

Colour : white

Odour : mild

Odour Threshold : Data not available

pH : 7

Melting / freezing point : 24.4 °C / 75.9 °F

Boiling point/boiling range : > 250 °C / > 482 °F

Flash point : 202 °C / 396 °F  
Method: ASTM D93 (PMCC)

Evaporation rate : Data not available

Flammability (solid, gas) : Not classified as flammable but will burn.

Upper explosion limit : Data not available

Lower explosion limit : Data not available

Vapour pressure : < 5 Pa (20 °C / 68 °F)

Relative vapour density : Data not available

Relative density : 0.982 (50 °C / 122 °F)  
Method: ASTM D4052

Density : 0.982 g/cm<sup>3</sup> (50 °C / 122 °F)  
Method: ASTM D4052

# SAFETY DATA SHEET

## BC AE-9A

Version 1.0

Revision Date 07.06.2024

Print Date 15.06.2024

### Solubility(ies)

Water solubility : completely soluble

Solubility in other solvents : Data not available

Partition coefficient: n-octanol/water : Data not available

Auto-ignition temperature : Data not available

Decomposition temperature : Data not available

### Viscosity

Viscosity, dynamic : 23.36 mPa.s (50 °C / 122 °F)  
Method: ASTM D445

Viscosity, dynamic : Not applicable (20 °C / 68 °F)  
Method: ASTM D445

Viscosity, kinematic : 23.8 mm<sup>2</sup>/s (50 °C / 122 °F)  
Method: ASTM D445

### Particle characteristics

Particle size : Data not available

Explosive properties : Not applicable

Oxidizing properties : Data not available

Surface tension : Data not available

Conductivity : Electrical conductivity: > 10,000 pS/m

A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid, This material is not expected to be a static accumulator.

Molecular weight : Data not available

## 10. STABILITY AND REACTIVITY

Reactivity : Stable at normal ambient temperature and pressure., May oxidise in the presence of air.

Chemical stability : Stable under normal conditions.

Possibility of hazardous : None known.

# SAFETY DATA SHEET

## BC AE-9A

Version 1.0

Revision Date 07.06.2024

Print Date 15.06.2024

reactions

Conditions to avoid : Extremes of temperature and direct sunlight.  
Product cannot ignite due to static electricity.

Incompatible materials : Copper.  
Copper alloys.  
Strong oxidising agents.  
Aluminum

Hazardous decomposition products : None expected under normal use conditions.

### 11. TOXICOLOGICAL INFORMATION

Basis for assessment : Information given is based on product testing, and/or similar products, and/or components.  
Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

Information on likely routes of exposure : Exposure may occur via inhalation, ingestion, skin absorption, skin or eye contact, and accidental ingestion.

#### Acute toxicity

##### Product:

Acute oral toxicity : LD50 Rat: > 300 - <= 2000 mg/kg  
Remarks: Harmful if swallowed.

Acute inhalation toxicity : Remarks: Low toxicity if inhaled.  
Based on available data, the classification criteria are not met.

Acute dermal toxicity : LD50 Rabbit: > 2000 - <= 5000 mg/kg  
Remarks: May be harmful in contact with skin.

#### Skin corrosion/irritation

##### Product:

Remarks: Causes mild skin irritation., Repeated exposure may cause skin dryness or cracking.

#### Serious eye damage/eye irritation

##### Product:

Remarks: Causes serious eye damage.

#### Respiratory or skin sensitisation

##### Product:

Remarks: Not a sensitiser.  
Based on available data, the classification criteria are not met.

# SAFETY DATA SHEET

## BC AE-9A

Version 1.0

Revision Date 07.06.2024

Print Date 15.06.2024

### Germ cell mutagenicity

**Product:**

: Remarks: Non mutagenic

### Carcinogenicity

**Product:**

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

Material	GHS/CLP Carcinogenicity Classification
Alcohols, C12-14, ethoxylated	No carcinogenicity classification.

### Reproductive toxicity

**Product:**

:  
Remarks: Does not impair fertility., Not a developmental toxicant.

### STOT - single exposure

**Product:**

Remarks: Based on available data, the classification criteria are not met.

### STOT - repeated exposure

**Product:**

Remarks: Based on available data, the classification criteria are not met.

### Aspiration toxicity

**Product:**

Not an aspiration hazard.

### Further information

**Product:**

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

## 12. ECOLOGICAL INFORMATION

# SAFETY DATA SHEET

## BC AE-9A

Version 1.0

Revision Date 07.06.2024

Print Date 15.06.2024

Basis for assessment : Incomplete ecotoxicological data are available for this product. The information given below is based partly on a knowledge of the components and the ecotoxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

### Ecotoxicity

#### Product:

Toxicity to fish (Acute toxicity) : Remarks: LC/EC/IC50 >1 - <=10 mg/l  
Toxic

Toxicity to crustacean (Acute toxicity) : Remarks: LC/EC/IC50 >1 - <=10 mg/l  
Toxic

Toxicity to algae/aquatic plants (Acute toxicity) : Remarks: LC/EC/IC50 >1 - <=10 mg/l  
Toxic

Toxicity to fish (Chronic toxicity) : Remarks: NOEC/NOEL > 0.1 - <=1.0 mg/l

Toxicity to crustacean (Chronic toxicity) : Remarks: NOEC/NOEL > 0.1 - <=1.0 mg/l

Toxicity to microorganisms (Acute toxicity) : Remarks: LC/EC/IC50 > 100 mg/l  
Practically non toxic:  
Based on available data, the classification criteria are not met.

### Persistence and degradability

#### Product:

Biodegradability : Remarks: Readily biodegradable.

### Bioaccumulative potential

#### Product:

Bioaccumulation : Remarks: Bioaccumulation is unlikely to occur due to metabolism and excretion.

Partition coefficient: n-octanol/water : Remarks: Data not available

### Mobility in soil

#### Product:

Mobility : Remarks: Dissolves in water., If the product enters soil, one or more constituents will or may be mobile and may contaminate groundwater.

### Other adverse effects

no data available

# SAFETY DATA SHEET

## BC AE-9A

Version 1.0

Revision Date 07.06.2024

Print Date 15.06.2024

### 13. DISPOSAL CONSIDERATIONS

#### Disposal methods

- Waste from residues : Recover or recycle if possible.  
It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.  
Do not dispose into the environment, in drains or in water courses.  
Waste product should not be allowed to contaminate soil or water.
- Disposal should be in accordance with applicable regional, national, and local laws and regulations.  
Local regulations may be more stringent than regional or national requirements and must be complied with.
- Contaminated packaging : Drain container thoroughly.  
After draining, vent in a safe place away from sparks and fire.  
Residues may cause an explosion hazard.  
Do not puncture, cut, or weld uncleaned drums.  
Send to drum recoverer or metal reclaimer.

### 14. TRANSPORT INFORMATION

#### International Regulations

##### ADR

Not regulated as a dangerous good

##### IATA-DGR

Not regulated as a dangerous good

##### IMDG-Code

Not regulated as a dangerous good

#### Maritime transport in bulk according to IMO instruments

- Pollution category : Y  
Ship type : 2  
Product name : Alcohol (C12-C16) poly (7-19) ethoxylates

#### Special precautions for user

- Remarks : Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

- Additional Information** : Transport in bulk according to Annex II of Marpol and the IBC Code  
This product may be transported under nitrogen blanketing.

# SAFETY DATA SHEET

## BC AE-9A

Version 1.0

Revision Date 07.06.2024

Print Date 15.06.2024

Nitrogen is an odourless and invisible gas. Exposure to nitrogen enriched atmospheres displaces available oxygen which may cause asphyxiation or death. Personnel must observe strict safety precautions when involved with a confined space entry.

### 15. REGULATORY INFORMATION

#### Safety, health and environmental regulations/legislation specific for the substance or mixture

##### Local Regulations

Workplace Safety and Health Act & Workplace Safety and Health (General Provision) Regulations	This product is subject to the requirements in the Act/ Regulations.
Fire Safety Act and Fire Safety (Petroleum & Flammable Materials) Regulations	This product is not subject to the requirements in the Act/Regulations.
Fire Safety Act and Fire Safety (Petroleum & Flammable Materials) Regulations	This product is not subject to the requirements in the Act/Regulations.
Maritime and Port Authority of Singapore (Dangerous Goods, Petroleum and Explosives) Regulations	This product is not subject to the requirements in the Act/Regulations.

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

##### Other international regulations

##### The components of this product are reported in the following inventories:

AIIC	: Listed
DSL	: Listed
IECSC	: Listed
KECI	: Listed
NZIoC	: Listed
PICCS	: Listed
TSCA	: Listed
ENCS	: Listed
TCSI	: Listed

### 16. OTHER INFORMATION

#### Full text of H-Statements

H302	Harmful if swallowed.
H313	May be harmful in contact with skin.
H318	Causes serious eye damage.
H401	Toxic to aquatic life.
H412	Harmful to aquatic life with long lasting effects.

# SAFETY DATA SHEET

## BC AE-9A

Version 1.0

Revision Date 07.06.2024

Print Date 15.06.2024

### Full text of other abbreviations

Acute Tox.	Acute toxicity
Aquatic Acute	Short-term (acute) aquatic hazard
Aquatic Chronic	Long-term (chronic) aquatic hazard
Eye Dam.	Serious eye damage

### Abbreviations and Acronyms

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

### Further information

Training advice	: Provide adequate information, instruction and training for operators.
Other information	: A vertical bar ( ) in the left margin indicates an amendment from the previous version.
Sources of key data used to compile the Safety Data Sheet	: The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID data base, EC 1272 regulation, etc).



# SAFETY DATA SHEET

## BC AE-9A

Version 1.0

Revision Date 07.06.2024

Print Date 15.06.2024

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

SG / EN