

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell GTL Fluid G100

Version	Revision Date:	SDS Number:	Date of last issue: 07.03.2023
1.2	07.06.2023	800010057841	Print Date 14.06.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name	: Shell GTL Fluid G100
Product code	: Q6581
Registration number EU	: 01-0000020119-75
Synonyms	: Distillates (Fischer-Tropsch) C8-26 - branched and linear
CAS-No.	: 848301-67-7

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- stance/Mixture	: Please refer to section 16 and/or the annexes for the registered uses under REACH. Use as a drilling mud solvent.
Uses advised against	: This product must not be used in applications other than the above without first seeking the advice of the supplier.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier	: Shell Chemicals Europe B.V. PO Box 2334 3000 CH Rotterdam Netherlands
Telephone	: +31 (0)10 441 5137 / +31 (0)10 441 5191
Telefax	: +31 (0)20 716 8316/ +31 (0)20 713 9230
Contact for Safety Data Sheet	: sccmsds@shell.com

1.4 Emergency telephone number

+44 (0) 1235 239 670 (This telephone number is available 24 hours per day, 7 days per week)
Poison Center Information: +358 9 471 977 (24h)

1.5 Other information

KT code	: no data available
TOL code	: no data available

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Aspiration hazard, Category 1	H304: May be fatal if swallowed and enters airways.
-------------------------------	---

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell GTL Fluid G100

Version	Revision Date:	SDS Number:	Date of last issue: 07.03.2023
1.2	07.06.2023	800010057841	Print Date 14.06.2023

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements :
PHYSICAL HAZARDS:
Not classified as a physical hazard according to CLP criteria.
HEALTH HAZARDS:
H304 May be fatal if swallowed and enters airways.
ENVIRONMENTAL HAZARDS:
Not classified as environmental hazard according to CLP criteria.

Supplemental Hazard Statements : EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statements : **Prevention:**
P243 Take action to prevent static discharges.
Response:
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P331 Do NOT induce vomiting.
Storage:
P405 Store locked up.
Disposal:
P501 Dispose of contents/ container to an approved waste disposal plant.

2.3 Other hazards

The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

May ignite on surfaces at temperatures above auto-ignition temperature.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell GTL Fluid G100

Version 1.2 Revision Date: 07.06.2023 SDS Number: 800010057841 Date of last issue: 07.03.2023
Print Date 14.06.2023

Vapour in the headspace of tanks and containers may ignite and explode at temperatures exceeding auto-ignition temperature, where vapour concentrations are within the flammability range. This material is a static accumulator.

Even with proper grounding and bonding, this material can still accumulate an electrostatic charge.

If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur.

SECTION 3: Composition/information on ingredients

3.1 Substances

Components

Chemical name	CAS-No. EC-No.	Concentration (% w/w)
Distillates (Fischer-Tropsch), C8-26 - Branched and Linear	848301-67-7 481-740-5	<= 100

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Not expected to be a health hazard when used under normal conditions.
- Protection of first-aiders : When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.
- If inhaled : No treatment necessary under normal conditions of use.
If symptoms persist, obtain medical advice.
- In case of skin contact : Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available.
If persistent irritation occurs, obtain medical attention.
- In case of eye contact : Flush eye with copious quantities of water.
Remove contact lenses, if present and easy to do. Continue rinsing.
If persistent irritation occurs, obtain medical attention.
- If swallowed : Call emergency number for your location / facility.
If swallowed, do not induce vomiting: transport to nearest medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.
If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility:

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell GTL Fluid G100

Version	Revision Date:	SDS Number:	Date of last issue: 07.03.2023
1.2	07.06.2023	800010057841	Print Date 14.06.2023

ty: fever greater than 101° F (38.3°C), shortness of breath, chest congestion or continued coughing or wheezing.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Not considered to be an inhalation hazard under normal conditions of use.
Possible respiratory irritation signs and symptoms may include a temporary burning sensation of the nose and throat, coughing, and/or difficulty breathing.

No specific hazards under normal use conditions.
Skin irritation signs and symptoms may include a burning sensation, redness, or swelling.

No specific hazards under normal use conditions.
Eye irritation signs and symptoms may include a burning sensation, redness, swelling, and/or blurred vision.

If material enters lungs, signs and symptoms may include coughing, choking, wheezing, difficulty in breathing, chest congestion, shortness of breath, and/or fever.
If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (38.3°C), shortness of breath, chest congestion or continued coughing or wheezing.

Defatting dermatitis signs and symptoms may include a burning sensation and/or a dried/cracked appearance.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.
Call a doctor or poison control center for guidance.
Potential for chemical pneumonitis.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

Unsuitable extinguishing media : Do not use water in a jet.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Clear fire area of all non-emergency personnel.
Hazardous combustion products may include:
A complex mixture of airborne solid and liquid particulates and gases (smoke).
Carbon monoxide.
Unidentified organic and inorganic compounds.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell GTL Fluid G100

Version	Revision Date:	SDS Number:	Date of last issue: 07.03.2023
1.2	07.06.2023	800010057841	Print Date 14.06.2023

Flammable vapours may be present even at temperatures below the flash point.
The vapour is heavier than air, spreads along the ground and distant ignition is possible.
Will float and can be reignited on surface water.

5.3 Advice for firefighters

- Special protective equipment for firefighters : Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).
- Specific extinguishing methods : Standard procedure for chemical fires.
- Further information : Keep adjacent containers cool by spraying with water.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- Personal precautions : Observe all relevant local and international regulations. Notify authorities if any exposure to the general public or the environment occurs or is likely to occur. Local authorities should be advised if significant spillages cannot be contained.
- 6.1.1 For non emergency personnel:
Avoid contact with skin, eyes and clothing.
Isolate hazard area and deny entry to unnecessary or unprotected personnel.
Do not breathe fumes, vapour.
Do not operate electrical equipment.
- 6.1.2 For emergency responders:
Avoid contact with skin, eyes and clothing.
Isolate hazard area and deny entry to unnecessary or unprotected personnel.
Do not breathe fumes, vapour.
Do not operate electrical equipment.

6.2 Environmental precautions

- Environmental precautions : Shut off leaks, if possible without personal risks. Remove all possible sources of ignition in the surrounding area. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. Attempt to disperse the vapour or to direct its flow to a safe location for example by using fog sprays. Take precautionary measures against static discharge. Ensure electrical continuity by bond-

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell GTL Fluid G100

Version	Revision Date:	SDS Number:	Date of last issue: 07.03.2023
1.2	07.06.2023	800010057841	Print Date 14.06.2023

ing and grounding (earthing) all equipment.
Monitor area with combustible gas indicator.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : For small liquid spills (< 1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.
For large liquid spills (> 1 drum), transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.

Ventilate contaminated area thoroughly.
If contamination of site occurs remediation may require specialist advice.

6.4 Reference to other sections

For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet.,
For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures : Avoid breathing of or direct contact with material. Only use in well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet.
Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.
Ensure that all local regulations regarding handling and storage facilities are followed.

Advice on safe handling : Avoid inhaling vapour and/or mists.
Avoid contact with skin, eyes and clothing.
Extinguish any naked flames. Do not smoke. Remove ignition sources. Avoid sparks.
Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols.
Bulk storage tanks should be diked (bunded).
When using do not eat or drink.

The vapour is heavier than air, spreads along the ground and distant ignition is possible.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell GTL Fluid G100

Version	Revision Date:	SDS Number:	Date of last issue: 07.03.2023
1.2	07.06.2023	800010057841	Print Date 14.06.2023

Product Transfer : Even with proper grounding and bonding, this material can still accumulate an electrostatic charge. If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur. Be aware of handling operations that may give rise to additional hazards that result from the accumulation of static charges. These include but are not limited to pumping (especially turbulent flow), mixing, filtering, splash filling, cleaning and filling of tanks and containers, sampling, switch loading, gauging, vacuum truck operations, and mechanical movements. These activities may lead to static discharge e.g. spark formation. Restrict line velocity during pumping in order to avoid generation of electrostatic discharge (≤ 1 m/s until fill pipe submerged to twice its diameter, then ≤ 7 m/s). Avoid splash filling. Do NOT use compressed air for filling, discharging, or handling operations.

Refer to guidance under Handling section.

Hygiene measures : Wash hands before eating, drinking, smoking and using the toilet. Launder contaminated clothing before re-use. Do not ingest. If swallowed, then seek immediate medical assistance.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Refer to section 15 for any additional specific legislation covering the packaging and storage of this product.

Further information on storage stability : Storage Temperature:
Ambient.

Bulk storage tanks should be diked (bunded).
Locate tanks away from heat and other sources of ignition.
Cleaning, inspection and maintenance of storage tanks is a specialist operation, which requires the implementation of strict procedures and precautions.
Must be stored in a diked (bunded) well-ventilated area, away from sunlight, ignition sources and other sources of heat.
Keep away from aerosols, flammables, oxidizing agents, corrosives and from other flammable products which are not harmful or toxic to man or to the environment.
Electrostatic charges will be generated during pumping.
Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment to reduce the risk.
The vapours in the head space of the storage vessel may lie in the flammable/explosive range and hence may be flammable.

Packaging material : Suitable material: For containers, or container linings use mild steel, stainless steel., For container paints, use epoxy paint, zinc silicate paint.
Unsuitable material: Avoid prolonged contact with natural, butyl or nitrile rubbers.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell GTL Fluid G100

Version 1.2 Revision Date: 07.06.2023 SDS Number: 800010057841 Date of last issue: 07.03.2023
Print Date 14.06.2023

Container Advice : Do not cut, drill, grind, weld or perform similar operations on or near containers.

7.3 Specific end use(s)

Specific use(s) : Please refer to section 16 and/or the annexes for the registered uses under REACH.

See additional references that provide safe handling practices for liquids that are determined to be static accumulators: American Petroleum Institute 2003 (Protection Against Ignitions Arising out of Static, Lightning and Stray Currents) or National Fire Protection Agency 77 (Recommended Practices on Static Electricity).
IEC/TS 60079-32-1: Electrostatic hazards, guidance

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

In the absence of a national exposure limit, the American Conference of Governmental Industrial Hygienists (ACGIH) recommends the following values for Diesel Fuel: TWA - 100 mg/m³ Critical effects based on Skin and Irritation.

Biological occupational exposure limits

No biological limit allocated.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Distillates (Fischer-Tropsch), C8-26 - Branched and Linear		
Remarks:	Substance is a hydrocarbon with a complex, unknown or variable composition. Conventional methods of deriving PNECs are not appropriate and it is not possible to identify a single representative PNEC for such substances.	

8.2 Exposure controls

Engineering measures

Use sealed systems as far as possible.
Adequate explosion-proof ventilation to control airborne concentrations below the exposure guidelines/limits.
Local exhaust ventilation is recommended.
Firewater monitors and deluge systems are recommended.
Eye washes and showers for emergency use.
Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.
The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

General Information:

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell GTL Fluid G100

Version	Revision Date:	SDS Number:	Date of last issue: 07.03.2023
1.2	07.06.2023	800010057841	Print Date 14.06.2023

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

Personal protective equipment

The provided information is made in consideration of the PPE directive (Council Directive 89/686/EEC) and the CEN European Committee for Standardisation (CEN) standards.

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Eye protection : If material is handled such that it could be splashed into eyes, protective eyewear is recommended.
Approved to EU Standard EN166.

Hand protection

Remarks : Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. Longer term protection: Nitrile rubber gloves. Incidental contact/Splash protection: PVC, neoprene or nitrile rubber gloves For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

Skin and body protection : Skin protection is not required under normal conditions of use.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell GTL Fluid G100

Version	Revision Date:	SDS Number:	Date of last issue: 07.03.2023
1.2	07.06.2023	800010057841	Print Date 14.06.2023

For prolonged or repeated exposures use impervious clothing over parts of the body subject to exposure.

If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to relevant Standard, and provide employee skin care programmes.

Protective clothing approved to EU Standard EN14605.

Wear antistatic and flame-retardant clothing, if a local risk assessment deems it so.

Respiratory protection : If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are unsuitable (e.g. airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. If air-filtering respirators are suitable for conditions of use: Select a filter suitable for organic gases and vapours [Type A boiling point > 65°C (149°F)] meeting EN14387.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	: Liquid.
Colour	: colourless
Odour	: Paraffinic
Odour Threshold	: no data available
Melting point/freezing point	: no data available
Boiling point/boiling range	: 200 - 350 °C

Flammability

Lower explosion limit and upper explosion limit / flammability limit

Upper explosion limit / upper flammability limit	: Data not available
--	----------------------

Lower explosion limit / Lower flammability limit	: Data not available
--	----------------------

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell GTL Fluid G100

Version	Revision Date:	SDS Number:	Date of last issue: 07.03.2023
1.2	07.06.2023	800010057841	Print Date 14.06.2023

Flash point	:	> 100 °C
Auto-ignition temperature	:	Data not available
Decomposition temperature	:	Data not available
Decomposition temperature	:	Data not available
pH	:	Not applicable
Viscosity	:	
Viscosity, kinematic	:	< 7 mm ² /s (40 °C) Method: ASTM D445
Solubility(ies)	:	
Water solubility	:	insoluble
Partition coefficient: n-octanol/water	:	Data not available
Vapour pressure	:	Data not available (50 °C)
Relative density	:	Data not available
Density	:	0,785 g/cm ³ (15 °C)
Relative vapour density	:	Data not available

9.2 Other information

Explosives	:	no data available
Oxidizing properties	:	Data not available
Evaporation rate	:	Data not available
Conductivity	:	Low conductivity: < 100 pS/m

The conductivity of this material makes it a static accumulator., A liquid is typically considered nonconductive if its conductivity is below 100 pS/m and is considered semi-conductive if its conductivity is below 10,000 pS/m., A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell GTL Fluid G100

Version	Revision Date:	SDS Number:	Date of last issue: 07.03.2023
1.2	07.06.2023	800010057841	Print Date 14.06.2023

SECTION 10: Stability and reactivity

10.1 Reactivity

The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.

10.2 Chemical stability

No hazardous reaction is expected when handled and stored according to provisions
Stable under normal conditions of use.

10.3 Possibility of hazardous reactions

Hazardous reactions : Reacts with strong oxidising agents.

10.4 Conditions to avoid

Conditions to avoid : Avoid heat, sparks, open flames and other ignition sources.

In certain circumstances product can ignite due to static electricity.

10.5 Incompatible materials

Materials to avoid : Strong oxidising agents.

10.6 Hazardous decomposition products

Hazardous decomposition products are not expected to form during normal storage.
Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids and gases including carbon monoxide, carbon dioxide, sulphur oxides and unidentified organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure : Inhalation is the primary route of exposure although absorption may occur through skin contact or following accidental ingestion.

Acute toxicity

Product:

Acute oral toxicity : LD50 (Rat): > 5000 mg/kg
Remarks: Low toxicity

Acute inhalation toxicity : LC50: > 5 mg/l
Exposure time: 4 h
Remarks: Low toxicity by inhalation.

Acute dermal toxicity : LD50 (Rat): > 2000 mg/kg

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell GTL Fluid G100

Version	Revision Date:	SDS Number:	Date of last issue: 07.03.2023
1.2	07.06.2023	800010057841	Print Date 14.06.2023

Remarks: Low toxicity

Components:

Distillates (Fischer-Tropsch), C8-26 - Branched and Linear:

Acute oral toxicity	:	LD50 (Rat): > 5.000 mg/kg Remarks: Based on available data, the classification criteria are not met.
Acute inhalation toxicity	:	LC50: > 5 mg/l Exposure time: 4 h Remarks: Based on available data, the classification criteria are not met.
Acute dermal toxicity	:	LD50 (Rat): > 2.000 mg/kg Remarks: Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Product:

Remarks	:	Prolonged/repeated contact may cause defatting of the skin which can lead to dermatitis. Not irritating to skin.
---------	---	---

Components:

Distillates (Fischer-Tropsch), C8-26 - Branched and Linear:

Remarks	:	Not irritating to skin. Based on available data, the classification criteria are not met.
---------	---	--

Serious eye damage/eye irritation

Product:

Remarks	:	Not irritating to eye.
---------	---	------------------------

Components:

Distillates (Fischer-Tropsch), C8-26 - Branched and Linear:

Remarks	:	Not irritating to eye. Based on available data, the classification criteria are not met.
---------	---	---

Respiratory or skin sensitisation

Product:

Remarks	:	Not a sensitiser. Based on available data, the classification criteria are not met.
---------	---	--

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell GTL Fluid G100

Version 1.2 Revision Date: 07.06.2023 SDS Number: 800010057841 Date of last issue: 07.03.2023
Print Date 14.06.2023

Components:

Distillates (Fischer-Tropsch), C8-26 - Branched and Linear:

Remarks : Not a sensitiser.
Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Product:

Genotoxicity in vivo : Remarks: Not mutagenic.

Germ cell mutagenicity- Assessment : This product does not meet the criteria for classification in categories 1A/1B.

Components:

Distillates (Fischer-Tropsch), C8-26 - Branched and Linear:

Genotoxicity in vitro : Remarks: Based on available data, the classification criteria are not met.

Genotoxicity in vivo : Remarks: Not mutagenic.
Based on available data, the classification criteria are not met.

Germ cell mutagenicity- Assessment : This product does not meet the criteria for classification in categories 1A/1B.

Carcinogenicity

Product:

Remarks : Not a carcinogen.
Based on available data, the classification criteria are not met.

Carcinogenicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

Components:

Distillates (Fischer-Tropsch), C8-26 - Branched and Linear:

Remarks : Not a carcinogen.
Based on available data, the classification criteria are not met.

Carcinogenicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

Material	GHS/CLP Carcinogenicity Classification
Distillates (Fischer-Tropsch), C8-26 - Branched and Linear	No carcinogenicity classification.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell GTL Fluid G100

Version	Revision Date:	SDS Number:	Date of last issue: 07.03.2023
1.2	07.06.2023	800010057841	Print Date 14.06.2023

Reproductive toxicity

Product:

Effects on fertility	:	Remarks: Does not impair fertility., Not a developmental toxicant., Based on available data, the classification criteria are not met.
Reproductive toxicity - Assessment	:	This product does not meet the criteria for classification in categories 1A/1B.

Components:

Distillates (Fischer-Tropsch), C8-26 - Branched and Linear:

Effects on fertility	:	Remarks: Does not impair fertility., Not a developmental toxicant., Based on available data, the classification criteria are not met.
Reproductive toxicity - Assessment	:	This product does not meet the criteria for classification in categories 1A/1B.

STOT - single exposure

Product:

Remarks	:	High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea.
---------	---	---

Components:

Distillates (Fischer-Tropsch), C8-26 - Branched and Linear:

Remarks	:	High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea. Based on available data, the classification criteria are not met.
---------	---	--

STOT - repeated exposure

Product:

Remarks	:	Based on available data, the classification criteria are not met.
---------	---	---

Components:

Distillates (Fischer-Tropsch), C8-26 - Branched and Linear:

Remarks	:	Based on available data, the classification criteria are not met.
---------	---	---

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell GTL Fluid G100

Version	Revision Date:	SDS Number:	Date of last issue: 07.03.2023
1.2	07.06.2023	800010057841	Print Date 14.06.2023

Aspiration toxicity

Product:

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

Components:

Distillates (Fischer-Tropsch), C8-26 - Branched and Linear:

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Further information

Product:

Remarks : Classifications by other authorities under varying regulatory frameworks may exist.

Remarks : Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

Components:

Distillates (Fischer-Tropsch), C8-26 - Branched and Linear:

Remarks : Classifications by other authorities under varying regulatory frameworks may exist.

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish : LC50 : > 100 mg/l
Remarks: Practically non toxic:

Toxicity to daphnia and other aquatic invertebrates : EC50 : > 100 mg/l
Remarks: Practically non toxic:

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell GTL Fluid G100

Version	Revision Date:	SDS Number:	Date of last issue: 07.03.2023
1.2	07.06.2023	800010057841	Print Date 14.06.2023

Toxicity to algae/aquatic plants	:	EC50 : > 100 mg/l Remarks: Practically non toxic:
Toxicity to fish (Chronic toxicity)	:	Remarks: NOEC/NOEL > 100 mg/l
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	Remarks: NOEC/NOEL > 10 - <=100 mg/l
Toxicity to microorganisms	:	IC50 : > 100 mg/l Remarks: Practically non toxic:

Components:

Distillates (Fischer-Tropsch), C8-26 - Branched and Linear:

Toxicity to fish	:	LL50 : > 1.000 mg/l Remarks: Based on available data, the classification criteria are not met.
Toxicity to daphnia and other aquatic invertebrates	:	LL50 : > 1.000 mg/l Remarks: Based on available data, the classification criteria are not met.
Toxicity to algae/aquatic plants	:	LL50 : > 1.000 mg/l Remarks: Based on available data, the classification criteria are not met.
Toxicity to microorganisms	:	LL50 : > 100 mg/l Remarks: Based on available data, the classification criteria are not met.
Toxicity to fish (Chronic toxicity)	:	NOEC: 100 mg/l Remarks: Based on available data, the classification criteria are not met.
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC: 32 mg/l Remarks: Based on available data, the classification criteria are not met.

12.2 Persistence and degradability

Product:

Biodegradability	:	Remarks: Readily biodegradable.
------------------	---	---------------------------------

Components:

Distillates (Fischer-Tropsch), C8-26 - Branched and Linear:

Biodegradability	:	Biodegradation: 80 % Exposure time: 28 d
------------------	---	---

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell GTL Fluid G100

Version	Revision Date:	SDS Number:	Date of last issue: 07.03.2023
1.2	07.06.2023	800010057841	Print Date 14.06.2023

Method: OECD Test Guideline 301F
Remarks: Readily biodegradable.
Oxidises rapidly by photo-chemical reactions in air.

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: Contains constituents with the potential to bioaccumulate.

Components:

Distillates (Fischer-Tropsch), C8-26 - Branched and Linear:

Bioaccumulation : Remarks: Contains constituents with the potential to bioaccumulate.

12.4 Mobility in soil

Product:

Mobility : Remarks: Floats on water., Partly evaporates from water or soil surfaces, but a significant proportion will remain after one day., Large volumes may penetrate soil and could contaminate groundwater.

Components:

Distillates (Fischer-Tropsch), C8-26 - Branched and Linear:

Mobility : Remarks: Floats on water., Partly evaporates from water or soil surfaces, but a significant proportion will remain after one day., Large volumes may penetrate soil and could contaminate groundwater.

12.5 Results of PBT and vPvB assessment

Product:

Assessment : The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB..

Components:

Distillates (Fischer-Tropsch), C8-26 - Branched and Linear:

Assessment : The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB..

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell GTL Fluid G100

Version	Revision Date:	SDS Number:	Date of last issue: 07.03.2023
1.2	07.06.2023	800010057841	Print Date 14.06.2023

57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : Films formed on water may affect oxygen transfer and damage organisms.

Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

Components:

Distillates (Fischer-Tropsch), C8-26 - Branched and Linear:

Additional ecological information : Films formed on water may affect oxygen transfer and damage organisms.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Recover or recycle if possible.
It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.
Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment.
Do not dispose into the environment, in drains or in water courses.
Do not dispose of tank water bottoms by allowing them to drain into the ground. This will result in soil and groundwater contamination.
Waste arising from a spillage or tank cleaning should be disposed of in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand.

Waste, spills or used product is dangerous waste.

Disposal should be in accordance with applicable regional, national, and local laws and regulations.
Local regulations may be more stringent than regional or national requirements and must be complied with.

MARPOL - see International Convention for the Prevention of Pollution from Ships (MARPOL 73/78) which provides technical aspects at controlling pollutions from ships.

Contaminated packaging : Drain container thoroughly.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell GTL Fluid G100

Version	Revision Date:	SDS Number:	Date of last issue: 07.03.2023
1.2	07.06.2023	800010057841	Print Date 14.06.2023

After draining, vent in a safe place away from sparks and fire.
Residues may cause an explosion hazard. Do not puncture,
cut or weld uncleaned drums.
Send to drum recoverer or metal reclaimer.
Comply with any local recovery or waste disposal regulations.

SECTION 14: Transport information

14.1 UN number or ID number

ADR	:	Not regulated as a dangerous good
RID	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
IATA	:	Not regulated as a dangerous good

14.2 UN proper shipping name

ADR	:	Not regulated as a dangerous good
RID	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
IATA	:	Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADR	:	Not regulated as a dangerous good
RID	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
IATA	:	Not regulated as a dangerous good

14.4 Packing group

ADR	:	Not regulated as a dangerous good
RID	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
IATA	:	Not regulated as a dangerous good

14.5 Environmental hazards

ADR	:	Not regulated as a dangerous good
RID	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good

14.6 Special precautions for user

Remarks	:	Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.
---------	---	--

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell GTL Fluid G100

Version	Revision Date:	SDS Number:	Date of last issue: 07.03.2023
1.2	07.06.2023	800010057841	Print Date 14.06.2023

14.7 Maritime transport in bulk according to IMO instruments

MARPOL Annex 1 rules apply for bulk shipments by sea.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - List of substances subject to authorisation (Annex XIV)	:	Product is not subject to Authorisation under REACH.
REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	:	This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).

Other regulations:

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

The components of this product are reported in the following inventories:

AIIC	:	Listed
KECI	:	Listed
PICCS	:	Listed
TCSI	:	Listed
DSL	:	Listed
TSCA	:	Listed
ENCS	:	Listed
TSCA	:	Listed
NZIoC	:	Listed
IECSC	:	Listed

15.2 Chemical safety assessment

A Chemical Safety Assessment has been carried out for this substance.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell GTL Fluid G100

Version	Revision Date:	SDS Number:	Date of last issue: 07.03.2023
1.2	07.06.2023	800010057841	Print Date 14.06.2023

SECTION 16: Other information

Full text of other abbreviations

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Training advice : Provide adequate information, instruction and training for operators.

Other information : For Industry guidance and tools on REACH please visit the CEFIC website at <http://cefic.org/Industry-support>.
The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB.

A vertical bar (|) in the left margin indicates an amendment from the previous version.

Sources of key data used to : The quoted data are from, but not limited to, one or more

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell GTL Fluid G100

Version 1.2	Revision Date: 07.06.2023	SDS Number: 800010057841	Date of last issue: 07.03.2023 Print Date 14.06.2023
----------------	------------------------------	-----------------------------	---

compile the Safety Data Sheet

sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID date base, EC 1272 regulation, etc).

Classification of the mixture:

Asp. Tox. 1

H304

Classification procedure:

Expert judgement and weight of evidence determination.

Identified Uses according to the Use Descriptor System

Uses - Worker

Title : Manufacture of substance- Industrial

Uses - Worker

Title : Use as an intermediate- Industrial

Uses - Worker

Title : Distribution of substance- Industrial

Uses - Worker

Title : Use as a fuel- Industrial

Uses - Worker

Title : Use as a fuel- Professional

Uses - Worker

Title : Use in Oil and Gas field drilling and production operations- Industrial

Uses - Worker

Title : Use in Oil and Gas field drilling and production operations- Professional

Uses - Worker

Title : Use in Cleaning Agents- Industrial

Uses - Worker

Title : Use in Cleaning Agents- Professional

Identified Uses according to the Use Descriptor System

Uses - Consumer

Title : Use as a fuel
- Consumer

Uses - Consumer

Title : Use in Cleaning Agents
- Consumer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell GTL Fluid G100

Version	Revision Date:	SDS Number:	Date of last issue: 07.03.2023
1.2	07.06.2023	800010057841	Print Date 14.06.2023

to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

FI / EN

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell GTL Fluid G100

Version 1.2 Revision Date: 07.06.2023 SDS Number: 800010057841 Date of last issue: 07.03.2023
Print Date 14.06.2023

Exposure Scenario - Worker

300000010600	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Manufacture of substance- Industrial
Use Descriptor	Sector of Use: SU3, SU8, SU9 Process Categories: PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC15 Environmental Release Categories: ERC1, ERC4, ESVOC SpERC 1.1.v1
Scope of process	Manufacture of the substance or use as a process chemical or extraction agent. Includes recycling/ recovery, material transfers, storage, maintenance and loading (including marine vessel/barge, road/rail car and bulk container), sampling and associated laboratory activities.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
------------------	--

Section 2.1	Control of Worker Exposure
Product Characteristics	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100%., Unless stated otherwise.,
Frequency and Duration of Use	
Covers daily exposures up to 8 hours (unless stated differently).	
Other Operational Conditions affecting Exposure	
Operation is carried out at elevated temperature (> 20°C above ambient temperature). Assumes a good basic standard of occupational hygiene is implemented.	

Contributing Scenarios	Risk Management Measures
General measures (Aspiration)	The H304 hazard statement (May be fatal if swallowed and enters airways) relates to potential for aspiration, a non-quantifiable hazard determined by physico-chemical properties (i.e. viscosity) that can occur during ingestion and also if it is vomited following ingestion. A DNEL cannot be derived. Risks from the physicochemical hazards of substances can be controlled by implementing risk management measures. For substances classified as H304, the following measures need to be implemented to control the aspiration hazard. Do not ingest. If swallowed, then seek immediate medical assistance

Section 2.2	Control of Environmental Exposure
Not applicable.	

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell GTL Fluid G100

Version
1.2

Revision Date:
07.06.2023

SDS Number:
800010057841

Date of last issue: 07.03.2023
Print Date 14.06.2023

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
Not applicable. Risk Management Measures are based on qualitative risk characterisation.	
Section 3.2 -Environment	
Not applicable.	
SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	
Not applicable.	
Section 4.2 -Environment	
Not applicable.	

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell GTL Fluid G100

Version 1.2 Revision Date: 07.06.2023 SDS Number: 800010057841 Date of last issue: 07.03.2023
Print Date 14.06.2023

Exposure Scenario - Worker

300000010634	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Use as an intermediate- Industrial
Use Descriptor	Sector of Use: SU3, SU8, SU9 Process Categories: PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC15 Environmental Release Categories: ERC6a, ESVOC SpERC 6.1a.v1
Scope of process	Use of substance as an intermediate (not related to Strictly Controlled Conditions). Includes recycling/ recovery, material transfers, storage, sampling, associated laboratory activities, maintenance and loading (including marine vessel/barge, road/rail car and bulk container).

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
------------------	--

Section 2.1	Control of Worker Exposure
Product Characteristics	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100%., Unless stated otherwise.,
Frequency and Duration of Use	
Covers daily exposures up to 8 hours (unless stated differently).	
Other Operational Conditions affecting Exposure	
Operation is carried out at elevated temperature (> 20°C above ambient temperature). Assumes a good basic standard of occupational hygiene is implemented.	

Contributing Scenarios	Risk Management Measures
General measures (Aspiration)	The H304 hazard statement (May be fatal if swallowed and enters airways) relates to potential for aspiration, a non-quantifiable hazard determined by physico-chemical properties (i.e. viscosity) that can occur during ingestion and also if it is vomited following ingestion. A DNEL cannot be derived. Risks from the physicochemical hazards of substances can be controlled by implementing risk management measures. For substances classified as H304, the following measures need to be implemented to control the aspiration hazard. Do not ingest. If swallowed, then seek immediate medical assistance

Section 2.2	Control of Environmental Exposure
Not applicable.	

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell GTL Fluid G100

Version
1.2

Revision Date:
07.06.2023

SDS Number:
800010057841

Date of last issue: 07.03.2023
Print Date 14.06.2023

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
Not applicable. Risk Management Measures are based on qualitative risk characterisation.	
Section 3.2 -Environment	
Not applicable.	
SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	
Not applicable.	
Section 4.2 -Environment	
Not applicable.	

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell GTL Fluid G100

Version 1.2 Revision Date: 07.06.2023 SDS Number: 800010057841 Date of last issue: 07.03.2023
Print Date 14.06.2023

Exposure Scenario - Worker

300000010601	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Distribution of substance- Industrial
Use Descriptor	Sector of Use: SU3, SU8, SU9 Process Categories: PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC9, PROC15 Environmental Release Categories: ERC1, ERC2, ERC3, ERC4, ERC5, ERC6a, ERC6b, ERC6c, ERC6d, ERC7, ESVOC SpERC 1.1b.v1
Scope of process	Loading (including marine vessel/barge, rail/road car and IBC loading) and repacking (including drums and small packs) of substance, including its sampling, storage, unloading distribution and associated laboratory activities.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
------------------	--

Section 2.1	Control of Worker Exposure
Product Characteristics	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100%., Unless stated otherwise.,
Frequency and Duration of Use	
Covers daily exposures up to 8 hours (unless stated differently).	
Other Operational Conditions affecting Exposure	
Operation is carried out at elevated temperature (> 20°C above ambient temperature). Assumes a good basic standard of occupational hygiene is implemented.	

Contributing Scenarios	Risk Management Measures
General measures (Aspiration)	The H304 hazard statement (May be fatal if swallowed and enters airways) relates to potential for aspiration, a non-quantifiable hazard determined by physico-chemical properties (i.e. viscosity) that can occur during ingestion and also if it is vomited following ingestion. A DNEL cannot be derived. Risks from the physicochemical hazards of substances can be controlled by implementing risk management measures. For substances classified as H304, the following measures need to be implemented to control the aspiration hazard. Do not ingest. If swallowed, then seek immediate medical assistance

Section 2.2	Control of Environmental Exposure
Not applicable.	

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell GTL Fluid G100

Version
1.2

Revision Date:
07.06.2023

SDS Number:
800010057841

Date of last issue: 07.03.2023
Print Date 14.06.2023

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
Not applicable. Risk Management Measures are based on qualitative risk characterisation.	
Section 3.2 -Environment	
Not applicable.	
SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	
Not applicable.	
Section 4.2 -Environment	
Not applicable.	

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell GTL Fluid G100

Version 1.2 Revision Date: 07.06.2023 SDS Number: 800010057841 Date of last issue: 07.03.2023
Print Date 14.06.2023

Exposure Scenario - Worker

300000010618	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Use as a fuel- Industrial
Use Descriptor	Sector of Use: SU3 Process Categories: PROC1, PROC2, PROC3, PROC8a, PROC8b, PROC16 Environmental Release Categories: ERC7, ESVOC SpERC 7.12a.v1
Scope of process	Covers the use as a fuel (or fuel additive) and includes activities associated with its transfer, use, equipment maintenance and handling of waste.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
------------------	--

Section 2.1	Control of Worker Exposure
Product Characteristics	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100%., Unless stated otherwise.,
Frequency and Duration of Use	
Covers daily exposures up to 8 hours (unless stated differently).	
Other Operational Conditions affecting Exposure	
Operation is carried out at elevated temperature (> 20°C above ambient temperature). Assumes a good basic standard of occupational hygiene is implemented.	

Contributing Scenarios	Risk Management Measures
General measures (Aspiration)	The H304 hazard statement (May be fatal if swallowed and enters airways) relates to potential for aspiration, a non-quantifiable hazard determined by physico-chemical properties (i.e. viscosity) that can occur during ingestion and also if it is vomited following ingestion. A DNEL cannot be derived. Risks from the physicochemical hazards of substances can be controlled by implementing risk management measures. For substances classified as H304, the following measures need to be implemented to control the aspiration hazard. Do not ingest. If swallowed, then seek immediate medical assistance

Section 2.2	Control of Environmental Exposure
Not applicable.	

SECTION 3	EXPOSURE ESTIMATION
------------------	----------------------------

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell GTL Fluid G100

Version
1.2

Revision Date:
07.06.2023

SDS Number:
800010057841

Date of last issue: 07.03.2023
Print Date 14.06.2023

Section 3.1 - Health

Not applicable.

Risk Management Measures are based on qualitative risk characterisation.

Section 3.2 -Environment

Not applicable.

SECTION 4

GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
--

Section 4.1 - Health

Not applicable.

Section 4.2 -Environment

Not applicable.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell GTL Fluid G100

Version 1.2 Revision Date: 07.06.2023 SDS Number: 800010057841 Date of last issue: 07.03.2023
Print Date 14.06.2023

Exposure Scenario - Worker

300000010619	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Use as a fuel- Professional
Use Descriptor	Sector of Use: SU22 Process Categories: PROC1, PROC2, PROC3, PROC8a, PROC8b, PROC16 Environmental Release Categories: ERC9a, ERC9b, ESVOC SpERC 9.12b.v1
Scope of process	Covers the use as a fuel (or fuel additive) and includes activities associated with its transfer, use, equipment maintenance and handling of waste.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
------------------	--

Section 2.1	Control of Worker Exposure
Product Characteristics	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100%., Unless stated otherwise.,
Frequency and Duration of Use	
Covers daily exposures up to 8 hours (unless stated differently).	
Other Operational Conditions affecting Exposure	
Operation is carried out at elevated temperature (> 20°C above ambient temperature). Assumes a good basic standard of occupational hygiene is implemented.	

Contributing Scenarios	Risk Management Measures
General measures (Aspiration)	The H304 hazard statement (May be fatal if swallowed and enters airways) relates to potential for aspiration, a non-quantifiable hazard determined by physico-chemical properties (i.e. viscosity) that can occur during ingestion and also if it is vomited following ingestion. A DNEL cannot be derived. Risks from the physicochemical hazards of substances can be controlled by implementing risk management measures. For substances classified as H304, the following measures need to be implemented to control the aspiration hazard. Do not ingest. If swallowed, then seek immediate medical assistance

Section 2.2	Control of Environmental Exposure
Not applicable.	

SECTION 3	EXPOSURE ESTIMATION
------------------	----------------------------

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell GTL Fluid G100

Version
1.2

Revision Date:
07.06.2023

SDS Number:
800010057841

Date of last issue: 07.03.2023
Print Date 14.06.2023

Section 3.1 - Health

Not applicable. Risk Management Measures are based on qualitative risk characterisation.

Section 3.2 -Environment

Not applicable.

SECTION 4

GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
--

Section 4.1 - Health

Not applicable.

Section 4.2 -Environment

Not applicable.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell GTL Fluid G100

Version 1.2 Revision Date: 07.06.2023 SDS Number: 800010057841 Date of last issue: 07.03.2023
Print Date 14.06.2023

Exposure Scenario - Worker

300000010632	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Use in Oil and Gas field drilling and production operations-Industrial
Use Descriptor	Sector of Use: SU3 Process Categories: PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b Environmental Release Categories: ERC4, ESVOC SpERC 4.5a.v1
Scope of process	Oil field well drilling and production operations (including drilling muds and well cleaning) including material transfers, on-site formulation, well head operations, shaker room activities and related maintenance.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
------------------	--

Section 2.1	Control of Worker Exposure
Product Characteristics	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100%., Unless stated otherwise.,
Frequency and Duration of Use	
Covers daily exposures up to 8 hours (unless stated differently).	
Other Operational Conditions affecting Exposure	
Operation is carried out at elevated temperature (> 20°C above ambient temperature). Assumes a good basic standard of occupational hygiene is implemented.	

Contributing Scenarios	Risk Management Measures
General measures (Aspiration)	The H304 hazard statement (May be fatal if swallowed and enters airways) relates to potential for aspiration, a non-quantifiable hazard determined by physico-chemical properties (i.e. viscosity) that can occur during ingestion and also if it is vomited following ingestion. A DNEL cannot be derived. Risks from the physicochemical hazards of substances can be controlled by implementing risk management measures. For substances classified as H304, the following measures need to be implemented to control the aspiration hazard. Do not ingest. If swallowed, then seek immediate medical assistance

Section 2.2	Control of Environmental Exposure
Not applicable.	

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell GTL Fluid G100

Version
1.2

Revision Date:
07.06.2023

SDS Number:
800010057841

Date of last issue: 07.03.2023
Print Date 14.06.2023

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
Not applicable. Risk Management Measures are based on qualitative risk characterisation.	
Section 3.2 -Environment	
Not applicable.	
SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	
Not applicable.	
Section 4.2 -Environment	
Not applicable.	

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell GTL Fluid G100

Version 1.2 Revision Date: 07.06.2023 SDS Number: 800010057841 Date of last issue: 07.03.2023
Print Date 14.06.2023

Exposure Scenario - Worker

300000010635	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Use in Oil and Gas field drilling and production operations- Professional
Use Descriptor	Sector of Use: SU22 Process Categories: PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b Environmental Release Categories: ERC8d, ESVOC SpERC 8.5b.v1
Scope of process	Oil field well drilling operations (including drilling muds and well cleaning) including material transfers, on-site formulation, well head operations, shaker room activities and related maintenance.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
------------------	--

Section 2.1	Control of Worker Exposure
Product Characteristics	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100%., Unless stated otherwise.,
Frequency and Duration of Use	
Covers daily exposures up to 8 hours (unless stated differently).	
Other Operational Conditions affecting Exposure	
Operation is carried out at elevated temperature (> 20°C above ambient temperature). Assumes a good basic standard of occupational hygiene is implemented.	

Contributing Scenarios	Risk Management Measures
General measures (Aspiration)	The H304 hazard statement (May be fatal if swallowed and enters airways) relates to potential for aspiration, a non-quantifiable hazard determined by physico-chemical properties (i.e. viscosity) that can occur during ingestion and also if it is vomited following ingestion. A DNEL cannot be derived. Risks from the physicochemical hazards of substances can be controlled by implementing risk management measures. For substances classified as H304, the following measures need to be implemented to control the aspiration hazard. Do not ingest. If swallowed, then seek immediate medical assistance

Section 2.2	Control of Environmental Exposure
Not applicable.	

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell GTL Fluid G100

Version 1.2 Revision Date: 07.06.2023 SDS Number: 800010057841 Date of last issue: 07.03.2023
Print Date 14.06.2023

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
Not applicable. Risk Management Measures are based on qualitative risk characterisation.	
Section 3.2 -Environment	
Not applicable.	
SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	
Not applicable.	
Section 4.2 -Environment	
Not applicable.	

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell GTL Fluid G100

Version 1.2 Revision Date: 07.06.2023 SDS Number: 800010057841 Date of last issue: 07.03.2023
Print Date 14.06.2023

Exposure Scenario - Worker

300000010605	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Use in Cleaning Agents- Industrial
Use Descriptor	Sector of Use: SU3 Process Categories: PROC1, PROC2, PROC3, PROC4, PROC7, PROC8a, PROC8b, PROC10, PROC13 Environmental Release Categories: ERC4, ESVOC SpERC 4.4a.v1
Scope of process	Covers the use as a component of cleaning products including transfer from storage, pouring/unloading from drums or containers. Exposures during mixing/diluting in the preparatory phase and cleaning activities (including spraying, brushing, dipping, wiping, automated and by hand), related equipment cleaning and maintenance.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
------------------	--

Section 2.1	Control of Worker Exposure
Product Characteristics	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100%., Unless stated otherwise.,
Frequency and Duration of Use	
Covers daily exposures up to 8 hours (unless stated differently).	
Other Operational Conditions affecting Exposure	
Operation is carried out at elevated temperature (> 20°C above ambient temperature). Assumes a good basic standard of occupational hygiene is implemented.	

Contributing Scenarios	Risk Management Measures
General measures (Aspiration)	The H304 hazard statement (May be fatal if swallowed and enters airways) relates to potential for aspiration, a non-quantifiable hazard determined by physico-chemical properties (i.e. viscosity) that can occur during ingestion and also if it is vomited following ingestion. A DNEL cannot be derived. Risks from the physicochemical hazards of substances can be controlled by implementing risk management measures. For substances classified as H304, the following measures need to be implemented to control the aspiration hazard. Do not ingest. If swallowed, then seek immediate medical assistance

Section 2.2	Control of Environmental Exposure
--------------------	--

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell GTL Fluid G100

Version 1.2 Revision Date: 07.06.2023 SDS Number: 800010057841 Date of last issue: 07.03.2023
Print Date 14.06.2023

Not applicable.	
-----------------	--

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
Not applicable. Risk Management Measures are based on qualitative risk characterisation.	

Section 3.2 -Environment	
Not applicable.	

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	
Not applicable.	

Section 4.2 -Environment	
Not applicable.	

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell GTL Fluid G100

Version 1.2 Revision Date: 07.06.2023 SDS Number: 800010057841 Date of last issue: 07.03.2023
Print Date 14.06.2023

Exposure Scenario - Worker

300000010606	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Use in Cleaning Agents- Professional
Use Descriptor	Sector of Use: SU22 Process Categories: PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC10, PROC11, PROC13, PROC19 Environmental Release Categories: ERC8a, ERC8d, ESVOC SpERC 8.4b.v1
Scope of process	Covers the use as a component of cleaning products including pouring/unloading from drums or containers; and exposures during mixing/diluting in the preparatory phase and cleaning activities (including spraying, brushing, dipping, wiping automated and by hand).

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
------------------	--

Section 2.1	Control of Worker Exposure
Product Characteristics	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100%., Unless stated otherwise.,
Frequency and Duration of Use	
Covers daily exposures up to 8 hours (unless stated differently).	
Other Operational Conditions affecting Exposure	
Operation is carried out at elevated temperature (> 20°C above ambient temperature). Assumes a good basic standard of occupational hygiene is implemented.	

Contributing Scenarios	Risk Management Measures
General measures (Aspiration)	The H304 hazard statement (May be fatal if swallowed and enters airways) relates to potential for aspiration, a non-quantifiable hazard determined by physico-chemical properties (i.e. viscosity) that can occur during ingestion and also if it is vomited following ingestion. A DNEL cannot be derived. Risks from the physicochemical hazards of substances can be controlled by implementing risk management measures. For substances classified as H304, the following measures need to be implemented to control the aspiration hazard. Do not ingest. If swallowed, then seek immediate medical assistance

Section 2.2	Control of Environmental Exposure
Not applicable.	

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell GTL Fluid G100

Version
1.2

Revision Date:
07.06.2023

SDS Number:
800010057841

Date of last issue: 07.03.2023
Print Date 14.06.2023

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
Not applicable. Risk Management Measures are based on qualitative risk characterisation.	
Section 3.2 -Environment	
Not applicable.	
SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	
Not applicable.	
Section 4.2 -Environment	
Not applicable.	

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell GTL Fluid G100

Version 1.2 Revision Date: 07.06.2023 SDS Number: 800010057841 Date of last issue: 07.03.2023
Print Date 14.06.2023

Exposure Scenario - Consumer

300000010620	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Use as a fuel - Consumer
Use Descriptor	Sector of Use: SU21 Product Categories: PC13 Environmental Release Categories: ERC9a, ERC9b, ESVOC SpERC 9.12c.v1
Scope of process	Covers consumer uses in liquid fuels.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
------------------	--

Section 2.1	Control of Consumer Exposure
Product Characteristics	

Product Categories	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
General measures (Aspiration)	The H304 hazard statement (May be fatal if swallowed and enters airways) relates to potential for aspiration, a non-quantifiable hazard determined by physico-chemical properties (i.e. viscosity) that can occur during ingestion and also if it is vomited following ingestion. A DNEL cannot be derived. Risks from the physicochemical hazards of substances can be controlled by implementing risk management measures. For substances classified as H304, the following measures need to be implemented to control the aspiration hazard. Do not ingest. If swallowed, then seek immediate medical assistance

Section 2.2	Control of Environmental Exposure
Not applicable.	

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
Not applicable. Risk Management Measures are based on qualitative risk characterisation.	

Section 3.2 -Environment	
Not applicable.	

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	
Not applicable.	

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell GTL Fluid G100

Version	Revision Date:	SDS Number:	Date of last issue: 07.03.2023
1.2	07.06.2023	800010057841	Print Date 14.06.2023

--

Section 4.2 -Environment

Not applicable.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell GTL Fluid G100

Version 1.2 Revision Date: 07.06.2023 SDS Number: 800010057841 Date of last issue: 07.03.2023
Print Date 14.06.2023

Exposure Scenario - Consumer

300000010608	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Use in Cleaning Agents - Consumer
Use Descriptor	Sector of Use: SU21 Product Categories: PC3, PC4, PC8 (excipient only), PC9a, PC9b, PC9c, PC24, PC35, PC38 Environmental Release Categories: ERC8a, ERC8d, ESVOC SpERC 8.4c.v1
Scope of process	Covers general exposures to consumers arising from the use of household products sold as washing and cleaning products, aerosols, coatings, de-icers, lubricants and air care products.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
------------------	--

Section 2.1	Control of Consumer Exposure
Product Characteristics	

Product Categories	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
General measures (Aspiration)	The H304 hazard statement (May be fatal if swallowed and enters airways) relates to potential for aspiration, a non-quantifiable hazard determined by physico-chemical properties (i.e. viscosity) that can occur during ingestion and also if it is vomited following ingestion. A DNEL cannot be derived. Risks from the physicochemical hazards of substances can be controlled by implementing risk management measures. For substances classified as H304, the following measures need to be implemented to control the aspiration hazard. Do not ingest. If swallowed, then seek immediate medical assistance

Section 2.2	Control of Environmental Exposure
Not applicable.	

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
Not applicable. Risk Management Measures are based on qualitative risk characterisation.	

Section 3.2 -Environment	
Not applicable.	

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell GTL Fluid G100

Version
1.2

Revision Date:
07.06.2023

SDS Number:
800010057841

Date of last issue: 07.03.2023
Print Date 14.06.2023

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	
Not applicable.	
Section 4.2 -Environment	
Not applicable.	