Mexican official standard NOM-018-STPS-2015

## Methyl DIPROXITOL

Version Revision Date: SDS Number: Print Date: 11/08/2023

2.0 11/01/2023 800001004876 Date of last issue: 06.07.2018

Date of first issue: 18.04.2014

# SECTION 1. IDENTIFICATION OF THE HAZARDOUS PRODUCT OR MIXTURE AND THE SUPPLIER OR MANUFACTURER

Product name : Methyl DIPROXITOL

Product code : U5139

CAS-No. : 34590-94-8

Other means of identification : 2-(2-methoxymethylethoxy)propanol, DPGME, DPM, Methoxy

dipropanol

## Manufacturer or supplier's details

Company : Shell Chemical LP

PO Box 576

**HOUSTON TX 77001** 

USA

SDS Request : +52 (55) 3223 9057

Customer Service : +52 (55) 5089 5792, +52 (55) 5089 5790

**Emergency telephone number** 

Chemtrec Domestic (24 hr) : SETIQ ANIQ 800 002 1400 (Rep. Mexicana), +52 (55) 5559

1588 (local e internacional)

Chemtrec International (24

hr)

: CHEMTREC +1 (703) 527-3887 (Internacional)

## Recommended use of the chemical and restrictions on use

Recommended use : Speciality solvent.

Restrictions on use : This product must not be used in applications other than the

above without first seeking the advice of the supplier.

Other information : DIPROXITOL is a trademark owned by Shell Trademark Man-

agement B.V. and Shell Brands Inc. and used by affiliates of

Shell plc.

### **SECTION 2. HAZARDS IDENTIFICATION**

**GHS Classification** 

Flammable liquids : Category 4

**GHS label elements** 

Hazard pictograms : No Hazard Symbol required

Mexican official standard NOM-018-STPS-2015

## Methyl DIPROXITOL

Version Revision Date: SDS Number: Print Date: 11/08/2023

2.0 11/01/2023 800001004876 Date of last issue: 06.07.2018
Date of first issue: 18.04.2014

Date of 1113t 135de. 10.04.2014

Signal word : Warning

Hazard statements : PHYSICAL HAZARDS:

H227 Combustible liquid. HEALTH HAZARDS:

Not classified as a health hazard under GHS criteria.

**ENVIRONMENTAL HAZARDS:** 

Not classified as an environmental hazard under GHS criteria.

Precautionary statements

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames

and other ignition sources. No smoking.

P280 Wear protective gloves/ protective clothing/ eye protection/

face protection.

Response:

P370 + P378 In case of fire: Use appropriate media to extin-

guish.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

Disposal:

P501 Dispose of contents and container to appropriate waste site or reclaimer in accordance with local and national regula-

tions.

### Other hazards which do not result in classification

Vapours are heavier than air. Vapours may travel across the ground and reach remote ignition sources causing a flashback fire danger.

Even with proper grounding and bonding, this material can still accumulate an electrostatic charge.

If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur.

### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Substance

#### **Hazardous components**

Chemical name	Synonyms	CAS-No.	Concentration (% w/w)
Dipropylene glycol methyl ether	(2- methoxymeth- yleth- oxy)propanol (Mixture of isomers)	34590-94-8	<= 100
2-methoxypropanol	2- methoxypropa- nol	1589-47-5	< 0.1

Mexican official standard NOM-018-STPS-2015

## **Methyl DIPROXITOL**

Version Revision Date: SDS Number: Print Date: 11/08/2023

2.0 11/01/2023 800001004876 Date of last issue: 06.07.2018

Date of first issue: 18.04.2014

#### **SECTION 4. FIRST-AID MEASURES**

General advice : Not expected to be a health hazard when used under normal

conditions.

If inhaled : No treatment necessary under normal conditions of use.

If symptoms persist, obtain medical advice.

In case of skin contact : Remove contaminated clothing. Flush exposed area with wa-

ter and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention.

In case of eye contact : Flush eye with copious quantities of water.

Remove contact lenses, if present and easy to do. Continue

rinsing.

If persistent irritation occurs, obtain medical attention.

If swallowed : In general no treatment is necessary unless large quantities

are swallowed, however, get medical advice.

Most important symptoms and effects, both acute and

delayed

Not considered to be an inhalation hazard under normal con-

ditions of use.

Possible respiratory irritation signs and symptoms may include a temporary burning sensation of the nose and throat, cough-

ing, and/or difficulty breathing.

No specific hazards under normal use conditions.

Skin irritation signs and symptoms may include a burning sen-

sation, redness, or swelling.

Eye irritation signs and symptoms may include a burning sen-

sation, redness, swelling, and/or blurred vision.

Ingestion may result in nausea, vomiting and/or diarrhoea. Breathing of high vapour concentrations may cause central nervous system (CNS) depression resulting in dizziness, lightheadedness, headache, nausea and loss of coordination. Continued inhalation may result in unconsciousness and

death.

Protection of first-aiders : When administering first aid, ensure that you are wearing the

appropriate personal protective equipment according to the

incident, injury and surroundings.

Indication of any immediate medical attention and special

treatment needed

Potential for chemical pneumonitis.

Call a doctor or poison control center for guidance.

Causes central nervous system depression.

#### **SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media : Alcohol-resistant foam, water spray or fog. Dry chemical pow-

der, carbon dioxide, sand or earth may be used for small fires

only.

Unsuitable extinguishing : None

Mexican official standard NOM-018-STPS-2015

## Methyl DIPROXITOL

Version 2.0

Revision Date: 11/01/2023

SDS Number: 800001004876

Print Date: 11/08/2023

Date of last issue: 06.07.2018 Date of first issue: 18.04.2014

media

Specific hazards during fire-

fighting

The vapour is heavier than air, spreads along the ground and

distant ignition is possible.

Carbon monoxide may be evolved if incomplete combustion

occurs.

Specific extinguishing meth-

ods

Standard procedure for chemical fires.

Further information : Clear fire area of all non-emergency personnel.

Keep adjacent containers cool by spraying with water.

Special protective equipment :

for firefighters

Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to

relevant Standards (e.g. Europe: EN469).

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures

Observe the relevant local and international regulations Notify authorities if any exposure to the general public or the

environment occurs or is likely to occur.

Local authorities should be advised if significant spillages

cannot be contained.

The vapour is heavier than air, spreads along the ground and

distant ignition is possible.

Vapour may form an explosive mixture with air. Avoid contact with skin, eyes and clothing.

Isolate hazard area and deny entry to unnecessary or unpro-

tected personnel.

Stay upwind and keep out of low areas.

**Environmental precautions** 

Shut off leaks, if possible without personal risks. Remove all possible sources of ignition in the surrounding area. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. Attempt to disperse the vapour or to direct its flow to a safe location for example by using fog sprays. Take precautionary measures against static discharge. Ensure electrical continuity by bond-

ing and grounding (earthing) all equipment. Ventilate contaminated area thoroughly. Monitor area with combustible gas indicator.

Methods and materials for containment and cleaning up

For large liquid spills (> 1 drum), transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely For small liquid spills (< 1 drum), transfer by mechanical

Mexican official standard NOM-018-STPS-2015

## Methyl DIPROXITOL

Version 2.0

**Revision Date:** 11/01/2023

SDS Number: 800001004876 Print Date: 11/08/2023

Date of last issue: 06.07.2018 Date of first issue: 18.04.2014

means to a labeled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove

contaminated soil and dispose of safely.

Additional advice

: For guidance on selection of personal protective equipment

see Section 8 of this Safety Data Sheet.

For guidance on disposal of spilled material see Section 13 of

this Safety Data Sheet.

#### **SECTION 7. HANDLING AND STORAGE**

Technical measures

Avoid breathing of or direct contact with material. Only use in well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see

Section 8 of this Safety Data Sheet.

Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this

material.

Ensure that all local regulations regarding handling and stor-

age facilities are followed.

Precautions that must be taken to ensure safe handlina

Avoid contact with skin, eyes and clothing.

Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols.

Bulk storage tanks should be diked (bunded).

Extinguish any naked flames. Do not smoke. Remove ignition

sources. Avoid sparks.

Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment to

reduce the risk.

The vapours in the head space of the storage vessel may lie in the flammable/explosive range and hence may be flamma-

Properly dispose of any contaminated rags or cleaning mate-

rials in order to prevent fires.

Do NOT use compressed air for filling, discharging, or han-

dling operations.

Avoidance of contact Strong oxidising agents.

**Product Transfer** : Refer to guidance under Handling section.

Conditions for safe storage, including any incompatibility The vapour is heavier than air. Beware of accumulation in pits

and confined spaces.

Refer to section 15 for any additional specific legislation cov-

ering the packaging and storage of this product.

Mexican official standard NOM-018-STPS-2015

## Methyl DIPROXITOL

Version Revision Date: SDS Number: Print Date: 11/08/2023

2.0 11/01/2023 800001004876 Date of last issue: 06.07.2018

Date of first issue: 18.04.2014

Packaging material : Suitable material: For containers, or container linings use mild

steel, stainless steel.

Unsuitable material: Natural, butyl, neoprene or nitrile rubbers.

Container Advice : Containers, even those that have been emptied, can contain

explosive vapours. Do not cut, drill, grind, weld or perform

similar operations on or near containers.

Specific use(s) : Not applicable

Ensure that all local regulations regarding handling and stor-

age facilities are followed.

See additional references that provide safe handling practices: American Petroleum Institute 2003 (Protection Against Ignitions Arising out of Static, Lightning and Stray Currents) or National Fire Protection Agency 77 (Recommended Practices

on Static Electricity).

IEC/TS 60079-32-1: Electrostatic hazards, guidance

#### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Dipropylene glycol methyl ether	34590-94-8	VLE-PPT	100 ppm	NOM-010- STPS-2014
Dipropylene glycol methyl ether		VLE-CT	150 ppm	NOM-010- STPS-2014
Dipropylene glycol methyl ether		TWA	50 ppm	ACGIH

### **Biological occupational exposure limits**

No biological limit allocated.

#### **Monitoring Methods**

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany

Mexican official standard NOM-018-STPS-2015

## Methyl DIPROXITOL

Version 2.0

Revision Date: 11/01/2023

SDS Number: 800001004876

Print Date: 11/08/2023

Date of last issue: 06.07.2018 Date of first issue: 18.04.2014

http://www.dguv.de/inhalt/index.jsp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

#### **Engineering measures**

Use sealed systems as far as possible.

Adequate explosion-proof ventilation to control airborne concentrations below the exposure guidelines/limits.

Local exhaust ventilation is recommended.

Firewater monitors and deluge systems are recommended.

Eye washes and showers for emergency use.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated. The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances.

Appropriate measures include:

#### General Information:

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance

Retain drain downs in sealed storage pending disposal or subsequent recycle.

#### Personal protective equipment

Respiratory protection

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are unsuitable (e.g. airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus.

Where air-filtering respirators are suitable, select an appropriate combination of mask and filter.

If air-filtering respirators are suitable for conditions of use: Select a filter suitable for organic gases and vapours [Type A boiling point >65°C (149°F)].

Hand protection

Mexican official standard NOM-018-STPS-2015

## **Methyl DIPROXITOL**

Version Revision Date: SDS Number: Print Date: 11/08/2023

2.0 11/01/2023 800001004876 Date of last issue: 06.07.2018

Date of first issue: 18.04.2014

Remarks

Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. Longer term protection: Nitrile rubber gloves. Incidental contact/Splash protection: PVC, neoprene or nitrile rubber gloves For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

Eye protection : If material is handled such that it could be splashed into eyes,

protective eyewear is recommended.

Skin and body protection : Skin protection is not required under normal conditions of

use.

For prolonged or repeated exposures use impervious clothing

over parts of the body subject to exposure.

If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to relevant Stand-

ard, and provide employee skin care programmes.

Wear antistatic and flame-retardant clothing, if a local risk

assessment deems it so.

Protective measures : Personal protective equipment (PPE) should meet recom-

mended national standards. Check with PPE suppliers.

Thermal hazards : Not applicable

#### **Environmental exposure controls**

General advice : Local guidelines on emission limits for volatile substances

must be observed for the discharge of exhaust air containing

vapour.

Minimise release to the environment. An environmental assessment must be made to ensure compliance with local envi-

ronmental legislation.

Information on accidental release measures are to be found in

section 6.

Mexican official standard NOM-018-STPS-2015

## Methyl DIPROXITOL

Version Revision Date: SDS Number: Print Date: 11/08/2023

2.0 11/01/2023 800001004876 Date of last issue: 06.07.2018

Date of first issue: 18.04.2014

#### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

**Appearance** liquid

Colour clear

Odour Ethereal

Odour Threshold Data not available

Not applicable рΗ

-83 °C / -117 °F Melting / freezing point

: 184 - 190 °C / 363 - 374 °F Boiling point/boiling range

Flash point : 75 °C / 167 °F

Method: ASTM D-93 / PMCC

0.01 Evaporation rate

Method: ASTM D 3539, nBuAc=1

Flammability

Flammability (solid, gas) Data not available

Lower explosion limit and upper explosion limit / flammability limit

Upper explosion limit / up- : 14 %(V)

per flammability limit

Lower explosion limit / Lower flammability limit : 1.1 %(V)

Vapour pressure 37.1 Pa (25 °C / 77 °F)

Relative vapour density Data not available

: 0.95 - 0.96 (20 °C / 68 °F) Relative density

Method: ASTM D4052

952 - 956 kg/m3 (20 °C / 68 °F) Density

Method: ASTM D4052

Solubility(ies)

Water solubility completely soluble (25 °C / 77 °F

Partition coefficient: n-

octanol/water

log Pow: < 0.01

Auto-ignition temperature : 205 °C / 401 °F

Mexican official standard NOM-018-STPS-2015

## Methyl DIPROXITOL

Version Revision Date: SDS Number: Print Date: 11/08/2023

2.0 11/01/2023 800001004876 Date of last issue: 06.07.2018

Date of first issue: 18.04.2014

Decomposition temperature : Data not available

Viscosity

Viscosity, dynamic : Data not available

Viscosity, kinematic : 4.55 mm2/s (20 °C / 68 °F)

Method: ASTM D445

Explosive properties : Not applicable

Oxidizing properties : Data not available

Surface tension :  $68.7 \text{ mN/m}, 20 ^{\circ}\text{C} / 68 ^{\circ}\text{F}$ 

Conductivity: > 10,000 pS/m

A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid, This material is not expected to be

a static accumulator.

Molecular weight : 148.2 g/mol

Particle size : Data not available

## **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : The product does not pose any further reactivity hazards in

addition to those listed in the following sub-paragraph.

Chemical stability : No hazardous reaction is expected when handled and stored

according to provisions

Possibility of hazardous reac-

tions

Reacts with strong oxidising agents.

Conditions to avoid : Avoid heat, sparks, open flames and other ignition sources.

Prevent vapour accumulation.

In certain circumstances product can ignite due to static elec-

tricity.

Incompatible materials : Strong oxidising agents.

Hazardous decomposition

products

: Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids and gases includ-

ing carbon monoxide, carbon dioxide, sulphur oxides and unidentified organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degra-

dation.

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

Mexican official standard NOM-018-STPS-2015

## **Methyl DIPROXITOL**

Version Revision Date: SDS Number: Print Date: 11/08/2023

2.0 11/01/2023 800001004876 Date of last issue: 06.07.2018

Date of first issue: 18.04.2014

Basis for assessment : Information given is based on product testing.

Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s). Information given is based on product testing. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual com-

ponent(s).

#### Information on likely routes of exposure

Exposure may occur via inhalation, ingestion, skin absorption, skin or eye contact, and accidental ingestion.

#### **Acute toxicity**

**Product:** 

Acute oral toxicity : LD50 (Rat): > 5000 mg/kg

Remarks: Low toxicity

Acute inhalation toxicity : Remarks: Breathing of high vapour concentrations may cause

central nervous system (CNS) depression resulting in dizzi-

ness, light-headedness, headache and nausea.

Low toxicity if inhaled.

Based on available data, the classification criteria are not met.

Acute dermal toxicity : LD50 (Rabbit): > 5000 mg/kg

Remarks: Low toxicity

#### Components:

Dipropylene glycol methyl ether:

Acute oral toxicity : LD50 (Rat): > 5000 mg/kg

Remarks: Low toxicity

Acute inhalation toxicity : Remarks: Breathing of high vapour concentrations may cause

central nervous system (CNS) depression resulting in dizzi-

ness, light-headedness, headache and nausea.

Low toxicity if inhaled.

Based on available data, the classification criteria are not met.

Acute dermal toxicity : LD50 (Rabbit): > 5000 mg/kg

Remarks: Low toxicity

#### Skin corrosion/irritation

**Product:** 

Remarks: Not irritating to skin.

### Components:

Dipropylene glycol methyl ether:

Remarks: Not irritating to skin.

Mexican official standard NOM-018-STPS-2015

## Methyl DIPROXITOL

Version Revision Date: SDS Number: Print Date: 11/08/2023

2.0 11/01/2023 800001004876 Date of last issue: 06.07.2018 Date of first issue: 18.04.2014

#### Serious eye damage/eye irritation

#### **Product:**

Remarks: Slightly irritating to the eye., Based on available data, the classification criteria are not

met.

#### **Components:**

## Dipropylene glycol methyl ether:

Remarks: Slightly irritating to the eye., Based on available data, the classification criteria are not

met.

#### Respiratory or skin sensitisation

#### **Product:**

Test Type: Skin sensitisation Remarks: Not a sensitiser.

Based on available data, the classification criteria are not met.

### **Components:**

### Dipropylene glycol methyl ether:

Test Type: Skin sensitisation

Remarks: Not a sensitiser. Based on available data, the classification criteria are not met.

## Germ cell mutagenicity

#### **Product:**

Genotoxicity in vivo : Remarks: No evidence of mutagenic activity.

#### **Components:**

### Dipropylene glycol methyl ether:

Genotoxicity in vivo : Remarks: No evidence of mutagenic activity.

### Carcinogenicity

#### **Product:**

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

### **Components:**

## Dipropylene glycol methyl ether:

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or

Mexican official standard NOM-018-STPS-2015

## Methyl DIPROXITOL

Version Revision Date: SDS Number: Print Date: 11/08/2023

2.0 11/01/2023 800001004876 Date of last issue: 06.07.2018

Date of first issue: 18.04.2014

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

### Reproductive toxicity

## **Product:**

Effects on fertility

Remarks: Not a developmental toxicant., Based on available data, the classification criteria are not met., Does not impair fertility.

## **Components:**

## Dipropylene glycol methyl ether:

Effects on fertility :

Remarks: Not a developmental toxicant.

Based on available data, the classification criteria are not met.

Does not impair fertility.

### STOT - single exposure

#### **Product:**

Remarks: Inhalation of vapours or mists may cause irritation to the respiratory system.

## **Components:**

## Dipropylene glycol methyl ether:

Remarks: Inhalation of vapours or mists may cause irritation to the respiratory system.

#### STOT - repeated exposure

#### **Product:**

Remarks: Based on available data, the classification criteria are not met.

### **Components:**

## Dipropylene glycol methyl ether:

Remarks: Based on available data, the classification criteria are not met.

### **Aspiration toxicity**

#### **Product:**

Not an aspiration hazard.

### **Components:**

### Dipropylene glycol methyl ether:

Not an aspiration hazard.

Mexican official standard NOM-018-STPS-2015

## **Methyl DIPROXITOL**

Version Revision Date: SDS Number: Print Date: 11/08/2023

2.0 11/01/2023 800001004876 Date of last issue: 06.07.2018
Date of first issue: 18.04.2014

## Further information

#### **Product:**

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

#### **Components:**

## Dipropylene glycol methyl ether:

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

### **SECTION 12. ECOTOXICOLOGICAL INFORMATION**

Basis for assessment : Information given is based on product testing.

Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s). Information given is based on product testing. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual com-

ponent(s).

**Ecotoxicity** 

**Product:** 

Toxicity to fish (Acute toxici-

tv)

Remarks: Practically non toxic:

LL/EL/IL50 > 100 mg/l

Toxicity to daphnia and other :

aquatic invertebrates (Acute

toxicity)

Remarks: Practically non toxic:

LL/EL/IL50 > 100 mg/l

Toxicity to algae (Acute tox-

icity)

Remarks: Practically non toxic:

LL/EL/IL50 > 100 mg/l

Toxicity to microorganisms

(Acute toxicity)

Remarks: Practically non toxic:

LL/EL/IL50 > 100 mg/l

#### **Components:**

## Dipropylene glycol methyl ether:

Toxicity to fish (Acute toxici-

ty)

Remarks: Practically non toxic:

LL/EL/IL50 > 100 mg/l

Toxicity to daphnia and other : aquatic invertebrates (Acute

toxicity)

Remarks: Practically non toxic:

LL/EL/IL50 > 100 mg/l

Toxicity to algae (Acute tox-

icity)

Remarks: Practically non toxic:

LL/EL/IL50 > 100 mg/l

Toxicity to microorganisms : Remarks: Practically non toxic:

Mexican official standard NOM-018-STPS-2015

## Methyl DIPROXITOL

Version Revision Date: SDS Number: Print Date: 11/08/2023

2.0 11/01/2023 800001004876 Date of last issue: 06.07.2018

Date of first issue: 18.04.2014

(Acute toxicity) LL/EL/IL50 > 100 mg/l

### Persistence and degradability

**Product:** 

Biodegradability : Remarks: Readily biodegradable.

Oxidises rapidly by photo-chemical reactions in air.

**Components:** 

Dipropylene glycol methyl ether:

Biodegradability : Remarks: Readily biodegradable.

Oxidises rapidly by photo-chemical reactions in air.

**Bioaccumulative potential** 

Product:

Bioaccumulation : Remarks: Does not bioaccumulate significantly.

**Components:** 

Dipropylene glycol methyl ether:

Bioaccumulation : Remarks: Does not bioaccumulate significantly.

Mobility in soil

**Product:** 

Mobility : Remarks: If product enters soil, one or more constituents will

be mobile and may contaminate groundwater.

Dissolves in water.

**Components:** 

Dipropylene glycol methyl ether:

Mobility : Remarks: If product enters soil, one or more constituents will

be mobile and may contaminate groundwater.

Dissolves in water.

Other adverse effects

Product:

Results of PBT and vPvB

assessment

The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not consid-

ered to be PBT or vPvB.

Additional ecological infor-

mation

: Data not available

Mexican official standard NOM-018-STPS-2015

## **Methyl DIPROXITOL**

Version Revision Date: SDS Number: Print Date: 11/08/2023

2.0 11/01/2023 800001004876 Date of last issue: 06.07.2018 Date of first issue: 18.04.2014

## **Components:**

## Dipropylene glycol methyl ether:

Results of PBT and vPvB

assessment

: The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not consid-

ered to be PBT or vPvB.

Additional ecological infor-

mation

Data not available

#### SECTION 13. INFORMATION ON PRODUCT DISPOSAL

#### **Disposal methods**

Waste from residues : Recover or recycle if possible.

It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal meth-

ods in compliance with applicable regulations.

Do not dispose into the environment, in drains or in water

courses.

Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment. Waste, spills or used product is dangerous waste.

Disposal should be in accordance with applicable regional,

national, and local laws and regulations.

Local regulations may be more stringent than regional or na-

tional requirements and must be complied with.

MARPOL - see International Convention for the Prevention of Pollution from Ships (MARPOL 73/78) which provides tech-

nical aspects at controlling pollutions from ships.

Contaminated packaging : Drain container thoroughly.

After draining, vent in a safe place away from sparks and fire.

Residues may cause an explosion hazard.
Do not, puncture, cut, or weld uncleaned drums.
Send to drum recoverer or metal reclaimer.

Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand.

### **SECTION 14. TRANSPORT INFORMATION**

### **National Regulations**

no data available

## **International Regulations**

### **IATA-DGR**

Not regulated as a dangerous good

Mexican official standard NOM-018-STPS-2015

## Methyl DIPROXITOL

Version Revision Date: SDS Number: Print Date: 11/08/2023

2.0 11/01/2023 800001004876 Date of last issue: 06.07.2018

Date of first issue: 18.04.2014

#### **IMDG-Code**

Not regulated as a dangerous good

## Maritime transport in bulk according to IMO instruments

Pollution category : Z Ship type : 3

Product name : Poly (2-8) alkylene glycol monoalkyl (C1-C6) ether

### Special precautions for user

Remarks : Special Precautions: Refer to Section 7, Handling & Storage,

for special precautions which a user needs to be aware of or

needs to comply with in connection with transport.

**Additional Information**: This product may be transported under nitrogen blanketing.

Nitrogen is an odourless and invisible gas. Exposure to nitrogen may cause asphyxiation or death. Personnel must observe strict safety precautions when involved with a confined

space entry.

Transport in bulk according to Annex II of Marpol and the IBC

Code

## **SECTION 15. REGULATORY INFORMATION**

#### Other regulations:

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

### The components of this product are reported in the following inventories:

AIIC : Listed

DSL : Listed

IECSC : Listed

ENCS : Listed

KECI : Listed

NZIoC : Listed

PICCS : Listed

TSCA : Listed

TCSI : Listed

Mexican official standard NOM-018-STPS-2015

## Methyl DIPROXITOL

Version **Revision Date:** SDS Number: Print Date: 11/08/2023

2.0 11/01/2023 800001004876 Date of last issue: 06.07.2018

Date of first issue: 18.04.2014

#### **SECTION 16. OTHER INFORMATION**

#### **Further information**

NFPA Rating (Health, Fire, Reac- 0, 2, 0

tivity)

Full text of other abbreviations

**ACGIH** USA. ACGIH Threshold Limit Values (TLV)

Mexico. Norm NOM-010-STPS-2014 on Chemicals Polluting NOM-010-STPS-2014

the Work Environment - Identification, Assessment and Con-

trol - Appendix 1 Occupational Exposure Limits

ACGIH / TWA

8-hour, time-weighted average NOM-010-STPS-2014 / VLE- : Time weighted average limit value

NOM-010-STPS-2014 / VLE- : Short term exposure limit value

CT

The standard abbreviations and acronyms used in this docu-Abbreviations and Acronyms

ment can be looked up in reference literature (e.g. scientific

dictionaries) and/or websites.

ACGIH = American Conference of Governmental Industrial

Hygienists

ADR = European Agreement concerning the International

Carriage of Dangerous Goods by Road

AICS = Australian Inventory of Chemical Substances ASTM = American Society for Testing and Materials

BEL = Biological exposure limits

BTEX = Benzene, Toluene, Ethylbenzene, Xylenes

CAS = Chemical Abstracts Service

CEFIC = European Chemical Industry Council CLP = Classification Packaging and Labelling

COC = Cleveland Open-Cup

DIN = Deutsches Institut fur Normung DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level

DSL = Canada Domestic Substance List

EC = European Commission EC50 = Effective Concentration fifty

ECETOC = European Center on Ecotoxicology and Toxicolo-

gy Of Chemicals

ECHA = European Chemicals Agency

EINECS = The European Inventory of Existing Commercial

**Chemical Substances** 

EL50 = Effective Loading fifty

**ENCS** = Japanese Existing and New Chemical Substances

Inventory

EWC = European Waste Code

GHS = Globally Harmonised System of Classification and

Labelling of Chemicals

IARC = International Agency for Research on Cancer

IATA = International Air Transport Association

Mexican official standard NOM-018-STPS-2015

## Methyl DIPROXITOL

Version 2.0

Revision Date: 11/01/2023

SDS Number: 800001004876

Print Date: 11/08/2023

Date of last issue: 06.07.2018 Date of first issue: 18.04.2014

IC50 = Inhibitory Concentration fifty

IL50 = Inhibitory Level fifty

IMDG = International Maritime Dangerous Goods

INV = Chinese Chemicals Inventory

IP346 = Institute of Petroleum test method N° 346 for the determination of polycyclic aromatics DMSO-extractables

KECI = Korea Existing Chemicals Inventory

LC50 = Lethal Concentration fifty LD50 = Lethal Dose fifty per cent.

LL/EL/IL = Lethal Loading/Effective Loading/Inhibitory loading

LL50 = Lethal Loading fifty

MARPOL = International Convention for the Prevention of

Pollution From Ships

NOEC/NOEL = No Observed Effect Concentration / No Ob-

served Effect Level

OE\_HPV = Occupational Exposure - High Production Volume

PBT = Persistent, Bioaccumulative and Toxic

PICCS = Philippine Inventory of Chemicals and Chemical

Substances

PNEC = Predicted No Effect Concentration

REACH = Registration Evaluation And Authorisation Of

Chemicals

RID = Regulations Relating to International Carriage of Dan-

gerous Goods by Rail

SKIN\_DES = Skin Designation

STEL = Short term exposure limit TRA = Targeted Risk Assessment

TSCA = US Toxic Substances Control Act

TWA = Time-Weighted Average

vPvB = very Persistent and very Bioaccumulative

A vertical bar (|) in the left margin indicates an amendment from the previous version.

Sources of key data used to compile the Safety Data

Sheet

The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU

IUCLID date base, EC 1272 regulation, etc).

Revision Date : 11/01/2023

The information is considered as correct, but not exhaustive, and will be used only as a guide, which is based in the current knowledge of the substance or mixture, and is applicable to proper safety precautions for the product.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

MX / EN