Version 4.0 Revision Date 01/24/2024 Print Date 01/31/2024

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : NEODOL 23-2

Product code : V2597

CAS-No. : 66455-14-9

Synonyms : Alcohols, C12-13, ethoxylated

Manufacturer or supplier's details

Manufacturer/Supplier : Shell CAPSA

Av. Roque Saenz Peña 788

Buenos Aires, 1383

Argentina

Telephone : (+54 11) 4130-2168

Telefax : (+54 11) 4130-2180

Contact for Safety Data Sheet

Emergency telephone number : En Argentina: (+11 15) 4970-7391 / 4970-7390 / 5062-6601 /

4973-7368; Desde el exterior: (+54 911) 4970-7391 / 4970-

7390 / 5062/6601

Recommended use of the chemical and restrictions on use

Recommended use : Use in detergent and intermediate manufacture

Restrictions on use : This product must not be used in applications other than the

above without first seeking the advice of the supplier.

Other information : NEODOL is a trademark owned by Shell Trademark Man-

agement B.V. and Shell Brands Inc. and used by affiliates of

Royal Dutch Shell plc.

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Short-term (acute) aquatic

: Category 1

hazard

Long-term (chronic) aquatic

: Category 2

hazard

GHS label elements

Version 4.0 Revision Date 01/24/2024 Print Date 01/31/2024

Hazard pictograms



Signal word : Warning

Hazard statements PHYSICAL HAZARDS:

Not classified as a physical hazard under GHS criteria.

HEALTH HAZARDS:

Not classified as a health hazard under GHS criteria.

ENVIRONMENTAL HAZARDS: H400 Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : Prevention:

P273 Avoid release to the environment.

Response:

P391 Collect spillage.

Storage:

No precautionary phrases.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

Other hazards which do not result in classification

Repeated exposure may cause skin dryness or cracking.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Substance

Hazardous components

Chemical name	CAS-No.	Classification	Concentration (% w/w)
Alcohols, C12-13, ethox-ylated		Aquatic Acute1; H400 Aquatic Chronic2; H411	<= 100

For explanation of abbreviations see section 16.

SECTION 4. FIRST-AID MEASURES

General advice : Not expected to be a health hazard when used under normal

conditions.

If inhaled : No treatment necessary under normal conditions of use.

If symptoms persist, obtain medical advice.

In case of skin contact : Remove contaminated clothing. Flush exposed area with wa-

ter and follow by washing with soap if available.

If persistent irritation occurs, obtain medical attention.

Version 4.0 Revision Date 01/24/2024 Print Date 01/31/2024

In case of eye contact : Flush eye with copious quantities of water.

Remove contact lenses, if present and easy to do. Continue

rinsing.

If persistent irritation occurs, obtain medical attention.

: In general no treatment is necessary unless large quantities If swallowed

are swallowed, however, get medical advice.

Most important symptoms and effects, both acute and

delayed

Not considered to be an inhalation hazard under normal conditions of use.

Possible respiratory irritation signs and symptoms may include a temporary burning sensation of the nose and throat, cough-

ing, and/or difficulty breathing.

No specific hazards under normal use conditions.

Skin irritation signs and symptoms may include a burning sen-

sation, redness, or swelling.

No specific hazards under normal use conditions.

Eye irritation signs and symptoms may include a burning sen-

sation, redness, swelling, and/or blurred vision. No specific hazards under normal use conditions.

Ingestion may result in nausea, vomiting and/or diarrhoea.

Protection of first-aiders : When administering first aid, ensure that you are wearing the

appropriate personal protective equipment according to the

incident, injury and surroundings.

Call a doctor or poison control center for guidance. Notes to physician

Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

: Alcohol-resistant foam, water spray or fog. Dry chemical pow-Suitable extinguishing media

der, carbon dioxide, sand or earth may be used for small fires

only.

Unsuitable extinguishing

media

: Do not use water in a jet.

Specific hazards during fire-

fighting

: Carbon monoxide may be evolved if incomplete combustion

Will float and can be reignited on surface water.

The vapour is heavier than air, spreads along the ground and

distant ignition is possible.

Specific extinguishing meth-

ods

: Standard procedure for chemical fires.

Clear fire area of all non-emergency personnel. Keep adjacent containers cool by spraying with water.

Special protective equipment

for firefighters

Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if

large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in

a confined space. Select fire fighter's clothing approved to

Version 4.0 Revision Date 01/24/2024 Print Date 01/31/2024

relevant Standards (e.g. Europe: EN469).

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

: Observe all relevant local and international regulations. Notify authorities if any exposure to the general public or the environment occurs or is likely to occur.

Local authorities should be advised if significant spillages

cannot be contained.

Avoid contact with spilled or released material. Immediately remove all contaminated clothing. For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet. For guidance on disposal of spilled material see

Section 13 of this Safety Data Sheet. Stay upwind and keep out of low areas. Be ready for fire or possible exposure.

Environmental precautions

Prevent from spreading or entering into drains, ditches or rivers by using sand, earth, or other appropriate barriers. Use appropriate containment to avoid environmental contamination.

Ventilate contaminated area thoroughly.

Methods and materials for containment and cleaning up For large liquid spills (> 1 drum), transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely For small liquid spills (< 1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.

Additional advice

: For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet.

For guidance on disposal of spilled material see Section 13 of

this Safety Data Sheet.

SECTION 7. HANDLING AND STORAGE

General Precautions : Avoid breathing of or direct contact with material. Only use in

well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see

Section 8 of this Safety Data Sheet.

Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this

Ensure that all local regulations regarding handling and stor-

age facilities are followed.

Version 4.0 Revision Date 01/24/2024 Print Date 01/31/2024

Advice on safe handling : Avoid contact with skin, eyes and clothing.

Do not empty into drains.

Sudden Release of Pressure Hazard

Avoidance of contact : Copper.

Copper alloys.

Strong oxidising agents.

Aluminum

Product Transfer : Keep containers closed when not in use. Do not use com-

pressed air for filling discharge or handling.

Storage

Conditions for safe storage : Refer to section 15 for any additional specific legislation cov-

ering the packaging and storage of this product.

Other data : Bulk storage tanks should be diked (bunded).

Vapours from tanks should not be released to atmosphere. Breathing losses during storage should be controlled by a

suitable vapour treatment system.

Nitrogen blanket recommended for large tanks (capacity 100

m3 or higher).

Insulation (lagging) will minimize heat loss in areas of low

ambient temperature.

Tanks should be fitted with heating coils in areas where ambient conditions can result in handling temperatures below the

freezing point/pour point of the product.

Packaging material : Suitable material: Stainless steel., Epoxy resins, Polyester.

Unsuitable material: Aluminum, Copper., Copper alloys.

Container Advice : Containers, even those that have been emptied, can contain

explosive vapours. Do not cut, drill, grind, weld or perform

similar operations on or near containers.

Specific use(s) : Not applicable

Ensure that all local regulations regarding handling and stor-

age facilities are followed.

SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Components with workplace control parameters

Contains no components with occupational exposure limit values.

Biological occupational exposure limits

No biological limit allocated.

Monitoring Methods

Version 4.0 Revision Date 01/24/2024 Print Date 01/31/2024

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA) , Germany http://www.dguv.de/inhalt/index.jsp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

Engineering measures

: Adequate ventilation to control airborne concentrations. Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated. Eye washes and showers for emergency use.

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

General Information:

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

Personal protective equipment

Respiratory protection

: If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are unsuitable (e.g. airborne concentrations are high, risk of oxygen deficiency, confined

Version 4.0 Revision Date 01/24/2024 Print Date 01/31/2024

> space) use appropriate positive pressure breathing apparatus.

Where air-filtering respirators are suitable, select an appropriate combination of mask and filter.

If air-filtering respirators are suitable for conditions of use: Select a filter suitable for the combination of organic gases and vapours and particles [Type A/Type P boiling point >65°C (149°F)].

Hand protection Remarks

: Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. When prolonged or frequent repeated contact occurs. Nitrile rubber gloves. Incidental contact/Splash protection: PVC or neoprene rubber gloves. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

Eye protection : If material is handled such that it could be splashed into eyes,

protective eyewear is recommended.

Skin and body protection : Skin protection is not ordinarily required beyond standard

work clothes.

It is good practice to wear chemical resistant gloves.

Thermal hazards : Not applicable

Protective measures : Personal protective equipment (PPE) should meet recom-

mended national standards. Check with PPE suppliers.

Hygiene measures : Wash hands before eating, drinking, smoking and using the

Launder contaminated clothing before re-use.

Version 4.0 Revision Date 01/24/2024 Print Date 01/31/2024

Environmental exposure controls

General advice : Local guidelines on emission limits for volatile substances

must be observed for the discharge of exhaust air containing

vapour.

Minimise release to the environment. An environmental assessment must be made to ensure compliance with local envi-

ronmental legislation.

Information on accidental release measures are to be found in

section 6.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Clear or slightly turbid liquid.

Colour : colourless

Odour : mild

Odour Threshold : Data not available

pH : 6,8, 0.5% mass aqueous solution.

pour point : 2 °C / 36 °F

Melting point/freezing point no data available

Boiling point/boiling range : Data not available

Flash point : 152 °C / 306 °F

Method: ASTM D93 (PMCC)

Evaporation rate : Data not available

Flammability

Flammability (solid, gas) : Not applicable

Lower explosion limit and upper explosion limit / flammability limit

Upper explosion limit : Data not available

Lower explosion limit : Data not available

Vapour pressure : 0,1 Pa $(20 \, ^{\circ}\text{C} \, / \, 68 \, ^{\circ}\text{F})$

Relative vapour density : Data not available

Relative density : 0,892

Method: ASTM D4052

Density : 892 kg/m3 (40 °C / 104 °F)Method: ASTM D4052

Solubility(ies)

Water solubility : 5.000 mg/l (22 °C / 72 °F

SAFETY DATA SHEET

NEODOL 23-2

Version 4.0 Revision Date 01/24/2024 Print Date 01/31/2024

)

Partition coefficient: n-

octanol/water

: log Pow: 3

Auto-ignition temperature : Data not available

Decomposition temperature : Data not available

Viscosity

Viscosity, dynamic : 35 mPa.s (20 °C / 68 °F)

Method: ASTM D445

50 mPa.s (Not applicable /)

Method: ASTM D445

Viscosity, kinematic : 15 mm2/s (40 °C / 104 °F)

Method: ASTM D445

Explosive properties : Not applicable

Oxidizing properties : Data not available

Surface tension : Data not available

Conductivity: > 10,000 pS/m

A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid, This material is not expected to be

a static accumulator.

Molecular weight : Data not available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Stable at normal ambient temperature and pressure.

May oxidise in the presence of air.

Chemical stability : The product is chemically stable.

Stable under normal conditions.

Possibility of hazardous reac-

tions

: None known.

Conditions to avoid : Extremes of temperature and direct sunlight.

Incompatible materials : Copper.

Copper alloys.

Strong oxidising agents.

Aluminum

Hazardous decomposition

products

: None expected under normal use conditions.

Version 4.0 Revision Date 01/24/2024 Print Date 01/31/2024

SECTION 11. TOXICOLOGICAL INFORMATION

Basis for assessment : Information given is based on product testing, and/or similar

products, and/or components.

Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual com-

ponent(s).

exposure

Information on likely routes of : Exposure may occur via inhalation, ingestion, skin absorption,

skin or eye contact, and accidental ingestion.

Acute toxicity

Product:

: LD 50 (Rat, male and female): > 5.000 mg/kg Acute oral toxicity

Method: Test(s) equivalent or similar to OECD Test Guideline

Remarks: Based on available data, the classification criteria

are not met. Low toxicity

LD50 >5000 mg/kg

Acute inhalation toxicity : LC 50 (Rat, male and female): > 1,6 mg/l

Exposure time: 4 h Test atmosphere: vapour

Method: Test(s) equivalent or similar to OECD Test Guideline

Remarks: Based on available data, the classification criteria

are not met.

LC50 greater than near-saturated vapour concentration.

Low toxicity

 $LC50 > 1.0 - \le 5.0 \text{ mg/l}$

: LD 50 (Rat, male and female): > 2.000 mg/kg Acute dermal toxicity

Method: OECD Test Guideline 402

Remarks: Based on available data, the classification criteria

are not met.

May be harmful in contact with skin. LD50 >2000 - <=5000 mg/kg

Components:

Alcohols, C12-13, ethoxylated:

Acute oral toxicity LD 50 (Rat, male and female): > 5.000 mg/kg

Method: Test(s) equivalent or similar to OECD Test Guideline

401

Remarks: Based on available data, the classification criteria

are not met. Low toxicity LD50 >5000 mg/kg

Acute inhalation toxicity : LC 50 (Rat, male and female): > 1,6 mg/l

Exposure time: 4 h Test atmosphere: vapour

Version 4.0 Revision Date 01/24/2024 Print Date 01/31/2024

Method: Test(s) equivalent or similar to OECD Test Guideline

403

Remarks: Based on available data, the classification criteria

are not met.

LC50 greater than near-saturated vapour concentration.

Low toxicity

 $LC50 > 1.0 - \le 5.0 \text{ mg/l}$

Acute dermal toxicity : LD 50 (Rat, male and female): > 2.000 mg/kg

Method: OECD Test Guideline 402

Remarks: Based on available data, the classification criteria

are not met.

May be harmful in contact with skin. LD50 >2000 - <=5000 mg/kg

Skin corrosion/irritation

Product:

Species: Rabbit

Method: Test(s) equivalent or similar to OECD Test Guideline 404

Remarks: Slightly irritating. Insufficient to classify.

Components:

Alcohols, C12-13, ethoxylated:

Species: Rabbit

Method: Test(s) equivalent or similar to OECD Test Guideline 404

Remarks: Slightly irritating. Insufficient to classify.

Serious eye damage/eye irritation

Product:

Species: Rabbit

Method: Test(s) equivalent or similar to OECD Test Guideline 405

Remarks: Slightly irritating. Insufficient to classify.

Components:

Alcohols, C12-13, ethoxylated:

Species: Rabbit

Method: Test(s) equivalent or similar to OECD Test Guideline 405

Remarks: Slightly irritating. Insufficient to classify.

Respiratory or skin sensitisation

Product:

Species: Guinea pig

Method: Test(s) equivalent or similar to OECD Test Guideline 406 Remarks: Based on available data, the classification criteria are not met.

Not a sensitiser.

Version 4.0 Revision Date 01/24/2024 Print Date 01/31/2024

Components:

Alcohols, C12-13, ethoxylated:

Species: Guinea pig

Method: Test(s) equivalent or similar to OECD Test Guideline 406 Remarks: Based on available data, the classification criteria are not met.

Not a sensitiser.

Germ cell mutagenicity

Product:

Genotoxicity in vitro : Method: Test(s) equivalent or similar to OECD Test Guideline

473

Remarks: Based on available data, the classification criteria

are not met. Non mutagenic

Genotoxicity in vivo : Species: Mouse

Method: OECD Test Guideline 474

Remarks: Based on available data, the classification criteria

are not met. Non mutagenic

Germ cell mutagenicity -

Assessment

This product does not meet the criteria for classification in

categories 1A/1B.

Components:

Alcohols, C12-13, ethoxylated:

Genotoxicity in vitro : Method: Test(s) equivalent or similar to OECD Test Guideline

473

Remarks: Based on available data, the classification criteria

are not met. Non mutagenic

Genotoxicity in vivo : Species: Mouse

Method: OECD Test Guideline 474

Remarks: Based on available data, the classification criteria

are not met. Non mutagenic

Germ cell mutagenicity -

Assessment

: This product does not meet the criteria for classification in

categories 1A/1B.

Carcinogenicity

Product:

Method: Based on weight of evidence.

Remarks: Based on available data, the classification criteria are not met.

Not a carcinogen.

Carcinogenicity - Assess-

: This product does not meet the criteria for classification in

ment categories 1A/1B.

Version 4.0 Revision Date 01/24/2024 Print Date 01/31/2024

Components:

Alcohols, C12-13, ethoxylated:

Method: Based on weight of evidence.

Remarks: Based on available data, the classification criteria are not met.

Not a carcinogen.

Carcinogenicity - Assess-

ment

: This product does not meet the criteria for classification in

categories 1A/1B.

Material	GHS/CLP Carcinogenicity Classification
Alcohols, C12-13, ethoxylated	No carcinogenicity classification.

Reproductive toxicity

Product:

Effects on fertility : Species: Rat

Sex: male and female Application Route: Dermal

Method: Equivalent or similar to OECD Test Guideline 416 Remarks: Based on available data, the classification criteria

are not met.

Does not impair fertility.

Effects on foetal develop-

ment

Species: Rat, male and female

Application Route: Dermal

Method: Test(s) equivalent or similar to OECD Test Guideline

414

Remarks: Based on available data, the classification criteria

are not met.

Not a developmental toxicant.

Reproductive toxicity - As-

sessment

This product does not meet the criteria for classification in

categories 1A/1B.

STOT - single exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

Components:

Alcohols, C12-13, ethoxylated:

Remarks: Based on available data, the classification criteria are not met.

STOT - repeated exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

Version 4.0 Revision Date 01/24/2024 Print Date 01/31/2024

Components:

Alcohols, C12-13, ethoxylated:

Remarks: Based on available data, the classification criteria are not met.

Repeated dose toxicity

Product:

Species: Rat, male and female Application Route: Oral

Method: Test(s) equivalent or similar to OECD Test Guideline 408

Target Organs: No specific target organs noted

Components:

Alcohols, C12-13, ethoxylated:

Species: Rat, male and female

Application Route: Oral

Method: Test(s) equivalent or similar to OECD Test Guideline 408

Target Organs: No specific target organs noted

Aspiration toxicity

Product:

Based on available data, the classification criteria are not met.

Components:

Alcohols, C12-13, ethoxylated:

Based on available data, the classification criteria are not met.

Further information

Product:

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

Components:

Alcohols, C12-13, ethoxylated:

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

SECTION 12. ECOLOGICAL INFORMATION

Basis for assessment : Incomplete ecoto

: Incomplete ecotoxicological data are available for this product. The information given below is based partly on a knowledge of the components and the ecotoxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual com-

ponent(s).

Version 4.0 Revision Date 01/24/2024 Print Date 01/31/2024

Ecotoxicity

Product:

Toxicity to fish (Acute toxici-

ty)

: LC50 (Pimephales promelas (fathead minnow)): 1.19 mg/l

Exposure time: 96 h

Method: Test(s) equivalent or similar to OECD Guideline 203

Remarks: Very toxic. LC/EC/IC50 < 1 mg/l

Toxicity to crustacean (Acute

toxicity)

(Daphnia magna (Water flea)): 0,238 mg/l

Exposure time: 48 h

Method: Test(s) equivalent or similar to OECD Guideline 202

Remarks: Very toxic. LC/EC/IC50 < 1 mg/l

Toxicity to algae/aquatic plants (Acute toxicity)

: EC50 (Selenastrum capricornutum (green algae)): 0,179 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: Very toxic. LC/EC/IC50 < 1 mg/l

Toxicity to fish (Chronic tox-

icity)

: NOEC (Lepomis macrochirus (Bluegill sunfish)): 0,328 mg/l

Method: Based on quantitative structure-activity relationship

(QSAR) modelling

Remarks: NOEC/NOEL > 0.1 - <=1.0 mg/l

Toxicity to crustacean

(Chronic toxicity)

NOEC (Daphnia magna (Water flea)): 0,012 mg/l

Exposure time: 21 d

Method: OECD Test Guideline 211 Remarks: NOEC/NOEL > 0.1 - <=1.0 mg/l

Toxicity to microorganisms

(Acute toxicity)

EC10 (Pseudomonas putida): > 10 g/l

Exposure time: 16,9 h

Method: Test(s) equivalent or similar to OECD Guideline 209

Remarks: Practically non toxic:

LC/EC/IC50 > 100 mg/l

Components:

Alcohols, C12-13, ethoxylated:

Toxicity to fish (Acute toxicity)

LC50 (Pimephales promelas (fathead minnow)): 0,96 mg/l

Exposure time: 96 h

Method: Test(s) equivalent or similar to OECD Guideline 203

Remarks: Very toxic. LC/EC/IC50 < 1 mg/l

Toxicity to crustacean (Acute

toxicity)

(Daphnia magna (Water flea)): 0,46 mg/l

Exposure time: 48 h

Method: Test(s) equivalent or similar to OECD Guideline 202

Remarks: Very toxic. LC/EC/IC50 < 1 mg/l

Toxicity to algae/aquatic plants (Acute toxicity)

: EC50 (Selenastrum capricornutum (green algae)): 0,069 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Version 4.0 Revision Date 01/24/2024 Print Date 01/31/2024

Remarks: Very toxic. LC/EC/IC50 < 1 mg/l

M-Factor (Acute aquatic tox-

icity)

: 1

Toxicity to fish (Chronic tox-

icity)

: NOEC (Lepomis macrochirus (Bluegill sunfish)): 0,16 mg/l

Exposure time: 10 d

Method: Information given is based on data obtained from

similar substances.

Remarks: NOEC/NOEL > 0.1 - <=1.0 mg/l

Toxicity to crustacean(Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 0,0123 mg/l

Exposure time: 21 d

Method: OECD Test Guideline 211 Remarks: Toxic with long lasting effects: NOEC/NOEL > 0.01 - <=0.1 mg/l

Toxicity to bacteria

: EC10 (Pseudomonas putida): > 10 g/l

Exposure time: 16,9 h

Method: Test(s) equivalent or similar to OECD Guideline 209

Remarks: Practically non toxic:

LC/EC/IC50 > 100 mg/l

Persistence and degradability

Product:

Biodegradability : Biodegradation: 67 %

Exposure time: 28 d

Method: OECD Test Guideline 301F Remarks: Readily biodegradable.

Components:

Alcohols, C12-13, ethoxylated:

Biodegradability : Biodegradation: 95 %

Exposure time: 28 d

Method: OECD Test Guideline 301F Remarks: Readily biodegradable.

Bioaccumulative potential

Product:

Bioaccumulation : Remarks: Biodegradation potential is based on data obtained

from constituents or similar substances.

Partition coefficient: n-

octanol/water

: log Pow: 3

Components:

Alcohols, C12-13, ethoxylated:

Bioaccumulation : Species: Pimephales promelas (fathead minnow)

Bioconcentration factor (BCF): 12,7

Exposure time: 24 d

Version 4.0 Revision Date 01/24/2024 Print Date 01/31/2024

Test substance: C12EO8

Method: Information given is based on data obtained from

similar substances.

Remarks: Bioaccumulation is unlikely to occur due to metabo-

lism and excretion.

Species: Pimephales promelas (fathead minnow)

Bioconcentration factor (BCF): 232,5

Exposure time: 24 d Test substance: C13EO4

Method: Information given is based on data obtained from

similar substances.

Remarks: Bioaccumulation is unlikely to occur due to metabo-

lism and excretion.

Mobility in soil

Product:

Mobility : Remarks: If the product enters soil, one or more constituents

will or may be mobile and may contaminate groundwater.

Floats on water.

Components:

Alcohols, C12-13, ethoxylated:

Mobility Remarks: If the product enters soil, one or more constituents

will or may be mobile and may contaminate groundwater.

Floats on water.

Other adverse effects

Product:

Results of PBT and vPvB

assessment

: The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not consid-

ered to be PBT or vPvB.

Components:

Alcohols, C12-13, ethoxylated:

Results of PBT and vPvB

assessment

The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not consid-

ered to be PBT or vPvB.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Recover or recycle if possible.

It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal meth-

ods in compliance with applicable regulations.

Do not dispose into the environment, in drains or in water

Version 4.0 Revision Date 01/24/2024 Print Date 01/31/2024

courses.

Waste product should not be allowed to contaminate soil or

water.

Disposal should be in accordance with applicable regional,

national, and local laws and regulations.

Local regulations may be more stringent than regional or na-

tional requirements and must be complied with.

Contaminated packaging : Drain container thoroughly.

After draining, vent in a safe place away from sparks and fire.

Residues may cause an explosion hazard. Do not puncture, cut, or weld uncleaned drums. Send to drum recoverer or metal reclaimer.

SECTION 14. TRANSPORT INFORMATION

International Regulations

ADR

UN number : 3082

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(ALCOHOL C12-C13 POLY (1-3)ETHOXYLATE)

Class : 9
Packing group : III
Labels : 9
Hazard Identification Number : 90
Environmentally hazardous : yes

IATA-DGR

UN/ID No. : UN 3082

Proper shipping name : Environmentally hazardous substances, liquid, n.o.s.

(ALCOHOL C12-C13 POLY (1-3)ETHOXYLATE)

Class : 9
Packing group : III
Labels : 9

IMDG-Code

UN number : UN 3082

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(ALCOHOL C12-C13 POLY (1-3)ETHOXYLATE)

Class : 9
Packing group : III
Labels : 9
Marine pollutant : yes

Maritime transport in bulk according to IMO instruments

Pollution category : Y Ship type : 2

Product name : ALCOHOL (C12-C16) POLY (1-6) ETHOXYLATES

Version 4.0 Revision Date 01/24/2024 Print Date 01/31/2024

Special precautions for user

Remarks : Special Precautions: Refer to Section 7, Handling & Storage,

for special precautions which a user needs to be aware of or

needs to comply with in connection with transport.

Additional Information: This product may be transported under nitrogen blanketing.

Nitrogen is an odourless and invisible gas. Exposure to nitrogen enriched atmospheres displaces available oxygen which may cause asphyxiation or death. Personnel must observe strict safety precautions when involved with a confined space entry. Transport in bulk according to Annex II of Marpol and

the IBC Code

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

The components of this product are reported in the following inventories:

AIIC : Listed

DSL : Listed

IECSC : Listed

KECI : Listed

NZIoC : Listed

PICCS : Listed

TSCA : Listed

ENCS : Listed

TCSI : Listed

SECTION 16. OTHER INFORMATION

Full text of H-Statements

H400 Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Aquatic Acute Short-term (acute) aquatic hazard Aquatic Chronic Long-term (chronic) aquatic hazard

Abbreviations and Acronyms : The standard abbreviations and acronyms used in this docu-

ment can be looked up in reference literature (e.g. scientific

Version 4.0 Revision Date 01/24/2024 Print Date 01/31/2024

dictionaries) and/or websites.

Further information

Training advice : Provide adequate information, instruction and training for op-

erators.

Other information : A vertical bar (|) in the left margin indicates an amendment

from the previous version.

Sources of key data used to compile the Safety Data

Sheet

: The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU

IUCLID date base, EC 1272 regulation, etc).

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.