According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Dicyclopentadiene (DCPD) - 85%

Version Revision Date: SDS Number: Print Date: 08/29/2022

12.0 04/06/2020 800010023866 Date of last issue: 05/07/2019

SECTION 1. IDENTIFICATION

Product name : Dicyclopentadiene (DCPD) - 85%

Product code : X2385

Synonyms : Distillates (petroleum), steam-cracked, C8-12 fraction

CAS-No. : 68477-54-3

Manufacturer or supplier's details

Company : Shell Chemical LP

PO Box 576

HOUSTON TX 77001

USA

SDS Request : 1-800-240-6737 Customer Service : 1-855-697-4355

Emergency telephone number

Chemtrec Domestic (24 hr) : 1-800-424-9300 Chemtrec International (24 : 1-703-527-3887

hr)

Recommended use of the chemical and restrictions on use

Recommended use : Base chemical., Use only as a chemical intermediate.

Restrictions on use : This product must not be used in applications other than the

above without first seeking the advice of the supplier.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Flammable liquids : Category 2

Acute toxicity (Oral) : Category 4

Aspiration hazard : Category 1

Acute toxicity (Inhalation) : Category 2

Skin irritation : Category 2

Eye irritation : Category 2A

Specific target organ toxicity

- single exposure

Category 3

Short-term (acute) aquatic

hazard

Category 1

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Dicyclopentadiene (DCPD) - 85%

Version Revision Date: SDS Number: Print Date: 08/29/2022 12.0 04/06/2020 800010023866 Date of last issue: 05/07/2019

Long-term (chronic) aquatic

hazard

Category 2

Reproductive toxicity : Category 2

GHS label elements

Hazard pictograms









Signal word : Danger

Hazard statements : PHYSICAL HAZARDS:

H225 Highly flammable liquid and vapour.

HEALTH HAZARDS: H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H330 Fatal if inhaled.

H335 May cause respiratory irritation.

H361 Suspected of damaging fertility or the unborn child.

ENVIRONMENTAL HAZARDS: H400 Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat/ sparks/ open flames/ hot surfaces.

No smoking.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ ventilating/ lighting equip-

ment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protection/

face protection.

P284 Wear respiratory protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/

shower.

P332 + P313 If skin irritation occurs: Get medical advice/ atten-

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Dicyclopentadiene (DCPD) - 85%

Version Revision Date: SDS Number: Print Date: 08/29/2022 12.0 04/06/2020 800010023866 Date of last issue: 05/07/2019

tion.

P362 Take off contaminated clothing and wash before reuse. P370 + P378 In case of fire: Use appropriate media to extinquish.

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P330 Rinse mouth.

P331 Do NOT induce vomiting.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice/ attention

P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P310 Immediately call a POISON CENTER/ doctor.

P308 + P313 IF exposed or concerned: Get medical advice/attention.

P391 Collect spillage.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P235 Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents and container to appropriate waste site or reclaimer in accordance with local and national regulations.

Other hazards which do not result in classification

May form explosive peroxides.

May form flammable/explosive vapour-air mixture.

Vapours are heavier than air. Vapours may travel across the ground and reach remote ignition sources causing a flashback fire danger.

Will float and can be reignited on surface water.

This material is a static accumulator.

Even with proper grounding and bonding, this material can still accumulate an electrostatic charge.

If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable airvapour mixtures can occur.

The classification of this material is based on OSHA HCS 2012 criteria.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Substance

Hazardous components

Chemical name	Synonyms	CAS-No.	Concentration (% w/w)
Distillates (Petrole-	Distillates (pe-	68477-54-3	<= 100
um), Steam-Cracked,	troleum),		
C8-C12 Fraction	steam-cracked,		

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Dicyclopentadiene (DCPD) - 85%

Version Revision Date: SDS Number: Print Date: 08/29/2022 12.0 04/06/2020 800010023866 Date of last issue: 05/07/2019

12.0 04/06/2020 800010023866 Date of last issue: 05/07/2019

	C8-12 fraction			
Inhibitor	4-tert- butylpyrocate- chol	98-29-3	>= 0.75 -	<= 150 PPM

Further information

Contains:

Chemical name	Identification number	Concentration (% w/w)
Dicyclopentadiene	77-73-6	>= 82 - <= 88

SECTION 4. FIRST-AID MEASURES

General advice : DO NOT DELAY.

Keep victim calm. Obtain medical treatment immediately.

If inhaled : Call emergency number for your location / facility.

Remove to fresh air. Do not attempt to rescue the victim unless proper respiratory protection is worn. If the victim has difficulty breathing or tightness of the chest, is dizzy, vomiting, or unresponsive, give 100% oxygen with rescue breathing or Cardio-Pulmonary Resuscitation as required and transport to

the nearest medical facility.

In case of skin contact : Remove contaminated clothing. Immediately flush skin with

large amounts of water for at least 15 minutes, and follow by washing with soap and water if available. If redness, swelling, pain and/or blisters occur, transport to the nearest medical

facility for additional treatment.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses, if present and easy to do. Continue

rinsing.

Transport to the nearest medical facility for additional treat-

ment.

If swallowed : Call emergency number for your location / facility.

If swallowed, do not induce vomiting: transport to nearest medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.

Rinse mouth.

If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (38.3°C), shortness of breath, chest congestion or continued coughing or wheezing.

Most important symptoms and effects, both acute and

delayed

Respiratory irritation signs and symptoms may include a temporary burning sensation of the nose and throat, coughing, and/or difficulty breathing.

Breathing of high vapour concentrations may cause central nervous system (CNS) depression resulting in dizziness, lightheadedness, headache, nausea and loss of coordination. Continued inhalation may result in unconsciousness and

death.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Dicyclopentadiene (DCPD) - 85%

Version Revision Date: SDS Number: Print Date: 08/29/2022 12.0 04/06/2020 800010023866 Date of last issue: 05/07/2019

Skin irritation signs and symptoms may include a burning sen-

sation, redness, swelling, and/or blisters.

Eye irritation signs and symptoms may include a burning sen-

sation, redness, swelling, and/or blurred vision.

If material enters lungs, signs and symptoms may include coughing, choking, wheezing, difficulty in breathing, chest

congestion, shortness of breath, and/or fever.

If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (38.3°C), shortness of breath, chest congestion or continued coughing or wheezing.

Protection of first-aiders When administering first aid, ensure that you are wearing the

appropriate personal protective equipment according to the

incident, injury and surroundings.

Indication of any immediate medical attention and special treatment needed

IMMEDIATE TREATMENT IS EXTREMELY IMPORTANT! Artificial respiration and/or oxygen may be necessary. Call a doctor or poison control center for guidance.

Potential for chemical pneumonitis.

Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Foam, water spray or fog. Dry chemical powder, carbon diox-Suitable extinguishing media :

ide, sand or earth may be used for small fires only.

Unsuitable extinguishing

media

Do not use water in a jet.

Specific hazards during fire-

fighting

Carbon monoxide may be evolved if incomplete combustion

occurs

Will float and can be reignited on surface water.

The vapour is heavier than air, spreads along the ground and

distant ignition is possible.

Flammable vapours may be present even at temperatures

below the flash point.

Specific extinguishing meth-

Standard procedure for chemical fires.

Further information Clear fire area of all non-emergency personnel.

Keep adjacent containers cool by spraying with water.

Special protective equipment :

for firefighters

Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if

large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to

relevant Standards (e.g. Europe: EN469).

SECTION 6. ACCIDENTAL RELEASE MEASURES

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Dicyclopentadiene (DCPD) - 85%

 Version
 Revision Date:
 SDS Number:
 Print Date: 08/29/2022

 12.0
 04/06/2020
 800010023866
 Date of last issue: 05/07/2019

Personal precautions, protective equipment and emergency procedures

Observe all relevant local and international regulations.

Notify authorities if any exposure to the general public or the environment occurs or is likely to occur.

Local authorities should be advised if significant spillages

cannot be contained.

Avoid contact with skin, eyes and clothing.

Isolate hazard area and deny entry to unnecessary or unpro-

tected personnel.

Do not breathe fumes, vapour. Do not operate electrical equipment.

Environmental precautions

Shut off leaks, if possible without personal risks. Remove all possible sources of ignition in the surrounding area. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. Attempt to disperse the vapour or to direct its flow to a safe location for example by using fog sprays. Take precautionary measures against static discharge. Ensure electrical continuity by bonding and grounding (earthing) all equipment.

Methods and materials for containment and cleaning up

For small liquid spills (< 1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.

For large liquid spills (> 1 drum), transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely

Observe all relevant local and international regulations.

Additional advice

For guidance on selection of personal protective equipment see Chapter 8 of this Safety Data Sheet.

Risk of explosion. Inform the emergency services if liquid en-

ters surface water drains.

For guidance on disposal of spilled material see Chapter 13 of

this Safety Data Sheet.

Vapour may form an explosive mixture with air.

Notify authorities if any exposure to the general public or the environment occurs or is likely to occur.

U.S. regulations may require reporting releases of this material to the environment which exceed the reportable quantity (refer to Section 15) to the National Response Center at (800)

424-8802.

SECTION 7. HANDLING AND STORAGE

Technical measures : Avoid breathing of or direct contact with material. Only use in

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Dicyclopentadiene (DCPD) - 85%

Version Revision Date: SDS Number: Print Date: 08/29/2022

12.0 04/06/2020 800010023866 Date of last issue: 05/07/2019

well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet.

Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.

Ensure that all local regulations regarding handling and storage facilities are followed.

Advice on safe handling : Avoid inhaling vapour and/or mists.

Avoid contact with skin, eyes and clothing.

Extinguish any naked flames. Do not smoke. Remove ignition sources. Avoid sparks.

The vapour is heavier than air. Beware of accumulation in pits and confined spaces.

Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols.

Bulk storage tanks should be diked (bunded).

Properly dispose of any contaminated rags or cleaning materials in order to prevent fires.

Even with proper grounding and bonding, this material can still accumulate an electrostatic charge.

If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur.

Be aware of handling operations that may give rise to additional hazards that result from the accumulation of static charges.

These include but are not limited to pumping (especially turbulent flow), mixing, filtering, splash filling, cleaning and filling of tanks and containers, sampling, switch loading, gauging, vacuum truck operations, and mechanical movements.

These activities may lead to static discharge e.g. spark formation.

Restrict line velocity during pumping in order to avoid generation of electrostatic discharge (≤ 1 m/s until fill pipe submerged to twice its diameter, then ≤ 7 m/s). Avoid splash filling. Do NOT use compressed air for filling, discharging, or handling operations.

Inhibitor levels should be maintained.

Protect against light.

Avoidance of contact : Strong oxidising agents.

Strong acids. Strong bases. Copper alloys

Product Transfer : If positive displacement pumps are used, these must be fitted

with a non-integral pressure relief valve. Refer to guidance

under Handling section.

Further information on stor-

age stability

Keep away from aerosols, flammables, oxidizing agents, cor-

rosives and from other flammable products which are not

harmful or toxic to man or to the environment.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Dicyclopentadiene (DCPD) - 85%

 Version
 Revision Date:
 SDS Number:
 Print Date: 08/29/2022

 12.0
 04/06/2020
 800010023866
 Date of last issue: 05/07/2019

Must be stored in a diked (bunded) well- ventilated area, away from sunlight, ignition sources and other sources of heat. Must be kept inhibited during storage and shipment as material can polymerise.

Vapours from tanks should not be released to atmosphere. Breathing losses during storage should be controlled by a suitable vapour treatment system.

Nitrogen blanket recommended.

Electrostatic charges will be generated during pumping. Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment to reduce the risk.

The vapours in the head space of the storage vessel may lie in the flammable/explosive range and hence may be flammable.

Reacts with atmospheric oxygen. Material contains a stabilizer to inhibit oxidative colour change.

Prolonged storage of the product can cause the stabiliser to lose its effectiveness.

The product is normally supplied in a stabilized form. If the permissible storage period and/or storage temperature is noticeably exceeded, the product may polymerise with heat evolution.

Packaging material

: Suitable material: For containers, or container linings use mild

steel, stainless steel.

Unsuitable material: Copper., Copper alloys.

Specific use(s) : Not applicable

See additional references that provide safe handling practices for liquids that are determined to be static accumulators: American Petroleum Institute 2003 (Protection Against Ignitions Arising out of Static, Lightning and Stray Currents) or National Fire Protection Agency 77 (Recommended Practices

on Static Electricity).

IEC/TS 60079-32-1: Electrostatic hazards, guidance

SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Dicyclopentadiene	77-73-6	TWA	0.5 ppm	ACGIH
Dicyclopentadiene		STEL	1 ppm	ACGIH

Biological occupational exposure limits

No biological limit allocated.

Monitoring Methods

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Dicyclopentadiene (DCPD) - 85%

Version Revision Date: SDS Number: Print Date: 08/29/2022 12.0 04/06/2020 800010023866 Date of last issue: 05/07/2019

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA) , Germany http://www.dguv.de/inhalt/index.jsp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

Engineering measures

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

Use sealed systems as far as possible.

Adequate explosion-proof ventilation to control airborne concentrations below the exposure guidelines/limits.

Local exhaust ventilation is recommended.

Firewater monitors and deluge systems are recommended. Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated. Eye washes and showers for emergency use.

General Information:

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

Personal protective equipment

Respiratory protection

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health,

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Dicyclopentadiene (DCPD) - 85%

Version Revision Date: SDS Number: Print Date: 08/29/2022 12.0 04/06/2020 800010023866 Date of last issue: 05/07/2019

select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are unsuitable (e.g. airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus.

If air-filtering respirators are suitable for conditions of use: Select a filter suitable for organic gases and vapours [Type A boiling point >65°C (149°F)].

Where air-filtering respirators are suitable, select an appropriate combination of mask and filter.

Respirator selection, use and maintenance should be in accordance with the requirements of the OSHA Respiratory Protection Standard, 29 CFR 1910.134.

Hand protection Remarks

Protective measures

: Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. Longer term protection: Viton. Incidental contact/Splash protection: Nitrile rubber. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced.

For continuous contact we recommend gloves with break-through time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model.

Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

Eye protection : Wear goggles for use against liquids and gas.

Wear full face shield if splashes are likely to occur.

Skin and body protection : Wear chemical resistant gloves/gauntlets and boots. Where

risk of splashing, also wear an apron. Wear antistatic and flame-retardant clothing.

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Hygiene measures : Wash hands before eating, drinking, smoking and using the

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Dicyclopentadiene (DCPD) - 85%

Version Revision Date: SDS Number: Print Date: 08/29/2022 12.0 04/06/2020 800010023866 Date of last issue: 05/07/2019

toilet

Launder contaminated clothing before re-use.

Environmental exposure controls

General advice : Local guidelines on emission limits for volatile substances

must be observed for the discharge of exhaust air containing

vapour.

Information on accidental release measures are to be found in

section 6.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : Data not available

Odour : Camphor-like

Odour Threshold : 0.01 ppm

pH : Data not available

Melting point/freezing point : Data not available

Boiling point/boiling range : 170.0 °C / 338.0 °F

Flash point : 33.0 °C / 91.4 °F

Method: Tagliabue Closed Cup

Evaporation rate : Data not available

Flammability (liquids) : Static-accumulating flammable liquid.

Upper explosion limit / upper

flammability limit

6.3 %(V)

Lower explosion limit / Lower :

flammability limit

0.8 %(V)

Vapour pressure : 186 Pa (20.0 °C / 68.0 °F)

Relative vapour density : 4.5

(Air = 1.0)

Relative density : 0.97

Density : Data not available

Solubility(ies)

Water solubility : ca. 40 mg/l (22.2 $^{\circ}$ C / 72.0 $^{\circ}$ F

)

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Dicyclopentadiene (DCPD) - 85%

Version Revision Date: SDS Number: Print Date: 08/29/2022 12.0 04/06/2020 800010023866 Date of last issue: 05/07/2019

Partition coefficient: n-

octanol/water

: Data not available

Auto-ignition temperature : Data not available

Decomposition temperature : Data not available

Viscosity

Viscosity, dynamic : Data not available

Viscosity, kinematic : Data not available

Explosive properties : Not applicable

Oxidizing properties : Data not available

Surface tension : Data not available

Conductivity: < 100 pS/m, The conductivity of this material

makes it a static accumulator., A liquid is typically considered nonconductive if its conductivity is below 100 pS/m and is considered semi-conductive if its conductivity is below 10,000 pS/m., Whether a liquid is nonconductive or semiconductive, the precautions are the same., A number of factors, for example liquid temperature, presence of contaminants, and antistatic additives can greatly influence the conductivity of a liq-

uid

Molecular weight : Data not available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Prolonged exposure to air may lead to peroxide formation.

Reacts with strong oxidising agents.

Chemical stability : The product is normally supplied in a stabilized form. If the

permissible storage period and/or storage temperature is noticeably exceeded, the product may polymerise with heat evo-

lution.

Reacts violently with:

Nitric, sulphuric and chlorosulphuric acids.

Oxidises on contact with air to form unstable peroxides. Polymerisation may occur at elevated temperatures.

Normally stable under ambient conditions and if properly in-

hibited.

Possibility of hazardous reac-

tions

Normally stable under ambient conditions and if properly in-

hibited.

Conditions to avoid : Heat, flames, and sparks.

Exposure to air.
Exposure to sunlight.

In certain circumstances product can ignite due to static elec-

tricity.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Dicyclopentadiene (DCPD) - 85%

Version Revision Date: SDS Number: Print Date: 08/29/2022 12.0 04/06/2020 800010023866 Date of last issue: 05/07/2019

Incompatible materials : Strong oxidising agents.

Strong acids. Strong bases. Copper alloys

Hazardous decomposition

products

Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids and gases, including carbon monoxide, carbon dioxide and other organic compounds will be evolved when this material undergoes combus-

tion or thermal or oxidative degradation.

SECTION 11. TOXICOLOGICAL INFORMATION

Basis for assessment : Information given is based on product testing.

Information on likely routes of exposure

Exposure may occur via inhalation, ingestion, skin absorption, skin or eye contact, and accidental ingestion.

Acute toxicity

Product:

Acute oral toxicity : LD 50 (Rat, male and female): >300-<=2000 mg/kg

Method: OECD Test Guideline 401 Remarks: Harmful if swallowed.

Acute inhalation toxicity : LC 50 (Rat, male and female): > 0.5 - <= 2 mg/l

Exposure time: 6 h
Test atmosphere: vapour

Method: OECD Test Guideline 403

Remarks: Fatal if inhaled.

Acute dermal toxicity : LD 50 (Rat, male and female): > 2,000 mg/kg

Method: OECD Test Guideline 402

Remarks: Based on available data, the classification criteria

are not met.

Skin corrosion/irritation

Product:

Species: Rabbit

Method: OECD Test Guideline 404 Remarks: Causes skin irritation.

Serious eye damage/eye irritation

Product:

Species: Rabbit

Method: OECD Test Guideline 405

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Dicyclopentadiene (DCPD) - 85%

Version Revision Date: SDS Number: Print Date: 08/29/2022 12.0 04/06/2020 800010023866 Date of last issue: 05/07/2019

Remarks: Causes serious eye irritation.

Respiratory or skin sensitisation

Product:

Species: Guinea pig

Method: OECD Test Guideline 406

Remarks: Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Product:

: Method: OECD Test Guideline 471

Remarks: Based on available data, the classification criteria

are not met.

: Method: Acceptable non-standard method.

Remarks: Based on available data, the classification criteria

are not met.

: Method: OECD Test Guideline 476

Remarks: Based on available data, the classification criteria

are not met.

: Test species: Mouse

Method: OECD Test Guideline 474

Remarks: Based on available data, the classification criteria

are not met.

Germ cell mutagenicity- As-

sessment

This product does not meet the criteria for classification in

categories 1A/1B.

Carcinogenicity

Product:

Carcinogenicity - Assess-

ment

: This product does not meet the criteria for classification in

categories 1A/1B.

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Dicyclopentadiene (DCPD) - 85%

Version Revision Date: SDS Number: Print Date: 08/29/2022 12.0 04/06/2020 800010023866 Date of last issue: 05/07/2019

Reproductive toxicity

Product:

: Species: Rat

Sex: male and female Application Route: Oral

Method: Equivalent or similar to OECD Test Guideline 416 Remarks: Suspected of damaging fertility or the unborn child.

Effects on foetal develop-

ment

Species: Rat, female Application Route: Oral

Method: Other guideline method.

Remarks: Suspected of damaging fertility or the unborn child.

Reproductive toxicity - As-

sessment

This product does not meet the criteria for classification in

categories 1A/1B.

STOT - single exposure

Product:

Exposure routes: Inhalation
Target Organs: Respiratory Tract

Remarks: May cause respiratory irritation.

STOT - repeated exposure

Product:

Remarks: Based on available data, the classification criteria are not met., Kidney: caused kidney effects in male rats which are not considered relevant to humans

Repeated dose toxicity

Product:

Species: Rat, male and female

Application Route: Oral

Method: Test(s) equivalent or similar to OECD Test Guideline 422

Target Organs: No specific target organs noted

Species: Rat, male and female Application Route: Inhalation Test atmosphere: vapour

Method: Test(s) equivalent or similar to OECD Test Guideline 413

Target Organs: No specific target organs noted

Aspiration toxicity

Product:

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Dicyclopentadiene (DCPD) - 85%

Version Revision Date: SDS Number: Print Date: 08/29/2022 12.0 04/06/2020 800010023866 Date of last issue: 05/07/2019

Further information

Product:

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

SECTION 12. ECOLOGICAL INFORMATION

Basis for assessment : Information given is based on product testing.

Ecotoxicity

Product:

Toxicity to fish (Acute toxici-

ty)

LC50 (Oryzias latipes (Japanese medaka)): 15.7 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Remarks: Harmful

LL/EL/IL50 >10 <= 100 mg/l

Toxicity to daphnia and other : aquatic invertebrates (Acute

toxicity)

EC50 (Daphnia magna (Water flea)): 0.62 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Remarks: Toxic

LL/EL/IL50 >10 <= 100 mg/l

Toxicity to algae (Acute tox-

icity)

Remarks: Harmful

LL/EL/IL50 >10 <= 100 mg/l

Toxicity to fish (Chronic tox-

icity)

NOEC (Lepomis macrochirus (Bluegill sunfish)): 0.98 mg/l

Exposure time: 14 d

Method: Test(s) equivalent or similar to OECD Test Guideline

204

Remarks: NOEC/NOEL > 0.1 - <=1.0 mg/l

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOEC (Daphnia sp. (water flea)): 0.574 mg/l

Exposure time: 21 d

Method: Based on quantitative structure-activity relationship

(QSAR) modelling

Toxicity to microorganisms

(Acute toxicity)

EC10 (Pseudomonas putida): 2.2 mg/l

Method: Other guideline method.

Remarks: Toxic

 $LL/EL/IL50 > 1 \le 10 \text{ mg/l}$

Persistence and degradability

Product:

Biodegradability : Biodegradation: 0 %

Exposure time: 28 d

Method: OECD Test Guideline 301F Remarks: Not readily biodegradable.

Oxidises rapidly by photo-chemical reactions in air.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Dicyclopentadiene (DCPD) - 85%

Version Revision Date: SDS Number: Print Date: 08/29/2022

12.0 04/06/2020 800010023866 Date of last issue: 05/07/2019

Bioaccumulative potential

Product:

Bioaccumulation : Remarks: Does not bioaccumulate significantly.

Mobility in soil

Product:

Mobility : Remarks: Floats on water.

Other adverse effects

Product:

Results of PBT and vPvB

assessment

The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not consid-

ered to be PBT or vPvB.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Recover or recycle if possible.

It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal meth-

ods in compliance with applicable regulations.

Do not dispose into the environment, in drains or in water

courses

Waste product should not be allowed to contaminate soil or

water.

Disposal should be in accordance with applicable regional,

national, and local laws and regulations.

Local regulations may be more stringent than regional or na-

tional requirements and must be complied with.

SECTION 14. TRANSPORT INFORMATION

National Regulations

US Department of Transportation Classification (49 CFR Parts 171-180)

UN/ID/NA number : UN 1992

Proper shipping name : Flammable Liquids, Toxic, N.O.S.

(DICYCLOPENTADIENE)

Class : 3
Subsidiary risk : 6.1
Packing group : III
Labels : 3 (6.1)
ERG Code : 131
Marine pollutant : no

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Dicyclopentadiene (DCPD) - 85%

Version Revision Date: SDS Number: Print Date: 08/29/2022

12.0 04/06/2020 800010023866 Date of last issue: 05/07/2019

Remarks : Oil

International Regulations

IATA-DGR

UN/ID No. : UN 1992

Proper shipping name : Flammable Liquids, Toxic, N.O.S.

(DICYCLOPENTADIENE)

Class : 3
Subsidiary risk : 6.1
Packing group : III
Labels : 3 (6.1)

IMDG-Code

UN number : UN 1992

Proper shipping name : FLAMMABLE LIQUIDS, TOXIC, N.O.S.

(DICYCLOPENTADIENE)

Class : 3
Subsidiary risk : 6.1
Packing group : III
Labels : 3 (6.1)
Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied. MARPOL Annex 1 rules apply for bulk shipments by sea.

Special precautions for user

Remarks : Special Precautions: Refer to Section 7, Handling & Storage,

for special precautions which a user needs to be aware of or

needs to comply with in connection with transport.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

*: This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)

Acute toxicity (any route of exposure)

Aspiration hazard

Skin corrosion or irritation

Serious eye damage or eye irritation

Specific target organ toxicity (single or repeated exposure)

Reproductive toxicity

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Dicyclopentadiene (DCPD) - 85%

Version Revision Date: SDS Number: Print Date: 08/29/2022 12.0 04/06/2020 800010023866 Date of last issue: 05/07/2019

SARA 313 : The following components are subject to reporting levels es-

tablished by SARA Title III, Section 313:

Dicyclopentadiene 77-73-6 >= 70 - < 90 %

Clean Water Act

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

US State Regulations

Pennsylvania Right To Know

Dicyclopentadiene 77-73-6

California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

California List of Hazardous Substances

Dicyclopentadiene 77-73-6

Other regulations:

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

The components of this product are reported in the following inventories:

AICS : Listed

DSL : Listed

IECSC : Listed

KECI : Listed

TSCA : Listed

TCSI : Listed

SECTION 16. OTHER INFORMATION

Further information

NFPA Rating (Health, Fire, Reac- 4, 3, 1

tivity)

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

ACGIH / TWA : 8-hour, time-weighted average ACGIH / STEL : Short-term exposure limit

Abbreviations and Acronyms : The standard abbreviations and acronyms used in this docu-

ment can be looked up in reference literature (e.g. scientific

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Dicyclopentadiene (DCPD) - 85%

 Version
 Revision Date:
 SDS Number:
 Print Date: 08/29/2022

 12.0
 04/06/2020
 800010023866
 Date of last issue: 05/07/2019

dictionaries) and/or websites.

ACGIH = American Conference of Governmental Industrial Hygienists

ADR = European Agreement concerning the International

Carriage of Dangerous Goods by Road

AICS = Australian Inventory of Chemical Substances ASTM = American Society for Testing and Materials

BEL = Biological exposure limits

BTEX = Benzene, Toluene, Ethylbenzene, Xylenes

CAS = Chemical Abstracts Service

CEFIC = European Chemical Industry Council

CLP = Classification Packaging and Labelling

COC = Cleveland Open-Cup

DIN = Deutsches Institut fur Normung

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

DSL = Canada Domestic Substance List

EC = European Commission

EC50 = Effective Concentration fifty

ECETOC = European Center on Ecotoxicology and Toxicology Of Chemicals

ECHA = European Chemicals Agency

EINECS = The European Inventory of Existing Commercial Chemical Substances

EL50 = Effective Loading fifty

ENCS = Japanese Existing and New Chemical Substances

Inventory EWC = European Waste Code

GHS = Globally Harmonised System of Classification and Labelling of Chemicals

IARC = International Agency for Research on Cancer

IATA = International Air Transport Association

IC50 = Inhibitory Concentration fifty

IL50 = Inhibitory Level fifty

IMDG = International Maritime Dangerous Goods

INV = Chinese Chemicals Inventory

IP346 = Institute of Petroleum test method N° 346 for the determination of polycyclic aromatics DMSO-extractables

KECI = Korea Existing Chemicals Inventory

LC50 = Lethal Concentration fifty

LD50 = Lethal Dose fifty per cent.

LL/EL/IL = Lethal Loading/Effective Loading/Inhibitory loading

LL50 = Lethal Loading fifty

MARPOL = International Convention for the Prevention of Pollution From Ships

NOEC/NOEL = No Observed Effect Concentration / No Observed Effect Level

OE_HPV = Occupational Exposure - High Production Volume

PBT = Persistent, Bioaccumulative and Toxic

PICCS = Philippine Inventory of Chemicals and Chemical Substances

PNEC = Predicted No Effect Concentration

REACH = Registration Evaluation And Authorisation Of

Chemicals

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Dicyclopentadiene (DCPD) - 85%

Version Revision Date: SDS Number: Print Date: 08/29/2022

12.0 04/06/2020 800010023866 Date of last issue: 05/07/2019

RID = Regulations Relating to International Carriage of Dan-

gerous Goods by Rail

SKIN_DES = Skin Designation STEL = Short term exposure limit TRA = Targeted Risk Assessment

TSCA = US Toxic Substances Control Act

TWA = Time-Weighted Average

vPvB = very Persistent and very Bioaccumulative

A vertical bar (I) in the left margin indicates an amendment from the previous version.

There has been a significant change in the required exposure controls/personal protection requirements in section 8.

Sources of key data used to compile the Safety Data

Sheet

The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU

IUCLID date base, EC 1272 regulation, etc).

Revision Date : 04/06/2020

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN