According to the Hazardous Products Regulations

Methyl PROXITOL

 Version
 Revision Date:
 SDS Number:
 Print Date: 2023-11-30

 3.5
 2023-11-23
 800001005738
 Date of last issue: 22.09

2023-11-23 800001005738 Date of last issue: 22.09.2021 Date of first issue: 17.10.2003

SECTION 1. IDENTIFICATION

Product name : Methyl PROXITOL

Product code : U5141

Other means of identification : 1-methoxy-2-propanol, PGME, PM, Propylene glycol

monomethyl ether

Manufacturer or supplier's details

Manufacturer/Supplier : Shell Chemicals Canada

PO Box 4280 STN C CALGARY AB T2T 5Z5

Canada

Telephone : 1-855-697-4355

Telefax : 1-866-213-7508

Emergency telephone number

CHEMTREC (24 hr) : 1-800-424-9300

Recommended use of the chemical and restrictions on use

Recommended use : Solvent.

Restrictions on use : This product must not be used in applications other than the

above without first seeking the advice of the supplier.

Other information : PROXITOL is a trademark owned by Shell Trademark Man-

agement B.V. and Shell Brands Inc. and used by affiliates of

Shell plc.

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids : Category 3

Specific target organ toxicity

- single exposure

: Category 3 (Narcotic effects)

GHS label elements

Hazard pictograms





According to the Hazardous Products Regulations

Methyl PROXITOL

 Version
 Revision Date:
 SDS Number:
 Print Date: 2023-11-30

 3.5
 2023-11-23
 800001005738
 Date of last issue: 22.09.2021

Date of first issue: 17.10.2003

Signal word : Warning

Hazard statements : PHYSICAL HAZARDS:

H226 Flammable liquid and vapour.

HEALTH HAZARDS:

H336 May cause drowsiness or dizziness.

ENVIRONMENTAL HAZARDS:

Not classified as an environmental hazard under GHS criteria.

Precautionary statements : Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames

and other ignition sources. No smoking.

P240 Ground and bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting equip-

ment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharges.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ protective clothing/ eye protection/

face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. P370 + P378 In case of fire: Use appropriate media to extinguish

guish.

P304 + P340 IF INHALED: Remove person to fresh air and

keep comfortable for breathing.

P312 Call a POISON CENTER/doctor if you feel unwell.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container

tightly closed. P235 Keep cool. P405 Store locked up.

Disposal:

P501 Dispose of contents and container to appropriate waste site or reclaimer in accordance with local and national regula-

tions.

Other hazards which do not result in classification

Vapours are heavier than air. Vapours may travel across the ground and reach remote ignition sources causing a flashback fire danger.

Even with proper grounding and bonding, this material can still accumulate an electrostatic charge.

If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable airvapour mixtures can occur.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Substance

According to the Hazardous Products Regulations

Methyl PROXITOL

 Version
 Revision Date:
 SDS Number:
 Print Date: 2023-11-30

 3.5
 2023-11-23
 800001005738
 Date of last issue: 22.09.2021

Date of first issue: 17.10.2003

Substance name : Methyl PROXITOL 107-98-2

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)	
1-Methoxypropane-2-ol	107-98-2	>= 99.6	
2-methoxypropanol	1589-47-5	< 0.1	

SECTION 4. FIRST-AID MEASURES

General advice : Not expected to be a health hazard when used under normal

conditions.

If inhaled : Remove to fresh air. If rapid recovery does not occur,

transport to nearest medical facility for additional treatment.

In case of skin contact : Remove contaminated clothing. Flush exposed area with wa-

ter and follow by washing with soap if available.

If persistent irritation occurs, obtain medical attention.

In case of eye contact : Flush eye with copious quantities of water.

Remove contact lenses, if present and easy to do. Continue

rinsing.

If persistent irritation occurs, obtain medical attention.

If swallowed : If swallowed, do not induce vomiting: transport to nearest

medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.

Rinse mouth.

Most important symptoms and effects, both acute and

delayed

: Breathing of high vapour concentrations may cause central nervous system (CNS) depression resulting in dizziness, light-headedness, headache, nausea and loss of coordination. Continued inhalation may result in unconsciousness and

death.

Skin irritation signs and symptoms may include a burning sen-

sation, redness, or swelling.

Eye irritation signs and symptoms may include a burning sen-

sation, redness, swelling, and/or blurred vision.

Ingestion may result in nausea, vomiting and/or diarrhoea. Defatting dermatitis signs and symptoms may include a burn-

ing sensation and/or a dried/cracked appearance.

Protection of first-aiders : When administering first aid, ensure that you are wearing the

appropriate personal protective equipment according to the

incident, injury and surroundings.

Notes to physician : Call a doctor or poison control center for guidance.

Treat symptomatically.

According to the Hazardous Products Regulations

Methyl PROXITOL

Version 3.5

Revision Date: 2023-11-23

SDS Number: 800001005738

Print Date: 2023-11-30 Date of last issue: 22.09.2021 Date of first issue: 17.10.2003

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

 Alcohol-resistant foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires

only.

Unsuitable extinguishing

media

: None

Specific hazards during fire-

fighting

The vapour is heavier than air, spreads along the ground and

distant ignition is possible.

Carbon monoxide may be evolved if incomplete combustion

occurs.

Specific extinguishing meth-

ods.

: Standard procedure for chemical fires.

Further information : Clear fire area of all non-emergency personnel.

Keep adjacent containers cool by spraying with water.

Special protective equipment

for firefighters

Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained

Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to

relevant Standards (e.g. Europe: EN469).

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

: Observe the relevant local and international regulations Notify authorities if any exposure to the general public or the

environment occurs or is likely to occur.

Local authorities should be advised if significant spillages

cannot be contained.

The vapour is heavier than air, spreads along the ground and

distant ignition is possible.

Vapour may form an explosive mixture with air. Avoid contact with skin, eyes and clothing.

Isolate hazard area and deny entry to unnecessary or unpro-

tected personnel.

Stay upwind and keep out of low areas.

Environmental precautions

Shut off leaks, if possible without personal risks. Remove all possible sources of ignition in the surrounding area. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. Attempt to disperse the vapour or to direct its flow to a safe location for example by using fog sprays. Take precautionary measures against static discharge. Ensure electrical continuity by bond-

ing and grounding (earthing) all equipment.

According to the Hazardous Products Regulations

Methyl PROXITOL

Version 3.5

Revision Date: 2023-11-23

SDS Number: 800001005738 Print Date: 2023-11-30 Date of last issue: 22.09.2021 Date of first issue: 17.10.2003

Ventilate contaminated area thoroughly. Monitor area with combustible gas indicator.

Methods and materials for containment and cleaning up For large liquid spills (> 1 drum), transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely For small liquid spills (< 1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove

contaminated soil and dispose of safely.

Additional advice

: For guidance on selection of personal protective equipment

see Section 8 of this Safety Data Sheet.

For guidance on disposal of spilled material see Section 13 of

this Safety Data Sheet.

SECTION 7. HANDLING AND STORAGE

General Precautions

: Avoid breathing of or direct contact with material. Only use in well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet.

Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.

Ensure that all local regulations regarding handling and storage facilities are followed.

Advice on safe handling

: Avoid contact with skin, eyes and clothing.

Use local exhaust ventilation if there is risk of inhalation of

vapours, mists or aerosols.

Bulk storage tanks should be diked (bunded).

Extinguish any naked flames. Do not smoke. Remove ignition

sources. Avoid sparks.

Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment to

reduce the risk.

The vapours in the head space of the storage vessel may lie in the flammable/explosive range and hence may be flamma-

Properly dispose of any contaminated rags or cleaning mate-

rials in order to prevent fires.

Do NOT use compressed air for filling, discharging, or han-

dling operations.

5/17 800001005738

According to the Hazardous Products Regulations

Methyl PROXITOL

 Version
 Revision Date:
 SDS Number:
 Print Date: 2023-11-30

 3.5
 2023-11-23
 800001005738
 Date of last issue: 22.09.2021

Date of first issue: 17.10.2003

Avoidance of contact : Strong oxidising agents.

Product Transfer : Refer to guidance under Handling section.

Storage

Conditions for safe storage : The vapour is heavier than air. Beware of accumulation in pits

and confined spaces.

Refer to section 15 for any additional specific legislation cov-

ering the packaging and storage of this product.

Packaging material : Suitable material: For containers, or container linings use mild

steel, stainless steel.

Unsuitable material: Natural, butyl, neoprene or nitrile rubbers.

Container Advice : Containers, even those that have been emptied, can contain

explosive vapours. Do not cut, drill, grind, weld or perform

similar operations on or near containers.

Specific use(s) : Not applicable

Ensure that all local regulations regarding handling and stor-

age facilities are followed.

See additional references that provide safe handling practices: American Petroleum Institute 2003 (Protection Against Ignitions Arising out of Static, Lightning and Stray Currents) or National Fire Protection Agency 77 (Recommended Practices

on Static Electricity).

IEC/TS 60079-32-1: Electrostatic hazards, guidance

SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
1-Methoxypropane-2-ol	107-98-2	TWA	50 ppm	CA BC OEL
		STEL	100 ppm	CA BC OEL
		TWA	50 ppm	ACGIH
		STEL	100 ppm	ACGIH

Biological occupational exposure limits

No biological limit allocated.

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

According to the Hazardous Products Regulations

Methyl PROXITOL

 Version
 Revision Date:
 SDS Number:
 Print Date: 2023-11-30

 3.5
 2023-11-23
 800001005738
 Date of last issue: 22.09.2021

Date of first issue: 17.10.2003

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA) , Germany http://www.dquv.de/inhalt/index.isp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

Engineering measures

: The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

Use sealed systems as far as possible.

Adequate explosion-proof ventilation to control airborne concentrations below the exposure guidelines/limits.

Local exhaust ventilation is recommended.

Firewater monitors and deluge systems are recommended.

Eye washes and showers for emergency use.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

General Information:

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance

Retain drain downs in sealed storage pending disposal or subsequent recycle.

Personal protective equipment

Respiratory protection

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation.

According to the Hazardous Products Regulations

Methyl PROXITOL

Version 3.5

Revision Date: 2023-11-23

SDS Number: 800001005738

Print Date: 2023-11-30 Date of last issue: 22.09.2021 Date of first issue: 17.10.2003

Check with respiratory protective equipment suppliers. Where air-filtering respirators are unsuitable (e.g. airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus.

Where air-filtering respirators are suitable, select an appropriate combination of mask and filter.

If air-filtering respirators are suitable for conditions of use: Select a filter suitable for organic gases and vapours [Type A boiling point >65°C (149°F)].

Hand protection Remarks

: Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. Longer term protection: butylrubber Nitrile rubber gloves.

Incidental contact/Splash protection: Nitrile rubber gloves. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

Eye protection

: If material is handled such that it could be splashed into eyes, protective eyewear is recommended.

Skin and body protection

: Skin protection is not required under normal conditions of

ise.

For prolonged or repeated exposures use impervious clothing over parts of the body subject to exposure.

If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to relevant Stand-

ard, and provide employee skin care programmes.

Wear antistatic and flame-retardant clothing, if a local risk

assessment deems it so.

Protective measures

: Personal protective equipment (PPE) should meet recom-

According to the Hazardous Products Regulations

Methyl PROXITOL

Version Revision Date: 3.5 2023-11-23

SDS Number: 800001005738

Print Date: 2023-11-30 Date of last issue: 22.09.2021

Date of first issue: 17.10.2003

mended national standards. Check with PPE suppliers.

Environmental exposure controls

General advice : Local guidelines on emission limits for volatile substances

must be observed for the discharge of exhaust air containing

vapour.

Minimise release to the environment. An environmental assessment must be made to ensure compliance with local envi-

ronmental legislation.

Information on accidental release measures are to be found in

section 6.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Liquid.

Colour : clear

Odour : Ethereal

Odour Threshold : Data not available

pH : Data not available

Melting / freezing point : -96 °C / -141 °F

Boiling point/boiling range : 117 - 125 °C / 243 - 257 °F

Flash point : 30 °C / 86 °F

Method: ASTM D93 (PMCC)

Evaporation rate : 0.75

Method: ASTM D 3539, nBuAc=1

Flammability

Flammability (solid, gas) : Data not available

Lower explosion limit and upper explosion limit / flammability limit

Upper explosion limit : 13.1 %(V)

Lower explosion limit : 1.9 %(V)

Vapour pressure : 1.170 Pa (20 °C / 68 °F)

Relative vapour density : 3.1

Relative density : 0.92 (20 °C / 68 °F)

Method: ASTM D4052

According to the Hazardous Products Regulations

Methyl PROXITOL

Version Revision Date: SDS Number: Print Date: 2023-11-30 3.5 2023-11-23 800001005738 Date of last issue: 22.09

5 2023-11-23 800001005738 Date of last issue: 22.09.2021 Date of first issue: 17.10.2003

Density : 920 - 923 kg/m3 (20 °C / 68 °F)Method: ASTM D4052

Solubility(ies)

Water solubility : completely soluble (20 °C / 68 °F

)

Solubility in other solvents : Data not available

Partition coefficient: n-

octanol/water

: log Pow: 0.37

Auto-ignition temperature : 290 °C / 554 °F

Decomposition temperature : Data not available

Viscosity

Viscosity, dynamic : Data not available

Viscosity, kinematic : Data not available

Explosive properties : Not applicable

Oxidizing properties : Data not available

Surface tension : 70.7 mN/m, $20 ^{\circ}\text{C} / 68 ^{\circ}\text{F}$

Conductivity: > 10,000 pS/m

A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid, This material is not expected to be

a static accumulator.

Molecular weight : 90.12 g/mol

SECTION 10. STABILITY AND REACTIVITY

Reactivity : The product does not pose any further reactivity hazards in

addition to those listed in the following sub-paragraph.

Chemical stability : No hazardous reaction is expected when handled and stored

according to provisions

Possibility of hazardous reac-

tions

: Reacts with strong oxidising agents.

Conditions to avoid : Avoid heat, sparks, open flames and other ignition sources.

Prevent vapour accumulation.

In certain circumstances product can ignite due to static elec-

tricity.

According to the Hazardous Products Regulations

Methyl PROXITOL

Version Revision Date: SDS Number: Print Date: 2023-11-30

3.5 2023-11-23 800001005738 Date of last issue: 22.09.2021 Date of first issue: 17.10.2003

Incompatible materials : Strong oxidising agents.

Hazardous decomposition : Thermal decomposition is highly dependent on conditions. A

products

complex mixture of airborne solids, liquids and gases including carbon monoxide, carbon dioxide, sulphur oxides and unidentified organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation.

SECTION 11. TOXICOLOGICAL INFORMATION

Basis for assessment : Information given is based on product testing.

Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual com-

ponent(s).

Information on likely routes of exposure

Exposure may occur via inhalation, ingestion, skin absorption, skin or eye contact, and accidental ingestion.

Acute toxicity

Components:

1-Methoxypropane-2-ol:

Acute oral toxicity : LD50: > 2000 - <= 5000 mg/kg

Remarks: May be harmful if swallowed.

Acute inhalation toxicity : Remarks: Low toxicity by inhalation.

Acute dermal toxicity : LD50: > 5000 mg/kg

Remarks: Low toxicity

Skin corrosion/irritation

Components:

1-Methoxypropane-2-ol:

Remarks: Not irritating to skin.

Prolonged/repeated contact may cause defatting of the skin which can lead to dermatitis.

Serious eye damage/eye irritation

Components:

1-Methoxypropane-2-ol:

Remarks: Slightly irritating to the eye.

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Components:

According to the Hazardous Products Regulations

Methyl PROXITOL

Version Revision Date: SDS Number: Print Date: 2023-11-30 3.5 2023-11-23 800001005738 Date of last issue: 22.09

00001005738 Date of last issue: 22.09.2021 Date of first issue: 17.10.2003

1-Methoxypropane-2-ol:

Remarks: Not a sensitiser.

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Components:

1-Methoxypropane-2-ol:

Genotoxicity in vivo : Remarks: No evidence of mutagenic activity.

Carcinogenicity

Components:

1-Methoxypropane-2-ol:

Remarks: Not carcinogenic in animal studies.

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

Reproductive toxicity

Components:

1-Methoxypropane-2-ol:

Effects on fertility

Remarks: Does not impair fertility.

Causes foetotoxicity in animals at doses which are maternally

toxic.

Causes adverse effects on the foetus based on animal stud-

ies.

STOT - single exposure

Components:

1-Methoxypropane-2-ol:

Remarks: High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea; continued inhalation may result in unconsciousness.

STOT - repeated exposure

Components:

1-Methoxypropane-2-ol:

According to the Hazardous Products Regulations

Methyl PROXITOL

 Version
 Revision Date:
 SDS Number:
 Print Date: 2023-11-30

 3.5
 2023-11-23
 800001005738
 Date of last issue: 22.09.2021

Date of first issue: 17.10.2003

Remarks: Kidney: caused kidney effects in male rats which are not considered relevant to hu-

mans

Based on available data, the classification criteria are not met.

Aspiration toxicity

Components:

1-Methoxypropane-2-ol:

Not an aspiration hazard.

Further information

Components:

1-Methoxypropane-2-ol:

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

SECTION 12. ECOLOGICAL INFORMATION

Basis for assessment : Ecotoxicological data are based on product testing.

Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual com-

ponent(s).

Ecotoxicity

Components:

1-Methoxypropane-2-ol:

Toxicity to fish (Acute toxici-

ty)

: Remarks: Practically non toxic:

LC/EC/IC50 > 1000 mg/l

Toxicity to crustacean (Acute

toxicity)

: Remarks: Practically non toxic:

LC/EC/IC50 > 1000 mg/l

Toxicity to algae/aquatic

plants (Acute toxicity)

: Remarks: Practically non toxic: LC/EC/IC50 > 1000 mg/l

Toxicity to fish (Chronic tox-

icity)

: Remarks: Data not available

Toxicity to crustacean(Chronic toxicity)

cean(Chronic toxicity)

: Remarks: Data not available

Toxicity to bacteria : Remarks: Data not available

Persistence and degradability

Components:

1-Methoxypropane-2-ol:

Biodegradability : Remarks: Readily biodegradable meeting the 10 day window

criterion.

According to the Hazardous Products Regulations

Methyl PROXITOL

Version 3.5

Revision Date: 2023-11-23

SDS Number: 800001005738

Print Date: 2023-11-30 Date of last issue: 22.09.2021 Date of first issue: 17.10.2003

Oxidises rapidly by photo-chemical reactions in air.

Bioaccumulative potential

Partition coefficient: n-

octanol/water

: log Pow: 0.37

Components:

1-Methoxypropane-2-ol:

Bioaccumulation : Remarks: Does not bioaccumulate significantly.

Mobility in soil

Components:

1-Methoxypropane-2-ol:

Makilik

Mobility : Remarks: Dissolves in water.

If product enters soil, it will be highly mobile and may contam-

inate groundwater.

Other adverse effects

no data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Recover or recycle if possible.

It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal meth-

ods in compliance with applicable regulations.

Do not dispose into the environment, in drains or in water

courses.

Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment. Waste, spills or used product is dangerous waste.

Disposal should be in accordance with applicable regional,

national, and local laws and regulations.

Local regulations may be more stringent than regional or na-

tional requirements and must be complied with.

MARPOL - see International Convention for the Prevention of Pollution from Ships (MARPOL 73/78) which provides tech-

nical aspects at controlling pollutions from ships.

Contaminated packaging : Drain container thoroughly.

After draining, vent in a safe place away from sparks and fire.

Residues may cause an explosion hazard. Do not, puncture, cut, or weld uncleaned drums. Send to drum recoverer or metal reclaimer.

According to the Hazardous Products Regulations

Methyl PROXITOL

Version **Revision Date:** SDS Number: Print Date: 2023-11-30 3.5 2023-11-23

800001005738 Date of last issue: 22.09.2021

Date of first issue: 17.10.2003

Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand.

Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand.

SECTION 14. TRANSPORT INFORMATION

TDG

UN number : 3092

Proper shipping name 1-METHOXY-2-PROPANOL

Class : 3 Packing group Ш Labels : 3 Marine pollutant : no

International Regulations

IATA-DGR

UN/ID No. : UN 3092

Proper shipping name : 1-METHOXY-2-PROPANOL

Class : 3 Packing group : III Labels : 3

IMDG-Code

UN number : UN 3092

Proper shipping name : 1-METHOXY-2-PROPANOL

Class : 3 Packing group : 111 Labels : 3 Marine pollutant : no

Maritime transport in bulk according to IMO instruments

Pollution category : Z Ship type

Product name Propylene glycol monoalkyl ether

Special precautions for user

Remarks : Special Precautions: Refer to Section 7, Handling & Storage,

for special precautions which a user needs to be aware of or

needs to comply with in connection with transport.

Additional Information : This product may be transported under nitrogen blanketing.

> Nitrogen is an odourless and invisible gas. Exposure to nitrogen may cause asphyxiation or death. Personnel must ob-

15 / 17 800001005738

According to the Hazardous Products Regulations

Methyl PROXITOL

Version 3.5

Revision Date: 2023-11-23

SDS Number: 800001005738

Print Date: 2023-11-30 Date of last issue: 22.09.2021 Date of first issue: 17.10.2003

serve strict safety precautions when involved with a confined space entry. Transport in bulk according to Annex II of Marpol and the IBC Code

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR.

The components of this product are reported in the following inventories:

AIIC : Listed

DSL : Listed

IECSC : Listed

ENCS : Listed

KECI : Listed

NZIoC : Listed

PICCS : Listed

TSCA : Listed

TCSI : Listed

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Or-

According to the Hazardous Products Regulations

Methyl PROXITOL

 Version
 Revision Date:
 SDS Number:
 Print Date: 2023-11-30

 3.5
 2023-11-23
 800001005738
 Date of last issue: 22.09.2021

Date of first issue: 17.10.2003

ganisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances: (Q)SAR - (Quantitative) Structure Activity Relationship: REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

A vertical bar () in the left margin indicates an amendment from the previous version.

Sources of key data used to compile the Safety Data

Sheet

: The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU

IUCLID date base, EC 1272 regulation, etc).

Revision Date : 2023-11-23

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CA / EN