According to EC No 1907/2006 as amended as at the date of this SDS

## Acetylene

Date of last issue: 28.03.2023 Version Revision Date: SDS Number:

18.08.2023 800001006002 Print Date 26.08.2023 3.2

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : Acetylene Product code X1930, X3087

Registration number EU : 01-2119457406-36-0001, 01-2119457406-36-0002

Synonyms : Ethyne CAS-No. : 74-86-2

EC-No. : 200-816-9

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-: Base chemical., Raw material for use in the chemical industry. stance/Mixture

Please refer to section 16 and/or the annexes for the regis-

tered uses under REACH.

: This product must not be used in applications other than the Uses advised against

above without first seeking the advice of the supplier.

### 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier : Shell Chemicals Europe B.V.

> PO Box 2334 3000 CH Rotterdam

Netherlands

: +31 (0)10 441 5137 / +31 (0)10 441 5191 Telephone : +31 (0)20 716 8316 / +31 (0)20 713 9230 Telefax

Contact for Safety Data : sccmsds@shell.com

Sheet

### 1.4 Emergency telephone number

+44 (0) 1235 239 670

Nationaal Vergiftigingen Informatie Centrum (NVIC): Tel. nr. +31(0)88 755 8000 (24 uur per

dag en 7 dagen per week).

(Uitsluitend bestemd om artsen te informeren bij accidentele vergiftigingen).

#### **SECTION 2: Hazards identification**

### 2.1 Classification of the substance or mixture

## Classification (REGULATION (EC) No 1272/2008)

Flammable gases, Category 1A H220: Extremely flammable gas.

Chemically unstable gas, Category A H230: May react explosively even in the absence

of air.

According to EC No 1907/2006 as amended as at the date of this SDS

## **Acetylene**

Version Revision Date: SDS Number: Date of last issue: 28.03.2023

3.2 18.08.2023 800001006002 Print Date 26.08.2023

Gases under pressure, Dissolved gas H280: Contains gas under pressure; may explode if

heated.

#### 2.2 Label elements

### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :





Signal word : Danger

Hazard statements : PHYSICAL HAZARDS:

H220 Extremely flammable gas.

H230 May react explosively even in the absence of air.H280 Contains gas under pressure; may explode if heated.

**HEALTH HAZARDS:** 

Not classified as a health hazard under CLP criteria.

**ENVIRONMENTAL HAZARDS:** 

Not classified as environmental hazard according to

CLP criteria.

Precautionary statements : Prevention:

P210 Keep away from heat, hot surfaces, sparks, open

flames and other ignition sources. No smoking.

P202 Do not handle until all safety precautions have been

read and understood.

Response:

P377 Leaking gas fire: Do not extinguish, unless leak can be

stopped safely.

P381 In case of leakage, eliminate all ignition sources.

Storage:

P410 + P403 Protect from sunlight. Store in a well-ventilated

place.

Disposal:

No precautionary phrases.

#### 2.3 Other hazards

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

High gas concentrations will displace available air; unconsciousness and death may occur sud-

According to EC No 1907/2006 as amended as at the date of this SDS

## **Acetylene**

Version Revision Date: SDS Number: Date of last issue: 28.03.2023

3.2 18.08.2023 800001006002 Print Date 26.08.2023

denly from lack of oxygen.

Exposure to rapidly expanding gases may cause frost burns to eyes and/or skin.

Vapours may cause drowsiness and dizziness.

Slightly irritating to respiratory system.

This material is shipped under pressure.

May form flammable/explosive vapour-air mixture.

This material has the potential to be a static accumulator.

Electrostatic charges may be generated during pumping. Electrostatic discharge may cause fire.

### **SECTION 3: Composition/information on ingredients**

#### 3.1 Substances

### Components

Chemical name	CAS-No.	Concentration (% w/w)
	EC-No.	, , ,
acetylene	74-86-2	<= 100
	200-816-9	

#### **SECTION 4: First aid measures**

### 4.1 Description of first aid measures

General advice : Not expected to be a health hazard when used under normal

conditions.

Protection of first-aiders : When administering first aid, ensure that you are wearing the

appropriate personal protective equipment according to the

incident, injury and surroundings.

If inhaled : Call emergency number for your location / facility.

Remove to fresh air. Do not attempt to rescue the victim unless proper respiratory protection is worn. If the victim has difficulty breathing or tightness of the chest, is dizzy, vomiting, or unresponsive, give 100% oxygen with rescue breathing or Cardio-Pulmonary Resuscitation as required and transport to

the nearest medical facility.

In case of skin contact : Slowly warm the exposed area by rinsing with warm water.

Transport to the nearest medical facility for additional treat-

ment.

In case of eye contact : Slowly warm the exposed area by rinsing with warm water.

Transport to the nearest medical facility for additional treat-

ment.

If swallowed : In general no treatment is necessary unless large quantities

are swallowed, however, get medical advice.

According to EC No 1907/2006 as amended as at the date of this SDS

## **Acetylene**

Version Revision Date: SDS Number: Date of last issue: 28.03.2023

3.2 18.08.2023 800001006002 Print Date 26.08.2023

### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Respiratory irritation signs and symptoms may include a tem-

porary burning sensation of the nose and throat, coughing,

and/or difficulty breathing.

Rapid release of gases which are liquids under pressure may cause frost burns of exposed tissues (skin, eye) due to evapo-

rative cooling.

No specific hazards under normal use conditions.

Ingestion may result in nausea, vomiting and/or diarrhoea.

Breathing of high vapour concentrations may cause central nervous system (CNS) depression resulting in dizziness, lightheadedness, headache, nausea and loss of coordination. Continued inhalation may result in unconsciousness and

death.

Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of

consciousness.

If material enters lungs, signs and symptoms may include coughing, choking, wheezing, difficulty in breathing, chest

congestion, shortness of breath, and/or fever.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : IMMEDIATE TREATMENT IS EXTREMELY IMPORTANT!

Call a doctor or poison control center for guidance. Artificial respiration and/or oxygen may be necessary.

Treat symptomatically.

#### **SECTION 5: Firefighting measures**

### 5.1 Extinguishing media

Suitable extinguishing media : Shut off supply. If not possible and no risk to surroundings, let

the fire burn itself out.

Unsuitable extinguishing

media

Do not use water in a jet.

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

: Sustained fire attack on vessels may result in a Boiling Liquid Expanding Vapor Explosion (BLEVE).

Contents are under pressure and can explode when exposed

to heat or flames.

As the vapours become lighter than air, the vapours may reach ignition sources at ground or elevated locations.

According to EC No 1907/2006 as amended as at the date of this SDS

## **Acetylene**

Version Revision Date: SDS Number: Date of last issue: 28.03.2023

3.2 18.08.2023 800001006002 Print Date 26.08.2023

### 5.3 Advice for firefighters

Special protective equipment :

for firefighters

Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to

relevant Standards (e.g. Europe: EN469).

Specific extinguishing meth-

ods

Standard procedure for chemical fires.

Further information : Clear fire area of all non-emergency personnel.

Keep adjacent containers cool by spraying with water. Evacuate the area of all non-essential personnel.

#### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : 6.1.1 For non emergency personnel:

Avoid contact with skin, eyes and clothing.

Isolate hazard area and deny entry to unnecessary or unpro-

tected personnel.

Do not breathe fumes, vapour. Do not operate electrical equipment. 6.1.2 For emergency responders:

Avoid contact with skin, eyes and clothing.

Isolate hazard area and deny entry to unnecessary or unpro-

tected personnel.

Do not breathe fumes, vapour. Do not operate electrical equipment.

### 6.2 Environmental precautions

Environmental precautions : Shut off leaks, if possible without personal risks. Remove all

possible sources of ignition in the surrounding area and evacuate all personnel. Attempt to disperse the gas or to direct its flow to a safe location for example by using fog sprays. Take precautionary measures against static discharge. Ensure electrical continuity by bonding and grounding (earthing) all equipment. Monitor area with combustible gas meter.

## 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Allow to evaporate.

Attempt to disperse the vapour or to direct its flow to a safe location, for example by using fog sprays. Otherwise treat as

for small spillage.

According to EC No 1907/2006 as amended as at the date of this SDS

## **Acetylene**

Version Revision Date: SDS Number: Date of last issue: 28.03.2023

3.2 18.08.2023 800001006002 Print Date 26.08.2023

#### 6.4 Reference to other sections

For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet., Vapour may form an explosive mixture with air., For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.

Local authorities should be advised if significant spillages cannot be contained.

### **SECTION 7: Handling and storage**

### 7.1 Precautions for safe handling

Technical measures : Avoid breathing of or direct contact with material. Only use in

well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see

Section 8 of this Safety Data Sheet.

Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this

materiai

Ensure that all local regulations regarding handling and stor-

age facilities are followed.

Advice on safe handling : Avoid inhaling vapour and/or mists.

Avoid contact with skin, eyes and clothing.

Extinguish any naked flames. Do not smoke. Remove ignition

sources. Avoid sparks.

Electrostatic charges may be generated during pumping. Elec-

trostatic discharge may cause fire.

Ensure electrical continuity by bonding and grounding (earthing) all equipment. Restrict line velocity during pumping in order to avoid generation of electrostatic discharge (<= 1 m/sec until fill pipe submerged to twice its diameter, then <= 7 m/sec). Avoid splash filling. Do NOT use compressed air for

filling, discharging, or handling operations.

Do not use compressed air for filling, discharging or handling.

Product Transfer : Refer to guidance under Handling section.

Hygiene measures : Wash hands before eating, drinking, smoking and using the

toilet. Launder contaminated clothing before re-use.

### 7.2 Conditions for safe storage, including any incompatibilities

Further information on storage stability

: Keep away from aerosols, flammables, oxidizing agents, corrosives and from products harmful or toxic to man or to the

environment.

Must be stored in a diked (bunded) well- ventilated area, away from sunlight, ignition sources and other sources of heat. Vapours from tanks should not be released to atmosphere. Breathing losses during storage should be controlled by a

suitable vapour treatment system.

According to EC No 1907/2006 as amended as at the date of this SDS

## **Acetylene**

Version Revision Date: SDS Number: Date of last issue: 28.03.2023

3.2 18.08.2023 800001006002 Print Date 26.08.2023

Packaging material : Suitable material: For containers, or container linings use mild

steel, stainless steel.

Unsuitable material: Aluminum, Copper.

7.3 Specific end use(s)

Specific use(s) : Please refer to section 16 and/or the annexes for the regis-

tered uses under REACH.

Ensure that all local regulations regarding handling and stor-

age facilities are followed.

See additional references that provide safe handling practices: American Petroleum Institute 2003 (Protection Against Ignitions Arising out of Static, Lightning and Stray Currents) or National Fire Protection Agency 77 (Recommended Practices

on Static Electricity).

IEC/TS 60079-32-1: Electrostatic hazards, guidance

## **SECTION 8: Exposure controls/personal protection**

### 8.1 Control parameters

#### Biological occupational exposure limits

No biological limit allocated.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Remarks:	Exposure assessments have not been presented for the	environment
	therefore PNEC values not required.	

## 8.2 Exposure controls

### **Engineering measures**

Read in conjunction with the Exposure Scenario for your specific use contained in the Annex. Use sealed systems as far as possible.

Adequate explosion-proof ventilation to control airborne concentrations below the exposure guidelines/limits.

Local exhaust ventilation is recommended.

Firewater monitors and deluge systems are recommended.

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

#### General Information:

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Define procedures for safe handling and maintenance of controls.

According to EC No 1907/2006 as amended as at the date of this SDS

## **Acetylene**

Version Revision Date: SDS Number: Date of last issue: 28.03.2023

3.2 18.08.2023 800001006002 Print Date 26.08.2023

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Purge system prior to equipment break-in or maintenance.

#### Personal protective equipment

Read in conjunction with the Exposure Scenario for your specific use contained in the Annex. The provided information is made in consideration of the PPE directive (Council Directive 89/686/EEC) and the CEN European Committee for Standardisation (CEN) standards.

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Eye protection : Wear goggles for use against liquids and gas, combined with

face shield with chin guard.

Approved to EU Standard EN166.

Hand protection

Remarks : Where hand contact with the product may occur the use of

gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. Neoprene rubber. If contact with liquefied product is possible or anticipated, gloves should be thermally insulated to prevent cold burns. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is

recommended.

Skin and body protection : Chemical and cryogenic gloves/gauntlets, boots, and apron.

Wear antistatic and flame-retardant clothing, if a local risk

assessment deems it so.

Respiratory protection : If engineering controls do not maintain airborne concentra-

According to EC No 1907/2006 as amended as at the date of this SDS

## **Acetylene**

Version Revision Date: SDS Number: Date of last issue: 28.03.2023

3.2 18.08.2023 800001006002 Print Date 26.08.2023

tions to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are unsuitable (e.g. airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus

If air-filtering respirators are suitable for conditions of use: Where air-filtering respirators are suitable, select an appropriate combination of mask and filter.

Select a filter suitable for organic gases and vapours [Type

AX boiling point < 65°C (149°F)] meeting EN14387.

## **SECTION 9: Physical and chemical properties**

9.1 Information on basic physical and chemical properties

Physical state : Gas.

Colour : colourless

Odour : Not applicable

Odour Threshold : Data not available

Data not available

Boiling point/boiling range : -84,7 °C

Flammability

Flammability (solid, gas) : Data not available

Lower explosion limit and upper explosion limit / flammability limit

Upper explosion limit / upper flammability limit

: 99 %(V)

Lower explosion limit / Lower flammability limit

1,5 %(V)

Flash point : Not applicable

Auto-ignition temperature : 305 °C

Decomposition temperature

Decomposition tempera-

Data not available

ture

pH : Not applicable

According to EC No 1907/2006 as amended as at the date of this SDS

## **Acetylene**

Version Revision Date: SDS Number: Date of last issue: 28.03.2023

3.2 18.08.2023 800001006002 Print Date 26.08.2023

Viscosity

Viscosity, kinematic : Data not available

Solubility(ies)

Water solubility : 1,200 mg/l (20 °C)

Solubility in other solvents : (based on alcohol(s))

(15 °C)

Description: soluble

Partition coefficient: n-

octanol/water

log Pow: 0,37

Vapour pressure : 44,000 mbar (20 °C)

Relative density : Data not available

Density : Data not available

Relative vapour density : 0,9

Particle characteristics

Particle size : Data not available

9.2 Other information

Explosives : no data available

Oxidizing properties : Data not available

Evaporation rate : Data not available

Conductivity : Data not available

Surface tension : Data not available

### **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

Thermally unstable.

### 10.2 Chemical stability

Thermally unstable.

Polymerises with risk of fire and explosion.

Reacts violently with strong oxidising agents.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : In acetylene atmosphere, fluoride or chloride under the influ-

ence of sunlight forms very sensitive explosive metallic com-

pounds with silver, mercury and copper.

According to EC No 1907/2006 as amended as at the date of this SDS

## **Acetylene**

Version Revision Date: SDS Number: Date of last issue: 28.03.2023

3.2 18.08.2023 800001006002 Print Date 26.08.2023

Thermally unstable.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames, and sparks.

Exposure to air.

Extremes of temperature and direct sunlight.

10.5 Incompatible materials

Materials to avoid : Copper.

Silver, mercury, halogenous compounds.

Aluminium

Strong oxidising agents.

#### 10.6 Hazardous decomposition products

Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids and gases including carbon monoxide, carbon dioxide, sulphur oxides and unidentified organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation.

### **SECTION 11: Toxicological information**

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of:

exposure

Inhalation is the primary route of exposure although absorption may occur through skin contact or following accidental

ingestion.

### **Acute toxicity**

### **Components:**

acetylene:

Acute inhalation toxicity : LC 50 (Rat, male): > 150000 mg/m3

Exposure time: 4 h Test atmosphere: gas

Method: Acceptable non-standard method.

Remarks: Based on available data, the classification criteria

are not met.

### Skin corrosion/irritation

### **Components:**

acetylene:

Remarks : Rapid release of gases which are liquids under pressure may

cause frost burns of exposed tissues (skin, eye) due to evapo-

rative cooling.

According to EC No 1907/2006 as amended as at the date of this SDS

## **Acetylene**

Version Revision Date: SDS Number: Date of last issue: 28.03.2023

3.2 18.08.2023 800001006002 Print Date 26.08.2023

### Serious eye damage/eye irritation

#### **Components:**

acetylene:

Remarks : Rapid release of gases which are liquids under pressure may

cause frost burns of exposed tissues (skin, eye) due to evapo-

rative cooling.

### Germ cell mutagenicity

### **Components:**

acetylene:

Genotoxicity in vitro : Method: OECD Test Guideline 471

Remarks: Based on available data, the classification criteria

are not met.

Method: OECD Test Guideline 473

Remarks: Based on available data, the classification criteria

are not met.

Method: OECD Test Guideline 476

Remarks: Based on available data, the classification criteria

are not met.

Germ cell mutagenicity- As-

sessment

This product does not meet the criteria for classification in

categories 1A/1B.

## Carcinogenicity

### **Components:**

### acetylene:

Species : Rat, male and female

Application Route : Inhalation

Method : Acceptable non-standard method.

Remarks : Based on available data, the classification criteria are not met.

Carcinogenicity - Assess-

ment

This product does not meet the criteria for classification in

categories 1A/1B.

Material	GHS/CLP Carcinogenicity Classification
acetylene	No carcinogenicity classification.

According to EC No 1907/2006 as amended as at the date of this SDS

## **Acetylene**

Version Revision Date: SDS Number: Date of last issue: 28.03.2023

3.2 18.08.2023 800001006002 Print Date 26.08.2023

### Reproductive toxicity

#### **Components:**

acetylene:

Effects on fertility

Remarks: Based on available data, the classification criteria

are not met.

Reproductive toxicity - As-

sessment

This product does not meet the criteria for classification in

categories 1A/1B.

### STOT - single exposure

#### **Components:**

acetylene:

Remarks : Based on available data, the classification criteria are not met.

Inhalation of vapours or mists may cause irritation to the res-

piratory system.

High gas concentrations will displace available air; unconsciousness and death may occur suddenly from lack of oxy-

gen.

### STOT - repeated exposure

### **Components:**

acetylene:

Remarks : Based on available data, the classification criteria are not met.

### **Aspiration toxicity**

#### Components:

#### acetylene:

Based on available data, the classification criteria are not met.

#### 11.2 Information on other hazards

### **Endocrine disrupting properties**

### **Product:**

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

According to EC No 1907/2006 as amended as at the date of this SDS

## Acetylene

Date of last issue: 28.03.2023 Version Revision Date: SDS Number:

3.2 18.08.2023 800001006002 Print Date 26.08.2023

#### **Further information**

**Product:** 

Remarks Unless indicated otherwise, the data presented is representa-

tive of the product as a whole, rather than for individual com-

ponent(s).

**Components:** 

acetylene:

Classifications by other authorities under varying regulatory Remarks

frameworks may exist.

### **SECTION 12: Ecological information**

### 12.1 Toxicity

### Components:

acetylene:

Toxicity to fish LC50 (Fish (freshwater)): 545 mg/l

Exposure time: 96 h

Method: Based on quantitative structure-activity relationship

(QSAR) modelling

Remarks: Practically non toxic: LL/EL/IL50 > 100 mg/l

Toxicity to daphnia and other :

aquatic invertebrates

LC50 (Daphnia (water flea)): 242 mg/l

Exposure time: 48 h

Method: Based on quantitative structure-activity relationship

(QSAR) modelling

Remarks: Practically non toxic: LL/EL/IL50 > 100 mg/l

EC50 (green algae): 57 mg/l Toxicity to algae/aquatic plants

Exposure time: 96 h

Method: Based on quantitative structure-activity relationship

(QSAR) modelling

Remarks: Data not available

Toxicity to microorganisms

Remarks: Data not available

Toxicity to fish (Chronic tox-

icity)

Remarks: Data not available

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

ic toxicity)

Remarks: Data not available

According to EC No 1907/2006 as amended as at the date of this SDS

## **Acetylene**

Version Revision Date: SDS Number: Date of last issue: 28.03.2023

3.2 18.08.2023 800001006002 Print Date 26.08.2023

### 12.2 Persistence and degradability

#### **Components:**

acetylene:

Biodegradability : Biodegradation: 50 %

Exposure time: 3 d

Method: Based on quantitative structure-activity relationship

(QSAR) modelling

Remarks: Readily biodegradable.

Oxidises rapidly by photo-chemical reactions in air.

### 12.3 Bioaccumulative potential

### **Components:**

acetylene:

Bioaccumulation : Remarks: Does not bioaccumulate significantly.

### 12.4 Mobility in soil

### **Components:**

acetylene:

Mobility : Remarks: Because of their extreme volatility, air is the only

environmental compartment that hydrocarbon gases will be

found.

#### 12.5 Results of PBT and vPvB assessment

### **Components:**

acetylene:

Assessment : The substance does not fulfill all screening criteria for persis-

tence, bioaccumulation and toxicity and hence is not consid-

ered to be PBT or vPvB..

#### 12.6 Endocrine disrupting properties

#### **Product:**

Assessment : The substance/mixture does not contain components considered to

have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### 12.7 Other adverse effects

#### **Product:**

Additional ecological infor-

mation

Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

According to EC No 1907/2006 as amended as at the date of this SDS

## **Acetylene**

Version Revision Date: SDS Number: Date of last issue: 28.03.2023

3.2 18.08.2023 800001006002 Print Date 26.08.2023

## **Components:**

#### acetylene:

Additional ecological infor-

mation

: In view of the high rate of loss from solution, the product is unlikely

to pose a significant hazard to aquatic life.

## **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Product : Recover or recycle if possible.

It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal meth-

ods in compliance with applicable regulations.

Do not dispose into the environment, in drains or in water

courses.

Waste product should not be allowed to contaminate soil or

water.

Disposal should be in accordance with applicable regional,

national, and local laws and regulations.

Local regulations may be more stringent than regional or na-

tional requirements and must be complied with.

Contaminated packaging : Data not available

### **SECTION 14: Transport information**

### 14.1 UN number or ID number

ADR : 1001 RID : 1001 IMDG : 1001

### 14.2 UN proper shipping name

ADR : ACETYLENE, DISSOLVED

RID : ACETYLENE, DISSOLVED

IMDG : ACETYLENE, DISSOLVED

### 14.3 Transport hazard class(es)

 ADR
 : 2

 RID
 : 2

 IMDG
 : 2.1

According to EC No 1907/2006 as amended as at the date of this SDS

## **Acetylene**

Version Revision Date: SDS Number: Date of last issue: 28.03.2023

3.2 18.08.2023 800001006002 Print Date 26.08.2023

14.4 Packing group

CDNI Inland Water Waste : NST 3302 Other natural gases

Agreement

**ADR** 

Packing group : Not assigned by regulation

Classification Code : 4F Hazard Identification Number : 239 Labels : 2.1

**RID** 

Packing group : Not assigned by regulation

Classification Code : 4F Hazard Identification Number : 239 Labels : 2.1

**IMDG** 

Packing group : Not assigned by regulation

Labels : 2.1

14.5 Environmental hazards

**ADR** 

Environmentally hazardous : no

rid

Environmentally hazardous : no

**IMDG** 

Marine pollutant : no

14.6 Special precautions for user

Remarks : Special Precautions: Refer to Section 7, Handling & Storage,

for special precautions which a user needs to be aware of or

needs to comply with in connection with transport.

14.7 Maritime transport in bulk according to IMO instruments

Pollution category : Not applicable
Ship type : Not applicable
Product name : Not applicable

### **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - List of substances subject to authorisation : Product is not subject to Authorisation under REACH.

REACH - Candidate List of Substances of Very High : This product does not contain sub-

Concern for Authorisation (Article 59). stances of very high concern (Regulation (EC) No 1907/2006 (REACH),

Article 57).

According to EC No 1907/2006 as amended as at the date of this SDS

## Acetylene

Version Revision Date: SDS Number: Date of last issue: 28.03.2023

3.2 18.08.2023 800001006002 Print Date 26.08.2023

Seveso III: Directive 2012/18/EU of the Euro- 19 Acetylene pean Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

#### Other regulations:

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

Product is subject to Major accident risk decision 2015 (BRZO+) based on Seveso III directive (2012/18/EU).

### The components of this product are reported in the following inventories:

TSCA : Listed

AIIC : Listed

DSL : Listed

IECSC : Listed

ENCS : Listed

KECI : Listed

NZIoC : Listed

PICCS : Listed

TCSI : Listed

### 15.2 Chemical safety assessment

A Chemical Safety Assessment has been carried out for this substance.

### **SECTION 16: Other information**

### Full text of other abbreviations

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergen-

According to EC No 1907/2006 as amended as at the date of this SDS

## Acetylene

Version Revision Date: SDS Number: Date of last issue: 28.03.2023

3.2 18.08.2023 800001006002 Print Date 26.08.2023

cy Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI -Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### **Further information**

Training advice : Provide adequate information, instruction and training for op-

erators.

Other information : For Industry guidance and tools on REACH please visit the

CEFIC website at http://cefic.org/Industry-support.

The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not consid-

ered to be PBT or vPvB.

A vertical bar (|) in the left margin indicates an amendment

from the previous version.

Sources of key data used to compile the Safety Data

Sheet

The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU

IUCLID date base, EC 1272 regulation, etc).

Identified Uses according to the Use Descriptor System

**Uses - Worker** 

Title : Manufacture of substance- Industrial

**Uses - Worker** 

Title : - IndustrialUse as an intermediate

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guid-

According to EC No 1907/2006 as amended as at the date of this SDS

## **Acetylene**

Version Revision Date: SDS Number: Date of last issue: 28.03.2023

3.2 18.08.2023 800001006002 Print Date 26.08.2023

ance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

NL / EN

According to EC No 1907/2006 as amended as at the date of this SDS

# **Acetylene**

Version Revision Date: SDS Number: Date of last issue: 28.03.2023

3.2 18.08.2023 800001006002 Print Date 26.08.2023

**Exposure Scenario - Worker** 

Exposure oceriano - Worke	,,
300000010081	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Manufacture of substance- Industrial
Use Descriptor	Sector of Use: SU3, SU8, SU9 Process Categories: PROC1, PROC2, PROC3, PROC8a, PROC8b, PROC15 Environmental Release Categories: ERC1, ERC4
Scope of process	Manufacture of the substance or use as a process chemical or extraction agent. Includes recycling/ recovery, material transfers, storage, maintenance and loading (including marine vessel/barge, road/rail car and bulk container), sampling and associated laboratory activities.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT
	MEASURES

Section 2.1	Control of Worker Exposure	
<b>Product Characteristics</b>		
Physical form of product	Gas/liquefied gas	
Concentration of the Sub-	Covers use of substance/product up to 100% (unless stated	
stance in Mixture/Article	differently).,	
Frequency and Duration of Use		
Covers daily exposures up to 8 hours (unless stated differently).		
Other Operational Conditions affecting Exposure		
Assumes a good basic standard of occupational hygiene is implemented.		

Contributing Scenarios	Risk Management Measures
General measures (Flammable gas)	Risks from the physicochemical hazards of substances, such as flammability or explosiveness can be controlled by implementing risk management measures at the workplace. It is recommended to follow the ATEX Directive 2014/34/EU and its subsequent updates.  Based on the implementation of a selection of handling and storage risk management measures for the identified uses, the risk can be regarded as controlled to an acceptable level. Use in contained systems.  Avoid ignition sources – No smoking.  Handle in well-ventilated area to prevent formation of explosive atmosphere.  Use equipment and protective systems approved for flammable substances.  Restrict line velocity during pumping to avoid generation of electrostatic discharge.
	Ground/bond container and receiving equipment.

According to EC No 1907/2006 as amended as at the date of this SDS

# **Acetylene**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 28.03.2023

 3.2
 18.08.2023
 800001006002
 Print Date 26.08.2023

Use non-sparking tools. Comply with relevant EU/national regulations. Review Safety Data Sheet for additional advice.	ply with relevant EU/national regulations.
---	--

Section 2.2	Control of Environmental Exposure	
Not applicable.		
Frequency and Duration of	Use	
Not applicable.		
<b>Environmental factors not</b>	influenced by risk management	
Not applicable.		
Other Operational Condition	ons affecting Environmental Exposure	
Not applicable.		
Technical conditions and n	neasures at process level (source) to pre	event release
Not applicable.		
Technical onsite condition	s and measures to reduce or limit discha	arges, air emis-
sions and releases to soil		
Not applicable.		
	o prevent/limit release from site	
Not applicable.		
Conditions and Measures r	related to municipal sewage treatment pl	ant
Not applicable.		
Conditions and Measures related to external treatment of waste for disposal		
Not applicable.		
Conditions and measures i	related to external recovery of waste	
Not applicable.		

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
Risk Management Measures are based on qualitative risk characterisation.	

Section 3.2 -Environment	
Not applicable.	

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO	
Section 4.1 - Health		
Not applicable.		

Section 4.2 -Environment	
Not applicable.	

According to EC No 1907/2006 as amended as at the date of this SDS

# **Acetylene**

Version Revision Date: SDS Number: Date of last issue: 28.03.2023

3.2 18.08.2023 800001006002 Print Date 26.08.2023

**Exposure Scenario - Worker** 

SECTION 1	EXPOSURE SCENARIO TITLE
Title	- IndustrialUse as an intermediate
Use Descriptor	Sector of Use: SU3, SU8, SU9 Process Categories: PROC1, PROC2, PROC3, PROC8a, PROC8b, PROC15 Environmental Release Categories: ERC6a
Scope of process	Use of substance as an intermediate (not related to Strictly Controlled Conditions). Includes recycling/ recovery, material transfers, storage, sampling, associated laboratory activities, maintenance and loading (including marine vessel/barge, road/rail car and bulk container).

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT
	MEASURES

Section 2.1	Control of Worker Exposure
Product Characteristics	
Physical form of product	Gas/liquefied gas
Concentration of the Sub-	Covers use of substance/product up to 100% (unless stated
stance in Mixture/Article	differently).,
Frequency and Duration o	f Use
Covers daily exposures up t	o 8 hours (unless stated differently).
Other Operational Condition	ons affecting Exposure
Assumes a good basic stand	dard of occupational hygiene is implemented.

Contributing Scenarios	Risk Management Measures
General measures (Flammable gas)	Risks from the physicochemical hazards of substances, such as flammability or explosiveness can be controlled by implementing risk management measures at the workplace. It is recommended to follow the ATEX Directive 2014/34/EU and its subsequent updates.  Based on the implementation of a selection of handling and storage risk management measures for the identified uses, the risk can be regarded as controlled to an acceptable level. Use in contained systems.  Avoid ignition sources – No smoking.  Handle in well-ventilated area to prevent formation of explosive atmosphere.  Use equipment and protective systems approved for flammable substances.  Restrict line velocity during pumping to avoid generation of electrostatic discharge.
	Use equipment and protective systems approved for flammable substances.  Restrict line velocity during pumping to avoid generation of

According to EC No 1907/2006 as amended as at the date of this SDS

# **Acetylene**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 28.03.2023

 3.2
 18.08.2023
 800001006002
 Print Date 26.08.2023

	Use non-sparking tools. Comply with relevant EU/national regulations. Review Safety Data Sheet for additional advice.	
--	---	--

Section 2.2	Control of Environmental Exposure	
Not applicable.		
Frequency and Duration of	Use	
Not applicable.		
<b>Environmental factors not</b>	influenced by risk management	
Not applicable.		
Other Operational Condition	ons affecting Environmental Exposure	
Not applicable.		
Technical conditions and n	neasures at process level (source) to pre	event release
Not applicable.		
Technical onsite condition	s and measures to reduce or limit discha	arges, air emis-
sions and releases to soil		
Not applicable.		
	o prevent/limit release from site	
Not applicable.		
Conditions and Measures r	related to municipal sewage treatment pl	lant
Not applicable.		
Conditions and Measures r	elated to external treatment of waste for	<sup>·</sup> disposal
Not applicable.		
Conditions and measures i	related to external recovery of waste	
Not applicable.		

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
Risk Management Measures	are based on qualitative risk characterisation.

Section 3.2 -Environment	
Not applicable.	

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	
Not applicable.	

Section 4.2 -Environment	
Not applicable.	

According to EC No 1907/2006 as amended as at the date of this SDS

# **Acetylene**

Version Revision Date: SDS Number: Date of last issue: 28.03.2023

3.2 18.08.2023 800001006002 Print Date 26.08.2023