Methyl DIPROXITOL

Version 6.0 Revision Date 01.11.2023 Print Date 08.11.2023

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Methyl DIPROXITOL

Product code : U5139

CAS-No. : 34590-94-8

Other means of identification : 2-(2-methoxymethylethoxy)propanol, DPGME, DPM, Methoxy

dipropanol

Manufacturer or supplier's details

Supplier :

SHELL EASTERN CHEMICALS (S)

A REGISTERED BUSINESS OF SHELL EASTERN

TRADING (PTE) LTD (UEN:198902087C)

9 North Buona Vista Drive, #07-01

The Metropolis Tower 1 Singapore 138588

Singapore

Telephone : +65 6384 8269 Telefax : +65 6384 8454

Contact for Safety Data

Emergency telephone

Sheet

number

: +800 2537 8747 (ALERT SGS- toll Free) or +65 6542 9595

(ALERT SGS)

Recommended use of the chemical and restrictions on use

Recommended use : Speciality solvent.

Restrictions on use : This product must not be used in applications other than the

above without first seeking the advice of the supplier.

Other information : DIPROXITOL is a trademark owned by Shell Trademark

Management B.V. and Shell Brands Inc. and used by affiliates

of Shell plc.

2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids : Category 4

GHS label elements

Hazard pictograms : No Hazard Symbol required

Signal word : Warning

1 / 19 800001004876 SG

Methyl DIPROXITOL

Version 6.0 Revision Date 01.11.2023 Print Date 08.11.2023

Hazard statements : PHYSICAL HAZARDS:

Combustible liquid. HEALTH HAZARDS:

Not classified as a health hazard under GHS criteria.

ENVIRONMENTAL HAZARDS:

Not classified as an environmental hazard under GHS criteria.

Precautionary statements

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames

and other ignition sources. No smoking.

P280 Wear protective gloves/ protective clothing/ eye

protection/ face protection.

Response:

P370 + P378 In case of fire: Use appropriate media to extinguish.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

Disposal:

P501 Dispose of contents and container to appropriate waste site or reclaimer in accordance with local and national

regulations.

Other hazards which do not result in classification

Vapours are heavier than air. Vapours may travel across the ground and reach remote ignition sources causing a flashback fire danger. Even with proper grounding and bonding, this material can still accumulate an electrostatic charge. If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Substance

Hazardous components

Chemical name	CAS-No.	Classification	Concentration (%
			w/w)
Dipropylene glycol methyl ether	34590-94-8	Flam. Liq.4; H227	<= 100
2-methoxypropanol	1589-47-5	Flam. Liq.3; H226 Skin Irrit.2; H315 Eye Dam.1; H318 STOT SE3; H335 Repr.1B; H360	< 0.1

For explanation of abbreviations see section 16.

Methyl DIPROXITOL

Version 6.0 Revision Date 01.11.2023 Print Date 08.11.2023

4. FIRST-AID MEASURES

General advice : Not expected to be a health hazard when used under normal

conditions.

If inhaled : No treatment necessary under normal conditions of use.

If symptoms persist, obtain medical advice.

In case of skin contact : Remove contaminated clothing. Flush exposed area with

> water and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention.

In case of eye contact : Flush eye with copious quantities of water.

Remove contact lenses, if present and easy to do. Continue

rinsing.

If persistent irritation occurs, obtain medical attention.

If swallowed In general no treatment is necessary unless large quantities

are swallowed, however, get medical advice.

Most important symptoms and effects, both acute and

delayed

: Not considered to be an inhalation hazard under normal

conditions of use.

Possible respiratory irritation signs and symptoms may include

a temporary burning sensation of the nose and throat,

coughing, and/or difficulty breathing.

No specific hazards under normal use conditions.

Skin irritation signs and symptoms may include a burning

sensation, redness, or swelling.

Eye irritation signs and symptoms may include a burning

sensation, redness, swelling, and/or blurred vision.

Ingestion may result in nausea, vomiting and/or diarrhoea. Breathing of high vapour concentrations may cause central nervous system (CNS) depression resulting in dizziness, lightheadedness, headache, nausea and loss of coordination. Continued inhalation may result in unconsciousness and

death.

Protection of first-aiders : When administering first aid, ensure that you are wearing the

appropriate personal protective equipment according to the

incident, injury and surroundings.

Potential for chemical pneumonitis. Notes to physician

Call a doctor or poison control center for guidance.

Causes central nervous system depression.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Alcohol-resistant foam, water spray or fog. Dry chemical

powder, carbon dioxide, sand or earth may be used for small

fires only.

3/19 800001004876 SG

Methyl DIPROXITOL

Version 6.0 Revision Date 01.11.2023 Print Date 08.11.2023

Unsuitable extinguishing

media

: None

Specific hazards during

firefighting

: The vapour is heavier than air, spreads along the ground and

distant ignition is possible.

Carbon monoxide may be evolved if incomplete combustion

occurs.

Specific extinguishing

methods

: Standard procedure for chemical fires.

Clear fire area of all non-emergency personnel.

Keep adjacent containers cool by spraying with water.

Special protective equipment

for firefighters

: Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to

relevant Standards (e.g. Europe: EN469).

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

: Observe the relevant local and international regulations Notify authorities if any exposure to the general public or the environment occurs or is likely to occur.

Local authorities should be advised if significant spillages

cannot be contained.

The vapour is heavier than air, spreads along the ground and distant ignition is possible.

Vapour may form an explosive mixture with air.

: Avoid contact with skin, eyes and clothing.

Isolate hazard area and deny entry to unnecessary or

unprotected personnel.

Stay upwind and keep out of low areas.

Environmental precautions

: Shut off leaks, if possible without personal risks. Remove all possible sources of ignition in the surrounding area. Use

appropriate containment to avoid environmental

contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. Attempt to disperse the vapour or to direct its flow to a safe location for example by using fog sprays. Take precautionary measures against static discharge. Ensure electrical continuity by bonding and grounding (earthing) all equipment.

Ventilate contaminated area thoroughly. Monitor area with combustible gas indicator.

Methods and materials for containment and cleaning up : For large liquid spills (> 1 drum), transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak

Methyl DIPROXITOL

Version 6.0 Revision Date 01.11.2023 Print Date 08.11.2023 up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely For small liquid spills (< 1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely. Additional advice : For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet. For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.

7. HANDLING AND STORAGE

General Precautions : Avoid breathing of or direct contact with material. Only use in

> well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see

Section 8 of this Safety Data Sheet.

Use the information in this data sheet as input to a risk assessment of local circumstances to help determine

appropriate controls for safe handling, storage and disposal of

this material.

Ensure that all local regulations regarding handling and

storage facilities are followed.

Advice on safe handling Avoid contact with skin, eyes and clothing.

Use local exhaust ventilation if there is risk of inhalation of

vapours, mists or aerosols.

Bulk storage tanks should be diked (bunded).

Extinguish any naked flames. Do not smoke. Remove ignition

sources. Avoid sparks.

Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment

to reduce the risk.

The vapours in the head space of the storage vessel may lie

in the flammable/explosive range and hence may be

flammable.

Properly dispose of any contaminated rags or cleaning

materials in order to prevent fires.

Do NOT use compressed air for filling, discharging, or

handling operations.

Avoidance of contact : Strong oxidising agents.

Product Transfer : Refer to guidance under Handling section.

Storage

Conditions for safe storage The vapour is heavier than air. Beware of accumulation in pits

and confined spaces.

Refer to section 15 for any additional specific legislation covering the packaging and storage of this product.

5/19 800001004876 SG

Methyl DIPROXITOL

Version 6.0	Revision Date 01.11.2023 Pr		Print Date 08.11.2023
Packaging material	:	Suitable material: For containers, or containers, o	•
Container Advice	:	Containers, even those that have been explosive vapours. Do not cut, drill, gri similar operations on or near container	ind, weld or perform
Specific use(s)	:	Not applicable	
		Ensure that all local regulations regarding handling and storage facilities are followed. See additional references that provide safe handling practice American Petroleum Institute 2003 (Protection Against Ignitions Arising out of Static, Lightning and Stray Currents) of National Fire Protection Agency 77 (Recommended Practices on Static Electricity). IEC/TS 60079-32-1: Electrostatic hazards, guidance	

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Dipropylene glycol methyl ether	34590-94-8	PEL (long term)	100 ppm 606 mg/m3	SG OEL
Dipropylene glycol methyl ether		PEL (short term)	150 ppm 909 mg/m3	SG OEL
Dipropylene glycol methyl ether	34590-94-8	TWA	100 ppm 600 mg/m3	OSHA Z-1
Dipropylene glycol methyl ether	34590-94-8	TWA	50 ppm	ACGIH

Biological occupational exposure limits

No biological limit allocated.

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Methyl DIPROXITOL

Version 6.0 Revision Date 01.11.2023 Print Date 08.11.2023

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany http://www.dauv.de/inhalt/index.isp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

Engineering measures

: Use sealed systems as far as possible.

Adequate explosion-proof ventilation to control airborne concentrations below the exposure guidelines/limits.

Local exhaust ventilation is recommended.

Firewater monitors and deluge systems are recommended.

Eye washes and showers for emergency use.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated. The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

General Information:

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating. drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

Personal protective equipment

Protective measures

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Respiratory protection

: If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are unsuitable (e.g. airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus.

Methyl DIPROXITOL

Version 6.0 Revision Date 01.11.2023 Print Date 08.11.2023

Where air-filtering respirators are suitable, select an appropriate combination of mask and filter.

If air-filtering respirators are suitable for conditions of use: Select a filter suitable for organic gases and vapours [Type A

boiling point >65°C (149°F)].

Hand protection Remarks

Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. Longer term protection: Nitrile rubber gloves. Incidental contact/Splash protection: PVC, neoprene or nitrile rubber gloves For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

Eye protection

If material is handled such that it could be splashed into eyes, protective eyewear is recommended.

Skin and body protection

Skin protection is not required under normal conditions of use. For prolonged or repeated exposures use impervious clothing over parts of the body subject to exposure.

If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to relevant Standard,

and provide employee skin care programmes.

Wear antistatic and flame-retardant clothing, if a local risk

assessment deems it so.

Thermal hazards : Not applicable

Environmental exposure controls

General advice : Local guidelines on emission limits for volatile substances

must be observed for the discharge of exhaust air containing

vapour.

Methyl DIPROXITOL

Version 6.0 Revision Date 01.11.2023 Print Date 08.11.2023

Minimise release to the environment. An environmental assessment must be made to ensure compliance with local

environmental legislation.

Information on accidental release measures are to be found in

section 6.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : clear
Odour : Ethereal

Odour Threshold : Data not available pH : Not applicable Melting / freezing point : -83 °C / -117 °F

Boiling point/boiling range : 184 - 190 °C / 363 - 374 °F

Flash point : 75 °C / 167 °F

Method: ASTM D-93 / PMCC

Evaporation rate : 0.01

Method: ASTM D 3539, nBuAc=1

Flammability (solid, gas) : Data not available

Upper explosion limit : 14 %(V)

Lower explosion limit : 1.1 %(V)

Vapour pressure : 37.1 Pa (25 °C / 77 °F)

Relative vapour density : Data not available

Relative density : 0.95 - 0.96 (20 °C / 68 °F)

Method: ASTM D4052

Density : 952 - 956 kg/m3 (20 °C / 68 °F)

Method: ASTM D4052

Solubility(ies)

Water solubility : completely soluble (25 °C / 77 °F)

Partition coefficient: n-

octanol/water

: log Pow: < 0.01

Auto-ignition temperature : 205 °C / 401 °F

9 / 19 800001004876 SG

Methyl DIPROXITOL

Version 6.0 Revision Date 01.11.2023 Print Date 08.11.2023

Decomposition temperature : Data not available

Viscosity

Viscosity, dynamic : Data not available

: 4.55 mm2/s (20 °C / 68 °F) Viscosity, kinematic

Method: ASTM D445

Explosive properties : Not applicable Oxidizing properties : Data not available

: 68.7 mN/m, 20 °C / 68 °F Surface tension

: Electrical conductivity: > 10,000 pS/m Conductivity

> A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid, This material is not expected to be

a static accumulator.

Particle size : Data not available

Molecular weight : 148.2 g/mol

10. STABILITY AND REACTIVITY

: The product does not pose any further reactivity hazards in Reactivity

addition to those listed in the following sub-paragraph.

: No hazardous reaction is expected when handled and stored Chemical stability

according to provisions

Possibility of hazardous

Conditions to avoid

reactions

: Reacts with strong oxidising agents.

: Avoid heat, sparks, open flames and other ignition sources.

Prevent vapour accumulation.

In certain circumstances product can ignite due to static

electricity.

Incompatible materials : Strong oxidising agents.

Hazardous decomposition

products

Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids and gases

including carbon monoxide, carbon dioxide, sulphur oxides and unidentified organic compounds will be evolved when this

material undergoes combustion or thermal or oxidative

degradation.

Methyl DIPROXITOL

Version 6.0 Revision Date 01.11.2023 Print Date 08.11.2023

11. TOXICOLOGICAL INFORMATION

Basis for assessment : Information given is based on product testing.

> Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s). Information given is based on product

Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for

individual component(s).

exposure

Information on likely routes of : Exposure may occur via inhalation, ingestion, skin absorption,

skin or eye contact, and accidental ingestion.

Acute toxicity

Product:

: LD50 Rat: > 5000 mg/kg Acute oral toxicity

Remarks: Low toxicity

: Remarks: Breathing of high vapour concentrations may cause Acute inhalation toxicity

central nervous system (CNS) depression resulting in dizziness, light-headedness, headache and nausea.

Low toxicity if inhaled.

Based on available data, the classification criteria are not met.

Acute dermal toxicity : LD50 Rabbit: > 5000 mg/kg

Remarks: Low toxicity

Components:

Dipropylene glycol methyl ether:

Acute oral toxicity : LD50 Rat: > 5000 mg/kg

Remarks: Low toxicity

Acute inhalation toxicity : Remarks: Breathing of high vapour concentrations may cause

> central nervous system (CNS) depression resulting in dizziness, light-headedness, headache and nausea.

Low toxicity if inhaled.

Based on available data, the classification criteria are not met.

: LD50 Rabbit: > 5000 mg/kg Acute dermal toxicity

Remarks: Low toxicity

Skin corrosion/irritation

Product:

Remarks: Not irritating to skin.

Components:

Dipropylene glycol methyl ether:

Methyl DIPROXITOL

Version 6.0 Revision Date 01.11.2023 Print Date 08.11.2023

Remarks: Not irritating to skin.

Serious eye damage/eye irritation

Product:

Remarks: Slightly irritating to the eye., Based on available data, the classification criteria are not met.

Components:

Dipropylene glycol methyl ether:

Remarks: Slightly irritating to the eye., Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Product:

Test Method: Skin sensitisation Remarks: Not a sensitiser.

Based on available data, the classification criteria are not met.

Components:

Dipropylene glycol methyl ether:

Test Method: Skin sensitisation Remarks: Not a sensitiser.

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Product:

: Remarks: No evidence of mutagenic activity.

Components:

Dipropylene glycol methyl ether:

: Remarks: No evidence of mutagenic activity.

Carcinogenicity

Product:

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

Components:

Dipropylene glycol methyl ether:

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

Material	GHS/CLP Carcinogenicity Classification
Dipropylene glycol methyl ether	No carcinogenicity classification.

Methyl DIPROXITOL

Ve	rsion 6.0	Revision Date 01.11.2023	Print Date 08.11.2023
	2-methoxypropanol	No carcinogenicity classification.	

Reproductive toxicity

Product:

Remarks: Not a developmental toxicant., Based on available data, the classification criteria are not met., Does not impair fertility.

Components:

Dipropylene glycol methyl ether:

Remarks: Not a developmental toxicant., Based on available data, the classification criteria are not met., Does not impair fertility.

STOT - single exposure

Product:

Remarks: Inhalation of vapours or mists may cause irritation to the respiratory system.

Components:

Dipropylene glycol methyl ether:

Remarks: Inhalation of vapours or mists may cause irritation to the respiratory system.

STOT - repeated exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

Components:

Dipropylene glycol methyl ether:

Remarks: Based on available data, the classification criteria are not met.

Aspiration toxicity

Product:

Not an aspiration hazard.

Components:

Dipropylene glycol methyl ether:

Not an aspiration hazard.

Further information

Methyl DIPROXITOL

Version 6.0 Revision Date 01.11.2023 Print Date 08.11.2023

Product:

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

Components:

Dipropylene glycol methyl ether:

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

12. ECOLOGICAL INFORMATION

Basis for assessment : Information given is based on product testing.

> Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s). Information given is based on product

testing.

Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for

individual component(s).

Ecotoxicity

Product:

Toxicity to fish (Acute

toxicity)

Remarks: Practically non toxic:

LL/EL/IL50 > 100 mg/l

Toxicity to crustacean (Acute

toxicity)

Remarks: Practically non toxic:

LL/EL/IL50 > 100 mg/l

Toxicity to algae/aquatic

plants (Acute toxicity)

Remarks: Practically non toxic:

LL/EL/IL50 > 100 mg/l

Toxicity to microorganisms

(Acute toxicity)

: Remarks: Practically non toxic:

LL/EL/IL50 > 100 mg/l

Components:

Dipropylene glycol methyl ether:

Toxicity to fish (Acute : Remarks: Practically non toxic:

toxicity) LL/EL/IL50 > 100 mg/l

Toxicity to crustacean (Acute

toxicity)

: Remarks: Practically non toxic:

LL/EL/IL50 > 100 mg/l

Toxicity to algae/aquatic

plants (Acute toxicity)

: Remarks: Practically non toxic:

LL/EL/IL50 > 100 mg/l

Toxicity to microorganisms

(Acute toxicity)

: Remarks: Practically non toxic:

LL/EL/IL50 > 100 mg/l

14/19 800001004876 SG

Methyl DIPROXITOL

Version 6.0 Revision Date 01.11.2023 Print Date 08.11.2023

Persistence and degradability

Product:

Biodegradability : Remarks: Readily biodegradable., Oxidises rapidly by photo-

chemical reactions in air.

Components:

Dipropylene glycol methyl ether:

Biodegradability : Remarks: Readily biodegradable.

Oxidises rapidly by photo-chemical reactions in air.

Bioaccumulative potential

Product:

Bioaccumulation : Remarks: Does not bioaccumulate significantly.

Partition coefficient: n- : log Pow: < 0.01

octanol/water **Components:**

Dipropylene glycol methyl ether :

Bioaccumulation : Remarks: Does not bioaccumulate significantly.

Mobility in soil

Product:

Mobility : Remarks: If product enters soil, one or more constituents will

be mobile and may contaminate groundwater., Dissolves in

water.

Components:

Dipropylene glycol methyl ether:

Mobility : Remarks: If product enters soil, one or more constituents will

be mobile and may contaminate groundwater., Dissolves in

water.

Other adverse effects

Product:

Results of PBT and vPvB

assessment

: The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not

considered to be PBT or vPvB.

Additional ecological

information

: Data not available

Components:

Dipropylene glycol methyl ether:

Results of PBT and vPvB

assessment

: The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not

considered to be PBT or vPvB.

Additional ecological

information

: Data not available

Methyl DIPROXITOL

Version 6.0 Revision Date 01.11.2023 Print Date 08.11.2023

13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Recover or recycle if possible.

It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Do not dispose into the environment, in drains or in water courses.

Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment. Waste, spills or used product is dangerous waste.

Disposal should be in accordance with applicable regional,

national, and local laws and regulations.

Local regulations may be more stringent than regional or national requirements and must be complied with.

MARPOL - see International Convention for the Prevention of Pollution from Ships (MARPOL 73/78) which provides technical aspects at controlling pollutions from ships.

Contaminated packaging : [

Drain container thoroughly.

After draining, vent in a safe place away from sparks and fire.

Residues may cause an explosion hazard. Do not, puncture, cut, or weld uncleaned drums. Send to drum recoverer or metal reclaimer.

Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand.

14. TRANSPORT INFORMATION

International Regulations

ADR

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Maritime transport in bulk according to IMO instruments

Pollution category : Z Ship type : 3

Product name : Poly (2-8) alkylene glycol monoalkyl (C1-C6) ether

Special precautions for user

Methyl DIPROXITOL

Version 6.0	Revision Date 01.11.2023	Print Date 08.11.2023	
Remarks	for special precautions which a us	: Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.	
Additional Information	 This product may be transported Nitrogen is an odourless and invision nitrogen may cause asphyxiation observe strict safety precautions confined space entry. Transport in bulk according to An Code 	sible gas. Exposure to or death. Personnel must when involved with a	

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Local Regulations

Workplace Safety and Health Act & Workplace	This product is subject to the SDS, Labelling,
Safety and Health (General Provision)	PEL and other requirements in the Act/
Regulations	Regulations.
rregulations	Regulations.
Fire Safety Act and Fire Safety (Petroleum &	This product is not subject to the requirements
Flammable Materials) Regulations	in the Act/Regulations.
Tiaminable Waterials) Regulations	in the Activegulations.
Maritime and Port Authority of Singapore	This product is subject to the requirements of
(Dangerous Goods, Petroleum and Explosives)	this regulation.
1 ' '	tino regulation.
Regulations	
Environmental Protection and Management Act	This product is not subject to the requirements
and Environmental Protection and	in the Act/Regulations.
	iii tile Activegulations.
Management (Hazardous Substances)	
Regulations	

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

Other international regulations

The components of this product are reported in the following inventories:

AIIC : Listed DSL : Listed **IECSC** : Listed **ENCS** : Listed KECI : Listed **NZIoC** : Listed **PICCS** : Listed TSCA : Listed TCSI : Listed

Methyl DIPROXITOL

Version 6.0 Revision Date 01.11.2023 Print Date 08.11.2023

16. OTHER INFORMATION

Full text of H-Statements

H226 Flammable liquid and vapour. H227 Combustible liquid.

H315 Causes skin irritation.

H318 Causes serious eye damage.
H335 May cause respiratory irritation.
H360 May damage fortility or the unbe

H360 May damage fertility or the unborn child.

Full text of other abbreviations

Eye Dam. Serious eye damage Flam. Liq. Flammable liquids Repr. Reproductive toxicity

Skin Irrit. Skin irritation

STOT SE Specific target organ toxicity - single exposure

Abbreviations and Acronyms

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 -Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate: NOM - Official Mexican Norm: NTP - National Toxicology Program: NZIoC -New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG -Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Further information

Training advice : Provide adequate information, instruction and training for

operators.

Methyl DIPROXITOL

Other information

Revision Date 01.11.2023

Print Date 08.11.2023

Other information

A vertical bar (|) in the left margin indicates an amendment from the previous version.

Sources of key data used to compile the Safety Data Sheet

: The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID date base, EC 1272 regulation, etc).

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

SG / EN