

# SAFETY DATA SHEET

## Butene-1

Version 3.0

Revision Date 22.02.2022

Print Date 03.09.2022

### 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product name : Butene-1

Product code : V1379, V1475, V1489, E6226, V1499, V1504, V1505, V1515, V1514

CAS-No. : 106-98-9

Synonyms : Butylene, alpha-; Ethyl ethylene; SHOP C4 Olefin

**Manufacturer or supplier's details**

Manufacturer/Supplier : **Shell Chemicals Europe B.V.**  
PO Box 2334  
3000 CH Rotterdam  
Netherlands

Telephone : +31 (0)10 441 5137 +31(0)10 441 5191

Telefax : +31 (0)20 716 8316/ +31 (0)20 713 9230

Emergency telephone number : +44 (0) 1235 239 670 (This telephone number is available 24 hours per day, 7 days per week)

#### Recommended use of the chemical and restrictions on use

Recommended use : Chemical intermediate.

Restrictions on use : This product must not be used in applications other than the above without first seeking the advice of the supplier.

### 2. HAZARDS IDENTIFICATION

#### Classification (REGULATION (EC) No 1272/2008)

Flammable gases : Category 1A

Gases under pressure : Liquefied gas

#### Label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : PHYSICAL HAZARDS:  
H220 Extremely flammable gas.  
H280 Contains gas under pressure; may explode if heated.  
HEALTH HAZARDS:  
Not classified as a health hazard under CLP criteria.

# SAFETY DATA SHEET

## Butene-1

Version 3.0

Revision Date 22.02.2022

Print Date 03.09.2022

### ENVIRONMENTAL HAZARDS:

Not classified as environmental hazard according to CLP criteria.

### Precautionary statements

#### : **Prevention:**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P243 Take action to prevent static discharges.

#### **Response:**

P377 Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

P381 In case of leakage, eliminate all ignition sources.

#### **Storage:**

P410 + P403 Protect from sunlight. Store in a well-ventilated place.

#### **Disposal:**

No precautionary phrases.

### Other hazards

Vapours are heavier than air. Vapours may travel across the ground and reach remote ignition sources causing a flashback fire danger. May form flammable/explosive vapour-air mixture. This material is a static accumulator. Even with proper grounding and bonding, this material can still accumulate an electrostatic charge. If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur. This material is shipped under pressure. High gas concentrations will displace available air; unconsciousness and death may occur suddenly from lack of oxygen. Exposure to rapidly expanding gases may cause frost burns to eyes and/or skin. Inhalation of vapours or mists may cause irritation to the respiratory system. Vapours may cause drowsiness and dizziness.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Substance

### Hazardous components

Chemical name	CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration (% w/w)
but-1-ene	106-98-9	Flam. Gas 1A; H220 Press. Gas Liquefied gas; H280	<= 100

Refer to Chapter 8 for Occupational Exposure Guidelines.

For explanation of abbreviations see section 16.

### Other information

Refer to Chapter 8 for Occupational Exposure Guidelines.

# SAFETY DATA SHEET

## Butene-1

Version 3.0

Revision Date 22.02.2022

Print Date 03.09.2022

### 4. FIRST-AID MEASURES

- |   |   |
|---|---|
| General advice  | : Not expected to be a health hazard when used under normal conditions.   |
| If inhaled  | : Call emergency number for your location / facility.<br>Remove to fresh air. Do not attempt to rescue the victim unless proper respiratory protection is worn. If the victim has difficulty breathing or tightness of the chest, is dizzy, vomiting, or unresponsive, give 100% oxygen with rescue breathing or Cardio-Pulmonary Resuscitation as required and transport to the nearest medical facility.  |
| In case of skin contact                                     | : Slowly warm the exposed area by rinsing with warm water. Transport to the nearest medical facility for additional treatment.  |
| In case of eye contact                                      | : Slowly warm the exposed area by rinsing with warm water. Transport to the nearest medical facility for additional treatment.  |
| If swallowed  | : In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.  |
| Most important symptoms and effects, both acute and delayed | : Respiratory irritation signs and symptoms may include a temporary burning sensation of the nose and throat, coughing, and/or difficulty breathing.<br>Breathing of high vapour concentrations may cause central nervous system (CNS) depression resulting in dizziness, light-headedness, headache, nausea and loss of coordination. Continued inhalation may result in unconsciousness and death.<br><br>Rapid release of gases which are liquids under pressure may cause frost burns of exposed tissues (skin, eye) due to evaporative cooling.<br><br>No specific hazards under normal use conditions. Ingestion may result in nausea, vomiting and/or diarrhoea. |
| Protection of first-aiders                                  | : When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.   |
| Notes to physician  | : IMMEDIATE TREATMENT IS EXTREMELY IMPORTANT!<br>Artificial respiration and/or oxygen may be necessary.<br>Call a doctor or poison control center for guidance.<br>Treat symptomatically.<br>Potential for cardiac sensitisation, particularly in abuse situations. Hypoxia or negative inotropes may enhance these effects. Consider: oxygen therapy.<br>Narcotic at high vapour concentrations.   |

# SAFETY DATA SHEET

## Butene-1

Version 3.0

Revision Date 22.02.2022

Print Date 03.09.2022

### 5. FIRE-FIGHTING MEASURES

#### Flammable properties

Flash point : -79 °C / -110 °F

Ignition temperature : 385 °C / 725 °F

Upper explosion limit : 10 %(V)

Lower explosion limit : 1,6 %(V)

Flammability (solid, gas) : Extremely flammable.

Suitable extinguishing media : Shut off supply. If not possible and no risk to surroundings, let the fire burn itself out.

Unsuitable extinguishing media : Do not use water in a jet.

Specific hazards during firefighting : Sustained fire attack on vessels may result in a Boiling Liquid Expanding Vapor Explosion (BLEVE).  
The vapour is heavier than air, spreads along the ground and distant ignition is possible.  
Contents are under pressure and can explode when exposed to heat or flames.  
As the vapours become lighter than air, the vapours may reach ignition sources at ground or elevated locations.

Specific extinguishing methods : Standard procedure for chemical fires.

Further information : Clear fire area of all non-emergency personnel.  
Keep adjacent containers cool by spraying with water.

Special protective equipment for firefighters : Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Observe the relevant local and international regulations  
Risk of explosion. Inform the emergency services if liquid enters surface water drains.  
Notify authorities if any exposure to the general public or the environment occurs or is likely to occur.  
Local authorities should be advised if significant spillages cannot be contained.

# SAFETY DATA SHEET

## Butene-1

Version 3.0

Revision Date 22.02.2022

Print Date 03.09.2022

- : Avoid contact with skin, eyes and clothing.  
Isolate hazard area and deny entry to unnecessary or unprotected personnel.  
Do not breathe fumes, vapour.  
Do not operate electrical equipment.
- Environmental precautions : Shut off leaks, if possible without personal risks. Remove all possible sources of ignition in the surrounding area and evacuate all personnel. Attempt to disperse the gas or to direct its flow to a safe location for example by using fog sprays. Take precautionary measures against static discharge. Ensure electrical continuity by bonding and grounding (earthing) all equipment. Monitor area with combustible gas meter.
- Methods and materials for containment and cleaning up : Allow to evaporate.  
Attempt to disperse the vapour or to direct its flow to a safe location, for example by using fog sprays. Otherwise treat as for small spillage.
- Additional advice : For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet.  
Risk of explosion. Inform the emergency services if liquid enters surface water drains.  
For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.  
Vapour may form an explosive mixture with air.

## 7. HANDLING AND STORAGE

- General Precautions : Avoid breathing of or direct contact with material. Only use in well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet.  
Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.
- Advice on safe handling : Extinguish any naked flames. Do not smoke. Remove ignition sources. Avoid sparks.  
Avoid inhaling vapour and/or mists.  
Avoid contact with skin, eyes and clothing.  
Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols.  
Bulk storage tanks should be diked (bunded).  
Properly dispose of any contaminated rags or cleaning materials in order to prevent fires.  
Even with proper grounding and bonding, this material can still accumulate an electrostatic charge.  
If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur.

# SAFETY DATA SHEET

## Butene-1

Version 3.0

Revision Date 22.02.2022

Print Date 03.09.2022

Be aware of handling operations that may give rise to additional hazards that result from the accumulation of static charges.

These include but are not limited to pumping (especially turbulent flow), mixing, filtering, splash filling, cleaning and filling of tanks and containers, sampling, switch loading, gauging, vacuum truck operations, and mechanical movements.

These activities may lead to static discharge e.g. spark formation.

Restrict line velocity during pumping in order to avoid generation of electrostatic discharge ( $\leq 1$  m/s until fill pipe submerged to twice its diameter, then  $\leq 7$  m/s). Avoid splash filling.

Do NOT use compressed air for filling, discharging, or handling operations.

The vapour is heavier than air. Beware of accumulation in pits and confined spaces.

Avoidance of contact : Strong oxidising agents.

Product Transfer : Refer to guidance under Handling section.

### Storage

Other data : Keep away from aerosols, flammables, oxidizing agents, corrosives and from products harmful or toxic to man or to the environment.  
Must be stored in a diked (bunded) well-ventilated area, away from sunlight, ignition sources and other sources of heat. Vapours from tanks should not be released to atmosphere. Breathing losses during storage should be controlled by a suitable vapour treatment system.  
Electrostatic charges will be generated during pumping. Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment to reduce the risk.  
The vapours in the head space of the storage vessel may lie in the flammable/explosive range and hence may be flammable.

Packaging material : Suitable material: For containers, or container linings use mild steel, stainless steel.

Container Advice : Containers, even those that have been emptied, can contain explosive vapours. Do not cut, drill, grind, weld or perform similar operations on or near containers.

Specific use(s) : Not applicable

Ensure that all local regulations regarding handling and storage facilities are followed.  
See additional references that provide safe handling practices for liquids that are determined to be static accumulators: American Petroleum Institute 2003 (Protection Against Ignitions Arising out of Static, Lightning and Stray Currents) or

# SAFETY DATA SHEET

## Butene-1

Version 3.0

Revision Date 22.02.2022

Print Date 03.09.2022

National Fire Protection Agency 77 (Recommended Practices on Static Electricity).  
IEC/TS 60079-32-1: Electrostatic hazards, guidance

### 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Data Source
but-1-ene	106-98-9	MPC-TWA (vapour and/or gas)	100 mg/m3	RU OEL
Further information: Class 4 - Low hazard				
		MPC-STEL (vapour and/or gas)	300 mg/m3	RU OEL
Further information: Class 4 - Low hazard				

#### Biological occupational exposure limits

No biological limit allocated.

#### Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods  
<http://www.cdc.gov/niosh/>

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods  
<http://www.osha.gov/>

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances  
<http://www.hse.gov.uk/>

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany  
<http://www.dguv.de/inhalt/index.jsp>

L'Institut National de Recherche et de Sécurité, (INRS), France <http://www.inrs.fr/accueil>

#### Engineering measures

- : Use sealed systems as far as possible.
- Adequate explosion-proof ventilation to control airborne concentrations below the exposure guidelines/limits.
- Local exhaust ventilation is recommended.
- Firewater monitors and deluge systems are recommended.
- The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances.
- Appropriate measures include:

# SAFETY DATA SHEET

## Butene-1

Version 3.0

Revision Date 22.02.2022

Print Date 03.09.2022

### General Information:

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Purge system prior to equipment break-in or maintenance.

### Personal protective equipment

#### Protective measures

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Respiratory protection : If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are unsuitable (e.g. airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus. If air-filtering respirators are suitable for conditions of use: Where air-filtering respirators are suitable, select an appropriate combination of mask and filter.

Select a filter suitable for organic gases and vapours [Type AX boiling point  $\leq 65^{\circ}\text{C}$  ( $149^{\circ}\text{F}$ )].

Hand protection  
Remarks

: Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. Neoprene rubber. If contact with liquefied product is possible or anticipated, gloves should be thermally insulated to prevent cold burns. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is



# SAFETY DATA SHEET

## Butene-1

Version 3.0

Revision Date 22.02.2022

Print Date 03.09.2022

dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

- Eye protection : Wear goggles for use against liquids and gas, combined with face shield with chin guard.
- Skin and body protection : Chemical and cryogenic gloves/gauntlets, boots, and apron. Wear antistatic and flame-retardant clothing.
- Thermal hazards : When handling cold material that can cause frost burns, wear cryogenic gloves, safety hat and visor, cold resistant overalls (with cuffs over gloves and legs over boots) and heavy duty boots e.g. leather for cold resistance.
- Hygiene measures : Wash hands before eating, drinking, smoking and using the toilet.  
Launder contaminated clothing before re-use.

### Environmental exposure controls

- General advice : Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour.  
Minimise release to the environment. An environmental assessment must be made to ensure compliance with local environmental legislation.  
Information on accidental release measures are to be found in section 6.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : Gas., Liquid under pressure.
- Colour : colourless
- Odour : Mild hydrocarbon
- Odour Threshold : Data not available
- pH : Data not available
- Melting / freezing point : -185 °C / -301 °F
- Boiling point/boiling range : -6,3 °C / 20,7 °F
- Flash point : -79 °C / -110 °F

# SAFETY DATA SHEET

## Butene-1

Version 3.0

Revision Date 22.02.2022

Print Date 03.09.2022

Evaporation rate	: Data not available
Flammability (solid, gas)	: Extremely flammable.
Upper explosion limit	: 10 %(V)
Lower explosion limit	: 1,6 %(V)
Vapour pressure	: 255 kPa (21 °C / 70 °F)
Relative vapour density	: 1,93
Relative density	: 0,588Method: ASTM D4052
Density	: 588 kg/m3 (25 °C / 77 °F) Method: ASTM D4052 Liquid at saturation pressure.
Solubility(ies)	
Water solubility	: 220 mg/l (22 °C / 72 °F)
Partition coefficient: n-octanol/water	: log Pow: 2,4
Auto-ignition temperature	: 385 °C / 725 °F
Decomposition temperature	: Data not available
Viscosity	
Viscosity, dynamic	: 0,156 mPa.s (20 °C / 68 °F) Method: ASTM D445
Viscosity, kinematic	: ca. 0,265 mm2/sMethod: ASTM D445
Explosive properties	: Material that is readily capable of detonation or explosive decomposition or explosive reaction at normal temperatures and pressures.
Oxidizing properties	: Data not available
Surface tension	: 13,1 mN/m
Conductivity	: Low conductivity: < 100 pS/m  The conductivity of this material makes it a static accumulator., A liquid is typically considered nonconductive if its conductivity is below 100 pS/m and is considered semi-conductive if its conductivity is below 10,000 pS/m., Whether a liquid is nonconductive or semi-conductive, the precautions are the same., A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid

# SAFETY DATA SHEET

## Butene-1

Version 3.0

Revision Date 22.02.2022

Print Date 03.09.2022

Particle size : Data not available

Molecular weight : 56 g/mol

### 10. STABILITY AND REACTIVITY

Reactivity : The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.

Chemical stability : Stable under normal conditions of use.

Possibility of hazardous reactions : Reacts violently with strong oxidising agents. Polymerisation may occur at elevated temperatures.

Conditions to avoid : Heat, flames, and sparks.  
Exposure to air.  
In certain circumstances product can ignite due to static electricity.

Incompatible materials : Strong oxidising agents.

Hazardous decomposition products : Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids and gases including carbon monoxide, carbon dioxide, sulphur oxides and unidentified organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation.

### 11. TOXICOLOGICAL INFORMATION

Basis for assessment : Information given is based on product data and on data on the components and the toxicology of similar products.

Information on likely routes of exposure : Inhalation is the primary route of exposure.

#### Acute toxicity

##### Components:

##### **but-1-ene:**

Acute inhalation toxicity : LC 50 Rat, male: > 2500 - <= 20000 ppm  
Exposure time: 4 h  
Test atmosphere: gas  
Method: OECD Test Guideline 403  
Remarks: Information given is based on data obtained from similar substances.  
Based on available data, the classification criteria are not met.

#### Skin corrosion/irritation

# SAFETY DATA SHEET

## Butene-1

Version 3.0

Revision Date 22.02.2022

Print Date 03.09.2022

no data available

### Serious eye damage/eye irritation

no data available

### Respiratory or skin sensitisation

no data available

### Germ cell mutagenicity

#### Components:

##### but-1-ene:

Method: Literature data

Remarks: Based on available data, the classification criteria are not met.

Method: OECD Test Guideline 473

Remarks: Based on available data, the classification criteria are not met.

Germ cell mutagenicity-  
Assessment

: This product does not meet the criteria for classification in categories 1A/1B.

### Carcinogenicity

#### Components:

##### but-1-ene:

Remarks: Based on available data, the classification criteria are not met.

Carcinogenicity -  
Assessment

: This product does not meet the criteria for classification in categories 1A/1B.

Material	GHS/CLP Carcinogenicity Classification
but-1-ene	No carcinogenicity classification.

### Reproductive toxicity

#### Components:

##### but-1-ene:

Species: Rat

Sex: male and female

Application Route: Inhalation

Method: OECD Test Guideline 422

Remarks: Based on available data, the classification criteria are not met.

Effects on foetal  
development

: Species: Rat, female  
Application Route: Inhalation  
Method: OECD Test Guideline 414  
Remarks: Information given is based on data obtained from

# SAFETY DATA SHEET

## Butene-1

Version 3.0

Revision Date 22.02.2022

Print Date 03.09.2022

similar substances., Based on available data, the classification criteria are not met.

Reproductive toxicity -  
Assessment

: This product does not meet the criteria for classification in categories 1A/1B.

### STOT - single exposure

#### Components:

##### **but-1-ene:**

Remarks: Inhalation of vapours or mists may cause irritation to the respiratory system., Based on available data, the classification criteria are not met.

### STOT - repeated exposure

#### Components:

##### **but-1-ene:**

Remarks: Based on available data, the classification criteria are not met.

### Repeated dose toxicity

#### Components:

##### **but-1-ene:**

rat, male and female:

Application Route: Inhalation

Test atmosphere: Gas

Method: OECD Test Guideline 422

Target Organs: No specific target organs noted

### Aspiration toxicity

#### Components:

##### **but-1-ene:**

Based on available data, the classification criteria are not met.

### Further information

#### Components:

##### **but-1-ene:**

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

---

## 12. ECOLOGICAL INFORMATION

Basis for assessment

: Incomplete ecotoxicological data are available for this product. The information given below is based partly on a knowledge of the components and the ecotoxicology of similar products.

### Ecotoxicity

# SAFETY DATA SHEET

## Butene-1

Version 3.0

Revision Date 22.02.2022

Print Date 03.09.2022

### Components:

#### **but-1-ene :**

Toxicity to fish (Acute toxicity)	: LC50 : 19 mg/l Exposure time: 96 h Method: Based on quantitative structure-activity relationship (QSAR) modelling Remarks: LL/EL/IL50 10-100 mg/l
Toxicity to crustacean (Acute toxicity)	: LC50 (Daphnia (water flea)): 16 mg/l Exposure time: 48 h Method: Based on quantitative structure-activity relationship (QSAR) modelling Remarks: LL/EL/IL50 10-100 mg/l
Toxicity to algae/aquatic plants (Acute toxicity)	: EC50 (green algae): 6,9 mg/l Exposure time: 96 h Method: Based on quantitative structure-activity relationship (QSAR) modelling Remarks: LL/EL/IL50 1-10 mg/l
Toxicity to microorganisms (Acute toxicity)	: Remarks: Data not available
Toxicity to fish (Chronic toxicity)	: Chronic Toxicity Value: 2 mg/l Exposure time: 30 d Method: Based on quantitative structure-activity relationship (QSAR) modelling
Toxicity to crustacean (Chronic toxicity)	: Chronic Toxicity Value: 1,6 mg/l Species: Daphnia (water flea) Method: Based on quantitative structure-activity relationship (QSAR) modelling

### **Persistence and degradability**

#### Components:

#### **but-1-ene :**

Biodegradability	: Method: Based on quantitative structure-activity relationship (QSAR) modelling Remarks: Readily biodegradable. Oxidises rapidly by photo-chemical reactions in air.
------------------	---

### **Bioaccumulative potential**

#### Product:

Partition coefficient: n-octanol/water	: log Pow: 2,4
--	----------------

#### Components:

#### **but-1-ene :**

Bioaccumulation	: Remarks: Does not bioaccumulate significantly.
-----------------	--

### **Mobility in soil**

#### Components:

#### **but-1-ene :**

Mobility	: Remarks: Because of their extreme volatility, air is the only
----------	---

# SAFETY DATA SHEET

## Butene-1

Version 3.0

Revision Date 22.02.2022

Print Date 03.09.2022

environmental compartment that hydrocarbon gases will be found.

### Other adverse effects

#### Components:

##### **but-1-ene :**

Results of PBT and vPvB assessment	: The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB.
Additional ecological information	: In view of the high rate of loss from solution, the product is unlikely to pose a significant hazard to aquatic life.

## 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : Recover or recycle if possible.  
It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.

Do not dispose into the environment, in drains or in water courses

Waste product should not be allowed to contaminate soil or water.

Disposal should be in accordance with applicable regional, national, and local laws and regulations.

Local regulations may be more stringent than regional or national requirements and must be complied with.

MARPOL - see International Convention for the Prevention of Pollution from Ships (MARPOL 73/78) which provides technical aspects at controlling pollutions from ships.

Contaminated packaging : Data not available

## 14. TRANSPORT INFORMATION

### International Regulations

#### **ADR**

UN number	: 1012
Proper shipping name	: BUTYLENE
Class	: 2
Packing group	: Not Assigned
Labels	: 2.1
Environmentally hazardous	: no

#### **ADN**

# SAFETY DATA SHEET

## Butene-1

Version 3.0

Revision Date 22.02.2022

Print Date 03.09.2022

UN number : 1012  
Proper shipping name : BUTYLENE  
Class : 2  
Packing group : Not Assigned  
Labels : 2.1  
Environmentally hazardous : no

### IATA-DGR

UN/ID No. : UN 1012  
Proper shipping name : Butylene  
Class : 2.1  
Packing group : Not Assigned  
Labels : 2.1

### IMDG-Code

UN number : UN 1012  
Proper shipping name : BUTYLENE  
Class : 2.1  
Packing group : Not Assigned  
Labels : 2.1  
Marine pollutant : no

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Pollution category : Not applicable  
Ship type : Not applicable  
Product name : Not applicable

### Special precautions for user

Remarks : Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

**Additional Information** : This product may be transported under nitrogen blanketing. Nitrogen is an odourless and invisible gas. Exposure to nitrogen enriched atmospheres displaces available oxygen which may cause asphyxiation or death. Personnel must observe strict safety precautions when involved with a confined space entry.

## 15. REGULATORY INFORMATION

### Safety, health and environmental regulations/legislation specific for the substance or mixture

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

### Other international regulations

#### The components of this product are reported in the following inventories:

AIIC : Listed  
DSL : Listed  
IECSC : Listed  
ENCS : Listed  
KECI : Listed



# SAFETY DATA SHEET

## Butene-1

Version 3.0

Revision Date 22.02.2022

Print Date 03.09.2022

NZIoC	: Listed
PICCS	: Listed
TSCA	: Listed
TCSI	: Listed

### 16. OTHER INFORMATION

#### Full text of H-Statements

H220	Extremely flammable gas.
H280	Contains gas under pressure; may explode if heated.

#### Full text of other abbreviations

Flam. Gas	Flammable gases
Press. Gas	Gases under pressure

Abbreviations and Acronyms : The standard abbreviations and acronyms used in this document can be looked up in reference literature (e.g. scientific dictionaries) and/or websites.

SDS Regulation : 1. GN 2.2.5.1313-03 "Maximum permissible concentration of harmful substance in the working zone area".  
2. GOST 12.1.007-76 "Harmful agents. Classification and safety requirements."  
3. GOST 12.1.005-88 "General hygiene requirements to the working zone area".  
4. GN 2.1.5.1315-03 "Reservoir water maximum permissible concentration".  
5. GOST 19433-88 "Dangerous goods. Classification and marking".  
6. Rail transportation safety rules and dangerous goods accidents liquidation procedure.  
7. GOST 30333-2007 Chemical product safety data sheet. General requirements.  
Regulation 1907/2006/EC

#### Further information

Training advice : Provide adequate information, instruction and training for operators.

Other information : A vertical bar (|) in the left margin indicates an amendment from the previous version.

Sources of key data used to compile the Safety Data Sheet : The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID data base, EC 1272 regulation, etc).

# SAFETY DATA SHEET

## Butene-1

Version 3.0

Revision Date 22.02.2022

Print Date 03.09.2022

---

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.