Version 1.3 Revision Date 26.01.2022 Print Date 03.09.2022

#### 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product name : NEODOL 91

Product code V2729, V2746

CAS-No. : 68603-15-6

Other means of identification : Alcohols, C9-11

Manufacturer or supplier's details

: Shell Chemicals Europe B.V. Manufacturer/Supplier

PO Box 2334

3000 CH Rotterdam

Netherlands

Telephone : +31 (0)10 441 5137 +31(0)10 441 5191 Telefax : +31 (0)20 716 8316/ +31 (0)20 713 9230

: +44 (0) 1235 239 670 (This telephone number is available 24 Emergency telephone

number hours per day, 7 days per week)

Recommended use of the chemical and restrictions on use

Recommended use : Use in detergent manufacture.

This product must not be used in applications other than the Restrictions on use

above without first seeking the advice of the supplier.

Other information : NEODOL is a trademark owned by Shell Trademark

Management B.V. and Shell Brands Inc. and used by affiliates

of Royal Dutch Shell plc.

#### 2. HAZARDS IDENTIFICATION

Classification (REGULATION (EC) No 1272/2008)

Eye irritation : Category 2 Long-term (chronic) aquatic Category 3

hazard

Label elements

Hazard pictograms

Signal word Warning

Version 1.3 Revision Date 26.01.2022 Print Date 03.09.2022

Hazard statements : PHYSICAL HAZARDS:

Not classified as a physical hazard according to CLP criteria.

**HEALTH HAZARDS:** 

H319 Causes serious eye irritation. ENVIRONMENTAL HAZARDS:

H412 Harmful to aquatic life with long lasting effects.

Supplemental Hazard

Statements

: EUH066 Repeated exposure may cause skin

dryness or cracking.

Precautionary statements : **Prevention:** 

P264 Wash hands thoroughly after handling.

P280 Wear protective gloves/ protective clothing/ eye

protection/ face protection.

P273 Avoid release to the environment.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice/

attention. Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

## Other hazards

Slightly irritating to respiratory system.

#### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Substance

### Hazardous components

Chemical name	CAS-No.	Classification	Concentration
	EC-No.	(REGULATION	(% w/w)
	Registration	(EC) No	
	number	1272/2008)	
Alcohols, C9-11	68603-15-6	Eye Irrit. 2; H319	100
		Aquatic Chronic 3;	
		H412	
		EUH066	

Refer to Chapter 8 for Occupational Exposure Guidelines.

For explanation of abbreviations see section 16.

#### 4. FIRST-AID MEASURES

General advice : Not expected to be a health hazard when used under normal

2 / 17 800001012129 RU

Version 1.3 Revision Date 26.01.2022 Print Date 03.09.2022 conditions. If inhaled : No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice. : Remove contaminated clothing. Immediately flush skin with In case of skin contact large amounts of water for at least 15 minutes, and follow by washing with soap and water if available. If redness, swelling, pain and/or blisters occur, transport to the nearest medical facility for additional treatment. In case of eye contact Immediately flush eye(s) with plenty of water. Remove contact lenses, if present and easy to do. Continue Transport to the nearest medical facility for additional treatment. If swallowed If swallowed, do not induce vomiting: transport to nearest medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (38.3°C), shortness of breath, chest congestion or continued coughing or wheezing. Most important symptoms If material enters lungs, signs and symptoms may include and effects, both acute and coughing, choking, wheezing, difficulty in breathing, chest delayed congestion, shortness of breath, and/or fever. If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (38.3°C), shortness of breath, chest congestion or continued coughing or wheezing. Skin irritation signs and symptoms may include a burning sensation, redness, or swelling. Eye irritation signs and symptoms may include a burning sensation, redness, swelling, and/or blurred vision. Defatting dermatitis signs and symptoms may include a burning sensation and/or a dried/cracked appearance. Not considered to be an inhalation hazard under normal conditions of use. Possible respiratory irritation signs and symptoms may include a temporary burning sensation of the nose and throat, coughing, and/or difficulty breathing. Protection of first-aiders When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings. : IMMEDIATE TREATMENT IS EXTREMELY IMPORTANT! Notes to physician Call a doctor or poison control center for guidance. Potential for chemical pneumonitis. Treat symptomatically.

Version 1.3 Revision Date 26.01.2022 Print Date 03.09.2022

#### 5. FIRE-FIGHTING MEASURES

#### Flammable properties

Flash point : 108 °C / 226 °F

Method: ASTM D93 (PMCC)

Ignition temperature : Data not available Upper explosion limit : Data not available Lower explosion limit : Data not available Flammability (solid, gas) : Not applicable

Suitable extinguishing media

: Alcohol-resistant foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small

fires only.

Unsuitable extinguishing

media

: Do not use water in a jet.

Specific hazards during

firefighting

: Carbon monoxide may be evolved if incomplete combustion

occurs.

Will float and can be reignited on surface water.

The vapour is heavier than air, spreads along the ground and

distant ignition is possible.

Specific extinguishing

methods

: Standard procedure for chemical fires.

Further information : Clear fire area of all non-emergency personnel.

Keep adjacent containers cool by spraying with water.

Special protective equipment

for firefighters

Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if

large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to

relevant Standards (e.g. Europe: EN469).

### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Observe all relevant local and international regulations. Notify authorities if any exposure to the general public or the

environment occurs or is likely to occur.

Local authorities should be advised if significant spillages

cannot be contained.

: Avoid contact with spilled or released material. Immediately remove all contaminated clothing. For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet. For guidance on disposal of spilled material see

Version 1.3 Revision Date 26.01.2022 Print Date 03.09.2022

Section 13 of this Safety Data Sheet. Stay upwind and keep out of low areas. Be ready for fire or possible exposure.

Environmental precautions

: Prevent from spreading or entering into drains, ditches or rivers by using sand, earth, or other appropriate barriers. Use appropriate containment to avoid environmental

contamination.

Ventilate contaminated area thoroughly.

Methods and materials for containment and cleaning up

: For large liquid spills (> 1 drum), transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely For small liquid spills (< 1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove

contaminated soil and dispose of safely.

Additional advice : For guidance on selection of personal protective equipment

see Section 8 of this Safety Data Sheet.

For guidance on disposal of spilled material see Section 13 of

this Safety Data Sheet.

### 7. HANDLING AND STORAGE

General Precautions : Avoid breathing of or direct contact with material. Only use in

well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see

Section 8 of this Safety Data Sheet.

Use the information in this data sheet as input to a risk assessment of local circumstances to help determine

appropriate controls for safe handling, storage and disposal of

this material.

Ensure that all local regulations regarding handling and

storage facilities are followed.

Advice on safe handling : Avoid contact with skin, eyes and clothing.

Do not empty into drains.

Sudden Release of Pressure Hazard

Avoidance of contact : Copper.

Copper alloys.

Strong oxidising agents.

Aluminum

Product Transfer : Keep containers closed when not in use. Do not use

compressed air for filling discharge or handling.

## **Storage**

Version 1.3 Revision Date 26.01.2022 Print Date 03.09.2022 Conditions for safe storage : Refer to section 15 for any additional specific legislation covering the packaging and storage of this product. : Bulk storage tanks should be diked (bunded). Other data Vapours from tanks should not be released to atmosphere. Breathing losses during storage should be controlled by a suitable vapour treatment system. Nitrogen blanket recommended for large tanks (capacity 100 m3 or higher). Insulation (lagging) will minimize heat loss in areas of low ambient temperature. Tanks should be fitted with heating coils in areas where ambient conditions can result in handling temperatures below the freezing point/pour point of the product. : Suitable material: Stainless steel., Epoxy resins, Polyester. Packaging material Unsuitable material: Aluminum, Copper., Copper alloys. Container Advice : Containers, even those that have been emptied, can contain explosive vapours. Do not cut, drill, grind, weld or perform similar operations on or near containers. Specific use(s) : Not applicable Ensure that all local regulations regarding handling and storage facilities are followed.

### 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

#### Components with workplace control parameters

#### Biological occupational exposure limits

No biological limit allocated.

## **Monitoring Methods**

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany http://www.dguv.de/inhalt/index.jsp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

Version 1.3 Revision Date 26.01.2022 Print Date 03.09.2022

### **Engineering measures**

: Use sealed systems as far as possible.

Adequate explosion-proof ventilation to control airborne concentrations below the exposure guidelines/limits.

Local exhaust ventilation is recommended.

Firewater monitors and deluge systems are recommended.

Eve washes and showers for emergency use.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated. The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances.

Appropriate measures include:

#### General Information:

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

#### Personal protective equipment

#### Protective measures

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Respiratory protection

: If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are unsuitable (e.g. airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus.

Where air-filtering respirators are suitable, select an appropriate combination of mask and filter.

If air-filtering respirators are suitable for conditions of use: Select a filter suitable for organic gases and vapours [Type A

boiling point >65°C (149°F)].

#### Hand protection

Version 1.3 Revision Date 26.01.2022 Print Date 03.09.2022

Remarks

: Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. Longer term protection: Butyl rubber. Nitrile rubber. Incidental contact/Splash protection: PVC or neoprene rubber gloves. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

Eve protection : Wear goggles for use against liquids and gas.

Wear full face shield if splashes are likely to occur.

: Wear antistatic and flame-retardant clothing, if a local risk Skin and body protection

assessment deems it so.

Skin protection is not required under normal conditions of use. For prolonged or repeated exposures use impervious clothing

over parts of the body subject to exposure.

If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to relevant Standard,

and provide employee skin care programmes.

Thermal hazards : Not applicable

Hygiene measures : Wash hands before eating, drinking, smoking and using the

Launder contaminated clothing before re-use.

## **Environmental exposure controls**

General advice : Local guidelines on emission limits for volatile substances

must be observed for the discharge of exhaust air containing

vapour.

Minimise release to the environment. An environmental assessment must be made to ensure compliance with local

environmental legislation.

Information on accidental release measures are to be found in

section 6.

Version 1.3 Revision Date 26.01.2022 Print Date 03.09.2022

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Liquid at 20 °C.

Colour : colourless

Odour : mild

Odour Threshold : Data not available pH : Data not available pour point : -12 °C / 10 °F

Method: ASTM D97

Melting point/freezing point -12 °C / 10 °F

Boiling point/boiling range : 213 - 245 °C / 415 - 473 °F

Flash point : 108 °C / 226 °F

Method: ASTM D93 (PMCC)

Evaporation rate : Data not available Flammability (solid, gas) : Not applicable

Upper explosion limit : Data not available

Lower explosion limit : Data not available

Vapour pressure : < 5 Pa (25 °C / 77 °F)

Relative vapour density : 5,7

Relative density : 0,83 (20 °C / 68 °F)

Density : 831 kg/m3 (20 °C / 68 °F)

Method: ASTM D4052

Solubility(ies)

Water solubility : Data not available Partition coefficient: n- : log Pow: 3,8 - 4,7

octanol/water

Auto-ignition temperature : Data not available

Decomposition temperature : Data not available

Viscosity

Viscosity, dynamic : 14 mPa.s (20 °C / 68 °F)

Viscosity, dynamic 50 mPa.s (Not applicable /)

Viscosity, kinematic : 9 mm2/s (40 °C / 104 °F)

# **NEODOL 91**

Version 1.3 Revision Date 26.01.2022 Print Date 03.09.2022

> 16 mm2/s (20 °C / 68 °F) Method: ASTM D445

Explosive properties : Not classified

Oxidizing properties : Not applicable

Surface tension : Data not available

Conductivity : Electrical conductivity: > 10,000 pS/m

> A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid, This material is not expected to be

a static accumulator.

Particle size : Data not available

Molecular weight : 160 g/mol

#### 10. STABILITY AND REACTIVITY

: Stable at normal ambient temperature and pressure., May Reactivity

oxidise in the presence of air.

Chemical stability : The product is chemically stable. Stable under normal

conditions.

Possibility of hazardous

reactions

: None known.

Conditions to avoid : Extremes of temperature and direct sunlight.

Incompatible materials Copper.

Copper alloys.

Strong oxidising agents.

Aluminum

Hazardous decomposition

products

: None expected under normal use conditions.

## 11. TOXICOLOGICAL INFORMATION

Basis for assessment : Information given is based on product testing, and/or similar

products, and/or components.

exposure

Information on likely routes of : Exposure may occur via inhalation, ingestion, skin absorption,

skin or eye contact, and accidental ingestion.

# **Acute toxicity**

## **NEODOL 91**

Version 1.3 Revision Date 26.01.2022 Print Date 03.09.2022

**Product:** 

Acute oral toxicity : LD50 Rat: > 5000 mg/kg

Remarks: Low toxicity:

Acute inhalation toxicity : Remarks: Low toxicity by inhalation.

Acute dermal toxicity : LD50 Rat: > 5000 mg/kg

Remarks: Low toxicity:

Components:

Alcohols, C9-11:

Acute oral toxicity : LD50 Rat: > 5000 mg/kg

Remarks: Low toxicity:

Acute inhalation toxicity : Remarks: Low toxicity by inhalation.

Acute dermal toxicity : LD50 Rat: > 5000 mg/kg

Remarks: Low toxicity:

### Skin corrosion/irritation

#### **Product:**

Remarks: Causes mild skin irritation.

### **Components:**

Alcohols, C9-11:

Remarks: Causes mild skin irritation.

# Serious eye damage/eye irritation

#### **Product:**

Remarks: Causes serious eye irritation.

## **Components:**

Alcohols, C9-11:

Remarks: Causes serious eye irritation.

## Respiratory or skin sensitisation

### **Product:**

Remarks: Not a sensitiser.

Based on available data, the classification criteria are not met.

## Components:

Alcohols, C9-11:

Remarks: Not a sensitiser.

Based on available data, the classification criteria are not met.

# **NEODOL 91**

Version 1.3 Revision Date 26.01.2022 Print Date 03.09.2022

## Germ cell mutagenicity

**Product:** 

Remarks: Non mutagenic

**Components:** 

Alcohols, C9-11:

Remarks: Non mutagenic

# Carcinogenicity

### **Product:**

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

## **Components:**

### Alcohols, C9-11:

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

Material	GHS/CLP Carcinogenicity Classification
Alcohols, C9-11	No carcinogenicity classification.

### Reproductive toxicity

**Product:** 

Remarks: Not a developmental toxicant., Based on available data, the classification criteria are not met., Does not impair fertility.

# Components:

Alcohols, C9-11:

Remarks: Not a developmental toxicant., Based on available data, the classification criteria are not met., Does not impair fertility.

## STOT - single exposure

### **Product:**

Remarks: Based on available data, the classification criteria are not met.

# **Components:**

Alcohols, C9-11:

Remarks: Based on available data, the classification criteria are not met.

Version 1.3 Revision Date 26.01.2022 Print Date 03.09.2022

## STOT - repeated exposure

#### **Product:**

Remarks: Based on available data, the classification criteria are not met.

### **Components:**

#### Alcohols, C9-11:

Remarks: Based on available data, the classification criteria are not met.

# **Aspiration toxicity**

#### **Product:**

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

## **Components:**

### Alcohols, C9-11:

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

#### **Further information**

#### **Product:**

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

### **Components:**

### Alcohols, C9-11:

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

#### 12. ECOLOGICAL INFORMATION

Basis for assessment : Incomplete ecotoxicological data are available for this product.

The information given below is based partly on a knowledge of the components and the ecotoxicology of similar products.

# **Ecotoxicity**

# **Product:**

Toxicity to fish (Acute

toxicity) Remarks: LL/EL/IL50 > 1 <= 10 mg/l

Toxic

Toxicity to crustacean (Acute

toxicity)

Remarks: LL/EL/IL50 > 1 <= 10 mg/l

Toxic

Toxicity to algae/aquatic

plants (Acute toxicity) Remarks: LL/EL/IL50 > 1 <= 10 mg/l

Toxic

## **NEODOL 91**

Version 1.3 Revision Date 26.01.2022 Print Date 03.09.2022

Toxicity to fish (Chronic

toxicity)

: Remarks: Data not available

Toxicity to crustacean

(Chronic toxicity)

: Remarks: Data not available

Toxicity to microorganisms

(Acute toxicity)

: Remarks: Data not available

Components:

Alcohols, C9-11:

Toxicity to fish (Acute

toxicity)

: Remarks: LL/EL/IL50 > 1 <= 10 mg/l

Toxic

Toxicity to crustacean (Acute

toxicity)

: Remarks: LL/EL/IL50 > 1 <= 10 mg/l

Toxic

Toxicity to algae/aquatic

plants (Acute toxicity)

: Remarks: LL/EL/IL50 > 1 <= 10 mg/l

Toxicity to microorganisms

(Acute toxicity)

Toxicity to fish (Chronic

toxicity) Toxicity to : Remarks: Data not available : Remarks: Data not available

: Remarks: Data not available

crustacean(Chronic toxicity)

Persistence and degradability

**Product:** 

Biodegradability : Remarks: Readily biodegradable.

**Components:** Alcohols, C9-11:

Biodegradability : Remarks: Readily biodegradable.

**Bioaccumulative potential** 

**Product:** 

Bioaccumulation : Remarks: Bioaccumulation is unlikely to occur due to

metabolism and excretion.

Partition coefficient: n-

octanol/water **Components:** Alcohols, C9-11: : log Pow: 3,8 - 4,7

Bioaccumulation : Remarks: Bioaccumulation is unlikely to occur due to

metabolism and excretion.

Mobility in soil

**Product:** 

Mobility : Remarks: Floats on water., Adsorbs to soil and has low

mobility

**Components:** 

Alcohols, C9-11:

Mobility : Remarks: Floats on water., Adsorbs to soil and has low

14 / 17 800001012129 RU

# **NEODOL 91**

Version 1.3 Revision Date 26.01.2022 Print Date 03.09.2022

mobility

Other adverse effects

no data available

**Product:** 

Additional ecological

information

: None known.

Components: Alcohols, C9-11:

Additional ecological

information

: None known.

#### 13. DISPOSAL CONSIDERATIONS

## **Disposal methods**

Waste from residues : Recover or recycle if possible.

It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Do not dispose into the environment, in drains or in water

courses

Waste product should not be allowed to contaminate soil or

water.

Disposal should be in accordance with applicable regional,

national, and local laws and regulations.

Local regulations may be more stringent than regional or

national requirements and must be complied with.

Contaminated packaging

Drain container thoroughly.

After draining, vent in a safe place away from sparks and fire.

Residues may cause an explosion hazard. Do not puncture, cut, or weld uncleaned drums. Send to drum recoverer or metal reclaimer.

#### 14. TRANSPORT INFORMATION

### **International Regulations**

**ADR** 

Not regulated as a dangerous good

**IATA-DGR** 

Not regulated as a dangerous good

**IMDG-Code** 

Not regulated as a dangerous good

## Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

15 / 17 800001012129 RU

Version 1.3 Revision Date 26.01.2022 Print Date 03.09.2022

Pollution category : X 2 Ship type :

: Noxious liquid, NF, (3) n.o.s. (Neodol 91 contains undecyl Product name

alcohol)

Special precautions for user

Remarks : Special Precautions: Refer to Section 7, Handling & Storage,

for special precautions which a user needs to be aware of or

needs to comply with in connection with transport.

**Additional Information** : This product may be transported under nitrogen blanketing.

> Nitrogen is an odourless and invisible gas. Exposure to nitrogen enriched atmospheres displaces available oxygen which may cause asphyxiation or death. Personnel must observe strict safety precautions when involved with a

confined space entry.

#### 15. REGULATORY INFORMATION

## Safety, health and environmental regulations/legislation specific for the substance or mixture

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

# Other international regulations

#### The components of this product are reported in the following inventories:

**AICS** : Listed DSL Listed **IECSC** Listed **ENCS** Listed KECI Listed **NZIoC** Listed : Listed **TSCA TCSI** : Listed

#### 16. OTHER INFORMATION

#### **Full text of H-Statements**

**EUH066** Repeated exposure may cause skin dryness or cracking.

H319 Causes serious eye irritation.

H412 Harmful to aquatic life with long lasting effects.

### Full text of other abbreviations

Aquatic Chronic Long-term (chronic) aquatic hazard

Eye Irrit. Eve irritation

Abbreviations and Acronyms The standard abbreviations and acronyms used in this

document can be looked up in reference literature (e.g.

scientific dictionaries) and/or websites.

Version 1.3 Revision Date 26.01.2022 Print Date 03.09.2022

SDS Regulation : 1. GN 2.2.5.1313-03 "Maximum permissible

concentration of harmful substance in the working zone

area".

2. GOST 12.1.007-76 "Harmful agents. Classification and

safety requirements."

3. GOST 12.1.005-88 "General hygiene requirements to

the working zone area".

4. GN 2.1.5.1315-03 "Reservoir water maximum

permissible concentration".

5. GOST 19433-88 "Dangerous goods. Classification and

marking".

6. Rail transportation safety rules and dangerous goods

accidents liquidation procedure.

7. GOST 30333-2007 Chemical product safety data

sheet. General requirements. Regulation 1907/2006/EC

**Further information** 

Training advice : Provide adequate information, instruction and training for

operators.

Other information : A vertical bar (|) in the left margin indicates an amendment

from the previous version.

Sources of key data used to

compile the Safety Data

Sheet

: The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU

IUCLID date base, EC 1272 regulation, etc).

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.