

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version	Revision Date:	SDS Number:	Date of last issue: 22.11.2023
2.1	28.03.2024	800010059269	Print Date 04.04.2024

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name	: ShellSol A100 Low Cumene
Product code	: Q7591
Registration number EU	: 01-2119455851-35-0000
Synonyms	: Hydrocarbons, C9, aromatics

EC-No. : 918-668-5

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- stance/Mixture	: Industrial Solvent. Please refer to section 16 and/or the annexes for the registered uses under REACH.
-----------------------------------	---

Uses advised against	: This product must not be used in applications other than the above without first seeking the advice of the supplier.
----------------------	--

#### 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier	: <b>Shell Chemicals Europe B.V.</b> PO Box 2334 3000 CH Rotterdam Netherlands
Telephone	: +31 (0)10 441 5137 / +31 (0)10 441 5191
Telefax	: +31 (0)20 716 8316 / +31 (0)20 713 9230
Contact for Safety Data Sheet	: sccmsds@shell.com

#### 1.4 Emergency telephone number

+44 (0) 1235 239 670  
National Poison Information Centre (NVIC): Tel. nr. +31(0)88 755 8000 (24 hrs a day and 7 days a week).  
Only for the purpose of informing medical personnel.

Other information	: SHELLSOL is a trademark owned by Shell Trademark Management B.V. and Shell Brands Inc. and used by affiliates of Shell plc.
-------------------	---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3	H226: Flammable liquid and vapour.
-------------------------------	------------------------------------

Aspiration hazard, Category 1	H304: May be fatal if swallowed and enters air-
-------------------------------	---

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version	Revision Date:	SDS Number:	Date of last issue: 22.11.2023
2.1	28.03.2024	800010059269	Print Date 04.04.2024

ways.

Specific target organ toxicity - single exposure, Category 3, Respiratory Tract

H335: May cause respiratory irritation.

Specific target organ toxicity - single exposure, Category 3, Narcotic effects

H336: May cause drowsiness or dizziness.

Long-term (chronic) aquatic hazard, Category 2

H411: Toxic to aquatic life with long lasting effects.

### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements :

PHYSICAL HAZARDS:

H226 Flammable liquid and vapour.

HEALTH HAZARDS:

H304 May be fatal if swallowed and enters airways.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

ENVIRONMENTAL HAZARDS:

H411 Toxic to aquatic life with long lasting effects.

Supplemental Hazard Statements : EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statements :

**Prevention:**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P243 Take action to prevent static discharges.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

**Response:**

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

#### Storage:

No precautionary phrases.

#### Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

### 2.3 Other hazards

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

May form flammable/explosive vapour-air mixture.

This material is a static accumulator.

Even with proper grounding and bonding, this material can still accumulate an electrostatic charge.

If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur.

Possibility of organ or organ system damage from prolonged exposure; see Section 11 for details.

Target organ(s):

Auditory system

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

#### Components

Chemical name	CAS-No. EC-No.	Concentration (% w/w)
Hydrocarbons, C9, aromatics	Not Assigned 918-668-5	<= 100

#### Further information

Contains:

Chemical name	Identification number	Classification	Concentration (% w/w)
Cumene	98-82-8, 202-704-5	Flam. Liq.3; H226 Asp. Tox.1; H304 STOT SE3; H335 Carc.1B; H350 Aquatic Chronic2; H411	>= 0 - <= 0,099
Benzene	71-43-2, 200-753-7	Flam. Liq.2; H225 Asp. Tox.1; H304 Skin Irrit.2; H315 Eye Irrit.2; H319 Muta.1B; H340 Carc.1A; H350 STOT RE1; H372 Aquatic Chronic3; H412	>= 0 - < 0,1

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version	Revision Date:	SDS Number:	Date of last issue: 22.11.2023
2.1	28.03.2024	800010059269	Print Date 04.04.2024

---

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- |                            |   |  |
|----------------------------|---|--|
| General advice             | : | Not expected to be a health hazard when used under normal conditions.  |
| Protection of first-aiders | : | When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.  |
| If inhaled                 | : | Remove to fresh air. If rapid recovery does not occur, transport to nearest medical facility for additional treatment.   |
| In case of skin contact    | : | Remove contaminated clothing. Immediately flush skin with large amounts of water for at least 15 minutes, and follow by washing with soap and water if available. If redness, swelling, pain and/or blisters occur, transport to the nearest medical facility for additional treatment.  |
| In case of eye contact     | : | Flush eye with copious quantities of water.<br>Remove contact lenses, if present and easy to do. Continue rinsing.<br>If persistent irritation occurs, obtain medical attention.   |
| If swallowed               | : | Call emergency number for your location / facility.<br>If swallowed, do not induce vomiting: transport to nearest medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.<br>If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (38.3°C), shortness of breath, chest congestion or continued coughing or wheezing. |

#### 4.2 Most important symptoms and effects, both acute and delayed

- |          |   |  |
|----------|---|--|
| Symptoms | : | <p>Respiratory irritation signs and symptoms may include a temporary burning sensation of the nose and throat, coughing, and/or difficulty breathing.</p> <p>Breathing of high vapour concentrations may cause central nervous system (CNS) depression resulting in dizziness, light-headedness, headache, nausea and loss of coordination. Continued inhalation may result in unconsciousness and death.</p> <p>Skin irritation signs and symptoms may include a burning sensation, redness, or swelling.</p> <p>No specific hazards under normal use conditions.</p> <p>Eye irritation signs and symptoms may include a burning sensation, redness, swelling, and/or blurred vision.</p> |
|----------|---|--|

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version	Revision Date:	SDS Number:	Date of last issue: 22.11.2023
2.1	28.03.2024	800010059269	Print Date 04.04.2024

---

If material enters lungs, signs and symptoms may include coughing, choking, wheezing, difficulty in breathing, chest congestion, shortness of breath, and/or fever.  
If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (38.3°C), shortness of breath, chest congestion or continued coughing or wheezing.

Defatting dermatitis signs and symptoms may include a burning sensation and/or a dried/cracked appearance.

Auditory system effects may include temporary hearing loss and/or ringing in the ears.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Call a doctor or poison control center for guidance.  
Potential for chemical pneumonitis.  
Treat symptomatically.

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

Unsuitable extinguishing media : Do not use water in a jet.

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Clear fire area of all non-emergency personnel.  
Hazardous combustion products may include:  
A complex mixture of airborne solid and liquid particulates and gases (smoke).  
Carbon monoxide.  
Unidentified organic and inorganic compounds.  
Flammable vapours may be present even at temperatures below the flash point.  
The vapour is heavier than air, spreads along the ground and distant ignition is possible.  
Will float and can be reignited on surface water.

### 5.3 Advice for firefighters

Special protective equipment for firefighters : Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version	Revision Date:	SDS Number:	Date of last issue: 22.11.2023
2.1	28.03.2024	800010059269	Print Date 04.04.2024

Specific extinguishing methods : Standard procedure for chemical fires.

Further information : Keep adjacent containers cool by spraying with water.

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions :

- Observe all relevant local and international regulations.
- Notify authorities if any exposure to the general public or the environment occurs or is likely to occur.
- Local authorities should be advised if significant spillages cannot be contained.
- 6.1.1 For non emergency personnel:
  - Avoid contact with skin, eyes and clothing.
  - Isolate hazard area and deny entry to unnecessary or unprotected personnel.
  - Do not breathe fumes, vapour.
  - Do not operate electrical equipment.
- 6.1.2 For emergency responders:
  - Avoid contact with skin, eyes and clothing.
  - Isolate hazard area and deny entry to unnecessary or unprotected personnel.
  - Do not breathe fumes, vapour.
  - Do not operate electrical equipment.

#### 6.2 Environmental precautions

Environmental precautions :

- Shut off leaks, if possible without personal risks. Remove all possible sources of ignition in the surrounding area. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. Attempt to disperse the vapour or to direct its flow to a safe location for example by using fog sprays. Take precautionary measures against static discharge. Ensure electrical continuity by bonding and grounding (earthing) all equipment.
- Monitor area with combustible gas indicator.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up :

- For small liquid spills (< 1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.
- For large liquid spills (> 1 drum), transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1	Revision Date: 28.03.2024	SDS Number: 800010059269	Date of last issue: 22.11.2023 Print Date 04.04.2024
----------------	------------------------------	-----------------------------	---

up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely

Ventilate contaminated area thoroughly.  
If contamination of site occurs remediation may require specialist advice.

### 6.4 Reference to other sections

For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet.,  
For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

- |                         |  |
|-------------------------|--|
| Technical measures      | :<br>Avoid breathing of or direct contact with material. Only use in well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet.<br>Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.<br>Ensure that all local regulations regarding handling and storage facilities are followed.   |
| Advice on safe handling | :<br>Avoid inhaling vapour and/or mists.<br>Avoid contact with skin, eyes and clothing.<br>Extinguish any naked flames. Do not smoke. Remove ignition sources. Avoid sparks.<br>Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols.<br>Bulk storage tanks should be diked (bunded).<br>When using do not eat or drink.<br><br>The vapour is heavier than air, spreads along the ground and distant ignition is possible.   |
| Product Transfer        | :<br>Even with proper grounding and bonding, this material can still accumulate an electrostatic charge. If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur. Be aware of handling operations that may give rise to additional hazards that result from the accumulation of static charges. These include but are not limited to pumping (especially turbulent flow), mixing, filtering, splash filling, cleaning and filling of tanks and containers, sampling, switch loading, gauging, vacuum truck operations, and mechanical movements. These activities may lead to static discharge e.g. spark formation. Restrict line velocity during pumping in order to avoid generation of electrostatic discharge ( $\leq 1$ m/s until fill pipe submerged to twice its diameter, then $\leq 7$ m/s). Avoid splash filling. Do NOT use |

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version	Revision Date:	SDS Number:	Date of last issue: 22.11.2023
2.1	28.03.2024	800010059269	Print Date 04.04.2024

compressed air for filling, discharging, or handling operations.

Refer to guidance under Handling section.

Hygiene measures : Wash hands before eating, drinking, smoking and using the toilet. Launder contaminated clothing before re-use. Do not ingest. If swallowed, then seek immediate medical assistance.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Refer to section 15 for any additional specific legislation covering the packaging and storage of this product.

Further information on storage stability : Storage Temperature: Ambient.

Bulk storage tanks should be diked (bunded).  
Locate tanks away from heat and other sources of ignition.  
Cleaning, inspection and maintenance of storage tanks is a specialist operation, which requires the implementation of strict procedures and precautions.  
Must be stored in a diked (bunded) well-ventilated area, away from sunlight, ignition sources and other sources of heat.  
Keep away from aerosols, flammables, oxidizing agents, corrosives and from other flammable products which are not harmful or toxic to man or to the environment.  
Electrostatic charges will be generated during pumping.  
Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment to reduce the risk.  
The vapours in the head space of the storage vessel may lie in the flammable/explosive range and hence may be flammable.

Packaging material : Suitable material: For containers, or container linings use mild steel, stainless steel., For container paints, use epoxy paint, zinc silicate paint.  
Unsuitable material: Avoid prolonged contact with natural, butyl or nitrile rubbers.

Container Advice : Do not cut, drill, grind, weld or perform similar operations on or near containers.

### 7.3 Specific end use(s)

Specific use(s) : Please refer to section 16 and/or the annexes for the registered uses under REACH.

See additional references that provide safe handling practices for liquids that are determined to be static accumulators: American Petroleum Institute 2003 (Protection Against Ignitions Arising out of Static, Lightning and Stray Currents) or National Fire Protection Agency 77 (Recommended Practices on Static Electricity).



# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

IEC/TS 60079-32-1: Electrostatic hazards, guidance

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

##### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Cumene	98-82-8	TLV-8hr	10 ppm 50 mg/m <sup>3</sup>	NL WG
Further information: Skin notation				
Cumene		TLV-15 min	50 ppm 250 mg/m <sup>3</sup>	NL WG
Further information: Skin notation				
Cumene		TWA	10 ppm 50 mg/m <sup>3</sup>	2019/1831/E U
Further information: A skin notation assigned to the occupational exposure limit value indicates the possibility of significant uptake through the skin., Indicative				
Cumene		STEL	50 ppm 250 mg/m <sup>3</sup>	2019/1831/E U
Further information: A skin notation assigned to the occupational exposure limit value indicates the possibility of significant uptake through the skin., Indicative				
Benzene	71-43-2	TLV-8hr	0,2 ppm 0,7 mg/m <sup>3</sup>	NL WG
Further information: Carcinogenic substances, based on the threshold limit effect, Skin notation				
Benzene		TWA	0,25 ppm 0,8 mg/m <sup>3</sup>	Shell Internal Standard (SIS) for 8-12 hour TWA.
Benzene		STEL	2,5 ppm 8 mg/m <sup>3</sup>	Shell Internal Standard (SIS) for 15 min (STEL)

##### Biological occupational exposure limits

No biological limit allocated.

##### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
ShellSol A100	Workers	Dermal	Long-term systemic effects	25 mg/kg bw/day
ShellSol A100	Workers	Inhalation	Long-term systemic effects	150 mg/m <sup>3</sup>
ShellSol A100	Consumers	Inhalation	Long-term systemic effects	32 mg/m <sup>3</sup>

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

ShellSol A100	Consumers	Dermal	Long-term systemic effects	11 mg/kg
ShellSol A100	Consumers	Oral	Long-term systemic effects	11 mg/kg

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Remarks:	Substance is a hydrocarbon with a complex, unknown or variable composition. Conventional methods of deriving PNECs are not appropriate and it is not possible to identify a single representative PNEC for such substances.	

## 8.2 Exposure controls

### Engineering measures

Read in conjunction with the Exposure Scenario for your specific use contained in the Annex. The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

Use sealed systems as far as possible.

Adequate explosion-proof ventilation to control airborne concentrations below the exposure guidelines/limits.

Local exhaust ventilation is recommended.

Firewater monitors and deluge systems are recommended.

Eye washes and showers for emergency use.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

### General Information:

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

### Personal protective equipment

Read in conjunction with the Exposure Scenario for your specific use contained in the Annex.

The provided information is made in consideration of the PPE directive (Council Directive 89/686/EEC) and the CEN European Committee for Standardisation (CEN) standards.

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Eye protection : If material is handled such that it could be splashed into eyes, protective eyewear is recommended.  
Approved to EU Standard EN166.

Hand protection

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1	Revision Date: 28.03.2024	SDS Number: 800010059269	Date of last issue: 22.11.2023 Print Date 04.04.2024
----------------	------------------------------	-----------------------------	---

---

Remarks : Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. Longer term protection: butyl-rubber Nitrile rubber gloves.  
Incidental contact/Splash protection: Nitrile rubber gloves.  
For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

Skin and body protection : Skin protection is not required under normal conditions of use.  
For prolonged or repeated exposures use impervious clothing over parts of the body subject to exposure.  
If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to relevant Standard, and provide employee skin care programmes.  
  
Protective clothing approved to EU Standard EN14605.  
  
Wear antistatic and flame-retardant clothing, if a local risk assessment deems it so.

Respiratory protection : If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are unsuitable (e.g. airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus.  
Where air-filtering respirators are suitable, select an appropriate combination of mask and filter.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version	Revision Date:	SDS Number:	Date of last issue: 22.11.2023
2.1	28.03.2024	800010059269	Print Date 04.04.2024

If air-filtering respirators are suitable for conditions of use:  
Select a filter suitable for organic gases and vapours [Type A  
boiling point > 65°C (149°F)] meeting EN14387.

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

Physical state	: Liquid.
Colour	: colourless
Odour	: aromatic
Odour Threshold	: Data not available
Melting point/freezing point	: Data not available
Boiling point/boiling range	: 150 - 185 °C
Flammability	
Flammability (solid, gas)	: Not applicable
Flammability (liquids)	: Flammable liquid and vapour.
Lower explosion limit and upper explosion limit / flammability limit	
Upper explosion limit / upper flammability limit	: 7 %(V)
Lower explosion limit / Lower flammability limit	: 0,6 %(V)
Flash point	: 38 - 50 °C Method: IP 170
Auto-ignition temperature	: 507 °C
Decomposition temperature	
Decomposition tempera- ture	: Data not available
pH	: Data not available
Viscosity	
Viscosity, dynamic	: Data not available
Viscosity, kinematic	: Typical 0,9 mm <sup>2</sup> /s (25 °C) Method: ASTM D445
Solubility(ies)	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1	Revision Date: 28.03.2024	SDS Number: 800010059269	Date of last issue: 22.11.2023 Print Date 04.04.2024
----------------	------------------------------	-----------------------------	---

---

Water solubility	: insoluble
------------------	-------------

Partition coefficient: n-octanol/water	: log Pow: 3,7 - 4,5
--	----------------------

Vapour pressure	: 210 - 1.300 Pa (20 °C)
-----------------	--------------------------

Relative density	: 0,87 - 0,88 (20 °C) Method: ASTM D4052
------------------	---

Density	: Typical 876 kg/m <sup>3</sup> (15 °C) Method: ASTM D4052
---------	---

Relative vapour density	: 4,3
-------------------------	-------

Particle characteristics Particle size	: Data not available
---	----------------------

### 9.2 Other information

Explosive properties	: Not applicable
----------------------	------------------

Oxidizing properties	: Data not available
----------------------	----------------------

Flammability (liquids)	: Flammable liquid and vapour.
------------------------	--------------------------------

Evaporation rate	: < 1 Method: ASTM D 3539, nBuAc=1
------------------	---------------------------------------

Conductivity	: Low conductivity: < 100 pS/m
--------------	--------------------------------

The conductivity of this material makes it a static accumulator. A liquid is typically considered nonconductive if its conductivity is below 100 pS/m and is considered semi-conductive if its conductivity is below 10,000 pS/m. Whether a liquid is nonconductive or semi-conductive, the precautions are the same. A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid

Surface tension	: Data not available
-----------------	----------------------

Molecular weight	: Data not available
------------------	----------------------

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version	Revision Date:	SDS Number:	Date of last issue: 22.11.2023
2.1	28.03.2024	800010059269	Print Date 04.04.2024

### 10.2 Chemical stability

No hazardous reaction is expected when handled and stored according to provisions  
Stable under normal conditions of use.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Reacts with strong oxidising agents.

### 10.4 Conditions to avoid

Conditions to avoid : Avoid heat, sparks, open flames and other ignition sources.  
  
In certain circumstances product can ignite due to static electricity.

### 10.5 Incompatible materials

Materials to avoid : Strong oxidising agents.

### 10.6 Hazardous decomposition products

Hazardous decomposition products are not expected to form during normal storage.  
Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids and gases including carbon monoxide, carbon dioxide, sulphur oxides and unidentified organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation.

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure : Exposure may occur via inhalation, ingestion, skin absorption, skin or eye contact, and accidental ingestion.

#### Acute toxicity

##### Components:

##### **Hydrocarbons, C9, aromatics:**

Acute oral toxicity	: LD 50 (Rat, male and female): > 2000 - <= 5000 Method: Acceptable non-standard method. Remarks: May be harmful if swallowed.
Acute inhalation toxicity	: LC 50 (Rat, male and female): > 2 -<= 10 mg/l Exposure time: 4 h Test atmosphere: vapour Method: Test(s) equivalent or similar to OECD Test Guideline 403 Remarks: LC50 greater than near-saturated vapour concentration. Based on available data, the classification criteria are not met.
Acute dermal toxicity	: LD 50 (Rabbit, male and female): > 2.000 mg/kg

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version	Revision Date:	SDS Number:	Date of last issue: 22.11.2023
2.1	28.03.2024	800010059269	Print Date 04.04.2024

---

Method: Test(s) equivalent or similar to OECD Test Guideline 402

Remarks: Based on available data, the classification criteria are not met.

### Skin corrosion/irritation

#### Components:

##### Hydrocarbons, C9, aromatics:

Species	:	Rabbit
Method	:	OECD Test Guideline 404
Remarks	:	Moderately irritating to skin (but insufficient to classify). Repeated exposure may cause skin dryness or cracking.

### Serious eye damage/eye irritation

#### Components:

##### Hydrocarbons, C9, aromatics:

Species	:	Rabbit
Method	:	Test(s) equivalent or similar to OECD Test Guideline 405
Remarks	:	Slightly irritating. Insufficient to classify.

### Respiratory or skin sensitisation

#### Components:

##### Hydrocarbons, C9, aromatics:

Species	:	Guinea pig
Method	:	OECD Test Guideline 406
Remarks	:	Based on available data, the classification criteria are not met.

### Germ cell mutagenicity

#### Components:

##### Hydrocarbons, C9, aromatics:

Genotoxicity in vitro	:	Method: Test(s) equivalent or similar to OECD Guideline 471 Remarks: Based on available data, the classification criteria are not met.
-----------------------	---	---

Method: Test(s) equivalent or similar to OECD Test Guideline 473

Remarks: Based on available data, the classification criteria are not met.

Method: Test(s) equivalent or similar to OECD Test Guideline 476

Remarks: Based on available data, the classification criteria

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

are not met.

Genotoxicity in vivo : Species: Rat  
Method: Test(s) equivalent or similar to OECD Test Guideline 475  
Remarks: Based on available data, the classification criteria are not met.

Germ cell mutagenicity- Assessment : This product does not meet the criteria for classification in categories 1A/1B.

### Carcinogenicity

#### Components:

##### Hydrocarbons, C9, aromatics:

Remarks : Tumours produced in animals are not considered relevant to humans.  
Not a carcinogen.  
Based on available data, the classification criteria are not met.

Carcinogenicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

Material	GHS/CLP Carcinogenicity Classification
Hydrocarbons, C9, aromatics	No carcinogenicity classification.
Cumene	Carcinogenicity Category 1B
Benzene	Carcinogenicity Category 1A

Material	Other Carcinogenicity Classification
Cumene	IARC: Group 2B: Possibly carcinogenic to humans
Benzene	IARC: Group 1: Carcinogenic to humans

### Reproductive toxicity

#### Components:

##### Hydrocarbons, C9, aromatics:

Effects on fertility : Species: Rat  
Sex: male and female  
Application Route: Inhalation  
  
Method: Other guideline method.  
Remarks: Based on available data, the classification criteria are not met.

Reproductive toxicity - As- : This product does not meet the criteria for classification in



# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version	Revision Date:	SDS Number:	Date of last issue: 22.11.2023
2.1	28.03.2024	800010059269	Print Date 04.04.2024

assessment categories 1A/1B.

### STOT - single exposure

#### Components:

##### Hydrocarbons, C9, aromatics:

Exposure routes	:	Inhalation
Target Organs	:	Lungs, Central nervous system
Remarks	:	May cause drowsiness and dizziness. May cause respiratory irritation.

### STOT - repeated exposure

#### Components:

##### Hydrocarbons, C9, aromatics:

Remarks	:	Based on available data, the classification criteria are not met. Auditory system: prolonged and repeated exposures to high concentrations have resulted in hearing loss in rats. Kidney: caused kidney effects in male rats which are not considered relevant to humans
---------	---	--

### Repeated dose toxicity

#### Components:

##### Hydrocarbons, C9, aromatics:

Species	:	Rat, male and female
Application Route	:	Oral
Method	:	Test(s) equivalent or similar to OECD Test Guideline 408
Target Organs	:	No specific target organs noted

Species	:	Rat, male and female
Application Route	:	Inhalation
Test atmosphere	:	vapour
Method	:	Test(s) equivalent or similar to OECD Test Guideline 452
Target Organs	:	No specific target organs noted

### Aspiration toxicity

#### Components:

##### Hydrocarbons, C9, aromatics:

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version	Revision Date:	SDS Number:	Date of last issue: 22.11.2023
2.1	28.03.2024	800010059269	Print Date 04.04.2024

### 11.2 Information on other hazards

#### Endocrine disrupting properties

##### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

#### Further information

##### Product:

Remarks : Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

##### Components:

#### Hydrocarbons, C9, aromatics:

Remarks : Classifications by other authorities under varying regulatory frameworks may exist.

## SECTION 12: Ecological information

### 12.1 Toxicity

##### Components:

#### Hydrocarbons, C9, aromatics:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 9,2 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203  
Remarks: Toxic  
LC/EC/IC50 >1 - <=10 mg/l

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 3,2 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202  
Remarks: Toxic  
LC/EC/IC50 >1 - <=10 mg/l

Toxicity to algae/aquatic plants : ErL50 (Pseudokirchneriella subcapitata (algae)): 2,9 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
Remarks: Toxic  
LC/EC/IC50 >1 - <=10 mg/l

Toxicity to microorganisms : NOEC (Activated sludge): > 99 mg/l

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version	Revision Date:	SDS Number:	Date of last issue: 22.11.2023
2.1	28.03.2024	800010059269	Print Date 04.04.2024

Exposure time: 0,16 h  
Method: OECD Test Guideline 209  
Remarks: Practically non toxic:  
LC/EC/IC50 > 100 mg/l

Toxicity to fish (Chronic toxicity) : Remarks: Data not available

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : Remarks: Data not available

### 12.2 Persistence and degradability

#### Components:

#### **Hydrocarbons, C9, aromatics:**

Biodegradability : Biodegradation: 78 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F  
Remarks: Readily biodegradable.  
Oxidises rapidly by photo-chemical reactions in air.

### 12.3 Bioaccumulative potential

#### Components:

#### **Hydrocarbons, C9, aromatics:**

Bioaccumulation : Remarks: Contains components with the potential to bioaccumulate.

### 12.4 Mobility in soil

#### Components:

#### **Hydrocarbons, C9, aromatics:**

Mobility : Remarks: Floats on water., If it enters soil, it will adsorb to soil particles and will not be mobile.

### 12.5 Results of PBT and vPvB assessment

#### Components:

#### **Hydrocarbons, C9, aromatics:**

Assessment : The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB..

### 12.6 Endocrine disrupting properties

#### Product:

Assessment : The substance/mixture does not contain components considered to

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version	Revision Date:	SDS Number:	Date of last issue: 22.11.2023
2.1	28.03.2024	800010059269	Print Date 04.04.2024

have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### 12.7 Other adverse effects

#### Product:

Additional ecological information : Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

#### Components:

##### **Hydrocarbons, C9, aromatics:**

Additional ecological information : Does not have ozone depletion potential.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : Recover or recycle if possible.  
It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.  
Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment.  
Do not dispose into the environment, in drains or in water courses.  
Do not dispose of tank water bottoms by allowing them to drain into the ground. This will result in soil and groundwater contamination.  
Waste arising from a spillage or tank cleaning should be disposed of in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand.

Waste, spills or used product is dangerous waste.

Disposal should be in accordance with applicable regional, national, and local laws and regulations.  
Local regulations may be more stringent than regional or national requirements and must be complied with.

MARPOL - see International Convention for the Prevention of Pollution from Ships (MARPOL 73/78) which provides technical aspects at controlling pollutions from ships.

Contaminated packaging : Drain container thoroughly.  
After draining, vent in a safe place away from sparks and fire.  
Residues may cause an explosion hazard. Do not puncture,

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version	Revision Date:	SDS Number:	Date of last issue: 22.11.2023
2.1	28.03.2024	800010059269	Print Date 04.04.2024

cut or weld uncleaned drums.  
Send to drum recoverer or metal reclaimer.  
Comply with any local recovery or waste disposal regulations.

### SECTION 14: Transport information

#### 14.1 UN number or ID number

ADN	: 1268
ADR	: 1268
RID	: 1268
IMDG	: 1268
IATA	: 1268

#### 14.2 UN proper shipping name

ADN	: PETROLEUM DISTILLATES, N.O.S. (NAPHTHA)
ADR	: PETROLEUM DISTILLATES, N.O.S.
RID	: PETROLEUM DISTILLATES, N.O.S.
IMDG	: PETROLEUM DISTILLATES, N.O.S. (NAPHTHA)
IATA	: Petroleum distillates, n.o.s.

#### 14.3 Transport hazard class(es)

ADN	: 3
ADR	: 3
RID	: 3
IMDG	: 3
IATA	: 3

#### 14.4 Packing group

ADN	
Packing group	: III
Classification Code	: F1
Labels	: 3 (N2, F)
CDNI Inland Water Waste Agreement	: NST 8963 Solvent
ADR	
Packing group	: III
Classification Code	: F1
Hazard Identification Number	: 30
Labels	: 3
RID	
Packing group	: III
Classification Code	: F1

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version	Revision Date:	SDS Number:	Date of last issue: 22.11.2023
2.1	28.03.2024	800010059269	Print Date 04.04.2024

Hazard Identification Number : 30  
Labels : 3

### IMDG

Packing group : III  
Labels : 3

### IATA

Packing group : III  
Labels : 3

#### 14.5 Environmental hazards

##### ADN

Environmentally hazardous : yes

##### ADR

Environmentally hazardous : yes

##### RID

Environmentally hazardous : yes

##### IMDG

Marine pollutant : yes

#### 14.6 Special precautions for user

Remarks : Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

#### 14.7 Maritime transport in bulk according to IMO instruments

MARPOL Annex 1 rules apply for bulk shipments by sea.

**Additional Information** : This product may be transported under nitrogen blanketing. Nitrogen is an odourless and invisible gas. Exposure to nitrogen may cause asphyxiation or death. Personnel must observe strict safety precautions when involved with a confined space entry.

## SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	: Conditions of restriction for the following entries should be considered: Cumene (Number on list 28) Benzene (Number on list 72, 5, 29, 28)
REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	: This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version	Revision Date:	SDS Number:	Date of last issue: 22.11.2023
2.1	28.03.2024	800010059269	Print Date 04.04.2024

REACH - List of substances subject to authorisation (Annex XIV) : Product is not subject to Authorisation under REACH.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P5c

FLAMMABLE LIQUIDS

E2

ENVIRONMENTAL HAZARDS

### Other regulations:

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

Product is subject to Major accident risk decision 2015 (BRZO+) based on Seveso III directive (2012/18/EU).

The national inventory is based on the CAS number 64742-95-6.

### The components of this product are reported in the following inventories:

DSL : Listed

IECSC : Listed

TSCA : Listed

KECI : Listed

PICCS : Listed

TCSI : Listed

AIIC : Listed

NZIoC : Listed

### 15.2 Chemical safety assessment

A Chemical Safety Assessment has been carried out for this substance.

## SECTION 16: Other information

### Full text of other abbreviations

2019/1831/EU	:	Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values
NL WG	:	Netherlands. Law on Labour conditions - Occupational Exposure Limits

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version	Revision Date:	SDS Number:	Date of last issue: 22.11.2023
2.1	28.03.2024	800010059269	Print Date 04.04.2024

2019/1831/EU / TWA	:	Limit Value - eight hours
2019/1831/EU / STEL	:	Short term exposure limit
NL WG / TLV-8hr	:	Time Weighted Average
NL WG / TLV-15 min	:	Short Term Exposure Limit

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

Training advice : Provide adequate information, instruction and training for operators.

Other information : For Industry guidance and tools on REACH please visit the CEFIC website at <http://cefic.org/Industry-support>.  
The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB.

A vertical bar (|) in the left margin indicates an amendment from the previous version.

This product is classified as H304 (May be fatal if swallowed)



# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1	Revision Date: 28.03.2024	SDS Number: 800010059269	Date of last issue: 22.11.2023 Print Date 04.04.2024
----------------	------------------------------	-----------------------------	---

and enters airways). The risk relates to potential for aspiration. The risk arising from aspiration hazard is solely related to the physico-chemical properties of the substance. The risk can therefore be controlled by implementing risk management measures tailored to this specific hazard and included within Section 8 of the SDS. An exposure scenario is not presented.

This product is classified as R66 / EUH066 (Repeated exposure may cause skin dryness or cracking). The risk relates to the potential for repeated or prolonged dermal contact. The risk arising from contact is solely related to the physico-chemical properties of the substance. The risk can therefore be controlled by implementing risk management measures tailored to this specific hazard and included within Section 8 of the SDS. An exposure scenario is not presented.

Sources of key data used to compile the Safety Data Sheet : The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID data base, EC 1272 regulation, etc).

### Identified Uses according to the Use Descriptor System

#### Uses - Worker

Title : Manufacture of substance  
- Industrial

#### Uses - Worker

Title : Distribution of substance  
- Industrial

#### Uses - Worker

Title : Formulation & (re)packing of substances and mixtures  
- Industrial

#### Uses - Worker

Title : Uses in Coatings  
- Industrial

#### Uses - Worker

Title : Use in Cleaning Agents  
- Industrial

#### Uses - Worker

Title : Uses in Coatings  
- Professional

#### Uses - Worker

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version	Revision Date:	SDS Number:	Date of last issue: 22.11.2023
2.1	28.03.2024	800010059269	Print Date 04.04.2024

---

Title	:	Use in Cleaning Agents - Professional
-------	---	--

### Uses - Worker

Title	:	Use in Oil and Gas field drilling and production operations - Industrial
-------	---	---

### Uses - Worker

Title	:	Lubricants - Industrial
-------	---	----------------------------

### Uses - Worker

Title	:	Lubricants - Professional Low Environmental Release
-------	---	---

### Uses - Worker

Title	:	Lubricants - Professional High Environmental Release
-------	---	--

### Uses - Worker

Title	:	Metal working fluids / rolling oils - Industrial
-------	---	---

### Uses - Worker

Title	:	Metal working fluids / rolling oils - Professional
-------	---	---

### Uses - Worker

Title	:	Use as binders and release agents - Industrial
-------	---	---

### Uses - Worker

Title	:	Use as binders and release agents - Professional
-------	---	---

### Uses - Worker

Title	:	Use in Agrochemicals uses - Professional
-------	---	---

### Uses - Worker

Title	:	Use as a fuel
-------	---	---------------

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1	Revision Date: 28.03.2024	SDS Number: 800010059269	Date of last issue: 22.11.2023 Print Date 04.04.2024
----------------	------------------------------	-----------------------------	---

---

- Industrial

**Uses - Worker**

Title : Use as a fuel  
- Professional

**Uses - Worker**

Title : Functional Fluids  
- Professional

**Uses - Worker**

Title : Functional Fluids  
- Industrial

**Uses - Worker**

Title : Road and construction applications  
- Professional

**Uses - Worker**

Title : Use in laboratories  
- Industrial

**Uses - Worker**

Title : Use in laboratories  
- Professional

**Uses - Worker**

Title : Water treatment chemicals  
- Industrial

**Uses - Worker**

Title : Water treatment chemicals  
- Professional

**Identified Uses according to the Use Descriptor System**

**Uses - Consumer**

Title : Functional Fluids  
- Consumer

**Uses - Consumer**

Title : Use as a fuel  
- Consumer

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version	Revision Date:	SDS Number:	Date of last issue: 22.11.2023
2.1	28.03.2024	800010059269	Print Date 04.04.2024

---

### Uses - Consumer

Title : Use in Agrochemicals uses  
- Consumer

### Uses - Consumer

Title : Lubricants  
- Consumer  
High Environmental Release

### Uses - Consumer

Title : Lubricants  
- Consumer  
Low Environmental Release

### Uses - Consumer

Title : Use in Cleaning Agents  
- Consumer

### Uses - Consumer

Title : Uses in Coatings  
- Consumer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

NL / EN

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

### Exposure Scenario - Worker

<b>300000000750</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Manufacture of substance- Industrial
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU3, SU8, SU9 <b>Process Categories:</b> PROC 1, PROC 2, PROC 3, PROC 4, PROC 8a, PROC 8b, PROC 15 <b>Environmental Release Categories:</b> ERC1, ERC4, ESVOC SpERC 1.1.v1
<b>Scope of process</b>	Manufacture of the substance or use as a process chemical or extraction agent. Includes recycling/ recovery, material transfers, storage, maintenance and loading (including marine vessel/barge, road/rail car and bulk container), sampling and associated laboratory activities.

SECTION 2		OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Section 2.1		Control of Worker Exposure	
Product Characteristics			
Physical form of product		Liquid, vapour pressure < 0.5 kPa at STP	
Concentration of the Substance in Mixture/Article		Covers use of substance/product up to 100% (unless stated differently).,	
Frequency and Duration of Use			
Covers daily exposures up to 8 hours (unless stated differently).			
Other Operational Conditions affecting Exposure			
Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.			
Contributing Scenarios		Risk Management Measures	
General exposures (closed systems)PROC1PROC2PROC3		No other specific measures identified.	
General exposures (open systems)PROC4		No other specific measures identified.	
Process samplingPROC8b		No other specific measures identified.	
Laboratory activitiesPROC15		No other specific measures identified.	
Bulk transfers(open systems)PROC8b		No other specific measures identified.	
Bulk transfers(closed systems)PROC8b		No other specific measures identified.	
Equipment cleaning and maintenancePROC8a		No other specific measures identified.	
Storage.PROC1PROC2		Store substance within a closed system.	
Section 2.2		Control of Environmental Exposure	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

Substance is complex UVCB.	
Predominantly hydrophobic.	
Readily biodegradable.	
<b>Amounts Used</b>	
Fraction of EU tonnage used in region:	0,1
Regional use tonnage (tonnes/year):	2,4E+04
Fraction of Regional tonnage used locally:	1
Annual site tonnage (tonnes/year):	2,4E+04
Maximum daily site tonnage (kg/day):	7,9E+04
<b>Frequency and Duration of Use</b>	
Continuous release.	
Emission Days (days/year):	300
<b>Environmental factors not influenced by risk management</b>	
Local freshwater dilution factor:	10
Local marine water dilution factor:	100
<b>Other Operational Conditions affecting Environmental Exposure</b>	
Release fraction to air from process (initial release prior to RMM):	1,0E-02
Release fraction to wastewater from process (initial release prior to RMM):	3,0E-04
Release fraction to soil from process (initial release prior to RMM):	1,0E-04
<b>Technical conditions and measures at process level (source) to prevent release</b>	
Common practices vary across sites thus conservative process re-lease estimates used.	
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>	
Risk from environmental exposure is driven by freshwater sediment.	
Prevent discharge of undissolved substance to or recover from onsite wastewater.	
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	90
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)	15,9
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	0
<b>Organisational measures to prevent/limit release from site</b>	
Do not apply industrial sludge to natural soils.	
Sludge should be incinerated, contained or reclaimed.	
<b>Conditions and Measures related to municipal sewage treatment plant</b>	
Estimated substance removal from wastewater via domestic sewage treatment (%)	93,6
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	93,6
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	1,0E+06
Assumed domestic sewage treatment plant flow (m3/d)	1,0E+04
<b>Conditions and Measures related to external treatment of waste for disposal</b>	
During manufacturing no waste of the substance is generated.	
<b>Conditions and measures related to external recovery of waste</b>	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version	Revision Date:	SDS Number:	Date of last issue: 22.11.2023
2.1	28.03.2024	800010059269	Print Date 04.04.2024

During manufacturing no waste of the substance is generated.

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
------------------	----------------------------

**Section 3.1 - Health**

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

**Section 3.2 -Environment**

The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
------------------	--

**Section 4.1 - Health**

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.  
Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

**Section 4.2 -Environment**

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org>).

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

### Exposure Scenario - Worker

<b>300000000753</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Distribution of substance- Industrial
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU3, SU8, SU9 <b>Process Categories:</b> PROC 1, PROC 2, PROC 3, PROC 4, PROC 8a, PROC 8b, PROC 9, PROC 15 <b>Environmental Release Categories:</b> ERC1, ERC2, ERC3, ERC4, ERC5, ERC6a, ERC6b, ERC 6C,, ERC7, ESVOC SpERC 1.1b.v1
<b>Scope of process</b>	Loading (including marine vessel/barge, rail/road car and IBC loading) and repacking (including drums and small packs) of substance, including its sampling, storage, unloading distribution and associated laboratory activities.

SECTION 2		OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Section 2.1		Control of Worker Exposure	
Product Characteristics			
Physical form of product		Liquid, vapour pressure < 0.5 kPa at STP	
Concentration of the Substance in Mixture/Article		Covers use of substance/product up to 100% (unless stated differently).,	
Frequency and Duration of Use			
Covers daily exposures up to 8 hours (unless stated differently).			
Other Operational Conditions affecting Exposure			
Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.			
Contributing Scenarios		Risk Management Measures	
General exposures (closed systems)PROC1PROC2PROC3		No other specific measures identified.	
General exposures (open systems)PROC4		No other specific measures identified.	
Process samplingPROC3		No other specific measures identified.	
Laboratory activitiesPROC15		No other specific measures identified.	
Bulk transfers(closed systems)PROC8b		No other specific measures identified.	
Bulk transfers(open systems)PROC8b		No other specific measures identified.	
Drum and small package fillingPROC9		No other specific measures identified.	
Equipment cleaning and maintenancePROC8a		No other specific measures identified.	
Storage.PROC1PROC2		Store substance within a closed system.	



# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

<b>Section 2.2</b>		<b>Control of Environmental Exposure</b>
Substance is complex UVCB.		
Predominantly hydrophobic.		
Readily biodegradable.		
<b>Amounts Used</b>		
Fraction of EU tonnage used in region:		0,1
Regional use tonnage (tonnes/year):		850
Fraction of Regional tonnage used locally:		2,0E-03
Annual site tonnage (tonnes/year):		1,7
Maximum daily site tonnage (kg/day):		85
<b>Frequency and Duration of Use</b>		
Continuous release.		
Emission Days (days/year):		20
<b>Environmental factors not influenced by risk management</b>		
Local freshwater dilution factor:		10
Local marine water dilution factor:		100
<b>Other Operational Conditions affecting Environmental Exposure</b>		
Release fraction to air from process (initial release prior to RMM):		1,0E-03
Release fraction to wastewater from process (initial release prior to RMM):		1,0E-05
Release fraction to soil from process (initial release prior to RMM):		1,0E-05
<b>Technical conditions and measures at process level (source) to prevent release</b>		
Common practices vary across sites thus conservative process re-release estimates used.		
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>		
Risk from environmental exposure is driven by freshwater.		
Prevent discharge of undissolved substance to or recover from onsite wastewater.		
No wastewater treatment required.		
Treat air emission to provide a typical removal efficiency of (%)		90
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)		0
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.		0
<b>Organisational measures to prevent/limit release from site</b>		
Do not apply industrial sludge to natural soils.		
Sludge should be incinerated, contained or reclaimed.		
<b>Conditions and Measures related to municipal sewage treatment plant</b>		
Estimated substance removal from wastewater via domestic sewage treatment (%)		93,6
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)		93,6
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)		2,1E+05
Assumed domestic sewage treatment plant flow (m3/d)		2,0E+03
<b>Conditions and Measures related to external treatment of waste for disposal</b>		
External treatment and disposal of waste should comply with applicable local and/or regional regulations.		

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

### Conditions and measures related to external recovery of waste

External recovery and recycling of waste should comply with applicable local and/or regional regulations.

### SECTION 3

### EXPOSURE ESTIMATION

#### Section 3.1 - Health

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

#### Section 3.2 -Environment

The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

### SECTION 4

### GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO

#### Section 4.1 - Health

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.  
Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

#### Section 4.2 -Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org>).

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

### Exposure Scenario - Worker

<b>300000000754</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Formulation & (re)packing of substances and mixtures- Industrial
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU3, SU10 <b>Process Categories:</b> PROC 1, PROC 2, PROC 3, PROC 4, PROC 5, PROC 8a, PROC 8b, PROC 9, PROC 14, PROC 15 <b>Environmental Release Categories:</b> ERC2, ESVOC SpERC 2.2.v1
<b>Scope of process</b>	Formulation, packing and re-packing of the substance and its mixtures in batch or continuous operations, including storage, materials transfers, mixing, tableting, compression, pelletisation, extrusion, large and small scale packing, sampling, maintenance and associated laboratory activities.

SECTION 2		OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Section 2.1		Control of Worker Exposure	
Product Characteristics			
Physical form of product		Liquid, vapour pressure < 0.5 kPa at STP	
Concentration of the Sub-stance in Mixture/Article		Covers use of substance/product up to 100% (unless stated differently).,	
Frequency and Duration of Use			
Covers daily exposures up to 8 hours (unless stated differently).			
Other Operational Conditions affecting Exposure			
Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.			
Contributing Scenarios		Risk Management Measures	
General exposures (closed systems)PROC1PROC2PROC3		No other specific measures identified.	
General exposures (open sys-tems)PROC4		No other specific measures identified.	
Batch processes at elevated temperaturesOperation is car-ried out at elevated temperature (> 20°C above ambient temper-ature).Use in contained batch processesPROC3		No other specific measures identified.	
Process samplingPROC3		No other specific measures identified.	
Laboratory activitiesPROC15		No other specific measures identified.	
Bulk transfersPROC8b		No other specific measures identified.	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

Mixing operations (open systems)PROC5	No other specific measures identified.
Manual Transfer from/pouring from containersPROC8a	No other specific measures identified.
Drum/batch transfersPROC8b	No other specific measures identified.
Production or preparation or articles by tableting, compression, extrusion or pelletisationPROC14	No other specific measures identified.
Drum and small package fillingPROC9	No other specific measures identified.
Equipment cleaning and maintenancePROC8a	No other specific measures identified.
Storage.PROC1PROC2	Store substance within a closed system.

<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Substance is complex UVCB.	
Predominantly hydrophobic.	
Readily biodegradable.	
<b>Amounts Used</b>	
Fraction of EU tonnage used in region:	0,1
Regional use tonnage (tonnes/year):	730
Fraction of Regional tonnage used locally:	1
Annual site tonnage (tonnes/year):	730
Maximum daily site tonnage (kg/day):	7,3E+03
<b>Frequency and Duration of Use</b>	
Continuous release.	
Emission Days (days/year):	100
<b>Environmental factors not influenced by risk management</b>	
Local freshwater dilution factor:	10
Local marine water dilution factor:	100
<b>Other Operational Conditions affecting Environmental Exposure</b>	
Release fraction to air from process (after typical onsite RMMs consistent with EU Solvent Emissions Directive requirements):	1,0E-02
Release fraction to wastewater from process (initial release prior to RMM):	2,0E-04
Release fraction to soil from process (initial release prior to RMM):	1,0E-04
<b>Technical conditions and measures at process level (source) to prevent release</b>	
Common practices vary across sites thus conservative process release estimates used.	
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>	
Risk from environmental exposure is driven by freshwater sediment.	
Prevent discharge of undissolved substance to or recover from onsite wastewater.	
No wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	0
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)	0
If discharging to domestic sewage treatment plant, no secondary	0

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

wastewater treatment required.	
<b>Organisational measures to prevent/limit release from site</b>	
Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.	
<b>Conditions and Measures related to municipal sewage treatment plant</b>	
Estimated substance removal from wastewater via domestic sewage treatment (%)	93,6
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	93,6
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	3,1E+05
Assumed domestic sewage treatment plant flow (m3/d)	2,0E+03
<b>Conditions and Measures related to external treatment of waste for disposal</b>	
External treatment and disposal of waste should comply with applicable local and/or regional regulations.	
<b>Conditions and measures related to external recovery of waste</b>	
External recovery and recycling of waste should comply with applicable local and/or regional regulations.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	

<b>Section 3.2 -Environment</b>	
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.	

<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
<b>Section 4.1 - Health</b>	
Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.	

<b>Section 4.2 -Environment</b>	
Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.	
Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.	
Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.	
Further details on scaling and control technologies are provided in SpERC factsheet	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version  
2.1

Revision Date:  
28.03.2024

SDS Number:  
800010059269

Date of last issue: 22.11.2023  
Print Date 04.04.2024

---

( <a href="http://cefic.org">http://cefic.org</a> ).
--

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version  
2.1

Revision Date:  
28.03.2024

SDS Number:  
800010059269

Date of last issue: 22.11.2023  
Print Date 04.04.2024

### Exposure Scenario - Worker

**300000000755**

SECTION 1	EXPOSURE SCENARIO TITLE
Title	Uses in Coatings- Industrial
Use Descriptor	<b>Sector of Use:</b> SU3 <b>Process Categories:</b> PROC 1, PROC 2, PROC 3, PROC 4, PROC 5, PROC 7, PROC 8a, PROC 8b, PROC 9, PROC 10, PROC 13, PROC 14, PROC 15 <b>Environmental Release Categories:</b> ERC4, ESVOC SpERC 4.3a.v1
Scope of process	Covers the use in coatings (paints, inks, adhesives, etc) including exposures during use (including materials receipt, storage, preparation and transfer from bulk and semi-bulk, application by spray, roller, spreader, dip, flow, fluidised bed on production lines and film formation) and equipment cleaning, maintenance and associated laboratory activities.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
Section 2.1	Control of Worker Exposure
<b>Product Characteristics</b>	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of the Substance in Mixture/Article	Covers use of substance/product up to 100% (unless stated differently).,
<b>Frequency and Duration of Use</b>	
Covers daily exposures up to 8 hours (unless stated differently).	
<b>Other Operational Conditions affecting Exposure</b>	
Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.	
<b>Contributing Scenarios</b>	<b>Risk Management Measures</b>
General exposures (closed systems)PROC1	No other specific measures identified.
General exposures (closed systems)with sample collectionUse in contained systemsPROC2	No other specific measures identified.
Film formation - force drying, stoving and other technologies.(closed systems)Operation is carried out at elevated temperature (> 20°C above ambient temperature).PROC2	No other specific measures identified.
Mixing operations (closed systems)General expo-	No other specific measures identified.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version  
2.1

Revision Date:  
28.03.2024

SDS Number:  
800010059269

Date of last issue: 22.11.2023  
Print Date 04.04.2024

tures (closed systems)PROC3	
Film formation - air dryingPROC4	No other specific measures identified.
Preparation of material for applicationMixing operations (open systems)PROC5	No other specific measures identified.
Spraying (automatic/robotic)PROC7	Carry out in a vented booth provided with laminar airflow.
ManualSprayingPROC7	Wear a respirator conforming to EN140 with Type A filter or better.
Material transfersNon-dedicated facilityPROC8a	No other specific measures identified.
Material transfersDedicated facilityPROC8b	No other specific measures identified.
Roller, spreader, flow applicationPROC10	No other specific measures identified.
Dipping, immersion and pouringPROC13	No other specific measures identified.
Laboratory activitiesPROC15	No other specific measures identified.
Material transfersDrum/batch transfersTransfer from/pouring from containersPROC9	No other specific measures identified.
Production or preparation or articles by tableting, compression, extrusion or pelletisationPROC14	No other specific measures identified.
Equipment cleaning and maintenancePROC8a	No other specific measures identified.
Storage.PROC1	Store substance within a closed system.
<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Substance is complex UVCB.	
Predominantly hydrophobic.	
Readily biodegradable.	
<b>Amounts Used</b>	
Fraction of EU tonnage used in region:	0,1
Regional use tonnage (tonnes/year):	7,6E+03
Fraction of Regional tonnage used locally:	1
Annual site tonnage (tonnes/year):	7,6E+03
Maximum daily site tonnage (kg/day):	2,5E+04
<b>Frequency and Duration of Use</b>	
Continuous release.	
Emission Days (days/year):	300
<b>Environmental factors not influenced by risk management</b>	
Local freshwater dilution factor:	10
Local marine water dilution factor:	100



# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

<b>Other Operational Conditions affecting Environmental Exposure</b>	
Release fraction to air from process (initial release prior to RMM):	9,8E-01
Release fraction to wastewater from process (initial release prior to RMM):	7,0E-04
Release fraction to soil from process (initial release prior to RMM):	0
<b>Technical conditions and measures at process level (source) to prevent release</b>	
Common practices vary across sites thus conservative process re-release estimates used.	
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>	
Risk from environmental exposure is driven by freshwater sediment.	
Prevent discharge of undissolved substance to or recover from onsite wastewater.	
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	90
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)	77,7
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	0
<b>Organisational measures to prevent/limit release from site</b>	
Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.	
<b>Conditions and Measures related to municipal sewage treatment plant</b>	
Estimated substance removal from wastewater via domestic sewage treatment (%)	93,6
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	93,6
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	8,8E+04
Assumed domestic sewage treatment plant flow (m3/d)	2,0E+03
<b>Conditions and Measures related to external treatment of waste for disposal</b>	
External treatment and disposal of waste should comply with applicable local and/or regional regulations.	
<b>Conditions and measures related to external recovery of waste</b>	
External recovery and recycling of waste should comply with applicable local and/or regional regulations.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	

<b>Section 3.2 -Environment</b>
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version	Revision Date:	SDS Number:	Date of last issue: 22.11.2023
2.1	28.03.2024	800010059269	Print Date 04.04.2024

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
<b>Section 4.1 - Health</b>	
Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.	
<b>Section 4.2 -Environment</b>	
Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.	
Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.	
Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.	
Further details on scaling and control technologies are provided in SpERC factsheet ( <a href="http://cefic.org">http://cefic.org</a> ).	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

### Exposure Scenario - Worker

<b>300000000757</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Use in Cleaning Agents- Industrial
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU3 <b>Process Categories:</b> PROC 1, PROC 2, PROC 3, PROC 4, PROC 7, PROC 8a, PROC 8b, PROC 10, PROC 13 <b>Environmental Release Categories:</b> ERC4, ESVOC SpERC 4.4a.v1
<b>Scope of process</b>	Covers the use as a component of cleaning products including transfer from storage, pouring/unloading from drums or containers. Exposures during mixing/diluting in the preparatory phase and cleaning activities (including spraying, brushing, dipping, wiping, automated and by hand), related equipment cleaning and maintenance.

<b>SECTION 2</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
<b>Section 2.1</b>	<b>Control of Worker Exposure</b>
<b>Product Characteristics</b>	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of the Substance in Mixture/Article	Covers use of substance/product up to 100% (unless stated differently).,
<b>Frequency and Duration of Use</b>	
Covers daily exposures up to 8 hours (unless stated differently).	
<b>Other Operational Conditions affecting Exposure</b>	
Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.	
<b>Contributing Scenarios</b>	<b>Risk Management Measures</b>

Bulk transfersNon-dedicated facilityPROC8a	No other specific measures identified.
Automated process with (semi) closed systems.Use in contained systemsPROC2	No other specific measures identified.
Automated process with (semi) closed systems.Drum/batch transfersUse in contained batch processesPROC3	No other specific measures identified.
Application of cleaning products in closed systemsPROC2	No other specific measures identified.
Filling/ preparation of equipment from drums or containers.PROC8b	No other specific measures identified.
Use in contained batch processesPROC4	No other specific measures identified.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

Degreasing small objects in cleaning stationPROC13	No other specific measures identified.
Cleaning with low-pressure washersPROC10	No other specific measures identified.
Cleaning with high pressure washersPROC7	Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Limit the substance content in the product to 5 %.
ManualSurfacesCleaningPROC10	No other specific measures identified.
Storage.PROC1	Store substance within a closed system.

<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Substance is complex UVCB.	
Predominantly hydrophobic.	
Readily biodegradable.	
<b>Amounts Used</b>	
Fraction of EU tonnage used in region:	0,1
Regional use tonnage (tonnes/year):	320
Fraction of Regional tonnage used locally:	3,2E-01
Annual site tonnage (tonnes/year):	100
Maximum daily site tonnage (kg/day):	5,0E+03
<b>Frequency and Duration of Use</b>	
Continuous release.	
Emission Days (days/year):	20
<b>Environmental factors not influenced by risk management</b>	
Local freshwater dilution factor:	10
Local marine water dilution factor:	100
<b>Other Operational Conditions affecting Environmental Exposure</b>	
Release fraction to air from process (initial release prior to RMM):	1,0
Release fraction to wastewater from process (initial release prior to RMM):	3,0E-06
Release fraction to soil from process (initial release prior to RMM):	0
<b>Technical conditions and measures at process level (source) to prevent release</b>	
Common practices vary across sites thus conservative process release estimates used.	
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>	
Risk from environmental exposure is driven by freshwater.	
Prevent discharge of undissolved substance to or recover from onsite wastewater.	
No wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	70
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)	0
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	0
<b>Organisational measures to prevent/limit release from site</b>	
Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

<b>Conditions and Measures related to municipal sewage treatment plant</b>	
Estimated substance removal from wastewater via domestic sewage treatment (%)	93,6
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	93,6
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	8,3E+06
Assumed domestic sewage treatment plant flow (m3/d)	2,0E+03
<b>Conditions and Measures related to external treatment of waste for disposal</b>	
External treatment and disposal of waste should comply with applicable local and/or regional regulations.	
<b>Conditions and measures related to external recovery of waste</b>	
External recovery and recycling of waste should comply with applicable local and/or regional regulations.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	

<b>Section 3.2 -Environment</b>
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
<b>Section 4.1 - Health</b>	
Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.	

<b>Section 4.2 -Environment</b>
Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.
Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.
Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.
Further details on scaling and control technologies are provided in SpERC factsheet ( <a href="http://cefic.org">http://cefic.org</a> ).

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

### Exposure Scenario - Worker

<b>300000000756</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Uses in Coatings- Professional
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU22 <b>Process Categories:</b> PROC 1, PROC 2, PROC 3, PROC 4, PROC 5, PROC 8a, PROC 8b, PROC 10, PROC 11, PROC 13, PROC 15, PROC 19 <b>Environmental Release Categories:</b> ERC8a, ERC8d, ESVOC SpERC 8.3b.v1
<b>Scope of process</b>	Covers the use in coatings (paints, inks, adhesives, etc) including exposures during use (including materials receipt, storage, preparation and transfer from bulk and semi-bulk, application by spray, roller, brush, spreader by hand or similar methods, and film formation), and equipment cleaning, maintenance and associated laboratory activities.

SECTION 2		OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Section 2.1		Control of Worker Exposure	
Product Characteristics			
Physical form of product		Liquid, vapour pressure < 0.5 kPa at STP	
Concentration of the Substance in Mixture/Article		Covers use of substance/product up to 100% (unless stated differently).,	
Frequency and Duration of Use			
Covers daily exposures up to 8 hours (unless stated differently).			
Other Operational Conditions affecting Exposure			
Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.			
Contributing Scenarios		Risk Management Measures	
General exposures (closed systems)PROC1		No other specific measures identified.	
Filling/ preparation of equipment from drums or containers.Use in contained systemsPROC2		No other specific measures identified.	
General exposures (closed systems)Use in contained systemsPROC2		No other specific measures identified.	
Preparation of material for applicationUse in contained batch processesPROC3		No other specific measures identified.	
Film formation - air dryingOutdoorPROC4		No other specific measures identified.	
Film formation - air dryingIndoorPROC4		No other specific measures identified.	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

Preparation of material for applicationIndoorPROC5	No other specific measures identified.
Preparation of material for applicationOutdoorPROC5	No other specific measures identified.
Material transfersDrum/batch transfersNon-dedicated facilityPROC8a	No other specific measures identified.
Material transfersDrum/batch transfersDedicated facilityPROC8b	No other specific measures identified.
Roller, spreader, flow application-IndoorPROC10	No other specific measures identified.
Roller, spreader, flow applicationOutdoorPROC10	No other specific measures identified.
ManualSprayingIndoorPROC11	Carry out in a vented booth or extracted enclosure. , or: Wear a full face respirator conforming to EN136 with Type A/P2 filter or better.
ManualSprayingOutdoorPROC11	Ensure operation is undertaken outdoors. Avoid carrying out activities involving exposure for more than 4 hours Limit the substance content in the mixture to 50 %. , or: Wear a full face respirator conforming to EN136 with Type A/P2 filter or better.
Dipping, immersion and pouringIndoorPROC13	No other specific measures identified.
Dipping, immersion and pouringOutdoorPROC13	No other specific measures identified.
Laboratory activitiesPROC15	No other specific measures identified.
Hand application - fingerpaints, pastels, adhesivesIndoorPROC19	No other specific measures identified.
Hand application - fingerpaints, pastels, adhesivesOutdoorPROC19	No other specific measures identified.
Storage.PROC1	Store substance within a closed system.

### Section 2.2

### Control of Environmental Exposure

Substance is complex UVCB.

Predominantly hydrophobic.

Readily biodegradable.

### Amounts Used

Fraction of EU tonnage used in region:

0,1

Regional use tonnage (tonnes/year):

2,2E+03

Fraction of Regional tonnage used locally:

5,0E-04

Annual site tonnage (tonnes/year):

1,1

Maximum daily site tonnage (kg/day):

3,0

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

<b>Frequency and Duration of Use</b>	
Continuous release.	
Emission Days (days/year):	365
<b>Environmental factors not influenced by risk management</b>	
Local freshwater dilution factor:	10
Local marine water dilution factor:	100
<b>Other Operational Conditions affecting Environmental Exposure</b>	
Release fraction to air from wide dispersive use (regional only):	9,8E-01
Release fraction to wastewater from wide dispersive use:	1,0E-02
Release fraction to soil from wide dispersive use (regional only):	1,0E-02
<b>Technical conditions and measures at process level (source) to prevent release</b>	
Common practices vary across sites thus conservative process re-lease estimates used.	
<b>Technical onsite conditions and measures to reduce or limit discharges, air emis-sions and releases to soil</b>	
Risk from environmental exposure is driven by freshwater.	
Prevent discharge of undissolved substance to or recover from onsite wastewater.	
No wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	0
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)	0
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	0
<b>Organisational measures to prevent/limit release from site</b>	
Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.	
<b>Conditions and Measures related to municipal sewage treatment plant</b>	
Estimated substance removal from wastewater via domestic sewage treatment (%)	93,6
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	93,6
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	4,7E+03
Assumed domestic sewage treatment plant flow (m3/d)	2,0E+03
<b>Conditions and Measures related to external treatment of waste for disposal</b>	
External treatment and disposal of waste should comply with applicable local and/or regional regulations.	
<b>Conditions and measures related to external recovery of waste</b>	
External recovery and recycling of waste should comply with applicable local and/or regional regulations.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	



# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version	Revision Date:	SDS Number:	Date of last issue: 22.11.2023
2.1	28.03.2024	800010059269	Print Date 04.04.2024

### Section 3.2 -Environment

The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

### SECTION 4

### GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO

#### Section 4.1 - Health

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

#### Section 4.2 -Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org>).

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

### Exposure Scenario - Worker

<b>300000000758</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Use in Cleaning Agents- Professional
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU22 <b>Process Categories:</b> PROC 1, PROC 2, PROC 3, PROC 4, PROC 8a, PROC 8b, PROC 10, PROC 11, PROC 13 <b>Environmental Release Categories:</b> ERC8a, ERC8d, ESVOC SpERC 8.4b.v1
<b>Scope of process</b>	Covers the use as a component of cleaning products including pouring/unloading from drums or containers; and exposures during mixing/diluting in the preparatory phase and cleaning activities (including spraying, brushing, dipping, wiping automated and by hand).

<b>SECTION 2</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
<b>Section 2.1</b>	<b>Control of Worker Exposure</b>
<b>Product Characteristics</b>	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of the Substance in Mixture/Article	Covers use of substance/product up to 100% (unless stated differently).
<b>Frequency and Duration of Use</b>	
Covers daily exposures up to 8 hours (unless stated differently).	
<b>Other Operational Conditions affecting Exposure</b>	
Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.	
<b>Contributing Scenarios</b>	<b>Risk Management Measures</b>

Filling/ preparation of equipment from drums or containers.Dedicated facilityPROC8b	No other specific measures identified.
Filling/ preparation of equipment from drums or containers.Non-dedicated facilityPROC8a	Avoid carrying out activities involving exposure for more than 4 hours
Automated process with (semi) closed systems.Use in contained systemsPROC2	No other specific measures identified.
Automated process with (semi) closed systems.Drum/batch transfersUse in contained batch processesPROC3	No other specific measures identified.
Semi Automated process. (e.g.: Semi automatic application of floor care and maintenance products)PROC4	No other specific measures identified.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

ManualSurfacesCleaningDipping, immersion and pouringPROC13	No other specific measures identified.
ManualSurfacesCleaningPROC13	No other specific measures identified.
Cleaning with low-pressure washersRolling, Brushingno sprayingPROC10	No other specific measures identified.
Cleaning with high pressure washersSprayingIndoorPROC11	Limit the substance content in the product to 1 %.
Cleaning with high pressure washersSprayingOutdoorPROC11	Limit the substance content in the product to 1 %.
ManualSurfacesCleaningPROC10	Limit the substance content in the product to 25 %.
Ad hoc manual application via trigger sprays, dipping, etc.Rolling, BrushingPROC10	Limit the substance content in the product to 25 %.
Application of cleaning products in closed systemsPROC4	No other specific measures identified.
Cleaning of medical devicesPROC4	No other specific measures identified.
Storage.PROC1	Store substance within a closed system.
<b>Section 2.2      Control of Environmental Exposure</b>	
Substance is complex UVCB.	
Predominantly hydrophobic.	
Readily biodegradable.	
<b>Amounts Used</b>	
Fraction of EU tonnage used in region:	0,1
Regional use tonnage (tonnes/year):	2,0
Fraction of Regional tonnage used locally:	5,0E-04
Annual site tonnage (tonnes/year):	1,0E-03
Maximum daily site tonnage (kg/day):	2,7E-03
<b>Frequency and Duration of Use</b>	
Continuous release.	
Emission Days (days/year):	365
<b>Environmental factors not influenced by risk management</b>	
Local freshwater dilution factor:	10
Local marine water dilution factor:	100
<b>Other Operational Conditions affecting Environmental Exposure</b>	
Release fraction to air from wide dispersive use (regional only):	2,0E-02
Release fraction to wastewater from wide dispersive use:	1,0E-06
Release fraction to soil from wide dispersive use (regional only):	0
<b>Technical conditions and measures at process level (source) to prevent release</b>	
Common practices vary across sites thus conservative process release estimates used.	
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>	
Risk from environmental exposure is driven by freshwater.	
No wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	0
Treat onsite wastewater (prior to receiving water discharge) to provide	0

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

the required removal efficiency of $\geq$ (%)	
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	0
<b>Organisational measures to prevent/limit release from site</b>	
Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.	
<b>Conditions and Measures related to municipal sewage treatment plant</b>	
Estimated substance removal from wastewater via domestic sewage treatment (%)	93,6
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	93,6
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	7,1
Assumed domestic sewage treatment plant flow (m3/d)	2,0E+03
<b>Conditions and Measures related to external treatment of waste for disposal</b>	
External treatment and disposal of waste should comply with applicable local and/or regional regulations.	
<b>Conditions and measures related to external recovery of waste</b>	
External recovery and recycling of waste should comply with applicable local and/or regional regulations.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	

<b>Section 3.2 -Environment</b>	
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.	

<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
<b>Section 4.1 - Health</b>	
Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.	

<b>Section 4.2 -Environment</b>	
Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.	
Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.	
Required removal efficiency for air can be achieved using on-site technologies, either alone	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version  
2.1

Revision Date:  
28.03.2024

SDS Number:  
800010059269

Date of last issue: 22.11.2023  
Print Date 04.04.2024

---

or in combination.
--------------------

Further details on scaling and control technologies are provided in SpERC factsheet ( <a href="http://cefic.org">http://cefic.org</a> ).
--

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

### Exposure Scenario - Worker

<b>300000000783</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Use in Oil and Gas field drilling and production operations-Industrial
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU3 <b>Process Categories:</b> PROC 1, PROC 2, PROC 3, PROC 4, PROC 8a, PROC 8b <b>Environmental Release Categories:</b> ERC4
<b>Scope of process</b>	Oil field well drilling and production operations (including drilling muds and well cleaning) including material transfers, on-site formulation, well head operations, shaker room activities and related maintenance.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Additional Information	No exposure assessment presented for the environment.	
Section 2.1	Control of Worker Exposure	
Product Characteristics		
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP	
Concentration of the Substance in Mixture/Article	Covers use of substance/product up to 100% (unless stated differently).,	
Frequency and Duration of Use		
Covers daily exposures up to 8 hours (unless stated differently).		
Other Operational Conditions affecting Exposure		
Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.		
Contributing Scenarios	Risk Management Measures	
Bulk transfersDedicated facilityPROC8b	No other specific measures identified.	
Filling/ preparation of equipment from drums or containers.Dedicated facilityPROC8b	No other specific measures identified.	
Drilling mud (re-)formulationPROC3	No other specific measures identified.	
Drill floor operationsPROC4	No other specific measures identified.	
Operation of solids filtering equipment - vapour exposuresPROC4		
Treatment and disposal of filtered solidsPROC3	No other specific measures identified.	
Process samplingPROC3	No other specific measures identified.	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

General exposures (closed systems)PROC1	No other specific measures identified.
Pouring from small containersPROC8a	
General exposures (open systems)PROC4	No other specific measures identified.
Equipment cleaning and maintenancePROC8a	No other specific measures identified.
Storage.PROC1PROC2	Store substance within a closed system.
<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
No exposure assessment presented for the environment.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	

<b>Section 3.2 -Environment</b>
No exposure assessment presented for the environment.
Quantitative exposure and risk assessment not possible due to lack of emissions to aquatic environment.
Qualitative approach used to conclude safe use.

<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
<b>Section 4.1 - Health</b>	
Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.	

<b>Section 4.2 -Environment</b>
No exposure assessment presented for the environment.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

### Exposure Scenario - Worker

<b>300000000784</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Lubricants- Industrial
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU3 <b>Process Categories:</b> PROC 1, PROC 2, PROC 3, PROC 4, PROC 7, PROC 8a, PROC 8b, PROC 9, PROC 10, PROC 13, PROC 17, PROC 18 <b>Environmental Release Categories:</b> ERC4, ERC7, ESVO SpERC 4.6a.v1
<b>Scope of process</b>	Covers the use of formulated lubricants in closed and open systems including transfer operations, operation of machinery/engines and similar articles, reworking on reject articles, equipment maintenance and disposal of wastes.

SECTION 2		OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Section 2.1		Control of Worker Exposure	
Product Characteristics			
Physical form of product		Liquid, vapour pressure < 0.5 kPa at STP	
Concentration of the Substance in Mixture/Article		Covers use of substance/product up to 100% (unless stated differently).,	
Frequency and Duration of Use			
Covers daily exposures up to 8 hours (unless stated differently).			
Other Operational Conditions affecting Exposure			
Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.			
Contributing Scenarios		Risk Management Measures	
General exposures (closed systems)PROC1PROC2PROC3		No other specific measures identified.	
General exposures (open systems)PROC4		No other specific measures identified.	
Bulk transfersDedicated facilityPROC8b		No other specific measures identified.	
Filling/ preparation of equipment from drums or containers.Non-dedicated facilityPROC8a		No other specific measures identified.	
Filling/ preparation of equipment from drums or containers.Dedicated facilityPROC8b		No other specific measures identified.	
Initial factory fill of equipmentPROC9		No other specific measures identified.	
Operation and lubrication of high energy open equipmentPROC17PROC18		No other specific measures identified.	



# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

ManualRolling, Brush-ingPROC10	No other specific measures identified.
Treatment by dipping and pouringPROC13	No other specific measures identified.
SprayingPROC7	Carry out in a vented booth or extracted enclosure.
Maintenance (of larger plant items) and machine set upDedicated facilityPROC8b	No other specific measures identified.
Maintenance (of larger plant items) and machine set upOperation is carried out at elevated temperature (> 20°C above ambient temperature).Dedicated facilityPROC8b	Drain down and flush system prior to equipment opening or maintenance.
Maintenance of small itemsNon-dedicated facilityPROC8a	No other specific measures identified.
Remanufacture of reject articlesPROC9	No other specific measures identified.
Storage.PROC1PROC2	Store substance within a closed system.
<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Substance is complex UVCB.	
Predominantly hydrophobic.	
Readily biodegradable.	
<b>Amounts Used</b>	
Fraction of EU tonnage used in region:	0,1
Regional use tonnage (tonnes/year):	700
Fraction of Regional tonnage used locally:	0,14
Annual site tonnage (tonnes/year):	100
Maximum daily site tonnage (kg/day):	5,0E+03
<b>Frequency and Duration of Use</b>	
Continuous release.	
Emission Days (days/year):	20
<b>Environmental factors not influenced by risk management</b>	
Local freshwater dilution factor:	10
Local marine water dilution factor:	100
<b>Other Operational Conditions affecting Environmental Exposure</b>	
Release fraction to air from process (initial release prior to RMM):	5,0E-03
Release fraction to wastewater from process (initial release prior to RMM):	3,0E-05
Release fraction to soil from process (initial release prior to RMM):	1,0E-03
<b>Technical conditions and measures at process level (source) to prevent release</b>	
Common practices vary across sites thus conservative process release estimates used.	
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>	
Risk from environmental exposure is driven by freshwater sediment.	
Prevent discharge of undissolved substance to or recover from onsite wastewater.	
No wastewater treatment required.	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

Treat air emission to provide a typical removal efficiency of (%)	70
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of $\geq$ (%)	0
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	0
<b>Organisational measures to prevent/limit release from site</b>	
Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.	
<b>Conditions and Measures related to municipal sewage treatment plant</b>	
Estimated substance removal from wastewater via domestic sewage treatment (%)	93,6
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	93,6
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	2,1E+06
Assumed domestic sewage treatment plant flow (m3/d)	2,0E+03
<b>Conditions and Measures related to external treatment of waste for disposal</b>	
External treatment and disposal of waste should comply with applicable local and/or regional regulations.	
<b>Conditions and measures related to external recovery of waste</b>	
External recovery and recycling of waste should comply with applicable local and/or regional regulations.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	

<b>Section 3.2 -Environment</b>	
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.	

<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
<b>Section 4.1 - Health</b>	
Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.	

<b>Section 4.2 -Environment</b>	
Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.	
Required removal efficiency for wastewater can be achieved using onsite/offsite technolo-	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version  
2.1

Revision Date:  
28.03.2024

SDS Number:  
800010059269

Date of last issue: 22.11.2023  
Print Date 04.04.2024

---

gies, either alone or in combination.
Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.
Further details on scaling and control technologies are provided in SpERC factsheet ( <a href="http://cefic.org">http://cefic.org</a> ).

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

### Exposure Scenario - Worker

<b>300000000785</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Lubricants- ProfessionalLow Environmental Release
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU22 <b>Process Categories:</b> PROC 1, PROC 2, PROC 3, PROC 4, PROC 8a, PROC 8b, PROC 9, PROC 10, PROC 11, PROC 13, PROC 17, PROC 18, PROC 20 <b>Environmental Release Categories:</b> ERC9a, ERC9b, ESVOC SpERC 8.6c.v1
<b>Scope of process</b>	Covers the use of formulated lubricants in closed and open systems including transfer operations, operation of engines and similar articles, reworking on reject articles, equipment maintenance and disposal of waste oil.

<b>SECTION 2</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
<b>Section 2.1</b>	<b>Control of Worker Exposure</b>
<b>Product Characteristics</b>	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of the Substance in Mixture/Article	Covers use of substance/product up to 100% (unless stated differently).,
<b>Frequency and Duration of Use</b>	
Covers daily exposures up to 8 hours (unless stated differently).	
<b>Other Operational Conditions affecting Exposure</b>	
Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.	
<b>Contributing Scenarios</b>	<b>Risk Management Measures</b>

General exposures (closed systems)PROC1PROC2PROC3	No other specific measures identified.
Operation of equipment containing engine oils and similar.PROC20	No other specific measures identified.
General exposures (open systems)PROC4	No other specific measures identified.
Bulk transfersPROC8b	No other specific measures identified.
Filling/ preparation of equipment from drums or containers.Dedicated facilityPROC8b	No other specific measures identified.
Filling/ preparation of equipment from drums or containers.Non-dedicated facilityPROC8a	Avoid carrying out activities involving exposure for more than 4 hours
Operation and lubrication of high energy open equipmentIndoorPROC17PROC18	Provide extraction ventilation at points where emissions occur.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

Operation and lubrication of high energy open equipmentOut-doorPROC17	Ensure operation is undertaken outdoors. Avoid carrying out activities involving exposure for more than 4 hours
Maintenance (of larger plant items) and machine set upPROC8b	No other specific measures identified.
Maintenance (of larger plant items) and machine set upOperation is carried out at elevated temperature (> 20°C above ambient temperature).Dedicated facilityPROC8b	Drain down system prior to equipment opening or maintenance.
Maintenance of small itemsOperation is carried out at elevated temperature (> 20°C above ambient temperature).Non-dedicated facilityPROC8a	Drain or remove substance from equipment prior to break-in or maintenance.
Engine lubricant servicePROC9	No other specific measures identified.
ManualRolling, BrushingPROC10	No other specific measures identified.
SprayingPROC11	Provide a good standard of general or controlled ventilation (5 to 15 air changes per hour). Avoid carrying out activities involving exposure for more than 4 hours , or: Wear a respirator conforming to EN140 with Type A filter or better.
Treatment by dipping and pouringPROC13	No other specific measures identified.
Storage.PROC1PROC2	Store substance within a closed system.

Section 2.2      Control of Environmental Exposure	
Substance is complex UVCB.	
Predominantly hydrophobic.	
Readily biodegradable.	
Amounts Used	
Fraction of EU tonnage used in region:	0,1
Regional use tonnage (tonnes/year):	12
Fraction of Regional tonnage used locally:	5,0E-04
Annual site tonnage (tonnes/year):	5,8E-03
Maximum daily site tonnage (kg/day):	1,6E-02
Frequency and Duration of Use	
Continuous release.	
Emission Days (days/year):	365
Environmental factors not influenced by risk management	
Local freshwater dilution factor:	10
Local marine water dilution factor:	100
Other Operational Conditions affecting Environmental Exposure	
Release fraction to air from process (initial release prior to RMM):	1,0E-02

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

Release fraction to wastewater from process (initial release prior to RMM):	1,0E-02
Release fraction to soil from process (initial release prior to RMM):	1,0E-02
<b>Technical conditions and measures at process level (source) to prevent release</b>	
Common practices vary across sites thus conservative process re-release estimates used.	
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>	
Risk from environmental exposure is driven by freshwater.	
No wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	0
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)	0
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	0
<b>Organisational measures to prevent/limit release from site</b>	
Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.	
<b>Conditions and Measures related to municipal sewage treatment plant</b>	
Estimated substance removal from wastewater via domestic sewage treatment (%)	93,6
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	93,6
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	41
Assumed domestic sewage treatment plant flow (m3/d)	2.000
<b>Conditions and Measures related to external treatment of waste for disposal</b>	
External treatment and disposal of waste should comply with applicable local and/or regional regulations.	
<b>Conditions and measures related to external recovery of waste</b>	
External recovery and recycling of waste should comply with applicable local and/or regional regulations.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	

<b>Section 3.2 -Environment</b>	
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.	

<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
<b>Section 4.1 - Health</b>	
Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version	Revision Date:	SDS Number:	Date of last issue: 22.11.2023
2.1	28.03.2024	800010059269	Print Date 04.04.2024

Measures/Operational Conditions outlined in Section 2 are implemented.  
Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

### Section 4.2 -Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org>).

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

### Exposure Scenario - Worker

<b>300000000786</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Lubricants- ProfessionalHigh Environmental Release
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU22 <b>Process Categories:</b> PROC 1, PROC 2, PROC 3, PROC 4, PROC 8a, PROC 8b, PROC 9, PROC 10, PROC 11, PROC 13, PROC 17, PROC 18, PROC 20 <b>Environmental Release Categories:</b> ERC8a, ERC8d, ESVOC SpERC 8.6c.v1
<b>Scope of process</b>	Covers the use of formulated lubricants in closed and open systems including transfer operations, operation of engines and similar articles, reworking on reject articles, equipment maintenance and disposal of waste oil.

<b>SECTION 2</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
<b>Section 2.1</b>	<b>Control of Worker Exposure</b>
<b>Product Characteristics</b>	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of the Substance in Mixture/Article	Covers use of substance/product up to 100% (unless stated differently).,
<b>Frequency and Duration of Use</b>	
Covers daily exposures up to 8 hours (unless stated differently).	
<b>Other Operational Conditions affecting Exposure</b>	
Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.	
<b>Contributing Scenarios</b>	<b>Risk Management Measures</b>

General exposures (closed systems)PROC1PROC2PROC3	No other specific measures identified.
Operation of equipment containing engine oils and similar.PROC20	No other specific measures identified.
General exposures (open systems)PROC4	No other specific measures identified.
Bulk transfersPROC8b	No other specific measures identified.
Filling/ preparation of equipment from drums or containers.Dedicated facilityPROC8b	No other specific measures identified.
Filling/ preparation of equipment from drums or containers.Non-dedicated facilityPROC8a	Avoid carrying out activities involving exposure for more than 4 hours
Operation and lubrication of high energy open equipmentIndoorPROC17PROC18	Provide extraction ventilation at points where emissions occur.



# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

Operation and lubrication of high energy open equipmentOut-doorPROC17	Avoid carrying out operation for more than 4 hours.
Maintenance (of larger plant items) and machine set upPROC8b	No other specific measures identified.
Maintenance (of larger plant items) and machine set upOperation is carried out at elevated temperature (> 20°C above ambient temperature).Dedicated facilityPROC8b	Drain down system prior to equipment opening or maintenance.
Maintenance of small itemsOperation is carried out at elevated temperature (> 20°C above ambient temperature).Non-dedicated facilityPROC8a	Drain or remove substance from equipment prior to break-in or maintenance.
Engine lubricant servicePROC9	No other specific measures identified.
ManualRolling, BrushingPROC10	No other specific measures identified.
SprayingPROC11	Provide a good standard of general or controlled ventilation (5 to 15 air changes per hour). Avoid carrying out activities involving exposure for more than 4 hours , or: Wear a respirator conforming to EN140 with Type A filter or better.
Treatment by dipping and pouringPROC13	No other specific measures identified.
Storage.PROC1PROC2	Store substance within a closed system.

### Section 2.2

### Control of Environmental Exposure

Substance is complex UVCB.

Predominantly hydrophobic.

Readily biodegradable.

### Amounts Used

Fraction of EU tonnage used in region:

0,1

Regional use tonnage (tonnes/year):

12

Fraction of Regional tonnage used locally:

5,0E-04

Annual site tonnage (tonnes/year):

5,8E-03

Maximum daily site tonnage (kg/day):

1,6E-02

### Frequency and Duration of Use

Continuous release.

Emission Days (days/year):

365

### Environmental factors not influenced by risk management

Local freshwater dilution factor:

10

Local marine water dilution factor:

100

### Other Operational Conditions affecting Environmental Exposure

Release fraction to air from wide dispersive use (regional only):

1,5E-01

Release fraction to air from wide dispersive use (regional only):

5,0E-02

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

Release fraction to soil from wide dispersive use (regional only):	5,0E-02
<b>Technical conditions and measures at process level (source) to prevent release</b>	
Common practices vary across sites thus conservative process release estimates used.	
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>	
Risk from environmental exposure is driven by freshwater.	
No wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	0
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)	0
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	0
<b>Organisational measures to prevent/limit release from site</b>	
Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.	
<b>Conditions and Measures related to municipal sewage treatment plant</b>	
Estimated substance removal from wastewater via domestic sewage treatment (%)	93,6
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	93,6
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	40
Assumed domestic sewage treatment plant flow (m3/d)	2.000
<b>Conditions and Measures related to external treatment of waste for disposal</b>	
External treatment and disposal of waste should comply with applicable local and/or regional regulations.	
<b>Conditions and measures related to external recovery of waste</b>	
External recovery and recycling of waste should comply with applicable local and/or regional regulations.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	

<b>Section 3.2 -Environment</b>	
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.	

<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
<b>Section 4.1 - Health</b>	
Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version	Revision Date:	SDS Number:	Date of last issue: 22.11.2023
2.1	28.03.2024	800010059269	Print Date 04.04.2024

should ensure that risks are managed to at least equivalent levels.

### Section 4.2 -Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org>).

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version  
2.1

Revision Date:  
28.03.2024

SDS Number:  
800010059269

Date of last issue: 22.11.2023  
Print Date 04.04.2024

### Exposure Scenario - Worker

**300000000787**

SECTION 1	EXPOSURE SCENARIO TITLE
Title	Metal working fluids / rolling oils- Industrial
Use Descriptor	<b>Sector of Use:</b> SU3 <b>Process Categories:</b> PROC 1, PROC 2, PROC 3, PROC 4, PROC 5, PROC 7, PROC 8a, PROC 8b, PROC 9, PROC 10, PROC 13, PROC 17 <b>Environmental Release Categories:</b> ERC4, ESVOC SpERC 4.7a.v1
Scope of process	Covers the use in formulated MWFs/rolling oils including transfer operations, rolling and annealing activities, cutting/machining activities, automated and manual application of corrosion protections (including brushing, dipping and spraying), equipment maintenance, draining and disposal of waste oils.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
Section 2.1	Control of Worker Exposure
<b>Product Characteristics</b>	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of the Substance in Mixture/Article	Covers use of substance/product up to 100% (unless stated differently).,
<b>Frequency and Duration of Use</b>	
Covers daily exposures up to 8 hours (unless stated differently).	
<b>Other Operational Conditions affecting Exposure</b>	
Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.	
<b>Contributing Scenarios</b>	<b>Risk Management Measures</b>
General exposures (closed systems)PROC1PROC2PROC3	No other specific measures identified.
General exposures (open systems)PROC4	No other specific measures identified.
Bulk transfersPROC8b	No other specific measures identified.
Filling/ preparation of equipment from drums or containers.PROC8bPROC5PROC9	No other specific measures identified.
Process samplingPROC8b	No other specific measures identified.
Metal machining operationsPROC17	No other specific measures identified.
Treatment by dipping and pouringPROC13	No other specific measures identified.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

SprayingPROC7	Minimise exposure by partial enclosure of the operation or equipment and provide extract ventilation at openings.
ManualRolling, BrushingPROC10	No other specific measures identified.
Automated metal rolling/formingUse in contained systemsOperation is carried out at elevated temperature (> 20°C above ambient temperature).PROC2	No other specific measures identified.
Semi-automated metal rolling/formingOperation is carried out at elevated temperature (> 20°C above ambient temperature).PROC17	Minimise exposure by partial enclosure of the operation or equipment and provide extract ventilation at openings.
Equipment cleaning and maintenanceDedicated facilityPROC8b	No other specific measures identified.
Equipment cleaning and maintenanceNon-dedicated facilityPROC8a	No other specific measures identified.
Storage.PROC1PROC2	Store substance within a closed system.

### Section 2.2

### Control of Environmental Exposure

Substance is complex UVCB.

Predominantly hydrophobic.

Readily biodegradable.

#### Amounts Used

Fraction of EU tonnage used in region:

0,1

Regional use tonnage (tonnes/year):

10

Fraction of Regional tonnage used locally:

1

Annual site tonnage (tonnes/year):

10

Maximum daily site tonnage (kg/day):

500

#### Frequency and Duration of Use

Continuous release.

Emission Days (days/year):

20

#### Environmental factors not influenced by risk management

Local freshwater dilution factor:

10

Local marine water dilution factor:

100

#### Other Operational Conditions affecting Environmental Exposure

Release fraction to air from process (initial release prior to RMM):

2,0E-02

Release fraction to wastewater from process (initial release prior to RMM):

3,0E-05

Release fraction to soil from process (initial release prior to RMM):

0

#### Technical conditions and measures at process level (source) to prevent release

Common practices vary across sites thus conservative process release estimates used.

#### Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Risk from environmental exposure is driven by freshwater.

Prevent discharge of undissolved substance to or recover from onsite

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

wastewater.	
No wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	70
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of $\geq$ (%)	0
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	0
<b>Organisational measures to prevent/limit release from site</b>	
Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.	
<b>Conditions and Measures related to municipal sewage treatment plant</b>	
Estimated substance removal from wastewater via domestic sewage treatment (%)	93,6
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	93,6
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	8,3E+05
Assumed domestic sewage treatment plant flow (m3/d)	2,0E+03
<b>Conditions and Measures related to external treatment of waste for disposal</b>	
External treatment and disposal of waste should comply with applicable local and/or regional regulations.	
<b>Conditions and measures related to external recovery of waste</b>	
External recovery and recycling of waste should comply with applicable local and/or regional regulations.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	

<b>Section 3.2 -Environment</b>	
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.	

<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
<b>Section 4.1 - Health</b>	
Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.	

<b>Section 4.2 -Environment</b>	
Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version  
2.1

Revision Date:  
28.03.2024

SDS Number:  
800010059269

Date of last issue: 22.11.2023  
Print Date 04.04.2024

---

measures.
Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.
Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.
Further details on scaling and control technologies are provided in SpERC factsheet ( <a href="http://cefic.org">http://cefic.org</a> ).

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version  
2.1

Revision Date:  
28.03.2024

SDS Number:  
800010059269

Date of last issue: 22.11.2023  
Print Date 04.04.2024

### Exposure Scenario - Worker

300000000788

SECTION 1	EXPOSURE SCENARIO TITLE
Title	Metal working fluids / rolling oils- Professional
Use Descriptor	<b>Sector of Use:</b> SU22 <b>Process Categories:</b> PROC 1, PROC 2, PROC 3, PROC 5, PROC 8a, PROC 8b, PROC 9, PROC 10, PROC 11, PROC 13, PROC 17 <b>Environmental Release Categories:</b> ERC8a, ERC8b, ESVOC SpERC 9.6b.v1
Scope of process	Covers the use in formulated MWFs including transfer operations, open and contained cutting/machining activities, automated and manual application of corrosion protections, draining and working on contaminated/ reject articles, and disposal of waste oils.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
Section 2.1	Control of Worker Exposure
<b>Product Characteristics</b>	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of the Substance in Mixture/Article	Covers use of substance/product up to 100% (unless stated differently).,
<b>Frequency and Duration of Use</b>	
Covers daily exposures up to 8 hours (unless stated differently).	
<b>Other Operational Conditions affecting Exposure</b>	
Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.	
<b>Contributing Scenarios</b>	<b>Risk Management Measures</b>

General exposures (closed systems)PROC1PROC2PROC3	No other specific measures identified.
Bulk transfersPROC8b	No other specific measures identified.
Filling/ preparation of equipment from drums or containers.PROC5PROC8aPROC8bPROC9	No other specific measures identified.
Process samplingDedicated facilityPROC8b	No other specific measures identified.
Metal machining operationsPROC17	Provide a good standard of general or controlled ventilation (5 to 15 air changes per hour).
ManualRolling, BrushingPROC10	No other specific measures identified.
SprayingPROC11	Provide a good standard of general or controlled ventilation (5 to 15 air changes per hour).



# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

	Avoid carrying out activities involving exposure for more than 4 hours , or: Wear a respirator conforming to EN140 with Type A/P2 filter or better.
Treatment by dipping and pouring PROC13	No other specific measures identified.
Equipment cleaning and maintenance- PROC8a PROC8b	Drain down system prior to equipment opening or maintenance.
Storage. PROC1 PROC2	Store substance within a closed system.

<b>Section 2.2      Control of Environmental Exposure</b>	
Substance is complex UVCB.	
Predominantly hydrophobic.	
Readily biodegradable.	
<b>Amounts Used</b>	
Fraction of EU tonnage used in region:	0,1
Regional use tonnage (tonnes/year):	5,0
Fraction of Regional tonnage used locally:	5,0E-04
Annual site tonnage (tonnes/year):	2,5E-03
Maximum daily site tonnage (kg/day):	6,8E-03
<b>Frequency and Duration of Use</b>	
Continuous release.	
Emission Days (days/year):	365
<b>Environmental factors not influenced by risk management</b>	
Local freshwater dilution factor:	10
Local marine water dilution factor:	100
<b>Other Operational Conditions affecting Environmental Exposure</b>	
Release fraction to air from wide dispersive use (regional only):	5,0E-02
Release fraction to wastewater from wide dispersive use:	2,5E-02
Release fraction to soil from wide dispersive use (regional only):	0
<b>Technical conditions and measures at process level (source) to prevent release</b>	
Common practices vary across sites thus conservative process re-release estimates used.	
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>	
Risk from environmental exposure is driven by freshwater.	
No wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	0
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)	0
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	0
<b>Organisational measures to prevent/limit release from site</b>	
Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.	
<b>Conditions and Measures related to municipal sewage treatment plant</b>	
Estimated substance removal from wastewater via domestic sewage	93,6

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

treatment (%)	
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	93,6
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	18
Assumed domestic sewage treatment plant flow (m3/d)	2,0E+03
<b>Conditions and Measures related to external treatment of waste for disposal</b>	
External treatment and disposal of waste should comply with applicable local and/or regional regulations.	
<b>Conditions and measures related to external recovery of waste</b>	
External recovery and recycling of waste should comply with applicable local and/or regional regulations.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	

<b>Section 3.2 -Environment</b>	
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.	

<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
<b>Section 4.1 - Health</b>	
Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.	

<b>Section 4.2 -Environment</b>	
Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.	
Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.	
Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.	
Further details on scaling and control technologies are provided in SpERC factsheet ( <a href="http://cefic.org">http://cefic.org</a> ).	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

### Exposure Scenario - Worker

<b>300000000790</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Use as binders and release agents- Industrial
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU3 <b>Process Categories:</b> PROC 1, PROC 2, PROC 3, PROC 4, PROC 6, PROC 7, PROC 8b, PROC 10, PROC 13, PROC 14 <b>Environmental Release Categories:</b> ERC4, ESVOC SpERC 4.10a.v1
<b>Scope of process</b>	Covers the use as binders and release agents including material transfers, mixing, application (including spraying and brushing), and handling of waste.

SECTION 2		OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Section 2.1		Control of Worker Exposure	
Product Characteristics			
Physical form of product		Liquid, vapour pressure < 0.5 kPa at STP	
Concentration of the Sub- stance in Mixture/Article		Covers use of substance/product up to 100% (unless stated differently).,	
Frequency and Duration of Use			
Covers daily exposures up to 8 hours (unless stated differently).			
Other Operational Conditions affecting Exposure			
Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.			
Contributing Scenarios		Risk Management Measures	
Material transfersUse in con- tained sys- temsPROC1PROC2PROC3		No other specific measures identified.	
Drum/batch transfersPROC8b		No other specific measures identified.	
Mixing operations (closed sys- tems)PROC3		No other specific measures identified.	
Mixing operations (open sys- tems)PROC4		No other specific measures identified.	
Mold formingPROC14		No other specific measures identified.	
Casting operations(open sys- tems)Operation is carried out at elevated temperature (> 20°C above ambient tempera- ture).Aerosol generation due to elevated process temperature- PROC6		Provide extraction ventilation at points where emissions oc- cur.	
SprayingMachinePROC7		Minimise exposure by partial enclosure of the operation or	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

	equipment and provide extract ventilation at openings.
SprayingManualPROC7	Provide a good standard of general or controlled ventilation (5 to 15 air changes per hour). Avoid carrying out activities involving exposure for more than 4 hours
ManualRolling, Brush-ingPROC10	No other specific measures identified.
Dipping, immersion and pouringPROC13	No other specific measures identified.
Storage.PROC1PROC2	Store substance within a closed system.
<b>Section 2.2      Control of Environmental Exposure</b>	
Substance is complex UVCB.	
Predominantly hydrophobic.	
Readily biodegradable.	
<b>Amounts Used</b>	
Fraction of EU tonnage used in region:	0,1
Regional use tonnage (tonnes/year):	70
Fraction of Regional tonnage used locally:	1
Annual site tonnage (tonnes/year):	70
Maximum daily site tonnage (kg/day):	3,5E+03
<b>Frequency and Duration of Use</b>	
Continuous release.	
Emission Days (days/year):	20
<b>Environmental factors not influenced by risk management</b>	
Local freshwater dilution factor:	10
Local marine water dilution factor:	100
<b>Other Operational Conditions affecting Environmental Exposure</b>	
Release fraction to air from process (initial release prior to RMM):	1,0
Release fraction to wastewater from process (initial release prior to RMM):	3,0E-06
Release fraction to soil from process (initial release prior to RMM):	0
<b>Technical conditions and measures at process level (source) to prevent release</b>	
Common practices vary across sites thus conservative process release estimates used.	
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>	
Risk from environmental exposure is driven by freshwater.	
Prevent discharge of undissolved substance to or recover from onsite wastewater.	
No wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	80
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)	0
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	0
<b>Organisational measures to prevent/limit release from site</b>	
Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

Conditions and Measures related to municipal sewage treatment plant	
Estimated substance removal from wastewater via domestic sewage treatment (%)	93,6
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	93,6
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	6,5E+06
Assumed domestic sewage treatment plant flow (m3/d)	2,0E+03
Conditions and Measures related to external treatment of waste for disposal	
External treatment and disposal of waste should comply with applicable local and/or regional regulations.	
Conditions and measures related to external recovery of waste	
External recovery and recycling of waste should comply with applicable local and/or regional regulations.	

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	

Section 3.2 -Environment
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	
Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.	

Section 4.2 -Environment
Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.
Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.
Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.
Further details on scaling and control technologies are provided in SpERC factsheet ( <a href="http://cefic.org">http://cefic.org</a> ).

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

### Exposure Scenario - Worker

<b>300000000791</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Use as binders and release agents- Professional
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU22 <b>Process Categories:</b> PROC 1, PROC 2, PROC 3, PROC 4, PROC 6, PROC 8a, PROC 8b, PROC 10, PROC 11, PROC 14 <b>Environmental Release Categories:</b> ERC8a, ERC8d, ESVOC SpERC 8.10b.v1
<b>Scope of process</b>	Covers the use as binders and release agents including material transfers, mixing, application by spraying, brushing, and handling of waste.

SECTION 2		OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Section 2.1		Control of Worker Exposure	
Product Characteristics			
Physical form of product		Liquid, vapour pressure < 0.5 kPa at STP	
Concentration of the Sub- stance in Mixture/Article		Covers use of substance/product up to 100% (unless stated differently).,	
Frequency and Duration of Use			
Covers daily exposures up to 8 hours (unless stated differently).			
Other Operational Conditions affecting Exposure			
Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.			
Contributing Scenarios		Risk Management Measures	
Bulk transfersUse in contained systemsPROC1PROC2PROC3		No other specific measures identified.	
Drum/batch transfer-sPROC8aPROC8b		No other specific measures identified.	
Mixing operations (closed sys- tems)PROC3		No other specific measures identified.	
Mixing operations (open sys- tems)PROC4		No other specific measures identified.	
Mold formingPROC14		No other specific measures identified.	
Casting operations(open sys- tems)Operation is carried out at elevated temperature (> 20°C above ambient tempera- ture).PROC6		Provide extraction ventilation at points where emissions oc- cur.	
SprayingMachinePROC11		Minimise exposure by partial enclosure of the operation or equipment and provide extract ventilation at openings. . or:	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

	Wear a respirator conforming to EN140 with Type A filter or better.
SprayingManualPROC11	Provide a good standard of general or controlled ventilation (5 to 15 air changes per hour). Avoid carrying out activities involving exposure for more than 4 hours
ManualRolling, Brush-ingPROC10	No other specific measures identified.
Storage.PROC1PROC2	Store substance within a closed system.
<b>Section 2.2      Control of Environmental Exposure</b>	
Substance is complex UVCB.	
Predominantly hydrophobic.	
Readily biodegradable.	
<b>Amounts Used</b>	
Fraction of EU tonnage used in region:	0,1
Regional use tonnage (tonnes/year):	30
Fraction of Regional tonnage used locally:	5,0E-04
Annual site tonnage (tonnes/year):	1,5E-02
Maximum daily site tonnage (kg/day):	4,1E-02
<b>Frequency and Duration of Use</b>	
Continuous release.	
Emission Days (days/year):	365
<b>Environmental factors not influenced by risk management</b>	
Local freshwater dilution factor:	10
Local marine water dilution factor:	100
<b>Other Operational Conditions affecting Environmental Exposure</b>	
Release fraction to air from wide dispersive use (regional only):	9,5E-01
Release fraction to wastewater from wide dispersive use:	2,5E-02
Release fraction to soil from wide dispersive use (regional only):	2,5E-02
<b>Technical conditions and measures at process level (source) to prevent release</b>	
Common practices vary across sites thus conservative process re-lease estimates used.	
<b>Technical onsite conditions and measures to reduce or limit discharges, air emis-sions and releases to soil</b>	
Risk from environmental exposure is driven by freshwater.	
No wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	0
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)	0
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	0
<b>Organisational measures to prevent/limit release from site</b>	
Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.	
<b>Conditions and Measures related to municipal sewage treatment plant</b>	
Estimated substance removal from wastewater via domestic sewage treatment (%)	93,6

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	93,6
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	82
Assumed domestic sewage treatment plant flow (m3/d)	2,0E+03
<b>Conditions and Measures related to external treatment of waste for disposal</b>	
External treatment and disposal of waste should comply with applicable local and/or regional regulations.	
<b>Conditions and measures related to external recovery of waste</b>	
External recovery and recycling of waste should comply with applicable local and/or regional regulations.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	

<b>Section 3.2 -Environment</b>	
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.	

<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
<b>Section 4.1 - Health</b>	
Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.	

<b>Section 4.2 -Environment</b>	
Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.	
Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.	
Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.	
Further details on scaling and control technologies are provided in SpERC factsheet ( <a href="http://cefic.org">http://cefic.org</a> ).	



# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

### Exposure Scenario - Worker

<b>300000000792</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Use in Agrochemicals uses- Professional
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU22 <b>Process Categories:</b> PROC 1, PROC 2, PROC 4, PROC 8a, PROC 8b, PROC 11, PROC 13 <b>Environmental Release Categories:</b> ERC8a, ERC8d, ESVOC SpERC 8.11a.v1
<b>Scope of process</b>	Use as an agrochemical excipient for application by manual or machine spraying, smokes and fogging; including equipment clean-downs and disposal.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Section 2.1	Control of Worker Exposure	
Product Characteristics		
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP	
Concentration of the Substance in Mixture/Article	Covers use of substance/product up to 100% (unless stated differently).,	
Frequency and Duration of Use		
Covers daily exposures up to 8 hours (unless stated differently).		
Other Operational Conditions affecting Exposure		
Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.		
Contributing Scenarios	Risk Management Measures	
Transfer from/pouring from containersPROC8b	No other specific measures identified.	
Mixing in containers.PROC4	No other specific measures identified.	
Spraying/ fogging by manual applicationPROC11	Wear a respirator conforming to EN140 with Type A/P2 filter or better.	
Spraying/ fogging by machine applicationPROC11	Apply within a vented cab supplied with filtered air under positive pressure and with a protection factor of >20. , or: Wear a respirator conforming to EN140 with Type A/P2 filter or better.	
Ad hoc manual application via trigger sprays, dipping, etc.PROC13	No other specific measures identified.	
Equipment cleaning and maintenancePROC8a	No other specific measures identified.	
Storage.PROC1PROC2	Store substance within a closed system.	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

<b>Section 2.2</b>		<b>Control of Environmental Exposure</b>
Substance is complex UVCB.		
Predominantly hydrophobic.		
Readily biodegradable.		
<b>Amounts Used</b>		
Fraction of EU tonnage used in region:		0,1
Regional use tonnage (tonnes/year):		610
Fraction of Regional tonnage used locally:		2,0E-03
Annual site tonnage (tonnes/year):		1,2
Maximum daily site tonnage (kg/day):		3,4
<b>Frequency and Duration of Use</b>		
Continuous release.		
Emission Days (days/year):		365
<b>Environmental factors not influenced by risk management</b>		
Local freshwater dilution factor:		10
Local marine water dilution factor:		100
<b>Other Operational Conditions affecting Environmental Exposure</b>		
Release fraction to air from wide dispersive use (regional only):		9,0E-01
Release fraction to wastewater from wide dispersive use:		1,0E-02
Release fraction to soil from wide dispersive use (regional only):		9,0E-02
<b>Technical conditions and measures at process level (source) to prevent release</b>		
Common practices vary across sites thus conservative process re-lease estimates used.		
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>		
Risk from environmental exposure is driven by soil.		
No wastewater treatment required.		
Treat air emission to provide a typical removal efficiency of (%)		0
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)		0
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.		0
<b>Organisational measures to prevent/limit release from site</b>		
Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.		
<b>Conditions and Measures related to municipal sewage treatment plant</b>		
Estimated substance removal from wastewater via domestic sewage treatment (%)		93,6
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)		93,6
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)		4,7E+03
Assumed domestic sewage treatment plant flow (m3/d)		2,0E+03
<b>Conditions and Measures related to external treatment of waste for disposal</b>		
External treatment and disposal of waste should comply with applicable local and/or regional regulations.		
<b>Conditions and measures related to external recovery of waste</b>		
External recovery and recycling of waste should comply with applicable local and/or regional		

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

regulations.

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
------------------	----------------------------

<b>Section 3.1 - Health</b>
-----------------------------

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
---

<b>Section 3.2 -Environment</b>
---------------------------------

The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.
--

<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
------------------	--

<b>Section 4.1 - Health</b>
-----------------------------

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.
---

<b>Section 4.2 -Environment</b>
---------------------------------

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.
--

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.
---

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.
---

Further details on scaling and control technologies are provided in SpERC factsheet ( <a href="http://cefic.org">http://cefic.org</a> ).
--

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

### Exposure Scenario - Worker

<b>300000000793</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Use as a fuel- Industrial
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU3 <b>Process Categories:</b> PROC 1, PROC 2, PROC 3, PROC 8a, PROC 8b, PROC 16 <b>Environmental Release Categories:</b> ERC7, ESVOC SpERC 7.12a.v1
<b>Scope of process</b>	Covers the use as a fuel (or fuel additive) and includes activities associated with its transfer, use, equipment maintenance and handling of waste.

SECTION 2		OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Section 2.1		Control of Worker Exposure	
Product Characteristics			
Physical form of product		Liquid, vapour pressure < 0.5 kPa at STP	
Concentration of the Substance in Mixture/Article		Covers use of substance/product up to 100% (unless stated differently).,	
Frequency and Duration of Use			
Covers daily exposures up to 8 hours (unless stated differently).			
Other Operational Conditions affecting Exposure			
Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.			
Contributing Scenarios		Risk Management Measures	
Bulk transfersDedicated facilityPROC8b		No other specific measures identified.	
Drum/batch transfersDedicated facilityPROC8b		No other specific measures identified.	
General exposures (closed systems)PROC1PROC2		No other specific measures identified.	
Use as a fuel(closed systems)PROC16PROC3		No other specific measures identified.	
Equipment cleaning and maintenancePROC8a		No other specific measures identified.	
Storage.PROC1PROC2		Store substance within a closed system.	
Section 2.2		Control of Environmental Exposure	
Substance is complex UVCB.			
Predominantly hydrophobic.			
Readily biodegradable.			
Amounts Used			
Fraction of EU tonnage used in region:		0,1	
Regional use tonnage (tonnes/year):		15	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

Fraction of Regional tonnage used locally:	1
Annual site tonnage (tonnes/year):	15
Maximum daily site tonnage (kg/day):	750
<b>Frequency and Duration of Use</b>	
Continuous release.	
Emission Days (days/year):	20
<b>Environmental factors not influenced by risk management</b>	
Local freshwater dilution factor:	10
Local marine water dilution factor:	100
<b>Other Operational Conditions affecting Environmental Exposure</b>	
Release fraction to air from process (initial release prior to RMM):	5,0E-03
Release fraction to wastewater from process (initial release prior to RMM):	1,0E-05
Release fraction to soil from process (initial release prior to RMM):	0
<b>Technical conditions and measures at process level (source) to prevent release</b>	
Common practices vary across sites thus conservative process re-release estimates used.	
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>	
Risk from environmental exposure is driven by freshwater.	
No wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	95
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)	0
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	0
<b>Organisational measures to prevent/limit release from site</b>	
Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.	
<b>Conditions and Measures related to municipal sewage treatment plant</b>	
Estimated substance removal from wastewater via domestic sewage treatment (%)	93,6
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	93,6
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	1,5E+06
Assumed domestic sewage treatment plant flow (m3/d)	2,0E+03
<b>Conditions and Measures related to external treatment of waste for disposal</b>	
Combustion emissions limited by required exhaust emission controls. Waste combustion emissions considered in regional exposure assessment.	
<b>Conditions and measures related to external recovery of waste</b>	
This substance is consumed during use and no waste of substance is generated.	

### SECTION 3

### EXPOSURE ESTIMATION

#### Section 3.1 - Health

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version	Revision Date:	SDS Number:	Date of last issue: 22.11.2023
2.1	28.03.2024	800010059269	Print Date 04.04.2024

### Section 3.2 -Environment

The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

### SECTION 4

### GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO

#### Section 4.1 - Health

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.  
Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

#### Section 4.2 -Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org>).

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

### Exposure Scenario - Worker

<b>300000000794</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Use as a fuel- Professional
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU22 <b>Process Categories:</b> PROC 1, PROC 2, PROC 3, PROC 8a, PROC 8b, PROC 16 <b>Environmental Release Categories:</b> ERC9a, ERC9b, ESVOC SpERC 9.12b.v1
<b>Scope of process</b>	Covers the use as a fuel (or fuel additive) and includes activities associated with its transfer, use, equipment maintenance and handling of waste.

SECTION 2		OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Section 2.1		Control of Worker Exposure	
Product Characteristics			
Physical form of product		Liquid, vapour pressure < 0.5 kPa at STP	
Concentration of the Substance in Mixture/Article		Covers use of substance/product up to 100% (unless stated differently).,	
Frequency and Duration of Use			
Covers daily exposures up to 8 hours (unless stated differently).			
Other Operational Conditions affecting Exposure			
Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.			
Contributing Scenarios		Risk Management Measures	
Bulk transfersDedicated facilityPROC8b		No other specific measures identified.	
Drum/batch transfersDedicated facilityPROC8b		No other specific measures identified.	
Refueling.Dedicated facilityPROC8b		No other specific measures identified.	
General exposures (closed systems)PROC1PROC2PROC3		No other specific measures identified.	
Use as a fuel(closed systems)PROC16		No other specific measures identified.	
Equipment cleaning and maintenancePROC8a		No other specific measures identified.	
Storage.PROC1		Store substance within a closed system.	
Section 2.2		Control of Environmental Exposure	
Substance is complex UVCB.			
Predominantly hydrophobic.			
Readily biodegradable.			
Amounts Used			

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

Fraction of EU tonnage used in region:	0,1
Regional use tonnage (tonnes/year):	15
Fraction of Regional tonnage used locally:	5,0E-04
Annual site tonnage (tonnes/year):	7,5E-03
Maximum daily site tonnage (kg/day):	2,1E-02
<b>Frequency and Duration of Use</b>	
Continuous release.	
Emission Days (days/year):	365
<b>Environmental factors not influenced by risk management</b>	
Local freshwater dilution factor:	10
Local marine water dilution factor:	100
<b>Other Operational Conditions affecting Environmental Exposure</b>	
Release fraction to air from wide dispersive use (regional only):	1,0E-04
Release fraction to wastewater from wide dispersive use:	1,0E-05
Release fraction to soil from wide dispersive use (regional only):	1,0E-05
<b>Technical conditions and measures at process level (source) to prevent release</b>	
Common practices vary across sites thus conservative process re-lease estimates used.	
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>	
Risk from environmental exposure is driven by freshwater.	
No wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	0
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)	0
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	0
<b>Organisational measures to prevent/limit release from site</b>	
Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.	
<b>Conditions and Measures related to municipal sewage treatment plant</b>	
Estimated substance removal from wastewater via domestic sewage treatment (%)	93,6
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	93,6
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	53
Assumed domestic sewage treatment plant flow (m3/d)	2,0E+03
<b>Conditions and Measures related to external treatment of waste for disposal</b>	
Combustion emissions limited by required exhaust emission controls. Waste combustion emissions considered in regional exposure assessment.	
<b>Conditions and measures related to external recovery of waste</b>	
This substance is consumed during use and no waste of substance is generated.	

### SECTION 3

### EXPOSURE ESTIMATION

#### Section 3.1 - Health

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.



# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1	Revision Date: 28.03.2024	SDS Number: 800010059269	Date of last issue: 22.11.2023 Print Date 04.04.2024
----------------	------------------------------	-----------------------------	---

--

### Section 3.2 -Environment

The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

### SECTION 4

### GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO

#### Section 4.1 - Health

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.  
Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

#### Section 4.2 -Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org>).

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

### Exposure Scenario - Worker

<b>300000000796</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Functional Fluids- Professional
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU22 <b>Process Categories:</b> PROC 1, PROC 2, PROC 3, PROC 8a, PROC 9, PROC 20 <b>Environmental Release Categories:</b> ERC9a, ERC9b, ESVOC SpERC 9.13b.v1
<b>Scope of process</b>	Use as functional fluids e.g. cable oils, transfer oils, coolants, insulators, refrigerants, hydraulic fluids in professional equipment including maintenance and related material transfers.

SECTION 2		OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Section 2.1		Control of Worker Exposure	
Product Characteristics			
Physical form of product		Liquid, vapour pressure < 0.5 kPa at STP	
Concentration of the Substance in Mixture/Article		Covers use of substance/product up to 100% (unless stated differently).,	
Frequency and Duration of Use			
Covers daily exposures up to 8 hours (unless stated differently).			
Other Operational Conditions affecting Exposure			
Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.			
Contributing Scenarios		Risk Management Measures	
Drum/batch transfersNon-dedicated facilityPROC8a		Use drum pumps.	
Transfer from/pouring from containersPROC9		No other specific measures identified.	
Filling/ preparation of equipment from drums or containers.PROC9		No other specific measures identified.	
General exposures (closed systems)PROC1PROC2PROC3		No other specific measures identified.	
Operation of equipment containing engine oils and similar.PROC20		No other specific measures identified.	
Operation of equipment containing engine oils and similar.Operation is carried out at elevated temperature (> 20°C above ambient temperature).PROC20		No other specific measures identified.	
Remanufacture of reject arti-		No other specific measures identified.	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

clesPROC9	
Equipment maintenance-PROC8a	Drain down system prior to equipment opening or maintenance.
Storage.PROC1PROC2	Store substance within a closed system.
<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Substance is complex UVCB.	
Predominantly hydrophobic.	
Readily biodegradable.	
<b>Amounts Used</b>	
Fraction of EU tonnage used in region:	0,1
Regional use tonnage (tonnes/year):	15
Fraction of Regional tonnage used locally:	5,0E-04
Annual site tonnage (tonnes/year):	7,5E-03
Maximum daily site tonnage (kg/day):	2,1E-02
<b>Frequency and Duration of Use</b>	
Continuous release.	
Emission Days (days/year):	365
<b>Environmental factors not influenced by risk management</b>	
Local freshwater dilution factor:	10
Local marine water dilution factor:	100
<b>Other Operational Conditions affecting Environmental Exposure</b>	
Release fraction to air from wide dispersive use (regional only):	5,0E-02
Release fraction to wastewater from wide dispersive use:	2,5E-02
Release fraction to soil from wide dispersive use (regional only):	2,5E-02
<b>Technical conditions and measures at process level (source) to prevent release</b>	
Common practices vary across sites thus conservative process release estimates used.	
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>	
Risk from environmental exposure is driven by freshwater.	
No wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	0
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)	0
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	0
<b>Organisational measures to prevent/limit release from site</b>	
Do not apply industrial sludge to natural soils.	
Sludge should be incinerated, contained or reclaimed.	
<b>Conditions and Measures related to municipal sewage treatment plant</b>	
Estimated substance removal from wastewater via domestic sewage treatment (%)	93,6
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	93,6
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	52
Assumed domestic sewage treatment plant flow (m3/d)	2,0E+03
<b>Conditions and Measures related to external treatment of waste for disposal</b>	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version	Revision Date:	SDS Number:	Date of last issue: 22.11.2023
2.1	28.03.2024	800010059269	Print Date 04.04.2024

External treatment and disposal of waste should comply with applicable local and/or regional regulations.

### Conditions and measures related to external recovery of waste

External recovery and recycling of waste should comply with applicable local and/or regional regulations.

## SECTION 3

### EXPOSURE ESTIMATION

#### Section 3.1 - Health

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

#### Section 3.2 -Environment

The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

## SECTION 4

### GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO

#### Section 4.1 - Health

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.  
Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

#### Section 4.2 -Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org>).

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

### Exposure Scenario - Worker

<b>300000000795</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Functional Fluids- Industrial
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU3 <b>Process Categories:</b> PROC 1, PROC 2, PROC 3, PROC 4, PROC 8a, PROC 8b, PROC 9 <b>Environmental Release Categories:</b> ERC7, ESVOC SpERC 7.13a.v1
<b>Scope of process</b>	Use as functional fluids e.g. cable oils, transfer oils, coolants, insulators, refrigerants, hydraulic fluids in industrial equipment including maintenance and related material transfers.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Section 2.1	Control of Worker Exposure	
Product Characteristics		
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP	
Concentration of the Substance in Mixture/Article	Covers use of substance/product up to 100% (unless stated differently).,	
Frequency and Duration of Use		
Covers daily exposures up to 8 hours (unless stated differently).		
Other Operational Conditions affecting Exposure		
Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.		
Contributing Scenarios	Risk Management Measures	
Bulk transfers(closed systems)PROC1PROC2	No other specific measures identified.	
Drum/batch transfersDedicated facilityPROC8b	No other specific measures identified.	
Filling of articles/equipment(closed systems)PROC9	No other specific measures identified.	
Filling/ preparation of equipment from drums or containers.Non-dedicated facilityPROC8a	No other specific measures identified.	
General exposures (closed systems)PROC2	No other specific measures identified.	
General exposures (open systems)PROC4	No other specific measures identified.	
Remanufacture of reject articlesPROC9	No other specific measures identified.	
Equipment maintenance-PROC8a	No other specific measures identified.	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

Storage.PROC1PROC2	Store substance within a closed system.
<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Substance is complex UVCB.	
Predominantly hydrophobic.	
Readily biodegradable.	
<b>Amounts Used</b>	
Fraction of EU tonnage used in region:	0,1
Regional use tonnage (tonnes/year):	15
Fraction of Regional tonnage used locally:	0,67
Annual site tonnage (tonnes/year):	10
Maximum daily site tonnage (kg/day):	500
<b>Frequency and Duration of Use</b>	
Continuous release.	
Emission Days (days/year):	20
<b>Environmental factors not influenced by risk management</b>	
Local freshwater dilution factor:	10
Local marine water dilution factor:	100
<b>Other Operational Conditions affecting Environmental Exposure</b>	
Release fraction to air from process (initial release prior to RMM):	5,0E-03
Release fraction to wastewater from process (initial release prior to RMM):	3,0E-05
Release fraction to soil from process (initial release prior to RMM):	1,0E-03
<b>Technical conditions and measures at process level (source) to prevent release</b>	
Common practices vary across sites thus conservative process re-release estimates used.	
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>	
Risk from environmental exposure is driven by freshwater.	
Prevent discharge of undissolved substance to or recover from onsite wastewater.	
No wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	0
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)	0
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	0
<b>Organisational measures to prevent/limit release from site</b>	
Do not apply industrial sludge to natural soils.	
Sludge should be incinerated, contained or reclaimed.	
<b>Conditions and Measures related to municipal sewage treatment plant</b>	
Estimated substance removal from wastewater via domestic sewage treatment (%)	93,6
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	93,6
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	8,3E+05
Assumed domestic sewage treatment plant flow (m3/d)	2,0E+03
<b>Conditions and Measures related to external treatment of waste for disposal</b>	
External treatment and disposal of waste should comply with applicable local and/or regional	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

regulations.

### Conditions and measures related to external recovery of waste

External recovery and recycling of waste should comply with applicable local and/or regional regulations.

## SECTION 3

### EXPOSURE ESTIMATION

#### Section 3.1 - Health

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

#### Section 3.2 -Environment

The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

## SECTION 4

### GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO

#### Section 4.1 - Health

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.  
Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

#### Section 4.2 -Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org>).

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

### Exposure Scenario - Worker

<b>300000000802</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Road and construction applications- Professional
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU22 <b>Process Categories:</b> PROC 8a, PROC 8b, PROC 9, PROC 10, PROC 11, PROC 13 <b>Environmental Release Categories:</b> ERC8d, ERC8f, ESVOC SpERC 8.15.v1
<b>Scope of process</b>	Application of surface coatings and binders in road and construction activities, including paving uses, manual mastic and in the application of roofing and water-proofing membranes.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Section 2.1	Control of Worker Exposure	
Product Characteristics		
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP	
Concentration of the Substance in Mixture/Article	Covers use of substance/product up to 100% (unless stated differently).,	
Frequency and Duration of Use		
Covers daily exposures up to 8 hours (unless stated differently).		
Other Operational Conditions affecting Exposure		
Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.		
Contributing Scenarios	Risk Management Measures	
Drum/batch transfersNon-dedicated facilityPROC8a	No other specific measures identified.	
Drum/batch transfersDedicated facilityPROC8b	No other specific measures identified.	
Drum/batch transfersDedicated facilityOperation is carried out at elevated temperature (> 20°C above ambient temperature).PROC8b	Ensure operation is undertaken outdoors. Avoid carrying out activities involving exposure for more than 4 hours	
ManualRolling, BrushingPROC10	Ensure operation is undertaken outdoors.	
Spraying/ fogging by machine applicationOperation is carried out at elevated temperature (> 20°C above ambient temperature).PROC11	Ensure operation is undertaken outdoors. Wear a respirator conforming to EN140 with Type A filter or better. Limit the substance content in the mixture to 50 %.	
Spraying/ fogging by ma-	Ensure operation is undertaken outdoors.	



# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

chine applicationPROC11	Wear a respirator conforming to EN140 with Type A filter or better.
Dipping, immersion and pouringPROC13	No other specific measures identified.
Drum and small package fillingPROC9	No other specific measures identified.
Equipment cleaning and maintenancePROC8a	Drain down system prior to equipment opening or maintenance.
<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Substance is complex UVCB.	
Predominantly hydrophobic.	
Readily biodegradable.	
<b>Amounts Used</b>	
Fraction of EU tonnage used in region:	0,1
Regional use tonnage (tonnes/year):	22
Fraction of Regional tonnage used locally:	5,0E-04
Annual site tonnage (tonnes/year):	1,1E-02
Maximum daily site tonnage (kg/day):	3,0E-02
<b>Frequency and Duration of Use</b>	
Continuous release.	
Emission Days (days/year):	365
<b>Environmental factors not influenced by risk management</b>	
Local freshwater dilution factor:	10
Local marine water dilution factor:	100
<b>Other Operational Conditions affecting Environmental Exposure</b>	
Release fraction to air from wide dispersive use (regional only):	9,5E-01
Release fraction to wastewater from wide dispersive use:	1,0E-02
Release fraction to soil from wide dispersive use (regional only):	4,0E-02
<b>Technical conditions and measures at process level (source) to prevent release</b>	
Common practices vary across sites thus conservative process release estimates used.	
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>	
Risk from environmental exposure is driven by freshwater.	
No wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	0
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)	0
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	0
<b>Organisational measures to prevent/limit release from site</b>	
Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.	
<b>Conditions and Measures related to municipal sewage treatment plant</b>	
Estimated substance removal from wastewater via domestic sewage treatment (%)	93,6
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	93,6

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	77
Assumed domestic sewage treatment plant flow (m3/d)	2,0E+03
<b>Conditions and Measures related to external treatment of waste for disposal</b>	
External treatment and disposal of waste should comply with applicable local and/or regional regulations.	
<b>Conditions and measures related to external recovery of waste</b>	
External recovery and recycling of waste should comply with applicable local and/or regional regulations.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	

<b>Section 3.2 -Environment</b>	
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.	

<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
<b>Section 4.1 - Health</b>	
Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.	

<b>Section 4.2 -Environment</b>	
Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.	
Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.	
Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.	
Further details on scaling and control technologies are provided in SpERC factsheet ( <a href="http://cefic.org">http://cefic.org</a> ).	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

### Exposure Scenario - Worker

<b>300000000806</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Use in laboratories- Industrial
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU3 <b>Process Categories:</b> PROC 10, PROC 15 <b>Environmental Release Categories:</b> ERC2, ERC4
<b>Scope of process</b>	Use of the substance within laboratory settings, including material transfers and equipment cleaning.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Section 2.1	Control of Worker Exposure	
Product Characteristics		
Physical form of product	Liquid, vapour pressure 0.5 - 10 kPa at STP	
Concentration of the Substance in Mixture/Article	Covers use of substance/product up to 100% (unless stated differently).,	
Frequency and Duration of Use		
Covers daily exposures up to 8 hours (unless stated differently).		
Other Operational Conditions affecting Exposure		
Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.		
Contributing Scenarios	Risk Management Measures	
Laboratory activitiesPROC15	No other specific measures identified.	
CleaningPROC10	No other specific measures identified.	
Section 2.2	Control of Environmental Exposure	
Substance is complex UVCB.		
Predominantly hydrophobic.		
Readily biodegradable.		
Amounts Used		
Fraction of EU tonnage used in region:		0,1
Regional use tonnage (tonnes/year):		2,5
Fraction of Regional tonnage used locally:		0,8
Annual site tonnage (tonnes/year):		2,0
Maximum daily site tonnage (kg/day):		100
Frequency and Duration of Use		
Continuous release.		
Emission Days (days/year):		20
Environmental factors not influenced by risk management		
Local freshwater dilution factor:		10
Local marine water dilution factor:		100
Other Operational Conditions affecting Environmental Exposure		

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

Release fraction to air from process (initial release prior to RMM):	2,5E-02
Release fraction to wastewater from process (initial release prior to RMM):	2,0E-02
Release fraction to soil from process (initial release prior to RMM):	1,0E-04
<b>Technical conditions and measures at process level (source) to prevent release</b>	
Common practices vary across sites thus conservative process re-release estimates used.	
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>	
Risk from environmental exposure is driven by freshwater sediment.	
No wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	0
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)	0
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	0
<b>Organisational measures to prevent/limit release from site</b>	
Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.	
<b>Conditions and Measures related to municipal sewage treatment plant</b>	
Estimated substance removal from wastewater via domestic sewage treatment (%)	93,6
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	93,6
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	3,1E+03
Assumed domestic sewage treatment plant flow (m3/d)	2,0E+03
<b>Conditions and Measures related to external treatment of waste for disposal</b>	
External treatment and disposal of waste should comply with applicable local and/or regional regulations.	
<b>Conditions and measures related to external recovery of waste</b>	
External recovery and recycling of waste should comply with applicable local and/or regional regulations.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	

<b>Section 3.2 -Environment</b>	
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.	

<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
<b>Section 4.1 - Health</b>	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version	Revision Date:	SDS Number:	Date of last issue: 22.11.2023
2.1	28.03.2024	800010059269	Print Date 04.04.2024

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

### Section 4.2 -Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

### Exposure Scenario - Worker

<b>300000000810</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Use in laboratories- Professional
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU22 <b>Process Categories:</b> PROC 10, PROC 15 <b>Environmental Release Categories:</b> ERC8a, ESVOC SpERC 8.17.v1
<b>Scope of process</b>	Use of small quantities within laboratory settings, including material transfers and equipment cleaning.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Section 2.1	Control of Worker Exposure	
Product Characteristics		
Physical form of product	Liquid, vapour pressure 0.5 - 10 kPa at STP	
Concentration of the Substance in Mixture/Article	Covers use of substance/product up to 100% (unless stated differently).,	
Frequency and Duration of Use		
Covers daily exposures up to 8 hours (unless stated differently).		
Other Operational Conditions affecting Exposure		
Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.		
Contributing Scenarios	Risk Management Measures	
Laboratory activitiesPROC15	No other specific measures identified.	
CleaningPROC10	No other specific measures identified.	
Section 2.2	Control of Environmental Exposure	
Substance is complex UVCB.		
Predominantly hydrophobic.		
Readily biodegradable.		
Amounts Used		
Fraction of EU tonnage used in region:		0,1
Regional use tonnage (tonnes/year):		2,0
Fraction of Regional tonnage used locally:		5,0E-04
Annual site tonnage (tonnes/year):		1,0E-03
Maximum daily site tonnage (kg/day):		2,7E-03
Frequency and Duration of Use		
Continuous release.		
Emission Days (days/year):		365
Environmental factors not influenced by risk management		
Local freshwater dilution factor:		10
Local marine water dilution factor:		100

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

<b>Other Operational Conditions affecting Environmental Exposure</b>	
Release fraction to air from wide dispersive use (regional only):	5,0E-01
Release fraction to wastewater from wide dispersive use:	5,0E-01
Release fraction to soil from wide dispersive use (regional only):	0
<b>Technical conditions and measures at process level (source) to prevent release</b>	
Common practices vary across sites thus conservative process re-release estimates used.	
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>	
Risk from environmental exposure is driven by freshwater.	
No wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	0
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)	0
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	0
<b>Organisational measures to prevent/limit release from site</b>	
Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.	
<b>Conditions and Measures related to municipal sewage treatment plant</b>	
Estimated substance removal from wastewater via domestic sewage treatment (%)	93,6
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	93,6
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	6,8
Assumed domestic sewage treatment plant flow (m3/d)	2,0E+03
<b>Conditions and Measures related to external treatment of waste for disposal</b>	
External treatment and disposal of waste should comply with applicable local and/or regional regulations.	
<b>Conditions and measures related to external recovery of waste</b>	
External recovery and recycling of waste should comply with applicable local and/or regional regulations.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	

<b>Section 3.2 -Environment</b>	
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.	

<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
<b>Section 4.1 - Health</b>	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version	Revision Date:	SDS Number:	Date of last issue: 22.11.2023
2.1	28.03.2024	800010059269	Print Date 04.04.2024

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

### Section 4.2 -Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org>).



# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

### Exposure Scenario - Worker

**300000000815**

SECTION 1	EXPOSURE SCENARIO TITLE
Title	Water treatment chemicals- Industrial
Use Descriptor	<b>Sector of Use:</b> SU3 <b>Process Categories:</b> PROC 1, PROC 2, PROC 3, PROC 4, PROC 8a, PROC 8b, PROC 13 <b>Environmental Release Categories:</b> ERC3, ERC4, ESVO SpERC 3.22a.v1
Scope of process	Covers the use of the substance for the treatment of water at industrial facilities in open and closed systems.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
Section 2.1	Control of Worker Exposure
<b>Product Characteristics</b>	
Physical form of product	Liquid, vapour pressure 0.5 - 10 kPa at STP
Concentration of the Substance in Mixture/Article	Covers use of substance/product up to 100% (unless stated differently).
<b>Frequency and Duration of Use</b>	
Covers daily exposures up to 8 hours (unless stated differently).	
<b>Other Operational Conditions affecting Exposure</b>	
Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.	
<b>Contributing Scenarios</b>	<b>Risk Management Measures</b>
Bulk transfersUse in contained systemsPROC2	No other specific measures identified.
Drum/batch transfersDedicated facilityPROC8b	No other specific measures identified.
General exposures (closed systems)Use in contained batch processesPROC3	No other specific measures identified.
General exposures (open systems)PROC4	No other specific measures identified.
Pouring from small containersPROC13	No other specific measures identified.
Equipment maintenance-PROC8a	Drain down and flush system prior to equipment opening or maintenance.
Storage.PROC1	Store substance within a closed system.
Section 2.2	Control of Environmental Exposure
Substance is complex UVCB.	
Predominantly hydrophobic.	
Readily biodegradable.	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

<b>Amounts Used</b>	
Fraction of EU tonnage used in region:	0,1
Regional use tonnage (tonnes/year):	55
Fraction of Regional tonnage used locally:	0,54
Annual site tonnage (tonnes/year):	30
Maximum daily site tonnage (kg/day):	100
<b>Frequency and Duration of Use</b>	
Continuous release.	
Emission Days (days/year):	300
<b>Environmental factors not influenced by risk management</b>	
Local freshwater dilution factor:	10
Local marine water dilution factor:	100
<b>Other Operational Conditions affecting Environmental Exposure</b>	
Release fraction to air from process (initial release prior to RMM):	5,0E-02
Release fraction to wastewater from process (initial release prior to RMM):	9,5E-01
Release fraction to soil from process (initial release prior to RMM):	0
<b>Technical conditions and measures at process level (source) to prevent release</b>	
Common practices vary across sites thus conservative process re-lease estimates used.	
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>	
Risk from environmental exposure is driven by freshwater sediment.	
Onsite waste water treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	0
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)	95,8
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	34,9
<b>Organisational measures to prevent/limit release from site</b>	
Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.	
<b>Conditions and Measures related to municipal sewage treatment plant</b>	
Estimated substance removal from wastewater via domestic sewage treatment (%)	93,6
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	95,8
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	100
Assumed domestic sewage treatment plant flow (m3/d)	2,0E+03
<b>Conditions and Measures related to external treatment of waste for disposal</b>	
External treatment and disposal of waste should comply with applicable local and/or regional regulations.	
<b>Conditions and measures related to external recovery of waste</b>	
External recovery and recycling of waste should comply with applicable local and/or regional regulations.	

### SECTION 3

### EXPOSURE ESTIMATION

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

### Section 3.1 - Health

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

### Section 3.2 -Environment

The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

## SECTION 4

### GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO

#### Section 4.1 - Health

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.  
Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

#### Section 4.2 -Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org>).

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

### Exposure Scenario - Worker

**300000000820**

SECTION 1	EXPOSURE SCENARIO TITLE
Title	Water treatment chemicals- Professional
Use Descriptor	<b>Sector of Use:</b> SU22 <b>Process Categories:</b> PROC 1, PROC 2, PROC 3, PROC 4, PROC 8a, PROC 8b, PROC 13 <b>Environmental Release Categories:</b> ERC8f, ESVOC SpERC 8.22b.v1
Scope of process	Covers the use of the substance for the treatment of water in open and closed systems.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
Section 2.1	Control of Worker Exposure
<b>Product Characteristics</b>	
Physical form of product	Liquid, vapour pressure 0.5 - 10 kPa at STP
Concentration of the Substance in Mixture/Article	Covers use of substance/product up to 100% (unless stated differently).,
<b>Frequency and Duration of Use</b>	
Covers daily exposures up to 8 hours (unless stated differently).	
<b>Other Operational Conditions affecting Exposure</b>	
Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.	
<b>Contributing Scenarios</b>	<b>Risk Management Measures</b>
Drum/batch transfersDedicated facilityPROC8b	No other specific measures identified.
General exposures (closed systems)PROC3	No other specific measures identified.
General exposures (open systems)PROC4	No other specific measures identified.
Pouring from small containersPROC13	No other specific measures identified.
Equipment maintenance-PROC8a	No other specific measures identified.
Storage.PROC1PROC2	Store substance within a closed system.
Section 2.2	Control of Environmental Exposure
Substance is complex UVCB.	
Predominantly hydrophobic.	
Readily biodegradable.	
<b>Amounts Used</b>	
Fraction of EU tonnage used in region:	0,1
Regional use tonnage (tonnes/year):	25
Fraction of Regional tonnage used locally:	6,0E-02

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

Annual site tonnage (tonnes/year):	1,5
Maximum daily site tonnage (kg/day):	4,0
<b>Frequency and Duration of Use</b>	
Continuous release.	
Emission Days (days/year):	365
<b>Environmental factors not influenced by risk management</b>	
Local freshwater dilution factor:	10
Local marine water dilution factor:	100
<b>Other Operational Conditions affecting Environmental Exposure</b>	
Release fraction to air from wide dispersive use (regional only):	1,0E-02
Release fraction to wastewater from wide dispersive use:	9,9E-01
Release fraction to soil from wide dispersive use (regional only):	0
<b>Technical conditions and measures at process level (source) to prevent release</b>	
Common practices vary across sites thus conservative process re-release estimates used.	
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>	
Risk from environmental exposure is driven by soil.	
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	0
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)	0,7
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	0
<b>Organisational measures to prevent/limit release from site</b>	
Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.	
<b>Conditions and Measures related to municipal sewage treatment plant</b>	
Estimated substance removal from wastewater via domestic sewage treatment (%)	93,6
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	93,6
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	48
Assumed domestic sewage treatment plant flow (m3/d)	2,0E+03
<b>Conditions and Measures related to external treatment of waste for disposal</b>	
External treatment and disposal of waste should comply with applicable local and/or regional regulations.	
<b>Conditions and measures related to external recovery of waste</b>	
External recovery and recycling of waste should comply with applicable local and/or regional regulations.	

### SECTION 3

### EXPOSURE ESTIMATION

#### Section 3.1 - Health

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version	Revision Date:	SDS Number:	Date of last issue: 22.11.2023
2.1	28.03.2024	800010059269	Print Date 04.04.2024

### Section 3.2 -Environment

The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

### SECTION 4

### GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO

#### Section 4.1 - Health

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.  
Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

#### Section 4.2 -Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org>).

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

### Exposure Scenario - Consumer

<b>300000001122</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Functional Fluids - Consumer
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU21 <b>Product Categories:</b> PC16, PC17 <b>Environmental Release Categories:</b> ERC9a, ERC9b, ESVOC SpERC 9.13c.v1
<b>Scope of process</b>	Use of sealed items containing functional fluids e.g. transfer oils, hydraulic fluids, refrigerants.

<b>SECTION 2</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
<b>Section 2.1</b>	<b>Control of Consumer Exposure</b>
<b>Product Characteristics</b>	
Physical form of product	Liquid, vapour pressure > 10 kPa at STP
Concentration of the Substance in Mixture/Article	Unless stated otherwise.
	Covers concentration up to (%): 100 %
<b>Amounts Used</b>	
Unless stated otherwise.	
for each use event, covers amount up to (g):	2.200
covers skin contact area (cm2):	468
<b>Frequency and Duration of Use</b>	
Unless stated otherwise.	
Covers use up to (days/year):	4
covers use up to (times/day of use):	1
Exposure (hours/event):	0,17
<b>Other Operational Conditions affecting Exposure</b>	
Unless stated otherwise. Covers use at ambient temperatures. Covers use in room size of 20m3 Covers use under typical household ventilation.	
<b>Product Categories</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
Heat transfer fluids Liquids.	Covers concentrations up to 100 %
	covers use up to 4 day/year
	covers skin contact area up to (cm2): 468,00 cm2
	For each use event, covers amount up to 2.200 g
	Covers use in a one car garage (34 m3) under typical ventilation.
	Covers use in room size of 34 m3
	Covers exposure up to 0,17 hours/event
Hydraulic fluids Liquids.	Covers concentrations up to 100 %
	covers use up to 4 day/year

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

	covers skin contact area up to (cm2): 468,00 cm2
	For each use event, covers amount up to 2.200 g
	Covers use in a one car garage (34 m3) under typical ventilation.
	Covers use in room size of 34 m3
	Covers exposure up to 0,17 hours/event

<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Substance is complex UVCB.	
Predominantly hydrophobic.	
Readily biodegradable.	
<b>Amounts Used</b>	
Fraction of EU tonnage used in region:	0,1
Regional use tonnage (tonnes/year):	15
Fraction of Regional tonnage used locally:	5,0E-04
Annual site tonnage (tonnes/year):	7,5E-03
Maximum daily site tonnage (kg/day):	2,1E-02
<b>Frequency and Duration of Use</b>	
Continuous release.	
Emission Days (days/year):	365
<b>Environmental factors not influenced by risk management</b>	
Local freshwater dilution factor:	10
Local marine water dilution factor:	100
<b>Other Operational Conditions affecting Environmental Exposure</b>	
Release fraction to air from wide dispersive use (regional only):	5,0E-02
Release fraction to wastewater from wide dispersive use:	2,5E-02
Release fraction to soil from wide dispersive use (regional only):	2,5E-02
<b>Conditions and Measures related to municipal sewage treatment plant</b>	
Estimated substance removal from wastewater via domestic sewage treatment (%)	93,6
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	52
Assumed domestic sewage treatment plant flow (m3/d)	2,0E+03
<b>Conditions and Measures related to external treatment of waste for disposal</b>	
External treatment and disposal of waste should comply with applicable local and/or regional regulations.	
<b>Conditions and measures related to external recovery of waste</b>	
External recovery and recycling of waste should comply with applicable local and/or regional regulations.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
The ECETOC TRA tool has been used to estimate consumer exposures unless otherwise indicated.	

<b>Section 3.2 -Environment</b>	
The Hydrocarbon Block Method has been used to calculate environmental exposure with	



# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1	Revision Date: 28.03.2024	SDS Number: 800010059269	Date of last issue: 22.11.2023 Print Date 04.04.2024
----------------	------------------------------	-----------------------------	---

the Petrorisk model.

### SECTION 4

### GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO

#### Section 4.1 - Health

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

#### Section 4.2 -Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org>).

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

### Exposure Scenario - Consumer

<b>300000001121</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Use as a fuel - Consumer
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU21 <b>Product Categories:</b> PC13 <b>Environmental Release Categories:</b> ERC9a, ERC9b, ESVOC SpERC 9.12c.v1
<b>Scope of process</b>	Covers consumer uses in liquid fuels.

<b>SECTION 2</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
<b>Section 2.1</b>	<b>Control of Consumer Exposure</b>
<b>Product Characteristics</b>	
Physical form of product	Liquid, vapour pressure > 10 kPa at STP
Concentration of the Sub-stance in Mixture/Article	Unless stated otherwise.
	Covers concentration up to (%): 100 %
<b>Amounts Used</b>	
Unless stated otherwise.	
for each use event, covers amount up to (g):	37.500
covers skin contact area (cm2):	420
<b>Frequency and Duration of Use</b>	
Unless stated otherwise.	
covers use up to (times/day of use):	1
Exposure (hours/event):	2
<b>Other Operational Conditions affecting Exposure</b>	
Unless stated otherwise. Covers use at ambient temperatures. Covers use in room size of 20m3 Covers use under typical household ventilation.	
<b>Product Categories</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
Fuels Liquid: Automotive Refuelling.	Covers concentrations up to 100 %
	covers use up to 52 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 210,00 cm2
	For each use event, covers amount up to 37.500 g
	Covers outdoor use.
	Covers use in room size of 100 m3
	Covers exposure up to 0,05 hours/event
Fuels Liquid Scooter Refuelling.	Covers concentrations up to 100 %
	covers use up to 52 day/year

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 210,00 cm2
	For each use event, covers amount up to 3.750 g
	Covers outdoor use.
	Covers use in room size of 100 m3
	Covers exposure up to 0,03 hours/event
Fuels Liquid, Garden Equipment - Use.	Covers concentrations up to 100 %
	covers use up to 26 day/year
	covers use up to 1 times/day of use
	For each use event, covers amount up to 750 g
	Covers outdoor use.
	Covers use in room size of 100 m3
	Covers exposure up to 2,00 hours/event
Fuels Liquid: Garden Equipment - Refuelling.	Covers concentrations up to 100 %
	covers use up to 26 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 420,00 cm2
	For each use event, covers amount up to 750 g
	Covers use in a one car garage (34 m3) under typical ventilation.
	Covers use in room size of 34 m3
	Covers exposure up to 0,03 hours/event
Fuels Liquid: Home space heater fuel.	Covers concentrations up to 100 %
	covers use up to 365 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 210,00 cm2
	For each use event, covers amount up to 3.000 g
	Covers use under typical household ventilation.
	Covers use in room size of 20m3
	Covers exposure up to 0,03 hours/event
Fuels Liquid: Lamp oil.	Covers concentrations up to 100 %
	covers use up to 52 day/year
	Covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 210,00 cm2
	For each use event, covers amount up to 100 g
	Covers use under typical household ventilation.
	Covers use in room size of 20m3
	Covers exposure up to 0,01 hours/event

<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Substance is complex UVCB.	
Predominantly hydrophobic.	
Readily biodegradable.	
<b>Amounts Used</b>	
Fraction of EU tonnage used in region:	0,1
Regional use tonnage (tonnes/year):	210
Fraction of Regional tonnage used locally:	5,0E-04

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

Annual site tonnage (tonnes/year):	0,11
Maximum daily site tonnage (kg/day):	0,29
<b>Frequency and Duration of Use</b>	
Continuous release.	
Emission Days (days/year):	365
<b>Environmental factors not influenced by risk management</b>	
Local freshwater dilution factor:	10
Local marine water dilution factor:	100
<b>Other Operational Conditions affecting Environmental Exposure</b>	
Release fraction to air from wide dispersive use (regional only):	1,0E-04
Release fraction to wastewater from wide dispersive use:	1,0E-05
Release fraction to soil from wide dispersive use (regional only):	1,0E-05
<b>Conditions and Measures related to municipal sewage treatment plant</b>	
Estimated substance removal from wastewater via domestic sewage treatment (%)	93,6
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	750
Assumed domestic sewage treatment plant flow (m3/d)	2,0E+03
<b>Conditions and Measures related to external treatment of waste for disposal</b>	
Combustion emissions limited by required exhaust emission controls. Waste combustion emissions considered in regional exposure assessment.	
<b>Conditions and measures related to external recovery of waste</b>	
This substance is consumed during use and no waste of substance is generated.	

### SECTION 3      EXPOSURE ESTIMATION

#### Section 3.1 - Health

The ECETOC TRA tool has been used to estimate consumer exposures unless otherwise indicated.

#### Section 3.2 -Environment

The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

### SECTION 4      GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO

#### Section 4.1 - Health

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.  
Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

#### Section 4.2 -Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technolo-

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version	Revision Date:	SDS Number:	Date of last issue: 22.11.2023
2.1	28.03.2024	800010059269	Print Date 04.04.2024

---

gies, either alone or in combination.
---------------------------------------

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.
---

Further details on scaling and control technologies are provided in SpERC factsheet ( <a href="http://cefic.org">http://cefic.org</a> ).
--

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

### Exposure Scenario - Consumer

<b>300000001120</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Use in Agrochemicals uses - Consumer
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU21 <b>Product Categories:</b> , PC27 <b>Environmental Release Categories:</b> ERC8a, ERC8d, ESVOC SpERC 8.11b.v1
<b>Scope of process</b>	Covers the consumer use in agrochemicals in liquid and solid forms.

<b>SECTION 2</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
<b>Section 2.1</b>	<b>Control of Consumer Exposure</b>
<b>Product Characteristics</b>	
Physical form of product	Liquid, vapour pressure > 10 kPa at STP
Concentration of the Sub-stance in Mixture/Article	Unless stated otherwise.
	Covers concentration up to (%): 50 %
<b>Amounts Used</b>	
Unless stated otherwise.	
covers skin contact area (cm2):	857,5
<b>Frequency and Duration of Use</b>	
Unless stated otherwise.	
Covers use up to (days/year):	365
covers use up to (times/day of use):	1
Exposure (hours/event):	4
<b>Other Operational Conditions affecting Exposure</b>	
Unless stated otherwise. Covers use at ambient temperatures. Covers use in room size of 20m3 Covers use under typical household ventilation.	
<b>Product Categories</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
Fertilizers Lawn and garden preparations.	Covers concentrations up to 15 %
	covers use up to 365 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 857,50 cm2
	For each use event, assumes swallowed amount of 0,3 g
	Covers exposure up to 4 hours/event
Plant protection products	Covers concentrations up to 15 %
	covers use up to 365 day/year
	Covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 857,50 cm2

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

	For each use event, assumes swallowed amount of 0,3 g
--	---

<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Substance is complex UVCB.	
Predominantly hydrophobic.	
Readily biodegradable.	
<b>Amounts Used</b>	
Fraction of EU tonnage used in region:	0,1
Regional use tonnage (tonnes/year):	20
Fraction of Regional tonnage used locally:	2,0E-03
Annual site tonnage (tonnes/year):	4,0E-02
Maximum daily site tonnage (kg/day):	0,11
<b>Frequency and Duration of Use</b>	
Continuous release.	
Emission Days (days/year):	365
<b>Environmental factors not influenced by risk management</b>	
Local freshwater dilution factor:	10
Local marine water dilution factor:	100
<b>Other Operational Conditions affecting Environmental Exposure</b>	
Release fraction to air from wide dispersive use (regional only):	9,0E-01
Release fraction to wastewater from wide dispersive use:	1,0E-02
Release fraction to soil from wide dispersive use (regional only):	9,0E-02
<b>Conditions and Measures related to municipal sewage treatment plant</b>	
Estimated substance removal from wastewater via domestic sewage treatment (%)	93,6
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	227
Assumed domestic sewage treatment plant flow (m3/d)	2,0E+03
<b>Conditions and Measures related to external treatment of waste for disposal</b>	
External treatment and disposal of waste should comply with applicable local and/or regional regulations.	
<b>Conditions and measures related to external recovery of waste</b>	
External recovery and recycling of waste should comply with applicable local and/or regional regulations.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
The ECETOC TRA tool has been used to estimate consumer exposures unless otherwise indicated.	

<b>Section 3.2 -Environment</b>	
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.	

<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
------------------	--

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version	Revision Date:	SDS Number:	Date of last issue: 22.11.2023
2.1	28.03.2024	800010059269	Print Date 04.04.2024

---

### Section 4.1 - Health

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.  
Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

### Section 4.2 -Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org>).



# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

### Exposure Scenario - Consumer

<b>300000001119</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Lubricants - Consumer High Environmental Release
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU21 <b>Product Categories:</b> PC1, PC24, PC31 <b>Environmental Release Categories:</b> ERC8a, ERC8d, ESVOC SpERC 8.6c.v1
<b>Scope of process</b>	Covers the consumer use of formulated lubricants in closed and open systems including transfer operations, application, operation of engines and similar articles, equipment maintenance and disposal of waste oil.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Section 2.1	Control of Consumer Exposure	
Product Characteristics		
Physical form of product	Liquid, vapour pressure > 10 kPa at STP	
Concentration of the Sub-stance in Mixture/Article	Unless stated otherwise.	
	Covers concentration up to (%): 100 %	
Amounts Used		
Unless stated otherwise.		
for each use event, covers amount up to (g):		6.390
covers skin contact area (cm2):		468
Frequency and Duration of Use		
Unless stated otherwise.		
covers use up to (times/day of use):		1
Exposure (hours/event):		6
Other Operational Conditions affecting Exposure		
Unless stated otherwise. Covers use at ambient temperatures. Covers use in room size of 20m3 Covers use under typical household ventilation.		
Product Categories	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Adhesives, sealants Glues, hobby use.	Covers concentrations up to 30 %	
	covers use up to 365 day/year	
	covers use up to 1 times/day of use	
	covers skin contact area up to (cm2): 35,73 cm2	
	For each use event, covers amount up to 9 g	
	Covers use in room size of 20m3	
	Covers use under typical household ventilation.	
	Covers exposure up to 4 hours/event	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

Adhesives, sealants Glues DIY-use (carpet glue, tile glue, wood parquet glue).	Covers concentrations up to 30 %
	covers use up to 1 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 110,00 cm2
	For each use event, covers amount up to 6.390 g
	Covers use under typical household ventilation.
	Covers use in room size of 20 m3
	Covers exposure up to 6,00 hours/event
Adhesives, sealants Glue from spray.	Covers concentrations up to 30 %
	covers use up to 6 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 35,73 cm2
	For each use event, covers amount up to 85,05 g
	Covers use under typical household ventilation.
	Covers use in room size of 20 m3
	Covers exposure up to 4,00 hours/event
Adhesives, sealants Seal- ants.	Covers concentrations up to 30 %
	covers use up to 365 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 35,73 cm2
	For each use event, covers amount up to 75 g
	Covers use under typical household ventilation.
	Covers use in room size of 20 m3
	Covers exposure up to 1,00 hours/event
Lubricants, greases, re- lease products Liquids.	Covers concentrations up to 100 %
	covers use up to 4 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 468,00 cm2
	For each use event, covers amount up to 2.200 g
	Covers use in a one car garage (34 m3) under typical ventila- tion.
	Covers use in room size of 34 m3
	Covers exposure up to 0,17 hours/event
Lubricants, greases, re- lease products Pastes.	Covers concentrations up to 20 %
	covers use up to 10 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 468,00 cm2
	For each use event, covers amount up to 34 g
	Covers exposure up to 4,00 hours/event
Lubricants, greases, re- lease products Sprays.	Covers concentrations up to 50 %
	covers use up to 6 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 428,75 cm2
	For each use event, covers amount up to 73 g

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

	Covers use under typical household ventilation.
	Covers use in room size of 20 m <sup>3</sup>
	Covers exposure up to 0,17 hours/event
Polishes and wax blends Polishes, wax / cream (floor, furniture, shoes).	Covers concentrations up to 50 %
	covers use up to 29 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm <sup>2</sup> ): 430,00 cm <sup>2</sup>
	For each use event, covers amount up to 142 g
	Covers use under typical household ventilation.
	Covers use in room size of 20 m <sup>3</sup>
	Covers exposure up to 1,23 hours/event
Polishes and wax blends Polishes, spray (furniture, shoes).	Covers concentrations up to 50 %
	covers use up to 8 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm <sup>2</sup> ): 430,00 cm <sup>2</sup>
	For each use event, covers amount up to 35 g
	Covers use under typical household ventilation.
	Covers use in room size of 20 m <sup>3</sup>
	Covers exposure up to 0,33 hours/event

Section 2.2	Control of Environmental Exposure
Substance is complex UVCB.	
Predominantly hydrophobic.	
Readily biodegradable.	
<b>Amounts Used</b>	
Fraction of EU tonnage used in region:	0,1
Regional use tonnage (tonnes/year):	12
Fraction of Regional tonnage used locally:	5,0E-04
Annual site tonnage (tonnes/year):	5,8E-03
Maximum daily site tonnage (kg/day):	1,6E-02
<b>Frequency and Duration of Use</b>	
Continuous release.	
Emission Days (days/year):	365
<b>Environmental factors not influenced by risk management</b>	
Local freshwater dilution factor:	10
Local marine water dilution factor:	100
<b>Other Operational Conditions affecting Environmental Exposure</b>	
Release fraction to air from wide dispersive use (regional only):	1,5E-01
Release fraction to wastewater from wide dispersive use:	5,0E-02
Release fraction to soil from wide dispersive use (regional only):	5,0E-02
<b>Conditions and Measures related to municipal sewage treatment plant</b>	
Estimated substance removal from wastewater via domestic sewage treatment (%)	93,6
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	40
Assumed domestic sewage treatment plant flow (m <sup>3</sup> /d)	2,0E+03

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

### Conditions and Measures related to external treatment of waste for disposal

External treatment and disposal of waste should comply with applicable local and/or regional regulations.

### Conditions and measures related to external recovery of waste

External recovery and recycling of waste should comply with applicable local and/or regional regulations.

## SECTION 3

### EXPOSURE ESTIMATION

#### Section 3.1 - Health

The ECETOC TRA tool has been used to estimate consumer exposures unless otherwise indicated.

#### Section 3.2 -Environment

The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

## SECTION 4

### GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO

#### Section 4.1 - Health

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.  
Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

#### Section 4.2 -Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org>).

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

### Exposure Scenario - Consumer

<b>300000001118</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Lubricants - Consumer Low Environmental Release
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU21 <b>Product Categories:</b> PC1, PC24, PC31 <b>Environmental Release Categories:</b> ERC9a, ERC9b, ESVOC SpERC 9.6d.v1
<b>Scope of process</b>	Covers the consumer use of formulated lubricants in closed and open systems including transfer operations, application, operation of engines and similar articles, equipment maintenance and disposal of waste oil.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Section 2.1	Control of Consumer Exposure	
Product Characteristics		
Physical form of product	Liquid, vapour pressure > 10 kPa at STP	
Concentration of the Sub-stance in Mixture/Article	Unless stated otherwise.	
	Covers concentration up to (%): 100 %	
Amounts Used		
Unless stated otherwise.		
for each use event, covers amount up to (g):		6.390
covers skin contact area (cm2):		468
Frequency and Duration of Use		
Unless stated otherwise.		
covers use up to (times/day of use):		1
Exposure (hours/event):		6
Other Operational Conditions affecting Exposure		
Unless stated otherwise. Covers use at ambient temperatures. Covers use in room size of 20m3 Covers use under typical household ventilation.		
Product Categories	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Adhesives, sealants Glues, hobby use.	Covers concentrations up to 30 %	
	covers use up to 365 day/year	
	covers use up to 1 times/day of use	
	covers skin contact area up to (cm2): 35,73 cm2	
	For each use event, covers amount up to 9 g	
	Covers use in room size of 20m3	
	Covers use under typical household ventilation.	
	Covers exposure up to 4 hours/event	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

Adhesives, sealants Glues DIY-use (carpet glue, tile glue, wood parquet glue).	Covers concentrations up to 30 %
	covers use up to 1 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 110,00 cm2
	For each use event, covers amount up to 6.390 g
	Covers use under typical household ventilation.
	Covers use in room size of 20 m3
	Covers exposure up to 6,00 hours/event
Adhesives, sealants Glue from spray.	Covers concentrations up to 30 %
	covers use up to 6 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 35,73 cm2
	For each use event, covers amount up to 85,05 g
	Covers use under typical household ventilation.
	Covers use in room size of 20 m3
	Covers exposure up to 4,00 hours/event
Adhesives, sealants Seal- ants.	Covers concentrations up to 30 %
	covers use up to 365 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 35,73 cm2
	For each use event, covers amount up to 75 g
	Covers use under typical household ventilation.
	Covers use in room size of 20 m3
	Covers exposure up to 1,00 hours/event
Lubricants, greases, re- lease products Liquids.	Covers concentrations up to 100 %
	covers use up to 4 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 468,00 cm2
	For each use event, covers amount up to 2.200 g
	Covers use in a one car garage (34 m3) under typical ventila- tion.
	Covers use in room size of 34 m3
	Covers exposure up to 0,17 hours/event
Lubricants, greases, re- lease products Pastes.	Covers concentrations up to 20 %
	covers use up to 10 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 468,00 cm2
	For each use event, covers amount up to 34 g
	Covers exposure up to 4,00 hours/event
Lubricants, greases, re- lease products Sprays.	Covers concentrations up to 50 %
	covers use up to 6 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 428,75 cm2
	For each use event, covers amount up to 73 g

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

	Covers use under typical household ventilation.
	Covers use in room size of 20 m3
	Covers exposure up to 0,17 hours/event
Polishes and wax blends Polishes, wax / cream (floor, furniture, shoes).	Covers concentrations up to 50 %
	covers use up to 29 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 430,00 cm2
	For each use event, covers amount up to 142 g
	Covers use under typical household ventilation.
	Covers use in room size of 20 m3
	Covers exposure up to 1,23 hours/event
Polishes and wax blends Polishes, spray (furniture, shoes).	Covers concentrations up to 50 %
	covers use up to 8 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 430,00 cm2
	For each use event, covers amount up to 35 g
	Covers use under typical household ventilation.
	Covers use in room size of 20 m3
	Covers exposure up to 0,33 hours/event

Section 2.2	Control of Environmental Exposure
Substance is complex UVCB.	
Predominantly hydrophobic.	
Readily biodegradable.	
<b>Amounts Used</b>	
Fraction of EU tonnage used in region:	0,1
Regional use tonnage (tonnes/year):	12
Fraction of Regional tonnage used locally:	5,0E-04
Annual site tonnage (tonnes/year):	5,8E-03
Maximum daily site tonnage (kg/day):	1,6E-02
<b>Frequency and Duration of Use</b>	
Continuous release.	
Emission Days (days/year):	365
<b>Environmental factors not influenced by risk management</b>	
Local freshwater dilution factor:	10
Local marine water dilution factor:	100
<b>Other Operational Conditions affecting Environmental Exposure</b>	
Release fraction to air from wide dispersive use (regional only):	1,0E-02
Release fraction to wastewater from wide dispersive use:	1,0E-02
Release fraction to soil from wide dispersive use (regional only):	1,0E-02
<b>Conditions and Measures related to municipal sewage treatment plant</b>	
Estimated substance removal from wastewater via domestic sewage treatment (%)	93,6
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	41
Assumed domestic sewage treatment plant flow (m3/d)	2,0E+03

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

### Conditions and Measures related to external treatment of waste for disposal

External treatment and disposal of waste should comply with applicable local and/or regional regulations.

### Conditions and measures related to external recovery of waste

External recovery and recycling of waste should comply with applicable local and/or regional regulations.

## SECTION 3

### EXPOSURE ESTIMATION

#### Section 3.1 - Health

The ECETOC TRA tool has been used to estimate consumer exposures unless otherwise indicated.

#### Section 3.2 -Environment

The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

## SECTION 4

### GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO

#### Section 4.1 - Health

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.  
Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

#### Section 4.2 -Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org>).



# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

### Exposure Scenario - Consumer

<b>300000001117</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Use in Cleaning Agents - Consumer
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU21 <b>Product Categories:</b> PC3, PC4, PC8 (excipient only), PC9a, PC24, PC35, PC38 <b>Environmental Release Categories:</b> ERC8a, ERC8d, ESVOC SpERC 8.4c.v1
<b>Scope of process</b>	Covers general exposures to consumers arising from the use of household products sold as washing and cleaning products, aerosols, coatings, de-icers, lubricants and air care products.

<b>SECTION 2</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
<b>Section 2.1</b>	<b>Control of Consumer Exposure</b>
<b>Product Characteristics</b>	
Physical form of product	Liquid, vapour pressure > 10 kPa at STP
Concentration of the Substance in Mixture/Article	Unless stated otherwise.
	Covers concentration up to (%): 100 %
<b>Amounts Used</b>	
Unless stated otherwise.	
for each use event, covers amount up to (g):	13.800
covers skin contact area (cm2):	857,50
<b>Frequency and Duration of Use</b>	
Unless stated otherwise.	
Covers use up to (days/year):	365
covers use up to (times/day of use):	4
Exposure (hours/event):	8
<b>Other Operational Conditions affecting Exposure</b>	
Unless stated otherwise. Covers use at ambient temperatures. Covers use in room size of 20m3 Covers use under typical household ventilation.	
<b>Product Categories</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
Air care products Air care, instant action (aerosol sprays).	Covers concentrations up to 50 %
	covers use up to 365 day/year
	covers use up to 4 times/day of use
	For each use event, covers amount up to 0,1 g
	Covers use under typical household ventilation.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

	Covers use in room size of 20m3
	Covers exposure up to 0,25 hours/event
Air care products Air care, instant action (aerosol sprays). pesticides (excipient only).	Covers concentrations up to 50 %
	covers use up to 365 day/year
	covers use up to 4 times/day of use
	For each use event, covers amount up to 0,5 g
	Covers use under typical household ventilation.
	Covers use in room size of 20 m3
	Covers exposure up to 0,25 hours/event
Air care products Air care, continuous action (solid and liquid).	Covers concentrations up to 10 %
	covers use up to 365 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 35,70 cm2
	For each use event, covers amount up to 0,48 g
	Covers use under typical household ventilation.
	Covers use in room size of 20 m3
	Covers exposure up to 8,00 hours/event
Air care products Air care, continuous action (solid and liquid). pesticides (excipient only).	Covers concentrations up to 50 %
	covers use up to 365 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 35,70 cm2
	For each use event, covers amount up to 0,48 g
	Covers use under typical household ventilation.
	Covers use in room size of 20 m3
	Covers exposure up to 8,00 hours/event
Anti-Freeze and de-icing products Washing car window.	Covers concentrations up to 1 %
	covers use up to 365 day/year
	covers use up to 1 times/day of use
	For each use event, covers amount up to 0,5 g
	Covers use in a one car garage (34 m3) under typical ventilation.
	Covers use in room size of 34 m3
	Covers exposure up to 0,02 hours/event
Anti-Freeze and de-icing products Pouring into radiator.	Covers concentrations up to 10 %
	covers use up to 365 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 428,00 cm2
	For each use event, covers amount up to 2.000 g
	Covers use in a one car garage (34 m3) under typical ventila-

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

	tion.
	Covers use in room size of 34 m3
	Covers exposure up to 0,17 hours/event
Anti-Freeze and de-icing products Lock de-icer.	Covers concentrations up to 50 %
	covers use up to 365 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 214,40 cm2
	For each use event, covers amount up to 4 g
	Covers use in a one car garage (34 m3) under typical ventilation.
	Covers use in room size of 34 m3
	Covers exposure up to 0,25 hours/event
Biocidal products (e.g. Disinfectants, pest control) (excipient only). Laundry and dish washing products.	Covers concentrations up to 5 %
	covers use up to 365 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 857,50 cm2
	For each use event, covers amount up to 15 g
	Covers use under typical household ventilation.
	Covers use in room size of 20m3
	Covers exposure up to 0,50 hours/event
Biocidal products (e.g. Disinfectants, pest control) (excipient only). Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners).	Covers concentrations up to 5 %
	covers use up to 128 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 857,50 cm2
	For each use event, covers amount up to 27 g
	Covers use under typical household ventilation.
	Covers use in room size of 20m3
	Covers exposure up to 0,33 hours/event
Biocidal products (e.g. Disinfectants, pest control) (excipient only). Cleaners, trigger sprays (all purpose cleaners, sanitary products, glass cleaners).	Covers concentrations up to 15 %
	covers use up to 128 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 428,00 cm2
	For each use event, covers amount up to 35 g
	Covers use under typical household ventilation.
	Covers use in room size of 20m3

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

	Covers exposure up to 0,17 hours/event
Coatings and paints, thinners, paint removers Waterborne latex wall paint.	Covers concentrations up to 1,5 %
	covers use up to 4 day/year
	Covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 428,75 cm2
	For each use event, covers amount up to 2.760 g
	Covers use under typical household ventilation.
	Covers use in room size of 20 m3
	Covers exposure up to 2,2 hours/event
Coatings and paints, thinners, paint removers Solvent rich, high solid, water borne paint.	Covers concentrations up to 27,5 %
	covers use up to 6 day/year
	Covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 428,75 cm2
	For each use event, covers amount up to 744 g
	Covers use under typical household ventilation.
	Covers use in room size of 20 m3
	Covers exposure up to 2,2 hours/event
Coatings and paints, thinners, paint removers Aerosol spray can.	Covers concentrations up to 50 %
	covers use up to 2 day/year
	Covers use up to 1 times/day of use
	For each use event, covers amount up to 215 g
	Covers use in a one car garage (34 m3) under typical ventilation.
	Covers use in room size of 24 m3
	Covers exposure up to 0,33 hours/event
Coatings and paints, thinners, paint removers Removers (paint-, glue-, wall paper-, sealant-remover).	Covers concentrations up to 50 %
	covers use up to 3 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 857,50 cm2
	For each use event, covers amount up to 491 g
	Covers use under typical household ventilation.
	Covers use in room size of 20 m3
	Covers exposure up to 2,00 hours/event
Lubricants, greases, release products Liquids.	Covers concentrations up to 100 %
	covers use up to 4 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 468,00 cm2
	For each use event, covers amount up to 2.200 g
	Covers use in a one car garage (34 m3) under typical ventilation.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

	Covers use in room size of 34 m3
	Covers exposure up to 0,17 hours/event
Lubricants, greases, re-release products Pastes.	Covers concentrations up to 20 %
	covers use up to 10 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 468,00 cm2
	For each use event, covers amount up to 34 g
	Covers exposure up to 4 hours/event
Lubricants, greases, re-release products Sprays.	Covers concentrations up to 50 %
	covers use up to 6 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 428,75 cm2
	For each use event, covers amount up to 73 g
	Covers use under typical household ventilation.
	Covers use in room size of 20 m3
	Covers exposure up to 0,17 hours/event
Washing and cleaning products (including solvent based products) Laundry and dish washing products.	Covers concentrations up to 5 %
	covers use up to 365 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 857,50 cm2
	For each use event, covers amount up to 15 g
	Covers use under typical household ventilation.
	Covers use in room size of 20 m3
	Covers exposure up to 0,50 hours/event
Washing and cleaning products (including solvent based products) Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners).	Covers concentrations up to 5 %
	covers use up to 1 times/day of use
	covers use up to 128 day/year
	covers skin contact area up to (cm2): 857,50 cm2
	For each use event, covers amount up to 27 g
	Covers use under typical household ventilation.
	Covers use in room size of 20 m3
	Covers exposure up to 0,33 hours/event
Washing and cleaning products (including solvent based products) Cleaners, trigger sprays (all purpose cleaners, sanitary products, glass cleaners).	Covers concentrations up to 15 %
	covers use up to 128 day/year

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 428,00 cm2
	For each use event, covers amount up to 35 g
	Covers use under typical household ventilation.
	Covers use in room size of 20m3
	Covers exposure up to 0,17 hours/event
Welding and soldering products (with flux coatings or flux cores.), flux products	Covers concentrations up to 20 %
	covers use up to 365 day/year
	covers use up to 1 times/day of use
	For each use event, covers amount up to 12 g
	Covers use under typical household ventilation.
	Covers use in room size of 20m3
	Covers exposure up to 1,00 hours/event

<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Substance is complex UVCB.	
Predominantly hydrophobic.	
Readily biodegradable.	
<b>Amounts Used</b>	
Fraction of EU tonnage used in region:	0,1
Regional use tonnage (tonnes/year):	5,1
Fraction of Regional tonnage used locally:	5,0E-04
Annual site tonnage (tonnes/year):	2,6E-03
Maximum daily site tonnage (kg/day):	7,0E-03
<b>Frequency and Duration of Use</b>	
Continuous release.	
Emission Days (days/year):	365
<b>Environmental factors not influenced by risk management</b>	
Local freshwater dilution factor:	10
Local marine water dilution factor:	100
<b>Other Operational Conditions affecting Environmental Exposure</b>	
Release fraction to air from wide dispersive use (regional only):	9,5E-01
Release fraction to wastewater from wide dispersive use:	2,5E-02
Release fraction to soil from wide dispersive use (regional only):	2,5E-02
<b>Conditions and Measures related to municipal sewage treatment plant</b>	
Estimated substance removal from wastewater via domestic sewage treatment (%)	93,6
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	18
Assumed domestic sewage treatment plant flow (m3/d)	2,0E+03
<b>Conditions and Measures related to external treatment of waste for disposal</b>	
External treatment and disposal of waste should comply with applicable local and/or regional regulations.	
<b>Conditions and measures related to external recovery of waste</b>	
External recovery and recycling of waste should comply with applicable local and/or regional regulations.	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
The ECETOC TRA tool has been used to estimate consumer exposures unless otherwise indicated.	
<b>Section 3.2 -Environment</b>	
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.	
<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
<b>Section 4.1 - Health</b>	
Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.	
<b>Section 4.2 -Environment</b>	
Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.	
Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.	
Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.	
Further details on scaling and control technologies are provided in SpERC factsheet ( <a href="http://cefic.org">http://cefic.org</a> ).	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

### Exposure Scenario - Consumer

<b>300000001109</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Uses in Coatings - Consumer
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU21 <b>Product Categories:</b> PC1, PC4, PC8 (excipient only), PC9a, PC9b, PC9c, PC15, PC18, PC23, PC24, PC31, PC34 <b>Environmental Release Categories:</b> ERC8a, ERC8b, ESVOC SpERC 8.3c.v1
<b>Scope of process</b>	Covers the use in coatings (paints, inks, adhesives, etc) including exposures during use (including product transfer and preparation, application by brush, spray by hand or similar methods) and equipment cleaning.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Section 2.1	Control of Consumer Exposure	
Product Characteristics		
Physical form of product	Liquid, vapour pressure > 10 kPa at STP	
Concentration of the Sub-stance in Mixture/Article	Unless stated otherwise.	
	Covers concentration up to (%): 100 %	
Amounts Used		
Unless stated otherwise.		
for each use event, covers amount up to (g):		13.800
covers skin contact area (cm2):		857,50
Frequency and Duration of Use		
Unless stated otherwise.		
Covers use up to (days/year):		365
covers use up to (times/day of use):		1
Exposure (hours/event):		6
Other Operational Conditions affecting Exposure		
Unless stated otherwise. Covers use at ambient temperatures. Covers use in room size of 20m3 Covers use under typical household ventilation.		
Product Categories	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Adhesives, sealants Glues, hobby use.	Covers concentrations up to 30 %	
	covers use up to 365 day/year	
	covers use up to 1 times/day of use	
	covers skin contact area up to (cm2): 35,73 cm2	
	For each use event, covers amount up to 9 g	
	Covers use in room size of 20m3	



# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

	Covers use under typical household ventilation.
	Covers exposure up to 4 hours/event
Adhesives, sealants Glues DIY-use (carpet glue, tile glue, wood parquet glue).	Covers concentrations up to 30 %
	covers use up to 1 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 110,00 cm2
	For each use event, covers amount up to 6.390 g
	Covers use under typical household ventilation.
	Covers use in room size of 20 m3
	Covers exposure up to 6,00 hours/event
Adhesives, sealants Glue from spray.	Covers concentrations up to 30 %
	covers use up to 6 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 35,73 cm2
	For each use event, covers amount up to 85,05 g
	Covers use under typical household ventilation.
	Covers use in room size of 20 m3
	Covers exposure up to 4,00 hours/event
Adhesives, sealants Seal- ants.	Covers concentrations up to 30 %
	covers use up to 365 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 35,73 cm2
	For each use event, covers amount up to 75 g
	Covers use under typical household ventilation.
	Covers use in room size of 20 m3
	Avoid using when windows closed.
	Covers exposure up to 1,00 hours/event
Anti-Freeze and de-icing products Washing car win- dow.	Covers concentrations up to 1 %
	covers use up to 365 day/year
	covers use up to 1 times/day of use
	For each use event, covers amount up to 0,5 g
	Covers use in a one car garage (34 m3) under typical ventila- tion.
	Covers use in room size of 34 m3
	Covers exposure up to 0,02 hours/event
Anti-Freeze and de-icing products Pouring into radia- tor.	Covers concentrations up to 10 %
	covers use up to 365 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 428,00 cm2
	For each use event, covers amount up to 2.000 g
	Covers use in a one car garage (34 m3) under typical ventila- tion.
	Covers use in room size of 34 m3

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

	Covers exposure up to 0,17 hours/event
Anti-Freeze and de-icing products Lock de-icer.	Covers concentrations up to 30 %
	covers use up to 365 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 214,40 cm2
	For each use event, covers amount up to 4 g
	Covers use in a one car garage (34 m3) under typical ventilation.
	Covers use in room size of 34 m3
	Covers exposure up to 0,25 hours/event
Biocidal products (e.g. Disinfectants, pest control) (excipient only). Laundry and dish washing products.	Covers concentrations up to 5 %
	covers use up to 365 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 857,50 cm2
	For each use event, covers amount up to 15 g
	Covers use under typical household ventilation.
	Covers use in room size of 20m3
	Covers exposure up to 0,50 hours/event
Biocidal products (e.g. Disinfectants, pest control) (excipient only). Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners).	Covers concentrations up to 5 %
	covers use up to 128 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 857,50 cm2
	For each use event, covers amount up to 27 g
	Covers use under typical household ventilation.
	Covers use in room size of 20m3
	Covers exposure up to 0,33 hours/event
Biocidal products (e.g. Disinfectants, pest control) (excipient only). Cleaners, trigger sprays (all purpose cleaners, sanitary products, glass cleaners).	Covers concentrations up to 15 %
	covers use up to 128 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 428,00 cm2
	For each use event, covers amount up to 35 g
	Covers use under typical household ventilation.
	Covers use in room size of 20m3
	Covers exposure up to 0,17 hours/event
Coatings and paints, thin-	Covers concentrations up to 1,5 %

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

ners, paint removers Waterborne latex wall paint.	
	covers use up to 4 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 428,75 cm2
	For each use event, covers amount up to 2.760 g
	Covers use under typical household ventilation.
	Covers use in room size of 20 m3
	Covers exposure up to 2,20 hours/event
Coatings and paints, thinners, paint removers Solvent rich, high solid, water borne paint.	Covers concentrations up to 27,5 %
	covers use up to 6 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 428,75 cm2
	For each use event, covers amount up to 744 g
	Covers use under typical household ventilation.
	Covers use in room size of 20 m3
	Covers exposure up to 2,20 hours/event
Coatings and paints, thinners, paint removers Aerosol spray can.	Covers concentrations up to 50 %
	covers use up to 2 day/year
	covers use up to 1 times/day of use
	For each use event, covers amount up to 215 g
	Covers use in a one car garage (34 m3) under typical ventilation.
	Covers use in room size of 34 m3
	Covers exposure up to 0,33 hours/event
Coatings and paints, thinners, paint removers Removers (paint-, glue-, wall paper-, sealant-remover).	Covers concentrations up to 50 %
	covers use up to 3 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 857,50 cm2
	For each use event, covers amount up to 491 g
	Covers use under typical household ventilation.
	Covers use in room size of 20 m3
	Covers exposure up to 2,00 hours/event
Fillers, Putties Fillers and putty.	Covers concentrations up to 2 %
	covers use up to 12 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 35,73 cm2
	For each use event, covers amount up to 85 g
	Covers use under typical household ventilation.
	Covers use in room size of 20 m3
	Covers exposure up to 4,00 hours/event
Fillers, Putties Plasters and	Covers concentrations up to 2 %

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

floor equalizers.	
	covers use up to 12 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 857,50 cm2
	For each use event, covers amount up to 13.800 g
	Covers use under typical household ventilation.
	Covers use in room size of 20 m3
	Covers exposure up to 2,00 hours/event
Fillers, Putties Modelling clay.	Covers concentrations up to 1 %
	covers use up to 365 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 254,40 cm2
	For each use event, assumes swallowed amount of 1 g
Finger paints	Covers concentrations up to 1,25 %
	covers use up to 365 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 254,40 cm2
	For each use event, assumes swallowed amount of 1,35 g
Non-metal-surface treatment products Waterborne latex wall paint.	Covers concentrations up to 1,5 %
	covers use up to 4 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 428,75 cm2
	For each use event, covers amount up to 2.760 g
	Covers use under typical household ventilation.
	Covers use in room size of 20m3
	Covers exposure up to 2,20 hours/event
Non-metal-surface treatment products Solvent rich, high solid, water borne paint.	Covers concentrations up to 27,5 %
	covers use up to 6 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 428,75 cm2
	For each use event, covers amount up to 744 g
	Covers use under typical household ventilation.
	Covers use in room size of 20 m3
	Covers exposure up to 2,20 hours/event
Non-metal-surface treatment products Aerosol spray can.	Covers concentrations up to 50 %
	covers use up to 2 day/year
	covers use up to 1 times/day of use
	For each use event, covers amount up to 215 g
	Covers use in a one car garage (34 m3) under typical ventilation.
	Covers use in room size of 34 m3
	Covers exposure up to 0,33 hours/event
Non-metal-surface treat-	Covers concentrations up to 50 %

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version  
2.1

Revision Date:  
28.03.2024

SDS Number:  
800010059269

Date of last issue: 22.11.2023  
Print Date 04.04.2024

ment products Removers (paint-, glue-, wall paper-, sealant-remover).	
	covers use up to 3 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 857,50 cm2
	For each use event, covers amount up to 491 g
	Covers use under typical household ventilation.
	Covers use in room size of 20 m3
	Covers exposure up to 2,00 hours/event
Ink and toners	Covers concentrations up to 10 %
	covers use up to 365 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 71,40 cm2
	For each use event, covers amount up to 40 g
	Covers use under typical household ventilation.
	Covers use in room size of 20m3
	Covers exposure up to 2,20 hours/event
Leather tanning, dye, finish- ing, impregnation and care products Polishes, wax / cream (floor, furniture, shoes).	Covers concentrations up to 50 %
	covers use up to 29 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 430,00 cm2
	For each use event, covers amount up to 56 g
	Covers use under typical household ventilation.
	Covers use in room size of 20m3
	Covers exposure up to 1,23 hours/event
Leather tanning, dye, finish- ing, impregnation and care products Polishes, spray (furniture, shoes).	Covers concentrations up to 50 %
	covers use up to 8 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 430,00 cm2
	For each use event, covers amount up to 56 g
	Covers use under typical household ventilation.
	Covers use in room size of 20m3
	Covers exposure up to 0,33 hours/event
Lubricants, greases, re- lease products Liquids.	Covers concentrations up to 100 %
	covers use up to 4 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 468,00 cm2
	For each use event, covers amount up to 2.200 g
	Covers use in a one car garage (34 m3) under typical ventila- tion.
	Covers use in room size of 34 m3
	Covers exposure up to 0,17 hours/event

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

Lubricants, greases, re-release products Pastes.	Covers concentrations up to 20 %
	covers use up to 10 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 468,00 cm2
	For each use event, covers amount up to 34 g
	Covers exposure up to 4 hours/event
Lubricants, greases, re-release products Sprays.	Covers concentrations up to 50 %
	covers use up to 6 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 428,75 cm2
	For each use event, covers amount up to 73 g
	Covers use under typical household ventilation.
	Covers use in room size of 20 m3
	Covers exposure up to 0,17 hours/event
Polishes and wax blends Polishes, wax / cream (floor, furniture, shoes).	Covers concentrations up to 50 %
	covers use up to 29 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 430,00 cm2
	For each use event, covers amount up to 142 g
	Covers use under typical household ventilation.
	Covers use in room size of 20 m3
	Covers exposure up to 1,23 hours/event
Polishes and wax blends Polishes, spray (furniture, shoes).	Covers concentrations up to 50 %
	covers use up to 8 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 430,00 cm2
	For each use event, covers amount up to 35 g
	Covers use under typical household ventilation.
	Covers use in room size of 20 m3
	Covers exposure up to 0,33 hours/event
Textile dyes, finishing and impregnating products; including bleaches and other processing aids	Covers concentrations up to 10 %
	covers use up to 365 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 857,50 cm2
	For each use event, covers amount up to 115 g
	Covers use under typical household ventilation.
	Covers use in room size of 20m3
	Covers exposure up to 1,00 hours/event

<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Substance is complex UVCB.	
Predominantly hydrophobic.	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version 2.1      Revision Date: 28.03.2024      SDS Number: 800010059269      Date of last issue: 22.11.2023  
Print Date 04.04.2024

Readily biodegradable.	
<b>Amounts Used</b>	
Fraction of EU tonnage used in region:	0,1
Regional use tonnage (tonnes/year):	270
Fraction of Regional tonnage used locally:	5,0E-04
Annual site tonnage (tonnes/year):	0,13
Maximum daily site tonnage (kg/day):	0,37
<b>Frequency and Duration of Use</b>	
Continuous release.	
Emission Days (days/year):	365
<b>Environmental factors not influenced by risk management</b>	
Local freshwater dilution factor:	10
Local marine water dilution factor:	100
<b>Other Operational Conditions affecting Environmental Exposure</b>	
Release fraction to air from wide dispersive use (regional only):	9,85E-01
Release fraction to wastewater from wide dispersive use:	1,0E-02
Release fraction to soil from wide dispersive use (regional only):	5,0E-03
<b>Conditions and Measures related to municipal sewage treatment plant</b>	
Estimated substance removal from wastewater via domestic sewage treatment (%)	93,6
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	840
Assumed domestic sewage treatment plant flow (m3/d)	2,0E+03
<b>Conditions and Measures related to external treatment of waste for disposal</b>	
External treatment and disposal of waste should comply with applicable local and/or regional regulations.	
<b>Conditions and measures related to external recovery of waste</b>	
External recovery and recycling of waste should comply with applicable local and/or regional regulations.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
The ECETOC TRA tool has been used to estimate consumer exposures unless otherwise indicated.	

<b>Section 3.2 -Environment</b>	
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.	

<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
<b>Section 4.1 - Health</b>	
Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## ShellSol A100 Low Cumene

Version	Revision Date:	SDS Number:	Date of last issue: 22.11.2023
2.1	28.03.2024	800010059269	Print Date 04.04.2024

---

### Section 4.2 -Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org>).