According to EC No 1907/2006 as amended as at the date of this SDS

NEODENE 14 Alpha Olefin

Version Revision Date: SDS Number: Date of last issue: 31.10.2024

3.5 17.02.2025 800001012232 Print Date 24.02.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : NEODENE 14 Alpha Olefin

Product code : V1143

Registration number EU : 01-2119472424-39-0000

CAS-No. : 1120-36-1

Other means of identification : 1-tetradecylene, Linear Alpha Olefin C14, Tetradec-1-ene,

Tetradecene, -1

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub
: Use as an intermediate in industrial chemicals manufacture.

stance/Mixture Please refer to section 16 and/or the annexes for the regis-

tered uses under REACH.

Uses advised against : This product must not be used in applications other than the

above without first seeking the advice of the supplier.

This product must not be used in applications other than those listed in Section 1 without first seeking the advice of the sup-

plier.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier : Shell Chemicals Europe B.V.

PO Box 2334 3000 CH Rotterdam

Netherlands

Telephone : +31 (0)10 441 5137 / +31 (0)10 441 5191 Telefax : +31 (0)20 716 8316 / +31 (0)20 713 9230

Contact for Safety Data : sccmsds@shell.com

Sheet

1.4 Emergency telephone number

+44 (0) 1235 239 670 (This telephone number is available 24 hours per day, 7 days per

week)

Poison Centre: (+41) 145

Other information : NEODENE is a trademark owned by Shell Trademark Man-

agement B.V. and Shell Brands Inc. and used by affiliates of

Shell plc.

According to EC No 1907/2006 as amended as at the date of this SDS

NEODENE 14 Alpha Olefin

Version Revision Date: SDS Number: Date of last issue: 31.10.2024

3.5 17.02.2025 800001012232 Print Date 24.02.2025

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Aspiration hazard, Category 1 H304: May be fatal if swallowed and enters air-

ways.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms

Signal word : Danger

Hazard statements : PHYSICAL HAZARDS:

Not classified as a physical hazard according to CLP

criteria.

HEALTH HAZARDS:

H304 May be fatal if swallowed and enters airways.

ENVIRONMENTAL HAZARDS:

Not classified as environmental hazard according to

CLP criteria.

Supplemental Hazard

Statements

EUH066

Repeated exposure may cause skin dryness or

cracking.

Precautionary statements : Prevention:

P243 Take precautionary measures against static discharge.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON

CENTER/ doctor.

P331 Do NOT induce vomiting.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

2.3 Other hazards

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

According to EC No 1907/2006 as amended as at the date of this SDS

NEODENE 14 Alpha Olefin

Version Revision Date: SDS Number: Date of last issue: 31.10.2024

3.5 17.02.2025 800001012232 Print Date 24.02.2025

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

This material is a static accumulator.

Even with proper grounding and bonding, this material can still accumulate an electrostatic charge.

If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable airvapour mixtures can occur.

SECTION 3: Composition/information on ingredients

3.1 Substances

Components

Chemical name	CAS-No.	Concentration (% w/w)
	EC-No.	
1-Tetradecene	1120-36-1	<= 100
	214-306-9	

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Not expected to be a health hazard when used under normal

conditions.

Protection of first-aiders : When administering first aid, ensure that you are wearing the

appropriate personal protective equipment according to the

incident, injury and surroundings.

If inhaled : No treatment necessary under normal conditions of use.

If symptoms persist, obtain medical advice.

In case of skin contact : Remove contaminated clothing. Immediately flush skin with

large amounts of water for at least 15 minutes, and follow by washing with soap and water if available. If redness, swelling, pain and/or blisters occur, transport to the nearest medical

facility for additional treatment.

In case of eye contact : Flush eye with copious quantities of water.

Remove contact lenses, if present and easy to do. Continue

rinsing.

If persistent irritation occurs, obtain medical attention.

If swallowed : Call emergency number for your location / facility.

If swallowed, do not induce vomiting: transport to nearest medical facility for additional treatment. If vomiting occurs

According to EC No 1907/2006 as amended as at the date of this SDS

NEODENE 14 Alpha Olefin

Version Revision Date: SDS Number: Date of last issue: 31.10.2024

3.5 17.02.2025 800001012232 Print Date 24.02.2025

spontaneously, keep head below hips to prevent aspiration. If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (38.3°C), shortness of breath, chest congestion or continued coughing or wheezing.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Not considered to be an inhalation hazard under normal con-

ditions of use.

Possible respiratory irritation signs and symptoms may include a temporary burning sensation of the nose and throat, cough-

ing, and/or difficulty breathing.

Skin irritation signs and symptoms may include a burning sen-

sation, redness, or swelling.

No specific hazards under normal use conditions.

Eye irritation signs and symptoms may include a burning sen-

sation, redness, swelling, and/or blurred vision.

If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (38.3°C), shortness of breath, chest congestion or continued coughing or wheezing.

The onset of respiratory symptoms may be delayed for sever-

al hours after exposure.

If material enters lungs, signs and symptoms may include coughing, choking, wheezing, difficulty in breathing, chest

congestion, shortness of breath, and/or fever.

Defatting dermatitis signs and symptoms may include a burn-

ing sensation and/or a dried/cracked appearance.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Call a doctor or poison control center for guidance.

Potential for chemical pneumonitis.

Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Foam, water spray or fog. Dry chemical powder, carbon diox-

ide, sand or earth may be used for small fires only.

Unsuitable extinguishing

media

Do not use water in a jet.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

Clear fire area of all non-emergency personnel. Hazardous combustion products may include:

A complex mixture of airborne solid and liquid particulates and

gases (smoke). Carbon monoxide.

Unidentified organic and inorganic compounds.

According to EC No 1907/2006 as amended as at the date of this SDS

NEODENE 14 Alpha Olefin

Version Revision Date: SDS Number: Date of last issue: 31.10.2024

3.5 17.02.2025 800001012232 Print Date 24.02.2025

Flammable vapours may be present even at temperatures

below the flash point.

The vapour is heavier than air, spreads along the ground and

distant ignition is possible.

Will float and can be reignited on surface water.

5.3 Advice for firefighters

Special protective equipment :

for firefighters

Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to

relevant Standards (e.g. Europe: EN469).

Specific extinguishing meth-

ods

Standard procedure for chemical fires.

Further information : Keep adjacent containers cool by spraying with water.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions

Observe all relevant local and international regulations. Notify authorities if any exposure to the general public or the

environment occurs or is likely to occur.

Local authorities should be advised if significant spillages

cannot be contained.

6.1.1 For non emergency personnel: Avoid contact with skin, eyes and clothing.

Isolate hazard area and deny entry to unnecessary or unpro-

tected personnel.

Do not breathe fumes, vapour. Do not operate electrical equipment. 6.1.2 For emergency responders:

Avoid contact with skin, eyes and clothing.

Isolate hazard area and deny entry to unnecessary or unpro-

tected personnel.

Do not breathe fumes, vapour. Do not operate electrical equipment.

6.2 Environmental precautions

Environmental precautions : Shut off leaks, if possible without personal risks. Remove all

possible sources of ignition in the surrounding area. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. Attempt to disperse the vapour or to direct its flow to a safe location for example by using fog sprays. Take precautionary measures

According to EC No 1907/2006 as amended as at the date of this SDS

NEODENE 14 Alpha Olefin

Version Revision Date: SDS Number: Date of last issue: 31.10.2024

3.5 17.02.2025 800001012232 Print Date 24.02.2025

against static discharge. Ensure electrical continuity by bonding and grounding (conthing) all equipment

ing and grounding (earthing) all equipment. Monitor area with combustible gas indicator.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : For small liquid spills (< 1 drum), transfer by mechanical

means to a labeled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove

contaminated soil and dispose of safely.

For large liquid spills (> 1 drum), transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely

Ventilate contaminated area thoroughly.

If contamination of site occurs remediation may require spe-

cialist advice.

6.4 Reference to other sections

For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet., For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures : Avoid breathing of or direct contact with material. Only use in

well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see

Section 8 of this Safety Data Sheet.

Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this

material.

Ensure that all local regulations regarding handling and stor-

age facilities are followed.

Advice on safe handling : Avoid inhaling vapour and/or mists.

Avoid contact with skin, eyes and clothing.

Extinguish any naked flames. Do not smoke. Remove ignition

sources. Avoid sparks.

Use local exhaust ventilation if there is risk of inhalation of

vapours, mists or aerosols.

Bulk storage tanks should be diked (bunded).

When using do not eat or drink.

The vapour is heavier than air, spreads along the ground and

distant ignition is possible.

According to EC No 1907/2006 as amended as at the date of this SDS

NEODENE 14 Alpha Olefin

Version Revision Date: SDS Number: Date of last issue: 31.10.2024

3.5 17.02.2025 800001012232 Print Date 24.02.2025

Product Transfer

: Even with proper grounding and bonding, this material can still accumulate an electrostatic charge. If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur. Be aware of handling operations that may give rise to additional hazards that result from the accumulation of static charges. These include but are not limited to pumping (especially turbulent flow), mixing, filtering, splash filling, cleaning and filling of tanks and containers, sampling, switch loading, gauging, vacuum truck operations, and mechanical movements. These activities may lead to static discharge e.g. spark formation. Restrict line velocity during pumping in order to avoid generation of electrostatic discharge (≤ 1 m/s until fill pipe submerged to twice its diameter, then ≤ 7 m/s). Avoid splash filling. Do NOT use compressed air for filling, discharging, or handling operations.

Refer to guidance under Handling section.

Hygiene measures

Wash hands before eating, drinking, smoking and using the toilet. Launder contaminated clothing before re-use. Do not ingest. If swallowed, then seek immediate medical assistance.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Refer to section 15 for any additional specific legislation cov-

ering the packaging and storage of this product.

Further information on storage stability

Storage Temperature:

Ambient.

Bulk storage tanks should be diked (bunded).

Locate tanks away from heat and other sources of ignition. Cleaning, inspection and maintenance of storage tanks is a specialist operation, which requires the implementation of

strict procedures and precautions.

Must be stored in a diked (bunded) well- ventilated area, away from sunlight, ignition sources and other sources of heat. Keep away from aerosols, flammables, oxidizing agents, corrosives and from other flammable products which are not

harmful or toxic to man or to the environment.

Electrostatic charges will be generated during pumping. Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment to reduce the risk.

The vapours in the head space of the storage vessel may lie in the flammable/explosive range and hence may be flamma-

ble.

According to EC No 1907/2006 as amended as at the date of this SDS

NEODENE 14 Alpha Olefin

Version Revision Date: SDS Number: Date of last issue: 31.10.2024

3.5 17.02.2025 800001012232 Print Date 24.02.2025

Packaging material : Suitable material: For containers, or container linings use mild

steel, stainless steel., For container paints, use epoxy paint,

zinc silicate paint.

Unsuitable material: Avoid prolonged contact with natural,

butyl or nitrile rubbers.

Container Advice : Do not cut, drill, grind, weld or perform similar operations on or

near containers.

7.3 Specific end use(s)

Specific use(s) : Please refer to section 16 and/or the annexes for the regis-

tered uses under REACH.

See additional references that provide safe handling practices for liquids that are determined to be static accumulators: American Petroleum Institute 2003 (Protection Against Ignitions Arising out of Static, Lightning and Stray Currents) or National Fire Protection Agency 77 (Recommended Practices

on Static Electricity).

IEC/TS 60079-32-1: Electrostatic hazards, guidance

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Biological occupational exposure limits

No biological limit allocated.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name		Environmental Compartment	Value
1-Tetradecene			
Remarks:	Exposure	Exposure assessments have not been presented for the environment	
	therefore PNEC values not required.		

8.2 Exposure controls

Engineering measures

Read in conjunction with the Exposure Scenario for your specific use contained in the Annex. The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

Use sealed systems as far as possible.

Adequate explosion-proof ventilation to control airborne concentrations below the exposure guidelines/limits.

Local exhaust ventilation is recommended.

Firewater monitors and deluge systems are recommended.

Eye washes and showers for emergency use.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

According to EC No 1907/2006 as amended as at the date of this SDS

NEODENE 14 Alpha Olefin

Version Revision Date: SDS Number: Date of last issue: 31.10.2024

3.5 17.02.2025 800001012232 Print Date 24.02.2025

General Information

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

Personal protective equipment

Read in conjunction with the Exposure Scenario for your specific use contained in the Annex. The provided information is made in consideration of the PPE directive (Council Directive 89/686/EEC) and the CEN European Committee for Standardisation (CEN) standards.

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Eye protection : If material is handled such that it could be splashed into eyes,

protective eyewear is recommended. Approved to EU Standard EN166.

Hand protection

Remarks : Where hand contact with the product may occur the use of

gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. Longer term protection: butyl-

rubber Nitrile rubber gloves.

Incidental contact/Splash protection: Nitrile rubber gloves. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on

clean hands. After using gloves, hands should be washed

According to EC No 1907/2006 as amended as at the date of this SDS

NEODENE 14 Alpha Olefin

Version Revision Date: SDS Number: Date of last issue: 31.10.2024

3.5 17.02.2025 800001012232 Print Date 24.02.2025

and dried thoroughly. Application of a non-perfumed moistur-

izer is recommended.

Skin and body protection : Skin protection is not required under normal conditions of

use.

For prolonged or repeated exposures use impervious clothing

over parts of the body subject to exposure.

If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to relevant Stand-

ard, and provide employee skin care programmes.

Protective clothing approved to EU Standard EN14605.

Wear antistatic and flame-retardant clothing, if a local risk

assessment deems it so.

Respiratory protection : If engineering controls do not maintain airborne concentra-

tions to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are unsuitable (e.g. airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing appa-

ratus.

Where air-filtering respirators are suitable, select an appro-

priate combination of mask and filter.

If air-filtering respirators are suitable for conditions of use: Select a filter suitable for organic gases and vapours [Type A

boiling point > 65°C (149°F)] meeting EN14387.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : Liquid at room temperature.

Colour : Clear colourless

Odour : Mild hydrocarbon

Odour Threshold : Data not available

Melting / freezing point : -14 °C

Boiling point/boiling range : 242 - 244 °C

Flammability

Flammability (solid, gas) : Not applicable

According to EC No 1907/2006 as amended as at the date of this SDS

NEODENE 14 Alpha Olefin

Date of last issue: 31.10.2024 Version Revision Date: SDS Number:

17.02.2025 800001012232 Print Date 24.02.2025 3.5

Lower explosion limit and upper explosion limit / flammability limit

Upper explosion limit /

Upper flammability limit

: Data not available

Lower explosion limit /

Lower flammability limit

Data not available

Flash point 113 °C

Method: ASTM D7236 (closed cup)

239 °C Auto-ignition temperature

Decomposition temperature

Decomposition tempera-

Data not available

ture

рΗ Not applicable

Viscosity

Viscosity, dynamic 1,53 mPa.s (38 °C)

Method: ASTM D445

2,01 mPa.s (20 °C) Method: ASTM D445

Viscosity, kinematic 1,89 mm2/s (40 °C)

Method: ASTM D445

2,75 mm2/s (20 °C) Method: ASTM D445

Solubility(ies)

Water solubility 0,014 mg/l (25 °C)

Partition coefficient: n-

octanol/water

log Pow: estimated value(s) 7,1

Vapour pressure : 6,9 Pa (38 °C)

2 Pa (25 °C)

Relative density 0,775 (20 °C)

Method: ASTM D4052

Density 775 kg/m3 (20 °C)

Method: ASTM D4052

Relative vapour density : >1

Particle characteristics

Particle size Data not available

According to EC No 1907/2006 as amended as at the date of this SDS

NEODENE 14 Alpha Olefin

Version Revision Date: SDS Number: Date of last issue: 31.10.2024

3.5 17.02.2025 800001012232 Print Date 24.02.2025

Data not available

9.2 Other information

Explosive properties : Not classified

Oxidizing properties : Not applicable

Evaporation rate : Data not available

Conductivity: < 100 pS/m

The conductivity of this material makes it a static accumulator., A liquid is typically considered nonconductive if its con-

ductivity is below 100 pS/m and is considered semi-

conductive if its conductivity is below 10,000 pS/m., Whether a liquid is nonconductive or semiconductive, the precautions are the same., A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can

greatly influence the conductivity of a liquid

Surface tension : Data not available

Molecular weight : 196 g/mol

SECTION 10: Stability and reactivity

10.1 Reactivity

The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.

10.2 Chemical stability

No hazardous reaction is expected when handled and stored according to provisions Stable under normal conditions of use.

10.3 Possibility of hazardous reactions

Hazardous reactions : Reacts with strong oxidising agents.

10.4 Conditions to avoid

Conditions to avoid : Avoid heat, sparks, open flames and other ignition sources.

In certain circumstances product can ignite due to static elec-

tricity.

10.5 Incompatible materials

Materials to avoid : Strong oxidising agents.

According to EC No 1907/2006 as amended as at the date of this SDS

NEODENE 14 Alpha Olefin

Date of last issue: 31.10.2024 Version Revision Date: SDS Number:

Print Date 24.02.2025 3.5 17.02.2025 800001012232

10.6 Hazardous decomposition products

Hazardous decomposition products are not expected to form during normal storage. Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids and gases including carbon monoxide, carbon dioxide, sulphur oxides and unidentified organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

exposure

Information on likely routes of : Exposure may occur via inhalation, ingestion, skin absorption,

skin or eye contact, and accidental ingestion.

Acute toxicity

Components:

1-Tetradecene:

Acute oral toxicity LD50: > 5000 mg/kg

Remarks: Low toxicity

Based on available data, the classification criteria are not met.

Acute inhalation toxicity Remarks: Low toxicity if inhaled.

Based on available data, the classification criteria are not met.

Acute dermal toxicity LD50: > 5000 mg/kg

Remarks: Low toxicity

Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Components:

1-Tetradecene:

Remarks Causes mild skin irritation.

Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Components:

1-Tetradecene:

Remarks Not irritating to eye.

Respiratory or skin sensitisation

Components:

1-Tetradecene:

According to EC No 1907/2006 as amended as at the date of this SDS

NEODENE 14 Alpha Olefin

Version Revision Date: SDS Number: Date of last issue: 31.10.2024

3.5 17.02.2025 800001012232 Print Date 24.02.2025

Remarks : Not a sensitiser.

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Components:

1-Tetradecene:

Genotoxicity in vivo : Remarks: Non mutagenic

Germ cell mutagenicity- As-

sessment

This product does not meet the criteria for classification in

categories 1A/1B.

Carcinogenicity

Components:

1-Tetradecene:

Remarks : Not a carcinogen.

Based on available data, the classification criteria are not met.

Carcinogenicity - Assess-

ment

This product does not meet the criteria for classification in

categories 1A/1B.

Material	GHS/CLP Carcinogenicity Classification
1-Tetradecene	No carcinogenicity classification.

Reproductive toxicity

Components:

1-Tetradecene:

Effects on fertility

Remarks: Not a developmental toxicant., Based on available data, the classification criteria are not met., Does not impair

fertility.

Reproductive toxicity - As-

sessment

This product does not meet the criteria for classification in

categories 1A/1B.

STOT - single exposure

Components:

1-Tetradecene:

Remarks : Based on available data, the classification criteria are not met.

According to EC No 1907/2006 as amended as at the date of this SDS

NEODENE 14 Alpha Olefin

Date of last issue: 31.10.2024 Version Revision Date: SDS Number:

800001012232 Print Date 24.02.2025 3.5 17.02.2025

STOT - repeated exposure

Components:

1-Tetradecene:

Remarks Based on available data, the classification criteria are not met.

Aspiration toxicity

Components:

1-Tetradecene:

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

The substance/mixture does not contain components consid-Assessment

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

Further information

Product:

Remarks Unless indicated otherwise, the data presented is representa-

tive of the product as a whole, rather than for individual com-

ponent(s).

Components:

1-Tetradecene:

Remarks Classifications by other authorities under varying regulatory

frameworks may exist.

SECTION 12: Ecological information

12.1 Toxicity

Components:

1-Tetradecene:

Toxicity to fish : Remarks: Not toxic at limit of water solubility:

Toxicity to daphnia and other : Remarks: Not toxic at limit of water solubility:

aquatic invertebrates

According to EC No 1907/2006 as amended as at the date of this SDS

NEODENE 14 Alpha Olefin

Version Revision Date: SDS Number: Date of last issue: 31.10.2024

3.5 17.02.2025 800001012232 Print Date 24.02.2025

Toxicity to algae/aquatic plants : Remarks: Not toxic at limit of water solubility:

Toxicity to microorganisms :

Remarks: Not toxic at limit of water solubility:

Toxicity to fish (Chronic tox-

icity)

Remarks: Data not available

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

ic toxicity)

Remarks: Data not available

12.2 Persistence and degradability

Components:

1-Tetradecene:

Biodegradability : Remarks: Readily biodegradable.

12.3 Bioaccumulative potential

Components:

1-Tetradecene:

Bioaccumulation : Remarks: Has the potential to bioaccumulate.

12.4 Mobility in soil

Components:

1-Tetradecene:

Mobility : Remarks: Floats on water., Adsorbs to soil and has low mobili-

ty

12.5 Results of PBT and vPvB assessment

Components:

1-Tetradecene:

Assessment : The substance does not fulfill all screening criteria for persis-

tence, bioaccumulation and toxicity and hence is not consid-

ered to be PBT or vPvB..

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to

have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

According to EC No 1907/2006 as amended as at the date of this SDS

NEODENE 14 Alpha Olefin

Version Revision Date: SDS Number: Date of last issue: 31.10.2024

3.5 17.02.2025 800001012232 Print Date 24.02.2025

12.7 Other adverse effects

Product:

Additional ecological infor-

mation

Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Recover or recycle if possible.

It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.

Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment. Do not dispose into the environment, in drains or in water courses.

Do not dispose of tank water bottoms by allowing them to drain into the ground. This will result in soil and groundwater contamination.

Waste arising from a spillage or tank cleaning should be disposed of in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand.

Waste, spills or used product is dangerous waste.

Disposal should be in accordance with applicable regional,

national, and local laws and regulations.

Local regulations may be more stringent than regional or national requirements and must be complied with.

MARPOL - see International Convention for the Prevention of Pollution from Ships (MARPOL 73/78) which provides technical aspects at controlling pollutions from ships.

Contaminated packaging : Drain c

Drain container thoroughly.

After draining, vent in a safe place away from sparks and fire. Residues may cause an explosion hazard. Do not puncture,

cut or weld uncleaned drums.

Send to drum recoverer or metal reclaimer.

Comply with any local recovery or waste disposal regulations.

SECTION 14: Transport information

14.1 UN number or ID number

According to EC No 1907/2006 as amended as at the date of this SDS

NEODENE 14 Alpha Olefin

Version Revision Date: SDS Number: Date of last issue: 31.10.2024

3.5 17.02.2025 800001012232 Print Date 24.02.2025

ADR : Not regulated as a dangerous good

RID : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

: Not regulated as a dangerous good

14.2 UN proper shipping name

ADR : Not regulated as a dangerous good

RID : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

: Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADR : Not regulated as a dangerous good

RID : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

: Not regulated as a dangerous good

14.4 Packing group

CDNI Inland Water Waste

Agreement

: NST 8969 Chemicals

ADR : Not regulated as a dangerous good

RID : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

: Not regulated as a dangerous good

14.5 Environmental hazards

ADR : Not regulated as a dangerous good

RID : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

14.6 Special precautions for user

Remarks : Special Precautions: Refer to Section 7, Handling & Storage,

for special precautions which a user needs to be aware of or

needs to comply with in connection with transport.

14.7 Maritime transport in bulk according to IMO instruments

Pollution category : Y Ship type : 2

Product name : Olefins, (C13+, all isomers)

Additional Information: This product may be transported under nitrogen blanketing.

Nitrogen is an odourless and invisible gas. Exposure to nitrogen enriched atmospheres displaces available oxygen which may cause asphyxiation or death. Personnel must observe

According to EC No 1907/2006 as amended as at the date of this SDS

NEODENE 14 Alpha Olefin

Version Revision Date: SDS Number: Date of last issue: 31.10.2024

3.5 17.02.2025 800001012232 Print Date 24.02.2025

strict safety precautions when involved with a confined space

entry.

Transport in bulk according to Annex II of Marpol and the IBC

Code

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - List of substances subject to authorisation : Product is not subject to Authorisa-

(Annex XIV) tion under REACH.

REACH - Candidate List of Substances of Very High : This product does not contain sub-Concern for Authorisation (Article 59). : stances of very high concern (Regu-

lation (EC) No 1907/2006 (REACH),

Article 57).

Waters Protection Ordinance (WPO 814.201)

Water pollution class : Swiss Class A, (www.tankportal.ch)

Other regulations:

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

The components of this product are reported in the following inventories:

DSL : Listed

IECSC : Listed

ENCS : Listed

KECI : Listed

NZIoC : Listed

PICCS : Listed

TSCA : Listed

TCSI : Listed

15.2 Chemical safety assessment

A Chemical Safety Assessment was performed for all substances of this product.

According to EC No 1907/2006 as amended as at the date of this SDS

NEODENE 14 Alpha Olefin

Version Revision Date: SDS Number: Date of last issue: 31.10.2024

3.5 17.02.2025 800001012232 Print Date 24.02.2025

SECTION 16: Other information

Full text of other abbreviations

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA -European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI -Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Training advice : Provide adequate information, instruction and training for op-

erators.

Other information : The eSDS(s) received to date have been reviewed for the

registered components in this mixture. The advice provided in the body of this SDS covers all necessary Risk Management

Measures.

For Industry guidance and tools on REACH please visit the

CEFIC website at http://cefic.org/Industry-support.

The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not consid-

ered to be PBT or vPvB.

A vertical bar (|) in the left margin indicates an amendment

According to EC No 1907/2006 as amended as at the date of this SDS

NEODENE 14 Alpha Olefin

Version Revision Date: SDS Number: Date of last issue: 31.10.2024

3.5 17.02.2025 800001012232 Print Date 24.02.2025

from the previous version.

This product is classified as H304 (May be fatal if swallowed and enters airways). The risk relates to potential for aspiration. The risk arising from aspiration hazard is solely related to the physico-chemical properties of the substance. The risk can therefore be controlled by implementing risk management measures tailored to this specific hazard and included within Section 8 of the SDS. An exposure scenario is not presented.

This product is classified as R66 / EUH066 (Repeated exposure may cause skin dryness or cracking). The risk relates to the potential for repeated or prolonged dermal contact. The risk arising from contact is solely related to the physicochemical properties of the substance. The risk can therefore be controlled by implementing risk management measures tailored to this specific hazard and included within Section 8 of the SDS. An exposure scenario is not presented.

Sources of key data used to compile the Safety Data Sheet

The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID date base, EC 1272 regulation, etc).

Classification of the mixture:

Classification procedure:

Asp. Tox. 1 H304 Expert judgement and weight of evidence determination.

Identified Uses according to the Use Descriptor System Uses - Worker

Title : - Industrial

Manufacture of substance Use as an intermediate Distribution of substance

Formulation & (re)packing of substances and mixtures Use in Oil and Gas field drilling and production operations

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CH / EN