

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR  
1910.1200

## C5/C7 Blend Stock

Version  
8.0

Revision Date:  
03/07/2025

SDS Number:  
800001008886

Print Date: 03/14/2025  
Date of last issue: 08/05/2022

---

### SECTION 1. IDENTIFICATION

Product name : C5/C7 Blend Stock

Product code : Q9242

#### Manufacturer or supplier's details

Company : **Shell Chemical LP**  
PO Box 576  
HOUSTON TX 77001  
USA  
SDS Request : 1-800-240-6737  
Customer Service : 1-855-697-4355

#### Emergency telephone number

Chemtrec Domestic (24 hr) : 1-800-424-9300  
Chemtrec International (24 hr) : 1-703-527-3887

#### Recommended use of the chemical and restrictions on use

Recommended use : Raw material for use in the chemical industry., Chemical intermediate.

Restrictions on use : This product must not be used in applications other than the above without first seeking the advice of the supplier.  
This product must not be used in applications other than those listed in Section 1 without first seeking the advice of the supplier.

---

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids : Category 1  
Skin irritation : Category 2  
Eye irritation : Category 2  
Germ cell mutagenicity : Category 1B  
Carcinogenicity : Category 1A

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR  
1910.1200

## C5/C7 Blend Stock

Version  
8.0

Revision Date:  
03/07/2025

SDS Number:  
800001008886

Print Date: 03/14/2025  
Date of last issue: 08/05/2022

Reproductive toxicity	: Category 2
Specific target organ toxicity - single exposure	: Category 3 (Narcotic effects)
Specific target organ toxicity - repeated exposure	: Category 1 (Blood, Blood-forming organs, Immune system)
Specific target organ toxicity - repeated exposure	: Category 2 (Central nervous system, Auditory system, Respiratory system, Visual system, Peripheral nervous system)
Aspiration hazard	: Category 1
Long-term (chronic) aquatic hazard	: Category 2

### GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : **PHYSICAL HAZARDS:**  
H224 Extremely flammable liquid and vapour.  
**HEALTH HAZARDS:**  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H340 May cause genetic defects.  
H350 May cause cancer.  
H361 Suspected of damaging fertility or the unborn child.  
H336 May cause drowsiness or dizziness.  
H372 Causes damage to organs through prolonged or repeated exposure.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H304 May be fatal if swallowed and enters airways.  
**ENVIRONMENTAL HAZARDS:**  
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**  
P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.  
P233 Keep container tightly closed.  
P240 Ground/bond container and receiving equipment.  
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.  
P242 Use only non-sparking tools.  
P243 Take precautionary measures against static discharge.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR  
1910.1200

## C5/C7 Blend Stock

Version  
8.0

Revision Date:  
03/07/2025

SDS Number:  
800001008886

Print Date: 03/14/2025  
Date of last issue: 08/05/2022

P264 Wash hands thoroughly after handling.  
P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.  
P270 Do not eat, drink or smoke when using this product.  
P273 Avoid release to the environment.

### Response:

P370+P378 In case of fire: Use appropriate media for extinction.  
P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.  
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.  
P332 + P313 If skin irritation occurs: Get medical advice/ attention.  
P362 Take off contaminated clothing and wash before reuse.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P337 + P313 If eye irritation persists: Get medical advice/ attention.  
P308 + P313 IF exposed or concerned: Get medical advice/ attention.  
P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.  
P331 Do NOT induce vomiting.  
P312 Call a POISON CENTER/ doctor if you feel unwell.

### Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
P235 Keep cool.  
P405 Store locked up.

### Disposal:

P501 Dispose of contents and container to appropriate waste site or reclaimer in accordance with local and national regulations.

### Other hazards which do not result in classification

In use, may form flammable/explosive vapour-air mixture.  
This material is a static accumulator.  
Even with proper grounding and bonding, this material can still accumulate an electrostatic charge.  
If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur.  
Slightly irritating to respiratory system.  
The classification of this material is based on OSHA HCS 2012 criteria.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR  
1910.1200

## C5/C7 Blend Stock

Version  
8.0

Revision Date:  
03/07/2025

SDS Number:  
800001008886

Print Date: 03/14/2025  
Date of last issue: 08/05/2022

### Hazardous components

Chemical name	Synonyms	CAS-No.	Concentration (% w/w)
distillates (petroleum), light arom.	Distillates (petroleum), light arom.	67891-80-9	50
naphtha (petroleum), light steam-cracked aromatic	Naphtha (petroleum), light steam-cracked arom.	68527-23-1	50

### Further information

Contains:

Chemical name	Identification number	Concentration (% w/w)
Toluene	108-88-3	$\geq 10$ - $\leq 20$
Benzene	71-43-2	$\geq 15$ - $\leq 25$

## SECTION 4. FIRST AID MEASURES

- General advice : Not expected to be a health hazard when used under normal conditions.
- If inhaled : Remove to fresh air. If rapid recovery does not occur, transport to nearest medical facility for additional treatment.
- In case of skin contact : Remove contaminated clothing. Immediately flush skin with large amounts of water for at least 15 minutes, and follow by washing with soap and water if available. If redness, swelling, pain and/or blisters occur, transport to the nearest medical facility for additional treatment.
- In case of eye contact : Immediately flush eye(s) with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Transport to the nearest medical facility for additional treatment.
- If swallowed : In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.
- Most important symptoms and effects, both acute and delayed : Breathing of high vapour concentrations may cause central nervous system (CNS) depression resulting in dizziness, light-headedness, headache, nausea and loss of coordination. Continued inhalation may result in unconsciousness and death. Skin irritation signs and symptoms may include a burning sensation, redness, swelling, and/or blisters. Eye irritation signs and symptoms may include a burning sensation, redness, swelling, and/or blurred vision. No specific hazards under normal use conditions. Ingestion may result in nausea, vomiting and/or diarrhoea. Damage to blood-forming organs may be evidenced by: a)

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## C5/C7 Blend Stock

Version  
8.0

Revision Date:  
03/07/2025

SDS Number:  
800001008886

Print Date: 03/14/2025  
Date of last issue: 08/05/2022

fatigue and anaemia (RBC), b) decreased resistance to infection, and/or excessive bruising and bleeding (platelet effect). Immunotoxicity may be evidenced by decreased resistance to infection.

Peripheral nerve damage may be evidenced by impairment of motor function (incoordination, unsteady walk, or muscle weakness in the extremities, and/or loss of sensation in the arms and legs).

Auditory system effects may include temporary hearing loss and/or ringing in the ears.

Visual system disturbances may be evidenced by decreases in the ability to discriminate between colours.

Protection of first-aiders : When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.

Indication of any immediate medical attention and special treatment needed : IMMEDIATE TREATMENT IS EXTREMELY IMPORTANT!  
Call a doctor or poison control center for guidance.  
Treat symptomatically.  
Potential for cardiac sensitisation, particularly in abuse situations. Hypoxia or negative inotropes may enhance these effects. Consider: oxygen therapy.  
Consider: oxygen therapy.

### SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

Unsuitable extinguishing media : Do not use water in a jet.

Specific hazards during fire-fighting : Clear fire area of all non-emergency personnel.  
Hazardous combustion products may include:  
A complex mixture of airborne solid and liquid particulates and gases (smoke).  
Carbon monoxide.  
Unidentified organic and inorganic compounds.  
Flammable vapours may be present even at temperatures below the flash point.  
The vapour is heavier than air, spreads along the ground and distant ignition is possible.  
Will float and can be reignited on surface water.

Specific extinguishing methods : Standard procedure for chemical fires.

Further information : Keep adjacent containers cool by spraying with water.

Special protective equipment for firefighters : Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## C5/C7 Blend Stock

Version  
8.0

Revision Date:  
03/07/2025

SDS Number:  
800001008886

Print Date: 03/14/2025  
Date of last issue: 08/05/2022

Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Observe all relevant local and international regulations. Notify authorities if any exposure to the general public or the environment occurs or is likely to occur. Local authorities should be advised if significant spillages cannot be contained. Avoid contact with skin, eyes and clothing. Isolate hazard area and deny entry to unnecessary or unprotected personnel. Do not breathe fumes, vapour. Do not operate electrical equipment.
- Environmental precautions : Shut off leaks, if possible without personal risks. Remove all possible sources of ignition in the surrounding area. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. Attempt to disperse the vapour or to direct its flow to a safe location for example by using fog sprays. Take precautionary measures against static discharge. Ensure electrical continuity by bonding and grounding (earthing) all equipment. Monitor area with combustible gas indicator.
- Methods and materials for containment and cleaning up : For small liquid spills (< 1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely. For large liquid spills (> 1 drum), transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely. Ventilate contaminated area thoroughly. If contamination of site occurs remediation may require specialist advice.
- Additional advice : For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet. For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet. U.S. regulations may require reporting releases of this material to the environment which exceed the reportable quantity

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## C5/C7 Blend Stock

Version  
8.0

Revision Date:  
03/07/2025

SDS Number:  
800001008886

Print Date: 03/14/2025  
Date of last issue: 08/05/2022

(refer to Section 15) to the National Response Center at (800) 424-8802.

Under Section 311 of the Clean Water Act (CWA) this material is considered an oil. As such, spills into surface waters must be reported to the National Response Center at (800) 424-8802.

This material is covered by EPA's Comprehensive Environmental Response, Compensation and Liability Act (CERCLA) Petroleum Exclusion. Therefore, releases to the environment may not be reportable under CERCLA.

### SECTION 7. HANDLING AND STORAGE

- Technical measures : Avoid breathing of or direct contact with material. Only use in well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet.  
Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.  
Ensure that all local regulations regarding handling and storage facilities are followed.
- Advice on safe handling : Avoid inhaling vapour and/or mists.  
Avoid contact with skin, eyes and clothing.  
Extinguish any naked flames. Do not smoke. Remove ignition sources. Avoid sparks.  
Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols.  
Bulk storage tanks should be diked (bunded).  
When using do not eat or drink.  
  
The vapour is heavier than air, spreads along the ground and distant ignition is possible.
- Avoidance of contact : Strong oxidising agents.
- Product Transfer : Even with proper grounding and bonding, this material can still accumulate an electrostatic charge. If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur. Be aware of handling operations that may give rise to additional hazards that result from the accumulation of static charges. These include but are not limited to pumping (especially turbulent flow), mixing, filtering, splash filling, cleaning and filling of tanks and containers, sampling, switch loading, gauging, vacuum truck operations, and mechanical movements. These activities may lead to static discharge e.g. spark formation. Restrict line velocity during pumping in order to avoid generation of electrostatic discharge ( $\leq 1$  m/s until fill pipe submerged to twice its diameter, then  $\leq 7$  m/s). Avoid splash filling. Do NOT use compressed air for filling, discharging, or handling operations.

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR  
1910.1200

## C5/C7 Blend Stock

Version  
8.0

Revision Date:  
03/07/2025

SDS Number:  
800001008886

Print Date: 03/14/2025  
Date of last issue: 08/05/2022

Refer to guidance under Handling section.

Conditions for safe storage : Refer to section 15 for any additional specific legislation covering the packaging and storage of this product.

Further information on storage stability : Storage Temperature:  
Ambient.

Bulk storage tanks should be diked (bunded).  
Locate tanks away from heat and other sources of ignition.  
Cleaning, inspection and maintenance of storage tanks is a specialist operation, which requires the implementation of strict procedures and precautions.  
Must be stored in a diked (bunded) well-ventilated area, away from sunlight, ignition sources and other sources of heat.  
Keep away from aerosols, flammables, oxidizing agents, corrosives and from other flammable products which are not harmful or toxic to man or to the environment.  
Electrostatic charges will be generated during pumping.  
Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment to reduce the risk.  
The vapours in the head space of the storage vessel may lie in the flammable/explosive range and hence may be flammable.

Packaging material : Suitable material: For containers, or container linings use mild steel, stainless steel., For container paints, use epoxy paint, zinc silicate paint.  
Unsuitable material: Avoid prolonged contact with natural, butyl or nitrile rubbers.

Container Advice : Do not cut, drill, grind, weld or perform similar operations on or near containers.

Specific use(s) : Not applicable

See additional references that provide safe handling practices for liquids that are determined to be static accumulators:  
American Petroleum Institute 2003 (Protection Against Ignitions Arising out of Static, Lightning and Stray Currents) or  
National Fire Protection Agency 77 (Recommended Practices on Static Electricity).  
IEC/TS 60079-32-1: Electrostatic hazards, guidance

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
------------	---------	----------------------------------	--	-------



# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## C5/C7 Blend Stock

Version  
8.0

Revision Date:  
03/07/2025

SDS Number:  
800001008886

Print Date: 03/14/2025  
Date of last issue: 08/05/2022

distillates (petroleum), light arom.	67891-80-9	TWA	500 ppm 2,000 mg/m3	OSHA Z-1
naphtha (petroleum), light steam-cracked aromatic	68527-23-1	TWA	500 ppm 2,000 mg/m3	OSHA Z-1
Benzene	71-43-2	TWA	0.25 ppm 0.8 mg/m3	Shell Internal Standard (SIS) for 8-12 hour TWA.
Benzene		STEL	2.5 ppm 8 mg/m3	Shell Internal Standard (SIS) for 15 min (STEL)
<b>Benzene</b>		<b>TWA</b>	<b>0.02 ppm</b>	<b>ACGIH</b>
Benzene		STEL	2.5 ppm	ACGIH
Benzene		PEL	1 ppm	OSHA CARC
Benzene		STEL	5 ppm	OSHA CARC
Benzene		TWA	10 ppm	OSHA Z-2
Benzene		CEIL	25 ppm	OSHA Z-2
Benzene		Peak	50 ppm (10 minutes)	OSHA Z-2
Toluene	108-88-3	TWA	20 ppm	ACGIH
Toluene		TWA	200 ppm	OSHA Z-2
Toluene		CEIL	300 ppm	OSHA Z-2
Toluene		Peak	500 ppm (10 minutes)	OSHA Z-2

### Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sam-pling time	Permissible concentra-tion	Basis
Toluene	108-88-3	Toluene	In blood	Prior to last shift of work-week	0.02 mg/l	ACGIH BEI
		Toluene	Urine	End of shift (As soon as possible after exposure ceases)	0.03 mg/l	ACGIH BEI
		o-Cresol	Urine	End of shift (As soon as possible after exposure ceases)	0.3 mg/g creatinine	ACGIH BEI
Benzene	71-43-2	S-Phenylmercapturic acid	Urine	End of shift (As soon as possible after exposure	25 µg/g creatinine	ACGIH BEI

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## C5/C7 Blend Stock

Version  
8.0

Revision Date:  
03/07/2025

SDS Number:  
800001008886

Print Date: 03/14/2025  
Date of last issue: 08/05/2022

		t,t-Muconic acid	Urine	End of shift (As soon as possible after exposure ceases)	500 µg/g creatinine	ACGIH BEI
--	--	------------------	-------	--	---------------------	-----------

### Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods <http://www.cdc.gov/niosh/>

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods <http://www.osha.gov/>

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances <http://www.hse.gov.uk/>

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA) , Germany <http://www.dguv.de/inhalt/index.jsp>

L'Institut National de Recherche et de Sécurité, (INRS), France <http://www.inrs.fr/accueil>

### Engineering measures

- : Use sealed systems as far as possible.
- Adequate explosion-proof ventilation to control airborne concentrations below the exposure guidelines/limits.
- Local exhaust ventilation is recommended.
- Firewater monitors and deluge systems are recommended.
- Eye washes and showers for emergency use.
- Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.
- The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances.
- Appropriate measures include:

#### General Information

Consider technical advances and process upgrades (including automation) for the elimination of releases. Minimise exposure using measures such as closed systems, dedicated facilities and suitable general/local exhaust ventilation. Drain down systems and clear transfer lines prior to breaking containment. Clean/flush equipment, where possible, prior to maintenance. Where there is potential for exposure: restrict access to authorised persons; provide specific activity training to operators to minimise exposures; wear suitable gloves and coveralls to prevent skin contamination; wear respiratory protection when there is potential for inhalation; clear up spills immediately and dispose of wastes safely. Ensure safe

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## C5/C7 Blend Stock

Version  
8.0

Revision Date:  
03/07/2025

SDS Number:  
800001008886

Print Date: 03/14/2025  
Date of last issue: 08/05/2022

systems of work or equivalent arrangements are in place to manage risks. Regularly inspect, test and maintain all control measures. Consider the need for risk based health surveillance.

### Personal protective equipment

Respiratory protection

: If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are unsuitable (e.g. airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. If air-filtering respirators are suitable for conditions of use: Select a filter suitable for organic gases and vapours [Type A boiling point >65°C (149°F)].

Respirator selection, use and maintenance should be in accordance with the requirements of the OSHA Respiratory Protection Standard, 29 CFR 1910.134.

Hand protection  
Remarks

: Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. Longer term protection: Viton. Incidental contact/Splash protection: Nitrile rubber. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

Eye protection

: Wear goggles for use against liquids and gas.

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## C5/C7 Blend Stock

Version  
8.0

Revision Date:  
03/07/2025

SDS Number:  
800001008886

Print Date: 03/14/2025  
Date of last issue: 08/05/2022

---

	Wear full face shield if splashes are likely to occur.
Skin and body protection	: Wear chemical resistant gloves/gauntlets and boots. Where risk of splashing, also wear an apron. Wear antistatic and flame-retardant clothing, if a local risk assessment deems it so.
Protective measures	: Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.
Thermal hazards	: When handling heated product, wear heat resistant gloves, safety hat with chin strap, face shield (preferably with a chin guard), safety glasses, heat resistant coveralls (with cuffs over gloves and legs over boots), neck protection and heavy duty boots, e.g. leather for heat resistance.
Hygiene measures	: Wash hands before eating, drinking, smoking and using the toilet. Launder contaminated clothing before re-use. Do not ingest. If swallowed, then seek immediate medical assistance.

### Environmental exposure controls

General advice	: Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour. Minimise release to the environment. An environmental assessment must be made to ensure compliance with local environmental legislation. Information on accidental release measures are to be found in section 6.
----------------	--

---

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: Liquid.
Colour	: amber
Odour	: Aromatic hydrocarbon
Odour Threshold	: Data not available
pH	: Data not available
Melting point/freezing point	: Data not available
Boiling point/boiling range	: Typical 30 - 200 °C / 86 - 392 °F
Flash point	: -7 °C / 19 °F
Evaporation rate	: Data not available

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## C5/C7 Blend Stock

Version  
8.0

Revision Date:  
03/07/2025

SDS Number:  
800001008886

Print Date: 03/14/2025  
Date of last issue: 08/05/2022

---

Flammability	
Flammability (liquids)	: Static-accumulating flammable liquid.
Lower explosion limit and upper explosion limit / flammability limit	
Upper explosion limit / Upper flammability limit	: No data available
Lower explosion limit / Lower flammability limit	: 0.12 %(V)
Vapour pressure	: Data not available (50 °C / 122 °F)
Relative vapour density	: > 1
Relative density	: < 1 Method: ASTM D4052
Density	: Data not available
Solubility(ies)	
Water solubility	: 0.05 g/l negligible
Partition coefficient: n-octanol/water	: Data not available
Auto-ignition temperature	: Data not available
Decomposition temperature	: Data not available
Viscosity	
Viscosity, dynamic	: Data not available
Viscosity, kinematic	: Data not available
Explosive properties	: Not applicable
Oxidizing properties	: Data not available
Surface tension	: Data not available
Conductivity	: Low conductivity: < 100 pS/m, The conductivity of this material makes it a static accumulator., A liquid is typically considered nonconductive if its conductivity is below 100 pS/m and is considered semi-conductive if its conductivity is below 10,000 pS/m., Whether a liquid is nonconductive or semiconductive, the precautions are the same., A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid
Molecular weight	: Data not available
Particle size	: Data not available

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR  
1910.1200

## C5/C7 Blend Stock

Version  
8.0

Revision Date:  
03/07/2025

SDS Number:  
800001008886

Print Date: 03/14/2025  
Date of last issue: 08/05/2022

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.
Chemical stability	:	No hazardous reaction is expected when handled and stored according to provisions Stable under normal conditions of use.
Possibility of hazardous reactions	:	Reacts with strong oxidising agents.
Conditions to avoid	:	Avoid heat, sparks, open flames and other ignition sources.  In certain circumstances product can ignite due to static electricity.
Incompatible materials	:	Strong oxidising agents.
Hazardous decomposition products	:	Hazardous decomposition products are not expected to form during normal storage. Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids and gases including carbon monoxide, carbon dioxide, sulphur oxides and unidentified organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation.

---

### SECTION 11. TOXICOLOGICAL INFORMATION

Basis for assessment	:	Information given is based on data from components. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).
----------------------	---	---

#### Information on likely routes of exposure

Exposure may occur via inhalation, ingestion, skin absorption, skin or eye contact, and accidental ingestion.

#### Acute toxicity

##### Product:

Acute oral toxicity	:	LD50 : > 5,000 mg/kg Remarks: Low toxicity Based on available data, the classification criteria are not met.
Acute inhalation toxicity	:	Remarks: Low toxicity if inhaled. Based on available data, the classification criteria are not met.
Acute dermal toxicity	:	LD50 : > 5,000 mg/kg Remarks: Low toxicity Based on available data, the classification criteria are not met.

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR  
1910.1200

## C5/C7 Blend Stock

Version  
8.0

Revision Date:  
03/07/2025

SDS Number:  
800001008886

Print Date: 03/14/2025  
Date of last issue: 08/05/2022

### Components:

#### **distillates (petroleum), light arom.:**

Acute oral toxicity : LD 50 (Rat, male and female): >300 <=2000 mg/kg  
Method: Test(s) equivalent or similar to OECD Test Guideline 401  
Remarks: Harmful if swallowed.

Acute inhalation toxicity : LC 50 (Rat, male and female): > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Test(s) equivalent or similar to OECD Test Guideline 403  
Remarks: Based on available data, the classification criteria are not met.

Acute dermal toxicity : LD 50 (Rabbit, male): 1,183 mg/kg  
Method: Literature data  
Remarks: Harmful in contact with skin.

#### **naphtha (petroleum), light steam-cracked aromatic:**

Acute oral toxicity : LD 50 (Rat, male and female): > 5,000 mg/kg  
Method: Other guideline method.  
Remarks: Based on available data, the classification criteria are not met.

Acute inhalation toxicity : LC 50 (Rat, male and female): > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Test(s) equivalent or similar to OECD Test Guideline 403  
Remarks: Based on available data, the classification criteria are not met.

Acute dermal toxicity : LD 50 (Rabbit, male and female): > 2,000 mg/kg  
Method: Other guideline method.  
Remarks: Based on available data, the classification criteria are not met.

### **Skin corrosion/irritation**

#### Product:

Remarks: Causes skin irritation.

### Components:

#### **distillates (petroleum), light arom.:**

Species: Rabbit  
Method: OECD Test Guideline 404  
Remarks: Causes skin irritation.

#### **naphtha (petroleum), light steam-cracked aromatic:**

Species: Rabbit  
Method: OECD Test Guideline 404

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR  
1910.1200

## C5/C7 Blend Stock

Version  
8.0

Revision Date:  
03/07/2025

SDS Number:  
800001008886

Print Date: 03/14/2025  
Date of last issue: 08/05/2022

Remarks: Causes skin irritation.

### Serious eye damage/eye irritation

#### Product:

Remarks: Causes serious eye irritation.

#### Components:

##### **distillates (petroleum), light arom.:**

Species: Rabbit

Method: Literature data

Remarks: Causes serious eye irritation.

##### **naphtha (petroleum), light steam-cracked aromatic:**

Species: Rabbit

Method: Other guideline method.

Remarks: Based on available data, the classification criteria are not met.

### Respiratory or skin sensitisation

#### Product:

Remarks: Not a skin sensitiser.

Based on available data, the classification criteria are not met.

#### Components:

##### **distillates (petroleum), light arom.:**

Species: Guinea pig

Method: Test(s) equivalent or similar to OECD Test Guideline 406

Remarks: Based on available data, the classification criteria are not met.

##### **naphtha (petroleum), light steam-cracked aromatic:**

Species: Guinea pig

Method: Other guideline method.

Remarks: Based on available data, the classification criteria are not met.

### Germ cell mutagenicity

#### Product:

Genotoxicity in vivo

: Remarks: Contains Benzene, CAS # 71-43-2., May cause heritable genetic damage

#### Components:

##### **distillates (petroleum), light arom.:**

Genotoxicity in vitro

: Method: Test(s) equivalent or similar to OECD Test Guideline 473

Remarks: Suspected of causing genetic defects., Mutagenic; positive in in-vivo and in-vitro assays.

: Method: Literature data

Remarks: Suspected of causing genetic defects., Mutagenic;



# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR  
1910.1200

## C5/C7 Blend Stock

Version  
8.0

Revision Date:  
03/07/2025

SDS Number:  
800001008886

Print Date: 03/14/2025  
Date of last issue: 08/05/2022

positive in in-vivo and in-vitro assays.

### Genotoxicity in vivo

: Test species: Mouse  
Method: OECD Test Guideline 474  
Remarks: Suspected of causing genetic defects., Mutagenic;  
positive in in-vivo assays.

Test species: Mouse  
Method: Test(s) equivalent or similar to OECD Test guideline  
478  
Remarks: Suspected of causing genetic defects., Mutagenic;  
positive in in-vivo assays.

### Germ cell mutagenicity- Assessment

: This product does not meet the criteria for classification in  
categories 1A/1B.

### **naphtha (petroleum), light steam-cracked aromatic:**

Genotoxicity in vitro : Method: Test(s) equivalent or similar to OECD Guideline 471  
Remarks: May cause genetic defects.

: Method: Test(s) equivalent or similar to OECD Test Guideline  
473  
Remarks: May cause genetic defects.

### Genotoxicity in vivo

: Test species: Mouse  
Method: OECD Test Guideline 474  
Remarks: May cause heritable genetic damage

### Germ cell mutagenicity- Assessment

: May cause genetic defects.

## Carcinogenicity

### **Product:**

Remarks: Contains Benzene, CAS # 71-43-2., Known human carcinogen., May cause leukaemia  
(AML - acute myelogenous leukaemia).

### **Components:**

#### **distillates (petroleum), light arom.:**

Species: Mouse, (male and female)

Application Route: Inhalation

Method: Other guideline method.

Remarks: May cause cancer., IARC Group 2B: Possibly carcinogenic to humans.

Species: Rat, (male and female)

Application Route: Inhalation

Method: Test(s) equivalent or similar to OECD Test Guideline 453

Remarks: May cause cancer., IARC Group 2B: Possibly carcinogenic to humans.

### Carcinogenicity - Assessment

: May cause cancer.

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## C5/C7 Blend Stock

Version  
8.0

Revision Date:  
03/07/2025

SDS Number:  
800001008886

Print Date: 03/14/2025  
Date of last issue: 08/05/2022

### naphtha (petroleum), light steam-cracked aromatic:

Species: Rat, (male and female)

Application Route: Oral

Method: Other guideline method.

Remarks: May cause cancer., Known human carcinogen., Contains benzene., Causes leukaemia (AML - acute myelogenous leukaemia).

Species: Rat, (male and female)

Application Route: Inhalation

Method: Test(s) equivalent or similar to OECD Test Guideline 453

Remarks: May cause cancer., Known human carcinogen., Contains benzene., Causes leukaemia (AML - acute myelogenous leukaemia).

Carcinogenicity - Assessment : May cause cancer.

### IARC

Group 1: Carcinogenic to humans

Benzene

71-43-2

Group 2B: Possibly carcinogenic to humans

distillates (petroleum), light arom.

67891-80-9

naphtha (petroleum), light steam-cracked aromatic

68527-23-1

### OSHA

OSHA specifically regulated carcinogen

Benzene

71-43-2

### NTP

Known to be human carcinogen

Benzene

71-43-2

### Reproductive toxicity

#### Product:

Effects on fertility

:

Remarks: Suspected of damaging fertility or the unborn child., Contains n-Hexane, CAS # 110-54-3., Affects reproductive system in animals at doses which produce other toxic effects., Contains Toluene, CAS # 108-88-3., Causes foetotoxicity in animals at doses which are maternally toxic.

#### Components:

distillates (petroleum), light arom.:

Effects on fertility

:

Species: Rat

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## C5/C7 Blend Stock

Version  
8.0

Revision Date:  
03/07/2025

SDS Number:  
800001008886

Print Date: 03/14/2025  
Date of last issue: 08/05/2022

Sex: male and female  
Application Route: Inhalation

Method: OECD Test Guideline 422  
Remarks: Based on available data, the classification criteria are not met.

Effects on foetal development : Species: Rat, male and female  
Application Route: Inhalation  
Method: OECD Test Guideline 422  
Remarks: Based on available data, the classification criteria are not met.

Reproductive toxicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

**naphtha (petroleum), light steam-cracked aromatic:**  
Effects on fertility :

Remarks: Suspected of damaging fertility or the unborn child.

Effects on foetal development : Species: Rat, female  
Application Route: Inhalation  
Method: Acceptable non-standard method.  
Remarks: Suspected of damaging fertility or the unborn child.

Reproductive toxicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

### STOT - single exposure

#### **Product:**

Exposure routes: Inhalation

Target Organs: Narcotic effects.

Remarks: May cause drowsiness and dizziness., Inhalation of vapours or mists may cause irritation to the respiratory system.

#### **Components:**

**distillates (petroleum), light arom.:**

Exposure routes: Inhalation

Target Organs: Central nervous system, Respiratory Tract

Remarks: Inhalation of vapours or mists may cause irritation to the respiratory system., May cause drowsiness or dizziness., May cause respiratory irritation., High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea.

**naphtha (petroleum), light steam-cracked aromatic:**

Exposure routes: Inhalation

Target Organs: Central nervous system

Remarks: May cause drowsiness or dizziness., Inhalation of vapours or mists may cause irritation to the respiratory system., Vapours may cause drowsiness and dizziness.

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR  
1910.1200

## C5/C7 Blend Stock

Version  
8.0

Revision Date:  
03/07/2025

SDS Number:  
800001008886

Print Date: 03/14/2025  
Date of last issue: 08/05/2022

---

### STOT - repeated exposure

#### Product:

Target Organs: Blood, Blood-forming organs, Immune system

Assessment: Causes damage to organs through prolonged or repeated exposure.

Remarks: Contains Benzene, CAS # 71-43-2., Blood: may cause haemolysis of red blood cells and/or anaemia., Blood-forming organs: repeated exposure affects the bone marrow., Immune System: animal studies on this material or its components have demonstrated immunotoxicity.

Target Organs: Central nervous system, Peripheral nervous system, Respiratory system, Visual system, Auditory system

Assessment: May cause damage to organs through prolonged or repeated exposure.

Remarks: Contains Toluene, CAS # 108-88-3., Central nervous system: repeated exposure affects the nervous system., Effects were seen at high doses only., Auditory system: prolonged and repeated exposures to high concentrations have resulted in hearing loss in rats. Solvent abuse and noise interaction in the work environment may cause hearing loss., Not applicable, Respiratory system: repeated exposure affects the respiratory system. Effects were seen at high doses only., Contains n-Hexane, CAS # 110-54-3., Peripheral nervous system: repeated exposure causes peripheral neuropathy in animals., Visual system: may cause decreased color perception. , These subtle changes have not been found to lead to functional colour vision deficits.

#### Components:

##### **distillates (petroleum), light arom.:**

Remarks: Based on available data, the classification criteria are not met.

##### **naphtha (petroleum), light steam-cracked aromatic:**

Exposure routes: Oral

Target Organs: Blood, Blood-forming organs, Peripheral nervous system, Auditory system, Immune system, Respiratory system, Visual system, Central nervous system

Remarks: May cause damage to organs or organ systems through prolonged or repeated exposure.

### Repeated dose toxicity

#### Components:

##### **distillates (petroleum), light arom.:**

Species: Rat, male and female

Application Route: Oral

Method: Test(s) equivalent or similar to OECD Test Guideline 422

Target Organs: No specific target organs noted

Species: Rat, male and female

Application Route: Inhalation

Test atmosphere: vapour

Method: Test(s) equivalent or similar to OECD Test Guideline 422

Target Organs: No specific target organs noted

##### **naphtha (petroleum), light steam-cracked aromatic:**

Species: Rat, male and female

Application Route: Oral

Method: Test(s) equivalent or similar to OECD Test Guideline 408

Target Organs: hematopoietic system

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR  
1910.1200

## C5/C7 Blend Stock

Version  
8.0

Revision Date:  
03/07/2025

SDS Number:  
800001008886

Print Date: 03/14/2025  
Date of last issue: 08/05/2022

Species: Rat, male and female  
Application Route: Inhalation  
Test atmosphere: vapour  
Method: Test(s) equivalent or similar to OECD Test Guideline 413  
Target Organs: No specific target organs noted

Species: Rabbit, female  
Application Route: Dermal  
Method: Test(s) equivalent or similar to OECD Test Guideline 410  
Target Organs: No specific target organs noted

### Aspiration toxicity

#### Product:

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

#### Components:

##### **distillates (petroleum), light arom.:**

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

##### **naphtha (petroleum), light steam-cracked aromatic:**

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

### Further information

#### Product:

Remarks: Exposure to very high concentrations of similar materials has been associated with irregular heart rhythms and cardiac arrest.

Remarks: Myelodysplastic syndrome (MDS) was observed in individuals exposed to very high levels (50 ppm to 300 ppm range) of benzene over a long period of time in the workplace. The relevance of these results to lower levels of exposure is not known.

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

#### Components:

##### **distillates (petroleum), light arom.:**

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

##### **naphtha (petroleum), light steam-cracked aromatic:**

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

---

## SECTION 12. ECOLOGICAL INFORMATION

Basis for assessment : Incomplete ecotoxicological data are available for this product.  
The information given below is based partly on a knowledge of the components and the ecotoxicology of similar products.

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR  
1910.1200

## C5/C7 Blend Stock

Version  
8.0

Revision Date:  
03/07/2025

SDS Number:  
800001008886

Print Date: 03/14/2025  
Date of last issue: 08/05/2022

Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

### Ecotoxicity

#### Product:

- Toxicity to fish (Acute toxicity) : LL50: > 1 - 10 mg/l  
Remarks: Toxic
- Toxicity to daphnia and other aquatic invertebrates (Acute toxicity) : EL50: > 1 - 10 mg/l  
Remarks: Toxic
- Toxicity to algae (Acute toxicity) : EL50: > 1 - 10 mg/l  
Remarks: Toxic
- Toxicity to fish (Chronic toxicity) : Remarks: Data not available
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : Remarks: Data not available
- Toxicity to microorganisms (Acute toxicity) : Remarks: LL/EL/IL50 >10 <= 100 mg/l  
Harmful

#### Components:

##### **distillates (petroleum), light arom.:**

- Toxicity to fish (Acute toxicity) : LL50 (Oncorhynchus mykiss (rainbow trout)): 14.1 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203  
Remarks: Harmful  
LL/EL/IL50 >10 <= 100 mg/l
- Toxicity to daphnia and other aquatic invertebrates (Acute toxicity) : EC50 (Daphnia magna (Water flea)): 4.7 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202  
Remarks: Toxic  
LL/EL/IL50 > 1 <= 10 mg/l
- Toxicity to algae (Acute toxicity) : EC50 (Pseudokirchneriella subcapitata (algae)): 12.4 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
Remarks: Harmful  
LL/EL/IL50 >10 <= 100 mg/l
- Toxicity to fish (Chronic toxicity) : Remarks: Data not available
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : Remarks: Data not available

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR  
1910.1200

## C5/C7 Blend Stock

Version  
8.0

Revision Date:  
03/07/2025

SDS Number:  
800001008886

Print Date: 03/14/2025  
Date of last issue: 08/05/2022

Toxicity to microorganisms (Acute toxicity) : NOELR (Activated sludge, domestic waste): 2 mg/l  
Exposure time: 5 h  
Method: OECD Test Guideline 301D  
Remarks: Data not available

### **naphtha (petroleum), light steam-cracked aromatic:**

Toxicity to fish (Acute toxicity) : LC50 (Oncorhynchus mykiss (rainbow trout)): 1 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203  
Remarks: Toxic  
LL/EL/IL50 > 1 <= 10 mg/l

Toxicity to daphnia and other aquatic invertebrates (Acute toxicity) : EC50 (Daphnia magna (Water flea)): 1.2 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202  
Remarks: Toxic  
LL/EL/IL50 > 1 <= 10 mg/l

Toxicity to algae (Acute toxicity) : EC50 (Pseudokirchneriella subcapitata (algae)): 1.3 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 201  
Remarks: Toxic  
LL/EL/IL50 > 1 <= 10 mg/l

Toxicity to fish (Chronic toxicity) : Remarks: Data not available

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : Remarks: Data not available

Toxicity to microorganisms (Acute toxicity) : LL50 (Tetrahymena pyriformis): 76.7 mg/l  
Exposure time: 72 h  
Method: Based on quantitative structure-activity relationship (QSAR) modelling  
Remarks: Harmful  
LL/EL/IL50 > 1 <= 10 mg/l

### **Persistence and degradability**

#### **Product:**

Biodegradability : Remarks: Not readily biodegradable.

Remarks: Oxidises rapidly by photo-chemical reactions in air.

#### **Components:**

##### **distillates (petroleum), light arom.:**

Biodegradability : Biodegradation: 9 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301D  
Remarks: Not readily biodegradable.

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR  
1910.1200

## C5/C7 Blend Stock

Version  
8.0

Revision Date:  
03/07/2025

SDS Number:  
800001008886

Print Date: 03/14/2025  
Date of last issue: 08/05/2022

---

### **naphtha (petroleum), light steam-cracked aromatic:**

Biodegradability : Biodegradation: 7.3 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F  
Remarks: Not readily biodegradable.  
Oxidises rapidly by photo-chemical reactions in air.

### **Bioaccumulative potential**

#### **Product:**

Bioaccumulation : Remarks: Contains components with the potential to bioaccumulate.

#### **Components:**

##### **distillates (petroleum), light arom.:**

Bioaccumulation : Species: Pimephales promelas (fathead minnow)  
Bioconcentration factor (BCF): 1.2 - 2.1  
Method: Based on quantitative structure-activity relationship (QSAR) modelling  
Remarks: Does not bioaccumulate significantly.

##### **naphtha (petroleum), light steam-cracked aromatic:**

Bioaccumulation : Species: Pimephales promelas (fathead minnow)  
Bioconcentration factor (BCF): 0.73 - 4.15  
Method: Based on quantitative structure-activity relationship (QSAR) modelling  
Remarks: Contains components with the potential to bioaccumulate.

### **Mobility in soil**

#### **Product:**

Mobility : Remarks: Floats on water.

Remarks: If product enters soil, one or more constituents will be mobile and may contaminate groundwater.

#### **Components:**

##### **distillates (petroleum), light arom.:**

Mobility : Remarks: Floats on water.

##### **naphtha (petroleum), light steam-cracked aromatic:**

Mobility : Remarks: Floats on water.  
If product enters soil, one or more constituents will be highly mobile and may contaminate groundwater.



# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## C5/C7 Blend Stock

Version  
8.0

Revision Date:  
03/07/2025

SDS Number:  
800001008886

Print Date: 03/14/2025  
Date of last issue: 08/05/2022

### Other adverse effects

#### Product:

Additional ecological information : In view of the high rate of loss from solution, the product is unlikely to pose a significant hazard to aquatic life.

#### Components:

##### **distillates (petroleum), light arom.:**

Results of PBT and vPvB assessment : The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB.

##### **naphtha (petroleum), light steam-cracked aromatic:**

Results of PBT and vPvB assessment : The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB.

## SECTION 13. DISPOSAL CONSIDERATIONS

### **Disposal methods**

- Waste from residues : Recover or recycle if possible.  
It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.  
Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment.  
Do not dispose into the environment, in drains or in water courses.  
Do not dispose of tank water bottoms by allowing them to drain into the ground. This will result in soil and groundwater contamination.  
Waste arising from a spillage or tank cleaning should be disposed of in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand.
- Waste, spills or used product is dangerous waste.
- Disposal should be in accordance with applicable regional, national, and local laws and regulations.  
Local regulations may be more stringent than regional or national requirements and must be complied with.
- MARPOL - see International Convention for the Prevention of Pollution from Ships (MARPOL 73/78) which provides technical aspects at controlling pollutions from ships.
- Contaminated packaging : Drain container thoroughly.  
After draining, vent in a safe place away from sparks and fire.  
Residues may cause an explosion hazard. Do not puncture,

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## C5/C7 Blend Stock

Version  
8.0

Revision Date:  
03/07/2025

SDS Number:  
800001008886

Print Date: 03/14/2025  
Date of last issue: 08/05/2022

cut or weld uncleaned drums.  
Send to drum recoverer or metal reclaimer.  
Comply with any local recovery or waste disposal regulations.

### SECTION 14. TRANSPORT INFORMATION

#### National Regulations

##### 49 CFR

UN/ID/NA number : UN 1268  
Proper shipping name : Petroleum distillates, n.o.s.  
Class : 3  
Packing group : I  
Labels : 3  
ERG Code : 128  
Marine pollutant : no

#### International Regulations

##### IATA-DGR

UN/ID No. : UN 1268  
Proper shipping name : Petroleum distillates, n.o.s.  
Class : 3  
Packing group : I  
Labels : 3

##### IMDG-Code

UN number : UN 1268  
Proper shipping name : PETROLEUM DISTILLATES, N.O.S.  
(Petroleum naphtha)  
Class : 3  
Packing group : I  
Labels : 3  
Marine pollutant : yes

#### Maritime transport in bulk according to IMO instruments

MARPOL Annex 1 rules apply for bulk shipments by sea.

#### Special precautions for user

Remarks : Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

### SECTION 15. REGULATORY INFORMATION

#### EPCRA - Emergency Planning and Community Right-to-Know Act

##### CERCLA Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
------------	---------	--------------	-----------------------

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## C5/C7 Blend Stock

Version  
8.0

Revision Date:  
03/07/2025

SDS Number:  
800001008886

Print Date: 03/14/2025  
Date of last issue: 08/05/2022

		(lbs)	(lbs)
<b>Benzene</b>	<b>71-43-2</b>	<b>10</b>	<b>40</b>
<b>Toluene</b>	<b>108-88-3</b>	<b>100</b>	<b>100 (F005)</b>
<b>Benzene</b>	<b>71-43-2</b>	<b>10</b>	<b>10 (D018)</b>

\*: The components with RQs are given for information., Shell classifies this material as an "oil" under the CERCLA Petroleum Exclusion, therefore releases to the environment are not reportable under CERCLA.

### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards** : Flammable (gases, aerosols, liquids, or solids)  
Skin corrosion or irritation  
Serious eye damage or eye irritation  
Aspiration hazard  
Germ cell mutagenicity  
Carcinogenicity  
Reproductive toxicity  
Specific target organ toxicity (single or repeated exposure)

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

Benzene	71-43-2	>= 20 - < 30 %
Toluene	108-88-3	>= 20 - < 30 %

### Clean Water Act

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3:

Toluene	108-88-3	20 %
Benzene	71-43-2	25 %

### US State Regulations

#### Pennsylvania Right To Know

distillates (petroleum), light arom.	67891-80-9
naphtha (petroleum), light steam-cracked aromatic	68527-23-1
Benzene	71-43-2
Toluene	108-88-3

#### California Prop. 65

WARNING: This product can expose you to chemicals including Benzene, which is/are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

#### California List of Hazardous Substances

Benzene	71-43-2
Toluene	108-88-3

#### California Regulated Carcinogens

Benzene	71-43-2
---------	---------

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## C5/C7 Blend Stock

Version  
8.0

Revision Date:  
03/07/2025

SDS Number:  
800001008886

Print Date: 03/14/2025  
Date of last issue: 08/05/2022

### Other regulations:

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

## SECTION 16. OTHER INFORMATION

### Further information

NFPA Rating (Health, Fire, Reactivity) 2, 4, 0

### Full text of other abbreviations

ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	: ACGIH - Biological Exposure Indices (BEI)
OSHA CARC	: OSHA Specifically Regulated Chemicals/Carcinogens
OSHA Z-1	: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-2	: USA. Occupational Exposure Limits (OSHA) - Table Z-2
ACGIH / TWA	: 8-hour, time-weighted average
ACGIH / STEL	: Short-term exposure limit
OSHA CARC / PEL	: Permissible exposure limit (PEL)
OSHA CARC / STEL	: Excursion limit
OSHA Z-1 / TWA	: 8-hour time weighted average
OSHA Z-2 / TWA	: 8-hour time weighted average
OSHA Z-2 / CEIL	: Acceptable ceiling concentration
OSHA Z-2 / Peak	: Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift
Abbreviations and Acronyms	: The standard abbreviations and acronyms used in this document can be looked up in reference literature (e.g. scientific dictionaries) and/or websites.

ACGIH = American Conference of Governmental Industrial Hygienists  
ADR = European Agreement concerning the International Carriage of Dangerous Goods by Road  
AICS = Australian Inventory of Chemical Substances  
ASTM = American Society for Testing and Materials  
BEL = Biological exposure limits  
BTEX = Benzene, Toluene, Ethylbenzene, Xylenes  
CAS = Chemical Abstracts Service  
CEFIC = European Chemical Industry Council  
CLP = Classification Packaging and Labelling  
COC = Cleveland Open-Cup  
DIN = Deutsches Institut für Normung  
DMEL = Derived Minimal Effect Level  
DNEL = Derived No Effect Level  
DSL = Canada Domestic Substance List  
EC = European Commission  
EC50 = Effective Concentration fifty  
ECETOC = European Center on Ecotoxicology and Toxicology

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR  
1910.1200

## C5/C7 Blend Stock

Version  
8.0

Revision Date:  
03/07/2025

SDS Number:  
800001008886

Print Date: 03/14/2025  
Date of last issue: 08/05/2022

gy Of Chemicals  
ECHA = European Chemicals Agency  
EINECS = The European Inventory of Existing Commercial Chemical Substances  
EL50 = Effective Loading fifty  
ENCS = Japanese Existing and New Chemical Substances Inventory  
EWC = European Waste Code  
GHS = Globally Harmonised System of Classification and Labelling of Chemicals  
IARC = International Agency for Research on Cancer  
IATA = International Air Transport Association  
IC50 = Inhibitory Concentration fifty  
IL50 = Inhibitory Level fifty  
IMDG = International Maritime Dangerous Goods  
INV = Chinese Chemicals Inventory  
IP346 = Institute of Petroleum test method N° 346 for the determination of polycyclic aromatics DMSO-extractables  
KECI = Korea Existing Chemicals Inventory  
LC50 = Lethal Concentration fifty  
LD50 = Lethal Dose fifty per cent.  
LL/EL/IL = Lethal Loading/Effective Loading/Inhibitory loading  
LL50 = Lethal Loading fifty  
MARPOL = International Convention for the Prevention of Pollution From Ships  
NOEC/NOEL = No Observed Effect Concentration / No Observed Effect Level  
OE\_HP V = Occupational Exposure - High Production Volume  
PBT = Persistent, Bioaccumulative and Toxic  
PICCS = Philippine Inventory of Chemicals and Chemical Substances  
PNEC = Predicted No Effect Concentration  
REACH = Registration Evaluation And Authorisation Of Chemicals  
RID = Regulations Relating to International Carriage of Dangerous Goods by Rail  
SKIN\_DES = Skin Designation  
STEL = Short term exposure limit  
TRA = Targeted Risk Assessment  
TSCA = US Toxic Substances Control Act  
TWA = Time-Weighted Average  
vPvB = very Persistent and very Bioaccumulative

A vertical bar (|) in the left margin indicates an amendment from the previous version.

Sources of key data used to compile the Safety Data Sheet : The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID date base, EC 1272 regulation, etc).

Revision Date : 03/07/2025

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR  
1910.1200

## C5/C7 Blend Stock

Version  
8.0

Revision Date:  
03/07/2025

SDS Number:  
800001008886

Print Date: 03/14/2025  
Date of last issue: 08/05/2022

---

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN