According to EC No 1907/2006 as amended as at the date of this SDS

LINEVOL 911

Version Revision Date: SDS Number: Date of last issue: 06.10.2023

6.0 23.01.2025 800001011477 Print Date 30.01.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : LINEVOL 911

Product code : V9332

Registration number EU : 01-2119485382-34-0000, 01-2119488024-39-0000

 Synonyms
 : Alcohols, C9-11

 CAS-No.
 : 85711-26-8

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Please refer to section 16 and/or the annexes for the regis-

stance/Mixture tered uses under REACH.

Uses advised against

This product must not be used in applications other than those

listed in Section 1 without first seeking the advice of the sup-

plier.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier : Shell Chemicals Europe B.V.

PO Box 2334

3000 CH Rotterdam

Netherlands

Telephone : +31 (0)10 441 5137 / +31 (0)10 441 5191 Telefax : +31 (0)20 716 8316 / +31 (0)20 713 9230

Contact for Safety Data : sccmsds@shell.com

Sheet

1.4 Emergency telephone number

+44 (0) 1235 239 670 (This telephone number is available 24 hours per day, 7 days per

week)

Giftnotruf (Berlin): +49 (0) 30 3068 6700

Other information : LINEVOL is a trademark owned by Shell Trademark Man-

agement B.V. and Shell Brands Inc. and used by affiliates of

Royal Dutch Shell plc.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin irritation, Category 2 H315: Causes skin irritation.

Eye irritation, Category 2 H319: Causes serious eye irritation.

According to EC No 1907/2006 as amended as at the date of this SDS

LINEVOL 911

Version Revision Date: SDS Number: Date of last issue: 06.10.2023

6.0 23.01.2025 800001011477 Print Date 30.01.2025

Long-term (chronic) aquatic hazard, Cat-

egory 3

H412: Harmful to aquatic life with long lasting ef-

fects.

Supplemental Hazard Statements EUH066: Repeated exposure may cause skin dry-

ness or cracking.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms

Signal word : Warning

Hazard statements : PHYSICAL HAZARDS:

Not classified as a physical hazard according to CLP

criteria.

HEALTH HAZARDS:

H315 Causes skin irritation.

H319 Causes serious eye irritation.

ENVIRONMENTAL HAZARDS:

H412 Harmful to aquatic life with long lasting effects.

Supplemental Hazard

Statements

EUH066

Repeated exposure may cause skin dryness or

cracking.

Precautionary statements : Prevention:

P264 Wash hands thoroughly after handling.

P280 Wear protective gloves/ protective clothing/ eye protec-

tion/ face protection.

P273 Avoid release to the environment.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water and

soap.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

According to EC No 1907/2006 as amended as at the date of this SDS

LINEVOL 911

Version Revision Date: SDS Number: Date of last issue: 06.10.2023

6.0 23.01.2025 800001011477 Print Date 30.01.2025

2.3 Other hazards

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Slightly irritating to respiratory system.

Harmful: May cause lung damage if swallowed.

SECTION 3: Composition/information on ingredients

3.1 Substances

Components

Chemical name	CAS-No.	Concentration (% w/w)
	EC-No.	
Alcohols, C9-11-branched	85711-26-8	<= 100
and linear	288-284-4	

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Not expected to be a health hazard when used under normal

conditions.

Protection of first-aiders : When administering first aid, ensure that you are wearing the

appropriate personal protective equipment according to the

incident, injury and surroundings.

If inhaled : No treatment necessary under normal conditions of use.

If symptoms persist, obtain medical advice.

In case of skin contact : Remove contaminated clothing. Immediately flush skin with

large amounts of water for at least 15 minutes, and follow by washing with soap and water if available. If redness, swelling, pain and/or blisters occur, transport to the nearest medical

facility for additional treatment.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses, if present and easy to do. Continue

rinsing.

Transport to the nearest medical facility for additional treat-

ment.

According to EC No 1907/2006 as amended as at the date of this SDS

LINEVOL 911

Version Revision Date: SDS Number: Date of last issue: 06.10.2023

6.0 23.01.2025 800001011477 Print Date 30.01.2025

If swallowed : If swallowed, do not induce vomiting: transport to nearest

medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (38.3°C), shortness of breath, chest congestion or continued coughing or wheezing.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : If material enters lungs, signs and symptoms may include coughing, choking, wheezing, difficulty in breathing, chest

congestion, shortness of breath, and/or fever.

If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (38.3°C), shortness of breath, chest congestion or continued coughing or wheezing.

Skin irritation signs and symptoms may include a burning sen-

sation, redness, or swelling.

Eye irritation signs and symptoms may include a burning sen-

sation, redness, swelling, and/or blurred vision.

Defatting dermatitis signs and symptoms may include a burn-

ing sensation and/or a dried/cracked appearance.

Not considered to be an inhalation hazard under normal con-

ditions of use.

Possible respiratory irritation signs and symptoms may include a temporary burning sensation of the nose and throat, cough-

ing, and/or difficulty breathing.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : IMMEDIATE TREATMENT IS EXTREMELY IMPORTANT!

Call a doctor or poison control center for guidance.

Potential for chemical pneumonitis.

Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam, water spray or fog. Dry chemical pow-

der, carbon dioxide, sand or earth may be used for small fires

only.

Unsuitable extinguishing

media

Do not use water in a jet.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

Carbon monoxide may be evolved if incomplete combustion

occurs.

Will float and can be reignited on surface water.

The vapour is heavier than air, spreads along the ground and distant ignition is possible.

According to EC No 1907/2006 as amended as at the date of this SDS

LINEVOL 911

Version Revision Date: SDS Number: Date of last issue: 06.10.2023

6.0 23.01.2025 800001011477 Print Date 30.01.2025

5.3 Advice for firefighters

Special protective equipment :

for firefighters

Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to

relevant Standards (e.g. Europe: EN469).

Specific extinguishing meth-

ods

Standard procedure for chemical fires.

Further information : Clear fire area of all non-emergency personnel.

Keep adjacent containers cool by spraying with water.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions

Observe all relevant local and international regulations.

Notify authorities if any exposure to the general public or the

environment occurs or is likely to occur. Local authorities should be advised if significant spillages

cannot be contained.

6.1.1 For non emergency personnel:

Avoid contact with spilled or released material. Immediately remove all contaminated clothing. For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet. For guidance on disposal of spilled material see

Section 13 of this Safety Data Sheet. Stay upwind and keep out of low areas. Be ready for fire or possible exposure. 6.1.2 For emergency responders:

Avoid contact with spilled or released material. Immediately remove all contaminated clothing. For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet. For guidance on disposal of spilled material see

Section 13 of this Safety Data Sheet. Stay upwind and keep out of low areas. Be ready for fire or possible exposure.

6.2 Environmental precautions

Environmental precautions : Prevent from spreading or entering into drains, ditches or riv-

ers by using sand, earth, or other appropriate barriers.

Use appropriate containment to avoid environmental contami-

nation.

Ventilate contaminated area thoroughly.

According to EC No 1907/2006 as amended as at the date of this SDS

LINEVOL 911

Version Revision Date: SDS Number: Date of last issue: 06.10.2023

6.0 23.01.2025 800001011477 Print Date 30.01.2025

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : For large liquid spills (> 1 drum), transfer by mechanical

means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely For small liquid spills (< 1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove

contaminated soil and dispose of safely.

6.4 Reference to other sections

For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet., For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures : Avoid breathing of or direct contact with material. Only use in

well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see

Section 8 of this Safety Data Sheet.

Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this

naterial.

Ensure that all local regulations regarding handling and stor-

age facilities are followed.

Advice on safe handling : Avoid contact with skin, eyes and clothing.

Do not empty into drains.

Sudden Release of Pressure Hazard

Product Transfer : Keep containers closed when not in use. Do not use com-

pressed air for filling discharge or handling.

Hygiene measures : Wash hands before eating, drinking, smoking and using the

toilet. Launder contaminated clothing before re-use.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Refer to section 15 for any additional specific legislation cov-

ering the packaging and storage of this product.

Storage class (TRGS 510) : 10, Combustible liquids

Further information on stor-

age stability

: Bulk storage tanks should be diked (bunded).

Vapours from tanks should not be released to atmosphere. Breathing losses during storage should be controlled by a

According to EC No 1907/2006 as amended as at the date of this SDS

LINEVOL 911

Version	Revision Date:	SDS Number:	Date of last issue: 06.10.2023
6.0	23 01 2025	800001011477	Print Date 30 01 2025

suitable vapour treatment system.

Nitrogen blanket recommended for large tanks (capacity 100

m3 or higher).

Insulation (lagging) will minimize heat loss in areas of low

ambient temperature.

Tanks should be fitted with heating coils in areas where ambient conditions can result in handling temperatures below the

freezing point/pour point of the product.

Packaging material : Suitable material: Stainless steel., Epoxy resins, Polyester.

Unsuitable material: Aluminum, Copper., Copper alloys.

Container Advice : Containers, even those that have been emptied, can contain

explosive vapours. Do not cut, drill, grind, weld or perform

similar operations on or near containers.

7.3 Specific end use(s)

Specific use(s) : Please refer to section 16 and/or the annexes for the regis-

tered uses under REACH.

Ensure that all local regulations regarding handling and stor-

age facilities are followed.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Biological occupational exposure limits

No biological limit allocated.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Remarks:	No DNEL value has been established.
----------	-------------------------------------

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Remarks:	e is a hydrocarbon with a complex, unknown or rentional methods of deriving PNECs are not a	•
	ole to identify a single representative PNEC for	

8.2 Exposure controls

Engineering measures

Adequate ventilation to control airborne concentrations below the exposure guidelines/limits. Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

Eye washes and showers for emergency use.

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

General Information:

According to EC No 1907/2006 as amended as at the date of this SDS

LINEVOL 911

Version Revision Date: SDS Number: Date of last issue: 06.10.2023

6.0 23.01.2025 800001011477 Print Date 30.01.2025

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

Do not ingest. If swallowed, then seek immediate medical assistance.

Personal protective equipment

The provided information is made in consideration of the PPE directive (Council Directive 89/686/EEC) and the CEN European Committee for Standardisation (CEN) standards.

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Eye protection : Wear goggles for use against liquids and gas.

Wear full face shield if splashes are likely to occur.

Approved to EU Standard EN166.

Hand protection

Remarks : Where hand contact with the product may occur the use of

gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. Longer term protection: Nitrile rubber gloves. Incidental contact/Splash protection: PVC or neoprene rubber gloves. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

Skin and body protection : Skin protection is not required under normal conditions of

According to EC No 1907/2006 as amended as at the date of this SDS

LINEVOL 911

Version 6.0 Revision Date: 23.01.2025

SDS Number: 800001011477

Date of last issue: 06.10.2023

Print Date 30.01.2025

use.

For prolonged or repeated exposures use impervious clothing

over parts of the body subject to exposure.

If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to relevant Standard, and provide employee skin care programmes.

Protective clothing approved to EU Standard EN14605.

Respiratory protection

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are unsuitable (e.g. airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus.

Where air-filtering respirators are suitable, select an appro-

priate combination of mask and filter.

If air-filtering respirators are suitable for conditions of use: Select a filter suitable for the combination of organic gases and vapours and particles meeting EN14387 and EN143 [Filter type A/P for use against certain organic gases and vapours with a boiling point >65°C (149°F) and for use

against particles].

Thermal hazards : Not applicable

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : Liquid at 20 °C.

Colour : colourless

Odour : mild

Odour Threshold : Data not available

pour point : -12 °C

Melting point/freezing point Data not available

Boiling point/boiling range : 213 - 245 °C

Flammability

Flammability (solid, gas) : No, product cannot ignite due to static electricity.

According to EC No 1907/2006 as amended as at the date of this SDS

LINEVOL 911

Version Revision Date: SDS Number: Date of last issue: 06.10.2023 800001011477 Print Date 30.01.2025

Lower explosion limit and upper explosion limit / flammability limit

Upper explosion limit / upper flammability limit

: Data not available

Lower explosion limit / Lower flammability limit Data not available

Flash point : 109 °C

Method: ASTM D93 (PMCC)

Auto-ignition temperature : Data not available

Decomposition temperature

Decomposition tempera-

Data not available

ture

pH : Data not available

Viscosity

Viscosity, dynamic : 14,1 mPa.s (20 °C)

Method: ASTM D445

50 mPa.s (Not applicable) Method: ASTM D445

Viscosity, kinematic : 9 mm2/s (38 °C)

Method: ASTM D445

15 mm2/s (25 °C) Method: ASTM D445

Solubility(ies)

Water solubility : practically insoluble

Partition coefficient: n-

octanol/water

log Pow: 3,8 - 4,7

Vapour pressure : < 5 Pa (20 °C)

Relative density : 0,829

Method: ASTM D4052

Density : 830 kg/m3 (20 °C)

Method: ASTM D4052

Relative vapour density : 5,5

Particle characteristics

Particle size : Data not available

9.2 Other information

According to EC No 1907/2006 as amended as at the date of this SDS

LINEVOL 911

Version Revision Date: SDS Number: Date of last issue: 06.10.2023

6.0 23.01.2025 800001011477 Print Date 30.01.2025

Explosive properties : Not classified

Oxidizing properties : Data not available

Evaporation rate : Data not available

Conductivity: > 10,000 pS/m, A number of factors,

for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid, This material is not expected to be a static accumu-

lator.

Surface tension : Data not available

Molecular weight : 160 g/mol

SECTION 10: Stability and reactivity

10.1 Reactivity

Stable at normal ambient temperature and pressure.

May oxidise in the presence of air.

10.2 Chemical stability

The product is chemically stable.

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : None known.

10.4 Conditions to avoid

Conditions to avoid : Extremes of temperature and direct sunlight.

10.5 Incompatible materials

Materials to avoid : Copper.

Copper alloys.

Strong oxidising agents.

Aluminum

10.6 Hazardous decomposition products

None expected under normal use conditions.

According to EC No 1907/2006 as amended as at the date of this SDS

LINEVOL 911

Version Revision Date: SDS Number: Date of last issue: 06.10.2023

6.0 23.01.2025 800001011477 Print Date 30.01.2025

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Components:

Alcohols, C9-11-branched and linear:

Acute oral toxicity : LD50 (Rat): > 5000 mg/kg

Remarks: Low toxicity

Acute inhalation toxicity : Remarks: Low toxicity by inhalation.

Acute dermal toxicity : Remarks: Low toxicity

Skin corrosion/irritation

Components:

Alcohols, C9-11-branched and linear:

Remarks : Causes skin irritation.

Serious eye damage/eye irritation

Components:

Alcohols, C9-11-branched and linear:

Remarks : Slightly irritating to the eye.

Respiratory or skin sensitisation

Components:

Alcohols, C9-11-branched and linear:

Remarks : Not a sensitiser.

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Components:

Alcohols, C9-11-branched and linear:

Genotoxicity in vivo : Remarks: Non mutagenic

Germ cell mutagenicity- As-

sessment

This product does not meet the criteria for classification in

categories 1A/1B.

According to EC No 1907/2006 as amended as at the date of this SDS

LINEVOL 911

Version Revision Date: SDS Number: Date of last issue: 06.10.2023

6.0 23.01.2025 800001011477 Print Date 30.01.2025

Carcinogenicity

Components:

Alcohols, C9-11-branched and linear:

Remarks : Not a carcinogen.

Based on available data, the classification criteria are not met.

Carcinogenicity - Assess-

ment

This product does not meet the criteria for classification in

categories 1A/1B.

Material	GHS/CLP Carcinogenicity Classification
Alcohols, C9-11	No carcinogenicity classification.

Reproductive toxicity

Components:

Alcohols, C9-11-branched and linear:

Effects on fertility :

Remarks: Not a developmental toxicant., Based on available data, the classification criteria are not met., Does not impair

fertility.

Reproductive toxicity - As-

sessment

This product does not meet the criteria for classification in

categories 1A/1B.

STOT - single exposure

Components:

Alcohols, C9-11-branched and linear:

Remarks : Based on available data, the classification criteria are not met.

STOT - repeated exposure

Components:

Alcohols, C9-11-branched and linear:

Remarks : Based on available data, the classification criteria are not met.

Aspiration toxicity

Components:

Alcohols, C9-11-branched and linear:

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

According to EC No 1907/2006 as amended as at the date of this SDS

LINEVOL 911

SDS Number: Date of last issue: 06.10.2023 Version Revision Date:

800001011477 23.01.2025 Print Date 30.01.2025 6.0

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment The substance/mixture does not contain components consid-

> ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

Further information

Product:

Remarks Unless indicated otherwise, the data presented is representa-

tive of the product as a whole, rather than for individual com-

ponent(s).

Components:

Alcohols, C9-11-branched and linear:

Remarks Classifications by other authorities under varying regulatory

frameworks may exist.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Alcohols, C9-11-branched and linear:

Toxicity to fish Remarks: LC/EC/IC50 >1 - <=10 mg/l

Toxic

Toxicity to daphnia and other :

aquatic invertebrates

Remarks: LC/EC/IC50 >1 - <=10 mg/l

Toxic

Toxicity to algae/aquatic plants : Remarks: LC/EC/IC50 >1 - <=10 mg/l

Toxic

Toxicity to microorganisms : EC50 : > 10.000 mg/l

Toxicity to fish (Chronic tox-

icity)

Remarks: Data not available

aquatic invertebrates (Chron-

ic toxicity)

Toxicity to daphnia and other : Remarks: NOEC/NOEL > 0.01 - <=0.1 mg/l

According to EC No 1907/2006 as amended as at the date of this SDS

LINEVOL 911

Version Revision Date: SDS Number: Date of last issue: 06.10.2023

6.0 23.01.2025 800001011477 Print Date 30.01.2025

12.2 Persistence and degradability

Components:

Alcohols, C9-11-branched and linear:

Biodegradability : Remarks: Readily biodegradable.

12.3 Bioaccumulative potential

Components:

Alcohols, C9-11-branched and linear:

Bioaccumulation : Remarks: Bioaccumulation is unlikely to occur due to metabolism

and excretion.

12.4 Mobility in soil

Components:

Alcohols, C9-11-branched and linear:

Mobility : Remarks: Floats on water., Adsorbs to soil and has low mobili-

ty

12.5 Results of PBT and vPvB assessment

Components:

Alcohols, C9-11-branched and linear:

Assessment : The substance does not fulfill all screening criteria for persis-

tence, bioaccumulation and toxicity and hence is not consid-

ered to be PBT or vPvB..

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to

have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological infor-

mation

Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

Components:

Alcohols, C9-11-branched and linear:

Additional ecological infor- : None known.

According to EC No 1907/2006 as amended as at the date of this SDS

LINEVOL 911

Version Revision Date: SDS Number: Date of last issue: 06.10.2023

6.0 23.01.2025 800001011477 Print Date 30.01.2025

mation

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Recover or recycle if possible.

It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal meth-

ods in compliance with applicable regulations.

Do not dispose into the environment, in drains or in water

courses.

Waste product should not be allowed to contaminate soil or

water.

Disposal should be in accordance with applicable regional,

national, and local laws and regulations.

Local regulations may be more stringent than regional or na-

tional requirements and must be complied with.

Contaminated packaging : Drain container thoroughly.

After draining, vent in a safe place away from sparks and fire.

Residues may cause an explosion hazard. Do not puncture, cut, or weld uncleaned drums. Send to drum recoverer or metal reclaimer.

SECTION 14: Transport information

14.1 UN number or ID number

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.2 UN proper shipping name

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good

According to EC No 1907/2006 as amended as at the date of this SDS

LINEVOL 911

Version Revision Date: SDS Number: Date of last issue: 06.10.2023

6.0 23.01.2025 800001011477 Print Date 30.01.2025

RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.4 Packing group

ADN : Not regulated as a dangerous good

CDNI Inland Water Waste : NST 8969 Chemicals

Agreement

ADR : Not regulated as a dangerous good

RID : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

i Not regulated as a dangerous good

14.5 Environmental hazards

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good

14.6 Special precautions for user

Remarks : Special Precautions: Refer to Section 7, Handling & Storage,

for special precautions which a user needs to be aware of or

needs to comply with in connection with transport.

14.7 Maritime transport in bulk according to IMO instruments

Pollution category : X Ship type : 2

Product name : LINEVOL 911 (contains Nonyl alcohol (all isomers); Undecyl

alcohol)

Additional Information: This product may be transported under nitrogen blanketing.

Nitrogen is an odourless and invisible gas. Exposure to nitrogen may cause asphyxiation or death. Personnel must observe strict safety precautions when involved with a confined space entry. Transport in bulk according to Annex II of Marpol

and the IBC Code

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Water hazard class (Germa: WGK 1 slightly hazardous to water

ny) Remarks: Classification according to AwSV

Volatile organic compounds : Volatile organic compounds (VOC) content: 99,96 %

According to EC No 1907/2006 as amended as at the date of this SDS

LINEVOL 911

Version Revision Date: SDS Number: Date of last issue: 06.10.2023

6.0 23.01.2025 800001011477 Print Date 30.01.2025

Other regulations:

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

The components of this product are reported in the following inventories:

AIIC : Listed

DSL : Listed

IECSC : Listed

ENCS : Listed

KECI : Listed

NZIoC : Listed

TSCA : Listed

TCSI : Listed

15.2 Chemical safety assessment

A Chemical Safety Assessment has been carried out for this substance.

SECTION 16: Other information

Full text of other abbreviations

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road: AIIC - Australian Inventory of Industrial Chemicals: ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA -European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - Interna-

According to EC No 1907/2006 as amended as at the date of this SDS

LINEVOL 911

Version Revision Date: SDS Number: Date of last issue: 06.10.2023

6.0 23.01.2025 800001011477 Print Date 30.01.2025

tional Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Training advice : Provide adequate information, instruction and training for op-

erators.

Other information : For Industry guidance and tools on REACH please visit the

CEFIC website at http://cefic.org/Industry-support.

The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not consid-

ered to be PBT or vPvB.

A vertical bar (|) in the left margin indicates an amendment

from the previous version.

Sources of key data used to compile the Safety Data

Sheet

The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU

IUCLID date base, EC 1272 regulation, etc).

Identified Uses according to the Use Descriptor System

Uses - Worker

Title : Manufacture of substance

- Industrial

Uses - Worker

Title : Use as an intermediate

- Industrial

Uses - Worker

Title : Formulation & (re)packing of substances and mixtures

- Industrial

Uses - Worker

Title : Uses in Coatings

- Industrial

According to EC No 1907/2006 as amended as at the date of this SDS

LINEVOL 911

Version Revision Date: SDS Number: Date of last issue: 06.10.2023

6.0 23.01.2025 800001011477 Print Date 30.01.2025

Uses - Worker

Title : Uses in Coatings

- Professional

Uses - Worker

Title : Use in Cleaning Agents

- Industrial

Uses - Worker

Title : Use in Cleaning Agents

- Professional

Identified Uses according to the Use Descriptor System

Uses - Consumer

Title : Uses in Coatings

- Consumer

Uses - Consumer

Title : Use in Cleaning Agents

- Consumer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

DE / EN

According to EC No 1907/2006 as amended as at the date of this SDS

LINEVOL 911

Version Revision Date: SDS Number: Date of last issue: 06.10.2023

6.0 23.01.2025 800001011477 Print Date 30.01.2025

Exposure Scenario - Worker

30000000521	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Manufacture of substance- Industrial
Use Descriptor	Sector of Use: SU3, SU8, SU9 Process Categories: PROC 1, PROC 2, PROC 3, PROC 4, PROC 8a, PROC 8b, PROC 15 Environmental Release Categories: ERC1
Scope of process	Manufacture of the substance or use as a process chemical or extraction agent. Includes recycling/ recovery, material transfers, storage, maintenance and loading (including marine vessel/barge, road/rail car and bulk container), sampling and associated laboratory activities.

SECTION 2	OPERATIONAL CONDITIONS AND RIS MEASURES	K MANAGEMENT
Section 2.1	Control of Worker Exposure	
Product Characteristics		
Physical form of product	Liquid	
Concentration of the Substance in Mixture/Article	Covers use of substance/product up to 10 differently).,	00% (unless stated
Frequency and Duration of		
	8 hours (unless stated differently).	
Other Operational Conditio		
	ard of occupational hygiene is implemented	d.
Contributing Scenarios	Risk Management Measures	
General measures (eye irritants).	Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands. No other specific measures identified.	
Section 2.2	Control of Environmental Exposure	
Substance is complex UVCB		
Alcohol.		
Readily biodegradable.		
Amounts Used		
Fraction of EU tonnage used	in region:	
Regional use tonnage (tonnes/year):		
Fraction of Regional tonnage used locally:		
Annual site tonnage (tonnes/year): 29,300		-
Maximum daily site tonnage (kg/day): 9,80E+04		9,80E+04
Frequency and Duration of	Use	
Continuous release.		
Emission Days (days/year): 300		300

According to EC No 1907/2006 as amended as at the date of this SDS

LINEVOL 911

Version Revision Date: SDS Number: Date of last issue: 06.10.2023

6.0 23.01.2025 800001011477 Print Date 30.01.2025

Environmental factors not influenced by risk management	
Local freshwater dilution factor:	10
Local marine water dilution factor:	100
Other Operational Conditions affecting Environmental Exposure	•
Release fraction to air from process (initial release prior to RMM):	
Release fraction to wastewater from process (initial release prior to	
RMM):	
Release fraction to soil from process (initial release prior to RMM):	
Technical conditions and measures at process level (source) to pr	event release
Common practices vary across sites thus conservative process re-	
lease estimates used.	
Technical onsite conditions and measures to reduce or limit disch sions and releases to soil	arges, air emis-
Risk from environmental exposure is driven by soil.	
Prevent discharge of undissolved substance to or recover from onsite	
wastewater.	
If discharging to domestic sewage treatment plant, no secondary	
wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	0
Treat onsite wastewater (prior to receiving water discharge) to provide	99
the required removal efficiency of >= (%)	
If discharging to domestic sewage treatment plant, no secondary	0
wastewater treatment required.	
Organisational measures to prevent/limit release from site	
Do not apply industrial sludge to natural soils.	
Sludge should be incinerated, contained or reclaimed.	
Conditions and Measures related to municipal sewage treatment p	
Estimated substance removal from wastewater via domestic sewage	99
treatment (%)	00
Total efficiency of removal from wastewater after onsite and offsite	99
(domestic treatment plant) RMMs (%)	10.000
Assumed domestic sewage treatment plant flow (m3/d) Maximum allowable site tonnage (MSafe) based on release following	10.000
total wastewater treatment removal (kg/d)	
Conditions and Measures related to external treatment of waste fo	r dienoeal
	i uispusai
During manufacturing no waste of the substance is generated.	
Conditions and measures related to external recovery of waste	

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
	enable the derivation of a DNEL for eye irritant effects. are based on qualitative risk characterisation.

Section 3.2 -Environment	
Used EUSES model.	

According to EC No 1907/2006 as amended as at the date of this SDS

LINEVOL 911

Version Revision Date: SDS Number: Date of last issue: 06.10.2023

6.0 23.01.2025 800001011477 Print Date 30.01.2025

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	

Risk Management Measures are based on qualitative risk characterisation.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 - Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required.

According to EC No 1907/2006 as amended as at the date of this SDS

LINEVOL 911

Version Revision Date: SDS Number: Date of last issue: 06.10.2023

6.0 23.01.2025 800001011477 Print Date 30.01.2025

Exposure Scenario - Worker

30000000523	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Use as an intermediate- Industrial
Use Descriptor	Sector of Use: SU3, SU8, SU9 Process Categories: PROC 1, PROC 2, PROC 3, PROC 4, PROC 8a, PROC 8b, PROC 15 Environmental Release Categories: ERC6a
Scope of process	Use of substance as an intermediate (not related to Strictly Controlled Conditions). Includes recycling/ recovery, material transfers, storage, sampling, associated laboratory activities, maintenance and loading (including marine vessel/barge, road/rail car and bulk container).

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Section 2.1	Control of Worker Exposure	
Product Characteristics		
Physical form of product	Liquid	
Concentration of the Substance in Mixture/Article	Covers use of substance/product up to 100% (unless stated differently).,	
Frequency and Duration of		
Covers daily exposures up to	8 hours (unless stated differently).	
Other Operational Conditio		
Assumes a good basic stand	ard of occupational hygiene is implemented	d.
Contributing Scenarios	Risk Management Measures	
General measures (eye irritants).	Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands. No other specific measures identified.	
Section 2.2	Control of Environmental Exposure	
Substance is complex UVCB	•	
Alcohol.		
Readily biodegradable.		
Amounts Used		
Fraction of EU tonnage used	in region:	
Regional use tonnage (tonnes/year):		
Fraction of Regional tonnage used locally:		
Annual site tonnage (tonnes/year):		163
Maximum daily site tonnage (kg/day): 543		543
Frequency and Duration of	Use	
Continuous release.		
Emission Days (days/year): 300		300

According to EC No 1907/2006 as amended as at the date of this SDS

LINEVOL 911

Version Revision Date: SDS Number: Date of last issue: 06.10.2023

6.0 23.01.2025 800001011477 Print Date 30.01.2025

Environmental factors not influenced by risk management	T
Local freshwater dilution factor:	10
Local marine water dilution factor:	100
Other Operational Conditions affecting Environmental Exposure	1
Release fraction to air from process (initial release prior to RMM):	0,05
Release fraction to wastewater from process (initial release prior to RMM):	0,007
Release fraction to soil from process (initial release prior to RMM):	
Technical conditions and measures at process level (source) to pro-	event release
Common practices vary across sites thus conservative process release estimates used.	
Technical onsite conditions and measures to reduce or limit disch	arges, air emis-
sions and releases to soil	
Risk from environmental exposure is driven by marine water.	
Prevent discharge of undissolved substance to or recover from onsite wastewater.	
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	0
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)	99
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	0
Organisational measures to prevent/limit release from site	
Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.	
Conditions and Measures related to municipal sewage treatment p	lant
Estimated substance removal from wastewater via domestic sewage	99
treatment (%)	
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	99
Assumed domestic sewage treatment plant flow (m3/d)	10.000
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	
Conditions and Measures related to external treatment of waste for	r disposal
External treatment and disposal of waste should comply with applicable local and/or regional regulations.	
This substance is consumed during use and no waste of substance is generated.	
Conditions and measures related to external recovery of waste	
External recovery and recycling of waste should comply with applicable regulations.	_
This substance is consumed during use and no waste of substance is g	enerated.

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
Available hazard data do not enable the derivation of a DNEL for eye irritant effects.	

Risk Management Measures are based on qualitative risk characterisation.

According to EC No 1907/2006 as amended as at the date of this SDS

LINEVOL 911

Version Revision Date: SDS Number: Date of last issue: 06.10.2023

6.0 23.01.2025 800001011477 Print Date 30.01.2025

Section 3.2 -Environment	
Used EUSES model.	

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	
Risk Management Measures are based on qualitative risk characterisation.	
Where other Risk Management Measures/Operational Conditions are adopted, then users	
should ensure that risks are managed to at least equivalent levels.	

Section 4.2 - Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required.

According to EC No 1907/2006 as amended as at the date of this SDS

LINEVOL 911

Version Revision Date: SDS Number: Date of last issue: 06.10.2023

6.0 23.01.2025 800001011477 Print Date 30.01.2025

Exposure Scenario - Worker

Exposure Scenario - Worker	
30000000525	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Formulation & (re)packing of substances and mixtures- Industrial
Use Descriptor	Sector of Use: SU3, SU10 Process Categories: PROC 1, PROC 2, PROC 3, PROC 4, PROC 5, PROC 8a, PROC 8b, PROC 9, PROC 14, PROC 15 Environmental Release Categories: ERC2
Scope of process	Formulation, packing and re-packing of the substance and its mixtures in batch or continuous operations, including storage, materials transfers, mixing, tabletting, compression, pelletisation, extrusion, large and small scale packing, sampling, maintenance and associated laboratory activities.

SECTION 2	OPERATIONAL CONDITIONS AND RIS	K MANAGEMENT
Section 2.1	Control of Worker Exposure	
Product Characteristics		
Physical form of product	Liquid	
Concentration of the Substance in Mixture/Article	Covers use of substance/product up to 100% (unless stated differently).,	
Frequency and Duration of		
Covers daily exposures up to	8 hours (unless stated differently).	
Other Operational Conditio	ns affecting Exposure	
Assumes a good basic stand	ard of occupational hygiene is implemented	d.
Contributing Scenarios	Risk Management Measures	
General measures (eye irritants).	Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands. No other specific measures identified.	
Section 2.2	Control of Environmental Exposure	
Substance is complex UVCB		
Alcohol.		
Readily biodegradable.		
Amounts Used		
Fraction of EU tonnage used in region:		
Regional use tonnage (tonnes/year):		
Fraction of Regional tonnage used locally:		
Annual site tonnage (tonnes/year): 41		
Maximum daily site tonnage (kg/day): 137		137
Frequency and Duration of	Use	
Continuous release.		
Emission Days (days/year): 300		300

According to EC No 1907/2006 as amended as at the date of this SDS

LINEVOL 911

Version Revision Date: SDS Number: Date of last issue: 06.10.2023

6.0 23.01.2025 800001011477 Print Date 30.01.2025

Environmental factors not influenced by risk management	
Local freshwater dilution factor:	10
Local marine water dilution factor:	100
Other Operational Conditions affecting Environmental Exposure	Į.
Release fraction to air from process (initial release prior to RMM):	1,75E-03
Release fraction to wastewater from process (initial release prior to	2,0E-05
RMM):	
Release fraction to soil from process (initial release prior to RMM):	
Technical conditions and measures at process level (source) to pro-	event release
Common practices vary across sites thus conservative process re-	
lease estimates used.	
Technical onsite conditions and measures to reduce or limit dischaions and releases to soil	arges, air emis-
Risk from environmental exposure is driven by marine water.	
Prevent discharge of undissolved substance to or recover from onsite	
wastewater.	
If discharging to domestic sewage treatment plant, no secondary	
wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	0
Treat onsite wastewater (prior to receiving water discharge) to provide	99
the required removal efficiency of >= (%)	
If discharging to domestic sewage treatment plant, no secondary	0
wastewater treatment required.	
Organisational measures to prevent/limit release from site	
Sludge should be incinerated, contained or reclaimed.	
Conditions and Measures related to municipal sewage treatment p	lant
Estimated substance removal from wastewater via domestic sewage	99
treatment (%)	
Total efficiency of removal from wastewater after onsite and offsite	99
(domestic treatment plant) RMMs (%)	
Assumed domestic sewage treatment plant flow (m3/d)	10.000
Maximum allowable site tonnage (MSafe) based on release following	
total wastewater treatment removal (kg/d)	!:!
Conditions and Measures related to external treatment of waste for	
External treatment and disposal of waste should comply with applicable local and/or regional regulations.	
Conditions and measures related to external recovery of waste	
External recovery and recycling of waste should comply with applicable	local and/or regional
regulations.	

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
Available hazard data do not enable the derivation of a DNEL for eye irritant effects. Risk Management Measures are based on qualitative risk characterisation.	

Section 3.2 -Environment	
Used EUSES model.	

According to EC No 1907/2006 as amended as at the date of this SDS

LINEVOL 911

Version Revision Date: SDS Number: Date of last issue: 06.10.2023

6.0 23.01.2025 800001011477 Print Date 30.01.2025

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE
	EXPOSURE SCENARIO

Section 4.1 - Health

Risk Management Measures are based on qualitative risk characterisation. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 - Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required.

According to EC No 1907/2006 as amended as at the date of this SDS

LINEVOL 911

Version Revision Date: SDS Number: Date of last issue: 06.10.2023

6.0 23.01.2025 800001011477 Print Date 30.01.2025

Exposure Scenario - Worker

Exposure occurred - Worker	
3000000526	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Uses in Coatings- Industrial
Use Descriptor	Sector of Use: SU3 Process Categories: PROC 1, PROC 2, PROC 3, PROC 4, PROC 5, PROC 7, PROC 8a, PROC 8b, PROC 10, PROC 13, PROC 15 Environmental Release Categories: ERC4
	Livilonnental Release Categories. LINC4
Scope of process	Covers the use in coatings (paints, inks, adhesives, etc) including exposures during use (including materials receipt, storage, preparation and transfer from bulk and semi-bulk, application by spray, roller, spreader, dip, flow, fluidised bed on production lines and film formation) and equipment cleaning, maintenance and associated laboratory activities.

SECTION 2	OPERATIONAL CONDITIONS AND RI MEASURES	SK MANAGEMENT
Section 2.1	Control of Worker Exposure	
Product Characteristics		
Physical form of product	Liquid	
Concentration of the Substance in Mixture/Article	Covers use of substance/product up to differently).,	100% (unless stated
Frequency and Duration o	f Use	
Covers daily exposures up t	o 8 hours (unless stated differently).	
Other Operational Condition		
Assumes a good basic stand	dard of occupational hygiene is implement	ed.
Contributing Scenarios	Risk Management Measures	
General measures (eye	Use suitable eye protection.	
irritants).	Avoid direct eye contact with product, all on hands.	lso via contamination
	No other specific measures identified.	
Section 2.2	Control of Environmental Exposure	
Substance is complex UVCI		
Alcohol.		
Readily biodegradable.		
Amounts Used		
Fraction of EU tonnage used in region:		
Regional use tonnage (tonn		
Fraction of Regional tonnag	e used locally:	
Annual site tonnage (tonnes/year):		5,20E-03
Maximum daily site tonnage (kg/day): 0,017		0,017
Frequency and Duration of	f Use	
Continuous release.		

According to EC No 1907/2006 as amended as at the date of this SDS

LINEVOL 911

Version Revision Date: SDS Number: Date of last issue: 06.10.2023

6.0 23.01.2025 800001011477 Print Date 30.01.2025

Emission Days (days/year):	300
Environmental factors not influenced by risk management	1 000
Local freshwater dilution factor:	10
Local marine water dilution factor:	100
Other Operational Conditions affecting Environmental Exposure	
Release fraction to air from process (initial release prior to RMM):	0,03
Release fraction to wastewater from process (initial release prior to	0,03
RMM):	
Release fraction to soil from process (initial release prior to RMM):	
Technical conditions and measures at process level (source) to pro-	event release
Common practices vary across sites thus conservative process re-	
lease estimates used.	
Technical onsite conditions and measures to reduce or limit disch	arges, air emis-
sions and releases to soil	
Risk from environmental exposure is driven by marine water.	
If discharging to domestic sewage treatment plant, no secondary	
wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	0
Treat onsite wastewater (prior to receiving water discharge) to provide	99
the required removal efficiency of >= (%)	
If discharging to domestic sewage treatment plant, no secondary	
wastewater treatment required.	
Organisational measures to prevent/limit release from site	
Sludge should be incinerated, contained or reclaimed.	
Conditions and Measures related to municipal sewage treatment p	lant
	99
Estimated substance removal from wastewater via domestic sewage treatment (%)	99
Total efficiency of removal from wastewater after onsite and offsite	99
(domestic treatment plant) RMMs (%)	99
Assumed domestic sewage treatment plant flow (m3/d)	2.000
Maximum allowable site tonnage (MSafe) based on release following	2.000
total wastewater treatment removal (kg/d)	
Conditions and Measures related to external treatment of waste for	r disposal
External treatment and disposal of waste should comply with applicable	
regulations.	iodai di ia, or rogiona.
Conditions and measures related to external recovery of waste	
External recovery and recycling of waste should comply with applicable	local and/or regional
regulations.	iocai anu/oi regionai
Togulations.	

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
	enable the derivation of a DNEL for eye irritant effects. are based on qualitative risk characterisation.

Section 3.2 -Environment	
Used EUSES model.	

According to EC No 1907/2006 as amended as at the date of this SDS

LINEVOL 911

Version Revision Date: SDS Number: Date of last issue: 06.10.2023

6.0 23.01.2025 800001011477 Print Date 30.01.2025

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	

Risk Management Measures are based on qualitative risk characterisation.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 - Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required.

According to EC No 1907/2006 as amended as at the date of this SDS

LINEVOL 911

Version Revision Date: SDS Number: Date of last issue: 06.10.2023

6.0 23.01.2025 800001011477 Print Date 30.01.2025

Exposure Scenario - Worker

	Exposure occinano - Worker	
30000000529		
SECTION 1	EXPOSURE SCENARIO TITLE	
Title	Uses in Coatings- Professional	
Use Descriptor	Sector of Use: SU22	
	Process Categories: PROC 1, PROC 2, PROC 3, PROC 4,	
	PROC 5, PROC 8a, PROC 8b, PROC 10, PROC 11, PROC	
	13, PROC 15, PROC 19	
	Environmental Release Categories: ERC8a, ERC8d	
Scope of process	Covers the use in coatings (paints, inks, adhesives, etc) including exposures during use (including materials receipt, storage, preparation and transfer from bulk and semi-bulk, application by spray, roller, brush, spreader by hand or similar methods, and film formation), and equipment cleaning, maintenance and associated laboratory activities.	

SECTION 2	OPERATIONAL CONDITIONS AND RIS	SK MANAGEMENT
Section 2.1	Control of Worker Exposure	
Product Characteristics		
Physical form of product	Liquid	
Concentration of the Substance in Mixture/Article	Covers use of substance/product up to 1 differently).,	00% (unless stated
Frequency and Duration of		
	8 hours (unless stated differently).	
Other Operational Conditio		
Assumes a good basic stand	ard of occupational hygiene is implemente	ed.
Contributing Scenarios	Risk Management Measures	
General measures (eye irritants).	Use suitable eye protection. Avoid direct eye contact with product, als on hands. No other specific measures identified.	so via contamination
Section 2.2	Control of Environmental Exposure	
Substance is complex UVCB		
Alcohol.		
Readily biodegradable.		
Amounts Used		
Fraction of EU tonnage used	in region:	
Regional use tonnage (tonnes/year):		
Fraction of Regional tonnage used locally:		
Annual site tonnage (tonnes/year): 0,16		0,16
Maximum daily site tonnage (kg/day): 0,53		0,53
Frequency and Duration of	Use	
Continuous release.		

According to EC No 1907/2006 as amended as at the date of this SDS

LINEVOL 911

Version Revision Date: SDS Number: Date of last issue: 06.10.2023

6.0 23.01.2025 800001011477 Print Date 30.01.2025

	I
Emission Days (days/year):	300
Environmental factors not influenced by risk management	
Local freshwater dilution factor:	10
Local marine water dilution factor:	100
Other Operational Conditions affecting Environmental Exposure	
Release fraction to air from process (initial release prior to RMM):	0,01
Release fraction to wastewater from process (initial release prior to	0,01
RMM):	
Release fraction to soil from process (initial release prior to RMM):	
Technical conditions and measures at process level (source) to pro	event release
Common practices vary across sites thus conservative process re-	
lease estimates used.	
Technical onsite conditions and measures to reduce or limit discharge	arges, air emis-
sions and releases to soil	
Risk from environmental exposure is driven by marine water.	
If discharging to domestic sewage treatment plant, no secondary	
wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	0
Treat onsite wastewater (prior to receiving water discharge) to provide	99
the required removal efficiency of >= (%)	
If discharging to domestic sewage treatment plant, no secondary	0
wastewater treatment required.	
Organisational measures to prevent/limit release from site	
Sludge should be incinerated, contained or reclaimed.	
Conditions and Measures related to municipal sewage treatment p	lant
Estimated substance removal from wastewater via domestic sewage	99
treatment (%)	
Total efficiency of removal from wastewater after onsite and offsite	99
(domestic treatment plant) RMMs (%)	
Assumed domestic sewage treatment plant flow (m3/d)	2.000
Maximum allowable site tonnage (MSafe) based on release following	
total wastewater treatment removal (kg/d)	
Conditions and Measures related to external treatment of waste for	r disposal
External treatment and disposal of waste should comply with applicable	local and/or regional
regulations.	•
Conditions and measures related to external recovery of waste	
External recovery and recycling of waste should comply with applicable	local and/or regional
regulations.	-

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
	enable the derivation of a DNEL for eye irritant effects. are based on qualitative risk characterisation.

Section 3.2 -Environment	
Used EUSES model.	

According to EC No 1907/2006 as amended as at the date of this SDS

LINEVOL 911

Version Revision Date: SDS Number: Date of last issue: 06.10.2023

6.0 23.01.2025 800001011477 Print Date 30.01.2025

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	

Risk Management Measures are based on qualitative risk characterisation.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 - Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required.

According to EC No 1907/2006 as amended as at the date of this SDS

LINEVOL 911

Version Revision Date: SDS Number: Date of last issue: 06.10.2023

6.0 23.01.2025 800001011477 Print Date 30.01.2025

Exposure Scenario - Worker

30000000531	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Use in Cleaning Agents- Industrial
Use Descriptor	Sector of Use: SU3 Process Categories: PROC 1, PROC 2, PROC 3, PROC 4, PROC 7, PROC 8a, PROC 8b, PROC 10, PROC 13 Environmental Release Categories: ERC4
Scope of process	Covers the use as a component of cleaning products including transfer from storage, pouring/unloading from drums or containers. Exposures during mixing/diluting in the preparatory phase and cleaning activities (including spraying, brushing, dipping, wiping, automated and by hand), related equipment cleaning and maintenance.

CECTION O	ODERATIONAL CONDITIONS AND DIS	NANAOEMENT
SECTION 2	OPERATIONAL CONDITIONS AND RIS MEASURES	K MANAGEMENT
Section 2.1	Control of Worker Exposure	
Product Characteristics		
Physical form of product	Liquid	
Concentration of the Substance in Mixture/Article	Covers use of substance/product up to 10 differently).,	00% (unless stated
Frequency and Duration of		
	8 hours (unless stated differently).	
Other Operational Conditio	ns affecting Exposure	
	Assumes a good basic standard of occupational hygiene is implemented.	
Contributing Scenarios	Risk Management Measures	
General measures (eye irritants).	Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands. No other specific measures identified.	
Section 2.2	Section 2.2 Control of Environmental Exposure	
Substance is complex UVCB		
Alcohol.		
Readily biodegradable.		
Amounts Used		
Fraction of EU tonnage used	in region:	
Regional use tonnage (tonne	Regional use tonnage (tonnes/year):	
Fraction of Regional tonnage used locally:		
Annual site tonnage (tonnes/year):		0,24
Maximum daily site tonnage (kg/day): 1,1		1,1
Frequency and Duration of Use		
Continuous release.		
Emission Days (days/year):		220

According to EC No 1907/2006 as amended as at the date of this SDS

LINEVOL 911

Version Revision Date: SDS Number: Date of last issue: 06.10.2023

6.0 23.01.2025 800001011477 Print Date 30.01.2025

Environmental factors not influenced by risk management	10
Local freshwater dilution factor:	10
Local marine water dilution factor:	100
Other Operational Conditions affecting Environmental Exposure	T -
Release fraction to air from process (initial release prior to RMM):	0
Release fraction to wastewater from process (initial release prior to	1
RMM):	
Release fraction to soil from process (initial release prior to RMM):	
Technical conditions and measures at process level (source) to pr	event release
Common practices vary across sites thus conservative process re-	
lease estimates used.	
Technical onsite conditions and measures to reduce or limit disch	arges, air emis-
sions and releases to soil	
Risk from environmental exposure is driven by marine water.	
If discharging to domestic sewage treatment plant, no secondary	
wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	0
Treat onsite wastewater (prior to receiving water discharge) to provide	99
the required removal efficiency of >= (%)	
If discharging to domestic sewage treatment plant, no secondary	0
wastewater treatment required.	
Organisational measures to prevent/limit release from site	
Sludge should be incinerated, contained or reclaimed.	
Conditions and Management alots of the management along the transfer of the state o	
Conditions and Measures related to municipal sewage treatment p Estimated substance removal from wastewater via domestic sewage	99
treatment (%)	99
Total efficiency of removal from wastewater after onsite and offsite	99
(domestic treatment plant) RMMs (%)	99
Assumed domestic sewage treatment plant flow (m3/d)	2.000
	2.000
Maximum allowable site tonnage (MSafe) based on release following	
total wastewater treatment removal (kg/d)	- diamanal
Conditions and Measures related to external treatment of waste fo	
External treatment and disposal of waste should comply with applicable	local and/or regiona
regulations.	
Conditions and magazines related to external receivery of weets	
Conditions and measures related to external recovery of waste	local and/a=====
External recovery and recycling of waste should comply with applicable regulations.	iocai and/or regiona

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
Available hazard data do not enable the derivation of a DNEL for eye irritant effects.	
Risk Management Measures are based on qualitative risk characterisation	

Section 3.2 -Environment	
Used EUSES model.	

According to EC No 1907/2006 as amended as at the date of this SDS

LINEVOL 911

Version Revision Date: SDS Number: Date of last issue: 06.10.2023

6.0 23.01.2025 800001011477 Print Date 30.01.2025

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Continu 1.1 Hoolth	

Section 4.1 - Health

Risk Management Measures are based on qualitative risk characterisation. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 -Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required.

According to EC No 1907/2006 as amended as at the date of this SDS

LINEVOL 911

Version Revision Date: SDS Number: Date of last issue: 06.10.2023

6.0 23.01.2025 800001011477 Print Date 30.01.2025

Exposure Scenario - Worker

30000000533		
SECTION 1		
Title	Use in Cleaning Agents- Professional	
Use Descriptor	Sector of Use: SU22 Process Categories: PROC 1, PROC 2, PROC 3, PROC 4, PROC 8a, PROC 8b, PROC 10, PROC 11, PROC 13 Environmental Release Categories: ERC8a, ERC8d	
Scope of process	Covers the use as a component of cleaning products including pouring/unloading from drums or containers; and exposures during mixing/diluting in the preparatory phase and cleaning activities (including spraying, brushing, dipping, wiping automated and by hand).	

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Section 2.1	Control of Worker Exposure	
Product Characteristics		
Physical form of product	Liquid	
Concentration of the Substance in Mixture/Article	Covers use of substance/product up to 10 differently).,	00% (unless stated
Frequency and Duration of		
	8 hours (unless stated differently).	
Other Operational Conditio		
Assumes a good basic standard of occupational hygiene is implemented.		d.
Contributing Scenarios	Risk Management Measures	
General measures (eye irritants).	Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands. No other specific measures identified.	
Section 2.2	Control of Environmental Exposure	
Substance is complex UVCB		
Alcohol.		
Readily biodegradable.		
Amounts Used		
Fraction of EU tonnage used		
Regional use tonnage (tonnes/year):		
Fraction of Regional tonnage used locally:		
Annual site tonnage (tonnes/year):		0,13
Maximum daily site tonnage (kg/day): 0,36		0,36
Frequency and Duration of Use		
Continuous release.		
Emission Days (days/year):		365

According to EC No 1907/2006 as amended as at the date of this SDS

LINEVOL 911

Version Revision Date: SDS Number: Date of last issue: 06.10.2023

6.0 23.01.2025 800001011477 Print Date 30.01.2025

Environmental factors not influenced by risk management	10
Local freshwater dilution factor:	10
Local marine water dilution factor:	100
Other Operational Conditions affecting Environmental Exposure	Га
Release fraction to air from process (initial release prior to RMM):	0
Release fraction to wastewater from process (initial release prior to	1
RMM):	
Release fraction to soil from process (initial release prior to RMM):	
Technical conditions and measures at process level (source) to pr	event release
Common practices vary across sites thus conservative process re-	
lease estimates used.	
Technical onsite conditions and measures to reduce or limit disch sions and releases to soil	arges, air emis-
Risk from environmental exposure is driven by freshwater.	
If discharging to domestic sewage treatment plant, no secondary	
wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	0
Treat onsite wastewater (prior to receiving water discharge) to provide	99
the required removal efficiency of >= (%)	
If discharging to domestic sewage treatment plant, no secondary	0
wastewater treatment required.	
Organisational measures to prevent/limit release from site	
Sludge should be incinerated, contained or reclaimed.	
Conditions and Measures related to municipal sewage treatment p	lant
Estimated substance removal from wastewater via domestic sewage	99
treatment (%)	
Total efficiency of removal from wastewater after onsite and offsite	99
(domestic treatment plant) RMMs (%)	
Assumed domestic sewage treatment plant flow (m3/d)	2.000
Maximum allowable site tonnage (MSafe) based on release following	
total wastewater treatment removal (kg/d)	
Conditions and Measures related to external treatment of waste fo	r disposal
External treatment and disposal of waste should comply with applicable	-
regulations.	ŭ
Conditions and measures related to external recovery of waste	
External recovery and recycling of waste should comply with applicable local and/or regional regulations.	

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
Available hazard data do not enable the derivation of a DNEL for eye irritant effects.	
Risk Management Measures are based on qualitative risk characterisation.	

Section 3.2 -Environment	
Used EUSES model.	

According to EC No 1907/2006 as amended as at the date of this SDS

LINEVOL 911

SDS Number: Date of last issue: 06.10.2023 Version Revision Date:

23.01.2025 800001011477 Print Date 30.01.2025 6.0

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	

Risk Management Measures are based on qualitative risk characterisation. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 -Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a sitespecific chemical safety assessment is required.

According to EC No 1907/2006 as amended as at the date of this SDS

LINEVOL 911

Version Revision Date: SDS Number: Date of last issue: 06.10.2023

6.0 23.01.2025 800001011477 Print Date 30.01.2025

Exposure Scenario - Consumer

30000001058	0000001058	
SECTION 1	EXPOSURE SCENARIO TITLE	
Title	Uses in Coatings - Consumer	
Use Descriptor	Sector of Use: SU21 Product Categories: PC1, PC4, PC8 (excipient only), PC9a, PC9b, PC9c, PC15, PC18, PC23, PC24, PC31, PC34 Environmental Release Categories: ERC8a, ERC8d	
Scope of process	Covers the use in coatings (paints, inks, adhesives, etc) including exposures during use (including product transfer and preparation, application by brush, spray by hand or similar methods) and equipment cleaning.	

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
Section 2.1	Control of Consumer Exposure
Product Characteristics	
Product Categories	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
General measures applicable to all Product Categories.	No risk management measures required if the substance in the mixture is below the classification threshold.
General measures (eye irritants).	Avoid direct eye contact with product, also via contamination on hands.

Section 2.2	Control of Environmental Exposure	
Substance is complex UVCB.		
Alcohol.		
Readily biodegradable.		
Amounts Used		
Fraction of EU tonnage used	in region:	
Regional use tonnage (tonnes	s/year):	
Fraction of Regional tonnage	used locally:	
Annual site tonnage (tonnes/)		0,16
Maximum daily site tonnage (kg/day):	0,53
Frequency and Duration of Use		
Continuous release.		
Emission Days (days/year):		300
Environmental factors not influenced by risk management		
Local freshwater dilution factor	or:	10
Local marine water dilution fa		100
Other Operational Conditions affecting Environmental Exposure		
Release fraction to air from pr	rocess (initial release prior to RMM):	0,01
	er from process (initial release prior to	0,01
RMM):		
Release fraction to soil from process (initial release prior to RMM):		

According to EC No 1907/2006 as amended as at the date of this SDS

LINEVOL 911

Version Revision Date: SDS Number: Date of last issue: 06.10.2023

6.0 23.01.2025 800001011477 Print Date 30.01.2025

Conditions and Measures related to municipal sewage treatment plant	
Risk from environmental exposure is driven by marine water.	
Estimated substance removal from wastewater via domestic sewage	99
treatment (%)	
Assumed domestic sewage treatment plant flow (m3/d)	2.000
Maximum allowable site tonnage (MSafe) based on release following	
total wastewater treatment removal (kg/d)	

Conditions and Measures related to external treatment of waste for disposal

External treatment and disposal of waste should comply with applicable local and/or regional regulations.

Conditions and measures related to external recovery of waste

External recovery and recycling of waste should comply with applicable local and/or regional regulations.

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
Available hazard data do not enable the derivation of a DNEL for eye irritant effects.	
Risk Management Measures are based on qualitative risk characterisation.	

Section 3.2 -Environment
Used EUSES model.

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE
	EXPOSURE SCENARIO

Section 4.1 - Health

Risk Management Measures are based on qualitative risk characterisation. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 - Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

According to EC No 1907/2006 as amended as at the date of this SDS

LINEVOL 911

Version Revision Date: SDS Number: Date of last issue: 06.10.2023

6.0 23.01.2025 800001011477 Print Date 30.01.2025

Exposure Scenario - Consumer

30000001059	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Use in Cleaning Agents - Consumer
Use Descriptor	Sector of Use: SU21 Product Categories: PC3, PC4, PC8 (excipient only), PC9a, PC24, PC35, Environmental Release Categories: ERC8a, ERC8d
Scope of process	Covers general exposures to consumers arising from the use of household products sold as washing and cleaning products, aerosols, coatings, de-icers, lubricants and air care products.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
Section 2.1	Control of Consumer Exposure
Product Characteristics	
Product Categories	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
General measures applicable to all Product Categories.	No risk management measures required if the substance in the mixture is below the classification threshold.
General measures (eye irritants).	Avoid direct eye contact with product, also via contamination on hands.

Section 2.2	Control of Environmental Exposure	
Substance is complex UVCB.		
Alcohol.		
Readily biodegradable.		
Amounts Used		
Fraction of EU tonnage used	in region:	
Regional use tonnage (tonnes/year):		
Fraction of Regional tonnage	used locally:	
Annual site tonnage (tonnes/		0,069
Maximum daily site tonnage (kg/day): 0,19		0,19
Frequency and Duration of Use		
Continuous release.		
Emission Days (days/year):		365
Environmental factors not influenced by risk management		
Local freshwater dilution factor	or:	10
Local marine water dilution fa		100
Other Operational Conditions affecting Environmental Exposure		
Release fraction to air from p	rocess (initial release prior to RMM):	0
Release fraction to wastewate RMM):	er from process (initial release prior to	1
Release fraction to soil from	process (initial release prior to RMM):	

According to EC No 1907/2006 as amended as at the date of this SDS

LINEVOL 911

Version Revision Date: SDS Number: Date of last issue: 06.10.2023

6.0 23.01.2025 800001011477 Print Date 30.01.2025

Conditions and Measures related to municipal sewage treatment plant	
Risk from environmental exposure is driven by freshwater.	
Estimated substance removal from wastewater via domestic sewage	99
treatment (%)	
Assumed domestic sewage treatment plant flow (m3/d)	2.000
Maximum allowable site tonnage (MSafe) based on release following	
total wastewater treatment removal (kg/d)	

Conditions and Measures related to external treatment of waste for disposal

External treatment and disposal of waste should comply with applicable local and/or regional regulations.

Conditions and measures related to external recovery of waste

External recovery and recycling of waste should comply with applicable local and/or regional regulations.

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
Available hazard data do not enable the derivation of a DNEL for eye irritant effects.	

Risk Management Measures are based on qualitative risk characterisation.

Section 3.2 -Environment Used EUSES model.

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	EXI COURT OCENANIO

Risk Management Measures are based on qualitative risk characterisation.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 - Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.