Prepared according to GB/T 16483, GB/T 17519

800010016387 NEODOL LM3

Revision Date 2023.11.21 Print Date 2023.11.28 Version 1.2

### 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : NEODOL LM3

Product code V2681, V2690

CAS-No. : 68439-50-9

## Manufacturer or supplier's details

Supplier

SHELL EASTERN CHEMICALS (S)

A REGISTERED BUSINESS OF SHELL EASTERN

TRADING (PTE) LTD (UEN:198902087C)

9 North Buona Vista Drive, #07-01

The Metropolis Tower 1 Singapore 138588

Singapore

Telephone : +65 6384 8269 Telefax : +65 6384 8454

Contact for Safety Data : If you have any enquiries about the content of this SDS

Sheet

please email sccmsds@shell.com 如果您有关于该SDS内容的

任何质询,请发电邮联系 sccmsds@shell.com

Emergency telephone

Restrictions on use

number

: +86-532-83889090

Recommended use of the chemical and restrictions on use

Recommended use : Use in detergent manufacture.

> This product must not be used in applications other than the above without first seeking the advice of the supplier.

Other information : NEODOL is a trademark owned by Shell Trademark

Management B.V. and Shell Brands Inc. and used by affiliates

of Royal Dutch Shell plc.

### 2. HAZARDS IDENTIFICATION

#### **Emergency Overview**

Appearance	Clear to slightly hazy liquid.	
Colour	Colourless to yellowish	
Odour	Data not available	
Health Hazards	Causes eye irritation.	
Safety Hazards	Not classified as flammable but will burn.	
Environmental Hazards	Very toxic to aquatic life. Harmful to aquatic life with long lasting effects.	

Prepared according to GB/T 16483, GB/T 17519

## NEODOL LM3

Revision Date 2023.11.21

**GHS Classification** 

Category 2B Eye irritation Short-term (acute) aquatic Category 1

Version 1.2

Long-term (chronic) aquatic

hazard

: Category 3

**GHS** label elements

Hazard pictograms

Signal word Warning

Hazard statements PHYSICAL HAZARDS:

Not classified as a physical hazard under GHS criteria.

800010016387

Print Date 2023.11.28

**HEALTH HAZARDS:** H320 Causes eye irritation. **ENVIRONMENTAL HAZARDS:** H400 Very toxic to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention:

P264 Wash hands thoroughly after handling. P273 Avoid release to the environment.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice/

attention.

P391 Collect spillage.

Storage:

No precautionary phrases.

Disposal:

P501 Dispose of contents and container to appropriate waste site or reclaimer in accordance with local and national

regulations.

Other hazards which do not result in classification

Repeated exposure may cause skin dryness or cracking.

Physical and chemical Not classified as flammable but will burn.

# **NEODOL LM3**

800010016387

/ersion 1.2		Revision Date 2023.11.21	Print Date 2023.11.28
	hazards		
	Health Hazards	Inhalation: No specific hazards under Skin: Causes mild skin irritation. Repeated exposure may cause skin of Eyes: Causes eye irritation. Ingestion: No specific hazards under	dryness or cracking.
	Environmental Hazards	Very toxic to aquatic life.Harmful to a effects.	quatic life with long lasting

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Substance

## **Hazardous components**

Chemical name	CAS-No.	Classification	Concentration (% w/w)
C12-14 Alcohol ethoxylate		Eye Irrit.2B; H320 Aquatic Acute1; H400 Aquatic Chronic3; H412	<= 100

For explanation of abbreviations see section 16.

## 4. FIRST-AID MEASURES

General advice : Not expected to be a health hazard when used under normal

conditions.

If inhaled : No treatment necessary under normal conditions of use. If

symptoms persist, obtain medical advice.

: Remove contaminated clothing. Flush exposed area with In case of skin contact

> water and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention.

: Immediately flush eye(s) with plenty of water. In case of eye contact

Remove contact lenses, if present and easy to do. Continue

Transport to the nearest medical facility for additional

treatment.

If swallowed : In general no treatment is necessary unless large quantities

are swallowed, however, get medical advice.

Most important symptoms and effects, both acute and

delayed

: Not considered to be an inhalation hazard under normal

conditions of use.

Possible respiratory irritation signs and symptoms may include

a temporary burning sensation of the nose and throat,

coughing, and/or difficulty breathing.

No specific hazards under normal use conditions.

Skin irritation signs and symptoms may include a burning

Prepared according to GB/T 16483, GB/T 17519

NEODOL LM3

800010016387

Version 1.2 Revision Date 2023.11.21 Print Date 2023.11.28

sensation, redness, or swelling.

Eye irritation signs and symptoms may include a burning sensation, redness, swelling, and/or blurred vision.

No specific hazards under normal use conditions.

Ingestion may result in nausea, vomiting and/or diarrhoea.

Defatting dermatitis signs and symptoms may include a burning sensation and/or a dried/cracked appearance.

Protection of first-aiders When administering first aid, ensure that you are wearing the

appropriate personal protective equipment according to the

incident, injury and surroundings.

Notes to physician IMMEDIATE TREATMENT IS EXTREMELY IMPORTANT!

Call a doctor or poison control center for guidance.

Treat symptomatically.

#### 5. FIRE-FIGHTING MEASURES

: Alcohol-resistant foam, water spray or fog. Dry chemical Suitable extinguishing media

powder, carbon dioxide, sand or earth may be used for small

fires only.

Unsuitable extinguishing

media

: None

Specific hazards during

firefighting

: Carbon monoxide may be evolved if incomplete combustion

occurs.

Specific extinguishing

methods

: Standard procedure for chemical fires.

Clear fire area of all non-emergency personnel.

Keep adjacent containers cool by spraying with water.

Special protective equipment

for firefighters

: Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if

large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to

relevant Standards (e.g. Europe: EN469).

### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

: Observe all relevant local and international regulations. Notify authorities if any exposure to the general public or the

environment occurs or is likely to occur.

Local authorities should be advised if significant spillages

cannot be contained.

Prepared according to GB/T 16483, GB/T 17519

## NEODOL LM3

800010016387

Version 1.2 Revision Date 2023.11.21 Print Date 2023.11.28

> Avoid contact with spilled or released material. Immediately remove all contaminated clothing. For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet. For guidance on disposal of spilled material see

Section 13 of this Safety Data Sheet. Stav upwind and keep out of low areas. Be ready for fire or possible exposure.

: Prevent from spreading or entering into drains, ditches or **Environmental precautions** 

rivers by using sand, earth, or other appropriate barriers. Use appropriate containment to avoid environmental

contamination.

Ventilate contaminated area thoroughly.

Methods and materials for containment and cleaning up For large liquid spills (> 1 drum), transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely For small liquid spills (< 1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove

contaminated soil and dispose of safely.

Additional advice : For guidance on selection of personal protective equipment

see Section 8 of this Safety Data Sheet.

For guidance on disposal of spilled material see Section 13 of

this Safety Data Sheet.

### 7. HANDLING AND STORAGE

## Handling

**General Precautions** : Avoid breathing of or direct contact with material. Only use in

well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see

Section 8 of this Safety Data Sheet.

Use the information in this data sheet as input to a risk assessment of local circumstances to help determine

appropriate controls for safe handling, storage and disposal of

this material.

Ensure that all local regulations regarding handling and

storage facilities are followed.

: Avoid contact with skin, eyes and clothing. Advice on safe handling

Do not empty into drains.

Avoidance of contact : Copper.

Copper alloys.

Strong oxidising agents.

Aluminum

Prepared according to GB/T 16483, GB/T 17519

## **NEODOL LM3**

800010016387

Version 1.2 Revision Date 2023.11.21 Print Date 2023.11.28

Product Transfer : Keep containers closed when not in use. Refer to guidance

under Handling section.

**Storage** 

Conditions for safe storage : Refer to section 15 for any additional specific legislation

covering the packaging and storage of this product.

Other data : Tanks should be fitted with heating coils in areas where the

ambient temperatures are below the recommended product handling temperatures. Heating coil skin temperatures should

not exceed 100 °C.

Bulk storage tanks should be diked (bunded).

Vapours from tanks should not be released to atmosphere. Breathing losses during storage should be controlled by a

suitable vapour treatment system.

Nitrogen blanket recommended for large tanks (capacity 100

m3 or higher).

Insulation (lagging) will minimize heat loss in areas of low

ambient temperature.

Tanks should be fitted with heating coils in areas where ambient conditions can result in handling temperatures below

the freezing point/pour point of the product.

Packaging material : Suitable material: Stainless steel., Epoxy resins, Polyester.

Unsuitable material: Aluminum, Copper., Copper alloys.

Container Advice : Containers, even those that have been emptied, can contain

explosive vapours. Do not cut, drill, grind, weld or perform

similar operations on or near containers.

Specific use(s) : Not applicable

Ensure that all local regulations regarding handling and

storage facilities are followed.

### 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

## Components with workplace control parameters

#### **Biological occupational exposure limits**

No biological limit allocated.

### **Monitoring Methods**

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or

# NEODOL LM3

Version 1.2 Revision Date 2023.11.21 Print Date 2023.11.28

contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany http://www.dauv.de/inhalt/index.isp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

#### **Engineering measures**

: Adequate ventilation to control airborne concentrations below the exposure guidelines/limits.

800010016387

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated. Eye washes and showers for emergency use.

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

#### General Information:

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

Do not ingest. If swallowed, then seek immediate medical assistance.

### Personal protective equipment

#### Protective measures

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Respiratory protection : If engineering controls do not maintain airborne

concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers.

## NEODOL LM3

800010016387

Version 1.2 Revision Date 2023.11.21 Print Date 2023.11.28

> Where air-filtering respirators are unsuitable (e.g. airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter.

> If air-filtering respirators are suitable for conditions of use: Select a filter suitable for the combination of organic gases and vapours and particles [Type A/Type P boiling point >65°C

(149°F)].

Hand protection Remarks

: Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. Longer term protection: Nitrile rubber gloves. Incidental contact/Splash protection: PVC or neoprene rubber gloves. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

Eye protection Wear goggles for use against liquids and gas. Wear full face shield if splashes are likely to occur.

Skin and body protection : Skin protection is not required under normal conditions of use.

For prolonged or repeated exposures use impervious clothing

over parts of the body subject to exposure.

If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to relevant Standard,

and provide employee skin care programmes.

Thermal hazards : Not applicable

Hygiene measures : Wash hands before eating, drinking, smoking and using the

toilet.

Launder contaminated clothing before re-use.

Prepared according to GB/T 16483, GB/T 17519

NEODOL LM3 800010016387

Version 1.2 Revision Date 2023.11.21 Print Date 2023.11.28

**Environmental exposure controls** 

General advice : Local guidelines on emission limits for volatile substances

must be observed for the discharge of exhaust air containing

vapour.

Minimise release to the environment. An environmental assessment must be made to ensure compliance with local

environmental legislation.

Information on accidental release measures are to be found in

section 6.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Clear to slightly hazy liquid.

Colour : Colourless to yellowish

Odour : Data not available
Odour Threshold : Data not available

pH : 6-8

Melting point/range : Data not available Boiling point/boiling range : 250 °C / 482 °F

Flash point :  $> 148.9 \, ^{\circ}\text{C} / 300.0 \, ^{\circ}\text{F}$ 

Method: Pensky-Martens closed cup

Evaporation rate : Data not available Flammability (solid, gas) : Data not available

Burning rate : no data available
Upper explosion limit : Data not available
Lower explosion limit : Data not available

Vapour pressure : <= 13 hPa (20 °C / 68 °F)

Relative vapour density : Data not available

Density : 0.96 g/cm3 (50 °C / 122 °F)

Solubility(ies)

Water solubility : Data not available Solubility in other solvents : Data not available

Partition coefficient: n-

octanol/water

: Data not available

Auto-ignition temperature : Data not available

Decomposition temperature : Data not available

Viscosity

Prepared according to GB/T 16483, GB/T 17519

NEODOL LM3 800010016387

Version 1.2 Revision Date 2023.11.21 Print Date 2023.11.28

Viscosity, dynamic : Data not available
Viscosity, kinematic : Data not available
Explosive properties : no data available
Oxidizing properties : Data not available

Surface tension : Data not available

Conductivity : Data not available
Particle size : Data not available

#### 10. STABILITY AND REACTIVITY

Reactivity : Stable at normal ambient temperature and pressure., May

oxidise in the presence of air.

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: None known.

Conditions to avoid : Extremes of temperature and direct sunlight.

Product cannot ignite due to static electricity.

Incompatible materials : Copper.

Copper alloys.

Strong oxidising agents.

Aluminum

Hazardous decomposition

products

: None expected under normal use conditions.

### 11. TOXICOLOGICAL INFORMATION

Basis for assessment : Information given is based on product testing, and/or similar

products, and/or components.

Exposure routes : Exposure may occur via inhalation, ingestion, skin absorption,

skin or eye contact, and accidental ingestion.

**Acute toxicity** 

**Product:** 

Acute oral toxicity : LD50 Rat: > 5000 mg/kg

Remarks: Low toxicity

Acute inhalation toxicity : Remarks: Low toxicity by inhalation.

Prepared according to GB/T 16483, GB/T 17519

800010016387 NEODOL LM3

Version 1.2 Revision Date 2023.11.21 Print Date 2023.11.28

Acute dermal toxicity : LD50 Rabbit: > 2000 mg/kg

Remarks: Low toxicity

Based on available data, the classification criteria are not met.

**Components:** 

C12-14 Alcohol ethoxylate:

Acute oral toxicity : LD50 Rat: > 5000 mg/kg

Remarks: Low toxicity

Acute inhalation toxicity : Remarks: Low toxicity by inhalation.

: LD50 Rabbit: > 2000 mg/kg Acute dermal toxicity

Remarks: Low toxicity

Based on available data, the classification criteria are not met.

#### Skin corrosion/irritation

### **Product:**

Remarks: Causes mild skin irritation., Repeated exposure may cause skin dryness or cracking.

### Components:

### C12-14 Alcohol ethoxylate:

Remarks: Causes mild skin irritation., Repeated exposure may cause skin dryness or cracking.

### Serious eye damage/eye irritation

## **Product:**

Remarks: Expected to be irritating to eyes.

# Components:

## C12-14 Alcohol ethoxylate:

Remarks: Expected to be irritating to eyes.

### Respiratory or skin sensitisation

#### **Product:**

Remarks: Not a sensitiser.

Based on available data, the classification criteria are not met.

## **Components:**

### C12-14 Alcohol ethoxylate:

Remarks: Not a sensitiser.

Based on available data, the classification criteria are not met.

### Germ cell mutagenicity

#### **Product:**

: Remarks: Non mutagenic

Prepared according to GB/T 16483, GB/T 17519

# **NEODOL LM3**

800010016387

Print Date 2023.11.28 Version 1.2 Revision Date 2023.11.21

**Components:** 

C12-14 Alcohol ethoxylate:

: Remarks: Non mutagenic

Carcinogenicity

**Product:** 

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

## **Components:**

#### C12-14 Alcohol ethoxylate:

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

Material	GHS/CLP Carcinogenicity Classification
C12-14 Alcohol ethoxylate	No carcinogenicity classification.

### Reproductive toxicity

**Product:** 

Remarks: Not a developmental toxicant., Based on available data, the classification criteria are not met., Does not impair fertility.

Components:

C12-14 Alcohol ethoxylate:

Remarks: Not a developmental toxicant., Based on available data, the classification criteria are not met., Does not impair fertility.

### STOT - single exposure

## **Product:**

Remarks: Based on available data, the classification criteria are not met.

## **Components:**

### C12-14 Alcohol ethoxylate:

Remarks: Based on available data, the classification criteria are not met.

## STOT - repeated exposure

#### **Product:**

Prepared according to GB/T 16483, GB/T 17519

NEODOL LM3 800010016387

Version 1.2 Revision Date 2023.11.21 Print Date 2023.11.28

Remarks: Based on available data, the classification criteria are not met.

#### **Components:**

## C12-14 Alcohol ethoxylate:

Remarks: Based on available data, the classification criteria are not met.

### **Aspiration toxicity**

#### **Product:**

Not an aspiration hazard.

### Components:

#### C12-14 Alcohol ethoxylate:

Not an aspiration hazard.

#### **Further information**

#### **Product:**

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

#### **Components:**

## C12-14 Alcohol ethoxylate:

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

### 12. ECOLOGICAL INFORMATION

Basis for assessment : Incomplete ecotoxicological data are available for this product.

The information given below is based partly on a knowledge of the components and the ecotoxicology of similar products.

## **Ecotoxicity**

## **Product:**

Toxicity to fish (Acute

toxicity) Remarks: LC/EC/IC50 < 1 mg/l

Very toxic.

Toxicity to crustacean (Acute

toxicity)

Remarks: LC/EC/IC50 < 1 mg/l

Very toxic.

Toxicity to algae/aquatic

plants (Acute toxicity)

Remarks: LC/EC/IC50 < 1 mg/l

Very toxic.

Toxicity to fish (Chronic

toxicity)

: Remarks: NOEC/NOEL > 0.1 - <=1.0 mg/l

Toxicity to crustacean (Chronic toxicity)

: Remarks: NOEC/NOEL > 0.1 - <=1.0 mg/l

13 / 18 800010016387 CN

Prepared according to GB/T 16483, GB/T 17519

800010016387 NEODOL LM3

Version 1.2 Revision Date 2023.11.21 Print Date 2023.11.28

Toxicity to microorganisms

(Acute toxicity)

Remarks: LC/EC/IC50 > 100 mg/l

Practically non toxic:

Based on available data, the classification criteria are not met.

Components:

C12-14 Alcohol ethoxylate:

Toxicity to fish (Acute

toxicity)

: Remarks: LC/EC/IC50 < 1 mg/l

Very toxic.

Toxicity to crustacean (Acute

toxicity)

: Remarks: LC/EC/IC50 < 1 mg/l

Very toxic.

Toxicity to algae/aguatic

plants (Acute toxicity)

: Remarks: LC/EC/IC50 < 1 mg/l

Very toxic.

: 1

M-Factor (Short-term (acute)

aquatic hazard)

Toxicity to microorganisms

(Acute toxicity)

: Remarks: LC/EC/IC50 > 100 mg/l

Practically non toxic:

Based on available data, the classification criteria are not met.

Toxicity to fish (Chronic

toxicity)

Toxicity to

: Remarks: NOEC/NOEL > 0.1 - <=1.0 mg/l : Remarks: NOEC/NOEL > 0.1 - <=1.0 mg/l

crustacean(Chronic toxicity)

Persistence and degradability

**Product:** 

Biodegradability : Remarks: Readily biodegradable.

Components:

C12-14 Alcohol ethoxylate:

Biodegradability : Remarks: Readily biodegradable.

Bioaccumulative potential

**Product:** 

Bioaccumulation : Remarks: Bioaccumulation is unlikely to occur due to

metabolism and excretion.

Partition coefficient: n-

octanol/water

: Remarks: Data not available

**Components:** 

C12-14 Alcohol ethoxylate:

Remarks: Bioaccumulation is unlikely to occur due to Bioaccumulation

metabolism and excretion.

Mobility in soil

**Product:** 

Mobility : Remarks: Floats on water., If product enters soil, it will be

highly mobile and may contaminate groundwater.

14 / 18 800010016387 CN

Prepared according to GB/T 16483, GB/T 17519

NEODOL LM3 800010016387

Version 1.2 Revision Date 2023.11.21 Print Date 2023.11.28

**Components:** 

C12-14 Alcohol ethoxylate:

Mobility : Remarks: Floats on water., If product enters soil, it will be

highly mobile and may contaminate groundwater.

Other adverse effects

no data available

#### 13. DISPOSAL CONSIDERATIONS

### **Disposal methods**

Waste from residues : Recover or recycle if possible.

It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.

Do not dispose into the environment, in drains or in water

courses.

Waste product should not be allowed to contaminate soil or

water.

Disposal should be in accordance with applicable regional,

national, and local laws and regulations.

Local regulations may be more stringent than regional or

national requirements and must be complied with.

Contaminated packaging : Drain container thoroughly.

After draining, vent in a safe place away from sparks and fire.

Residues may cause an explosion hazard.
Do not puncture, cut, or weld uncleaned drums.
Send to drum recoverer or metal reclaimer.

Local legislation

Remarks : If potential for exposure exists refer to Section 8 for specific

personal protective equipment.

#### 14. TRANSPORT INFORMATION

# International Regulations

ADR

UN number : 3082

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(Alcohol C12-C16 Poly (1-6) Ethoxylate)

Class : 9
Packing group : III
Labels : 9
Hazard Identification Number : 90

Prepared according to GB/T 16483, GB/T 17519

NEODOL LM3 800010016387

Version 1.2 Revision Date 2023.11.21 Print Date 2023.11.28

Environmentally hazardous : yes

**IATA-DGR** 

UN/ID No. : UN 3082

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S

(Alcohol C12-C16 Poly (1-6) Ethoxylate)

Class : 9
Packing group : III
Labels : 9

**IMDG-Code** 

UN number : UN 3082

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(Alcohol C12-C16 Poly (1-6) Ethoxylate)

Class : 9
Packing group : III
Labels : 9
Marine pollutant : yes

### Maritime transport in bulk according to IMO instruments

Pollution category : Y Ship type : 2

Product name : ALCOHOL (C12-C16) POLY (1-6) ETHOXYLATES

Special precautions for user

Remarks : Special Precautions: Refer to Section 7, Handling & Storage,

for special precautions which a user needs to be aware of or

needs to comply with in connection with transport.

**Additional Information**: This product may be transported under nitrogen blanketing.

Nitrogen is an odourless and invisible gas. Exposure to nitrogen may cause asphyxiation or death. Personnel must observe strict safety precautions when involved with a

confined space entry.

## 15. REGULATORY INFORMATION

#### **National regulatory information**

Rotterdam Convention (Prior Informed Consent)

Not applicable

Stockholm Convention (Persistent Organic Pollutants)

Not applicable

### Law on the Prevention and Control of Occupational Diseases

The categories of occupational disease:

Not applicable

Occupational Disease Classification list:

Not applicable

## **Regulations on Safety Management of Hazardous Chemicals**

Catalogue of Hazardous Chemicals : Not applicable

Prepared according to GB/T 16483, GB/T 17519

## NEODOL LM3

800010016387

Print Date 2023.11.28 Version 1.2 Revision Date 2023.11.21

Identification of Major Hazard Installations for

Hazardous Chemicals (GB 18218)

Not applicable

Hazardous Chemicals for Priority Management under

SAWS

Not applicable

#### Regulations on Labour Protection in Workplaces where Toxic Substances are Used

Catalogue of Highly Toxic Chemicals : Not applicable

## Regulation of Environmental Management on the First Import of Chemicals and the Import and Export of Toxic Chemicals

Catalogue of Toxic Chemicals Severely Restricted in Not applicable

China

## Other international regulations

#### The components of this product are reported in the following inventories:

AICS : Listed DSL Listed **IECSC** Listed KECI : Listed **PICCS** : Listed TSCA : Listed **ENCS** : Listed

#### 16. OTHER INFORMATION

### **Full text of H-Statements**

H320 Causes eve irritation. H400 Very toxic to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

## Full text of other abbreviations

Aquatic Acute Short-term (acute) aquatic hazard Aquatic Chronic Long-term (chronic) aquatic hazard

Eye Irrit. Eye irritation

### **Abbreviations and Acronyms**

AIIC - Australian Inventory of Industrial Chemicals: ANTT - National Agency for Transport by Land of Brazil: ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing

Prepared according to GB/T 16483, GB/T 17519

## NEODOL LM3

Version 1.2

Revision Date 2023.11.21

Print Date 2023.11.28 Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 -Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships: n.o.s. - Not Otherwise Specified: Nch - Chilean Norm: NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate: NOM - Official Mexican Norm: NTP - National Toxicology Program: NZIoC -New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG -Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

### **Further information**

: Provide adequate information, instruction and training for Training advice

operators.

Other information : A vertical bar (|) in the left margin indicates an amendment

from the previous version.

Sources of key data used to compile the Safety Data

Sheet

: The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU

IUCLID date base, EC 1272 regulation, etc).

### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a quidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CN / EN

18 / 18 800010016387

800010016387