

SAFETY DATA SHEET

Mexican official standard NOM-018-STPS-2015

ShellSol A150 ND

Version
1.1

Revision Date:
11/24/2023

SDS Number:
800001007477

Print Date: 12/01/2023
Date of last issue: 04.08.2023

SECTION 1. IDENTIFICATION OF THE HAZARDOUS PRODUCT OR MIXTURE AND THE SUPPLIER OR MANUFACTURER

Product name : ShellSol A150 ND

Product code : Q7497

Synonyms : Hydrocarbons, C10, aromatics, <1% naphthalene

CAS-No. : 64742-94-5

Manufacturer or supplier's details

Company : **Shell Chemical LP**
PO Box 576
HOUSTON TX 77001
USA

SDS Request : +52 (55) 3223 9057

Customer Service : +52 (55) 5089 5792, +52 (55) 5089 5790

Emergency telephone number

Chemtrec Domestic (24 hr) : SETIQ ANIQ 800 002 1400 (Rep. Mexicana), +52 (55) 5559 1588 (local e internacional)

Chemtrec International (24 hr) : CHEMTREC +1 (703) 527-3887 (Internacional)

Recommended use of the chemical and restrictions on use

Recommended use : Industrial Solvent.

Restrictions on use : This product must not be used in applications other than the above without first seeking the advice of the supplier.

Other information : SHELLSOL is a trademark owned by Shell Trademark Management B.V. and Shell Brands Inc. and used by affiliates of Shell plc.

SECTION 2. HAZARDS IDENTIFICATION

Flammable liquids : Category 4

Aspiration hazard : Category 1

Specific target organ toxicity - single exposure : Category 3 (Narcotic effects)

Short-term (acute) aquatic hazard : Category 2

SAFETY DATA SHEET

Mexican official standard NOM-018-STPS-2015

ShellSol A150 ND

Version
1.1

Revision Date:
11/24/2023

SDS Number:
800001007477

Print Date: 12/01/2023
Date of last issue: 04.08.2023

Long-term (chronic) aquatic hazard : Category 2

GHS label elements

Other hazards which do not result in classification

In use, may form flammable/explosive vapour-air mixture.

This material is a static accumulator.

Even with proper grounding and bonding, this material can still accumulate an electrostatic charge.

If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur.

Repeated exposure may cause skin dryness or cracking.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Substance

Hazardous components

Chemical name	Synonyms	CAS-No.	Concentration (% w/w)
Solvent naphtha (petroleum), heavy aromatic	Solvent naphtha (petroleum), heavy arom.	64742-94-5	<= 100

Further information

Contains:

Chemical name	Identification number	Concentration (% w/w)
Naphthalene	91-20-3	<1

SECTION 4. FIRST-AID MEASURES

- General advice : Not expected to be a health hazard when used under normal conditions.
- If inhaled : Remove to fresh air. If rapid recovery does not occur, transport to nearest medical facility for additional treatment.
- In case of skin contact : Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available.
If persistent irritation occurs, obtain medical attention.
- In case of eye contact : Flush eye with copious quantities of water.
Remove contact lenses, if present and easy to do. Continue rinsing.
If persistent irritation occurs, obtain medical attention.
- If swallowed : Call emergency number for your location / facility.
If swallowed, do not induce vomiting: transport to nearest medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.
If any of the following delayed signs and symptoms appear

SAFETY DATA SHEET

Mexican official standard NOM-018-STPS-2015

ShellSol A150 ND

Version
1.1

Revision Date:
11/24/2023

SDS Number:
800001007477

Print Date: 12/01/2023
Date of last issue: 04.08.2023

		within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (38.3°C), shortness of breath, chest congestion or continued coughing or wheezing.
Most important symptoms and effects, both acute and delayed	:	<p>Breathing of high vapour concentrations may cause central nervous system (CNS) depression resulting in dizziness, light-headedness, headache, nausea and loss of coordination. Continued inhalation may result in unconsciousness and death.</p> <p>No specific hazards under normal use conditions.</p> <p>Skin irritation signs and symptoms may include a burning sensation, redness, or swelling.</p> <p>No specific hazards under normal use conditions.</p> <p>Eye irritation signs and symptoms may include a burning sensation, redness, swelling, and/or blurred vision.</p> <p>If material enters lungs, signs and symptoms may include coughing, choking, wheezing, difficulty in breathing, chest congestion, shortness of breath, and/or fever.</p> <p>If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (38.3°C), shortness of breath, chest congestion or continued coughing or wheezing.</p> <p>Defatting dermatitis signs and symptoms may include a burning sensation and/or a dried/cracked appearance.</p>
Protection of first-aiders	:	When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.
Indication of any immediate medical attention and special treatment needed	:	<p>Call a doctor or poison control center for guidance.</p> <p>Potential for chemical pneumonitis.</p> <p>Treat symptomatically.</p>

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	:	Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
Unsuitable extinguishing media	:	Do not use water in a jet.
Specific hazards during fire-fighting	:	<p>Clear fire area of all non-emergency personnel.</p> <p>Hazardous combustion products may include:</p> <p>A complex mixture of airborne solid and liquid particulates and gases (smoke).</p> <p>Carbon monoxide.</p> <p>Unidentified organic and inorganic compounds.</p> <p>Flammable vapours may be present even at temperatures below the flash point.</p> <p>The vapour is heavier than air, spreads along the ground and distant ignition is possible.</p> <p>Will float and can be reignited on surface water.</p>
Specific extinguishing method	:	Standard procedure for chemical fires.

SAFETY DATA SHEET

Mexican official standard NOM-018-STPS-2015

ShellSol A150 ND

Version
1.1

Revision Date:
11/24/2023

SDS Number:
800001007477

Print Date: 12/01/2023
Date of last issue: 04.08.2023

ods

Further information : Keep adjacent containers cool by spraying with water.

Special protective equipment for firefighters : Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Observe all relevant local and international regulations. Notify authorities if any exposure to the general public or the environment occurs or is likely to occur. Local authorities should be advised if significant spillages cannot be contained. Avoid contact with skin, eyes and clothing. Isolate hazard area and deny entry to unnecessary or unprotected personnel. Do not breathe fumes, vapour. Do not operate electrical equipment.

Environmental precautions : Shut off leaks, if possible without personal risks. Remove all possible sources of ignition in the surrounding area. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. Attempt to disperse the vapour or to direct its flow to a safe location for example by using fog sprays. Take precautionary measures against static discharge. Ensure electrical continuity by bonding and grounding (earthing) all equipment. Monitor area with combustible gas indicator.

Methods and materials for containment and cleaning up : For small liquid spills (< 1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely. For large liquid spills (> 1 drum), transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely. Ventilate contaminated area thoroughly. If contamination of site occurs remediation may require specialist advice.

Additional advice : For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet.

SAFETY DATA SHEET

Mexican official standard NOM-018-STPS-2015

ShellSol A150 ND

Version
1.1

Revision Date:
11/24/2023

SDS Number:
800001007477

Print Date: 12/01/2023
Date of last issue: 04.08.2023

For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.

SECTION 7. HANDLING AND STORAGE

- Technical measures : Avoid breathing of or direct contact with material. Only use in well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet.
Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.
Ensure that all local regulations regarding handling and storage facilities are followed.
- Precautions that must be taken to ensure safe handling : Avoid inhaling vapour and/or mists.
Avoid contact with skin, eyes and clothing.
Extinguish any naked flames. Do not smoke. Remove ignition sources. Avoid sparks.
Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols.
Bulk storage tanks should be diked (bunded).
When using do not eat or drink.

The vapour is heavier than air, spreads along the ground and distant ignition is possible.
- Avoidance of contact : Strong oxidising agents.
- Product Transfer : Even with proper grounding and bonding, this material can still accumulate an electrostatic charge. If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur. Be aware of handling operations that may give rise to additional hazards that result from the accumulation of static charges. These include but are not limited to pumping (especially turbulent flow), mixing, filtering, splash filling, cleaning and filling of tanks and containers, sampling, switch loading, gauging, vacuum truck operations, and mechanical movements. These activities may lead to static discharge e.g. spark formation. Restrict line velocity during pumping in order to avoid generation of electrostatic discharge (≤ 1 m/s until fill pipe submerged to twice its diameter, then ≤ 7 m/s). Avoid splash filling. Do NOT use compressed air for filling, discharging, or handling operations.

Refer to guidance under Handling section.
- Hygiene measures : Wash hands before eating, drinking, smoking and using the toilet.
Launder contaminated clothing before re-use.
Do not ingest. If swallowed, then seek immediate medical assistance.
- Conditions for safe storage, : Refer to section 15 for any additional specific legislation cov-

SAFETY DATA SHEET

Mexican official standard NOM-018-STPS-2015

ShellSol A150 ND

Version
1.1

Revision Date:
11/24/2023

SDS Number:
800001007477

Print Date: 12/01/2023
Date of last issue: 04.08.2023

including any incompatibility

ering the packaging and storage of this product.

Further information on stor-
age stability

: Storage Temperature:
Ambient.

Bulk storage tanks should be diked (bunded).
Locate tanks away from heat and other sources of ignition.
Cleaning, inspection and maintenance of storage tanks is a
specialist operation, which requires the implementation of
strict procedures and precautions.
Must be stored in a diked (bunded) well- ventilated area, away
from sunlight, ignition sources and other sources of heat.
Keep away from aerosols, flammables, oxidizing agents, cor-
rosives and from other flammable products which are not
harmful or toxic to man or to the environment.
Electrostatic charges will be generated during pumping.
Electrostatic discharge may cause fire. Ensure electrical con-
tinuity by bonding and grounding (earthing) all equipment to
reduce the risk.
The vapours in the head space of the storage vessel may lie
in the flammable/explosive range and hence may be flamma-
ble.

Packaging material

: Suitable material: For containers, or container linings use mild
steel, stainless steel., For container paints, use epoxy paint,
zinc silicate paint.
Unsuitable material: Avoid prolonged contact with natural,
butyl or nitrile rubbers.

Container Advice

: Do not cut, drill, grind, weld or perform similar operations on or
near containers.

Specific use(s)

: Not applicable

See additional references that provide safe handling practices
for liquids that are determined to be static accumulators:
American Petroleum Institute 2003 (Protection Against Ig-
nitions Arising out of Static, Lightning and Stray Currents) or
National Fire Protection Agency 77 (Recommended Practices
on Static Electricity).
IEC/TS 60079-32-1: Electrostatic hazards, guidance

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control param- eters / Permissible concentration	Basis
Aromatic solvents 160 - 185	Not Assigned	TWA	100 mg/m3	EU HSPA
Solvent naphtha (petroleum), heavy aromatic	64742-94-5	TWA	200 mg/m3 (total hydrocarbon vapor)	ACGIH

SAFETY DATA SHEET

Mexican official standard NOM-018-STPS-2015

ShellSol A150 ND

Version
1.1

Revision Date:
11/24/2023

SDS Number:
800001007477

Print Date: 12/01/2023
Date of last issue: 04.08.2023

Biological occupational exposure limits

No biological limit allocated.

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods <http://www.cdc.gov/niosh/>

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods <http://www.osha.gov/>

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances <http://www.hse.gov.uk/>

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany
<http://www.dguv.de/inhalt/index.jsp>

L'Institut National de Recherche et de Sécurité, (INRS), France <http://www.inrs.fr/accueil>

Engineering measures

: The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:
Use sealed systems as far as possible.
Adequate explosion-proof ventilation to control airborne concentrations below the exposure guidelines/limits.
Local exhaust ventilation is recommended.
Firewater monitors and deluge systems are recommended.
Eye washes and showers for emergency use.
Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

General Information:

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned.

Practice good housekeeping.

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

SAFETY DATA SHEET

Mexican official standard NOM-018-STPS-2015

ShellSol A150 ND

Version
1.1

Revision Date:
11/24/2023

SDS Number:
800001007477

Print Date: 12/01/2023
Date of last issue: 04.08.2023

Personal protective equipment

Respiratory protection : If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are unsuitable (e.g. airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. If air-filtering respirators are suitable for conditions of use: Select a filter suitable for organic gases and vapours [Type A boiling point >65°C (149°F)].

Hand protection
Remarks

: Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. Longer term protection: butyl-rubber Nitrile rubber gloves. Incidental contact/Splash protection: Nitrile rubber gloves. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

Eye protection : If material is handled such that it could be splashed into eyes, protective eyewear is recommended.

Skin and body protection : Skin protection is not required under normal conditions of use. For prolonged or repeated exposures use impervious clothing over parts of the body subject to exposure. If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to relevant Standard, and provide employee skin care programmes. Wear antistatic and flame-retardant clothing, if a local risk

SAFETY DATA SHEET

Mexican official standard NOM-018-STPS-2015

ShellSol A150 ND

Version
1.1

Revision Date:
11/24/2023

SDS Number:
800001007477

Print Date: 12/01/2023
Date of last issue: 04.08.2023

assessment deems it so.

Protective measures : Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Environmental exposure controls

General advice : Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour.
Minimise release to the environment. An environmental assessment must be made to ensure compliance with local environmental legislation.
Information on accidental release measures are to be found in section 6.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Liquid.

Colour : colourless

Odour : aromatic

Odour Threshold : Data not available

pH : Data not available

Melting point/freezing point : Data not available

Boiling point/boiling range : Typical 183 - 197 °C / 361 - 387 °F

Flash point : Typical 63 °C / 145 °F
Method: ASTM D-93 / PMCC

Evaporation rate : 0.1
Method: ASTM D 3539, nBuAc=1

Flammability
Flammability (solid, gas) : Data not available

Lower explosion limit and upper explosion limit / flammability limit
Upper explosion limit / upper flammability limit : upper flammability limit
per flammability limit 6 %(V)

Lower explosion limit / Lower flammability limit : Lower flammability limit
0.6 %(V)

Vapour pressure : Typical 150 Pa

Relative vapour density : Data not available

Relative density : Data not available

Density : Typical 884 kg/m³ (15 °C / 59 °F)

SAFETY DATA SHEET

Mexican official standard NOM-018-STPS-2015

ShellSol A150 ND

Version
1.1

Revision Date:
11/24/2023

SDS Number:
800001007477

Print Date: 12/01/2023
Date of last issue: 04.08.2023

Method: ASTM D4052

Solubility(ies)
Water solubility : immiscible

Partition coefficient: n-
octanol/water : log Pow: > 3.7 - 4.2

Auto-ignition temperature : 499 °C / 930 °F

Method: ASTM E-659

477 °C / 891 °F

Method: DIN 51794

Decomposition temperature : Data not available

Viscosity
Viscosity, dynamic : Data not available

Viscosity, kinematic : 1.1 mm²/s (25 °C / 77 °F)

Method: ASTM D445

Explosive properties : Not applicable

Oxidizing properties : Data not available

Surface tension : Data not available

Conductivity : estimated value(s) 3 pS/m (20 °C / 68 °F)

Method: ASTM 3114

Low conductivity: < 100 pS/m

The conductivity of this material makes it a static accumulator., A liquid is typically considered nonconductive if its conductivity is below 100 pS/m and is considered semi-conductive if its conductivity is below 10,000 pS/m., Whether a liquid is nonconductive or semi-conductive, the precautions are the same., A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid

Particle size : Data not available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.

Chemical stability : No hazardous reaction is expected when handled and stored according to provisions
Stable under normal conditions of use.

SAFETY DATA SHEET

Mexican official standard NOM-018-STPS-2015

ShellSol A150 ND

Version
1.1

Revision Date:
11/24/2023

SDS Number:
800001007477

Print Date: 12/01/2023
Date of last issue: 04.08.2023

Possibility of hazardous reactions	: Reacts with strong oxidising agents.
Conditions to avoid	: Avoid heat, sparks, open flames and other ignition sources. In certain circumstances product can ignite due to static electricity.
Incompatible materials	: Strong oxidising agents.
Hazardous decomposition products	: Hazardous decomposition products are not expected to form during normal storage. Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids and gases including carbon monoxide, carbon dioxide, sulphur oxides and unidentified organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation.

SECTION 11. TOXICOLOGICAL INFORMATION

Basis for assessment	: Information given is based on product data and on data on the components and the toxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).
----------------------	--

Information on likely routes of exposure

Exposure may occur via inhalation, ingestion, skin absorption, skin or eye contact, and accidental ingestion.

Acute toxicity

Components:

Solvent naphtha (petroleum), heavy aromatic:

Acute oral toxicity : LD50 (Rat): > 5000 mg/kg
Remarks: Low toxicity

Acute inhalation toxicity : LC50 (Rat): > 2 - 20 mg/l
Remarks: Low toxicity if inhaled.
Based on available data, the classification criteria are not met.

Acute dermal toxicity : LD50 (Rabbit): > 2000 mg/kg
Remarks: Low toxicity

Skin corrosion/irritation

Components:

Solvent naphtha (petroleum), heavy aromatic:

Remarks: Not irritating to skin., Prolonged/repeated contact may cause defatting of the skin which can lead to dermatitis.

SAFETY DATA SHEET

Mexican official standard NOM-018-STPS-2015

ShellSol A150 ND

Version
1.1

Revision Date:
11/24/2023

SDS Number:
800001007477

Print Date: 12/01/2023
Date of last issue: 04.08.2023

Serious eye damage/eye irritation

Components:

Solvent naphtha (petroleum), heavy aromatic:

Remarks: Not irritating to eye.

Respiratory or skin sensitisation

Components:

Solvent naphtha (petroleum), heavy aromatic:

Remarks: Not a sensitiser. Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Components:

Solvent naphtha (petroleum), heavy aromatic:

Genotoxicity in vivo : Remarks: Not mutagenic.

Carcinogenicity

Components:

Solvent naphtha (petroleum), heavy aromatic:

Remarks: Limited evidence of carcinogenic effect

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Components:

Solvent naphtha (petroleum), heavy aromatic:

Effects on fertility :

Remarks: Causes foetotoxicity in animals at doses which are maternally toxic.
Not a developmental toxicant.
Based on available data, the classification criteria are not met.
Does not impair fertility.

STOT - single exposure

Components:

SAFETY DATA SHEET

Mexican official standard NOM-018-STPS-2015

ShellSol A150 ND

Version
1.1

Revision Date:
11/24/2023

SDS Number:
800001007477

Print Date: 12/01/2023
Date of last issue: 04.08.2023

Solvent naphtha (petroleum), heavy aromatic:

Remarks: May cause drowsiness and dizziness., High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea.

STOT - repeated exposure

Components:

Solvent naphtha (petroleum), heavy aromatic:

Remarks: Kidney: caused kidney effects in male rats which are not considered relevant to humans

Aspiration toxicity

Components:

Solvent naphtha (petroleum), heavy aromatic:

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

Further information

Components:

Solvent naphtha (petroleum), heavy aromatic:

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

SECTION 12. ECOTOXICOLOGICAL INFORMATION

Basis for assessment : Incomplete ecotoxicological data are available for this product. The information given below is based partly on a knowledge of the components and the ecotoxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

Ecotoxicity

Components:

Solvent naphtha (petroleum), heavy aromatic:

Toxicity to fish (Acute toxicity) : Remarks: LC/EC/IC50 >1 - <=10 mg/l
Toxic

Toxicity to daphnia and other aquatic invertebrates (Acute toxicity) : Remarks: LC/EC/IC50 >1 - <=10 mg/l
Toxic

Toxicity to algae (Acute toxicity) : Remarks: LC/EC/IC50 >1 - <=10 mg/l
Toxic

Toxicity to fish (Chronic toxicity) : Remarks: Data not available

Toxicity to daphnia and other : Remarks: Data not available

SAFETY DATA SHEET

Mexican official standard NOM-018-STPS-2015

ShellSol A150 ND

Version
1.1

Revision Date:
11/24/2023

SDS Number:
800001007477

Print Date: 12/01/2023
Date of last issue: 04.08.2023

aquatic invertebrates (Chronic toxicity)

Toxicity to microorganisms (Acute toxicity) : Remarks: Data not available

Persistence and degradability

Components:

Solvent naphtha (petroleum), heavy aromatic:

Biodegradability : Remarks: Readily biodegradable.
Oxidises rapidly by photo-chemical reactions in air.

Bioaccumulative potential

Components:

Solvent naphtha (petroleum), heavy aromatic:

Bioaccumulation : Remarks: Has the potential to bioaccumulate.

Mobility in soil

Components:

Solvent naphtha (petroleum), heavy aromatic:

Mobility : Remarks: Floats on water.

Other adverse effects

Components:

Solvent naphtha (petroleum), heavy aromatic:

Additional ecological information : Does not have ozone depletion potential.

SECTION 13. INFORMATION ON PRODUCT DISPOSAL

Disposal methods

Waste from residues : Recover or recycle if possible.
It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.
Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment.
Do not dispose into the environment, in drains or in water courses.
Do not dispose of tank water bottoms by allowing them to drain into the ground. This will result in soil and groundwater contamination.
Waste arising from a spillage or tank cleaning should be disposed of in accordance with prevailing regulations, preferably

SAFETY DATA SHEET

Mexican official standard NOM-018-STPS-2015

ShellSol A150 ND

Version
1.1

Revision Date:
11/24/2023

SDS Number:
800001007477

Print Date: 12/01/2023
Date of last issue: 04.08.2023

to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand.

Waste, spills or used product is dangerous waste.

Disposal should be in accordance with applicable regional, national, and local laws and regulations.

Local regulations may be more stringent than regional or national requirements and must be complied with.

MARPOL - see International Convention for the Prevention of Pollution from Ships (MARPOL 73/78) which provides technical aspects at controlling pollutions from ships.

Contaminated packaging : Drain container thoroughly.
After draining, vent in a safe place away from sparks and fire.
Residues may cause an explosion hazard. Do not puncture, cut or weld uncleaned drums.
Send to drum recoverer or metal reclaimer.
Comply with any local recovery or waste disposal regulations.

SECTION 14. TRANSPORT INFORMATION

National Regulations

no data available

International Regulations

IATA-DGR

UN/ID No. : UN 3082
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(Hydrocarbons, C10, aromatics)
Class : 9
Packing group : III
Labels : 9

IMDG-Code

UN number : UN 3082
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(Hydrocarbons, C10, aromatics)
Class : 9
Packing group : III
Labels : 9
Marine pollutant : yes

Maritime transport in bulk according to IMO instruments

MARPOL Annex 1 rules apply for bulk shipments by sea.

Special precautions for user

Remarks : Special Precautions: Refer to Section 7, Handling & Storage,

SAFETY DATA SHEET

Mexican official standard NOM-018-STPS-2015

ShellSol A150 ND

Version
1.1

Revision Date:
11/24/2023

SDS Number:
800001007477

Print Date: 12/01/2023
Date of last issue: 04.08.2023

for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

Additional Information

: This product may be transported under nitrogen blanketing. Nitrogen is an odourless and invisible gas. Exposure to nitrogen may cause asphyxiation or death. Personnel must observe strict safety precautions when involved with a confined space entry.

SECTION 15. REGULATORY INFORMATION

Other regulations:

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

The components of this product are reported in the following inventories:

DSL	: Listed
IECSC	: Listed
KECI	: Listed
PICCS	: Listed
TSCA	: Listed
TCSI	: Listed
NZIoC	: Listed
ENCS	: Listed

SECTION 16. OTHER INFORMATION

Further information

NFPA Rating (Health, Fire, Reactivity) 0, 2, 0

Full text of other abbreviations

ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
EU HSPA	: OEL based on European Hydrocarbon Solvents Producers (CEFIC-HSPA) methodology.
ACGIH / TWA	: 8-hour, time-weighted average
EU HSPA / TWA	: Time-Weighted Average Concentration (TWA) (8 hrs.)
Abbreviations and Acronyms	: The standard abbreviations and acronyms used in this document can be looked up in reference literature (e.g. scientific dictionaries) and/or websites.

SAFETY DATA SHEET

Mexican official standard NOM-018-STPS-2015

ShellSol A150 ND

Version
1.1

Revision Date:
11/24/2023

SDS Number:
800001007477

Print Date: 12/01/2023
Date of last issue: 04.08.2023

ACGIH = American Conference of Governmental Industrial Hygienists
ADR = European Agreement concerning the International Carriage of Dangerous Goods by Road
AICS = Australian Inventory of Chemical Substances
ASTM = American Society for Testing and Materials
BEL = Biological exposure limits
BTEX = Benzene, Toluene, Ethylbenzene, Xylenes
CAS = Chemical Abstracts Service
CEFIC = European Chemical Industry Council
CLP = Classification Packaging and Labelling
COC = Cleveland Open-Cup
DIN = Deutsches Institut für Normung
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
DSL = Canada Domestic Substance List
EC = European Commission
EC50 = Effective Concentration fifty
ECETOC = European Center on Ecotoxicology and Toxicology Of Chemicals
ECHA = European Chemicals Agency
EINECS = The European Inventory of Existing Commercial Chemical Substances
EL50 = Effective Loading fifty
ENCS = Japanese Existing and New Chemical Substances Inventory
EWC = European Waste Code
GHS = Globally Harmonised System of Classification and Labelling of Chemicals
IARC = International Agency for Research on Cancer
IATA = International Air Transport Association
IC50 = Inhibitory Concentration fifty
IL50 = Inhibitory Level fifty
IMDG = International Maritime Dangerous Goods
INV = Chinese Chemicals Inventory
IP346 = Institute of Petroleum test method N° 346 for the determination of polycyclic aromatics DMSO-extractables
KECI = Korea Existing Chemicals Inventory
LC50 = Lethal Concentration fifty
LD50 = Lethal Dose fifty per cent.
LL/EL/IL = Lethal Loading/Effective Loading/Inhibitory loading
LL50 = Lethal Loading fifty
MARPOL = International Convention for the Prevention of Pollution From Ships
NOEC/NOEL = No Observed Effect Concentration / No Observed Effect Level
OE_HPV = Occupational Exposure - High Production Volume
PBT = Persistent, Bioaccumulative and Toxic
PICCS = Philippine Inventory of Chemicals and Chemical Substances
PNEC = Predicted No Effect Concentration
REACH = Registration Evaluation And Authorisation Of Chemicals
RID = Regulations Relating to International Carriage of Dangerous Goods by Rail
SKIN_DES = Skin Designation

SAFETY DATA SHEET

Mexican official standard NOM-018-STPS-2015

ShellSol A150 ND

Version
1.1

Revision Date:
11/24/2023

SDS Number:
800001007477

Print Date: 12/01/2023
Date of last issue: 04.08.2023

STEL = Short term exposure limit
TRA = Targeted Risk Assessment
TSCA = US Toxic Substances Control Act
TWA = Time-Weighted Average
vPvB = very Persistent and very Bioaccumulative

A vertical bar (|) in the left margin indicates an amendment from the previous version.

Sources of key data used to compile the Safety Data Sheet : The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID date base, EC 1272 regulation, etc).

Revision Date : 11/24/2023

The information is considered as correct, but not exhaustive, and will be used only as a guide, which is based in the current knowledge of the substance or mixture, and is applicable to proper safety precautions for the product.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

MX / EN