Methyl DIPROXITOL

Print Date 08.11.2023 Revision Date 01.11.2023 Version 1.1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Methyl DIPROXITOL

Product code : U5139 CAS-No. : 34590-94-8

Other means of identification : 2-(2-methoxymethylethoxy)propanol, DPGME, DPM, Methoxy

dipropanol

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the : Speciality solvent.

Substance/Mixture

Uses advised against : This product must not be used in applications other than the

above without first seeking the advice of the supplier.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier : SHELL MARKETS (MIDDLE EAST) LIMITED

CHEMICALS PO Box 307 JEBEL ALI, DUBAI Unit.Arab Emir.

Telephone Telefax

Contact for Safety Data

Sheet

1.4 Emergency telephone number

Other information : DIPROXITOL is a trademark owned by Shell Trademark

Management B.V. and Shell Brands Inc. and used by affiliates

of Shell plc.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

GHS Classification

Flammable liquids : Category 4

2.2 Label elements

GHS-Labelling

Methyl DIPROXITOL

Print Date 08.11.2023 Revision Date 01.11.2023 Version 1.1

Hazard pictograms : No Hazard Symbol required

Signal word : Warning

Hazard statements PHYSICAL HAZARDS:

> H227 Combustible liquid. **HEALTH HAZARDS:**

Not classified as a health hazard under GHS criteria.

ENVIRONMENTAL HAZARDS:

Not classified as an environmental hazard under GHS criteria.

: Prevention: Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames

and other ignition sources. No smoking.

P280 Wear protective gloves/ protective clothing/ eye

protection/ face protection.

Response:

P370 + P378 In case of fire: Use appropriate media to

extinguish. Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

Disposal:

P501 Dispose of contents and container to appropriate waste

site or reclaimer in accordance with local and national

regulations.

2.3 Other hazards

Vapours are heavier than air. Vapours may travel across the ground and reach remote ignition sources causing a flashback fire danger.

Even with proper grounding and bonding, this material can still accumulate an electrostatic charge. If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable airvapour mixtures can occur.

SECTION 3: Composition/information on ingredients

3.1 Substances

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
Dipropylene glycol methyl ether	34590-94-8	<= 100
2-methoxypropanol	1589-47-5	< 0,1

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Not expected to be a health hazard when used under normal

	Methy	I DIPROXITOL
Print Date 08.11.2023	Revision Date 01.11.2023	Version 1.1
Drataction of first siders	conditions.	vou are wearing the
Protection of first-aiders	 When administering first aid, ensure that appropriate personal protective equipme incident, injury and surroundings. 	,
If inhaled	: No treatment necessary under normal co- lf symptoms persist, obtain medical advice	
In case of skin contact	 Remove contaminated clothing. Flush ex water and follow by washing with soap if If persistent irritation occurs, obtain medi 	available.
In case of eye contact	 Flush eye with copious quantities of water Remove contact lenses, if present and erinsing. If persistent irritation occurs, obtain media 	asy to do. Continue
If swallowed	: In general no treatment is necessary unleare swallowed, however, get medical adv	.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Not considered to be an inhalation hazard under normal

conditions of use.

Possible respiratory irritation signs and symptoms may include

a temporary burning sensation of the nose and throat,

coughing, and/or difficulty breathing.

No specific hazards under normal use conditions.

Skin irritation signs and symptoms may include a burning

sensation, redness, or swelling.

Eye irritation signs and symptoms may include a burning

sensation, redness, swelling, and/or blurred vision.

Ingestion may result in nausea, vomiting and/or diarrhoea. Breathing of high vapour concentrations may cause central nervous system (CNS) depression resulting in dizziness, lightheadedness, headache, nausea and loss of coordination. Continued inhalation may result in unconsciousness and

death.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Potential for chemical pneumonitis.

Call a doctor or poison control center for guidance. Causes central nervous system depression.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam, water spray or fog. Dry chemical

	Meth	nyl DIPROXITOL
Print Date 08.11.2023	Revision Date 01.11.2023	Version 1.1
Unsuitable extinguishing media 5.2 Special hazards arising from the s	powder, carbon dioxide, sand or earth fires only. : None substance or mixture	may be used for small
Specific hazards during firefighting	 The vapour is heavier than air, spreads distant ignition is possible. Carbon mor if incomplete combustion occurs. 	
5.3 Advice for firefighters	1	
Special protective equipment for firefighters	: Proper protective equipment including gloves are to be worn; chemical resista large contact with spilled product is exp Breathing Apparatus must be worn who a confined space. Select fire fighter's c relevant Standards (e.g. Europe: EN4)	ant suit is indicated if pected. Self-Contained en approaching a fire in lothing approved to
Specific extinguishing methods	: Standard procedure for chemical fires.	,
Further information	: Clear fire area of all non-emergency pe Keep adjacent containers cool by spray	

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Observe the relevant local and international regulations Notify authorities if any exposure to the general public or the

environment occurs or is likely to occur.

Local authorities should be advised if significant spillages

cannot be contained.

The vapour is heavier than air, spreads along the ground and

distant ignition is possible.

Vapour may form an explosive mixture with air. Avoid contact with skin, eyes and clothing.

Isolate hazard area and deny entry to unnecessary or

unprotected personnel.

Stay upwind and keep out of low areas.

6.2 Environmental precautions

Environmental precautions : Shut off leaks, if possible without personal risks. Remove all

possible sources of ignition in the surrounding area. Use

appropriate containment to avoid environmental

contamination. Prevent from spreading or entering drains. ditches or rivers by using sand, earth, or other appropriate barriers. Attempt to disperse the vapour or to direct its flow to a safe location for example by using fog sprays. Take precautionary measures against static discharge. Ensure electrical continuity by bonding and grounding (earthing) all

Methyl DIPROXITOL

Print Date 08.11.2023 Revision Date 01.11.2023

Version 1.1

equipment.

Ventilate contaminated area thoroughly.

Monitor area with combustible gas indicator.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up

: For large liquid spills (> 1 drum), transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely For small liquid spills (< 1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.

6.4 Reference to other sections

For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet., For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.

SECTION 7: Handling and storage

General Precautions

: Avoid breathing of or direct contact with material. Only use in well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet.

Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of

this material.

Ensure that all local regulations regarding handling and storage facilities are followed.

7.1 Precautions for safe handling

Advice on safe handling

: Avoid contact with skin, eyes and clothing.

Use local exhaust ventilation if there is risk of inhalation of

vapours, mists or aerosols.

Bulk storage tanks should be diked (bunded).

Extinguish any naked flames. Do not smoke. Remove ignition

sources. Avoid sparks.

Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment to reduce the risk.

The vapours in the head space of the storage vessel may lie

in the flammable/explosive range and hence may be

flammable.

Properly dispose of any contaminated rags or cleaning

materials in order to prevent fires.

	Methyl DIPROXITOL
Print Date 08.11.2023	Revision Date 01.11.2023 Version 1.1
	Do NOT use compressed air for filling, discharging, or handling operations.
Product Transfer	: Refer to guidance under Handling section.
7.2 Conditions for safe storage, inclu	uding any incompatibilities
Requirements for storage areas and containers	: The vapour is heavier than air. Beware of accumulation in pits and confined spaces. Refer to section 15 for any additional specific legislation covering the packaging and storage of this product.
Packaging material	 Suitable material: For containers, or container linings use mild steel, stainless steel. Unsuitable material: Natural, butyl, neoprene or nitrile rubbers.
Container Advice	: Containers, even those that have been emptied, can contain explosive vapours. Do not cut, drill, grind, weld or perform similar operations on or near containers.
7.3 Specific end use(s)	
Specific use(s)	: Not applicable
	Ensure that all local regulations regarding handling and storage facilities are followed. See additional references that provide safe handling practices:

American Petroleum Institute 2003 (Protection Against

Ignitions Arising out of Static, Lightning and Stray Currents) or National Fire Protection Agency 77 (Recommended Practices

on Static Electricity).

IEC/TS 60079-32-1: Electrostatic hazards, guidance

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Biological occupational exposure limits

No biological limit allocated.

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples

Methyl DIPROXITOL

Print Date 08.11.2023

Revision Date 01.11.2023

Version 1.1

analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany http://www.dguv.de/inhalt/index.jsp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

8.2 Exposure controls

Engineering measures Use sealed systems as far as possible.

Adequate explosion-proof ventilation to control airborne concentrations below the exposure quidelines/limits.

Local exhaust ventilation is recommended.

Firewater monitors and deluge systems are recommended.

Eye washes and showers for emergency use.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

General Information:

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

Personal protective equipment

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Eye protection : If material is handled such that it could be splashed into eyes,

protective eyewear is recommended.

Hand protection

Remarks : Where hand contact with the product may occur the use of

gloves approved to relevant standards (e.g. Europe: EN374,

US: F739) made from the following materials may provide

Methyl DIPROXITOL

Print Date 08.11.2023

Revision Date 01.11.2023

Version 1.1

suitable chemical protection. Longer term protection: Nitrile rubber gloves. Incidental contact/Splash protection: PVC, neoprene or nitrile rubber gloves For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

Skin and body protection

Skin protection is not required under normal conditions of use. For prolonged or repeated exposures use impervious clothing over parts of the body subject to exposure. If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to relevant Standard. and provide employee skin care programmes.

Wear antistatic and flame-retardant clothing, if a local risk assessment deems it so.

Respiratory protection

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are unsuitable (e.g. airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. If air-filtering respirators are suitable for conditions of use: Select a filter suitable for organic gases and vapours [Type A

boiling point >65°C (149°F)].

Thermal hazards : Not applicable

Methyl DIPROXITOL

Print Date 08.11.2023 Revision Date 01.11.2023 Version 1.1

Environmental exposure controls

General advice : Local guidelines on emission limits for volatile substances

must be observed for the discharge of exhaust air containing

vapour.

Minimise release to the environment. An environmental assessment must be made to ensure compliance with local

environmental legislation.

Information on accidental release measures are to be found in

section 6.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : clear
Odour : Ethereal

Odour Threshold : Data not available pH : Not applicable

Melting / freezing point : -83 °C

Boiling point/boiling range : 184 - 190 °C

Flash point : 75 °C

Method: ASTM D-93 / PMCC

Evaporation rate : 0,01

Method: ASTM D 3539, nBuAc=1

Flammability

Flammability (solid, gas) : Data not available

Lower explosion limit and upper explosion limit / flammability limit

Upper explosion limit : 14 %(V)

Lower explosion limit : 1,1 %(V)

Vapour pressure : 37,1 Pa (25 °C)

Relative vapour density : Data not available
Relative density : 0,95 - 0,96 (20 °C)

Method: ASTM D4052

Density : 952 - 956 kg/m3 (20 °C)

Methyl DIPROXITOL

Print Date 08.11.2023 Revision Date 01.11.2023 Version 1.1

Method: ASTM D4052

Solubility(ies)

Water solubility : completely soluble (25 °C)

Partition coefficient: n-

octanol/water

: log Pow: < 0.01

Auto-ignition temperature : 205 °C

Decomposition temperature : Data not available

Viscosity

Viscosity, dynamic : Data not available : 4.55 mm2/s (20 °C) Viscosity, kinematic Method: ASTM D445

Explosive properties : Not applicable : Data not available Oxidizing properties

9.2 Other information

Surface tension : 68,7 mN/m, 20 °C

Conductivity : Electrical conductivity: > 10,000 pS/m

> A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid, This material is not expected to be

a static accumulator.

Molecular weight : 148,2 g/mol

SECTION 10: Stability and reactivity

10.1 Reactivity

The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.

10.2 Chemical stability

No hazardous reaction is expected when handled and stored according to provisions

10.3 Possibility of hazardous reactions

Hazardous reactions : Reacts with strong oxidising agents.

10.4 Conditions to avoid

Print Date 08.11.2023 Revision Date 01.11.2023 Version 1.1

Conditions to avoid : Avoid heat, sparks, open flames and other ignition sources.

Prevent vapour accumulation.

In certain circumstances product can ignite due to static

electricity.

10.5 Incompatible materials

Materials to avoid : Strong oxidising agents.

10.6 Hazardous decomposition products

Hazardous decomposition

products

: Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids and gases including carbon monoxide, carbon dioxide, sulphur oxides and unidentified organic compounds will be evolved when this material undergoes combustion or thermal or oxidative

degradation.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Basis for assessment : Information given is based on product testing.

Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).Information given is based on product

testing.

Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for

individual component(s).

Information on likely routes of :

exposure

Exposure may occur via inhalation, ingestion, skin absorption,

skin or eye contact, and accidental ingestion.

Acute toxicity

Product:

Acute oral toxicity : LD50 Rat: > 5000 mg/kg

Remarks: Low toxicity

Acute inhalation toxicity : Remarks: Breathing of high vapour concentrations may cause

central nervous system (CNS) depression resulting in dizziness, light-headedness, headache and nausea.

Low toxicity if inhaled.

Based on available data, the classification criteria are not met.

Acute dermal toxicity : LD50 Rabbit: > 5000 mg/kg

Remarks: Low toxicity

Methyl DIPROXITOL

Print Date 08.11.2023 Revision Date 01.11.2023 Version 1.1

Components:

Dipropylene glycol methyl ether:

Acute oral toxicity : LD50 Rat: > 5000 mg/kg

Remarks: Low toxicity

Acute inhalation toxicity : Remarks: Breathing of high vapour concentrations may cause

central nervous system (CNS) depression resulting in dizziness, light-headedness, headache and nausea.

Low toxicity if inhaled.

Based on available data, the classification criteria are not met.

Acute dermal toxicity : LD50 Rabbit: > 5000 mg/kg

Remarks: Low toxicity

Skin corrosion/irritation

Product:

Remarks: Not irritating to skin.

Components:

Dipropylene glycol methyl ether:

Remarks: Not irritating to skin.

Serious eye damage/eye irritation

Product:

Remarks: Slightly irritating to the eye., Based on available data, the classification criteria are not met.

Components:

Dipropylene glycol methyl ether:

Remarks: Slightly irritating to the eye., Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Product:

Test Method: Skin sensitisation

Remarks: Not a sensitiser., Based on available data, the classification criteria are not met.

Components:

Dipropylene glycol methyl ether:

Test Method: Skin sensitisation

Remarks: Not a sensitiser., Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Methyl DIPROXITOL

Print Date 08.11.2023 Revision Date 01.11.2023 Version 1.1

Product:

: Remarks: No evidence of mutagenic activity.

Components:

Dipropylene glycol methyl ether:

: Remarks: No evidence of mutagenic activity.

Carcinogenicity

Product:

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

Components:

Dipropylene glycol methyl ether:

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

Material	GHS/CLP Carcinogenicity Classification
Dipropylene glycol methyl ether	No carcinogenicity classification.
2-methoxypropanol	No carcinogenicity classification.

Reproductive toxicity

Product:

Remarks: Not a developmental toxicant., Based on available data, the classification criteria are not met., Does not impair fertility.

Components:

Dipropylene glycol methyl ether:

Remarks: Not a developmental toxicant., Based on available data, the classification criteria are not met., Does not impair fertility.

STOT - single exposure

Product:

Remarks: Inhalation of vapours or mists may cause irritation to the respiratory system.

Components:

Methyl DIPROXITOL

Print Date 08.11.2023 Revision Date 01.11.2023 Version 1.1

Dipropylene glycol methyl ether:

Remarks: Inhalation of vapours or mists may cause irritation to the respiratory system.

STOT - repeated exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

Components:

Dipropylene glycol methyl ether:

Remarks: Based on available data, the classification criteria are not met.

Aspiration toxicity

Product:

Not an aspiration hazard.

Components:

Dipropylene glycol methyl ether:

Not an aspiration hazard.

Further information

Product:

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

Components:

Dipropylene glycol methyl ether:

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

SECTION 12: Ecological information

12.1 Toxicity

Basis for assessment : Information given is based on product testing.

Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).Information given is based on product

testing.

Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for

Methyl DIPROXITOL

Print Date 08.11.2023 Revision Date 01.11.2023 Version 1.1

individual component(s).

Product:

Toxicity to fish (Acute : Remarks: Practically non toxic:

LL/EL/IL50 > 100 mg/ltoxicity)

Toxicity to daphnia and other aquatic invertebrates (Acute

: Remarks: Practically non toxic: LL/EL/IL50 > 100 mg/l

toxicity)

Toxicity to algae (Acute : Remarks: Practically non toxic: LL/EL/IL50 > 100 mg/ltoxicity)

Toxicity to bacteria (Acute

toxicity) Remarks: Practically non toxic:

LL/EL/IL50 > 100 mg/l

Components:

Dipropylene glycol methyl ether:

Toxicity to fish (Acute : Remarks: Practically non toxic:

toxicity) LL/EL/IL50 > 100 mg/l

Toxicity to daphnia and other

aquatic invertebrates (Acute

toxicity)

Toxicity to algae (Acute : Remarks: Practically non toxic:

LL/EL/IL50 > 100 mg/ltoxicity)

Toxicity to bacteria (Acute

Remarks: Practically non toxic: toxicity)

LL/EL/IL50 > 100 mg/l

: Remarks: Practically non toxic:

LL/EL/IL50 > 100 mg/l

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: Readily biodegradable., Oxidises rapidly by photo-

chemical reactions in air.

Components:

Dipropylene glycol methyl ether:

: Remarks: Readily biodegradable., Oxidises rapidly by photo-Biodegradability

chemical reactions in air.

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: Does not bioaccumulate significantly.

Partition coefficient: n-

octanol/water

: log Pow: < 0.01

Methyl DIPROXITOL

Print Date 08.11.2023 Revision Date 01.11.2023 Version 1.1

Components:

Dipropylene glycol methyl ether:

Bioaccumulation : Remarks: Does not bioaccumulate significantly.

12.4 Mobility in soil

Product:

Mobility : Remarks: If product enters soil, one or more constituents will

be mobile and may contaminate groundwater., Dissolves in

water.

Components:

Dipropylene glycol methyl ether:

Mobility : Remarks: If product enters soil, one or more constituents will

be mobile and may contaminate groundwater., Dissolves in

water.

12.5 Results of PBT and vPvB assessment

Product:

Assessment : The substance does not fulfill all screening criteria for

persistence, bioaccumulation and toxicity and hence is not

considered to be PBT or vPvB.

Components:

Dipropylene glycol methyl ether:

Assessment : The substance does not fulfill all screening criteria for

persistence, bioaccumulation and toxicity and hence is not

considered to be PBT or vPvB.

12.6 Other adverse effects

Product:

Additional ecological

information

: Data not available

Components:

Dipropylene glycol methyl ether:

Additional ecological

information

: Data not available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Recover or recycle if possible.

It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Do not dispose into the environment, in drains or in water

courses.

Waste product should not be allowed to contaminate soil or

ground water, or be disposed of into the environment.

	Met	hyl DIPROXITOL
Print Date 08.11.2023	Revision Date 01.11.2023	Version 1.1
	Waste, spills or used product is dangerous waste. Disposal should be in accordance with applicable regional, national, and local laws and regulations. Local regulations may be more stringent than regional or national requirements and must be complied with. MARPOL - see International Convention for the Prevention of Pollution from Ships (MARPOL 73/78) which provides	
Contaminated packaging	 technical aspects at controlling pollution Drain container thoroughly. After draining, vent in a safe place aw Residues may cause an explosion had Do not, puncture, cut, or weld unclear Send to drum recoverer or metal rectains. 	ray from sparks and fire. zard. ned drums.
	Dispose in accordance with prevailing to a recognized collector or contractor the collector or contractor should be e	The competence of

SECTION 14: Transport information

14.1 UN number	14.	.1	UN	num	ber
----------------	-----	----	----	-----	-----

Local legislation

ADR : Not regulated as a dangerous good | Not regulated as a dange

14.2 Proper shipping name

ADR : Not regulated as a dangerous good IMDG : Not regulated as a dangerous good IATA : Not regulated as a dangerous good

14.3 Transport hazard class

ADR : Not regulated as a dangerous good IMDG : Not regulated as a dangerous good IATA : Not regulated as a dangerous good

14.4 Packing group

ADR : Not regulated as a dangerous good IMDG : Not regulated as a dangerous good IATA : Not regulated as a dangerous good

14.5 Environmental hazards

ADR : Not regulated as a dangerous good : Not regulated as a dangerous good

14.6 Special precautions for user

Remarks : Special Precautions: Refer to Section 7, Handling & Storage,

for special precautions which a user needs to be aware of or

needs to comply with in connection with transport.

Methyl DIPROXITOL

Print Date 08.11.2023 Revision Date 01.11.2023 Version 1.1

14.7 Maritime transport in bulk according to IMO instruments

Pollution category · 7 Ship type

Product name Poly (2-8) alkylene glycol monoalkyl (C1-C6) ether

Additional Information : This product may be transported under nitrogen blanketing.

> Nitrogen is an odourless and invisible gas. Exposure to nitrogen may cause asphyxiation or death. Personnel must observe strict safety precautions when involved with a

confined space entry.

Transport in bulk according to Annex II of Marpol and the IBC

Code

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Other regulations : The regulatory information is not intended to be

comprehensive. Other regulations may apply to this material.

The components of this product are reported in the following inventories:

AIIC : Listed DSL : Listed **IECSC** : Listed **ENCS** : Listed KECI : Listed NZIoC : Listed **PICCS** : Listed **TSCA** : Listed **TCSI** : Listed

SECTION 16: Other information

Abbreviations and Acronyms : The standard abbreviations and acronyms used in this

document can be looked up in reference literature (e.g.

scientific dictionaries) and/or websites.

ACGIH = American Conference of Governmental Industrial

Hygienists

ADR = European Agreement concerning the International

Carriage of Dangerous Goods by Road

AICS = Australian Inventory of Chemical Substances ASTM = American Society for Testing and Materials

BEL = Biological exposure limits

Methyl DIPROXITOL

Version 1.1

Print Date 08.11.2023 Revision Date 01.11.2023

BTEX = Benzene, Toluene, Ethylbenzene, Xylenes

CAS = Chemical Abstracts Service

CEFIC = European Chemical Industry Council

CLP = Classification Packaging and Labelling

COC = Cleveland Open-Cup

DIN = Deutsches Institut fur Normung

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

DSL = Canada Domestic Substance List

EC = European Commission

EC50 = Effective Concentration fifty

ECETOC = European Center on Ecotoxicology and

Toxicology Of Chemicals

ECHA = European Chemicals Agency

EINECS = The European Inventory of Existing Commercial

Chemical Substances

EL50 = Effective Loading fifty

ENCS = Japanese Existing and New Chemical Substances

Inventory

EWC = European Waste Code

GHS = Globally Harmonised System of Classification and

Labelling of Chemicals

IARC = International Agency for Research on Cancer

IATA = International Air Transport Association

IC50 = Inhibitory Concentration fifty

IL50 = Inhibitory Level fifty

IMDG = International Maritime Dangerous Goods

INV = Chinese Chemicals Inventory

IP346 = Institute of Petroleum test method N° 346 for the

determination of polycyclic aromatics DMSO-extractables

KECI = Korea Existing Chemicals Inventory

LC50 = Lethal Concentration fifty

LD50 = Lethal Dose fifty per cent.

LL/EL/IL = Lethal Loading/Effective Loading/Inhibitory loading

LL50 = Lethal Loading fifty

MARPOL = International Convention for the Prevention of

Pollution From Ships

NOEC/NOEL = No Observed Effect Concentration / No

Observed Effect Level

OE HPV = Occupational Exposure - High Production Volume

PBT = Persistent, Bioaccumulative and Toxic

PICCS = Philippine Inventory of Chemicals and Chemical

Substances

PNEC = Predicted No Effect Concentration

REACH = Registration Evaluation And Authorisation Of

Chemicals

RID = Regulations Relating to International Carriage of

Dangerous Goods by Rail

SKIN_DES = Skin Designation

STEL = Short term exposure limit

TRA = Targeted Risk Assessment

TSCA = US Toxic Substances Control Act

TWA = Time-Weighted Average

	Meth	yl DIPROXITOL
Print Date 08.11.2023	Revision Date 01.11.2023	Version 1.1
	vPvB = very Persistent and very Bioacc	umulative
Further information		
Training advice	: Provide adequate information, instruction operators.	on and training for
Other information	: A vertical bar () in the left margin indication from the previous version.	ites an amendment
Sources of key data used to compile the Safety Data Sheet	: The quoted data are from, but not limite sources of information (e.g. toxicologica Health Services, material suppliers' data IUCLID date base, EC 1272 regulation,	ll data from Shell a, CONCAWE, EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.