

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version	Revision Date:	SDS Number:	Date of last issue: 31.10.2024
4.3	17.02.2025	800001033919	Print Date 24.02.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name	: Methyl Isobutyl Ketone
Product code	: S1215
Registration number EU	: 01-2119473980-30-0002
Synonyms	: 4-methyl-2-pentanone, Hexanone, Hexone, MIBK
CAS-No.	: 108-10-1
EC-No.	: 203-550-1

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture	: Use only in industrial processes. Please refer to section 16 and/or the annexes for the registered uses under REACH.
Uses advised against	: This product must not be used in applications other than the above without first seeking the advice of the supplier.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier	: Shell Chemicals Europe B.V. PO Box 2334 3000 CH Rotterdam Netherlands
Telephone	: +31 (0)10 441 5137 / +31 (0)10 441 5191
Telefax	: +31 (0)20 716 8316 / +31 (0)20 713 9230
Contact for Safety Data Sheet	: sccmsds@shell.com

1.4 Emergency telephone number

+44 (0) 1235 239 670 (This telephone number is available 24 hours per day, 7 days per week)
Poison Centre: (+41) 145

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 2	H225: Highly flammable liquid and vapour.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Acute toxicity, Category 4, Inhalation	H332: Harmful if inhaled.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version 4.3	Revision Date: 17.02.2025	SDS Number: 800001033919	Date of last issue: 31.10.2024 Print Date 24.02.2025
----------------	------------------------------	-----------------------------	---

Specific target organ toxicity - single exposure, Category 3, Central nervous system

H336: May cause drowsiness or dizziness.

Carcinogenicity, Category 2

H351: Suspected of causing cancer.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements :
PHYSICAL HAZARDS:
H225 Highly flammable liquid and vapour.
HEALTH HAZARDS:
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H336 May cause drowsiness or dizziness.
H351 Suspected of causing cancer.
ENVIRONMENTAL HAZARDS:
Not classified as environmental hazard according to CLP criteria.

Supplemental Hazard Statements : EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statements : **Prevention:**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P312 Call a POISON CENTER/ doctor if you feel unwell.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version 4.3 Revision Date: 17.02.2025 SDS Number: 800001033919 Date of last issue: 31.10.2024
Print Date 24.02.2025

2.3 Other hazards

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Vapours are heavier than air. Vapours may travel across the ground and reach remote ignition sources causing a flashback fire danger.

Even with proper grounding and bonding, this material can still accumulate an electrostatic charge.

If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur.

Exposure may enhance the toxicity of other materials.

See Chapter 11 for details.

Vapours may be irritating to the eye.

SECTION 3: Composition/information on ingredients

3.1 Substances

Components

Chemical name	CAS-No. EC-No.	Concentration (% w/w)
Methyl isobutyl ketone	108-10-1 203-550-1	<= 100

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : DO NOT DELAY.
Keep victim calm. Obtain medical treatment immediately.
- Protection of first-aiders : When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.
- If inhaled : Call emergency number for your location / facility.
Remove to fresh air. Do not attempt to rescue the victim unless proper respiratory protection is worn. If the victim has difficulty breathing or tightness of the chest, is dizzy, vomiting, or unresponsive, give 100% oxygen with rescue breathing or Cardio-Pulmonary Resuscitation as required and transport to the nearest medical facility.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version 4.3	Revision Date: 17.02.2025	SDS Number: 800001033919	Date of last issue: 31.10.2024 Print Date 24.02.2025
----------------	------------------------------	-----------------------------	---

-
- | | |
|-------------------------|--|
| In case of skin contact | : Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention. |
| In case of eye contact | : Immediately flush eye(s) with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Transport to the nearest medical facility for additional treatment. |
| If swallowed | : If swallowed, do not induce vomiting: transport to nearest medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Rinse mouth. |

4.2 Most important symptoms and effects, both acute and delayed

- | | |
|----------|---|
| Symptoms | : Respiratory irritation signs and symptoms may include a temporary burning sensation of the nose and throat, coughing, and/or difficulty breathing.
Skin irritation signs and symptoms may include a burning sensation, redness, or swelling.
Eye irritation signs and symptoms may include a burning sensation, redness, swelling, and/or blurred vision.
Ingestion may result in nausea, vomiting and/or diarrhoea.
Defatting dermatitis signs and symptoms may include a burning sensation and/or a dried/cracked appearance. |
|----------|---|

4.3 Indication of any immediate medical attention and special treatment needed

- | | |
|-----------|---|
| Treatment | : IMMEDIATE TREATMENT IS EXTREMELY IMPORTANT!
Call a doctor or poison control center for guidance.
Treat symptomatically. |
|-----------|---|

SECTION 5: Firefighting measures

5.1 Extinguishing media

- | | |
|--------------------------------|--|
| Suitable extinguishing media | : Alcohol-resistant foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only. |
| Unsuitable extinguishing media | : None |

5.2 Special hazards arising from the substance or mixture

- | | |
|---------------------------------------|---|
| Specific hazards during fire-fighting | : The vapour is heavier than air, spreads along the ground and distant ignition is possible.
Carbon monoxide may be evolved if incomplete combustion occurs. |
|---------------------------------------|---|

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version	Revision Date:	SDS Number:	Date of last issue: 31.10.2024
4.3	17.02.2025	800001033919	Print Date 24.02.2025

5.3 Advice for firefighters

- Special protective equipment for firefighters : Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).
- Specific extinguishing methods : Standard procedure for chemical fires.
- Further information : Clear fire area of all non-emergency personnel.
Keep adjacent containers cool by spraying with water.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- Personal precautions : Observe the relevant local and international regulations
Notify authorities if any exposure to the general public or the environment occurs or is likely to occur.
Local authorities should be advised if significant spillages cannot be contained.
The vapour is heavier than air, spreads along the ground and distant ignition is possible.
Vapour may form an explosive mixture with air.
- 6.1.1 For non emergency personnel:
Avoid contact with skin, eyes and clothing.
Isolate hazard area and deny entry to unnecessary or unprotected personnel.
Stay upwind and keep out of low areas.
- 6.1.2 For emergency responders:
Avoid contact with skin, eyes and clothing.
Isolate hazard area and deny entry to unnecessary or unprotected personnel.
Stay upwind and keep out of low areas.

6.2 Environmental precautions

- Environmental precautions : Shut off leaks, if possible without personal risks. Remove all possible sources of ignition in the surrounding area. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. Attempt to disperse the vapour or to direct its flow to a safe location for example by using fog sprays. Take precautionary measures against static discharge. Ensure electrical continuity by bonding and grounding (earthing) all equipment. Ventilate contaminated area thoroughly. Monitor area with combustible gas indicator.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version	Revision Date:	SDS Number:	Date of last issue: 31.10.2024
4.3	17.02.2025	800001033919	Print Date 24.02.2025

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : For large liquid spills (> 1 drum), transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely. For small liquid spills (< 1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.

6.4 Reference to other sections

For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet.,
For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures : Avoid breathing of or direct contact with material. Only use in well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet.
Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.
Ensure that all local regulations regarding handling and storage facilities are followed.

Advice on safe handling : Avoid contact with skin, eyes and clothing.
Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols.
Bulk storage tanks should be diked (bunded).
Extinguish any naked flames. Do not smoke. Remove ignition sources. Avoid sparks.
Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment to reduce the risk.
The vapours in the head space of the storage vessel may lie in the flammable/explosive range and hence may be flammable.
Properly dispose of any contaminated rags or cleaning materials in order to prevent fires.
Do NOT use compressed air for filling, discharging, or handling operations.

Product Transfer : Refer to guidance under Handling section.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version 4.3 Revision Date: 17.02.2025 SDS Number: 800001033919 Date of last issue: 31.10.2024
Print Date 24.02.2025

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : The vapour is heavier than air. Beware of accumulation in pits and confined spaces. Refer to section 15 for any additional specific legislation covering the packaging and storage of this product.
- Packaging material : Suitable material: For containers, or container linings use mild steel, stainless steel.
Unsuitable material: Natural, butyl, neoprene or nitrile rubbers.
- Container Advice : Containers, even those that have been emptied, can contain explosive vapours. Do not cut, drill, grind, weld or perform similar operations on or near containers.

7.3 Specific end use(s)

- Specific use(s) : Please refer to section 16 and/or the annexes for the registered uses under REACH.
- Ensure that all local regulations regarding handling and storage facilities are followed.
See additional references that provide safe handling practices: American Petroleum Institute 2003 (Protection Against Ignitions Arising out of Static, Lightning and Stray Currents) or National Fire Protection Agency 77 (Recommended Practices on Static Electricity).
IEC/TS 60079-32-1: Electrostatic hazards, guidance

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Methyl isobutyl ketone	108-10-1	TWA	20 ppm 82 mg/m ³	CH SUVA
	Further information: Toxic by skin resorption possible; Substances, which are easily absorbed through the skin, can give by additional skin resorption a substantial higher risk compared to only inhalation by the airways., National Institute for Occupational Safety and Health, German Research Foundation, National Institute of Research and Safety for the prevention of work accidents and occupational diseases, Harm to the unborn child is not to be expected when the OEL-value is respected			
Methyl isobutyl ketone		STEL	40 ppm 164 mg/m ³	CH SUVA
	Further information: Toxic by skin resorption possible; Substances, which are easily absorbed through the skin, can give by additional skin resorption a substantial higher risk compared to only inhalation by the airways., National Institute for Occupational Safety and Health, German Research Foundation, National Institute of Research and Safety for the prevention of work accidents			

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version
4.3

Revision Date:
17.02.2025

SDS Number:
800001033919

Date of last issue: 31.10.2024
Print Date 24.02.2025

and occupational diseases, Harm to the unborn child is not to be expected when the OEL-value is respected

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
Methyl isobutyl ketone	108-10-1	4-methylpentan-2-one: 0,7 mg/l (Urine)	Immediately after exposure or after working hours	CH BAT

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Methyl Isobutyl Ketone, 108-10-1	Workers	Inhalation	Acute systemic effects	208 mg/m3
Methyl Isobutyl Ketone, 108-10-1	Workers	Inhalation	Acute local effects	208 mg/m3
Methyl Isobutyl Ketone, 108-10-1	Workers	Inhalation	Long-term systemic effects	83 mg/m3
Methyl Isobutyl Ketone, 108-10-1	Workers	Inhalation	Long-term local effects	83 mg/m3
Methyl Isobutyl Ketone, 108-10-1	Workers	Dermal	Long-term systemic effects	11,8 mg/kg bw/day
Methyl Isobutyl Ketone, 108-10-1	Consumers	Inhalation	Acute systemic effects	155,2 mg/m3
Methyl Isobutyl Ketone, 108-10-1	Consumers	Inhalation	Acute local effects	155,2 mg/m3
Methyl Isobutyl Ketone, 108-10-1	Consumers	Inhalation	Long-term systemic effects	14,7 mg/m3
Methyl Isobutyl Ketone, 108-10-1	Consumers	Inhalation	Long-term local effects	14,7 mg/m3
Methyl Isobutyl Ketone, 108-10-1	Consumers	Dermal	Long-term systemic effects	4,2 mg/kg bw/day
Methyl Isobutyl Ketone, 108-10-1	Consumers	Oral	Long-term systemic effects	4,2 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Remarks:	Exposure assessments have not been presented for the environment therefore PNEC values not required.	

8.2 Exposure controls

Engineering measures

Read in conjunction with the Exposure Scenario for your specific use contained in the Annex.
Use sealed systems as far as possible.

Adequate explosion-proof ventilation to control airborne concentrations below the exposure guidelines/limits.

Local exhaust ventilation is recommended.

Firewater monitors and deluge systems are recommended.

Eye washes and showers for emergency use.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version 4.3	Revision Date: 17.02.2025	SDS Number: 800001033919	Date of last issue: 31.10.2024 Print Date 24.02.2025
----------------	------------------------------	-----------------------------	---

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

General Information

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

Personal protective equipment

Read in conjunction with the Exposure Scenario for your specific use contained in the Annex. The provided information is made in consideration of the PPE directive (Council Directive 89/686/EEC) and the CEN European Committee for Standardisation (CEN) standards.

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Eye protection : Wear goggles for use against liquids and gas.
Wear full face shield if splashes are likely to occur.
Approved to EU Standard EN166.

Hand protection

Remarks : Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. Longer term protection: Butyl rubber. Nitrile rubber. Incidental contact/Splash protection: PVC or neoprene rubber gloves. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version 4.3	Revision Date: 17.02.2025	SDS Number: 800001033919	Date of last issue: 31.10.2024 Print Date 24.02.2025
----------------	------------------------------	-----------------------------	---

-
- care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.
- Skin and body protection : Wear antistatic and flame-retardant clothing, if a local risk assessment deems it so.
Skin protection is not required under normal conditions of use.
For prolonged or repeated exposures use impervious clothing over parts of the body subject to exposure.
If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to relevant Standard, and provide employee skin care programmes.
Protective clothing approved to EU Standard EN14605.
- Respiratory protection : If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation.
Check with respiratory protective equipment suppliers.
Where air-filtering respirators are unsuitable (e.g. airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus.
Where air-filtering respirators are suitable, select an appropriate combination of mask and filter.
If air-filtering respirators are suitable for conditions of use: Select a filter suitable for organic gases and vapours [Type A boiling point > 65°C (149°F)] meeting EN14387.
- Thermal hazards : Not applicable

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- Physical state : Liquid.
- Colour : clear
- Odour : characteristic
- Odour Threshold : < 100 ppm
- Melting point/freezing point : -85 °C
- Boiling point/boiling range : 114 - 117 °C
- Flammability
- Flammability (solid, gas) : Not applicable

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version 4.3	Revision Date: 17.02.2025	SDS Number: 800001033919	Date of last issue: 31.10.2024 Print Date 24.02.2025
----------------	------------------------------	-----------------------------	---

Lower explosion limit and upper explosion limit / flammability limit

Upper explosion limit /
Upper flammability limit : Upper flammability limit
8 %(V)

Lower explosion limit /
Lower flammability limit : Lower flammability limit
1,3 %(V)

Flash point : 14 °C
Method: Abel

Auto-ignition temperature : 448 °C

Decomposition temperature
Decomposition temperature : Not applicable

pH : Not applicable

Viscosity
Viscosity, dynamic : Data not available

Viscosity, kinematic : Not applicable

Solubility(ies)
Water solubility : 20 g/l (20 °C)

Partition coefficient: n-
octanol/water : log Pow: 1,31

Vapour pressure : 1,900 Pa (20 °C)

Relative density : 0,799 - 0,802 (20 °C)
Method: ASTM D4052

Density : 799 - 802 kg/m³ (20 °C)
Method: ASTM D4052

Relative vapour density : 3,5 (20 °C)

Particle characteristics
Particle size : Data not available

9.2 Other information

Explosive properties : Not applicable

Oxidizing properties : Data not available

Evaporation rate : 1,6
Method: ASTM D 3539, nBuAc=1

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version	Revision Date:	SDS Number:	Date of last issue: 31.10.2024
4.3	17.02.2025	800001033919	Print Date 24.02.2025

Conductivity : Electrical conductivity: > 10,000 pS/m

A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid, This material is not expected to be a static accumulator.

Surface tension : Data not available

Molecular weight : Data not available

SECTION 10: Stability and reactivity

10.1 Reactivity

The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.

10.2 Chemical stability

No hazardous reaction is expected when handled and stored according to provisions

10.3 Possibility of hazardous reactions

Hazardous reactions : Reacts with strong oxidising agents.

10.4 Conditions to avoid

Conditions to avoid : Avoid heat, sparks, open flames and other ignition sources.
Prevent vapour accumulation.
In certain circumstances product can ignite due to static electricity.

10.5 Incompatible materials

Materials to avoid : Strong oxidising agents.

10.6 Hazardous decomposition products

Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids and gases including carbon monoxide, carbon dioxide, sulphur oxides and unidentified organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure : Inhalation is the primary route of exposure although absorption may occur through skin contact or following accidental ingestion.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version
4.3

Revision Date:
17.02.2025

SDS Number:
800001033919

Date of last issue: 31.10.2024
Print Date 24.02.2025

Acute toxicity

Components:

Methyl isobutyl ketone:

- Acute oral toxicity : LD50 (Rat): > 2.000 mg/kg
Method: Test(s) equivalent or similar to OECD Test Guideline 401
Remarks: LD50 >2000 - <=5000 mg/kg
May be harmful if swallowed.
- Acute inhalation toxicity : LC50 (Rat): > 10 - 20 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Test(s) equivalent or similar to OECD Test Guideline 403
Remarks: LC50 > 10,0 - <= 20,0 mg/l
Harmful if inhaled.
- Acute dermal toxicity : LD50 (Rat, male and female): > 2.000 mg/kg
Method: OECD Test Guideline 402
Remarks: Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Components:

Methyl isobutyl ketone:

- Species : Rabbit
Method : OECD Test Guideline 404
Remarks : Based on available data, the classification criteria are not met.
Prolonged/repeated contact may cause defatting of the skin which can lead to dermatitis.

Serious eye damage/eye irritation

Components:

Methyl isobutyl ketone:

- Species : Rabbit
Method : OECD Test Guideline 405
Remarks : Causes serious eye irritation.

Respiratory or skin sensitisation

Components:

Methyl isobutyl ketone:

- Species : Guinea pig
Method : OECD Test Guideline 406
Remarks : Based on available data, the classification criteria are not met.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version 4.3 Revision Date: 17.02.2025 SDS Number: 800001033919 Date of last issue: 31.10.2024
Print Date 24.02.2025

Germ cell mutagenicity

Components:

Methyl isobutyl ketone:

Genotoxicity in vitro : Method: Test(s) equivalent or similar to OECD Guideline 471
Remarks: Based on available data, the classification criteria are not met.

Method: Test(s) equivalent or similar to OECD Test Guideline 476
Remarks: Based on available data, the classification criteria are not met.

Method: Test(s) equivalent or similar to OECD Test Guideline 473
Remarks: Based on available data, the classification criteria are not met.

Genotoxicity in vivo : Species: Mouse
Method: Test(s) equivalent or similar to OECD Test Guideline 474
Remarks: Based on available data, the classification criteria are not met.

Germ cell mutagenicity- Assessment : This product does not meet the criteria for classification in categories 1A/1B.

Carcinogenicity

Components:

Methyl isobutyl ketone:

Species : Rat, male and female
Application Route : Inhalation
Method : OECD Test Guideline 451
Remarks : Suspected of causing cancer.

Carcinogenicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

Material	GHS/CLP Carcinogenicity Classification
Methyl isobutyl ketone	Carcinogenicity Category 2

Material	Other Carcinogenicity Classification
Methyl isobutyl ketone	IARC: Group 2B: Possibly carcinogenic to humans

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version 4.3	Revision Date: 17.02.2025	SDS Number: 800001033919	Date of last issue: 31.10.2024 Print Date 24.02.2025
----------------	------------------------------	-----------------------------	---

Reproductive toxicity

Components:

Methyl isobutyl ketone:

Effects on fertility : Species: Rat
Sex: male and female
Application Route: Oral

Method: Equivalent or similar to OECD Test Guideline 416
Remarks: Based on available data, the classification criteria are not met.

Reproductive toxicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

STOT - single exposure

Components:

Methyl isobutyl ketone:

Exposure routes : Inhalation
Target Organs : Narcotic effects
Remarks : May cause drowsiness or dizziness.

STOT - repeated exposure

Components:

Methyl isobutyl ketone:

Remarks : Based on available data, the classification criteria are not met.
Kidney: caused kidney effects in male rats which are not considered relevant to humans

Repeated dose toxicity

Components:

Methyl isobutyl ketone:

Species : Rat, male and female
Application Route : Oral
Method : Test(s) equivalent or similar to OECD Test Guideline 408
Target Organs : No specific target organs noted

Species : Rat, male and female
Application Route : Inhalation
Test atmosphere : vapour
Method : Test(s) equivalent or similar to OECD Test Guideline 451
Target Organs : No specific target organs noted

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version 4.3	Revision Date: 17.02.2025	SDS Number: 800001033919	Date of last issue: 31.10.2024 Print Date 24.02.2025
----------------	------------------------------	-----------------------------	---

Aspiration toxicity

Components:

Methyl isobutyl ketone:

Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Further information

Product:

Remarks : Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

Components:

Methyl isobutyl ketone:

Remarks : Classifications by other authorities under varying regulatory frameworks may exist.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Methyl isobutyl ketone:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 179 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
Remarks: Practically non toxic:
LL/EL/IL50 > 100 mg/l

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 200 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
Remarks: Practically non toxic:
LL/EL/IL50 > 100 mg/l

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version	Revision Date:	SDS Number:	Date of last issue: 31.10.2024
4.3	17.02.2025	800001033919	Print Date 24.02.2025

-
- | | | |
|--|---|--|
| Toxicity to algae/aquatic plants | : | EC50 (Lemna gibba (gibbous duckweed)): > 146 mg/l
Exposure time: 168 h
Method: OECD Test Guideline 221
Remarks: Practically non toxic:
LL/EL/IL50 > 100 mg/l |
| Toxicity to microorganisms | : | TTC (Pseudomonas putida): 275 mg/l
Exposure time: 72 h
Method: Literature data.
Remarks: Practically non toxic:
LL/EL/IL50 > 100 mg/l |
| Toxicity to fish (Chronic toxicity) | : | Remarks: Data not available |
| Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) | : | NOEC: 30 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: Test(s) equivalent or similar to OECD Guideline 211
Remarks: NOEC/NOEL > 10 - <=100 mg/l |

12.2 Persistence and degradability

Components:

Methyl isobutyl ketone:

- | | | |
|------------------|---|--|
| Biodegradability | : | Biodegradation: 83 %
Exposure time: 28 d
Method: OECD Test Guideline 301F
Remarks: Readily biodegradable.
Oxidises rapidly by photo-chemical reactions in air. |
|------------------|---|--|

12.3 Bioaccumulative potential

Components:

Methyl isobutyl ketone:

- | | | |
|-----------------|---|--|
| Bioaccumulation | : | Remarks: Does not have the potential to bioaccumulate significantly. |
|-----------------|---|--|

12.4 Mobility in soil

Components:

Methyl isobutyl ketone:

- | | | |
|----------|---|---|
| Mobility | : | Remarks: Dissolves in water., If the product enters soil, one or more constituents will or may be mobile and may contaminate groundwater. |
|----------|---|---|

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version	Revision Date:	SDS Number:	Date of last issue: 31.10.2024
4.3	17.02.2025	800001033919	Print Date 24.02.2025

12.5 Results of PBT and vPvB assessment

Components:

Methyl isobutyl ketone:

Assessment : The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB..

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

Components:

Methyl isobutyl ketone:

Additional ecological information : Does not have ozone depletion potential.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Recover or recycle if possible.
It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.
Do not dispose into the environment, in drains or in water courses.
Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment.
Waste, spills or used product is dangerous waste.

Disposal should be in accordance with applicable regional, national, and local laws and regulations.
Local regulations may be more stringent than regional or national requirements and must be complied with.

MARPOL - see International Convention for the Prevention of

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version	Revision Date:	SDS Number:	Date of last issue: 31.10.2024
4.3	17.02.2025	800001033919	Print Date 24.02.2025

Pollution from Ships (MARPOL 73/78) which provides technical aspects at controlling pollutions from ships.

Contaminated packaging : Drain container thoroughly.
After draining, vent in a safe place away from sparks and fire.
Residues may cause an explosion hazard.
Do not, puncture, cut, or weld uncleaned drums.
Send to drum recoverer or metal reclaimer.

Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand.

SECTION 14: Transport information

14.1 UN number or ID number

ADN	: 1245
ADR	: 1245
RID	: 1245
IMDG	: 1245
IATA	: 1245

14.2 UN proper shipping name

ADN	: METHYL ISOBUTYL KETONE
ADR	: METHYL ISOBUTYL KETONE
RID	: METHYL ISOBUTYL KETONE
IMDG	: METHYL ISOBUTYL KETONE
IATA	: METHYL ISOBUTYL KETONE

14.3 Transport hazard class(es)

ADN	: 3
ADR	: 3
RID	: 3
IMDG	: 3
IATA	: 3

14.4 Packing group

ADN	
Packing group	: II
Classification Code	: F1
Labels	: 3
CDNI Inland Water Waste Agreement	: NST 8963 Solvent
ADR	

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version	Revision Date:	SDS Number:	Date of last issue: 31.10.2024
4.3	17.02.2025	800001033919	Print Date 24.02.2025

Packing group	:	II
Classification Code	:	F1
Hazard Identification Number	:	33
Labels	:	3

RID

Packing group	:	II
Classification Code	:	F1
Hazard Identification Number	:	33
Labels	:	3

IMDG

Packing group	:	II
Labels	:	3

IATA

Packing group	:	II
Labels	:	3

14.5 Environmental hazards

ADN

Environmentally hazardous	:	no
---------------------------	---	----

ADR

Environmentally hazardous	:	no
---------------------------	---	----

RID

Environmentally hazardous	:	no
---------------------------	---	----

IMDG

Marine pollutant	:	no
------------------	---	----

14.6 Special precautions for user

Remarks	:	Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.
---------	---	--

14.7 Maritime transport in bulk according to IMO instruments

Pollution category	:	Z
Ship type	:	3
Product name	:	Methyl Isobutyl Ketone

Additional Information	:	This product may be transported under nitrogen blanketing. Nitrogen is an odourless and invisible gas. Exposure to nitrogen may cause asphyxiation or death. Personnel must observe strict safety precautions when involved with a confined space entry.
-------------------------------	---	--

Transport in bulk according to Annex II of Marpol and the IBC Code

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version 4.3	Revision Date: 17.02.2025	SDS Number: 800001033919	Date of last issue: 31.10.2024 Print Date 24.02.2025
----------------	------------------------------	-----------------------------	---

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - List of substances subject to authorisation (Annex XIV) : Product is not subject to Authorisation under REACH.

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.
P5c FLAMMABLE LIQUIDS

Waters Protection Ordinance (WPO 814.201)
Water pollution class : Swiss Class B, (www.tankportal.ch)

Other regulations:

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

Product is subject to Störfallverordnung (StFV).
Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act – Mutterschutzverordnung).
Compliance with the requirements of the Youth Employment Protection Ordinance (ArGV 5, SR 822.115) must be ensured.
Maternity Protection Act (Mutterschutzverordnung) - Not Applicable.
Compliance with the requirements of the Youth Employment Protection Ordinance (ArGV 5, SR 822.115) & Ordinance on Dangerous Labour for Young People (SR 822.115.2) must be ensured.

The components of this product are reported in the following inventories:

AIIC	: Listed
DSL	: Listed
IECSC	: Listed
ENCS	: Listed
KECI	: Listed
PICCS	: Listed
TSCA	: Listed
TCSI	: Listed

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version	Revision Date:	SDS Number:	Date of last issue: 31.10.2024
4.3	17.02.2025	800001033919	Print Date 24.02.2025

NZIoC : Listed

15.2 Chemical safety assessment

A Chemical Safety Assessment has been carried out for this substance.

SECTION 16: Other information

Full text of other abbreviations

CH BAT	: Switzerland. List of BAT-values
CH SUVA	: Switzerland. Limit values at the work place
CH SUVA / TWA	: Time Weighted Average
CH SUVA / STEL	: Short Term Exposure Limit

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Training advice : Provide adequate information, instruction and training for operators.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version 4.3	Revision Date: 17.02.2025	SDS Number: 800001033919	Date of last issue: 31.10.2024 Print Date 24.02.2025
----------------	------------------------------	-----------------------------	---

Other information : For Industry guidance and tools on REACH please visit the CEFIC website at <http://cefic.org/Industry-support>.
The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB.

A vertical bar (|) in the left margin indicates an amendment from the previous version.

Sources of key data used to compile the Safety Data Sheet : The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID data base, EC 1272 regulation, etc).

Classification of the mixture:

Flam. Liq. 2	H225
Eye Irrit. 2	H319
Acute Tox. 4	H332
STOT SE 3	H336
Carc. 2	H351

Classification procedure:

On basis of test data.
Expert judgement and weight of evidence determination.
Expert judgement and weight of evidence determination.
Expert judgement and weight of evidence determination.
Expert judgement and weight of evidence determination.

Identified Uses according to the Use Descriptor System

Uses - Worker

Title : Manufacture of substance
- Industrial

Uses - Worker

Title : Use as an intermediate
- Industrial

Uses - Worker

Title : Distribution of substance
- Industrial

Uses - Worker

Title : Formulation & (re)packing of substances and mixtures
- Industrial

Uses - Worker

Title : Uses in Coatings
- Industrial

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version 4.3	Revision Date: 17.02.2025	SDS Number: 800001033919	Date of last issue: 31.10.2024 Print Date 24.02.2025
----------------	------------------------------	-----------------------------	---

Uses - Worker

Title : Uses in Coatings
- Professional

Uses - Worker

Title : Use in Cleaning Agents
- Industrial

Uses - Worker

Title : Use in Cleaning Agents
- Professional

Uses - Worker

Title : Lubricants
- Industrial

Uses - Worker

Title : Use in Agrochemicals uses
- Professional

Uses - Worker

Title : Use in laboratories
- Industrial

Uses - Worker

Title : Use in laboratories
- Professional

Identified Uses according to the Use Descriptor System

Uses - Consumer

Title : Uses in Coatings
- Consumer

Uses - Consumer

Title : Use in Cleaning Agents
- Consumer

Uses - Consumer

Title : Use in lubricants
- Consumer

Uses - Consumer

Title : Other Consumer Uses

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version	Revision Date:	SDS Number:	Date of last issue: 31.10.2024
4.3	17.02.2025	800001033919	Print Date 24.02.2025

- Consumer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CH / EN

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version
4.3

Revision Date:
17.02.2025

SDS Number:
800001033919

Date of last issue: 31.10.2024
Print Date 24.02.2025

Exposure Scenario - Worker

300000000394	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Manufacture of substance- Industrial
Use Descriptor	Sector of Use: SU 3, SU8, SU9 Process Categories: PROC 1, PROC 2, PROC 3, PROC 4, PROC 8a, PROC 8b, PROC 15 Environmental Release Categories: ERC1, ERC4
Scope of process	Manufacture of the substance or use as a process chemical or extraction agent. Includes recycling/ recovery, material transfers, storage, maintenance and loading (including marine vessel/barge, road/rail car and bulk container), sampling and associated laboratory activities.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Additional Information	No exposure assessment presented for the environment.	
Section 2.1	Control of Worker Exposure	
Product Characteristics		
Physical form of product	Liquid, vapour pressure 0.5 - 10 kPa at STP	
Concentration of the Substance in Mixture/Article	Covers use of substance/product up to 100% (unless stated differently).,	
Frequency and Duration of Use		
Covers daily exposures up to 8 hours (unless stated differently).		
Other Operational Conditions affecting Exposure		
Assumes a good basic standard of occupational hygiene is implemented. Assumes use at not more than 20°C above ambient temperature (unless stated differently).		
Contributing Scenarios	Risk Management Measures	
General measures (eye irritants).	Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands.	
General exposures (closed systems)no sam- plingPROC1	No other specific measures identified.	
General exposures (closed systems)with sample col- lectionPROC2PROC3	No other specific measures identified.	
General exposures (open systems)IndoorPROC4	Provide extraction ventilation at points where emissions occur.	
General exposures (open systems)OutdoorPROC4	Ensure operation is undertaken outdoors. Wear suitable gloves tested to EN374.	

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version
4.3

Revision Date:
17.02.2025

SDS Number:
800001033919

Date of last issue: 31.10.2024
Print Date 24.02.2025

Process samplingPROC8b	Ensure samples are obtained under containment or extract ventilation.
Bulk transfersDedicated facilityPROC8b	Provide a good standard of general or controlled ventilation (5 to 15 air changes per hour). , or: Ensure material transfers are under containment or extract ventilation. Clear transfer lines prior to de-coupling. Wear suitable gloves tested to EN374.
Equipment cleaning and maintenancePROC8a	Drain down system prior to equipment opening or maintenance. Wear chemically resistant gloves (tested to EN374) in combination with specific activity training. Retain drain downs in sealed storage pending disposal or for subsequent recycle. Clear spills immediately.
Laboratory activitiesPROC15	No other specific measures identified.
Storage.PROC1PROC2	Store substance within a closed system.
Section 2.2	Control of Environmental Exposure
No exposure assessment presented for the environment.	

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	

Section 3.2 -Environment
No exposure assessment presented for the environment.

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	
Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.	

Section 4.2 -Environment
No exposure assessment presented for the environment.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version
4.3

Revision Date:
17.02.2025

SDS Number:
800001033919

Date of last issue: 31.10.2024
Print Date 24.02.2025

Exposure Scenario - Worker

300000000395	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Use as an intermediate- Industrial
Use Descriptor	Sector of Use: SU 3, SU8, SU9 Process Categories: PROC 1, PROC 2, PROC 3, PROC 4, PROC 8a, PROC 8b, PROC 15 Environmental Release Categories: ERC6a
Scope of process	Use of substance as an intermediate (not related to Strictly Controlled Conditions). Includes recycling/ recovery, material transfers, storage, sampling, associated laboratory activities, maintenance and loading (including marine vessel/barge, road/rail car and bulk container).

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Additional Information	No exposure assessment presented for the environment.	
Section 2.1	Control of Worker Exposure	
Product Characteristics		
Physical form of product	Liquid, vapour pressure 0.5 - 10 kPa at STP	
Concentration of the Substance in Mixture/Article	Covers use of substance/product up to 100% (unless stated differently).,	
Frequency and Duration of Use		
Covers daily exposures up to 8 hours (unless stated differently).		
Other Operational Conditions affecting Exposure		
Assumes a good basic standard of occupational hygiene is implemented. Assumes use at not more than 20°C above ambient temperature (unless stated differently).		
Contributing Scenarios	Risk Management Measures	
General measures (eye irritants).	Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands.	
General exposures (closed systems)no sam- plingPROC1	No other specific measures identified.	
General exposures (closed systems)with sample col- lectionPROC2PROC3	No other specific measures identified.	
General exposures (open systems)IndoorPROC4	Provide extraction ventilation at points where emissions occur.	
General exposures (open systems)OutdoorPROC4	Ensure operation is undertaken outdoors. Wear suitable gloves tested to EN374.	

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version 4.3 Revision Date: 17.02.2025 SDS Number: 800001033919 Date of last issue: 31.10.2024
Print Date 24.02.2025

Process samplingPROC8b	Ensure samples are obtained under containment or extract ventilation.
Bulk transfersDedicated facilityPROC8b	Provide a good standard of general or controlled ventilation (5 to 15 air changes per hour). , or: Ensure material transfers are under containment or extract ventilation. Clear transfer lines prior to de-coupling. Wear suitable gloves tested to EN374.
Equipment cleaning and maintenancePROC8a	Drain down system prior to equipment opening or maintenance. Wear chemically resistant gloves (tested to EN374) in combination with specific activity training. Retain drain downs in sealed storage pending disposal or for subsequent recycle. Clear spills immediately.
Laboratory activitiesPROC15	No other specific measures identified.
Storage.PROC1PROC2	Store substance within a closed system.
Section 2.2	Control of Environmental Exposure
No exposure assessment presented for the environment.	

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	

Section 3.2 -Environment
No exposure assessment presented for the environment.

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	
Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.	

Section 4.2 -Environment
No exposure assessment presented for the environment.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version
4.3

Revision Date:
17.02.2025

SDS Number:
800001033919

Date of last issue: 31.10.2024
Print Date 24.02.2025

Exposure Scenario - Worker

300000000396	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Distribution of substance- Industrial
Use Descriptor	Sector of Use: SU 3, SU8, SU9 Process Categories: PROC 1, PROC 2, PROC 3, PROC 4, PROC 8a, PROC 8b, PROC 9, PROC 15 Environmental Release Categories: ERC1, ERC2, ERC3, ERC4, ERC5, ERC6a, ERC6b, ERC6c, ERC6d, ERC7
Scope of process	Loading (including marine vessel/barge, rail/road car and IBC loading) and repacking (including drums and small packs) of substance, including its sampling, storage, unloading distribution and associated laboratory activities.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Additional Information	No exposure assessment presented for the environment.	
Section 2.1	Control of Worker Exposure	
Product Characteristics		
Physical form of product	Liquid, vapour pressure 0.5 - 10 kPa at STP	
Concentration of the Substance in Mixture/Article	Covers use of substance/product up to 100% (unless stated differently).,	
Frequency and Duration of Use		
Covers daily exposures up to 8 hours (unless stated differently).		
Other Operational Conditions affecting Exposure		
Assumes a good basic standard of occupational hygiene is implemented. Assumes use at not more than 20°C above ambient temperature (unless stated differently).		
Contributing Scenarios	Risk Management Measures	
General measures (eye irritants).	Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands.	
General exposures (closed systems)PROC1	No other specific measures identified.	
General exposures (closed systems)General measures (skin irritants).PROC2	No other specific measures identified.	
General exposures.Use in contained batch processesPROC3	Ensure material transfers are under containment or extract ventilation.	
General exposures (open systems)PROC4	Provide extraction ventilation at points where emissions occur.	
Process samplingPROC3	Ensure samples are obtained under containment or extract	

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version
4.3

Revision Date:
17.02.2025

SDS Number:
800001033919

Date of last issue: 31.10.2024
Print Date 24.02.2025

	ventilation. Avoid carrying out activities involving exposure for more than 4 hours Avoid dip sampling.
Laboratory activitiesPROC15	No other specific measures identified.
Bulk transfersDedicated facilityPROC8b	Provide a good standard of general or controlled ventilation (5 to 15 air changes per hour). , or: Ensure material transfers are under containment or extract ventilation. Clear transfer lines prior to de-coupling. Wear suitable gloves tested to EN374.
Drum and small package fillingPROC9	Fill containers/cans at dedicated filling points supplied with local extract ventilation. Clear spills immediately.
Equipment cleaning and maintenancePROC8a	Drain down and flush system prior to equipment opening or maintenance. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Retain drain downs in sealed storage pending disposal or for subsequent recycle.
Storage.PROC1PROC2	Store substance within a closed system.
Section 2.2	Control of Environmental Exposure
No exposure assessment presented for the environment.	

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	

Section 3.2 -Environment
No exposure assessment presented for the environment.

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	
Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.	

Section 4.2 -Environment

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version
4.3

Revision Date:
17.02.2025

SDS Number:
800001033919

Date of last issue: 31.10.2024
Print Date 24.02.2025

No exposure assessment presented for the environment.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version
4.3

Revision Date:
17.02.2025

SDS Number:
800001033919

Date of last issue: 31.10.2024
Print Date 24.02.2025

Exposure Scenario - Worker

300000000397	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Formulation & (re)packing of substances and mixtures- Industrial
Use Descriptor	Sector of Use: SU 10 Process Categories: PROC 1, PROC 2, PROC 3, PROC 4, PROC 5, PROC 8a, PROC 8b, PROC 9, PROC 14, PROC 15 Environmental Release Categories: ERC2
Scope of process	Formulation, packing and re-packing of the substance and its mixtures in batch or continuous operations, including storage, materials transfers, mixing, tableting, compression, pelletisation, extrusion, large and small scale packing, sampling, maintenance and associated laboratory activities.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Additional Information	No exposure assessment presented for the environment.	
Section 2.1	Control of Worker Exposure	
Product Characteristics		
Physical form of product	Liquid, vapour pressure 0.5 - 10 kPa at STP	
Concentration of the Substance in Mixture/Article	Covers use of substance/product up to 100% (unless stated differently).,	
Frequency and Duration of Use		
Covers daily exposures up to 8 hours (unless stated differently).		
Other Operational Conditions affecting Exposure		
Assumes a good basic standard of occupational hygiene is implemented. Assumes use at not more than 20°C above ambient temperature (unless stated differently).		
Contributing Scenarios		Risk Management Measures
General measures (eye irritants).		Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands.
General exposures (closed systems)PROC1		No other specific measures identified.
General exposures.(closed systems)General measures (skin irritants).PROC2		No other specific measures identified.
General exposures.Use in contained batch processesPROC3		Ensure material transfers are under containment or extract ventilation.
General exposures (open systems)PROC4		Provide extraction ventilation at points where emissions occur.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version
4.3

Revision Date:
17.02.2025

SDS Number:
800001033919

Date of last issue: 31.10.2024
Print Date 24.02.2025

Batch processes at elevated temperaturesPROC3	Formulate in enclosed or ventilated mixing vessels. Provide extraction ventilation at points where emissions occur.
Process samplingPROC3	Ensure samples are obtained under containment or extract ventilation.
Laboratory activitiesPROC15	No other specific measures identified.
Bulk transfersDedicated facilityPROC8b	Ensure material transfers are under containment or extract ventilation.
Mixing operations (open systems)PROC5	Provide extraction ventilation at points where emissions occur. Wear suitable gloves tested to EN374.
Transfer from/pouring from containersManualPROC8a	Use drum pumps or carefully pour from container. Wear suitable gloves tested to EN374.
Drum/batch transfersDedicated facilityPROC8b	Provide extraction ventilation at points where emissions occur.
Production or preparation of articles by tableting, compression, extrusion or pelletisationPROC14	Handle substance within a predominantly closed system provided with extract ventilation.
Drum and small package fillingPROC9	Fill containers/cans at dedicated filling points supplied with local extract ventilation.
Equipment cleaning and maintenancePROC8a	Drain down and flush system prior to equipment opening or maintenance. Wear suitable gloves tested to EN374.
Storage.PROC1PROC2	Store substance within a closed system.
Section 2.2	Control of Environmental Exposure
No exposure assessment presented for the environment.	

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	

Section 3.2 -Environment	
No exposure assessment presented for the environment.	

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version
4.3

Revision Date:
17.02.2025

SDS Number:
800001033919

Date of last issue: 31.10.2024
Print Date 24.02.2025

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.
Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 -Environment

No exposure assessment presented for the environment.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version
4.3

Revision Date:
17.02.2025

SDS Number:
800001033919

Date of last issue: 31.10.2024
Print Date 24.02.2025

Exposure Scenario - Worker

300000000398	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Uses in Coatings- Industrial
Use Descriptor	Sector of Use: SU 3 Process Categories: PROC 1, PROC 2, PROC 3, PROC 4, PROC 5, PROC 7, PROC 8a, PROC 8b, PROC 9, PROC 10, PROC 13, PROC 14, PROC 15 Environmental Release Categories: ERC4
Scope of process	Covers the use in coatings (paints, inks, adhesives, etc) including exposures during use (including materials receipt, storage, preparation and transfer from bulk and semi-bulk, application by spray, roller, spreader, dip, flow, fluidised bed on production lines and film formation) and equipment cleaning, maintenance and associated laboratory activities.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Additional Information	No exposure assessment presented for the environment.	
Section 2.1	Control of Worker Exposure	
Product Characteristics		
Physical form of product	Liquid, vapour pressure 0.5 - 10 kPa at STP	
Concentration of the Substance in Mixture/Article	Covers use of substance/product up to 100% (unless stated differently).,	
Frequency and Duration of Use		
Covers daily exposures up to 8 hours (unless stated differently).		
Other Operational Conditions affecting Exposure		
Assumes a good basic standard of occupational hygiene is implemented. Assumes use at not more than 20°C above ambient temperature (unless stated differently).		
Contributing Scenarios		Risk Management Measures
General measures (eye irritants).		Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands.
General exposures (closed systems)PROC1		No other specific measures identified.
General exposures (closed systems)with sample collectionUse in contained systemsPROC2		No other specific measures identified.
Film formation - force drying, stoving and other technologies.Use in contained systemsPROC2		Ensure material transfers are under containment or extract ventilation.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version
4.3

Revision Date:
17.02.2025

SDS Number:
800001033919

Date of last issue: 31.10.2024
Print Date 24.02.2025

Mixing operations (closed systems)PROC3	Ensure material transfers are under containment or extract ventilation.
Film formation - air dryingPROC4	Provide extraction ventilation at points where emissions occur.
Preparation of material for applicationMixing operations (open systems)PROC5	Provide extraction ventilation at points where emissions occur. Wear suitable gloves tested to EN374.
Spraying (automatic/robotic)PROC7	Carry out in a vented booth provided with laminar airflow. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
ManualSprayingPROC7	Provide a good standard of general or controlled ventilation (5 to 15 air changes per hour). Wear a respirator conforming to EN140 with Type A filter or better. Wear chemically resistant gloves (tested to EN374) in combination with intensive management supervision controls.
Material transfersPROC8aPROC8b	Ensure material transfers are under containment or extract ventilation. Clear transfer lines prior to de-coupling. Wear suitable gloves tested to EN374.
Roller, spreader, flow applicationPROC10	Minimise exposure by partial enclosure of the operation or equipment and provide extract ventilation at openings. Wear suitable gloves tested to EN374.
Dipping, immersion and pouringPROC13	Provide extraction ventilation at points where emissions occur. Avoid manual contact with wet work pieces. Wear suitable gloves tested to EN374.
Laboratory activitiesPROC15	No other specific measures identified.
Material transfersDrum/batch transfersTransfer from/pouring from containersPROC9	Provide extract ventilation to material transfer points and other openings.
Production or preparation of articles by tableting, compression, extrusion or pelletisationPROC14	Provide extraction ventilation at points where emissions occur.
Storage.PROC1	Store substance within a closed system.
Section 2.2	Control of Environmental Exposure
No exposure assessment presented for the environment.	

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version	Revision Date:	SDS Number:	Date of last issue: 31.10.2024
4.3	17.02.2025	800001033919	Print Date 24.02.2025

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

Section 3.2 -Environment

No exposure assessment presented for the environment.

SECTION 4

GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO

Section 4.1 - Health

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.
Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 -Environment

No exposure assessment presented for the environment.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version
4.3

Revision Date:
17.02.2025

SDS Number:
800001033919

Date of last issue: 31.10.2024
Print Date 24.02.2025

Exposure Scenario - Worker

300000000399	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Uses in Coatings- Professional
Use Descriptor	Sector of Use: SU 22 Process Categories: PROC 1, PROC 2, PROC 3, PROC 4, PROC 5, PROC 8a, PROC 8b, PROC 10, PROC 11, PROC 13, PROC 15, PROC 19 Environmental Release Categories: ERC8a, ERC8d
Scope of process	Covers the use in coatings (paints, inks, adhesives, etc) including exposures during use (including materials receipt, storage, preparation and transfer from bulk and semi-bulk, application by spray, roller, brush, spreader by hand or similar methods, and film formation), and equipment cleaning, maintenance and associated laboratory activities.

SECTION 2		OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Additional Information		No exposure assessment presented for the environment.	
Section 2.1		Control of Worker Exposure	
Product Characteristics			
Physical form of product		Liquid, vapour pressure 0.5 - 10 kPa at STP	
Concentration of the Substance in Mixture/Article		Covers use of substance/product up to 100% (unless stated differently).,	
Frequency and Duration of Use			
Covers daily exposures up to 8 hours (unless stated differently).			
Other Operational Conditions affecting Exposure			
Assumes a good basic standard of occupational hygiene is implemented. Assumes use at not more than 20°C above ambient temperature (unless stated differently).			
Contributing Scenarios		Risk Management Measures	
General measures (eye irritants).		Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands.	
General exposures (closed systems)PROC1		No other specific measures identified.	
Filling/ preparation of equipment from drums or containers.Use in contained systemsPROC2		Ensure material transfers are under containment or extract ventilation.	
General exposures (closed systems)Use in contained systemsPROC2		Ensure material transfers are under containment or extract ventilation.	
Preparation of material for applicationUse in contained batch		Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).	

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version
4.3

Revision Date:
17.02.2025

SDS Number:
800001033919

Date of last issue: 31.10.2024
Print Date 24.02.2025

processesPROC3	
Film formation - air dryingIn-doorPROC4	Provide a good standard of general or controlled ventilation (5 to 15 air changes per hour).
Film formation - air dryingOutdoorPROC4	Ensure operation is undertaken outdoors. Avoid carrying out activities involving exposure for more than 1 hour.
Preparation of material for applicationIndoorPROC5	Provide a good standard of general or controlled ventilation (5 to 15 air changes per hour). Wear a respirator conforming to EN140 with Type A filter or better. Wear suitable gloves tested to EN374.
Preparation of material for applicationOutdoorPROC5	Ensure operation is undertaken outdoors. Wear a respirator conforming to EN140 with Type A filter or better. Wear suitable gloves tested to EN374.
Material transfersDrum/batch transfersNon-dedicated facilityPROC8a	Provide a good standard of general or controlled ventilation (5 to 15 air changes per hour). Avoid carrying out activities involving exposure for more than 1 hour. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
Material transfersDrum/batch transfersDedicated facilityPROC8b	Provide extract ventilation to material transfer points and other openings.
Roller, spreader, flow application-IndoorPROC10	Provide a good standard of general or controlled ventilation (5 to 15 air changes per hour). Avoid carrying out activities involving exposure for more than 1 hour. Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.
Roller, spreader, flow applicationOutdoorPROC10	Ensure operation is undertaken outdoors. Wear a respirator conforming to EN140 with Type A filter or better. Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.
ManualSprayingIndoorPROC11	Limit the substance content in the product to 25 %. Carry out in a vented booth or extracted enclosure. Avoid carrying out operation for more than 15 minutes. , or: Wear a respirator conforming to EN140 with Type A filter or better. Wear suitable gloves tested to EN374.
ManualSprayingOutdoorPROC11	Limit the substance content in the product to 5 %. Ensure operation is undertaken outdoors.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version 4.3 Revision Date: 17.02.2025 SDS Number: 800001033919 Date of last issue: 31.10.2024
Print Date 24.02.2025

	Wear a respirator conforming to EN140 with Type A filter or better. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
Dipping, immersion and pouringIndoorPROC13	Provide extraction ventilation at points where emissions occur. Avoid carrying out activities involving exposure for more than 4 hours Wear suitable gloves tested to EN374. Avoid manual contact with wet work pieces.
Dipping, immersion and pouringOutdoorPROC13	Ensure operation is undertaken outdoors. Wear a respirator conforming to EN140 with Type A filter or better. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Avoid manual contact with wet work pieces.
Laboratory activitiesPROC15	Provide a good standard of general or controlled ventilation (5 to 15 air changes per hour).
Hand application - fingerpaints, pastels, adhesivesIndoorPROC19	Ensure doors and windows are opened. Avoid carrying out activities involving exposure for more than 1 hour. Wear chemically resistant gloves (tested to EN374) in combination with intensive management supervision controls.
Hand application - fingerpaints, pastels, adhesivesOutdoorPROC19	Ensure operation is undertaken outdoors. Avoid carrying out activities involving exposure for more than 1 hour. Wear chemically resistant gloves (tested to EN374) in combination with intensive management supervision controls.
Storage.PROC1	Store substance within a closed system.

Section 2.2

Control of Environmental Exposure

No exposure assessment presented for the environment.

SECTION 3

EXPOSURE ESTIMATION

Section 3.1 - Health

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

Section 3.2 -Environment

No exposure assessment presented for the environment.

SECTION 4

GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO

Section 4.1 - Health

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version
4.3

Revision Date:
17.02.2025

SDS Number:
800001033919

Date of last issue: 31.10.2024
Print Date 24.02.2025

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.
Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 -Environment

No exposure assessment presented for the environment.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version
4.3

Revision Date:
17.02.2025

SDS Number:
800001033919

Date of last issue: 31.10.2024
Print Date 24.02.2025

Exposure Scenario - Worker

300000000400	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Use in Cleaning Agents- Industrial
Use Descriptor	Sector of Use: SU 3 Process Categories: PROC 1, PROC 2, PROC 3, PROC 4, PROC 7, PROC 8a, PROC 8b, PROC 10, PROC 13 Environmental Release Categories: ERC4
Scope of process	Covers the use as a component of cleaning products including transfer from storage, pouring/unloading from drums or containers. Exposures during mixing/diluting in the preparatory phase and cleaning activities (including spraying, brushing, dipping, wiping, automated and by hand), related equipment cleaning and maintenance.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
Additional Information	No exposure assessment presented for the environment.
Section 2.1	Control of Worker Exposure
Product Characteristics	
Physical form of product	Liquid, vapour pressure 0.5 - 10 kPa at STP
Concentration of the Substance in Mixture/Article	Covers use of substance/product up to 100% (unless stated differently).,
Frequency and Duration of Use	
Covers daily exposures up to 8 hours (unless stated differently).	
Other Operational Conditions affecting Exposure	
Assumes a good basic standard of occupational hygiene is implemented. Assumes use at not more than 20°C above ambient temperature (unless stated differently).	
Contributing Scenarios	Risk Management Measures
General measures (eye irritants).	Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands.
Bulk transfersNon-dedicated facilityPROC8a	Ensure material transfers are under containment or extract ventilation. Wear suitable gloves tested to EN374.
Automated process with (semi) closed systems.Use in contained systemsPROC2	No other specific measures identified.
Automated process with (semi) closed systems.Drum/batch transfer-	Avoid carrying out activities involving exposure for more than 1 hour. , or:

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version 4.3 Revision Date: 17.02.2025 SDS Number: 800001033919 Date of last issue: 31.10.2024
Print Date 24.02.2025

sUse in contained batch processesPROC3	Wear a respirator conforming to EN140 with Type A filter or better.
Application of cleaning products in closed systemsPROC2	No other specific measures identified.
Filling/ preparation of equipment from drums or containers.Dedicated facilityPROC8b	Ensure material transfers are under containment or extract ventilation.
Use in contained batch processesPROC4	Provide extraction ventilation at points where emissions occur. Avoid carrying out activities involving exposure for more than 4 hours , or: Wear a respirator conforming to EN140 with Type A filter or better.
Degreasing small objects in cleaning stationPROC13	Provide extraction ventilation at points where emissions occur. Wear suitable gloves tested to EN374.
Cleaning with low-pressure washersPROC10	Provide a good standard of general or controlled ventilation (5 to 15 air changes per hour). Avoid carrying out activities involving exposure for more than 1 hour. , or: Wear a respirator conforming to EN140 with Type A filter or better. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
Cleaning with high pressure washersPROC7	Provide a good standard of general or controlled ventilation (5 to 15 air changes per hour). Wear a respirator conforming to EN140 with Type A filter or better. Wear chemically resistant gloves (tested to EN374) in combination with intensive management supervision controls.
ManualSurfacesCleaningno sprayingPROC10	Provide a good standard of general or controlled ventilation (5 to 15 air changes per hour). Wear suitable gloves tested to EN374.
Storage.PROC1	Store substance within a closed system.
Section 2.2	Control of Environmental Exposure
No exposure assessment presented for the environment.	

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version
4.3

Revision Date:
17.02.2025

SDS Number:
800001033919

Date of last issue: 31.10.2024
Print Date 24.02.2025

--

Section 3.2 -Environment

No exposure assessment presented for the environment.

SECTION 4

GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO

Section 4.1 - Health

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.
Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 -Environment

No exposure assessment presented for the environment.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version
4.3

Revision Date:
17.02.2025

SDS Number:
800001033919

Date of last issue: 31.10.2024
Print Date 24.02.2025

Exposure Scenario - Worker

300000000401	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Use in Cleaning Agents- Professional
Use Descriptor	Sector of Use: SU 22 Process Categories: PROC 1, PROC 2, PROC 3, PROC 4, PROC 8a, PROC 8b, PROC 10, PROC 11, PROC 13, PROC 19 Environmental Release Categories: ERC8a, ERC8d
Scope of process	Covers the use as a component of cleaning products including pouring/unloading from drums or containers; and exposures during mixing/diluting in the preparatory phase and cleaning activities (including spraying, brushing, dipping, wiping automated and by hand).

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
Additional Information	No exposure assessment presented for the environment.
Section 2.1	Control of Worker Exposure
Product Characteristics	
Physical form of product	Liquid, vapour pressure 0.5 - 10 kPa at STP
Concentration of the Substance in Mixture/Article	Covers use of substance/product up to 100% (unless stated differently).,
Frequency and Duration of Use	
Covers daily exposures up to 8 hours (unless stated differently).	
Other Operational Conditions affecting Exposure	
Assumes a good basic standard of occupational hygiene is implemented. Assumes use at not more than 20°C above ambient temperature (unless stated differently).	
Contributing Scenarios	Risk Management Measures

General measures (eye irritants).	Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands.
Filling/ preparation of equipment from drums or containers.Dedicated facilityPROC8b	Avoid carrying out activities involving exposure for more than 4 hours Provide a good standard of general or controlled ventilation (5 to 15 air changes per hour). Wear suitable gloves tested to EN374.
Automated process with (semi) closed systems.Use in contained systemsPROC2	Avoid carrying out activities involving exposure for more than 4 hours , or: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version
4.3

Revision Date:
17.02.2025

SDS Number:
800001033919

Date of last issue: 31.10.2024
Print Date 24.02.2025

Automated process with (semi) closed systems.Drum/batch transfersPROC3	Avoid carrying out activities involving exposure for more than 4 hours , or: Wear a respirator conforming to EN140 with Type A filter or better.
Semi Automated process. (e.g.: Semi automatic application of floor care and maintenance products)PROC4	Provide a good standard of general or controlled ventilation (5 to 15 air changes per hour). Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.
Filling/ preparation of equipment from drums or containers.Non-dedicated facilityPROC8a	Ensure operation is undertaken outdoors. Avoid carrying out activities involving exposure for more than 15 minutes. , or: Wear a respirator conforming to EN140 with Type A filter or better. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
ManualSurfacesCleaningDipping, immersion and pouringPROC13	Provide a good standard of general or controlled ventilation (5 to 15 air changes per hour). Avoid carrying out activities involving exposure for more than 1 hour. , or: Wear a respirator conforming to EN140 with Type A filter or better. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
Cleaning with low-pressure washers-Rolling, Brushingno sprayingPROC10	Limit the substance content in the product to 5 %. Provide a good standard of general or controlled ventilation (5 to 15 air changes per hour). Wear suitable gloves tested to EN374.
Cleaning with high pressure washers-SprayingIndoorPROC11	Limit the substance content in the product to 1 %. Provide a good standard of general or controlled ventilation (5 to 15 air changes per hour). Avoid carrying out activities involving exposure for more than 4 hours , or: Wear a respirator conforming to EN140 with Type A filter or better. Wear chemically resistant gloves (tested to EN374) in combination with intensive management supervision controls.
Cleaning with high pressure washers-SprayingOutdoorPROC11	Ensure operation is undertaken outdoors. Limit the substance content in the product to 1 %. Avoid carrying out activities involving exposure for more than 1 hour.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version
4.3

Revision Date:
17.02.2025

SDS Number:
800001033919

Date of last issue: 31.10.2024
Print Date 24.02.2025

	, or: Wear a respirator conforming to EN140 with Type A filter or better. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
ManualSurfacesCleaningSprayingPROC10	Ensure doors and windows are opened. Avoid carrying out activities involving exposure for more than 4 hours , or: Wear a respirator conforming to EN140 with Type A filter or better. Limit the substance content in the product to 25 %. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
Ad hoc manual application via trigger sprays, dipping, etc.Rolling, Brush-ingPROC10	Limit the substance content in the product to 25 %. Provide extraction ventilation at points where emissions occur. Wear suitable gloves tested to EN374. , or: Wear a respirator conforming to EN140 with Type A filter or better. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
Cleaning of medical devicesPROC4	Provide extraction ventilation at points where emissions occur. Avoid carrying out activities involving exposure for more than 4 hours , or: Wear a respirator conforming to EN140 with Type A filter or better.
Storage.PROC1	Store substance within a closed system.

Section 2.2

Control of Environmental Exposure

No exposure assessment presented for the environment.

SECTION 3

EXPOSURE ESTIMATION

Section 3.1 - Health

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

Section 3.2 -Environment

No exposure assessment presented for the environment.

SECTION 4

GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO

Section 4.1 - Health

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version
4.3

Revision Date:
17.02.2025

SDS Number:
800001033919

Date of last issue: 31.10.2024
Print Date 24.02.2025

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.
Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 -Environment

No exposure assessment presented for the environment.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version
4.3

Revision Date:
17.02.2025

SDS Number:
800001033919

Date of last issue: 31.10.2024
Print Date 24.02.2025

Exposure Scenario - Worker

300000000402	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Lubricants- Industrial
Use Descriptor	Sector of Use: SU 3 Process Categories: PROC 1, PROC 2, PROC 3, PROC 4, PROC 7, PROC 8a, PROC 8b, PROC 9, PROC 10, PROC 13, PROC 17, PROC 18 Environmental Release Categories: ERC7, ERC4
Scope of process	Covers the use of formulated lubricants in closed and open systems including transfer operations, operation of machinery/engines and similar articles, reworking on reject articles, equipment maintenance and disposal of wastes.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Additional Information	No exposure assessment presented for the environment.	
Section 2.1	Control of Worker Exposure	
Product Characteristics		
Physical form of product	Liquid, vapour pressure 0.5 - 10 kPa at STP	
Concentration of the Substance in Mixture/Article	Covers use of substance/product up to 100% (unless stated differently).,	
Frequency and Duration of Use		
Covers daily exposures up to 8 hours (unless stated differently).		
Other Operational Conditions affecting Exposure		
Assumes a good basic standard of occupational hygiene is implemented. Assumes use at not more than 20°C above ambient temperature (unless stated differently).		
Contributing Scenarios		Risk Management Measures
General measures (eye irritants).	Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands.	
General exposures (closed systems)PROC1	No other specific measures identified.	
General exposures (closed systems)with sample collectionPROC2PROC3	Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).	
General exposures (open systems)PROC4	Ensure material transfers are under containment or extract ventilation. Wear suitable gloves tested to EN374.	
Bulk transfersDedicated facilityPROC8b	Provide a good standard of general or controlled ventilation (5 to 15 air changes per hour). Wear suitable gloves tested to EN374.	

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version
4.3

Revision Date:
17.02.2025

SDS Number:
800001033919

Date of last issue: 31.10.2024
Print Date 24.02.2025

Filling/ preparation of equipment from drums or containers.Non-dedicated facilityPROC8a	Use drum pumps or carefully pour from container. Wear suitable gloves tested to EN374.
Initial factory fill of equipmentPROC9	Ensure material transfers are under containment or extract ventilation.
Operation and lubrication of high energy open equipmentPROC17PROC18	Provide extraction ventilation at points where emissions occur. Restrict area of openings to equipment. Wear suitable gloves tested to EN374.
ManualRolling, BrushingPROC10	Provide a good standard of controlled ventilation (10 to 15 air changes per hour). Wear suitable gloves tested to EN374. Wear a respirator conforming to EN140 with Type A filter or better.
Treatment by dipping and pouringPROC13	Restrict area of openings to equipment. Allow time for product to drain from workpiece. Provide a good standard of controlled ventilation (10 to 15 air changes per hour). Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
SprayingPROC7	Minimise exposure by partial enclosure of the operation or equipment and provide extract ventilation at openings. Wear suitable gloves (tested to EN374), coverall and eye protection.
Maintenance (of larger plant items) and machine set upDedicated facilityPROC8b	Provide a good standard of controlled ventilation (10 to 15 air changes per hour). Ensure material transfers are under containment or extract ventilation. Provide extract ventilation to emission points when contact with warm (>50oC) product is likely. Wear suitable gloves tested to EN374.
Maintenance of small itemsNon-dedicated facilityPROC8a	Provide a good standard of controlled ventilation (10 to 15 air changes per hour). Wear suitable gloves tested to EN374. Avoid manual contact with wet work pieces. Retain drain downs in sealed storage pending disposal or for subsequent recycle.
Remanufacture of reject articlesPROC9	Provide a good standard of controlled ventilation (10 to 15 air changes per hour). Wear suitable gloves tested to EN374.
Storage.PROC1PROC2	Store substance within a closed system.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version 4.3 Revision Date: 17.02.2025 SDS Number: 800001033919 Date of last issue: 31.10.2024
Print Date 24.02.2025

Section 2.2	Control of Environmental Exposure
No exposure assessment presented for the environment.	

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	

Section 3.2 -Environment	
No exposure assessment presented for the environment.	

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	
Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.	

Section 4.2 -Environment	
No exposure assessment presented for the environment.	

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version
4.3

Revision Date:
17.02.2025

SDS Number:
800001033919

Date of last issue: 31.10.2024
Print Date 24.02.2025

Exposure Scenario - Worker

300000000403	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Use in Agrochemicals uses- Professional
Use Descriptor	Sector of Use: SU 22 Process Categories: PROC 1, PROC 2, PROC 4, PROC 8a, PROC 8b, PROC 11, PROC 13 Environmental Release Categories: ERC8a, ERC8d
Scope of process	Use as an agrochemical excipient for application by manual or machine spraying, smokes and fogging; including equipment clean-downs and disposal.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Additional Information	No exposure assessment presented for the environment.	
Section 2.1	Control of Worker Exposure	
Product Characteristics		
Physical form of product	Liquid, vapour pressure 0.5 - 10 kPa at STP	
Concentration of the Substance in Mixture/Article	Covers use of substance/product up to 100% (unless stated differently).,	
Frequency and Duration of Use		
Covers daily exposures up to 8 hours (unless stated differently).		
Other Operational Conditions affecting Exposure		
Assumes a good basic standard of occupational hygiene is implemented. Assumes use at not more than 20°C above ambient temperature (unless stated differently).		
Contributing Scenarios	Risk Management Measures	
General measures (eye irritants).	Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands.	
Transfer from/pouring from containersDedicated facilityPROC8b	Avoid carrying out activities involving exposure for more than 1 hour. Wear suitable gloves tested to EN374.	
Mixing in containers.PROC4	Avoid carrying out activities involving exposure for more than 1 hour. Ensure operation is undertaken outdoors.	
Spraying/ fogging by manual applicationPROC11	Provide a good standard of general or controlled ventilation (5 to 15 air changes per hour). Wear chemically resistant gloves (tested to EN374) in combination with intensive management supervision controls. Wear a respirator conforming to EN140 with Type A filter or better.	

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version 4.3 Revision Date: 17.02.2025 SDS Number: 800001033919 Date of last issue: 31.10.2024
Print Date 24.02.2025

	Avoid carrying out operation for more than 4 hours.
Spraying/ fogging by machine application PROC11	Provide extraction ventilation at points where emissions occur. Apply within a vented cab supplied with filtered air under positive pressure and with a protection factor of >20. Wear a respirator conforming to EN140 with Type A filter or better. Wear chemically resistant gloves (tested to EN374) in combination with intensive management supervision controls.
Ad hoc manual application via trigger sprays, dipping, etc. PROC13	Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Avoid carrying out activities involving exposure for more than 1 hour. Limit the substance content in the product to 25 %.
Equipment cleaning and maintenance PROC8a	Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Avoid carrying out activities involving exposure for more than 1 hour. Limit the substance content in the product to 25 %. Retain drain downs in sealed storage pending disposal or for subsequent recycle.
Storage. PROC1 PROC2	Store substance within a closed system. Ensure operation is undertaken outdoors.
Section 2.2	Control of Environmental Exposure
No exposure assessment presented for the environment.	

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	

Section 3.2 -Environment
No exposure assessment presented for the environment.

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	
Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.	

Section 4.2 -Environment

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version
4.3

Revision Date:
17.02.2025

SDS Number:
800001033919

Date of last issue: 31.10.2024
Print Date 24.02.2025

No exposure assessment presented for the environment.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version
4.3

Revision Date:
17.02.2025

SDS Number:
800001033919

Date of last issue: 31.10.2024
Print Date 24.02.2025

Exposure Scenario - Worker

300000000420	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Use in laboratories- Industrial
Use Descriptor	Sector of Use: SU 3 Process Categories: PROC 10, PROC 15 Environmental Release Categories: ERC2, ERC4
Scope of process	Use of the substance within laboratory settings, including material transfers and equipment cleaning.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Additional Information	No exposure assessment presented for the environment.	
Section 2.1	Control of Worker Exposure	
Product Characteristics		
Physical form of product	Liquid, vapour pressure 0.5 - 10 kPa at STP	
Concentration of the Substance in Mixture/Article	Covers use of substance/product up to 100% (unless stated differently).,	
Frequency and Duration of Use		
Covers daily exposures up to 8 hours (unless stated differently).		
Other Operational Conditions affecting Exposure		
Assumes a good basic standard of occupational hygiene is implemented. Assumes activities are at ambient temperature (unless stated differently).		
Contributing Scenarios		Risk Management Measures
General measures (eye irritants).		Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands.
Laboratory activitiesPROC15		Handle within a fume cupboard or implement suitable equivalent methods to minimise exposure.
CleaningPROC10		Handle within a fume cupboard or implement suitable equivalent methods to minimise exposure. Retain drain downs in sealed storage pending disposal or for subsequent recycle. Wear suitable gloves tested to EN374.
Section 2.2	Control of Environmental Exposure	
No exposure assessment presented for the environment.		

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version
4.3

Revision Date:
17.02.2025

SDS Number:
800001033919

Date of last issue: 31.10.2024
Print Date 24.02.2025

--

Section 3.2 -Environment

No exposure assessment presented for the environment.

SECTION 4

GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO

Section 4.1 - Health

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.
Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 -Environment

No exposure assessment presented for the environment.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version
4.3

Revision Date:
17.02.2025

SDS Number:
800001033919

Date of last issue: 31.10.2024
Print Date 24.02.2025

Exposure Scenario - Worker

300000000421	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Use in laboratories- Professional
Use Descriptor	Sector of Use: SU 22 Process Categories: PROC 10, PROC 15 Environmental Release Categories: ERC8a
Scope of process	Use of small quantities within laboratory settings, including material transfers and equipment cleaning.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Additional Information	No exposure assessment presented for the environment.	
Section 2.1	Control of Worker Exposure	
Product Characteristics		
Physical form of product	Liquid, vapour pressure 0.5 - 10 kPa at STP	
Concentration of the Substance in Mixture/Article	Covers use of substance/product up to 100% (unless stated differently).,	
Frequency and Duration of Use		
Covers daily exposures up to 8 hours (unless stated differently).		
Other Operational Conditions affecting Exposure		
Assumes a good basic standard of occupational hygiene is implemented. Assumes activities are at ambient temperature (unless stated differently).		
Contributing Scenarios	Risk Management Measures	
General measures (eye irritants).	Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands.	
Laboratory activitiesPROC15	Handle within a fume cupboard or implement suitable equivalent methods to minimise exposure.	
CleaningPROC10	Handle within a fume cupboard or implement suitable equivalent methods to minimise exposure. Retain drain downs in sealed storage pending disposal or for subsequent recycle. Wear suitable gloves tested to EN374.	
Section 2.2	Control of Environmental Exposure	
No exposure assessment presented for the environment.		

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version
4.3

Revision Date:
17.02.2025

SDS Number:
800001033919

Date of last issue: 31.10.2024
Print Date 24.02.2025

--

Section 3.2 -Environment

No exposure assessment presented for the environment.

SECTION 4

GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
--

Section 4.1 - Health

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 -Environment

No exposure assessment presented for the environment.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version
4.3

Revision Date:
17.02.2025

SDS Number:
800001033919

Date of last issue: 31.10.2024
Print Date 24.02.2025

Exposure Scenario - Consumer

300000001035	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Uses in Coatings - Consumer
Use Descriptor	Sector of Use: SU 21 Product Categories: PC1, PC4, PC8 (excipient only), PC9a, PC9b, PC9c, PC15, PC18, PC23, PC24, PC31, PC34 Environmental Release Categories: ERC8a, ERC8d
Scope of process	Covers the use in coatings (paints, inks, adhesives, etc) including exposures during use (including product transfer and preparation, application by brush, spray by hand or similar methods) and equipment cleaning.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Additional Information	No exposure assessment presented for the environment.	
Section 2.1	Control of Consumer Exposure	
Product Characteristics		
Physical form of product	Liquid, vapour pressure > 10 kPa at STP	
Concentration of the Sub-stance in Mixture/Article	Unless stated otherwise.	
	Covers concentration up to (%): 100 %	
Amounts Used		
Unless stated otherwise.		
for each use event, covers amount up to (g):		13.800
covers skin contact area (cm2):		857,5
Frequency and Duration of Use		
Unless stated otherwise.		
covers use up to (times/day of use):		1
Exposure (hours/event):		6
Other Operational Conditions affecting Exposure		
Unless stated otherwise. Covers use at ambient temperatures. Covers use in room size of 20m3 Covers use under typical household ventilation.		
Product Categories	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Adhesives, sealants Glues, hobby use.	Covers concentrations up to 30 %	
	covers use up to 365 day/year	
	covers use up to 1 times/day of use	
	covers skin contact area up to (cm2): 35,73 cm2	
	For each use event, covers amount up to 5 g	
	Covers use in room size of 20 m3	

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version
4.3

Revision Date:
17.02.2025

SDS Number:
800001033919

Date of last issue: 31.10.2024
Print Date 24.02.2025

	Covers exposure up to 4 hours/event
Adhesives, sealants Glues DIY-use (carpet glue, tile glue, wood parquet glue).	Covers concentrations up to 30 %
	covers use up to 1 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 110,00 cm2
	For each use event, covers amount up to 6.390 g
	Covers use in room size of 20 m3
	Covers exposure up to 6,00 hours/event
	Avoid using when windows closed.
Adhesives, sealants Glue from spray.	Covers concentrations up to 30 %
	covers use up to 6 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 35,73 cm2
	For each use event, covers amount up to 85,05 g
	Covers use in room size of 20 m3
	Covers exposure up to 4,00 hours/event
Adhesives, sealants Seal- ants.	Covers concentrations up to 5,5 %
	covers use up to 365 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 35,73 cm2
	For each use event, covers amount up to 75 g
	Covers use in room size of 20 m3
	Covers exposure up to 1,00 hours/event
	Avoid using when windows closed.
Anti-Freeze and de-icing products Washing car win- dow.	Covers concentrations up to 1 %
	covers use up to 365 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 857,50 cm2
	For each use event, covers amount up to 0,5 g
	Covers use in a one car garage (34 m3) under typical ventila- tion.
	Covers use in room size of 34 m3
	Covers exposure up to 0,02 hours/event
Anti-Freeze and de-icing products Pouring into radia- tor.	Covers concentrations up to 1,2 %
	covers use up to 365 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 428,00 cm2
	For each use event, covers amount up to 2.000 g
	Covers use in a one car garage (34 m3) under typical ventila- tion.
	Covers use in room size of 34 m3
	Covers exposure up to 0,17 hours/event
Anti-Freeze and de-icing	Covers concentrations up to 2,5 %

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version
4.3

Revision Date:
17.02.2025

SDS Number:
800001033919

Date of last issue: 31.10.2024
Print Date 24.02.2025

products Lock de-icer.	
	covers use up to 365 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 214,40 cm2
	For each use event, covers amount up to 4 g
	Covers use in a one car garage (34 m3) under typical ventilation.
	Covers use in room size of 34 m3
	Covers exposure up to 0,25 hours/event
Biocidal products (e.g. Disinfectants, pest control) (excipient only). Laundry and dish washing products.	Covers concentrations up to 5 %
	covers use up to 365 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 857,50 cm2
	For each use event, covers amount up to 15 g
	Covers use in room size of 20 m3
	Covers exposure up to 0,50 hours/event
Biocidal products (e.g. Disinfectants, pest control) (excipient only). Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners).	Covers concentrations up to 5 %
	covers use up to 128 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 857,50 cm2
	For each use event, covers amount up to 27 g
	Covers use in room size of 20 m3
	Covers exposure up to 0,33 hours/event
Biocidal products (e.g. Disinfectants, pest control) (excipient only). Cleaners, trigger sprays (all purpose cleaners, sanitary products, glass cleaners).	Covers concentrations up to 15 %
	covers use up to 128 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 428,00 cm2
	For each use event, covers amount up to 35 g
	Covers use in room size of 20 m3
	Covers exposure up to 0,17 hours/event
Coatings and paints, thinners, paint removers Waterborne latex wall paint.	Covers concentrations up to 1,5 %
	covers use up to 4 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 428,75 cm2

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version
4.3

Revision Date:
17.02.2025

SDS Number:
800001033919

Date of last issue: 31.10.2024
Print Date 24.02.2025

	For each use event, covers amount up to 2.760 g
	Covers use in room size of 20 m3
	Covers exposure up to 2,20 hours/event
Coatings and paints, thinners, paint removers Solvent rich, high solid, water borne paint.	Covers concentrations up to 27,5 %
	covers use up to 6 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 428,75 cm2
	For each use event, covers amount up to 744 g
	Covers use in room size of 20 m3
	Covers exposure up to 2,20 hours/event
Coatings and paints, thinners, paint removers Aerosol spray can.	Covers concentrations up to 50 %
	covers use up to 2 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 857,50 cm2
	For each use event, covers amount up to 215 g
	Covers use in a one car garage (34 m3) under typical ventilation.
	Covers use in room size of 34 m3
	Covers exposure up to 0,33 hours/event
Coatings and paints, thinners, paint removers Removers (paint-, glue-, wall paper-, sealant-remover).	Covers concentrations up to 50 %
	covers use up to 3 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 857,50 cm2
	for each use event, covers amount up to (g): 491 g
	Covers use in room size of 20 m3
	Covers exposure up to 2,00 hours/event
Fillers, putties, plasters, modelling clay Fillers and putty.	Covers concentrations up to 2 %
	covers use up to 12 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 35,73 cm2
	For each use event, covers amount up to 85 g
	Covers use in room size of 20 m3
	Covers exposure up to 4,00 hours/event
Fillers, Putties Plasters and floor equalizers.	Covers concentrations up to 1,2 %
	covers use up to 12 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 857,50 cm2
	For each use event, covers amount up to 13.800 g
	Covers use in room size of 20 m3
	Covers exposure up to 2,00 hours/event

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version
4.3

Revision Date:
17.02.2025

SDS Number:
800001033919

Date of last issue: 31.10.2024
Print Date 24.02.2025

	Avoid using when windows closed.
Fillers, putties, plasters, modelling clay Modelling clay.	Covers concentrations up to 1 %
	covers use up to 365 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 254,40 cm2
	For each use event, assumes swallowed amount of 1 g
	Covers use in room size of 20 m3
	Covers exposure up to 2,20 hours/event
Finger paints Finger paints	Covers concentrations up to 0,25 %
	covers use up to 365 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 254,40 cm2
	For each use event, assumes swallowed amount of 1,35 g
	Covers use in room size of 20 m3
	Covers exposure up to 2,20 hours/event
Non-metal-surface treatment products Waterborne latex wall paint.	Covers concentrations up to 1,5 %
	covers use up to 4 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 428,75 cm2
	For each use event, covers amount up to 2.760 g
	Covers use in room size of 20 m3
	Covers exposure up to 2,20 hours/event
Non-metal-surface treatment products Solvent rich, high solid, water borne paint.	Covers concentrations up to 27,5 %
	covers use up to 6 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 428,75 cm2
	For each use event, covers amount up to 744 g
	Covers use in room size of 20 m3
	Covers exposure up to 2,20 hours/event
Non-metal-surface treatment products Aerosol spray can.	Covers concentrations up to 50 %
	covers use up to 2 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 857,50 cm2
	For each use event, covers amount up to 215 g
	Covers use in a one car garage (34 m3) under typical ventilation.
	Covers use in room size of 34 m3
	Covers exposure up to 0,33 hours/event
Non-metal-surface treatment products Removers (paint-, glue-, wall paper-, sealant-remover).	Covers concentrations up to 50 %

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version
4.3

Revision Date:
17.02.2025

SDS Number:
800001033919

Date of last issue: 31.10.2024
Print Date 24.02.2025

	covers use up to 3 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 857,50 cm2
	For each use event, covers amount up to 491 g
	Covers use in room size of 20 m3
	Covers exposure up to 2,00 hours/event
Ink and toners Inks and toners.	Covers concentrations up to 10 %
	covers use up to 365 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 71,40 cm2
	For each use event, covers amount up to 40 g
	Covers use in room size of 20 m3
	Covers exposure up to 2,20 hours/event
Leather tanning, dye, finishing, impregnation and care products Polishes, wax / cream (floor, furniture, shoes).	Covers concentrations up to 50 %
	covers use up to 29 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 430,00 cm2
	For each use event, covers amount up to 56 g
	Covers use in room size of 20 m3
	Covers exposure up to 1,23 hours/event
Leather tanning, dye, finishing, impregnation and care products Polishes, spray (furniture, shoes).	Covers concentrations up to 50 %
	covers use up to 8 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 430,00 cm2
	For each use event, covers amount up to 56 g
	Covers use in room size of 20 m3
	Covers exposure up to 0,33 hours/event
Lubricants, greases, re-release products Liquids.	Covers concentrations up to 100 %
	covers use up to 4 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 468,00 cm2
	For each use event, covers amount up to 2.200 g
	Covers use in a one car garage (34 m3) under typical ventilation.
	Covers use in room size of 34 m3
	Covers exposure up to 0,17 hours/event
Lubricants, greases, re-release products Pastes.	Covers concentrations up to 20 %
	covers use up to 10 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 468,00 cm2
	For each use event, covers amount up to 34 g

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version
4.3

Revision Date:
17.02.2025

SDS Number:
800001033919

Date of last issue: 31.10.2024
Print Date 24.02.2025

	Covers use in room size of 20 m3
Lubricants, greases, re-release products Sprays.	Covers concentrations up to 50 %
	covers use up to 6 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 428,75 cm2
	For each use event, covers amount up to 73 g
	Covers use in room size of 20 m3
	Covers exposure up to 0,17 hours/event
Polishes and wax blends Polishes, wax / cream (floor, furniture, shoes).	Covers concentrations up to 10 %
	covers use up to 29 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 430,00 cm2
	For each use event, covers amount up to 142 g
	Covers use in room size of 20 m3
	Covers exposure up to 1,23 hours/event
Polishes and wax blends Polishes, spray (furniture, shoes).	Covers concentrations up to 50 %
	covers use up to 8 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 430,00 cm2
	For each use event, covers amount up to 35 g
	Covers use in room size of 20 m3
	Covers exposure up to 0,33 hours/event
Textile dyes, finishing and impregnating products; including bleaches and other processing aids	Covers concentrations up to 2,5 %
	covers use up to 365 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 857,50 cm2
	For each use event, covers amount up to 115 g
	Covers use in room size of 20 m3
	Covers exposure up to 1,00 hours/event

Section 2.2	Control of Environmental Exposure
No exposure assessment presented for the environment.	

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
The ECETOC TRA tool has been used to estimate consumer exposures unless otherwise indicated.	

Section 3.2 -Environment
No exposure assessment presented for the environment.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version
4.3

Revision Date:
17.02.2025

SDS Number:
800001033919

Date of last issue: 31.10.2024
Print Date 24.02.2025

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	
Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.	
Section 4.2 -Environment	
No exposure assessment presented for the environment.	

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version 4.3 Revision Date: 17.02.2025 SDS Number: 800001033919 Date of last issue: 31.10.2024
Print Date 24.02.2025

Exposure Scenario - Consumer

300000001036	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Use in Cleaning Agents - Consumer
Use Descriptor	Sector of Use: SU 21 Product Categories: PC3, PC4, PC8 (excipient only), PC9a, PC24, PC35, PC38 Environmental Release Categories: ERC8a, ERC8d
Scope of process	Covers general exposures to consumers arising from the use of household products sold as washing and cleaning products, aerosols, coatings, de-icers, lubricants and air care products.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Additional Information	No exposure assessment presented for the environment.	
Section 2.1	Control of Consumer Exposure	
Product Characteristics		
Physical form of product	Liquid, vapour pressure > 10 kPa at STP	
Concentration of the Sub-stance in Mixture/Article	Unless stated otherwise.	
	Covers concentration up to (%): 100 %	
Amounts Used		
Unless stated otherwise.		
for each use event, covers amount up to (g):		13.800
covers skin contact area (cm2):		857,5
Frequency and Duration of Use		
Unless stated otherwise.		
covers use up to (times/day of use):		4
Exposure (hours/event):		8
Other Operational Conditions affecting Exposure		
Unless stated otherwise. Covers use at ambient temperatures. Covers use in room size of 20m3 Covers use under typical household ventilation.		
Product Categories	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Air care products Air care, instant action (aerosol sprays).	Covers concentrations up to 50 %	
	covers use up to 365 day/year	
	covers use up to 4 times/day of use	
	for each use event, covers amount up to (g): 0,1 g	
	Covers use in room size of 20 m3	

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version
4.3

Revision Date:
17.02.2025

SDS Number:
800001033919

Date of last issue: 31.10.2024
Print Date 24.02.2025

	Covers exposure up to 0,25 hours/event
Air care products Air care, continuous action (solid and liquid).	Covers concentrations up to 10 %
	covers use up to 365 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 35,70 cm2
	For each use event, covers amount up to 0,48 g
	Covers use in room size of 20 m3
	Covers exposure up to 8,00 hours/event
Anti-Freeze and de-icing products Washing car window.	Covers concentrations up to 1 %
	covers use up to 365 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 857,50 cm2
	For each use event, covers amount up to 0,5 g
	Covers use in a one car garage (34 m3) under typical ventilation.
	Covers use in room size of 34 m3
	Covers exposure up to 0,02 hours/event
Anti-Freeze and de-icing products Pouring into radiator.	Covers concentrations up to 1,2 %
	covers use up to 365 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 428,00 cm2
	For each use event, covers amount up to 2.000 g
	Covers use in a one car garage (34 m3) under typical ventilation.
	Covers use in room size of 34 m3
	Covers exposure up to 0,17 hours/event
Anti-Freeze and de-icing products Lock de-icer.	Covers concentrations up to 2,5 %
	covers use up to 365 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 214,40 cm2
	For each use event, covers amount up to 4 g
	Covers use in a one car garage (34 m3) under typical ventilation.
	Covers use in room size of 34 m3
	Covers exposure up to 0,25 hours/event
Biocidal products (e.g. Disinfectants, pest control) (excipient only). Laundry and dish washing products.	Covers concentrations up to 5 %
	covers use up to 365 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 857,50 cm2
	For each use event, covers amount up to 15 g
	Covers use in room size of 20 m3

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version
4.3

Revision Date:
17.02.2025

SDS Number:
800001033919

Date of last issue: 31.10.2024
Print Date 24.02.2025

	Covers exposure up to 0,50 hours/event
Biocidal products (e.g. Disinfectants, pest control) (excipient only). Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners).	Covers concentrations up to 5 %
	covers use up to 128 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 857,50 cm2
	For each use event, covers amount up to 27 g
	Covers use in room size of 20 m3
	Covers exposure up to 0,33 hours/event
Biocidal products (e.g. Disinfectants, pest control) (excipient only). Cleaners, trigger sprays (all purpose cleaners, sanitary products, glass cleaners).	Covers concentrations up to 15 %
	covers use up to 128 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 428,00 cm2
	For each use event, covers amount up to 35 g
	Covers use in room size of 20 m3
	Covers exposure up to 0,17 hours/event
Coatings and paints, thinners, paint removers Aerosol spray can.	Covers concentrations up to 50 %
	covers use up to 2 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 857,50 cm2
	For each use event, covers amount up to 215 g
	Covers use in a one car garage (34 m3) under typical ventilation.
	Covers use in room size of 34 m3
	Covers exposure up to 0,33 hours/event
Coatings and paints, thinners, paint removers Removers (paint-, glue-, wall paper-, sealant-remover).	Covers concentrations up to 50 %
	covers use up to 3 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 857,50 cm2
	For each use event, covers amount up to 491 g
	Covers use in room size of 20 m3
	Covers exposure up to 2,00 hours/event
Lubricants, greases, release products Liquids.	Covers concentrations up to 100 %
	covers use up to 4 day/year

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version
4.3

Revision Date:
17.02.2025

SDS Number:
800001033919

Date of last issue: 31.10.2024
Print Date 24.02.2025

	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 468,00 cm2
	For each use event, covers amount up to 2.200 g
	Covers use in a one car garage (34 m3) under typical ventilation.
	Covers use in room size of 34 m3
	Covers exposure up to 0,17 hours/event
Lubricants, greases, re-lease products Pastes.	Covers concentrations up to 20 %
	covers use up to 10 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 468,00 cm2
	For each use event, covers amount up to 34 g
	Covers use in room size of 20 m3
	Covers exposure up to 8,00 hours/event
Lubricants, greases, re-lease products Sprays.	Covers concentrations up to 50 %
	covers use up to 6 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 428,75 cm2
	For each use event, covers amount up to 73 g
	Covers use in room size of 20 m3
	Covers exposure up to 0,17 hours/event
Washing and cleaning products (including solvent based products) Laundry and dish washing products.	Covers concentrations up to 5 %
	covers use up to 365 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 857,50 cm2
	For each use event, covers amount up to 15 g
	Covers use in room size of 20 m3
	Covers exposure up to 0,50 hours/event
Washing and cleaning products (including solvent based products) Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners).	Covers concentrations up to 5 %
	covers use up to 128 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 857,50 cm2
	For each use event, covers amount up to 27 g
	Covers use in room size of 20 m3
	Covers exposure up to 0,33 hours/event
Washing and cleaning products (including solvent based products) Cleaners, trigger sprays (all purpose	Covers concentrations up to 15 %

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version 4.3 Revision Date: 17.02.2025 SDS Number: 800001033919 Date of last issue: 31.10.2024
Print Date 24.02.2025

cleaners,sanitary products, glass cleaners).	
	covers use up to 128 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 428,00 cm2
	For each use event, covers amount up to 35 g
	Covers use in room size of 20 m3
	Covers exposure up to 0,17 hours/event
Welding and soldering products (with flux coatings or flux cores.), flux products	Covers concentrations up to 20 %
	covers use up to 365 day/year
	covers use up to 1 times/day of use
	For each use event, covers amount up to 12 g
	Covers use in room size of 20 m3
	Covers exposure up to 1,00 hours/event

Section 2.2	Control of Environmental Exposure
No exposure assessment presented for the environment.	

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
The ECETOC TRA tool has been used to estimate consumer exposures unless otherwise indicated.	

Section 3.2 -Environment
No exposure assessment presented for the environment.

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	
Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.	

Section 4.2 -Environment
No exposure assessment presented for the environment.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version
4.3

Revision Date:
17.02.2025

SDS Number:
800001033919

Date of last issue: 31.10.2024
Print Date 24.02.2025

Exposure Scenario - Consumer

300000010047	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Use in lubricants - Consumer
Use Descriptor	Sector of Use: SU 21 Product Categories: PC1, PC24, PC31 Environmental Release Categories: ERC8a, ERC8d, ERC9a, ERC9b
Scope of process	Covers the consumer use of formulated lubricants in closed and open systems including transfer operations, application, operation of engines and similar articles, equipment maintenance and disposal of waste oil.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Additional Information	No exposure assessment presented for the environment.	
Section 2.1	Control of Consumer Exposure	
Product Characteristics		
Physical form of product	Liquid, vapour pressure > 10 kPa at STP	
Concentration of the Sub-stance in Mixture/Article	Unless stated otherwise.	
	Covers concentration up to (%): 100 %	
Amounts Used		
Unless stated otherwise.		
for each use event, covers amount up to (g):		13.800
covers skin contact area (cm2):		857,5
Frequency and Duration of Use		
Unless stated otherwise.		
covers use up to (times/day of use):		1
Exposure (hours/event):		6
Other Operational Conditions affecting Exposure		
Unless stated otherwise. Covers use at ambient temperatures. Covers use in room size of 20m3 Covers use under typical household ventilation.		
Product Categories	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Adhesives, sealants Glues, hobby use.	Covers concentrations up to 30 %	
	covers use up to 365 day/year	
	Covers use up to 1 times/day of use	
	covers skin contact area up to (cm2): 35,73 cm2	
	For each use event, covers amount up to 5 g	
	Covers use in room size of 20 m3	

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version
4.3

Revision Date:
17.02.2025

SDS Number:
800001033919

Date of last issue: 31.10.2024
Print Date 24.02.2025

	Covers exposure up to 4 hours/event
Adhesives, sealants Glues DIY-use (carpet glue, tile glue, wood parquet glue).	Covers concentrations up to 30 %
	covers use up to 1 day/year
	Covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 110 cm2
	For each use event, covers amount up to 6.390 g
	Covers use in room size of 20 m3
	Covers exposure up to 6 hours/event
	Avoid using when windows closed.
Adhesives, sealants Glue from spray.	Covers concentrations up to 30 %
	covers use up to 6 day/year
	Covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 35,73 cm2
	For each use event, covers amount up to 85,05 g
	Covers use in room size of 20 m3
	Covers exposure up to 4 hours/event
Adhesives, sealants Seal- ants.	Covers concentrations up to 5,5 %
	covers use up to 365 day/year
	Covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 35,73 cm2
	For each use event, covers amount up to 75 g
	Covers use in room size of 20 m3
	Covers exposure up to 1 hours/event
	Avoid using when windows closed.
Lubricants, greases, re- lease products Liquids.	Covers concentrations up to 100 %
	covers use up to 4 day/year
	Covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 468 cm2
	For each use event, covers amount up to 2.200 g
	Covers use in a one car garage (34 m3) under typical ventila- tion.
	Covers use in room size of 34 m3
	Covers exposure up to 0,17 hours/event
Lubricants, greases, re- lease products Pastes.	Covers concentrations up to 20 %
	covers use up to 10 day/year
	Covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 468 cm2
	For each use event, covers amount up to 34 g
	Covers use in room size of 20 m3
Lubricants, greases, re- lease products Sprays.	Covers concentrations up to 50 %
	covers use up to 6 day/year
	Covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 428,75 cm2
	For each use event, covers amount up to 75 g

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version 4.3 Revision Date: 17.02.2025 SDS Number: 800001033919 Date of last issue: 31.10.2024
Print Date 24.02.2025

	Covers use in room size of 20 m3
	Covers exposure up to 0,17 hours/event
Polishes and wax blends Polishes, wax / cream (floor, furniture, shoes).	Covers concentrations up to 10 %
	covers use up to 29 day/year
	Covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 430 cm2
	For each use event, covers amount up to 142 g
	Covers use in room size of 20 m3
	Covers exposure up to 1,23 hours/event
Polishes and wax blends Polishes, spray (furniture, shoes).	Covers concentrations up to 50 %
	covers use up to 8 day/year
	Covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 430 cm2
	For each use event, covers amount up to 35 g
	Covers use in room size of 20 m3
	Covers exposure up to 0,33 hours/event

Section 2.2	Control of Environmental Exposure
No exposure assessment presented for the environment.	

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
The ECETOC TRA tool has been used to estimate consumer exposures unless otherwise indicated.	

Section 3.2 -Environment	
No exposure assessment presented for the environment.	

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	
Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.	

Section 4.2 -Environment	
No exposure assessment presented for the environment.	

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version
4.3

Revision Date:
17.02.2025

SDS Number:
800001033919

Date of last issue: 31.10.2024
Print Date 24.02.2025

Exposure Scenario - Consumer

300000001038	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Other Consumer Uses - Consumer
Use Descriptor	Sector of Use: SU 21 Product Categories: PC28, PC39 Environmental Release Categories: ERC8a, ERC8d
Scope of process	Consumer uses e.g. as a carrier in cosmetics/personal care products, perfumes and fragrances. Note: For cosmetic and personal care products, risk assessment only required for the environment under REACH as human health is covered by alternative legislation.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
Additional Information	No exposure assessment presented for human health. No exposure assessment presented for the environment.
Section 2.1	Control of Consumer Exposure
Product Characteristics	
Product Categories	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES

Section 2.2	Control of Environmental Exposure
No exposure assessment presented for the environment.	

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
No exposure assessment presented for human health.	

Section 3.2 -Environment	
No exposure assessment presented for the environment.	

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	
No exposure assessment presented for human health.	

Section 4.2 -Environment	
No exposure assessment presented for the environment.	

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl Isobutyl Ketone

Version
4.3

Revision Date:
17.02.2025

SDS Number:
800001033919

Date of last issue: 31.10.2024
Print Date 24.02.2025
