

SAFETY DATA SHEET

according to the Hazardous Products Regulations

Hexane (extraction grade)

Version	Revision Date:	SDS Number:	Print Date: 2025-05-21
6.1	2025-05-16	800001010779	Date of last issue: 26.09.2024
			Date of first issue: 16.05.2025

SECTION 1. IDENTIFICATION

Product name : Hexane (extraction grade)

Product code : Q1252

Manufacturer or supplier's details

Manufacturer/Supplier : **Shell Chemicals Canada**
PO Box 4280 STN C
CALGARY AB T2T 5Z5
Canada

Telephone : 1-855-697-4355

Telefax : 1-866-213-7508

Emergency telephone number

CHEMTREC (24 hr) : 1-800-424-9300

Recommended use of the chemical and restrictions on use

Recommended use : Industrial Solvent.

Restrictions on use : Restricted to professional users.
This product must not be used in applications other than those listed in Section 1 without first seeking the advice of the supplier.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Flammable liquids : Category 2

Aspiration hazard : Category 1

Skin irritation : Category 2

Specific target organ toxicity : Category 3 (Narcotic effects)
- single exposure

Reproductive toxicity : Category 2

Specific target organ toxicity : Category 2 (Central nervous system, Peripheral nervous system)
- repeated exposure

Long-term (chronic) aquatic : Category 2
hazard

SAFETY DATA SHEET

according to the Hazardous Products Regulations

Hexane (extraction grade)

Version
6.1

Revision Date:
2025-05-16

SDS Number:
800001010779

Print Date: 2025-05-21
Date of last issue: 26.09.2024
Date of first issue: 16.05.2025

GHS label elements

Hazard pictograms

:



Signal word

:

Danger

Hazard statements

:

PHYSICAL HAZARDS:
H225 Highly flammable liquid and vapour.
HEALTH HAZARDS:
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H361 Suspected of damaging fertility or the unborn child.
H373 May cause damage to organs (Central nervous system, Peripheral nervous system) through prolonged or repeated exposure.
ENVIRONMENTAL HAZARDS:
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

:

Prevention:

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P264 Wash hands thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P370 + P378 In case of fire: Use appropriate media to extinguish.
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P331 Do NOT induce vomiting.
P302 + P352 IF ON SKIN: Wash with plenty of water and soap.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

SAFETY DATA SHEET

according to the Hazardous Products Regulations

Hexane (extraction grade)

Version
6.1

Revision Date:
2025-05-16

SDS Number:
800001010779

Print Date: 2025-05-21
Date of last issue: 26.09.2024
Date of first issue: 16.05.2025

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312 Call a POISON CENTER/ doctor if you feel unwell.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P391 Collect spillage.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Disposal:

P501 Dispose of contents and container to appropriate waste site or reclaimer in accordance with local and national regulations.

Other hazards which do not result in classification

May form flammable/explosive vapour-air mixture.

This material is a static accumulator.

Even with proper grounding and bonding, this material can still accumulate an electrostatic charge.

If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur.

Vapours may be irritating to the eye.

Repeated exposure may cause skin dryness or cracking.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Substance
Substance name : Hexane (extraction grade)
CAS-No. : 64742-49-0

Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
Naphtha (petroleum), hydrotreated light	Naphtha (petroleum), hydrotreated light	64742-49-0	99 - 100

Further information

Contains:

Chemical name	Identification number	Concentration (% w/w)
n-Hexane	110-54-3	<= 55
Hexane, other isomers		>= 45

SAFETY DATA SHEET

according to the Hazardous Products Regulations

Hexane (extraction grade)

Version	Revision Date:	SDS Number:	Print Date: 2025-05-21
6.1	2025-05-16	800001010779	Date of last issue: 26.09.2024
			Date of first issue: 16.05.2025

SECTION 4. FIRST-AID MEASURES

- | | |
|---|---|
| General advice | : Not expected to be a health hazard when used under normal conditions. |
| If inhaled | : Remove to fresh air. If rapid recovery does not occur, transport to nearest medical facility for additional treatment. |
| In case of skin contact | : Remove contaminated clothing. Immediately flush skin with large amounts of water for at least 15 minutes, and follow by washing with soap and water if available. If redness, swelling, pain and/or blisters occur, transport to the nearest medical facility for additional treatment. |
| In case of eye contact | : Flush eye with copious quantities of water.
Remove contact lenses, if present and easy to do. Continue rinsing.
If persistent irritation occurs, obtain medical attention. |
| If swallowed | : Call emergency number for your location / facility.
If swallowed, do not induce vomiting: transport to nearest medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (38.3°C), shortness of breath, chest congestion or continued coughing or wheezing. |
| Most important symptoms and effects, both acute and delayed | : Breathing of high vapour concentrations may cause central nervous system (CNS) depression resulting in dizziness, light-headedness, headache, nausea and loss of coordination. Continued inhalation may result in unconsciousness and death.
Skin irritation signs and symptoms may include a burning sensation, redness, swelling, and/or blisters.
No specific hazards under normal use conditions.
Eye irritation signs and symptoms may include a burning sensation, redness, swelling, and/or blurred vision.
If material enters lungs, signs and symptoms may include coughing, choking, wheezing, difficulty in breathing, chest congestion, shortness of breath, and/or fever.
If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (38.3°C), shortness of breath, chest congestion or continued coughing or wheezing.
Peripheral nerve damage may be evidenced by impairment of motor function (incoordination, unsteady walk, or muscle weakness in the extremities, and/or loss of sensation in the arms and legs).

Defatting dermatitis signs and symptoms may include a burning sensation and/or a dried/cracked appearance. |
| Protection of first-aiders | : When administering first aid, ensure that you are wearing the |

SAFETY DATA SHEET

according to the Hazardous Products Regulations

Hexane (extraction grade)

Version 6.1	Revision Date: 2025-05-16	SDS Number: 800001010779	Print Date: 2025-05-21 Date of last issue: 26.09.2024 Date of first issue: 16.05.2025
----------------	------------------------------	-----------------------------	---

appropriate personal protective equipment according to the incident, injury and surroundings.

Notes to physician : Call a doctor or poison control center for guidance.
Potential for chemical pneumonitis.
Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

Unsuitable extinguishing media : Do not use water in a jet.

Specific hazards during fire-fighting : Clear fire area of all non-emergency personnel.
Hazardous combustion products may include:
A complex mixture of airborne solid and liquid particulates and gases (smoke).
Carbon monoxide.
Unidentified organic and inorganic compounds.
Flammable vapours may be present even at temperatures below the flash point.
The vapour is heavier than air, spreads along the ground and distant ignition is possible.
Will float and can be reignited on surface water.

Specific extinguishing methods : Standard procedure for chemical fires.

Special protective equipment for firefighters : Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

Further information : Keep adjacent containers cool by spraying with water.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Observe all relevant local and international regulations.
Notify authorities if any exposure to the general public or the environment occurs or is likely to occur.
Local authorities should be advised if significant spillages cannot be contained.
Avoid contact with skin, eyes and clothing.
Isolate hazard area and deny entry to unnecessary or unprotected personnel.
Do not breathe fumes, vapour.
Do not operate electrical equipment.

SAFETY DATA SHEET

according to the Hazardous Products Regulations

Hexane (extraction grade)

Version
6.1

Revision Date:
2025-05-16

SDS Number:
800001010779

Print Date: 2025-05-21
Date of last issue: 26.09.2024
Date of first issue: 16.05.2025

Environmental precautions : Shut off leaks, if possible without personal risks. Remove all possible sources of ignition in the surrounding area. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. Attempt to disperse the vapour or to direct its flow to a safe location for example by using fog sprays. Take precautionary measures against static discharge. Ensure electrical continuity by bonding and grounding (earthing) all equipment. Monitor area with combustible gas indicator.

Methods and materials for containment and cleaning up : For small liquid spills (< 1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.
For large liquid spills (> 1 drum), transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely

Ventilate contaminated area thoroughly.
If contamination of site occurs remediation may require specialist advice.

Additional advice : For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet.
For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.

SECTION 7. HANDLING AND STORAGE

Technical measures : Avoid breathing of or direct contact with material. Only use in well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet.
Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this

SAFETY DATA SHEET

according to the Hazardous Products Regulations

Hexane (extraction grade)

Version
6.1

Revision Date:
2025-05-16

SDS Number:
800001010779

Print Date: 2025-05-21
Date of last issue: 26.09.2024
Date of first issue: 16.05.2025

		material. Ensure that all local regulations regarding handling and storage facilities are followed.
Advice on safe handling	:	Avoid inhaling vapour and/or mists. Avoid contact with skin, eyes and clothing. Extinguish any naked flames. Do not smoke. Remove ignition sources. Avoid sparks. Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Bulk storage tanks should be diked (bunded). When using do not eat or drink. The vapour is heavier than air, spreads along the ground and distant ignition is possible.
Avoidance of contact	:	Strong oxidising agents.
Product Transfer	:	Even with proper grounding and bonding, this material can still accumulate an electrostatic charge. If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur. Be aware of handling operations that may give rise to additional hazards that result from the accumulation of static charges. These include but are not limited to pumping (especially turbulent flow), mixing, filtering, splash filling, cleaning and filling of tanks and containers, sampling, switch loading, gauging, vacuum truck operations, and mechanical movements. These activities may lead to static discharge e.g. spark formation. Restrict line velocity during pumping in order to avoid generation of electrostatic discharge (≤ 1 m/s until fill pipe submerged to twice its diameter, then ≤ 7 m/s). Avoid splash filling. Do NOT use compressed air for filling, discharging, or handling operations. Refer to guidance under Handling section.
Conditions for safe storage	:	Refer to section 15 for any additional specific legislation covering the packaging and storage of this product.
Further information on storage stability	:	Storage Temperature: Ambient. Bulk storage tanks should be diked (bunded). Locate tanks away from heat and other sources of ignition. Cleaning, inspection and maintenance of storage tanks is a specialist operation, which requires the implementation of strict procedures and precautions. Must be stored in a diked (bunded) well-ventilated area, away from sunlight, ignition sources and other sources of heat. Keep away from aerosols, flammables, oxidizing agents, corrosives and from other flammable products which are not harmful or toxic to man or to the environment. Electrostatic charges will be generated during pumping.

SAFETY DATA SHEET

according to the Hazardous Products Regulations

Hexane (extraction grade)

Version
6.1

Revision Date:
2025-05-16

SDS Number:
800001010779

Print Date: 2025-05-21
Date of last issue: 26.09.2024
Date of first issue: 16.05.2025

Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment to reduce the risk.
The vapours in the head space of the storage vessel may lie in the flammable/explosive range and hence may be flammable.

Packaging material : Suitable material: For containers, or container linings use mild steel, stainless steel., For container paints, use epoxy paint, zinc silicate paint.
Unsuitable material: Avoid prolonged contact with natural, butyl or nitrile rubbers.

Specific end use(s)

Specific use(s) : Not applicable

See additional references that provide safe handling practices for liquids that are determined to be static accumulators: American Petroleum Institute 2003 (Protection Against Ignitions Arising out of Static, Lightning and Stray Currents) or National Fire Protection Agency 77 (Recommended Practices on Static Electricity).
IEC/TS 60079-32-1: Electrostatic hazards, guidance

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Naphtha (petroleum), hydrotreated light	64742-49-0	TWA	500 ppm 2,000 mg/m3	OSHA Z-1
		TWA (Mist)	5 mg/m3	OSHA Z-1
n-Hexane	110-54-3	TWA	50 ppm 176 mg/m3	CA AB OEL
		TWA	20 ppm	CA BC OEL
		TWAEV	50 ppm 176 mg/m3	CA QC OEL
		TWA	50 ppm	ACGIH

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
n-Hexane	110-54-3	2,5-Hexanedi-one	Urine	End of shift	0.5 mg/l	ACGIH BEI

Biological occupational exposure limits

No biological limit allocated.

SAFETY DATA SHEET

according to the Hazardous Products Regulations

Hexane (extraction grade)

Version
6.1

Revision Date:
2025-05-16

SDS Number:
800001010779

Print Date: 2025-05-21
Date of last issue: 26.09.2024
Date of first issue: 16.05.2025

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods <http://www.cdc.gov/niosh/>

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods <http://www.osha.gov/>

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances <http://www.hse.gov.uk/>

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany
<http://www.dguv.de/inhalt/index.jsp>

L'Institut National de Recherche et de Sécurité, (INRS), France <http://www.inrs.fr/accueil>

Engineering measures

- : Use sealed systems as far as possible.
- Adequate explosion-proof ventilation to control airborne concentrations below the exposure guidelines/limits.
- Local exhaust ventilation is recommended.
- Firewater monitors and deluge systems are recommended.
- Eye washes and showers for emergency use.
- Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.
- The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances.
- Appropriate measures include:

General Information

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned.

Practice good housekeeping.

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

Personal protective equipment

SAFETY DATA SHEET

according to the Hazardous Products Regulations

Hexane (extraction grade)

Version
6.1

Revision Date:
2025-05-16

SDS Number:
800001010779

Print Date: 2025-05-21
Date of last issue: 26.09.2024
Date of first issue: 16.05.2025

Respiratory protection : If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are unsuitable (e.g. airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. If air-filtering respirators are suitable for conditions of use: Select a filter suitable for organic gases and vapours [Type A boiling point >65°C (149°F)].

Hand protection

Remarks : Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. Longer term protection: Nitrile rubber gloves. Incidental contact/Splash protection: PVC or neoprene rubber gloves. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

Eye protection : If material is handled such that it could be splashed into eyes, protective eyewear is recommended.

Skin and body protection : Wear chemical resistant gloves/gauntlets and boots. Where risk of splashing, also wear an apron. Wear antistatic and flame-retardant clothing, if a local risk assessment deems it so.

SAFETY DATA SHEET

according to the Hazardous Products Regulations

Hexane (extraction grade)

Version
6.1

Revision Date:
2025-05-16

SDS Number:
800001010779

Print Date: 2025-05-21
Date of last issue: 26.09.2024
Date of first issue: 16.05.2025

Protective measures : Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers. The following information, while appropriate for the product is general in nature. The selection of Personal Protective Equipment will vary depending on the conditions of use.

Hygiene measures : Wash hands before eating, drinking, smoking and using the toilet.
Launder contaminated clothing before re-use.
Do not ingest. If swallowed, then seek immediate medical assistance.

Environmental exposure controls

General advice : Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour.
Minimise release to the environment. An environmental assessment must be made to ensure compliance with local environmental legislation.
Information on accidental release measures are to be found in section 6.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Physical state : liquid

Colour : colourless

Odour : Paraffinic, sweet

Odour Threshold : Data not available

Melting / freezing point : -95 °C

Initial boiling point and boiling range : Typical 63 - 79 °C

Flammability (solid, gas) : Not applicable

Upper explosion limit / Upper flammability limit : Upper flammability limit
7.4 %(V)

SAFETY DATA SHEET

according to the Hazardous Products Regulations

Hexane (extraction grade)

Version	Revision Date:	SDS Number:	Print Date: 2025-05-21
6.1	2025-05-16	800001010779	Date of last issue: 26.09.2024
			Date of first issue: 16.05.2025

Lower explosion limit / Lower flammability limit : Lower flammability limit
1.1 %(V)

Flash point : -27 °C
Method: IP 170

Auto-ignition temperature : 375 °C
Method: ASTM E-659

Decomposition temperature : Not applicable

pH : Not applicable

Viscosity
Viscosity, dynamic : Data not available

Viscosity, kinematic : Typical 0.45 mm²/s (25 °C)
Method: ASTM D445

Solubility(ies)
Water solubility : 9.5 mg/l

Partition coefficient: n-octanol/water : log Pow: 4

Vapour pressure : Typical 8,000 Pa (0 °C)

Typical 19,000 Pa (20 °C)

Typical 58,500 Pa (50 °C)

Relative density : 0.66
Method: ASTM D4052

Density : Typical 670 - 675 kg/m³ (15 °C)
Method: ASTM D4052

Relative vapour density : 2.8

Particle characteristics
Particle size : Data not available

SAFETY DATA SHEET

according to the Hazardous Products Regulations

Hexane (extraction grade)

Version	Revision Date:	SDS Number:	Print Date: 2025-05-21
6.1	2025-05-16	800001010779	Date of last issue: 26.09.2024
			Date of first issue: 16.05.2025

9.2 Other information

Explosives : Not applicable

Oxidizing properties : Data not available

Evaporation rate : 1.4
Method: DIN 53170, di-ethyl ether=1

8
Method: ASTM D 3539, nBuAc=1

Conductivity : 0.04 pS/m at 20 °C
Method: ASTM D-4308

Low conductivity: < 100 pS/m

The conductivity of this material makes it a static accumulator. A liquid is typically considered nonconductive if its conductivity is below 100 pS/m and is considered semi-conductive if its conductivity is below 10,000 pS/m. Whether a liquid is nonconductive or semi-conductive, the precautions are the same. A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid

Surface tension : 18.5 mN/m, 20 °C, ASTM D-971

Molecular weight : 86 g/mol

SECTION 10. STABILITY AND REACTIVITY

Reactivity : The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.

Chemical stability : No hazardous reaction is expected when handled and stored according to provisions
Stable under normal conditions of use.

Possibility of hazardous reactions : Reacts with strong oxidising agents.

SAFETY DATA SHEET

according to the Hazardous Products Regulations

Hexane (extraction grade)

Version	Revision Date:	SDS Number:	Print Date: 2025-05-21
6.1	2025-05-16	800001010779	Date of last issue: 26.09.2024
			Date of first issue: 16.05.2025

Conditions to avoid	: Avoid heat, sparks, open flames and other ignition sources. In certain circumstances product can ignite due to static electricity.
Incompatible materials	: Strong oxidising agents.
Hazardous decomposition products	: Hazardous decomposition products are not expected to form during normal storage. Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids and gases including carbon monoxide, carbon dioxide, sulphur oxides and unidentified organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation.

SECTION 11. TOXICOLOGICAL INFORMATION

Basis for assessment	: Information given is based on product testing, and/or similar products, and/or components. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).
----------------------	--

Information on likely routes of exposure

Exposure may occur via inhalation, ingestion, skin absorption, skin or eye contact, and accidental ingestion.

Acute toxicity

Product:

Acute oral toxicity	: LD50 (Rat): Remarks: Low toxicity
Acute inhalation toxicity	: LC50 (Rat): > 20 mg/l Remarks: Low toxicity by inhalation.
Acute dermal toxicity	: LD50 (Rabbit): Remarks: Low toxicity

Components:

Naphtha (petroleum), hydrotreated light:

Acute oral toxicity	: LD50 (Rat): > 5000 mg/kg Remarks: Low toxicity
Acute inhalation toxicity	: LC50 (Rat): > 20 mg/l Remarks: Low toxicity by inhalation.
Acute dermal toxicity	: LD50 (Rabbit): > 2000 mg/kg Remarks: Low toxicity

SAFETY DATA SHEET

according to the Hazardous Products Regulations

Hexane (extraction grade)

Version
6.1

Revision Date:
2025-05-16

SDS Number:
800001010779

Print Date: 2025-05-21
Date of last issue: 26.09.2024
Date of first issue: 16.05.2025

Skin corrosion/irritation

Product:

Remarks : Causes skin irritation.
Repeated exposure may cause skin dryness or cracking.

Components:

Naphtha (petroleum), hydrotreated light:

Remarks : Causes skin irritation.
Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Product:

Remarks : Not irritating to eye.
Vapours may be irritating to the eye.

Components:

Naphtha (petroleum), hydrotreated light:

Remarks : Not irritating to eye.
Vapours may be irritating to the eye.

Respiratory or skin sensitisation

Product:

Remarks : Not a sensitiser.
Based on available data, the classification criteria are not met.

Components:

Naphtha (petroleum), hydrotreated light:

Remarks : Not a sensitiser.
Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Product:

Genotoxicity in vivo : Remarks: Not mutagenic.

Components:

Naphtha (petroleum), hydrotreated light:

Genotoxicity in vivo : Remarks: Not mutagenic.

Carcinogenicity

Product:

SAFETY DATA SHEET

according to the Hazardous Products Regulations

Hexane (extraction grade)

Version
6.1

Revision Date:
2025-05-16

SDS Number:
800001010779

Print Date: 2025-05-21
Date of last issue: 26.09.2024
Date of first issue: 16.05.2025

Remarks : Tumours produced in animals are not considered relevant to humans.
Not a carcinogen.
Based on available data, the classification criteria are not met.

Components:

Naphtha (petroleum), hydrotreated light:

Remarks : Tumours produced in animals are not considered relevant to humans.
Not a carcinogen.
Based on available data, the classification criteria are not met.

IARC No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Remarks : Suspected of damaging fertility or the unborn child.
Causes foetotoxicity in animals at doses which are maternally toxic.
Affects reproductive system in animals at doses which produce other toxic effects.

STOT - single exposure

Product:

Remarks : May cause drowsiness and dizziness.

Components:

Naphtha (petroleum), hydrotreated light:

Remarks : May cause drowsiness and dizziness.

STOT - repeated exposure

Product:

Remarks : Central nervous system: repeated exposure affects the nervous system.
Peripheral nervous system: causes peripheral neuropathy which can be potentiated by ketones.
Kidney: caused kidney effects in male rats which are not considered relevant to humans

SAFETY DATA SHEET

according to the Hazardous Products Regulations

Hexane (extraction grade)

Version
6.1

Revision Date:
2025-05-16

SDS Number:
800001010779

Print Date: 2025-05-21
Date of last issue: 26.09.2024
Date of first issue: 16.05.2025

Components:

Naphtha (petroleum), hydrotreated light:

Remarks : Central nervous system: repeated exposure affects the nervous system.
Peripheral nervous system: causes peripheral neuropathy which can be potentiated by ketones.
Kidney: caused kidney effects in male rats which are not considered relevant to humans

Aspiration toxicity

Product:

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

Components:

Naphtha (petroleum), hydrotreated light:

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

Further information

Product:

Remarks : Classifications by other authorities under varying regulatory frameworks may exist.

Components:

Naphtha (petroleum), hydrotreated light:

Remarks : Classifications by other authorities under varying regulatory frameworks may exist.

SECTION 12. ECOLOGICAL INFORMATION

Basis for assessment : Incomplete ecotoxicological data are available for this product. The information given below is based partly on a knowledge of the components and the ecotoxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

Ecotoxicity

Product:

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other :

according to the Hazardous Products Regulations

Version 6.1	Revision Date: 2025-05-16	SDS Number: 800001010779	Print Date: 2025-05-21 Date of last issue: 26.09.2024 Date of first issue: 16.05.2025
----------------	------------------------------	-----------------------------	---

aquatic invertebrates	Remarks: Toxic LL/EL/IL50 > 1 <= 10 mg/l
Toxicity to algae/aquatic plants	Remarks: Harmful LL/EL/IL50 >10 <= 100 mg/l
Toxicity to fish (Chronic toxicity)	Remarks: Data not available
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	Remarks: Data not available
Toxicity to microorganisms	Remarks: Data not available

Naphtha (petroleum), hydrotreated light:

Toxicity to fish	:	Remarks: No data available
Toxicity to daphnia and other aquatic invertebrates	:	Remarks: Toxic LL/EL/IL50 > 1 <= 10 mg/l
Toxicity to algae/aquatic plants	:	Remarks: Harmful LL/EL/IL50 >10 <= 100 mg/l
Toxicity to fish (Chronic toxicity)	:	Remarks: Data not available
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	Remarks: Data not available
Toxicity to microorganisms	:	Remarks: Data not available

Product:

Biodegradability	: Remarks: Readily biodegradable. Oxidises rapidly by photo-chemical reactions in air.
------------------	---

Naphtha (petroleum), hydrotreated light:

Biodegradability	: Remarks: Readily biodegradable. Oxidises rapidly by photo-chemical reactions in air.
------------------	---

SAFETY DATA SHEET

according to the Hazardous Products Regulations

Hexane (extraction grade)

Version
6.1

Revision Date:
2025-05-16

SDS Number:
800001010779

Print Date: 2025-05-21
Date of last issue: 26.09.2024
Date of first issue: 16.05.2025

Bioaccumulative potential

Product:

Bioaccumulation : Remarks: Has the potential to bioaccumulate.

Components:

Naphtha (petroleum), hydrotreated light:

Bioaccumulation : Remarks: Has the potential to bioaccumulate.

Mobility in soil

Product:

Mobility : Remarks: Floats on water.
If it enters soil, it will adsorb to soil particles and will not be mobile.

Components:

Naphtha (petroleum), hydrotreated light:

Mobility : Remarks: Floats on water.
If it enters soil, it will adsorb to soil particles and will not be mobile.

Other adverse effects

Product:

Additional ecological information : Does not have ozone depletion potential.

Components:

Naphtha (petroleum), hydrotreated light:

Additional ecological information : Does not have ozone depletion potential.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Recover or recycle if possible.
It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.
Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment.
Do not dispose into the environment, in drains or in water courses.

SAFETY DATA SHEET

according to the Hazardous Products Regulations

Hexane (extraction grade)

Version
6.1

Revision Date:
2025-05-16

SDS Number:
800001010779

Print Date: 2025-05-21
Date of last issue: 26.09.2024
Date of first issue: 16.05.2025

Do not dispose of tank water bottoms by allowing them to drain into the ground. This will result in soil and groundwater contamination.

Waste arising from a spillage or tank cleaning should be disposed of in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand.

Waste, spills or used product is dangerous waste.

Disposal should be in accordance with applicable regional, national, and local laws and regulations.
Local regulations may be more stringent than regional or national requirements and must be complied with.

MARPOL - see International Convention for the Prevention of Pollution from Ships (MARPOL 73/78) which provides technical aspects at controlling pollutions from ships.

Contaminated packaging : Drain container thoroughly.
After draining, vent in a safe place away from sparks and fire.
Residues may cause an explosion hazard. Do not puncture, cut or weld uncleaned drums.
Send to drum recoverer or metal reclaimer.
Comply with any local recovery or waste disposal regulations.

SECTION 14. TRANSPORT INFORMATION

TDG

UN number : 1208
Proper shipping name : HEXANES
Class : 3
Packing group : II
Labels : 3
Marine pollutant : no

International Regulations

IATA-DGR

UN/ID No. : UN 1208
Proper shipping name : HEXANES
Class : 3
Packing group : II
Labels : 3

IMDG-Code

UN number : UN 1208
Proper shipping name : HEXANES
Class : 3

SAFETY DATA SHEET

according to the Hazardous Products Regulations

Hexane (extraction grade)

Version	Revision Date:	SDS Number:	Print Date: 2025-05-21
6.1	2025-05-16	800001010779	Date of last issue: 26.09.2024
			Date of first issue: 16.05.2025

Packing group	: II
Labels	: 3
Marine pollutant	: yes

Maritime transport in bulk according to IMO instruments

Pollution category	: Y
Ship type	: 2
Product name	: Hexane (all isomers)

Special precautions for user

Remarks	: Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.
---------	--

Additional Information	: This product may be transported under nitrogen blanketing. Nitrogen is an odourless and invisible gas. Exposure to nitrogen enriched atmospheres displaces available oxygen which may cause asphyxiation or death. Personnel must observe strict safety precautions when involved with a confined space entry. Transport in bulk according to Annex II of Marpol and the IBC Code
-------------------------------	--

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR.

The components of this product are reported in the following inventories:

DSL	: Listed
IECSC	: Listed
KECI	: Listed
PICCS	: Listed
TSCA	: Listed
TCSI	: Listed
ENCS	: Listed
NZIoC	: Listed

SAFETY DATA SHEET

according to the Hazardous Products Regulations

Hexane (extraction grade)

Version	Revision Date:	SDS Number:	Print Date: 2025-05-21
6.1	2025-05-16	800001010779	Date of last issue: 26.09.2024
			Date of first issue: 16.05.2025

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	:	ACGIH - Biological Exposure Indices (BEI)
CA AB OEL	:	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	:	Canada. British Columbia OEL
CA QC OEL	:	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for air-borne contaminants
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
ACGIH / TWA	:	8-hour, time-weighted average
CA AB OEL / TWA	:	8-hour Occupational exposure limit
CA BC OEL / TWA	:	8-hour time weighted average
CA QC OEL / TWA EV	:	Time-weighted average exposure value
OSHA Z-1 / TWA	:	8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

A vertical bar (|) in the left margin indicates an amendment from the previous version.

SAFETY DATA SHEET

according to the Hazardous Products Regulations

Hexane (extraction grade)

Version	Revision Date:	SDS Number:	Print Date: 2025-05-21
6.1	2025-05-16	800001010779	Date of last issue: 26.09.2024
			Date of first issue: 16.05.2025

Sources of key data used to compile the Safety Data Sheet : The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID date base, EC 1272 regulation, etc).

Revision Date : 2025-05-16
Date format : mm/dd/yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CA / EN