Diethylene Glycol

Print Date 12.02.2025 Revision Date 12.02.2025 Version 1.5

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Diethylene Glycol Product code : U1237, U1239 CAS-No. : 111-46-6

Synonyms : 2,2' Dihydroxy diethyl ether, bis (2-hydroxyethyl) ether, DEG,

Diglycol, Digol, Ethylene diglycol

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the : Chemical intermediate.

Substance/Mixture

Uses advised against : This product must not be used in applications other than the

above without first seeking the advice of the supplier., Do not

use in the manufacture or preparation of foods or

pharmaceuticals., Keep out of reach of children and pets., Do not use in theatrical fogs or other artificial smoke generator applications., Do not use in aircraft deicing applications. This product must not be used in applications other than those

listed in Section 1 without first seeking the advice of the

supplier.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier : Shell Trading (M.E.) Pvt. Ltd.

PO Box 16968 16968 Jebel Ali Unit.Arab Emir. +971 4 331 6500

 Telephone
 : +971 4 331 6500

 Telefax
 : +971 4 332 1597

 Contact for Safety Data
 : sccmsds@shell.com

Sheet

1.4 Emergency telephone number

+ (65) 6542 9595 (Alert-SGS)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

GHS Classification

Acute toxicity (Oral) : Category 4

Diethylene Glycol

Print Date 12.02.2025 Revision Date 12.02.2025 Version 1.5

2.2 Label elements

GHS-Labelling

Hazard pictograms :

Signal word : Warning

Hazard statements : PHYSICAL HAZARDS:

Not classified as a physical hazard under GHS criteria.

HEALTH HAZARDS: H302 Harmful if swallowed. ENVIRONMENTAL HAZARDS:

Not classified as an environmental hazard under GHS criteria.

Precautionary statements : **Prevention:**

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

Response:

P301 + P312 IF SWALLOWED: Call a POISON CENTER/

doctor if you feel unwell. P330 Rinse mouth.

Storage:

No precautionary phrases.

Disposal:

P501 Dispose of contents and container to appropriate waste

site or reclaimer in accordance with local and national

regulations.

2.3 Other hazards

Slightly irritating to the skin.

Slightly irritating to respiratory system.

Slightly irritating to the eye.

Vapours may be irritating to the eye.

SECTION 3: Composition/information on ingredients

3.1 Substances

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
Diethylene glycol	111-46-6	95- 100

Further information

Contains:

Diethylene Glycol

Print Date 12.02.2025 Revision Date 12.02.2025 Version 1.5

Chemical name	Identification number	Concentration (% w/w)
Ethanediol	107-21-1	<=0,15

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Not expected to be a health hazard when used under normal

conditions.

Protection of first-aiders : When administering first aid, ensure that you are wearing the

appropriate personal protective equipment according to the

incident, injury and surroundings.

If inhaled : No treatment necessary under normal conditions of use. If

symptoms persist, obtain medical advice.

In case of skin contact : Remove contaminated clothing. Flush exposed area with

water and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention.

In case of eye contact : Flush eye with copious quantities of water.

Remove contact lenses, if present and easy to do. Continue

rinsing.

If persistent irritation occurs, obtain medical attention.

If swallowed : If swallowed, do not induce vomiting: transport to nearest

medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.

Rinse mouth.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Not considered to be an inhalation hazard under normal

conditions of use.

Possible respiratory irritation signs and symptoms may include

a temporary burning sensation of the nose and throat,

coughing, and/or difficulty breathing.

No specific hazards under normal use conditions.

Skin irritation signs and symptoms may include a burning

sensation, redness, or swelling.

Eye irritation signs and symptoms may include a burning

sensation, redness, swelling, and/or blurred vision.

Ingestion may result in nausea, vomiting and/or diarrhoea. High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea; continued inhalation may result in unconsciousness and/or

death.

Kidney toxicity may be recognized by blood in the urine or increased or decreased urine flow. Other signs and symptoms can include nausea, vomiting, abdominal cramps, diarrhoea,

		Diethylene Glycol
Print Date 12.02.2025	Revision Date 12.02.2025	Version 1.5

lumbar pain shortly after ingestion, and possibly narcosis and

death.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : IMMEDIATE TREATMENT IS EXTREMELY IMPORTANT!

Call a doctor or poison control center for guidance.

Treat symptomatically.

May cause significant renal, respiratory, and CNS toxicity.

May cause significant acidosis.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam, water spray or fog. Dry chemical

powder, carbon dioxide, sand or earth may be used for small

fires only.

Unsuitable extinguishing

media

: Do not use water in a jet.

5.2 Special hazards arising from the substance or mixture

Specific hazards during

firefighting

: Material will not burn unless preheated. Carbon monoxide may be evolved if incomplete combustion occurs. Containers exposed to intense heat from fires should be cooled with large quantities of water.

5.3 Advice for firefighters

Special protective equipment

for firefighters

: Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to

relevant Standards (e.g. Europe: EN469).

Specific extinguishing

methods

Further information

: Standard procedure for chemical fires.

: Evacuate the area of all non-essential personnel.

Keep adjacent containers cool by spraying with water.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions :

Observe all relevant local and international regulations. Notify authorities if any exposure to the general public or the

environment occurs or is likely to occur.

Local authorities should be advised if significant spillages

cannot be contained.

			Diethylene	Glycol
Print Date	12.02.2025	Revision Date 12.02.2025	\	/ersion 1.5

Avoid contact with skin, eyes and clothing.

6.2 Environmental precautions

Environmental precautions

 Prevent from spreading or entering into drains, ditches or rivers by using sand, earth, or other appropriate barriers. Use appropriate containment to avoid environmental contamination.

Ventilate contaminated area thoroughly.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Contain run-c

: Contain run-off from residue flush and dispose of properly.

Soak up residue with an absorbent such as clay, sand or other

suitable material.

For small liquid spills (< 1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove

contaminated soil and dispose of safely.

For large liquid spills (> 1 drum), transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely

6.4 Reference to other sections

For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet., For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.

SECTION 7: Handling and storage

General Precautions : Avoid breathing of or direct contact with material. Only use in

well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see

Section 8 of this Safety Data Sheet.

Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of

this material.

Ensure that all local regulations regarding handling and

storage facilities are followed.

7.1 Precautions for safe handling

Advice on safe handling : Use local exhaust extraction over processing area.

Handle and open container with care in a well-ventilated area.

	D	iethylene Glycol
Print Date 12.02.2025	Revision Date 12.02.2025	Version 1.5
	Do not empty into drains. When handling product in drums, safety worn and proper handling equipment she Handling Temperature: Ambient.	
Product Transfer	: Keep containers closed when not in use drum containers to empty.	e. Do not pressurize

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Refer to section 15 for any additional specific legislation covering the packaging and storage of this product.

Other data : Tanks must be clean, dry and rust-free. Keep container tightly

closed. Must be stored in a diked (bunded) well- ventilated area, away from sunlight, ignition sources and other sources of heat. Cleaning, inspection and maintenance of storage

tanks is a specialist operation, which requires the

implementation of strict procedures and precautions. Drums

should be stacked to a maximum of 3 high. Storage

Temperature: Ambient.

Packaging material : Suitable material: Stainless steel. Mild steel. Carbon steel

Unsuitable material: Data not available

Container Advice : Containers, even those that have been emptied, can contain

explosive vapours. Do not cut, drill, grind, weld or perform

similar operations on or near containers.

7.3 Specific end use(s)

Specific use(s) : Not applicable

Ensure that all local regulations regarding handling and

storage facilities are followed.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Biological occupational exposure limits

No biological limit allocated.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

diethylene glycol : End Use: Workers

	Die	ethylene Glycol
Print Date 12.02.2025	Revision Date 12.02.2025	Version 1.5
	Exposure routes: Dermal Potential health effects: Long-term syste Value: 43 mg/kg bw/day End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term local Value: 60 mg/m3 End Use: Consumers Exposure routes: Dermal Potential health effects: Long-term syste Value: 21 mg/kg bw/day End Use: Consumers	effects
	Exposure routes: Inhalation Potential health effects: Long-term local	effects

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Value: 12 mg/m3

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA) , Germany http://www.dguv.de/inhalt/index.jsp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

8.2 Exposure controls

Engineering measuresThe level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

Adequate ventilation to control airborne concentrations.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

Eye washes and showers for emergency use.

General Information

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g.

Diethylene Glycol

Print Date 12.02.2025 Revision Date 12.02.2025 Version 1.5

personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

Personal protective equipment

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Eye protection : If material is handled such that it could be splashed into eyes,

protective eyewear is recommended.

Hand protection

Remarks : Where hand contact with the product may occur the use of

gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. Longer term protection: Nitrile rubber gloves. Incidental contact/Splash protection: PVC or neoprene rubber gloves. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we

recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be

replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

Skin and body protection : Skin protection is not ordinarily required beyond standard

work clothes.

It is good practice to wear chemical resistant gloves.

Respiratory protection : If engineering controls do not maintain airborne

concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are unsuitable (e.g. airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus.

Where air-filtering respirators are suitable, select an

Diethylene Glycol

Print Date 12.02.2025 Revision Date 12.02.2025 Version 1.5

appropriate combination of mask and filter.

If air-filtering respirators are suitable for conditions of use: Select a filter suitable for the combination of organic gases and vapours and particles [Type A/Type P boiling point >65°C

(149°F)].

Thermal hazards : Not applicable

: Wash hands before eating, drinking, smoking and using the Hygiene measures

toilet. Launder contaminated clothing before re-use.

Environmental exposure controls

General advice Local guidelines on emission limits for volatile substances

must be observed for the discharge of exhaust air containing

vapour.

Minimise release to the environment. An environmental assessment must be made to ensure compliance with local

environmental legislation.

Information on accidental release measures are to be found in

section 6.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : Slightly viscous liquid.

Colour : colourless

Odour : mild

Odour Threshold : Data not available

pΗ Not applicable

Melting point/freezing point : -10 °C

Boiling point/boiling range : 244 - 250 °C

Flash point : 149 °C

Method: Pensky-Martens closed cup

Evaporation rate : < 0.01

Method: ASTM D 3539, nBuAc=1

Flammability

Flammability (solid, gas) : Not applicable

Lower explosion limit and upper explosion limit / flammability limit

Upper explosion limit : 10,8 %(V)

9/21 800001033914

Diethylene Glycol

Print Date 12.02.2025 Revision Date 12.02.2025 Version 1.5

: 1,6 %(V) Lower explosion limit

Vapour pressure : < 1,3 Pa (20 °C)

Relative vapour density : 3,7

Relative density : 1,12Method: ASTM D4052

Density : 1.116 g/cm3 (20 °C)

Method: ASTM D4052

Solubility(ies)

Water solubility : completely soluble

Partition coefficient: n-

octanol/water

: log Pow: -1,98

Auto-ignition temperature : 365 °C

Decomposition temperature : Data not available

Viscosity

Viscosity, dynamic : Data not available : 33 mm2/s (20 °C) Viscosity, kinematic Method: ASTM D445

Explosive properties : Not applicable : Data not available Oxidizing properties

9.2 Other information

Surface tension : Data not available

Conductivity : Electrical conductivity: > 10,000 pS/m

> A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid, This material is not expected to be

a static accumulator.

Molecular weight : 106,12 g/mol

10/21 800001033914

Diethylene Glycol Print Date 12.02.2025 Revision Date 12.02.2025 Version 1.5

SECTION 10: Stability and reactivity

10.1 Reactivity

The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.

10.2 Chemical stability

No hazardous reaction is expected when handled and stored according to provisions, Oxidises on contact with air.

10.3 Possibility of hazardous reactions

: None known. Hazardous reactions

10.4 Conditions to avoid

Conditions to avoid : Extremes of temperature and direct sunlight.

Product cannot ignite due to static electricity.

10.5 Incompatible materials

Materials to avoid : Strong oxidising agents.

> Strong acids. Strong bases.

degradation.

10.6 Hazardous decomposition products

Hazardous decomposition

products

: Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids and gases including carbon monoxide, carbon dioxide, sulphur oxides and unidentified organic compounds will be evolved when this material undergoes combustion or thermal or oxidative

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Basis for assessment : Information given is based on product testing.

> Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for

individual component(s).

exposure

Information on likely routes of : Exposure may occur via inhalation, ingestion, skin absorption,

skin or eye contact, and accidental ingestion.

Acute toxicity

Diethylene Glycol

Print Date 12.02.2025 Revision Date 12.02.2025 Version 1.5

Components:

Diethylene glycol:

Acute oral toxicity : LD 50 Rat, male and female: > 5.000 mg/kg

Method: Literature data

Remarks: Harmful if swallowed.

There is a marked difference in acute oral toxicity between rodents and man, man being more susceptible than rodents. The estimated fatal dose for man is 100 milliliters (1/2 cup). This material has also been shown to be toxic and potentially

lethal by ingestion to cats and dogs.

Acute inhalation toxicity : LC 50 Rat: Exposure time: 4 h

Test atmosphere: Aerosol Method: Literature data

Remarks: LC50 greater than near-saturated vapour

concentration.

Based on available data, the classification criteria are not met.

Acute dermal toxicity : LD 50 Rabbit: > 5.000 mg/kg

Method: Literature data

Remarks: Based on available data, the classification criteria

are not met.

Skin corrosion/irritation

Components:

Diethylene glycol:

Species: Rabbit

Method: Literature data

Remarks: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Components:

Diethylene glycol:

Species: Rabbit

Method: Literature data

Remarks: Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Components:

Diethylene glycol:

Species: Guinea pig

Method: Regulation (EC) No. 440/2008, Annex, B.6

Remarks: Based on available data, the classification criteria are not met.

Method: Tested according to Annex V of Directive 67/548/EEC.

Print Date 12.02.2025 Revision Date 12.02.2025 Version 1.5

Germ cell mutagenicity

Components:

Diethylene glycol:

Genotoxicity in vitro : Method: OECD Test Guideline 471

Remarks: Based on available data, the classification criteria

are not met.

: Method: OECD Test Guideline 473

Remarks: Based on available data, the classification criteria

are not met.

: Method: OECD Test Guideline 476

Remarks: Based on available data, the classification criteria

are not met.

: Method: OECD Test Guideline 479

Remarks: Based on available data, the classification criteria

are not met.

Test species: MouseMethod: OECD Test Guideline 474

Remarks: Based on available data, the classification criteria

are not met.

Germ cell mutagenicity-

Assessment

: This product does not meet the criteria for classification in

categories 1A/1B.

Carcinogenicity

Components:

Diethylene glycol:

Species: Rat, (male and female)

Application Route: Oral Method: Literature data

Remarks: Based on available data, the classification criteria are not met., Tumours produced in

animals are not considered relevant to humans.

Material	GHS/CLP Carcinogenicity Classification
Diethylene glycol	No carcinogenicity classification.
Ethanediol	No carcinogenicity classification.

Reproductive toxicity

Components:

Diethylene glycol:

Species: Mouse

Sex: male and female

Diethylene Glycol

Print Date 12.02.2025 Revision Date 12.02.2025 Version 1.5

Application Route: Oral

Method: Acceptable non-standard method.

Remarks: Based on available data, the classification criteria

are not met.

Effects on foetal : Species: Rabbit, female development : Application Route: Oral

Method: OECD Test Guideline 414

Remarks: Based on available data, the classification criteria

are not met.

Reproductive toxicity - : This product does not meet the criteria for classification in

Assessment categories 1A/1B.

STOT - single exposure

Components:

Diethylene glycol:

Remarks: Based on available data, the classification criteria are not met., Inhalation of vapours or mists may cause irritation to the respiratory system., Ingestion may cause drowsiness and dizziness.

STOT - repeated exposure

Components:

Diethylene glycol:

Remarks: Based on available data, the classification criteria are not met.

Repeated dose toxicity

Components:

Diethylene glycol:

Rat, male and female: Application Route: Oral

Method: Acceptable non-standard method. Target Organs: No specific target organs noted

No observed adverse effect level: : 300 mg/kg

Exposure time: 98 Days

Lowest observed adverse effect level: : 1500 mg/kg

Exposure time: 98 Days

Dog, male:

Application Route: Dermal

Diethylene Glycol

Print Date 12.02.2025 Revision Date 12.02.2025 Version 1.5

Method: OECD Test Guideline 410

Target Organs: No specific target organs noted

No observed adverse effect level: : 4440 mg/kg

Lowest observed adverse effect level: : 8880 mg/kg

Aspiration toxicity

Components:

Diethylene glycol:

Based on available data, the classification criteria are not met.

Further information

Components:

Diethylene glycol:

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

SECTION 12: Ecological information

12.1 Toxicity

Basis for assessment : Information given is based on product testing.

Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for

individual component(s).

Components:

Diethylene glycol:

Toxicity to fish (Acute

toxicity)

: LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l

Exposure time: 96 h Method: Literature data.

Remarks: Practically non toxic:

Method: Other guideline method. Remarks: LL/EL/IL50 > 100 mg/l

Toxicity to daphnia and other aquatic invertebrates (Acute

toxicity)

: EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Method: Other guideline method. Remarks: Practically non toxic:

	Die	ethylene Glycol
Print Date 12.02.2025	Revision Date 12.02.2025	Version 1.5
	LL/EL/IL50 > 100 mg/l	
Toxicity to algae (Acute toxicity)	: EC50 (Scenedesmus quadricauda (Gree Exposure time: 72 h Method: Information given is based on da similar substances. Remarks: Practically non toxic: LL/EL/IL50 > 100 mg/l	
Toxicity to bacteria (Acute toxicity)	: EC20 (Activated sludge, domestic waste Exposure time: 3 h Method: Test(s) equivalent or similar to 0 Remarks: Practically non toxic: LL/EL/IL50 > 100 mg/l	· -
Toxicity to fish (Chronic toxicity)	 : NOEC: > 40 mg/l Exposure time: 28 d Species: Pimephales promelas (fathead Method: Information given is based on dasimilar substances. Remarks: NOEC/NOEL > 100 mg/l 	
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	 NOEC: > 100 mg/l Species: Ceriodaphnia dubia (Water flea Method: Information given is based on di similar substances. Remarks: NOEC/NOEL > 100 mg/l 	
12.2 Persistence and degradability		
Components: Diethylene glycol:		
Biodegradability	: Biodegradation: 70 - 80 % Exposure time: 28 d Method: OECD Test Guideline 301B Remarks: Inherently biodegradable.	
12.3 Bioaccumulative potential		
Product:		
Partition coefficient: n- octanol/water <u>Components:</u> Diethylene glycol:	: log Pow: -1,98	
Bioaccumulation	: Remarks: Does not bioaccumulate signif	icantly.
12.4 Mobility in soil		

16 / 21 800001033914 AE

<u>Components:</u> Diethylene glycol :

Diethylene Glycol

Print Date 12.02.2025 Revision Date 12.02.2025 Version 1.5

Mobility : Remarks: If the product enters soil, one or more constituents

will or may be mobile and may contaminate groundwater.,

Dissolves in water.

12.5 Results of PBT and vPvB assessment

Components:

Diethylene glycol:

Assessment : The substance does not fulfill all screening criteria for

persistence, bioaccumulation and toxicity and hence is not

considered to be PBT or vPvB.

12.6 Other adverse effects

Components:

Diethylene glycol:

Additional ecological

information

: Data not available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Recover or recycle if possible.

It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Remove all packaging for recovery or waste disposal. Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment. Do not dispose of tank water bottoms by allowing them to drain into the ground. This will result in soil and groundwater contamination.

Do not dispose into the environment, in drains or in water courses.

Waste arising from a spillage or tank cleaning should be disposed of in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand.

established beloreriand.

Disposal should be in accordance with applicable regional,

national, and local laws and regulations.

Local regulations may be more stringent than regional or national requirements and must be complied with.

MARPOL - see International Convention for the Prevention of Pollution from Ships (MARPOL 73/78) which provides technical aspects at controlling pollutions from ships.

Diethylene Glycol

Print Date 12.02.2025 Revision Date 12.02.2025 Version 1.5

Contaminated packaging : Dispose in accordance with prevailing regulations, preferably

to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand.

Local legislation

SECTION 14: Transport information

14.1 UN number

ADR : Not regulated as a dangerous good IMDG : Not regulated as a dangerous good IATA : Not regulated as a dangerous good

14.2 Proper shipping name

ADR : Not regulated as a dangerous good IMDG : Not regulated as a dangerous good IATA : Not regulated as a dangerous good

14.3 Transport hazard class

ADR : Not regulated as a dangerous good IMDG : Not regulated as a dangerous good IATA : Not regulated as a dangerous good

14.4 Packing group

ADR : Not regulated as a dangerous good IMDG : Not regulated as a dangerous good IATA : Not regulated as a dangerous good

14.5 Environmental hazards

ADR : Not regulated as a dangerous good IMDG : Not regulated as a dangerous good

14.6 Special precautions for user

Remarks : Special Precautions: Refer to Section 7, Handling & Storage,

for special precautions which a user needs to be aware of or

needs to comply with in connection with transport.

14.7 Maritime transport in bulk according to IMO instruments

Pollution category : Z Ship type : 3

Product name : Diethylene glycol

Additional Information: This product may be transported under nitrogen blanketing.

Nitrogen is an odourless and invisible gas. Exposure to nitrogen enriched atmospheres displaces available oxygen which may cause asphyxiation or death. Personnel must observe strict safety precautions when involved with a

confined space entry.

Transport in bulk according to Annex II of Marpol and the IBC

Code

Print Date 12.02.2025 Revision Date 12.02.2025 Version 1.5

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Other regulations : The regulatory information is not intended to be

comprehensive. Other regulations may apply to this material.

The components of this product are reported in the following inventories:

DSL Listed **IECSC** Listed **ENCS** : Listed KECI : Listed **NZIoC** : Listed **PICCS** : Listed TSCA : Listed TCSI : Listed

SECTION 16: Other information

Abbreviations and Acronyms : The standard abbreviations and acronyms used in this document can be looked up in reference literature (e.g.

scientific dictionaries) and/or websites.

ACGIH = American Conference of Governmental Industrial

Hygienists

ADR = European Agreement concerning the International

Carriage of Dangerous Goods by Road

AICS = Australian Inventory of Chemical Substances ASTM = American Society for Testing and Materials

BEL = Biological exposure limits

BTEX = Benzene, Toluene, Ethylbenzene, Xylenes

CAS = Chemical Abstracts Service

CEFIC = European Chemical Industry Council CLP = Classification Packaging and Labelling

COC = Cleveland Open-Cup

DIN = Deutsches Institut fur Normung DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level

DSL = Canada Domestic Substance List

EC = European Commission EC50 = Effective Concentration fifty

ECETOC = European Center on Ecotoxicology and

	Diethylene Gl	ycol
Print Date 12.02.2025	Revision Date 12.02.2025 Versio	n 1.5
	Toxicology Of Chemicals ECHA = European Chemicals Agency EINECS = The European Inventory of Existing Commerci Chemical Substances EL50 = Effective Loading fifty ENCS = Japanese Existing and New Chemical Substance Inventory EWC = European Waste Code GHS = Globally Harmonised System of Classification and Labelling of Chemicals IARC = International Agency for Research on Cancer IATA = International Air Transport Association IC50 = Inhibitory Concentration fifty IL50 = Inhibitory Level fifty IMDG = International Maritime Dangerous Goods INV = Chinese Chemicals Inventory IP346 = Institute of Petroleum test method N° 346 for the determination of polycyclic aromatics DMSO-extractables KECI = Korea Existing Chemicals Inventory LC50 = Lethal Concentration fifty LD50 = Lethal Loading/Effective Loading/Inhibitory loa LL50 = Lethal Loading fifty MARPOL = International Convention for the Prevention of Pollution From Ships NOEC/NOEL = No Observed Effect Concentration / No Observed Effect Level OE_HPV = Occupational Exposure - High Production Vol PBT = Persistent, Bioaccumulative and Toxic PICCS = Philippine Inventory of Chemicals and Chemical Substances PNEC = Predicted No Effect Concentration REACH = Registration Evaluation And Authorisation Of Chemicals RID = Regulations Relating to International Carriage of Dangerous Goods by Rail SKIN_DES = Skin Designation STEL = Short term exposure limit TRA = Targeted Risk Assessment TSCA = US Toxic Substances Control Act TWA = Time-Weighted Average vPvB = very Persistent and very Bioaccumulative	es ding f
Further information		
Training advice	: Provide adequate information, instruction and training for operators.	
Other information	: A vertical bar () in the left margin indicates an amendmer from the previous version.	ıt
Sources of key data used to compile the Safety Data	: The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell	

20 / 21 800001033914

			Diethylene Glycol
Print D	ate 12.02.2025	Revision Date 12.02.2025	Version 1.5
Sheet		Health Services, material suppliers IUCLID date base, EC 1272 regula	

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

21 / 21