According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Isopropyl alcohol-cosmetic

Product code : S1114

Registration number EU : 01-2119457558-25-0001, 01-2119457558-25-0002 Synonyms : 2-propanol, Dimethyl carbinol, IPA C+, IPSC, Isopropanol

CAS-No. : 67-63-0

EC-No. : 200-661-7

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Solvent.

stance/Mixture Please refer to section 16 and/or the annexes for the regis-

tered uses under REACH.

Uses advised against : This product must not be used in applications other than the

above without first seeking the advice of the supplier.

This product must not be used in applications other than those listed in Section 1 without first seeking the advice of the sup-

plier.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier : Shell Chemicals Europe B.V.

PO Box 2334 3000 CH Rotterdam

Telephone : +31 (0)10 441 5137 / +31 (0)10 441 5191 Telefax : +31 (0)20 716 8316/ +31 (0)20 713 9230

Netherlands

Contact for Safety Data : sccmsds@shell.com

Sheet

1.4 Emergency telephone number

+44 (0) 1235 239 670 (This telephone number is available 24 hours per day, 7 days per

week)

ETTSZ: +36 80 20 11 99

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 2 H225: Highly flammable liquid and vapour.

Eye irritation, Category 2 H319: Causes serious eye irritation.

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

Specific target organ toxicity - single exposure, Category 3, Inhalation, Narcotic effects

H336: May cause drowsiness or dizziness.

, Oral

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms





Signal word : Danger

Hazard statements : PHYSICAL HAZARDS:

H225 Highly flammable liquid and vapour.

HEALTH HAZARDS:

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

ENVIRONMENTAL HAZARDS:

Not classified as environmental hazard according to

CLP criteria.

Precautionary statements : Prevention:

P210 Keep away from heat, hot surfaces, sparks, open

flames and other ignition sources. No smoking. P243 Take action to prevent static discharges.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice/

attention.

P304 + P340 IF INHALED: Remove person to fresh air and

keep comfortable for breathing.

Storage:

No precautionary phrases.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

2.3 Other hazards

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Vapours are heavier than air. Vapours may travel across the ground and reach remote ignition sources causing a flashback fire danger.

Even with proper grounding and bonding, this material can still accumulate an electrostatic charge.

If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable airvapour mixtures can occur.

Slightly irritating to respiratory system.

SECTION 3: Composition/information on ingredients

3.1 Substances

Components

| Chemical name | CAS-No. | Concentration (% w/w) |
|-------------------|-----------|-----------------------|
| | EC-No. | , , |
| Isopropyl alcohol | 67-63-0 | <= 100 |
| | 200-661-7 | |

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Not expected to be a health hazard when used under normal

conditions.

Protection of first-aiders : When administering first aid, ensure that you are wearing the

appropriate personal protective equipment according to the

incident, injury and surroundings.

If inhaled : Remove to fresh air. If rapid recovery does not occur,

transport to nearest medical facility for additional treatment.

In case of skin contact : Remove contaminated clothing. Flush exposed area with wa-

ter and follow by washing with soap if available.

If persistent irritation occurs, obtain medical attention.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses, if present and easy to do. Continue

rinsing.

Transport to the nearest medical facility for additional treat-

ment.

If swallowed : If swallowed, do not induce vomiting: transport to nearest

medical facility for additional treatment. If vomiting occurs

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

spontaneously, keep head below hips to prevent aspiration. If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (38.3°C), shortness of breath, chest congestion or continued coughing or wheezing.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Breathing of high vapour concentrations may cause central

nervous system (CNS) depression resulting in dizziness, light-headedness, headache, nausea and loss of coordination. Continued inhalation may result in unconsciousness and

death.

No specific hazards under normal use conditions.

Skin irritation signs and symptoms may include a burning sen-

sation, redness, or swelling.

Eye irritation signs and symptoms may include a burning sen-

sation, redness, swelling, and/or blurred vision.

If material enters lungs, signs and symptoms may include coughing, choking, wheezing, difficulty in breathing, chest

congestion, shortness of breath, and/or fever.

If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (38.3°C), shortness of breath, chest congestion or continued coughing or wheezing.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : IMMEDIATE TREATMENT IS EXTREMELY IMPORTANT!

Call a doctor or poison control center for guidance.

Potential for chemical pneumonitis.

Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam, water spray or fog. Dry chemical pow-

der, carbon dioxide, sand or earth may be used for small fires

only.

Unsuitable extinguishing

media

None

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

The vapour is heavier than air, spreads along the ground and

distant ignition is possible.

Carbon monoxide may be evolved if incomplete combustion

occurs.

5.3 Advice for firefighters

Special protective equipment : Proper protective equipment including chemical resistant

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

for firefighters gloves are to be worn; chemical resistant suit is indicated if

large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to

relevant Standards (e.g. Europe: EN469).

Specific extinguishing meth-

ods

Standard procedure for chemical fires.

Further information : Clear fire area of all non-emergency personnel.

Keep adjacent containers cool by spraying with water.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Observe the relevant local and international regulations

Notify authorities if any exposure to the general public or the

environment occurs or is likely to occur.

Local authorities should be advised if significant spillages

cannot be contained.

The vapour is heavier than air, spreads along the ground and

distant ignition is possible.

Vapour may form an explosive mixture with air.

6.1.1 For non emergency personnel: Avoid contact with skin, eyes and clothing.

Isolate hazard area and deny entry to unnecessary or unpro-

tected personnel.

Stay upwind and keep out of low areas. 6.1.2 For emergency responders:

Avoid contact with skin, eyes and clothing.

Isolate hazard area and deny entry to unnecessary or unpro-

tected personnel.

Stay upwind and keep out of low areas.

6.2 Environmental precautions

Environmental precautions : Shut off leaks, if possible without personal risks. Remove all

possible sources of ignition in the surrounding area. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. Attempt to disperse the vapour or to direct its flow to a safe location for example by using fog sprays. Take precautionary measures against static discharge. Ensure electrical continuity by bond-

ing and grounding (earthing) all equipment. Ventilate contaminated area thoroughly. Monitor area with combustible gas indicator.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : For large liquid spills (> 1 drum), transfer by mechanical

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely For small liquid spills (< 1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.

6.4 Reference to other sections

For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet., For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures : Avoid breathing of or direct contact with material. Only use in

well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see

Section 8 of this Safety Data Sheet.

Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this

material.

Ensure that all local regulations regarding handling and stor-

age facilities are followed.

Advice on safe handling : Avoid contact with skin, eyes and clothing.

Use local exhaust ventilation if there is risk of inhalation of

vapours, mists or aerosols.

Bulk storage tanks should be diked (bunded).

Extinguish any naked flames. Do not smoke. Remove ignition

sources. Avoid sparks.

Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment to

reduce the risk.

The vapours in the head space of the storage vessel may lie in the flammable/explosive range and hence may be flamma-

ble.

Properly dispose of any contaminated rags or cleaning mate-

rials in order to prevent fires.

Do NOT use compressed air for filling, discharging, or han-

dling operations.

Product Transfer : Refer to guidance under Handling section.

Fire-fighting class : The fire classification according to the valid Hungarian Fire

Protection Regulation:

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

Highly flammable and explosive "A".

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

The vapour is heavier than air. Beware of accumulation in pits and confined spaces. Refer to section 15 for any additional specific legislation covering the packaging and storage of this product.

Packaging material : Suitable material: For containers, or container linings use mild

steel, stainless steel.

Unsuitable material: Natural, butyl, neoprene or nitrile rubbers.

Container Advice : Containers, even those that have been emptied, can contain

explosive vapours. Do not cut, drill, grind, weld or perform

similar operations on or near containers.

7.3 Specific end use(s)

Specific use(s) : Please refer to section 16 and/or the annexes for the regis-

tered uses under REACH.

Ensure that all local regulations regarding handling and stor-

age facilities are followed.

See additional references that provide safe handling practices: American Petroleum Institute 2003 (Protection Against Ignitions Arising out of Static, Lightning and Stray Currents) or National Fire Protection Agency 77 (Recommended Practices

on Static Electricity).

IEC/TS 60079-32-1: Electrostatic hazards, guidance

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

| Components | CAS-No. | Value type (Form | Control parameters | Basis |
|-------------------|--|------------------|--------------------|--------|
| | | of exposure) | | |
| Isopropyl alcohol | 67-63-0 | TWA | 200 ppm | HU OEL |
| | | | 500 mg/m3 | |
| | Further information: Substances which have a health hazard due to SHORT | | | |
| | exposure. Corrected value = TWA x 8 / number of hours per day, Absorbed | | | |
| | through the skin., Irritant substance (irritates the skin, the mucous membrane | | | |
| | and the eyes or all three) | | | |

Biological occupational exposure limits

| Substance name | CAS-No. | Control parameters | Sampling time | Basis |
|-------------------|---------|--------------------|---------------|--------|
| Isopropyl alcohol | 67-63-0 | Acetone: 25 mg/l | End of shift | HU BAT |
| | | (Urine) | | |
| | | Acetone: 430 mi- | End of shift | HU BAT |
| | | cromol per litre | | |

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023 5.1 09.10.2024 800001006805 Print Date 16.10.2024

(Urine)

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

| Substance name | End Use | Exposure routes | Potential health effects | Value |
|-------------------|-----------|-----------------|----------------------------|---------------------|
| Isopropyl alcohol | Workers | Dermal | Long-term systemic effects | 888 mg/kg bw/day |
| Isopropyl alcohol | Workers | Inhalation | Long-term systemic effects | 500 mg/m3 |
| Isopropyl alcohol | Consumers | Dermal | Long-term systemic effects | 319 mg/kg bw/day |
| Isopropyl alcohol | Consumers | Inhalation | Long-term systemic effects | 89 mg/m3 |
| Isopropyl alcohol | Consumers | Oral | Long-term systemic effects | 26 mg/kg bw/day |

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

| Substance name | | Environmental Compartment | Value |
|-------------------|-----------|---|-------------|
| Isopropyl alcohol | | | |
| Remarks: | Exposure | assessments have not been presented for the | environment |
| | therefore | PNEC values not required. | |

8.2 Exposure controls

Engineering measures

Read in conjunction with the Exposure Scenario for your specific use contained in the Annex. Read in conjunction with the Exposure Scenario for your specific use contained in the Annex. Use sealed systems as far as possible.

Adequate explosion-proof ventilation to control airborne concentrations below the exposure quidelines/limits.

Local exhaust ventilation is recommended.

Firewater monitors and deluge systems are recommended.

Eye washes and showers for emergency use.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

General Information:

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

Personal protective equipment

Read in conjunction with the Exposure Scenario for your specific use contained in the Annex.

Read in conjunction with the Exposure Scenario for your specific use contained in the Annex. The provided information is made in consideration of the PPE directive (Council Directive 89/686/EEC) and the CEN European Committee for Standardisation (CEN) standards.

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Eye protection : Wear goggles for use against liquids and gas.

Wear full face shield if splashes are likely to occur.

Approved to EU Standard EN166.

Hand protection

Remarks : Where hand contact with the product may occur the use of

gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. Longer term protection: Butvl rubber. Nitrile rubber. Incidental contact/Splash protection: PVC or neoprene rubber gloves. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

Skin and body protection

Wear antistatic and flame-retardant clothing, if a local risk assessment deems it so.

Skin protection is not required under normal conditions of use.

For prolonged or repeated exposures use impervious clothing

over parts of the body subject to exposure. If repeated and/or prolonged skin exposure to the substance

is likely, then wear suitable gloves tested to relevant Standard, and provide employee skin care programmes.

Protective clothing approved to EU Standard EN14605.

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

Respiratory protection : If engineering controls do not maintain airborne concentra-

tions to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are unsuitable (e.g. airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing appa-

ratus.

Where air-filtering respirators are suitable, select an appro-

priate combination of mask and filter.

If air-filtering respirators are suitable for conditions of use: Select a filter suitable for organic gases and vapours [Type A

boiling point > 65°C (149°F)] meeting EN14387.

Thermal hazards : Not applicable

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : Liquid.

Colour : clear

Odour : characteristic

Odour Threshold : Data not available

Melting / freezing point : -88 °C

Boiling point/boiling range : 82 - 83 °C

Flammability

Flammability (solid, gas) : Not applicable

Lower explosion limit and upper explosion limit / flammability limit

Upper explosion limit / : upper flammability limit

upper flammability limit 12 %(V)

Lower explosion limit / : Lower flammability limit

Lower flammability limit 2 %(V)

Flash point : 12 °C

Method: IP 170

Auto-ignition temperature : 425 °C

Method: ASTM E-659

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

Decomposition temperature

Decomposition tempera: Not applicable

ture

pH : Not applicable

Viscosity

Viscosity, dynamic : 2,43 mPa.s (20 °C)

Method: ASTM D445

Viscosity, kinematic : Data not available

Solubility(ies)

Water solubility : completely miscible

Solubility in other solvents : Readily soluble in various organic solvents.

Partition coefficient: n-

octanol/water

log Pow: 0,05

Vapour pressure : 6.020 Pa

Relative density : 0,78 - 0,79 (20 °C)

Method: ASTM D4052

Density : 785 - 786 kg/m3 (20 °C)

Method: ASTM D4052

Relative vapour density : 2 (20 °C)

Particle characteristics

Particle size : Data not available

9.2 Other information

Explosive properties : Not applicable

Oxidizing properties : Data not available

Evaporation rate : 1,5

Method: ASTM D 3539, nBuAc=1

11

Method: DIN 53170, di-ethyl ether=1

Conductivity: > 10,000 pS/m

A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid, This material is not expected to be

a static accumulator.

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

Surface tension : 22,7 mN/m, 20 °C

Molecular weight : 60,1 g/mol

SECTION 10: Stability and reactivity

10.1 Reactivity

The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.

10.2 Chemical stability

No hazardous reaction is expected when handled and stored according to provisions

10.3 Possibility of hazardous reactions

Hazardous reactions : Reacts with strong oxidising agents.

10.4 Conditions to avoid

Conditions to avoid : Avoid heat, sparks, open flames and other ignition sources.

Prevent vapour accumulation.

In certain circumstances product can ignite due to static elec-

tricity.

10.5 Incompatible materials

Materials to avoid : Strong oxidising agents.

10.6 Hazardous decomposition products

Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids and gases including carbon monoxide, carbon dioxide, sulphur oxides and unidentified organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of : Exposure may occur via inhalation, ingestion, skin absorption,

exposure skin or eye contact, and accidental ingestion.

Acute toxicity

Components:

Isopropyl alcohol:

Acute oral toxicity : LD50 (Rat): > 5000 mg/kg

Remarks: Low toxicity

Acute inhalation toxicity : LC50 (Rat, male and female): > 10000 ppm

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

Exposure time: 6 h

Method: Test(s) equivalent or similar to OECD Test Guideline

403

Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcot-

ic effects.

Remarks: Low toxicity by inhalation.

Acute dermal toxicity : LD50 (Rabbit): > 5000 mg/kg

Remarks: Low toxicity

Skin corrosion/irritation

Components:

Isopropyl alcohol:

Remarks : Not irritating to skin.

Serious eye damage/eye irritation

Components:

Isopropyl alcohol:

Species : Rabbit Exposure time : 24 h

Method : Test(s) equivalent or similar to OECD Test Guideline 405

Remarks : Irritating to eyes.

Species : Rabbit Exposure time : 48 h

Method : Test(s) equivalent or similar to OECD Test Guideline 405

Remarks : Irritating to eyes.

Species : Rabbit Exposure time : 72 h

Method : Test(s) equivalent or similar to OECD Test Guideline 405

Remarks : Irritating to eyes.

Respiratory or skin sensitisation

Components:

Isopropyl alcohol:

Species : Guinea pig
Method : Buehler Test
Result : negative

Remarks : Not a sensitiser.

Based on available data, the classification criteria are not met.

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

Germ cell mutagenicity

Components:

Isopropyl alcohol:

Genotoxicity in vitro : Remarks: Based on available data, the classification criteria

are not met.

Genotoxicity in vivo : Remarks: Not mutagenic.

Germ cell mutagenicity- As-

sessment

This product does not meet the criteria for classification in

categories 1A/1B.

Carcinogenicity

Components:

Isopropyl alcohol:

Remarks : Not a carcinogen.

Carcinogenicity - Assess-

ment

This product does not meet the criteria for classification in

categories 1A/1B.

| Material | GHS/CLP Carcinogenicity Classification |
|-------------------|--|
| Isopropyl alcohol | No carcinogenicity classification. |

| Material | Other Carcinogenicity Classification |
|-------------------|---|
| Isopropyl alcohol | IARC: Group 3: Not classifiable as to its carcinogenicity to humans |

Reproductive toxicity

Components:

Isopropyl alcohol:

Effects on fertility

Remarks: Does not impair fertility., Not a developmental toxicant., Based on available data, the classification criteria are

not met.

Reproductive toxicity - As-

sessment

: This product does not meet the criteria for classification in

categories 1A/1B.

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

STOT - single exposure

Components:

Isopropyl alcohol:

Remarks : May cause drowsiness and dizziness.

STOT - repeated exposure

Components:

Isopropyl alcohol:

Remarks : Kidney: caused kidney effects in male rats which are not con-

sidered relevant to humans

Aspiration toxicity

Components:

Isopropyl alcohol:

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

Further information

Product:

Remarks : Unless indicated otherwise, the data presented is representa-

tive of the product as a whole, rather than for individual com-

ponent(s).

Components:

Isopropyl alcohol:

Remarks : Exposure may enhance the toxicity of other materials.

Classifications by other authorities under varying regulatory

frameworks may exist.

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Date of last issue: 23.11.2023 Version Revision Date: SDS Number:

09.10.2024 800001006805 Print Date 16.10.2024 5.1

SECTION 12: Ecological information

12.1 Toxicity

Components:

Isopropyl alcohol:

Toxicity to fish : Remarks: Practically non toxic:

LL/EL/IL50 > 100 mg/l

aquatic invertebrates

Toxicity to daphnia and other : Remarks: Practically non toxic:

LL/EL/IL50 > 100 mg/l

Toxicity to algae/aquatic plants : Remarks: Practically non toxic:

LL/EL/IL50 > 100 mg/l

Toxicity to microorganisms

Remarks: Practically non toxic:

LL/EL/IL50 > 100 mg/l

Toxicity to fish (Chronic tox-

icity)

Remarks: Data not available

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

Remarks: Data not available

12.2 Persistence and degradability

Components:

Isopropyl alcohol:

Biodegradability Remarks: Readily biodegradable.

Oxidises rapidly by photo-chemical reactions in air.

12.3 Bioaccumulative potential

Components:

Isopropyl alcohol:

Bioaccumulation : Remarks: Does not bioaccumulate significantly.

12.4 Mobility in soil

Components:

Isopropyl alcohol:

Mobility Remarks: Dissolves in water., If the product enters soil, one or

more constituents will or may be mobile and may contaminate

groundwater.

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

12.5 Results of PBT and vPvB assessment

Components:

Isopropyl alcohol:

Assessment : The substance does not fulfill all screening criteria for persis-

tence, bioaccumulation and toxicity and hence is not consid-

ered to be PBT or vPvB..

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to

have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological infor-

mation

: Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

Components:

Isopropyl alcohol:

Additional ecological infor-

mation

: Does not have ozone depletion potential.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Recover or recycle if possible.

It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal meth-

ods in compliance with applicable regulations.

Do not dispose into the environment, in drains or in water

courses.

Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment. Waste, spills or used product is dangerous waste.

Disposal should be in accordance with applicable regional,

national, and local laws and regulations.

Local regulations may be more stringent than regional or na-

tional requirements and must be complied with.

MARPOL - see International Convention for the Prevention of

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

Pollution from Ships (MARPOL 73/78) which provides tech-

nical aspects at controlling pollutions from ships.

Contaminated packaging : Drain container thoroughly.

After draining, vent in a safe place away from sparks and fire.

Residues may cause an explosion hazard. Do not, puncture, cut, or weld uncleaned drums. Send to drum recoverer or metal reclaimer.

Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand.

SECTION 14: Transport information

14.1 UN number or ID number

ADN : 1219
ADR : 1219
RID : 1219
IMDG : 1219
IATA : 1219

14.2 UN proper shipping name

ADN : ISOPROPANOL
ADR : ISOPROPANOL
RID : ISOPROPANOL
IMDG : ISOPROPANOL

IATA : ISOPROPANOL

14.3 Transport hazard class(es)

ADN : 3
ADR : 3
RID : 3
IMDG : 3
IATA : 3

14.4 Packing group

ADN

Packing group : II
Classification Code : F1
Labels : 3

ADR

Packing group : II Classification Code : F1

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

Hazard Identification Number : 33 Labels : 3

RID

Packing group : II
Classification Code : F1
Hazard Identification Number : 33
Labels : 3

IMDG

Packing group : II Labels : 3

IATA

Packing group : II Labels : 3

14.5 Environmental hazards

ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

Remarks : Special Precautions: Refer to Section 7, Handling & Storage,

for special precautions which a user needs to be aware of or

needs to comply with in connection with transport.

14.7 Maritime transport in bulk according to IMO instruments

Pollution category : Z

Ship type : IBC Chapter 18 cargo, must be double hulled

Product name : Isopropyl alcohol

Additional Information: This product may be transported under nitrogen blanketing.

Nitrogen is an odourless and invisible gas. Exposure to nitrogen may cause asphyxiation or death. Personnel must observe strict safety precautions when involved with a confined

space entry.

Transport in bulk according to Annex II of Marpol and the IBC

Code

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

REACH - List of substances subject to authorisation

(Annex XIV)

: Product is not subject to Authorisa-

tion under REACH.

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

: This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH),

Article 57).

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

FLAMMABLE LIQUIDS

Other regulations:

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

P5c

Hazardous substances:

- -2000, XXV, Decree
- -44/2000. (XII. 27.) EüM. decree
- 5/2020. (II. 6.) ITM decree

Hazardous waste legislation:

- 2012. évi CLXXXV. Decree
- 225/2015. (VIII.7.) Government Decree
- 72/2013. (VIII. 27.) VM Regulation
- 180/2007. (VII. 3.) Gov. Decree

Water pollution regulations:

- 220/2004 (VII. 21) Gov. Decree
- 28/2004(XII.5) KvVm Regulation

Occupational safety/OSH regulations:

- 1993. XCIII. Decree

Fire protection regulation

- 54/2014(XII.5.) BM Regulation

Transport regulations:

- 387/2021 (VI. 30) Gov. Decree.

Product is subject to Government Regulation No 219/2011. (X. 20) on the control of major accidents involving dangerous substances, based on SEVESO III Directive (2012/18/EU).

The components of this product are reported in the following inventories:

AIIC : Listed

DSL : Listed

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

IECSC : Listed

ENCS : Listed

KECI : Listed

NZIoC : Listed

PICCS : Listed

TSCA : Listed

TCSI : Listed

15.2 Chemical safety assessment

A Chemical Safety Assessment has been carried out for this substance.

SECTION 16: Other information

Full text of other abbreviations

HU BAT : Hungary. Permissible limit values of biological exposure (ef-

fect) indices

HU OEL : Hungary. Occupational Exposure Limits - Annex 1: Permissi-

ble concentration values

HU OEL / TWA : Mean concentration

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways: ADR - Agreement concerning the International Carriage of Dangerous Goods by Road: AIIC - Australian Inventory of Industrial Chemicals: ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA -European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Training advice : Provide adequate information, instruction and training for op-

erators.

Other information : For Industry guidance and tools on REACH please visit the

CEFIC website at http://cefic.org/Industry-support.

The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not consid-

ered to be PBT or vPvB.

A vertical bar (|) in the left margin indicates an amendment

from the previous version.

Sources of key data used to compile the Safety Data

Sheet

The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU

IUCLID date base, EC 1272 regulation, etc).

Classification of the mixture: Classification procedure:

Flam. Liq. 2 H225 On basis of test data.

Eye Irrit. 2 H319 Expert judgement and weight of evi-

dence determination.

STOT SE 3 H336 Expert judgement and weight of evi-

dence determination.

Identified Uses according to the Use Descriptor System Uses - Worker

Title : Water treatment chemicals

- Professional

Uses - Worker

Title : Water treatment chemicals

- Industrial

Uses - Worker

Title : Use in laboratories

- Professional

Uses - Worker

Title : Use in laboratories

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: 5.1 09.10.2024

SDS Number: 800001006805

Date of last issue: 23.11.2023

Print Date 16.10.2024

- Industrial

Uses - Worker

Title : De-icing and anti-icing applications

- Professional

Uses - Worker

Title : Functional Fluids

- Professional

Uses - Worker

Title : Functional Fluids

- Industrial

Uses - Worker

Title : Use as a fuel

- Professional

Uses - Worker

Title : Use as a fuel

- Industrial

Uses - Worker

Title : Use in Agrochemicals uses

- Professional

Uses - Worker

Title : Use as binders and release agents

- Professional

Uses - Worker

Title : Use as binders and release agents

- Industrial

Uses - Worker

Title : Metal working fluids / rolling oils

- Professional

Uses - Worker

Title : Metal working fluids / rolling oils

- Industrial

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

Uses - Worker

Title : Lubricants

- Professional

Uses - Worker

Title : Lubricants

- Industrial

Uses - Worker

Title : Use in Cleaning Agents

- Professional

Uses - Worker

Title : Use in Cleaning Agents

- Industrial

Uses - Worker

Title : Uses in Coatings

- Professional

Uses - Worker

Title : Uses in Coatings

- Industrial

Uses - Worker

Title : Formulation & (re)packing of substances and mixtures

- Industrial

Uses - Worker

Title : Distribution of substance

- Industrial

Uses - Worker

Title : Use as an intermediate

- Industrial

Uses - Worker

Title : Manufacture of substance

- Industrial

Identified Uses according to the Use Descriptor System

Uses - Consumer

Title : Use in coatings

- Consumer

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

Uses - Consumer

Title : Use in Cleaning Agents

- Consumer

Uses - Consumer

Title : Lubricants

- Consumer

Uses - Consumer

Title : Use in agrochemicals

- Consumer

Uses - Consumer

Title : Use as a fuel

- Consumer

Uses - Consumer

Title : Functional Fluids

- Consumer

Uses - Consumer

Title : Use in de-icing and anti-icing fluids

- Consumer

Uses - Consumer

Title : Other Consumer Uses

- Consumer

Uses - Consumer

Title : Water treatment chemicals

- Consumer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

HU / EN

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

Exposure Scenario - Worker

| 30000000313 | 000000313 | | |
|------------------|---|--|--|
| SECTION 1 | EXPOSURE SCENARIO TITLE | | |
| Title | Water treatment chemicals- Professional | | |
| Use Descriptor | Sector of Use: SU22 Process Categories: PROC1, PROC3, PROC4, PROC8a, PROC8b, PROC13 Environmental Release Categories: ERC8f | | |
| Scope of process | Covers the use of the substance for the treatment of water in open and closed systems. | | |

| SECTION 2 | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES |
|---|--|
| Additional Information | No exposure assessment presented for the environment. |
| Section 2.1 | Control of Worker Exposure |
| Product Characteristics | |
| Physical form of product | Liquid, vapour pressure 0.5 - 10 kPa at STP |
| Concentration of the Substance in Mixture/Article | Covers percentage substance in the product up to 100%., Unless stated otherwise., |
| Frequency and Duration of | Use |
| | 8 hours (unless stated differently). |
| Other Operational Condition | ns affecting Exposure |
| | an 20°C above ambient temperature (unless stated differently). |
| Assumes a good basic stand | lard of occupational hygiene is implemented. |
| Contributing Scenarios | Risk Management Measures |
| General measures (eye irritants). | Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands. |
| Bulk transfersDedicated facilityPROC8b | Clear transfer lines prior to de-coupling. |
| Drum/batch transfer- sPROC8b | Use drum pumps or carefully pour from container. |
| General exposures (closed systems)Use in contained batch processesPROC3 | No other specific measures identified. |
| General exposures (open systems)PROC4 | No other specific measures identified. |
| ManualPouring from small containersPROC13 | Carefully pour from containers. |
| | Datain durin dayuna in a alla datanana manding dianggal autan |
| Equipment cleaning and maintenancePROC8a | Retain drain downs in sealed storage pending disposal or for subsequent recycle. |

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

| Section 2.2 | Control of Environmental Exposure | |
|---|-----------------------------------|--|
| No exposure assessment presented for the environment. | | |

| | SECTION 3 | EXPOSURE ESTIMATION |
|--|------------|---------------------|
| Section 3.1 - Health | | |
| The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise | | |
| | indicated. | |

Section 3.2 -Environment

No exposure assessment presented for the environment.

| SECTION 4 | GUIDANCE TO CHECK COMPLIANCE WITH THE |
|--|---------------------------------------|
| | EXPOSURE SCENARIO |
| Section 4.1 - Health | |
| Predicted exposures are not expected to exceed the DN(M)EL when the Risk Managem Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then use should ensure that risks are managed to at least equivalent levels. | |

Section 4.2 -Environment

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

Exposure Scenario - Worker

| 30000000312 | |
|------------------|--|
| SECTION 1 | EXPOSURE SCENARIO TITLE |
| Title | Water treatment chemicals- Industrial |
| Use Descriptor | Sector of Use: SU3 Process Categories: PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC13 Environmental Release Categories: ERC3, ERC4 |
| Scope of process | Covers the use of the substance for the treatment of water at industrial facilities in open and closed systems. |

| SECTION 2 | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES |
|---|--|
| Additional Information | No exposure assessment presented for the environment. |
| Section 2.1 | Control of Worker Exposure |
| Product Characteristics | |
| Physical form of product | Liquid, vapour pressure 0.5 - 10 kPa at STP |
| Concentration of the Substance in Mixture/Article | Covers percentage substance in the product up to 100%., Unless stated otherwise., |
| Frequency and Duration of | Use |
| | 8 hours (unless stated differently). |
| Other Operational Condition | |
| | an 20°C above ambient temperature (unless stated differently). |
| Assumes a good basic stand | lard of occupational hygiene is implemented. |
| Contributing Scenarios | Risk Management Measures |
| General measures (eye irritants). | Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands. |
| Bulk transfers(closed systems)PROC2 | Clear transfer lines prior to de-coupling. |
| Drum/batch transfersDedicated facilityPROC8b | Use drum pumps or carefully pour from container. |
| General exposures (closed systems)Use in contained batch processesPROC3 | No other specific measures identified. |
| General exposures (open systems)PROC4 | No other specific measures identified. |
| ManualPouring from small containersPROC13 | Carefully pour from containers. |
| Equipment cleaning and maintenancePROC8a | Retain drain downs in sealed storage pending disposal or for subsequent recycle. |
| Storage.PROC1 | Store substance within a closed system. |
| | |

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

| Section 2.2 | Control of Environmental Exposure | |
|---|-----------------------------------|--|
| No exposure assessment presented for the environment. | | |

| SECTION 3 | EXPOSURE ESTIMATION |
|--|---------------------|
| Section 3.1 - Health | |
| The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise | |
| indicated. | |

Section 3.2 - Environment

No exposure assessment presented for the environment.

| SECTION 4 | GUIDANCE TO CHECK COMPLIANCE WITH THE |
|---|---|
| | EXPOSURE SCENARIO |
| Section 4.1 - Health | |
| Measures/Operational Condi Where other Risk Manageme | expected to exceed the DN(M)EL when the Risk Management tions outlined in Section 2 are implemented. ent Measures/Operational Conditions are adopted, then users managed to at least equivalent levels. |

Section 4.2 -Environment

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

Exposure Scenario - Worker

| Exposure obeniano Worker | |
|--------------------------|--|
| 30000000311 | |
| SECTION 1 | EXPOSURE SCENARIO TITLE |
| Title | Use in laboratories- Professional |
| Use Descriptor | Sector of Use: SU22 Process Categories: PROC10, PROC15 Environmental Release Categories: ERC8a |
| Scope of process | Use of small quantities within laboratory settings, including material transfers and equipment cleaning. |

| SECTION 2 | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES | |
|--|---|--|
| Additional Information | No exposure assessment presented for the environment. | |
| Section 2.1 | Control of Worker Exposure | |
| Product Characteristics | | |
| Physical form of product | Liquid, vapour pressure 0.5 - 10 kPa at STP | |
| Concentration of the Sub- | Covers percentage substance in the product up to 100%., | |
| stance in Mixture/Article | Unless stated otherwise., | |
| Frequency and Duration of | Use | |
| Covers daily exposures up to | 8 hours (unless stated differently). | |
| Other Operational Conditio | ns affecting Exposure | |
| Assumes use at not more than 20°C above ambient temperature (unless stated differently). | | |
| Assumes a good basic standard of occupational hygiene is implemented. | | |
| Contributing Scenarios | Risk Management Measures | |
| General measures (eye | Use suitable eye protection. | |
| irritants). | Avoid direct eye contact with product, also via contamination on hands. | |
| Laboratory activitiesPROC15 | No other specific measures identified. | |
| CleaningPROC10 | No other specific measures identified. | |
| Section 2.2 | Control of Environmental Exposure | |

| SECTION 3 | EXPOSURE ESTIMATION |
|--|---------------------|
| Section 3.1 - Health | |
| The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise | |
| indicated. | |

Section 3.2 - Environment

No exposure assessment presented for the environment.

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

SECTION 4 GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO

Section 4.1 - Health

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 - Environment

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

Exposure Scenario - Worker

| 30000000310 | |
|------------------|---|
| SECTION 1 | EXPOSURE SCENARIO TITLE |
| Title | Use in laboratories- Industrial |
| Use Descriptor | Sector of Use: SU3 Process Categories: PROC10, PROC15 Environmental Release Categories: ERC2, ERC4 |
| Scope of process | Use of the substance within laboratory settings, including material transfers and equipment cleaning. |

| SECTION 2 | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES |
|-----------------------------|--|
| Additional Information | No exposure assessment presented for the environment. |
| Section 2.1 | Control of Worker Exposure |
| Product Characteristics | |
| Physical form of product | Liquid, vapour pressure 0.5 - 10 kPa at STP |
| Concentration of the Sub- | Covers percentage substance in the product up to 100%., |
| stance in Mixture/Article | Unless stated otherwise., |
| Frequency and Duration o | f Use |
| | o 8 hours (unless stated differently). |
| Other Operational Condition | |
| Assumes use at not more th | an 20°C above ambient temperature (unless stated differently). |
| Assumes a good basic stand | dard of occupational hygiene is implemented. |
| Contributing Scenarios | Risk Management Measures |
| General measures (eye | Use suitable eye protection. |
| irritants). | Avoid direct eye contact with product, also via contamination |
| | on hands. |
| Laboratory activi- | No other specific measures identified. |
| tiesPROC15 | · · |
| CleaningPROC10 | No other specific measures identified. |
| Section 2.2 | Control of Environmental Exposure |

| SECTION 3 | EXPOSURE ESTIMATION |
|--|---------------------|
| Section 3.1 - Health | |
| The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise | |
| indicated. | |

Section 3.2 - Environment

No exposure assessment presented for the environment.

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

SECTION 4 GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO

Section 4.1 - Health

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 - Environment

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

Exposure Scenario - Worker

| 30000000306 | |
|------------------|--|
| SECTION 1 | EXPOSURE SCENARIO TITLE |
| Title | De-icing and anti-icing applications- Professional |
| Use Descriptor | Sector of Use: SU22 Process Categories: PROC1, PROC2, PROC8a, PROC8b, PROC11 Environmental Release Categories: ERC8d |
| Scope of process | Ice prevention and de-icing of vehicles, aircraft and other equipment by spraying. |

| SECTION 2 | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES | |
|---|---|--|
| Additional Information | No exposure assessment presented for the environment. | |
| Section 2.1 | Control of Worker Exposure | |
| Product Characteristics | | |
| Physical form of product | Liquid, vapour pressure 0.5 - 10 kPa at STP | |
| Concentration of the Substance in Mixture/Article | Covers percentage substance in the product up to 100%., Unless stated otherwise., | |
| Frequency and Duration of | Use | |
| Covers daily exposures up to | 8 hours (unless stated differently). | |
| Other Operational Conditions affecting Exposure | | |
| | an 20°C above ambient temperature (unless stated differently). | |
| Assumes a good basic stand | lard of occupational hygiene is implemented. | |
| Contributing Scenarios | Risk Management Measures | |
| General measures (eye | Use suitable eye protection. | |
| irritants). | Avoid direct eye contact with product, also via contamination on hands. | |
| Bulk transfersDedicated facilityPROC8b | Clear transfer lines prior to de-coupling. | |
| Drum/batch transfer- sPROC8b | No other specific measures identified. | |
| Spraying/ fogging by ma- | Ensure operation is undertaken outdoors. | |
| chine applicationPROC11 | Avoid carrying out activities involving exposure for more than | |
| | 1 hour. | |
| | Stay upwind/ keep distance from source. | |
| Ad hoc manual application | Ensure operation is undertaken outdoors. | |
| via trigger sprays, dipping, | Avoid carrying out activities involving exposure for more than | |
| etc.PROC11 | 1 hour. | |
| | Stay upwind/ keep distance from source. | |
| Equipment cleaning and | No other specific measures identified. | |

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

| maintenancePROC8a | | |
|---|---|--|
| Storage.PROC1PROC2 | Store substance within a closed system. | |
| | | |
| Section 2.2 | Control of Environmental Exposure | |
| No exposure assessment presented for the environment. | | |

| SECTION 3 | EXPOSURE ESTIMATION |
|---|---------------------|
| Section 3.1 - Health | |
| The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated. | |

Section 3.2 -Environment

No exposure assessment presented for the environment.

| XPOSURE SCENARIO | |
|--|--|
| Section 4.1 - Health | |
| Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. | |
| | |

Measures/Operational Conditions outlined in Section 2 are implemented.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 -Environment No exposure assessment presented for the environment.

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

Exposure Scenario - Worker

| 30000000305 | |
|------------------|---|
| SECTION 1 | EXPOSURE SCENARIO TITLE |
| Title | Functional Fluids- Professional |
| Use Descriptor | Sector of Use: SU22 Process Categories: PROC1, PROC2, PROC3, PROC8a, PROC9, PROC20 Environmental Release Categories: ERC9a, ERC9b |
| Scope of process | Use as functional fluids e.g. cable oils, transfer oils, coolants, insulators, refrigerants, hydraulic fluids in professional equipment including maintenance and related material transfers. |

| SECTION 2 | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES | |
|--|---|--|
| Additional Information | No exposure assessment presented for the environment. | |
| Section 2.1 | Control of Worker Exposure | |
| Product Characteristics | | |
| Physical form of product | Liquid, vapour pressure 0.5 - 10 kPa at STP | |
| Concentration of the Substance in Mixture/Article | Covers percentage substance in the product up to 100%., Unless stated otherwise., | |
| Frequency and Duration of Use | | |
| Covers daily exposures up to 8 hours (unless stated differently). | | |
| Other Operational Conditions affecting Exposure | | |
| Assumes use at not more than 20°C above ambient temperature (unless stated differently). | | |
| Assumes a good basic standard of occupational hygiene is implemented. | | |

| Contributing Scenarios | Risk Management Measures |
|--|--|
| General measures (eye irritants). | Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands. |
| Drum/batch transfersPROC8a | No other specific measures identified. |
| Transfer from/pouring from cor tainersPROC9 | No other specific measures identified. |
| ManualFilling of arti- cles/equipmentPROC9 | Carefully pour from containers. |
| Use of sealed items containing functional fluids e.g. transfer oils, hydraulic fluids, refrigerants.PROC20 | No other specific measures identified. |
| General exposures (closed systems)PROC1PROC2PROC | No other specific measures identified. |
| Remanufacture of reject articlesPROC9 | No other specific measures identified. |

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

| maintenancePROC8a Storage.PROC1PROC2 | Store substance within a closed system. |
|---------------------------------------|---|
| Section 2.2 Co | ontrol of Environmental Exposure |

No exposure assessment presented for the environment.

| SECTION 3 | EXPOSURE ESTIMATION |
|---|---------------------|
| Section 3.1 - Health | |
| The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated. | |

Section 3.2 -Environment No exposure assessment presented for the environment.

| SECTION 4 | GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO | |
|--|---|--|
| Section 4.1 - Healt | th | |
| Predicted exposure | Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management | |
| Measures/Operational Conditions outlined in Section 2 are implemented. | | |
| Where other Risk N | Apparement Measures/Operational Conditions are adopted, then users | |

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

| Section 4.2 -Environment |
|---|
| No exposure assessment presented for the environment. |

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

Exposure Scenario - Worker

| 30000000303 | |
|------------------|---|
| SECTION 1 | EXPOSURE SCENARIO TITLE |
| Title | Functional Fluids- Industrial |
| Use Descriptor | Sector of Use: SU3 Process Categories: PROC1, PROC2, PROC4, PROC8a, PROC9, PROC8b Environmental Release Categories: ERC7 |
| Scope of process | Use as functional fluids e.g. cable oils, transfer oils, coolants, insulators, refrigerants, hydraulic fluids in industrial equipment including maintenance and related material transfers. |

| SECTION 2 | OPERATIONAL CONDITIONS AND RIS | K MANAGEMENT |
|---|---|-------------------|
| Additional Information | No exposure assessment presented for the | he environment. |
| Section 2.1 | Control of Worker Exposure | |
| Product Characteristics | | |
| Physical form of product | Liquid, vapour pressure 0.5 - 10 kPa at S | TP |
| Concentration of the Sub- | Covers percentage substance in the proc | luct up to 100%., |
| stance in Mixture/Article | Unless stated otherwise., | - |
| Frequency and Duration of Use | | |
| Covers daily exposures up to 8 hours (unless stated differently). | | |
| Other Operational Conditions affecting Exposure | | |

Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.

| Contributing Scenarios | Risk Management Measures |
|---|--|
| General measures (eye irritants). | Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands. |
| Bulk transfers(closed systems)PROC1PROC2 | Clear transfer lines prior to de-coupling. |
| Drum/batch transfersDedicated facilityPROC8b | No other specific measures identified. |
| Filling of arti- cles/equipmentUse of closed filling equip- ment.PROC9 | No other specific measures identified. |
| ManualFilling of arti- cles/equipmentPROC8a | Carefully pour from containers. |
| Use of sealed items containing functional fluids e.g. transfer oils, hydraulic fluids, refrigerants.PROC2 | No other specific measures identified. |

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

| General exposures (open systems)PROC4 | No other specific measures identified. |
|---|--|
| Equipment cleaning and maintenancePROC8a | Retain drain downs in sealed storage pending disposal or for subsequent recycle. |
| Storage.PROC1PROC2 | Store substance within a closed system. |
| Section 2.2 | Control of Environmental Exposure |
| No exposure assessment presented for the environment. | |

| SECTION 3 | EXPOSURE ESTIMATION |
|---------------------------|--|
| Section 3.1 - Health | |
| The ECETOC TDA tool hoe h | and the action of the continuous control of the marine |

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

Section 3.2 - Environment

No exposure assessment presented for the environment.

| SECTION 4 | GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO |
|--|---|
| Section 4.1 - Health | |
| Dradicted expensions are not expected to exceed the DN/M/EL when the Dick Management | |

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 - Environment

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Date of last issue: 23.11.2023 Version Revision Date: SDS Number:

5.1 09.10.2024 800001006805 Print Date 16.10.2024

Exposure Scenario - Worker

| 30000000302 | |
|------------------|---|
| SECTION 1 | EXPOSURE SCENARIO TITLE |
| Title | Use as a fuel- Professional |
| Use Descriptor | Sector of Use: SU22 Process Categories: PROC1, PROC2, PROC3, PROC8a, PROC8b, PROC16 Environmental Release Categories: ERC9a, ERC9b |
| Scope of process | Covers the use as a fuel (or fuel additive) and includes activities associated with its transfer, use, equipment maintenance and handling of waste. |

| SECTION 2 | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES |
|--|---|
| Additional Information | No exposure assessment presented for the environment. |
| Section 2.1 | Control of Worker Exposure |
| Product Characteristics | |
| Physical form of product | Liquid, vapour pressure 0.5 - 10 kPa at STP |
| Concentration of the Substance in Mixture/Article | Covers percentage substance in the product up to 100%., Unless stated otherwise., |
| Frequency and Duration of Use | |
| Covers daily exposures up to 8 hours (unless stated differently). | |
| Other Operational Conditions affecting Exposure | |
| Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented. | |

| Contributing Scenarios | Risk Management Measures |
|--|--|
| General measures (eye irritants). | Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands. |
| Bulk transfersDedicated facili- tyPROC8b | Transfer via enclosed lines. Clear transfer lines prior to de-coupling. |
| Drum/batch transfersDedicated facilityPROC8b | d Avoid spillage when withdrawing pump. |
| Refueling.Dedicated facili- tyPROC8b | Avoid spillage when withdrawing pump. |
| Use as a fuel(closed systems)PROC16 | No other specific measures identified. |
| General exposures (closed systems)PROC1PROC2PROC | No other specific measures identified. |
| Equipment cleaning and maintenancePROC8a | Retain drain downs in sealed storage pending disposal or for subsequent recycle. |

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

Storage.PROC1 Store substance within a closed system.

Section 2.2 Control of Environmental Exposure

No exposure assessment presented for the environment.

| SECTION 3 | EXPOSURE ESTIMATION | |
|--|---------------------|--|
| Section 3.1 - Health | | |
| The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise | | |
| indicated. | | |

Section 3.2 - Environment

No exposure assessment presented for the environment.

| SECTION 4 | GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO |
|---|---|
| Section 4.1 - Health | |
| Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management | |
| Measures/Operational Conditions outlined in Section 2 are implemented. | |
| Where other Risk Management Measures/Operational Conditions are adopted, then users | |
| should ensure that risks are managed to at least equivalent levels. | |

Section 4.2 - Environment

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

Exposure Scenario - Worker

| 30000000301 | |
|------------------|---|
| SECTION 1 | EXPOSURE SCENARIO TITLE |
| Title | Use as a fuel- Industrial |
| Use Descriptor | Sector of Use: SU3 Process Categories: PROC1, PROC2, PROC3, PROC8a, PROC8b, PROC16 Environmental Release Categories: ERC7 |
| Scope of process | Covers the use as a fuel (or fuel additive) and includes activities associated with its transfer, use, equipment maintenance and handling of waste. |

| SECTION 2 | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES | |
|--|---|--|
| Additional Information | No exposure assessment presented for the environment. | |
| Section 2.1 | Control of Worker Exposure | |
| Product Characteristics | | |
| Physical form of product | Liquid, vapour pressure 0.5 - 10 kPa at STP | |
| Concentration of the Substance in Mixture/Article | Covers percentage substance in the product up to 100%., Unless stated otherwise., | |
| Frequency and Duration of Use | | |
| Covers daily exposures up to 8 hours (unless stated differently). | | |
| Other Operational Conditions affecting Exposure | | |
| Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented. | | |

Contributing Scenarios Risk Management Measures General measures (eye irri-Use suitable eye protection. Avoid direct eye contact with product, also via contamination tants). on hands. Bulk transfersDedicated facili-Transfer via enclosed lines. tyPROC8b Clear transfer lines prior to de-coupling. Drum/batch transfersDedicated Use drum pumps or carefully pour from container. facilityPROC8b General exposures (closed No other specific measures identified. systems)PROC1PROC2PROC3 Use as a fuel(closed sys-No other specific measures identified. tems)PROC16 Equipment cleaning and Drain down system prior to equipment opening or maintemaintenancePROC8a Retain drain downs in sealed storage pending disposal or for subsequent recycle.

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

09.10.2024 800001006805 Print Date 16.10.2024 5.1

Storage.PROC1PROC2 Store substance within a closed system. **Control of Environmental Exposure** Section 2.2 No exposure assessment presented for the environment.

| SECTION 3 | EXPOSURE ESTIMATION |
|--|---------------------|
| Section 3.1 - Health | |
| The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise | |
| indicated. | |

Section 3.2 - Environment No exposure assessment presented for the environment.

| SECTION 4 | GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO |
|---|---|
| Section 4.1 - Health | |
| Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management | |
| Measures/Operational Conditions outlined in Section 2 are implemented. | |
| Where other Risk Management Measures/Operational Conditions are adopted, then users | |

vvnere other RISK Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 - Environment No exposure assessment presented for the environment.

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

Exposure Scenario - Worker

| 30000000300 | |
|------------------|---|
| SECTION 1 | EXPOSURE SCENARIO TITLE |
| Title | Use in Agrochemicals uses- Professional |
| Use Descriptor | Sector of Use: SU22 Process Categories: PROC1, PROC2, PROC4, PROC8a, PROC8b, PROC11, PROC13 Environmental Release Categories: ERC8a, ERC8d |
| Scope of process | Use as an agrochemical excipient for application by manual or machine spraying, smokes and fogging; including equipment clean-downs and disposal. |

| SECTION 2 | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES | |
|---|---|--|
| Additional Information | No exposure assessment presented for the environment. | |
| Section 2.1 | Control of Worker Exposure | |
| Product Characteristics | | |
| Physical form of product | Liquid, vapour pressure 0.5 - 10 kPa at STP | |
| Concentration of the Substance in Mixture/Article | Covers percentage substance in the product up to 100%., Unless stated otherwise., | |
| Frequency and Duration of Use | | |
| Covers daily exposures up to 8 hours (unless stated differently). | | |
| Other Operational Conditions affecting Exposure | | |
| Assumes use at not more th | an 20°C above ambient temperature (unless stated differently). | |

Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.

| Contributing Scenarios | Risk Management Measures | |
|---|--|--|
| General measures (eye irritants). | Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands. | |
| Transfer from/pouring from containersPROC8b | No other specific measures identified. | |
| Mixing operations (open systems)PROC4 | No other specific measures identified. | |
| Spraying/ fogging by manual applicationPROC11 | Limit the substance content in the product to 25 %. Avoid carrying out activities involving exposure for more than 4 hours | |
| Spraying/ fogging by machine applicationPROC11 | Apply within a vented cab supplied with filtered air under positive pressure and with a protection factor of >20. | |
| Ad hoc manual application via trigger sprays, dipping, etc.PROC13 | No other specific measures identified. | |

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

| Equipment cleaning and maintenancePROC8a | Retain drain downs in sealed storage pending disposal or for subsequent recycle. |
|---|--|
| Storage.PROC1PROC2 | Store substance within a closed system. |
| Section 2.2 | Control of Environmental Evacuus |
| Section 2.2 | Control of Environmental Exposure |
| No exposure assessment presented for the environment. | |

| SECTION 3 | EXPOSURE ESTIMATION | |
|---|---------------------|--|
| Section 3.1 - Health | | |
| The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated. | | |

Section 3.2 - Environment

No exposure assessment presented for the environment.

| SECTION 4 | GUIDANCE TO CHECK COMPLIANCE WITH THE |
|----------------------|---------------------------------------|
| | EXPOSURE SCENARIO |
| Section 4.1 - Health | |

Section 4.1 - Health

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 -Environment

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Date of last issue: 23.11.2023 Version Revision Date: SDS Number:

5.1 09.10.2024 800001006805 Print Date 16.10.2024

Exposure Scenario - Worker

| Exposure occitatio - Worker | |
|-----------------------------|--|
| 30000000299 | |
| SECTION 1 | EXPOSURE SCENARIO TITLE |
| Title | Use as binders and release agents- Professional |
| Use Descriptor | Sector of Use: SU22 Process Categories: PROC 1, PROC 2, PROC 3, PROC 4, PROC 6, PROC 8a, PROC 8b, PROC 10, PROC 11, PROC 14 Environmental Release Categories: ERC8a, ERC8d |
| Scope of process | Covers the use as binders and release agents including material transfers, mixing, application by spraying, brushing, and handling of waste. |

| SECTION 2 | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES | |
|--|---|--|
| Additional Information | No exposure assessment presented for the environment. | |
| Section 2.1 | Control of Worker Exposure | |
| Product Characteristics | | |
| Physical form of product | Liquid, vapour pressure 0.5 - 10 kPa at STP | |
| Concentration of the Sub- | Covers percentage substance in the product up to 100%., | |
| stance in Mixture/Article | Unless stated otherwise., | |
| Frequency and Duration of Use | | |
| Covers daily exposures up to 8 hours (unless stated differently). | | |
| Other Operational Conditions affecting Exposure | | |
| Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented. | | |

| Contributing Scenarios | Risk Management Measures |
|--|--|
| General measures (eye irritants). | Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands. |
| Bulk transfers(closed systems)PROC1PROC2PROC3 | No other specific measures identified. |
| Drum/batch transfer- sPROC8aPROC8b | No other specific measures identified. |
| Mixing operations (open systems)PROC4 | No other specific measures identified. |
| Mixing operations (closed systems)PROC3 | No other specific measures identified. |
| Mold formingPROC14 | No other specific measures identified. |
| Casting operations(open systems)elevated temperature- PROC6 | Provide extraction ventilation at points where emissions occur. |

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

| Continu 0.0 | Control of Engineering Languages |
|---|---|
| Storage.PROC1PROC2 | Store substance within a closed system. |
| | , or: Wear a respirator conforming to EN140 with Type A/P2 filter or better. Segregate the activity away from other operations. |
| ManualSprayingPROC11 | Carry out in a vented booth or extracted enclosure. |
| Roller, spreader, flow applica tionPROC10 | No other specific measures identified. |
| MachineSprayingPROC11 | Carry out in a vented booth or extracted enclosure. Segregate the activity away from other operations. |

| Section 2.2 | Control of Environmental Exposure | |
|---|-----------------------------------|--|
| No exposure assessment presented for the environment. | | |

| SECTION 3 | EXPOSURE ESTIMATION |
|--|---------------------|
| Section 3.1 - Health | |
| The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise | |
| indicated | |

Section 3.2 - Environment

No exposure assessment presented for the environment.

| SECTION 4 | GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO |
|--------------------|---|
| Castian 4.4 Haalth | |

Section 4.1 - Health

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 - Environment

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

Exposure Scenario - Worker

| Exposure occitatio Worker | |
|---------------------------|---|
| 30000000298 | |
| SECTION 1 | EXPOSURE SCENARIO TITLE |
| Title | Use as binders and release agents- Industrial |
| Use Descriptor | Sector of Use: SU3 Process Categories: PROC1, PROC2, PROC3, PROC4, PROC6, PROC7, PROC8a, PROC8b, PROC10, PROC13, PROC14 Environmental Release Categories: ERC4 |
| Scope of process | Covers the use as binders and release agents including material transfers, mixing, application (including spraying and brushing), mould forming and casting, and handling of waste. |

| SECTION 2 | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES |
|--|---|
| Additional Information | No exposure assessment presented for the environment. |
| Section 2.1 | Control of Worker Exposure |
| Product Characteristics | |
| Physical form of product | Liquid, vapour pressure 0.5 - 10 kPa at STP |
| Concentration of the Sub- | Covers percentage substance in the product up to 100%., |
| stance in Mixture/Article | Unless stated otherwise., |
| Frequency and Duration of Use | |
| Covers daily exposures up to 8 hours (unless stated differently). | |
| Other Operational Conditions affecting Exposure | |
| Assumes use at not more than 20°C above ambient temperature (unless stated differently). | |
| Assumes a good basic standard of occupational hygiene is implemented. | |

| Contributing Scenarios | Risk Management Measures |
|--|--|
| General measures (eye irritants). | Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands. |
| Bulk transfers(closed systems)PROC1PROC2PROC3 | Clear transfer lines prior to de-coupling. |
| Drum/batch transfer- sPROC8aPROC8b | No other specific measures identified. |
| Mixing operations (closed systems)PROC3 | No other specific measures identified. |
| Mixing operations (open systems)PROC4 | No other specific measures identified. |
| Mold formingPROC14 | No other specific measures identified. |
| Casting operations(open systems)elevated temperature- PROC6 | Provide extraction ventilation at points where emissions occur. |

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

| Treatment by dipping and pour-ingPROC13 | No other specific measures identified. |
|--|---|
| Spraying (automatic/robotic)PROC7 | Minimise exposure by partial enclosure of the operation or equipment and provide extract ventilation at openings. |
| SprayingManualPROC7 | Carry out in a vented booth or extracted enclosure. |
| Equipment cleaning and maintenancePROC8a | No other specific measures identified. |
| Storage.PROC1PROC2 | Store substance within a closed system. |

| Section 2.2 | Control of Environmental Exposure | |
|---|-----------------------------------|--|
| No exposure assessment presented for the environment. | | |

| SECTION 3 | EXPOSURE ESTIMATION |
|--|---------------------|
| Section 3.1 - Health | |
| The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise | |
| indicated. | |

Section 3.2 - Environment

No exposure assessment presented for the environment.

| SECTION 4 | GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO |
|----------------------|---|
| Section 4.1 - Health | |

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

| Section 4.2 -Environment | |
|--|--|
| No exposure assessment presented for the environment | |

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

Exposure Scenario - Worker

| 30000000297 | |
|------------------|--|
| SECTION 1 | EXPOSURE SCENARIO TITLE |
| Title | Metal working fluids / rolling oils- Professional |
| Use Descriptor | Sector of Use: SU22 Process Categories: PROC1, PROC2, PROC3, PROC5, PROC8a, PROC8b, PROC9, PROC10, PROC11, PROC13, PROC17 Environmental Release Categories: ERC8a, ERC8d |
| Scope of process | Covers the use in formulated MWFs including transfer operations, open and contained cutting/machining activities, automated and manual application of corrosion protections, draining and working on contaminated/reject articles, and disposal of waste oils. |

| SECTION 2 | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES | |
|------------------------------|---|--|
| Additional Information | No exposure assessment presented for the environment. | |
| Section 2.1 | Control of Worker Exposure | |
| Product Characteristics | | |
| Physical form of product | Liquid, vapour pressure 0.5 - 10 kPa at STP | |
| Concentration of the Sub- | Covers percentage substance in the product up to 100%., | |
| stance in Mixture/Article | Unless stated otherwise., | |
| Frequency and Duration of | f Use | |
| Covers daily exposures up to | o 8 hours (unless stated differently). | |
| Other Operational Condition | ons affecting Exposure | |

Other Operational Conditions affecting Exposure
Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.

| Contributing Scenarios | Risk Management Measures |
|------------------------|--------------------------|
| | |

| General measures (eye irritants). | Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands. |
|--|--|
| General exposures (closed systems)PROC1PROC2PROC3 | No other specific measures identified. |
| Bulk transfersDedicated facilityPROC8b | Clear transfer lines prior to de-coupling. |
| Filling/ preparation of equipment from drums or contain- ers.PROC5PROC8aPROC8bPROC9 | No other specific measures identified. |
| Product sampling.PROC8b | No other specific measures identified. |
| Metal machining operationsPROC17 | Provide extraction ventilation at points where emissions occur. |

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

| Roller, spreader, flow applicationPROC10 | No other specific measures identified. |
|---|--|
| SprayingPROC11 | Carry out in a vented booth or extracted enclosure. , or: Wear a respirator conforming to EN140 with Type A/P2 filter or better. |
| Treatment by dipping and pouringPROC13 | Allow time for product to drain from workpiece. No other specific measures identified. |
| Equipment cleaning and maintenance-PROC8aPROC8b | Retain drain downs in sealed storage pending disposal or for subsequent recycle. No other specific measures identified. |
| Storage.PROC1PROC2 | Handle substance within a closed system. |

| Section 2.2 | Control of Environmental Exposure | |
|---|-----------------------------------|--|
| No exposure assessment presented for the environment. | | |

| SECTION 3 | EXPOSURE ESTIMATION |
|--|---------------------|
| Section 3.1 - Health | |
| The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise | |
| indicated | |

Section 3.2 - Environment

No exposure assessment presented for the environment.

| SECTION 4 | GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO |
|---|---|
| Section 4.1 - Health | |
| Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management | |
| Measures/Operational Conditions outlined in Section 2 are implemented | |

Measures/Operational Conditions outlined in Section 2 are implemented.
Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

| Section 4.2 -Environment | |
|---|---|
| No exposure assessment presented for the environment. | - |

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

Exposure Scenario - Worker

| Exposure decriario - Worker | | | |
|-----------------------------|---|--|--|
| 30000000296 | | | |
| | | | |
| SECTION 1 | EXPOSURE SCENARIO TITLE | | |
| Title | Metal working fluids / rolling oils- Industrial | | |
| Use Descriptor | Sector of Use: SU3 | | |
| | Process Categories: PROC1, PROC2, PROC3, PROC4, | | |
| | PROC5, PROC7, PROC8a, PROC8b, PROC9, PROC10, | | |
| | PROC13, PROC17 | | |
| | Environmental Release Categories: ERC4 | | |
| | _ | | |
| Scope of process | Covers the use in formulated MWFs/rolling oils including transfer operations, rolling and annealing activities, cutting/machining activities, automated and manual application of corrosion protections (including brushing, dipping and spraying), equipment maintenance, draining and disposal of waste oils. | | |

| SECTION 2 | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES | | |
|---|---|--|--|
| Additional Information | No exposure assessment presented for the environment. | | |
| Section 2.1 | Control of Worker Exposure | | |
| Product Characteristics | | | |
| Physical form of product | Liquid, vapour pressure 0.5 - 10 kPa at STP | | |
| Concentration of the Substance in the product up to 100%., stance in Mixture/Article Covers percentage substance in the product up to 100%., Unless stated otherwise., | | | |
| Frequency and Duration of Use | | | |
| Covers daily exposures up to 8 hours (unless stated differently). | | | |
| Other Operational Conditions affecting Exposure | | | |
| Assumes use at not more than 20°C above ambient temperature (unless stated differently). | | | |

Assumes a good basic standard of occupational hygiene is implemented.

| Contributing Scenarios Risl | | k Management Measures | |
|---|-----------|---|----|
| General measures (eye irritar | nts). | Use suitable eye protection. Avoid direct eye contact with product, also via contamination hands. | on |
| General exposures (closed sy tems)PROC1PROC2PROC3 | | No other specific measures identified. | |
| General exposures (open systems)PROC4 | 5- | No other specific measures identified. | |
| Bulk transfersDrum/batch tranfersPROC5PROC8bPROC9 | าร- | No other specific measures identified. | |
| Product sampling.PROC8b | | No other specific measures identified. | |
| Metal machining operationsPROC17 | | No other specific measures identified. | |

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

| Treatment by dipping and pour-ingPROC13 | No other specific measures identified. |
|---|---|
| SprayingPROC7 | Minimise exposure by partial enclosure of the operation or equipment and provide extract ventilation at openings. |
| Manual applications e.g. brushing, rollingPROC10 | No other specific measures identified. |
| Automated metal roll- ing/formingelevated tempera- tureUse in contained sys- temsPROC2 | No other specific measures identified. |
| Semi-automated metal roll- ing/formingelevated tempera- turePROC17 | Automate activity where possible. No other specific measures identified. |
| Equipment cleaning and maintenancePROC8aPROC8b | Retain drain downs in sealed storage pending disposal or for subsequent recycle. |
| Storage.PROC1PROC2 | Store substance within a closed system. |

| Section 2.2 | Control of Environmental Exposure |
|----------------------------|-----------------------------------|
| No exposure assessment pre | sented for the environment. |

| SECTION 3 | EXPOSURE ESTIMATION |
|---------------------------|--|
| Section 3.1 - Health | |
| The ECETOC TRA tool has b | peen used to estimate workplace exposures unless otherwise |

indicated.

Section 3.2 -Environment No exposure assessment presented for the environment.

| | SECTION 4 | GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO | |
|--|-----------|---|--|
| Section 4.1 - Health | | | |
| Predicted exposures are not expected to exceed the DN(M)FL when the Risk Managem | | | |

Measures/Operational Conditions outlined in Section 2 are implemented.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

| Section 4.2 -Environment |
|---|
| No exposure assessment presented for the environment. |

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

Exposure Scenario - Worker

| 30000000295 | |
|------------------|---|
| SECTION 1 | EXPOSURE SCENARIO TITLE |
| Title | Lubricants- Professional |
| Use Descriptor | Sector of Use: SU22 Process Categories: PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC9, PROC10, PROC11, PROC13, PROC17, PROC18, PROC20 Environmental Release Categories: ERC8a, ERC8d, ERC9a, ERC9b |
| Scope of process | Covers the use of formulated lubricants in closed and open systems including transfer operations, operation of engines and similar articles, reworking on reject articles, equipment maintenance and disposal of waste oil. |

| SECTION 2 | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES | | |
|---|---|--|--|
| Additional Information | No exposure assessment presented for the environment. | | |
| Section 2.1 | Control of Worker Exposure | | |
| Product Characteristics | | | |
| Physical form of product | Liquid, vapour pressure 0.5 - 10 kPa at STP | | |
| Concentration of the Substance in Mixture/Article | Covers percentage substance in the product up to 100%., Unless stated otherwise., | | |
| Frequency and Duration of Use | | | |
| Covers daily exposures up to | 8 hours (unless stated differently). | | |
| Other Operational Conditions affecting Exposure | | | |

Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.

| Contributing Scenarios | Risk M | anagement Measures | |
|--|--------|--|------|
| General measures (eye irritar | nts). | Use suitable eye protection. Avoid direct eye contact with product, also via contamition on hands. | ina- |
| General exposures (closed sy tems)PROC1PROC2PROC3 | /S- | No other specific measures identified. | |
| Operation of equipment conta engine oils and similar.PROC | _ | No other specific measures identified. | |
| General exposures (open systems)PROC4 | - | No other specific measures identified. | |
| Bulk transfersDedicated facilityPROC8b | - | No other specific measures identified. | |
| Filling/ preparation of equipm from drums or containers.PROC8aPROC8b | ent | No other specific measures identified. | |

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

| Operation and lubrication of high | Restrict area of openings to equipment. |
|--|--|
| energy open equipmentIn- doorPROC17PROC18 | Provide extraction ventilation at points where emissions occur. |
| Operation and lubrication of high energy open equipmentOut-doorPROC17PROC18 | No other specific measures identified. |
| Maintenance and machine set upelevated temperaturePROC8b | Provide extract ventilation to emission points when contact with warm (>50 Degrees C) lubricant is likely. |
| Maintenance of small itemselevated temperatureCovers percentage substance in the product up to 5%.PROC8a | Avoid carrying out activities involving exposure for more than 4 hours Retain drain downs in sealed storage pending disposal or for subsequent recycle. |
| Engine lubricant servicePROC9 | No other specific measures identified. |
| Manual applications e.g. brushing, rollingPROC10 | No other specific measures identified. |
| SprayingPROC11 | Minimise exposure by partial enclosure of the operation or equipment and provide extract ventilation at openings. , or: Wear a respirator conforming to EN140 with Type A/P2 filter or better. |
| Treatment by dipping and pour- ingPROC13 | Minimise exposure by partial enclosure of the operation or equipment and provide extract ventilation at openings. , or: Provide a good standard of controlled ventilation (10 to 15 air changes per hour). Allow time for product to drain from workpiece. |
| Storage.PROC1PROC2 | Store substance within a closed system. |
| Continu 0.0 | Let Chrisenmental Cymenus |

| Section 2.2 | Control of Environmental Exposure | |
|---|-----------------------------------|--|
| No exposure assessment presented for the environment. | | |

| SECTION 3 | EXPOSURE ESTIMATION |
|--------------------------------------|---|
| Section 3.1 - Health | |
| The ECETOC TRA tool has b indicated. | een used to estimate workplace exposures unless otherwise |

| Section 3.2 -Environment | |
|---|--|
| No exposure assessment presented for the environment. | |

| SECTION 4 | GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO |
|-----------------------------|---|
| Section 4.1 - Health | |
| Predicted exposures are not | expected to exceed the DN(M)EL when the Risk Management |

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

Measures/Operational Conditions outlined in Section 2 are implemented.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Should chould that how are managed to at least equivalent levels.

Section 4.2 - Environment

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

Exposure Scenario - Worker

| 30000000294 | |
|------------------|--|
| SECTION 1 | EXPOSURE SCENARIO TITLE |
| Title | Lubricants- Industrial |
| Use Descriptor | Sector of Use: SU3 Process Categories: PROC1, PROC2, PROC3, PROC4, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC17, PROC18 Environmental Release Categories: ERC7, ERC4 |
| Scope of process | Covers the use of formulated lubricants in closed and open systems including transfer operations, operation of machinery/engines and similar articles, reworking on reject articles, equipment maintenance and disposal of wastes. |

| SECTION 2 | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES |
|--|---|
| Additional Information | No exposure assessment presented for the environment. |
| Section 2.1 | Control of Worker Exposure |
| Product Characteristics | |
| Physical form of product | Liquid, vapour pressure 0.5 - 10 kPa at STP |
| Concentration of the Substance in Mixture/Article | Covers percentage substance in the product up to 100%., Unless stated otherwise., |
| Frequency and Duration of Use | |
| Covers daily exposures up to 8 hours (unless stated differently). | |
| Other Operational Conditions affecting Exposure | |
| Assumes use at not more than 20°C above ambient temperature (unless stated differently). | |

Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.

| Contributing Scenarios | Risk Management Measures |
|---|--|
| General measures (eye irritants). | Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands. |
| General exposures (closed systems)PROC1PROC2PROC | No other specific measures identified. |
| General exposures (open systems)PROC4 | No other specific measures identified. |
| Bulk transfersDedicated facilityPROC8b | Clear transfer lines prior to de-coupling. |
| Filling/ preparation of equipme from drums or containers.PROC8aPROC8b | nt No other specific measures identified. |
| Initial factory fill of equip- mentPROC9 | No other specific measures identified. |
| Operation and lubrication of | Provide extraction ventilation at points where emissions oc- |

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

| high energy open equip- mentPROC17PROC18 | cur. Restrict area of openings to equipment. |
|---|---|
| Manual applications e.g. brushing, rollingPROC10 | No other specific measures identified. |
| Treatment by dipping and pour- ingPROC13 | No other specific measures identified. |
| SprayingPROC7 | Minimise exposure by partial enclosure of the operation or equipment and provide extract ventilation at openings. |
| Maintenance (of larger plant items) and machine set up-PROC8b | No other specific measures identified. |
| Maintenance of small itemsPROC8a | No other specific measures identified. |
| Storage.PROC1PROC2 | Store substance within a closed system. |

| Section 2.2 | Control of Environmental Exposure |
|-----------------------------|-----------------------------------|
| No exposure assessment pres | ented for the environment. |

| SECTION 3 | EXPOSURE ESTIMATION |
|---|---------------------|
| Section 3.1 - Health | |
| The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated. | |

Section 3.2 - Environment

No exposure assessment presented for the environment.

| SECTION 4 | EXPOSURE SCENARIO |
|---|-------------------|
| Section 4.1 - Health | |
| Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management | |
| Measures/Operational Conditions outlined in Section 2 are implemented. | |
| Where other Risk Management Measures/Operational Conditions are adopted then users | |

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 -Environment No exposure assessment presented for the environment.

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

Exposure Scenario - Worker

| 30000000278 | 0000000278 | |
|------------------|---|--|
| SECTION 1 | EXPOSURE SCENARIO TITLE | |
| Title | Use in Cleaning Agents- Professional | |
| Use Descriptor | Sector of Use: SU22 Process Categories: PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC10, PROC11, PROC13 Environmental Release Categories: ERC8a, ERC8d | |
| Scope of process | Covers the use as a component of cleaning products including pouring/unloading from drums or containers; and exposures during mixing/diluting in the preparatory phase and cleaning activities (including spraying, brushing, dipping, wiping automated and by hand). | |

| SECTION 2 | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES |
|--|---|
| Additional Information | No exposure assessment presented for the environment. |
| Section 2.1 | Control of Worker Exposure |
| Product Characteristics | |
| Physical form of product | Liquid, vapour pressure 0.5 - 10 kPa at STP |
| Concentration of the Substance in Mixture/Article | Covers percentage substance in the product up to 100%., Unless stated otherwise., |
| Frequency and Duration of Use | |
| Covers daily exposures up to 8 hours (unless stated differently). | |
| Other Operational Conditions affecting Exposure | |
| Assumes use at not more than 20°C above ambient temperature (unless stated differently). | |

Assumes a good basic standard of occupational hygiene is implemented.

Contributing Scenarios Risk Management Measures General measures (eye irritants). Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands. Filling/ preparation of equipment from No other specific measures identified. drums or containers.PROC8b Automated process with (semi) closed No other specific measures identified. systems. Use in contained systemsPROC2PROC3 Semi Automated process. (e.g.: Semi au-No other specific measures identified. tomatic application of floor care and maintenance products)PROC4 Filling/ preparation of equipment from No other specific measures identified. drums or containers.PROC8a ManualSurfacesCleaningDipping, immer-No other specific measures identified. sion and pouringPROC13

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

| Cleaning with low-pressure washers- | No other specific measures identified. |
|--|--|
| Rolling, Brushingno sprayingPROC10 | |
| Cleaning with high pressure washers- | Provide a good standard of controlled ventilation |
| SprayingIndoorPROC11 | (10 to 15 air changes per hour). |
| | |
| Cleaning with high pressure washers- | Limit the substance content in the product to 1 %. |
| SprayingOutdoorPROC11 | , or: |
| g chraying canadan read re | Avoid carrying out activities involving exposure for |
| | more than 15 minutes. |
| | There than to minutes. |
| ManualSurfacesCleaningSprayingPROC10 | No other specific measures identified. |
| Warnacicarracocoloarinigopraying: 110010 | The earler opening meaning administra |
| Ad hoc manual application via trigger | No other specific measures identified. |
| sprays, dipping, etc.Rolling, Brush- | |
| ingPROC10 | |
| Application of cleaning products in closed | No other specific measures identified. |
| systemsOutdoorPROC4 | |
| Cleaning of medical devicesPROC4 | No other specific measures identified. |
| | The other specific measures identified. |
| Storage.PROC1 | Store substance within a closed system. |
| | |

| Section 2.2 | Control of Environmental Exposure |
|---|-----------------------------------|
| No exposure assessment presented for the environment. | |

| SECTION 3 | EXPOSURE ESTIMATION |
|--|---------------------|
| Section 3.1 - Health | |
| The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise | |

indicated.

Section 3.2 -Environment No exposure assessment presented for the environment.

| | SECTION 4 | GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO |
|---|---|---|
| | Section 4.1 - Health | |
| | Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management | |
| | Measures/Operational Conditions outlined in Section 2 are implemented. | |
| | Where other Risk Management Measures/Operational Conditions are adopted, then users | |
| should ensure that risks are managed to at least equivalent levels. | | nanaged to at least equivalent levels. |

| Section 4.2 -Environment | |
|---|--|
| No exposure assessment presented for the environment. | |

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

Exposure Scenario - Worker

| 30000000277 | |
|------------------|---|
| SECTION 1 | EXPOSURE SCENARIO TITLE |
| Title | Use in Cleaning Agents- Industrial |
| Use Descriptor | Sector of Use: SU3 Process Categories: PROC1, PROC2, PROC3, PROC4, PROC7, PROC8a, PROC8b, PROC10, PROC13 Environmental Release Categories: ERC4 |
| Scope of process | Covers the use as a component of cleaning products including transfer from storage, pouring/unloading from drums or containers. Exposures during mixing/diluting in the preparatory phase and cleaning activities (including spraying, brushing, dipping, wiping, automated and by hand), related equipment cleaning and maintenance. |

| SECTION 2 | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES |
|---|---|
| Additional Information | No exposure assessment presented for the environment. |
| Section 2.1 | Control of Worker Exposure |
| Product Characteristics | |
| Physical form of product | Liquid, vapour pressure 0.5 - 10 kPa at STP |
| Concentration of the Substance in Mixture/Article | Covers percentage substance in the product up to 100%., Unless stated otherwise., |
| Frequency and Duration of Use | |
| Covers daily exposures up to 8 hours (unless stated differently). | |
| Other Operational Conditions affecting Exposure | |
| Assumes use at not more th | an 20°C above ambient temperature (unless stated differently). |

Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.

| Contributing Scenarios | Risk Management Measures |
|--|--|
| General measures (eye irritants). | Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands. |
| Bulk transfersPROC8a | Clear transfer lines prior to de-coupling. |
| Automated process with (semi) closed systems.Use in contained systemsPROC2 | No other specific measures identified. |
| Application of cleaning products in closed systemsPROC2 | No other specific measures identified. |
| Filling/ preparation of equipment from drums or | No other specific measures identified. |

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

| containers.PROC8b | |
|--|--|
| Use in contained batch processesPROC4 | No other specific measures identified. |
| Degreasing small objects in cleaning stationPROC13 | No other specific measures identified. |
| Cleaning with low-pressure washersPROC10 | No other specific measures identified. |
| Cleaning with high pressure washersPROC7 | Provide a good standard of controlled ventilation (10 to 15 air changes per hour). |
| ManualSurfacesCleaningno sprayingPROC10 | No other specific measures identified. |
| Storage.PROC1 | Store substance within a closed system. |
| Section 2.2 | Control of Environmental Exposure |
| No exposure assessment pre | sented for the environment. |

| | SECTION 3 | EXPOSURE ESTIMATION |
|----------------------|---------------------------|---|
| Section 3.1 - Health | | |
| | The ECETOC TRA tool has b | een used to estimate workplace exposures unless otherwise |

indicated.

Section 3.2 - Environment

No exposure assessment presented for the environment.

| SECTION 4 | GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO |
|--|---|
| Section 4.1 - Health | |
| Measures/Operational Condi Where other Risk Manageme | expected to exceed the DN(M)EL when the Risk Management tions outlined in Section 2 are implemented. ent Measures/Operational Conditions are adopted, then users managed to at least equivalent levels. |

Section 4.2 - Environment

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

Exposure Scenario - Worker

| 30000000276 | |
|------------------|--|
| SECTION 1 | EXPOSURE SCENARIO TITLE |
| Title | Uses in Coatings- Professional |
| Use Descriptor | Sector of Use: SU22 Process Categories: PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC10, PROC11, PROC13, PROC15, PROC19 Environmental Release Categories: ERC8a, ERC8d |
| Scope of process | Covers the use in coatings (paints, inks, adhesives, etc) including exposures during use (including materials receipt, storage, preparation and transfer from bulk and semi-bulk, application by spray, roller, brush, spreader by hand or similar methods, and film formation), and equipment cleaning, maintenance and associated laboratory activities. |

| SECTION 2 | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES | |
|---|---|--|
| Additional Information | No exposure assessment presented for the environment. | |
| Section 2.1 | Control of Worker Exposure | |
| Product Characteristics | | |
| Physical form of product | Liquid, vapour pressure 0.5 - 10 kPa at STP | |
| Concentration of the Substance in Mixture/Article | Covers percentage substance in the product up to 100%., Unless stated otherwise., | |
| Frequency and Duration o | f Use | |
| Covers daily exposures up to 8 hours (unless stated differently). | | |
| Other Operational Condition | ons affecting Exposure | |
| | an 20°C above ambient temperature (unless stated differently). | |

Assumes a good basic standard of occupational hygiene is implemented.

| Contributing Scenarios | Risk | k Management Measures |
|--|-----------|--|
| General measures (eye irritar | nts). | Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands. |
| General exposures (closed sy tems)PROC1PROC2PROC3 | | No other specific measures identified. |
| Filling/ preparation of equipm from drums or containers.Use contained systemsPROC2 | | No other specific measures identified. |
| General exposures (open systems)PROC4 | 5- | No other specific measures identified. |
| Preparation of material for ap cationUse in contained batch processesPROC3 | | No other specific measures identified. |

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

| Film formation - air dry- ingOutdoorPROC4 | No other specific measures identified. |
|---|---|
| Film formation - air dryingln- doorPROC4 | No other specific measures identified. |
| Preparation of material for applicationIndoorPROC5 | No other specific measures identified. |
| Material transfersDrum/batch transfersPROC8aPROC8b | No other specific measures identified. |
| Roller, spreader, flow applicationPROC10 | No other specific measures identified. |
| ManualSprayingIndoorPROC11 | Carry out in a vented booth or extracted enclosure. |
| ManualSprayingOutdoorPROC11 | Wear a respirator conforming to EN140 with Type A filter or better. |
| Dipping, immersion and pouringPROC13 | No other specific measures identified. |
| Laboratory activitiesPROC15 | No other specific measures identified. |
| Hand application - fingerpaints, pastels, adhesivesPROC19 | No other specific measures identified. |
| 0 1 0 0 | |

| Section 2.2 | Control of Environmental Exposure | |
|---|-----------------------------------|--|
| No exposure assessment presented for the environment. | | |
| | | |

| SECTION 3 | EXPOSURE ESTIMATION | |
|--|---------------------|--|
| Section 3.1 - Health | | |
| The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise | | |

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

Section 3.2 -Environment No exposure assessment presented for the environment.

| SECTION 4 | GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO | |
|---|---|--|
| Section 4.1 - Health | | |
| Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. | | |

| Se | ection 4.2 -Environment |
|----|--|
| No | o exposure assessment presented for the environment. |

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

Exposure Scenario - Worker

| 2000000007 | | |
|------------------|--|--|
| 30000000275 | | |
| | | |
| SECTION 1 | EXPOSURE SCENARIO TITLE | |
| Title | Uses in Coatings- Industrial | |
| Use Descriptor | Sector of Use: SU3 | |
| | Process Categories: PROC1, PROC2, PROC3, PROC4, | |
| | PROC5, PROC7, PROC8a, PROC8b, PROC10, PROC13, | |
| | PROC15 | |
| | Environmental Release Categories: ERC4 | |
| | | |
| Scope of process | Covers the use in coatings (paints, inks, adhesives, etc) including exposures during use (including materials receipt, storage, preparation and transfer from bulk and semi-bulk, application by spray, roller, spreader, dip, flow, fluidised bed on production lines and film formation) and equipment cleaning, maintenance and associated laboratory activities. | |

| SECTION 2 | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES | |
|--|--|--|
| Additional Information | No exposure assessment presented for the environment. | |
| Section 2.1 | Control of Worker Exposure | |
| Product Characteristics | | |
| Physical form of product | Liquid, vapour pressure 0.5 - 10 kPa at STP | |
| Concentration of the Substance in Mixture/Article | and the process processing a constraint of the control of the cont | |
| Frequency and Duration o | f Use | |
| Covers daily exposures up to 8 hours (unless stated differently). | | |
| Other Operational Condition | ons affecting Exposure | |
| Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented. | | |

Assumes a good basic standard of occupational hygiene is implemented.

| Contributing Scenarios | Risk M | lanagement Measures | |
|---|--------|---|-----|
| General measures (eye irritar | nts). | Use suitable eye protection. Avoid direct eye contact with product, also via contamir tion on hands. | na- |
| General exposures (closed sy tems)PROC1PROC2 | /S- | No other specific measures identified. | |
| General exposures (open systems)PROC4 | ;- | No other specific measures identified. | |
| Film formation - force drying, ing and other technologies.Us contained systemsPROC2 | | No other specific measures identified. | |
| Mixing operations (closed systems)General exposures (closesystems)PROC3 | | No other specific measures identified. | |

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

| Film formation - air dryingPROC4 | No other specific measures identified. |
|--|--|
| Preparation of material for applicationMixing operations (open systems)PROC5 | No other specific measures identified. |
| Spraying (automatic/robotic)PROC7 | Carry out in a vented booth or extracted enclosure. |
| ManualSprayingPROC7 | Provide a good standard of controlled ventilation (10 to 15 air changes per hour). |
| Roller, spreader, flow applicationPROC10 | No other specific measures identified. |
| Dipping, immersion and pouringPROC13 | No other specific measures identified. |
| Laboratory activitiesPROC15 | No other specific measures identified. |
| Material transfersDrum/batch transfersTransfer from/pouring from containersPROC8aPROC8bPROC9 | No other specific measures identified. |
| Production or preparation or articles by tabletting, compression, extrusion or pelletisationPROC14 | No other specific measures identified. |

| Section 2.2 | Control of Environmental Exposure | |
|---|-----------------------------------|--|
| No exposure assessment presented for the environment. | | |

| SECTION 3 | EXPOSURE ESTIMATION |
|--|---------------------|
| Section 3.1 - Health | |
| The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise | |

indicated.

Section 3.2 -Environment

No exposure assessment presented for the environment.

| SECTION 4 | GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO |
|--|---|
| Section 4.1 - Health | |
| Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. | |

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

| Section 4.2 -Environment |
|---|
| No exposure assessment presented for the environment. |

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

Exposure Scenario - Worker

| 30000000274 | |
|------------------|--|
| SECTION 1 | EXPOSURE SCENARIO TITLE |
| Title | Formulation & (re)packing of substances and mixtures- Industrial |
| Use Descriptor | Sector of Use: SU3, SU10 Process Categories: PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9, PROC14, PROC15 Environmental Release Categories: ERC2 |
| Scope of process | Formulation, packing and re-packing of the substance and its mixtures in batch or continuous operations, including storage, materials transfers, mixing, tabletting, compression, pelletisation, extrusion, large and small scale packing, sampling, maintenance and associated laboratory activities. |

| SECTION 2 | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES | |
|---|---|--|
| Additional Information | No exposure assessment presented for the environment. | |
| Section 2.1 | Control of Worker Exposure | |
| Product Characteristics | | |
| Physical form of product | Liquid, vapour pressure 0.5 - 10 kPa at STP | |
| Concentration of the Sub- | Covers percentage substance in the product up to 100%., | |
| stance in Mixture/Article | Unless stated otherwise., | |
| Frequency and Duration of Use | | |
| Covers daily exposures up to 8 hours (unless stated differently). | | |
| Other Operational Conditions affecting Exposure | | |

Other Operational Conditions affecting Exposure

Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.

| Contributing Scenarios F | Risk Management Measures |
|---|--|
| General measures (eye irritants). | Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands. |
| General exposures (closed systems)PROC1PROC2PROC3 | No other specific measures identified. 3 |
| General exposures (open systems)PROC4 | No other specific measures identified. |
| Batch processes at elevated temperaturesPROC3 | No other specific measures identified. |
| Process samplingPROC3 | No other specific measures identified. |
| Laboratory activitiesPROC15 | No other specific measures identified. |
| Bulk transfersPROC8b | No other specific measures identified. |

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

| Storage.PROC2 | Store substance within a closed system. | |
|--|---|--|
| Equipment cleaning and maintenancePROC8a | Drain down system prior to equipment opening or maintenance. Retain drain downs in sealed storage pending disposal or for subsequent recycle. | |
| Drum and small package fill- ingPROC9 | No other specific measures identified. | |
| Production or preparation or articles by tabletting, compression, extrusion or pelletisa- tionPROC14 | No other specific measures identified. | |
| Drum/batch transfersPROC8 | | |
| ManualTransfer from/pouring from containersPROC8a | No other specific measures identified. | |
| Mixing operations (open systems)PROC5 | No other specific measures identified. | |

| Section 2.2 | Control of Environmental Exposure | |
|---|-----------------------------------|--|
| No exposure assessment presented for the environment. | | |

| SECTION 3 | EXPOSURE ESTIMATION |
|--|---------------------|
| Section 3.1 - Health | |
| The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise | |

indicated.

Section 3.2 -Environment

No exposure assessment presented for the environment.

| SECTION 4 | GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO |
|----------------------|---|
| Section 4.1 - Health | |

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

| Section 4.2 -Environment | |
|--|--|
| No exposure assessment presented for the environment | |

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

Exposure Scenario - Worker

| 30000000273 | |
|------------------|--|
| SECTION 1 | EXPOSURE SCENARIO TITLE |
| Title | Distribution of substance- Industrial |
| Use Descriptor | Sector of Use: SU3, SU8, SU9 Process Categories: PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC9, PROC15 Environmental Release Categories: ERC1, ERC2, ERC3, ERC4, ERC5, ERC6a, ERC7 |
| Scope of process | Loading (including marine vessel/barge, rail/road car and IBC loading) and repacking (including drums and small packs) of substance, including its sampling, storage, unloading distribution and associated laboratory activities. |

| SECTION 2 | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES |
|--|---|
| Additional Information | No exposure assessment presented for the environment. |
| Section 2.1 | Control of Worker Exposure |
| Product Characteristics | |
| Physical form of product | Liquid, vapour pressure 0.5 - 10 kPa at STP |
| Concentration of the Substance in Mixture/Article | Covers percentage substance in the product up to 100%., Unless stated otherwise., |
| Frequency and Duration of Use | |
| Covers daily exposures up to 8 hours (unless stated differently). | |
| Other Operational Conditions affecting Exposure | |
| Assumes use at not more than 20°C above ambient temperature (unless stated differently). | |

Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.

| Contributing Scenarios | Risk Management Measures | |
|---|---|---|
| General measures (eye irritants). | Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands. | n |
| General exposures (closed systems)PROC1PROC2PRO | No other specific measures identified. | |
| General exposures (open systems)PROC4 | No other specific measures identified. | |
| Process samplingPROC3 | No other specific measures identified. | |
| Laboratory activitiesPROC15 | No other specific measures identified. | |
| Bulk transfers(open systems)PROC8b | No other specific measures identified. | |
| Bulk transfers(closed systems)PROC8b | No other specific measures identified. | |

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

| Drum and small package fill-ingPROC9 | No other specific measures identified. |
|--|---|
| Equipment cleaning and maintenancePROC8a | Drain down system prior to equipment opening or maintenance. Retain drain downs in sealed storage pending disposal or for subsequent recycle. |
| Storage.PROC2 | Store substance within a closed system. |

| Section 2.2 | Control of Environmental Exposure | |
|---|-----------------------------------|--|
| No exposure assessment presented for the environment. | | |

| SECTION 3 | EXPOSURE ESTIMATION |
|---------------------------------------|---|
| Section 3.1 - Health | |
| The ECETOC TRA tool has be indicated. | een used to estimate workplace exposures unless otherwise |

Section 3.2 - Environment

No exposure assessment presented for the environment.

| SECTION 4 | GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO |
|---|---|
| Section 4.1 - Health | |
| Dradicted expecures are not expected to exceed the DN/M/CL when the Dick Management | |

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 - Environment

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

Exposure Scenario - Worker

| 30000000272 | |
|------------------|--|
| SECTION 1 | EXPOSURE SCENARIO TITLE |
| Title | Use as an intermediate- Industrial |
| Use Descriptor | Sector of Use: SU3, SU8, SU9 Process Categories: PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC15 Environmental Release Categories: ERC6a |
| Scope of process | Use of substance as an intermediate (not related to Strictly Controlled Conditions). Includes recycling/ recovery, material transfers, storage, sampling, associated laboratory activities, maintenance and loading (including marine vessel/barge, road/rail car and bulk container). |

| SECTION 2 | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES | |
|--|--|--|
| Additional Information | No exposure assessment presented for the environment. | |
| Section 2.1 | Control of Worker Exposure | |
| Product Characteristics | | |
| Physical form of product | Liquid, vapour pressure 0.5 - 10 kPa at STP | |
| Concentration of the Substance in Mixture/Article | Covers percentage substance in the product up to 100%., Unless stated otherwise., | |
| Frequency and Duration of Use | | |
| Covers daily exposures up to 8 hours (unless stated differently). | | |
| Other Operational Conditions affecting Exposure | | |
| Assumes use at not more than 20°C above ambient temperature (unless stated differently). | | |

Assumes a good basic standard of occupational hygiene is implemented.

| Contributing Scenarios | Risk Management Measures |
|---|--|
| General measures (eye irritants). | Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands. |
| General exposures (closed systems)PROC1PROC2PRO | No other specific measures identified. |
| General exposures (open systems)PROC4 | No other specific measures identified. |
| Process samplingPROC8a | No other specific measures identified. |
| Laboratory activitiesPROC15 | No other specific measures identified. |
| Bulk transfers(open systems)PROC8b | No other specific measures identified. |
| Bulk transfers(closed systems)PROC8b | No other specific measures identified. |

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

| Equipment cleaning and maintenancePROC8a | Drain down system prior to equipment opening or maintenance. Retain drain downs in sealed storage pending disposal or for subsequent recycle. |
|--|--|
| Storage. | Store substance within a closed system. |
| Section 2.2 | Control of Environmental Exposure |
| No exposure assessment presented for the environment | |

| SECTION 3 | EXPOSURE ESTIMATION |
|--|---------------------|
| Section 3.1 - Health | |
| The FORTOO TDA (cell as leave as life as foreign and above a cell as a few allows in | |

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

Section 3.2 - Environment

No exposure assessment presented for the environment.

| SECTION 4 | GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO |
|----------------------|---|
| Section 4.1 - Health | |

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 - Environment

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

Exposure Scenario - Worker

| 30000000271 | |
|------------------|---|
| SECTION 1 | EXPOSURE SCENARIO TITLE |
| Title | Manufacture of substance- Industrial |
| Use Descriptor | Sector of Use: SU3, SU8, SU9 Process Categories: PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC15 Environmental Release Categories: ERC1, ERC4 |
| Scope of process | Manufacture of the substance or use as a process chemical or extraction agent. Includes recycling/ recovery, material transfers, storage, maintenance and loading (including marine vessel/barge, road/rail car and bulk container), sampling and associated laboratory activities. |

| SECTION 2 | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES | |
|--|---|--|
| Additional Information | No exposure assessment presented for the environment. | |
| Section 2.1 | Control of Worker Exposure | |
| Product Characteristics | | |
| Physical form of product | Liquid, vapour pressure 0.5 - 10 kPa at STP | |
| Concentration of the Substance in Mixture/Article | | |
| Frequency and Duration o | f Use | |
| Covers daily exposures up to 8 hours (unless stated differently). | | |
| Other Operational Condition | ons affecting Exposure | |
| Assumes use at not more than 20°C above ambient temperature (unless stated differently). | | |

Assumes a good basic standard of occupational hygiene is implemented.

| Contributing Scenarios | Risk Management Measures |
|--|--|
| General measures (eye irritants). | Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands. |
| General exposures (closed systems)PROC1PROC2PROC | No other specific measures identified. |
| General exposures (open systems)PROC4 | No other specific measures identified. |
| Process samplingPROC8b | No other specific measures identified. |
| Laboratory activitiesPROC15 | No other specific measures identified. |
| Bulk transfers(open systems)PROC8b | No other specific measures identified. |
| Bulk transfers(closed systems)PROC8b | No other specific measures identified. |

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

09.10.2024 800001006805 Print Date 16.10.2024 5.1

| Equipment cleaning and maintenancePROC8a | Drain down system prior to equipment opening or maintenance. Retain drain downs in sealed storage pending disposal or for subsequent recycle. |
|--|---|
| Storage.PROC2 | Store substance within a closed system. |
| Section 2.2 | Control of Environmental Exposure |
| No exposure assessment pres | ented for the environment. |

| SECTION 3 | EXPOSURE ESTIMATION |
|---------------------------|---|
| Section 3.1 - Health | |
| The ECETOC TRA tool has b | een used to estimate workplace exposures unless otherwise |

indicated.

Section 3.2 - Environment

No exposure assessment presented for the environment.

| SECTION 4 | GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO |
|----------------------|---|
| Section 4.1 - Health | |

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 - Environment

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

Exposure Scenario - Consumer

| 30000001013 | |
|------------------|---|
| SECTION 1 | EXPOSURE SCENARIO TITLE |
| Title | Use in coatings - Consumer |
| Use Descriptor | Sector of Use: SU21 Product Categories: PC1, PC4, PC8 (excipient only), PC9a, PC9b, PC9c, PC15, PC18, PC23, PC31, PC34 Environmental Release Categories: ERC8a, ERC8d |
| Scope of process | Covers the use in coatings (paints, inks, adhesives, etc) including exposures during use (including product transfer and preparation, application by brush, spray by hand or similar methods) and equipment cleaning. |

| SECTION 2 | OPERATIONAL CONDITIONS AN MEASURES | ID RISK MANAGEMENT |
|---|------------------------------------|-------------------------|
| Additional Information | No exposure assessment presente | ed for the environment. |
| Section 2.1 | Control of Consumer Exposure | |
| Product Characteristics | • | |
| Physical form of product | Liquid, vapour pressure > 10 Pa at | STP |
| Concentration of the Substance in Mixture/Article | Unless stated otherwise. | |
| | Covers concentration up to (%): 10 | 00 % |
| Amounts Used | | |
| Unless stated otherwise. | | |
| for each use event, covers a | amount up to (g): | 13.800 |
| covers skin contact area (cn | n2): | 857,5 |
| Frequency and Duration o | f Use | |
| Unless stated otherwise. | | |
| covers use up to (times/day | of use): | 1 |
| Exposure (hours/event): | | 6 |
| Other Operational Condition | ons affecting Exposure | |
| Unless stated otherwise | | |

Unless stated otherwise.

Covers use at ambient temperatures.

Covers use in room size of 20m3

| Product Categories | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES |
|---------------------------------------|---|
| Adhesives, sealants Glues, hobby use. | Covers concentrations up to 50 % |
| | covers use up to 365 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 35,73 cm2 |
| | For each use event, covers amount up to 9 g |
| | Covers use in room size of 20 m3 |

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

| | for each use event Covers exposure up to 4 hours/event |
|--|---|
| Adhesives, sealants Glues | Covers concentrations up to 50 % |
| DIY-use (carpet glue, tile | Corole concentrations up to co // |
| glue, wood parquet glue). | |
| giao, wood parquot giao). | covers use up to 1 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 110,00 cm2 |
| | For each use event, covers amount up to 6.390 g |
| | Covers use in room size of 20 m3 |
| | for each use event Covers exposure up to 6,00 hours/event |
| Adhesives, sealants Glue | Covers concentrations up to 50 % |
| from spray. | |
| | covers use up to 6 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 35,73 cm2 |
| | For each use event, covers amount up to 85,05 g |
| | Covers use in room size of 20 m3 |
| | for each use event Covers exposure up to 4,00 hours/event |
| Adhesives, sealants Sealants. | Covers concentrations up to 50 % |
| | covers use up to 365 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 35,73 cm2 |
| | For each use event, covers amount up to 75 g |
| | Covers use in room size of 20 m3 |
| | for each use event Covers exposure up to 1,00 hours/event |
| Anti-Freeze and de-icing products Washing car window. | Covers concentrations up to 50 % |
| dow. | covers use up to 365 day/year |
| | covers use up to 1000 day/year |
| | For each use event, covers amount up to 0,5 g |
| | Covers use in a one car garage (34 m3) under typical ventila- |
| | tion. |
| | Covers use in room size of 34 m3 |
| | for each use event Covers exposure up to 0,02 hours/event |
| Anti-Freeze and de-icing products Pouring into radiator. | Covers concentrations up to 50 % |
| | covers use up to 365 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 428,00 cm2 |
| | For each use event, covers amount up to 2.000 g |
| | Covers use in a one car garage (34 m3) under typical ventila- |
| | tion. |
| | Covers use in room size of 34 m3 |
| | for each use event Covers exposure up to 0,17 hours/event |
| Anti-Freeze and de-icing | Covers concentrations up to 50 % |
| products Lock de-icer. | · |
| | covers use up to 365 day/year |
| | covers use up to 1 times/day of use |

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

| | covers skin contact area up to (cm2): 214,40 cm2 |
|---|---|
| | For each use event, covers amount up to 4 g |
| | Covers use in a one car garage (34 m3) under typical ventilation. |
| | Covers use in room size of 34 m3 |
| | for each use event Covers exposure up to 0,25 hours/event |
| Biocidal products (e.g. Dis- infectants, pest control) (excipient only). Laundry and dish washing products. | Covers concentrations up to 50 % |
| | covers use up to 365 day/year |
| | Covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 857,50 cm2 |
| | For each use event, covers amount up to 15 g |
| | Covers use in room size of 20 m3 |
| | for each use event Covers exposure up to 0,50 hours/event |
| Biocidal products (e.g. Dis- infectants, pest control) (excipient only). Cleaners, liquids (all purpose clean- ers, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners). | Covers concentrations up to 50 % |
| | covers use up to 128 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 857,50 cm2 |
| | For each use event, covers amount up to 27 g |
| | Covers use in room size of 20 m3 |
| | for each use event Covers exposure up to 0,33 hours/event |
| Biocidal products (e.g. Dis- infectants, pest control) (excipient only). Cleaners, trigger sprays (all purpose cleaners,sanitary products, glass cleaners). | Covers concentrations up to 50 % |
| | covers use up to 128 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 428,00 cm2 |
| | For each use event, covers amount up to 35 g |
| | Covers use in room size of 20 m3 |
| | for each use event Covers exposure up to 0,17 hours/event |
| Coatings and paints, thin- ners, paint removers Sol- vent rich, high solid, water borne paint. | Covers concentrations up to 27,5 % |
| | covers use up to 6 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 428,75 cm2 |
| | For each use event, covers amount up to 744 g |
| | Covers use in room size of 20 m3 |

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

| | for each use event Covers exposure up to 2,20 hours/event |
|-------------------------------|---|
| Coatings and paints, thin- | Covers concentrations up to 50 % |
| ners, paint removers Aero- | от |
| sol spray can. | |
| | covers use up to 2 day/year |
| | covers use up to 1 times/day of use |
| | For each use event, covers amount up to 215 g |
| | Covers use in a one car garage (34 m3) under typical ventila- |
| | tion. |
| | Covers use in room size of 34 m3 |
| | for each use event Covers exposure up to 0,33 hours/event |
| Coatings and paints, thin- | Covers concentrations up to 50 % |
| ners, paint removers Re- | |
| movers (paint-, glue-, wall | |
| paper-, sealant-remover). | |
| | covers use up to 3 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 857,50 cm2 |
| | for each use event, covers amount up to (g): 491 g |
| | Covers use in room size of 20 m3 |
| | for each use event Covers exposure up to 2,00 hours/event |
| Fillers, Putties Fillers and | Covers concentrations up to 50 % |
| putty. | · · |
| . , | covers use up to 12 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 35,73 cm2 |
| | For each use event, covers amount up to 85 g |
| | Covers use in room size of 20 m3 |
| | for each use event Covers exposure up to 4,00 hours/event |
| Fillers, Putties Plasters and | Covers concentrations up to 2 % |
| floor equalizers. | · |
| • | covers use up to 12 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 857,50 cm2 |
| | For each use event, covers amount up to 13.800 g |
| | Covers use in room size of 20 m3 |
| | for each use event Covers exposure up to 2,00 hours/event |
| Fillers, Putties Modelling | Covers concentrations up to 10 % |
| clay. | |
| | covers use up to 365 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 254,40 cm2 |
| | For each use event, assumes swallowed amount of 1 g |
| | Covers use in room size of 20 m3 |
| Finger paints | Covers concentrations up to 15 % |
| | covers use up to 365 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 254,40 cm2 |
| | For each use event, assumes swallowed amount of 1,35 g |
| | Covers use in room size of 20 m3 |
| Non-metal-surface treat- | Covers concentrations up to 27,5 % |

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

| ment products Solvent rich, | |
|---|---|
| high solid, water borne paint. | |
| panti | covers use up to 6 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 428,75 cm2 |
| | For each use event, covers amount up to 744 g |
| | Covers use in room size of 20 m3 |
| | for each use event Covers exposure up to 2,20 hours/event |
| Non-metal-surface treat- | Covers concentrations up to 50 % |
| ment products Aerosol | |
| spray can. | according to 2 day/year |
| | covers use up to 2 day/year |
| | covers use up to 1 times/day of use |
| | For each use event, covers amount up to 215 g |
| | Covers use in a one car garage (34 m3) under typical ventilation. |
| | Covers use in room size of 34 m3 |
| | for each use event Covers exposure up to 0,33 hours/event |
| Non-metal-surface treat- | Covers concentrations up to 50 % |
| ment products Removers | · |
| (paint-, glue-, wall paper-, | |
| sealant-remover). | |
| | covers use up to 3 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 857,50 cm2 |
| | For each use event, covers amount up to 491 g |
| | Covers use in room size of 20 m3 |
| | for each use event Covers exposure up to 2,00 hours/event |
| Ink and toners Inks and toners. | Covers concentrations up to 50 % |
| | covers use up to 365 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 71,40 cm2 |
| | For each use event, covers amount up to 40 g |
| | Covers use in room size of 20 m3 |
| | for each use event Covers exposure up to 2,20 hours/event |
| Leather tanning, dye, finishing, impregnation and care products Polishes, wax / | Covers concentrations up to 50 % |
| cream (floor, furniture, shoes). | |
| 011000). | covers use up to 29 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 430,00 cm2 |
| | For each use event, covers amount up to 56 g |
| | Covers use in room size of 20 m3 |
| | for each use event Covers exposure up to 1,23 hours/event |
| Leather tanning, dye, finish- | Covers concentrations up to 50 % |
| ing, impregnation and care | |
| products Polishes, spray | |

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

| (furniture obses) | |
|--|---|
| (furniture, shoes). | covers use units. O devilueer |
| | covers use up to 8 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 430,00 cm2 |
| | for each use event, covers amount up to (g): 56 g |
| | Covers use in room size of 20 m3 |
| | for each use event Covers exposure up to 0,33 hours/event |
| Lubricants, greases, release products Liquids. | Covers concentrations up to 100 % |
| | covers use up to 4 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 468,00 cm2 |
| | For each use event, covers amount up to 2.200 g |
| | Covers use in a one car garage (34 m3) under typical ventilation. |
| | Covers use in room size of 34 m3 |
| | for each use event Covers exposure up to 0,17 hours/event |
| Lubricants, greases, release products Pastes. | Covers concentrations up to 20 % |
| p | covers use up to 10 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 468,00 cm2 |
| | For each use event, covers amount up to 34 g |
| | Covers use in room size of 20 m3 |
| Lubricants, greases, re- | Covers concentrations up to 50 % |
| lease products Sprays. | · · · · · · · · · · · · · · · · · · · |
| | covers use up to 6 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 428,75 cm2 |
| | For each use event, covers amount up to 73 g |
| | Covers use in room size of 20 m3 |
| | for each use event Covers exposure up to 0,17 hours/event |
| Polishes and wax blends Polishes, wax / cream (floor, furniture, shoes). | Covers concentrations up to 50 % |
| (Heer, ranneare, enece): | covers use up to 29 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 430,00 cm2 |
| | For each use event, covers amount up to 142 g |
| | Covers use in room size of 20 m3 |
| | for each use event Covers exposure up to 1,23 hours/event |
| Polishes and wax blends | Covers concentrations up to 50 % |
| Polishes, spray (furniture, shoes). | Covers concentrations up to 50 % |
| | covers use up to 8 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 430,00 cm2 |
| | For each use event, covers amount up to 35 g |
| _ | Covers use in room size of 20 m3 |
| _ | for each use event Covers exposure up to 0,33 hours/event |
| | |

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

| impregnating products; including bleaches and other processing aids | |
|---|---|
| | covers use up to 365 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 857,50 cm2 |
| | For each use event, covers amount up to 115 g |
| | Covers use in room size of 20 m3 |
| | for each use event Covers exposure up to 1,00 hours/event |

| Section 2.2 | Control of Environmental Exposure | |
|---|-----------------------------------|--|
| No exposure assessment presented for the environment. | | |

| SECTION 3 EXPOSURE ESTIMATION | | |
|---------------------------------------|---|--|
| Section 3.1 - Health | | |
| The ECETOC TRA tool has be indicated. | peen used to estimate consumer exposures unless otherwise | |

Section 3.2 - Environment

No exposure assessment presented for the environment.

| SECTION 4 | GUIDANCE TO CHECK COMPLIANCE WITH THE |
|----------------------|---------------------------------------|
| | EXPOSURE SCENARIO |
| Section 4.1 - Health | |

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 -Environment No exposure assessment presented for the environment.

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

Exposure Scenario - Consumer

| 30000001015 | |
|------------------|---|
| SECTION 1 | EXPOSURE SCENARIO TITLE |
| Title | Use in Cleaning Agents - Consumer |
| Use Descriptor | Sector of Use: SU21 Product Categories: PC3, PC4, PC8 (excipient only), PC9a, PC24, PC35, PC38 Environmental Release Categories: ERC8a, ERC8d |
| Scope of process | Covers general exposures to consumers arising from the use of household products sold as washing and cleaning products, aerosols, coatings, de-icers, lubricants and air care products. |

| No exposure assessment prese | nted for the environment. | |
|--|--|--|
| Control of Concumer Expects | | |
| Control of Consumer Exposur | Control of Consumer Exposure | |
| | | |
| Liquid, vapour pressure > 10 Pa | at STP | |
| Unless stated otherwise. | | |
| Covers concentration up to (%): | 100 % | |
| | | |
| | | |
| for each use event, covers amount up to (g): | | |
| covers skin contact area (cm2): | | |
| Use | | |
| | | |
| covers use up to (times/day of use): | | |
| Exposure (hours/event): | | |
| ns affecting Exposure | | |
| | | |
| eratures. | | |
| 0m3 | | |
| | Liquid, vapour pressure > 10 Pa Unless stated otherwise. Covers concentration up to (%): mount up to (g): 2): Use | |

| Product Categories | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES |
|--|---|
| Air care products Air care, instant action (aerosol sprays). | Covers concentrations up to 50 % |
| | covers use up to 365 day/year |
| | covers use up to 4 times/day of use |
| | for each use event, covers amount up to (g): 0,1 g |
| | Covers use in room size of 20 m3 |

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

| for each use event Covers exposure up to 0,25 hours/event Covers use under typical household ventilation. |
|---|
| , |
| |
| |
| Covers concentrations up to 100 % |
| covers use up to 365 day/year |
| covers use up to 2 times/day of use |
| covers skin contact area up to (cm2): 35,70 cm2 |
| For each use event, covers amount up to 12 g |
| Covers use in room size of 20 m3 |
| for each use event Covers exposure up to 12 hours/event |
| Covers concentrations up to 50 % |
| · |
| covers use up to 365 day/year |
| covers use up to 1 times/day of use |
| For each use event, covers amount up to 0,5 g |
| Covers use in a one car garage (34 m3) under typical ventila- |
| tion. |
| Covers use in room size of 34 m3 |
| for each use event Covers exposure up to 0,02 hours/event |
| Covers concentrations up to 50 % |
| Covers concentrations up to 30 % |
| covers use up to 365 day/year |
| covers use up to 1 times/day of use |
| covers skin contact area up to (cm2): 428,00 cm2 |
| For each use event, covers amount up to 2.000 g |
| Covers use in a one car garage (34 m3) under typical ventila- |
| tion. |
| Covers use in room size of 34 m3 |
| for each use event Covers exposure up to 0,17 hours/event |
| Covers concentrations up to 50 % |
| covers use up to 365 day/year |
| covers use up to 1 times/day of use |
| covers skin contact area up to (cm2): 214,40 cm2 |
| For each use event, covers amount up to 4 g |
| Covers use in a one car garage (34 m3) under typical ventila- |
| tion. |
| Covers use in room size of 34 m3 |
| for each use event Covers exposure up to 0,25 hours/event |
| Covers concentrations up to 50 % |
| COTOTO COMOCIMICATION OF TO CO 70 |
| |
| |
| covers use up to 365 day/year |
| covers use up to 1 times/day of use |
| covers skin contact area up to (cm2): 857,50 cm2 |
| covere extra contract area up to (onle). Cor, co onle |
| For each use event, covers amount up to 15 g |
| |

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

| | for each use event Covers expenses up to 0.50 hours/event |
|---|--|
| Dissidal products (s. p.:- | for each use event Covers exposure up to 0,50 hours/event |
| Biocidal products (e.g. Dis- | Covers concentrations up to 50 % |
| infectants, pest control) | |
| (excipient only). Cleaners, | |
| liquids (all purpose clean- | |
| ers, sanitary products, floor | |
| cleaners, glass cleaners, carpet cleaners, metal | |
| cleaners). | |
| cleariers). | covers use up to 128 day/year |
| | covers use up to 125 day/year covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 857,50 cm2 |
| | For each use event, covers amount up to 27 g |
| | Covers use in room size of 20 m3 |
| | |
| Piocidal products (a.e. Die | for each use event Covers exposure up to 0,33 hours/event |
| Biocidal products (e.g. Dis- infectants, pest control) | Covers concentrations up to 50 % |
| (excipient only). Cleaners, | |
| trigger sprays (all purpose | |
| cleaners, sanitary products, | |
| glass cleaners). | |
| glass cleariers). | covers use up to 128 day/year |
| | covers use up to 125 day/year |
| | covers skin contact area up to (cm2): 428,00 cm2 |
| | For each use event, covers amount up to 35 g |
| | Covers use in room size of 20 m3 |
| | for each use event Covers exposure up to 0,17 hours/event |
| Coatings and paints, thin- | Covers concentrations up to 50 % |
| ners, paint removers Wa- | Covers concentrations up to 30 % |
| terborne latex wall paint. | |
| terserrie latex wan panta | covers use up to 4 day/year |
| | Covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 428,75 cm2 |
| | For each use event, covers amount up to 2.760 g |
| | Covers use in room size of 20 m3 |
| | for each use event Covers exposure up to 2,20 hours/event |
| Coatings and paints, thin- | Covers concentrations up to 27,5 % |
| ners, paint removers Sol- | 201010 0011001111 attion 3 ap to 21,0 /0 |
| vent rich, high solid, water | |
| borne paint. | |
| | covers use up to 6 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 428,75 cm2 |
| | For each use event, covers amount up to 744 g |
| | Covers use in room size of 20 m3 |
| | for each use event Covers exposure up to 2,20 hours/event |
| Coatings and paints, thin- | Covers concentrations up to 50 % |
| ners, paint removers Aero- | OUTUS CONCONTINUIONS UP to 30 /0 |
| sol spray can. | |
| oc. opiay our. | covers use up to 2 day/year |
| | covers use up to 1 times/day of use |
| | 1 00 voto abo ap to 1 timos/day of abo |

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

| | For each use event, covers amount up to 215 g |
|-----------------------------|--|
| | Covers use in a one car garage (34 m3) under typical ventila- |
| | tion. |
| | Covers use in room size of 34 m3 |
| | for each use event Covers exposure up to 0,33 hours/event |
| Coatings and paints, thin- | Covers concentrations up to 50 % |
| ners, paint removers Re- | Covers concentrations up to 30 % |
| movers (paint-, glue-, wall | |
| paper-, sealant-remover). | |
| paper, sealant remover). | covers use up to 3 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 857,50 cm2 |
| | For each use event, covers amount up to 491 g |
| | Covers use in room size of 20 m3 |
| | for each use event Covers exposure up to 2,00 hours/event |
| Lubricants, greases, re- | Covers concentrations up to 100 % |
| lease products Liquids. | Covers concentrations up to 100 % |
| 10000 producto Elquido. | covers use up to 4 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 468,00 cm2 |
| | For each use event, covers amount up to 2.200 g |
| | Covers use in a one car garage (34 m3) under typical ventila- |
| | tion. |
| | Covers use in room size of 34 m3 |
| | for each use event Covers exposure up to 0,17 hours/event |
| Lubricants, greases, re- | Covers concentrations up to 20 % |
| lease products Pastes. | Covers concentrations up to 20 // |
| | covers use up to 10 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 468,00 cm2 |
| | For each use event, covers amount up to 34 g |
| | Covers use in room size of 20 m3 |
| Lubricants, greases, re- | Covers concentrations up to 50 % |
| lease products Sprays. | эр нь нь нь |
| 1 -1 -7 - | covers use up to 6 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 428,75 cm2 |
| | For each use event, covers amount up to 73 g |
| | Covers use in room size of 20 m3 |
| | for each use event Covers exposure up to 0,17 hours/event |
| Washing and cleaning | Covers concentrations up to 70 % |
| products (including solvent | , |
| based products) Laundry | |
| and dish washing products. | |
| <u> </u> | covers use up to 365 day/year |
| | Covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 857,50 cm2 |
| | For each use event, covers amount up to 15 g |
| | |
| | |
| | Covers use in room size of 20 m3 for each use event Covers exposure up to 0,50 hours/event |

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

| products (including solvent | |
|--------------------------------|---|
| based products) Cleaners, | |
| liquids (all purpose clean- | |
| ers, sanitary products, floor | |
| cleaners, glass cleaners, | |
| carpet cleaners, metal | |
| cleaners). | |
| | covers use up to 128 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 857,50 cm2 |
| | For each use event, covers amount up to 27 g |
| | Covers use in room size of 20 m3 |
| | for each use event Covers exposure up to 0,33 hours/event |
| Washing and cleaning | Covers concentrations up to 70 % |
| products (including solvent | |
| based products) Cleaners, | |
| trigger sprays (all purpose | |
| cleaners, sanitary products, | |
| glass cleaners). | |
| | covers use up to 128 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 428,00 cm2 |
| | For each use event, covers amount up to 35 g |
| | Covers use in room size of 20 m3 |
| | for each use event Covers exposure up to 0,17 hours/event |
| Welding and soldering | Covers concentrations up to 50 % |
| products (with flux coatings | |
| or flux cores.), flux products | |
| | covers use up to 365 day/year |
| | covers use up to 1 times/day of use |
| | For each use event, covers amount up to 12 g |
| | Covers use in room size of 20 m3 |
| | for each use event Covers exposure up to 1,00 hours/event |

| Section 2.2 Control of Environmental Exposure | | |
|---|-----------------------------|--|
| No exposure assessment pre | sented for the environment. | |

| SECTION 3 | EXPOSURE ESTIMATION |
|---------------------------------------|---|
| Section 3.1 - Health | |
| The ECETOC TRA tool has be indicated. | peen used to estimate consumer exposures unless otherwise |

| Section 3.2 -Environment |
|---|
| No exposure assessment presented for the environment. |

| SECTION 4 | GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO |
|-----------------------|--|
| Section 4.1 - Health | |
| Predicted exposures a | re not expected to exceed the DN(M)EL when the Risk Management |

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

Measures/Operational Conditions outlined in Section 2 are implemented.

Where other Risk Management Measures/Operational Conditions are adopted, then users

should ensure that risks are managed to at least equivalent levels.

Section 4.2 - Environment

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

Exposure Scenario - Consumer

| 30000001017 | |
|------------------|---|
| SECTION 1 | EXPOSURE SCENARIO TITLE |
| Title | Lubricants - Consumer |
| Use Descriptor | Sector of Use: SU21 Product Categories: PC1, PC24, PC31 Environmental Release Categories: ERC8a, ERC8d, ERC9a, ERC9b |
| Scope of process | Covers the consumer use of formulated lubricants in closed and open systems including transfer operations, application, operation of engines and similar articles, equipment maintenance and disposal of waste oil. |

| SECTION 2 | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES | | |
|---|---|-------|--|
| Additional Information | No exposure assessment presented for the environment. | | |
| Section 2.1 | Control of Consumer Exposur | e | |
| Product Characteristics | | | |
| Physical form of product | Liquid, vapour pressure > 10 Pa | | |
| Concentration of the Substance in Mixture/Article | Unless stated otherwise. | | |
| | Covers concentration up to (%): | 100 % | |
| Amounts Used | | | |
| Unless stated otherwise. | | | |
| for each use event, covers amount up to (g): | | 6.390 | |
| covers skin contact area (cm2): | | 468 | |
| Frequency and Duration o | f Use | | |
| Unless stated otherwise. | | | |
| covers use up to (times/day of use): | | 1 | |
| Exposure (hours/event): | | 6 | |
| Other Operational Condition | ons affecting Exposure | | |
| Unless stated otherwise | · | · | |

Unless stated otherwise.

Covers use at ambient temperatures.

Covers use in room size of 20m3

| Product Categories | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES |
|---------------------------------------|---|
| Adhesives, sealants Glues, hobby use. | Covers concentrations up to 30 % |
| | covers use up to 365 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 35,73 cm2 |
| | For each use event, covers amount up to 9 g |
| | Covers use in room size of 20 m3 |

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

| | for each use event Covers exposure up to 4 hours/event |
|---|---|
| Adhesives, sealants Glues | Covers concentrations up to 30 % |
| DIY-use (carpet glue, tile | |
| glue, wood parquet glue). | |
| grad, moda parquet grad, | covers use up to 1 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 110,00 cm2 |
| | For each use event, covers amount up to 6.390 g |
| | Covers use in room size of 20 m3 |
| | for each use event Covers exposure up to 6,00 hours/event |
| Adhesives, sealants Glue | Covers concentrations up to 30 % |
| from spray. | · |
| | covers use up to 6 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 35,73 cm2 |
| | For each use event, covers amount up to 85,05 g |
| | Covers use in room size of 20 m3 |
| | for each use event Covers exposure up to 4,00 hours/event |
| Adhesives, sealants Sealants. | Covers concentrations up to 30 % |
| | covers use up to 365 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 35,73 cm2 |
| | For each use event, covers amount up to 75 g |
| | Covers use in room size of 20 m3 |
| | for each use event Covers exposure up to 1,00 hours/event |
| Lubricants, greases, re- lease products Liquids. | Covers concentrations up to 100 % |
| | covers use up to 4 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 468,00 cm2 |
| | For each use event, covers amount up to 2.200 g |
| | Covers use in a one car garage (34 m3) under typical ventilation. |
| | Covers use in room size of 34 m3 |
| | for each use event Covers exposure up to 0,17 hours/event |
| Lubricants, greases, re- lease products Pastes. | Covers concentrations up to 20 % |
| • | covers use up to 10 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 468,00 cm2 |
| | For each use event, covers amount up to 34 g |
| | Covers use in room size of 20 m3 |
| Lubricants, greases, re- lease products Sprays. | Covers concentrations up to 50 % |
| | covers use up to 6 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 428,75 cm2 |
| | For each use event, covers amount up to 73 g |
| | Covers use in room size of 20 m3 |
| | for each use event Covers exposure up to 0,17 hours/event |

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

| Polishes and wax blends Polishes, wax / cream (floor, furniture, shoes). | Covers concentrations up to 50 % | |
|--|---|--|
| | covers use up to 29 day/year | |
| | covers use up to 1 times/day of use | |
| | covers skin contact area up to (cm2): 430,00 cm2 | |
| | For each use event, covers amount up to 142 g | |
| | Covers use in room size of 20 m3 | |
| | for each use event Covers exposure up to 1,23 hours/event | |
| Polishes and wax blends Polishes, spray (furniture, shoes). | Covers concentrations up to 50 % | |
| | covers use up to 8 day/year | |
| | covers use up to 1 times/day of use | |
| | covers skin contact area up to (cm2): 430,00 cm2 | |
| | For each use event, covers amount up to 35 g | |
| | Covers use in room size of 20 m3 | |
| | for each use event Covers exposure up to 0,33 hours/event | |

| Section 2.2 Control of Environmental Exposure | | | |
|---|---|--|--|
| No exposure assessment pre | No exposure assessment presented for the environment. | | |

| SECTION 3 | EXPOSURE ESTIMATION | | |
|----------------------|---------------------|------|--|
| Section 3.1 - Health | | | |
| | | | |

The ECETOC TRA tool has been used to estimate consumer exposures unless otherwise indicated.

Section 3.2 - Environment

No exposure assessment presented for the environment.

| SECTION 4 | GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO |
|----------------------|---|
| Section 4.1 - Health | |

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 -Environment

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

Exposure Scenario - Consumer

| Expedit Contains | | |
|------------------|---|--|
| 30000001019 | | |
| SECTION 1 | EXPOSURE SCENARIO TITLE | |
| Title | Use in agrochemicals - Consumer | |
| Use Descriptor | Sector of Use: SU21 Product Categories: PC12, PC27 Environmental Release Categories: ERC8a, ERC8d | |
| Scope of process | Covers the consumer use in agrochemicals in liquid and solid forms. | |

| SECTION 2 | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES | |
|---|---|---------------------------|
| Additional Information | No exposure assessment prese | nted for the environment. |
| Section 2.1 | Control of Consumer Exposu | re |
| Product Characteristics | | |
| Physical form of product | Liquid, vapour pressure > 10 Pa | a at STP |
| Concentration of the Substance in Mixture/Article | Unless stated otherwise. | |
| | Covers concentration up to (%): | 50 % |
| Amounts Used | | |
| Unless stated otherwise. | | |
| for each use event, covers amount up to (g): | | 50 |
| covers skin contact area (cr | m2): | 857,50 |
| Frequency and Duration of | of Use | · |
| Unless stated otherwise. | | |
| covers use up to (times/day of use): | | 0 |
| Other Operational Conditi | ons affecting Exposure | <u> </u> |

Other Operational Conditions affecting Exposure

Unless stated otherwise.

Covers use at ambient temperatures.

Covers use in room size of 20m3

| Product Categories | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES | |
|---------------------------|---|--|
| Fertilizers | Covers concentrations up to 50 % | |
| | covers use up to 365 day/year | |
| | covers use up to 1 times/day of use | |
| | covers skin contact area up to (cm2): 857,50 cm2 | |
| | For each use event, assumes swallowed amount of 0,3 g | |
| | Covers use in room size of 20 m3 | |
| Plant protection products | Covers concentrations up to 50 % | |
| | covers use up to 365 day/year | |
| | covers use up to 1 times/day of use | |
| | covers skin contact area up to (cm2): 857,50 cm2 | |

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

| For each use event, assumes swallowed amount of 0,3 g |
|---|
| Covers use in room size of 20 m3 |

| Section 2.2 | Control of Environmental Exposure | |
|--|-----------------------------------|--|
| No exposure assessment presented for the environment | | |

| SECTION 3 | EXPOSURE ESTIMATION | |
|--|---------------------|--|
| Section 3.1 - Health | | |
| The ECETOC TRA tool has been used to estimate consumer exposures unless otherwise indicated. | | |

Section 3.2 - Environment

No exposure assessment presented for the environment.

| SECTION 4 | GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO |
|----------------------|---|
| Section 4.1 - Health | |

Section 4.1 - Health

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 - Environment

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

Exposure Scenario - Consumer

| 30000001021 | |
|------------------|---|
| SECTION 1 | EXPOSURE SCENARIO TITLE |
| Title | Use as a fuel - Consumer |
| Use Descriptor | Sector of Use: SU21 Product Categories: PC13 Environmental Release Categories: ERC9a, ERC9b |
| Scope of process | Covers consumer uses in liquid fuels. |

| SECTION 2 | OPERATIONAL CONDITIONS A MEASURES | AND RISK MANAGEMENT |
|---|-----------------------------------|--------------------------|
| Additional Information | No exposure assessment presen | ted for the environment. |
| Section 2.1 | Control of Consumer Exposure | • |
| Product Characteristics | | |
| Physical form of product | Liquid, vapour pressure > 10 Pa | at STP |
| Concentration of the Substance in Mixture/Article | Unless stated otherwise. | |
| | Covers concentration up to (%): | 100 % |
| Amounts Used | | |
| Unless stated otherwise. | | |
| for each use event, covers amount up to (g): | | 37.500 |
| covers skin contact area (cm2): | | 420 |
| Frequency and Duration of | f Use | • |
| Unless stated otherwise. | | |
| covers use up to (times/day of use): | | 0,143 |
| Exposure (hours/event): 2 | | 2 |
| Other Operational Conditi | one offecting Evnecure | • |

Other Operational Conditions affecting Exposure

Unless stated otherwise.

Covers use at ambient temperatures.

Covers use in room size of 20m3

| Product Categories | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES | |
|--------------------------------------|---|--|
| Fuels Liquid: Automotive Refuelling. | Covers concentrations up to 100 % | |
| | covers use up to 52 day/year | |
| | covers use up to 1 times/day of use | |
| | covers skin contact area up to (cm2): 210,00 cm2 | |
| | For each use event, covers amount up to 37.500 g | |
| | Covers outdoor use. | |
| | Covers use in room size of 100 m3 | |
| | for each use event Covers exposure up to 0,05 hours/event | |
| Fuels Liquid Scooter Refu- | Covers concentrations up to 100 % | |

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

| elling. | |
|--|---|
| Ciling. | covers use up to 52 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 210,00 cm2 |
| | For each use event, covers amount up to 3.750 g |
| | Covers outdoor use. |
| | Covers use in room size of 100 m3 |
| | for each use event Covers exposure up to 0,03 hours/event |
| Fuels Liquid, Garden | Covers concentrations up to 100 % |
| Equipment - Use. | , i |
| | covers use up to 26 day/year |
| | covers use up to 1 times/day of use |
| | For each use event, covers amount up to 750 g |
| | Covers outdoor use. |
| | Covers use in room size of 100 m3 |
| | for each use event Covers exposure up to 2,00 hours/event |
| Fuels Liquid: Garden Equipment - Refuelling. | Covers concentrations up to 100 % |
| | covers use up to 26 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 420,00 cm2 |
| | For each use event, covers amount up to 750 g |
| | Covers use in a one car garage (34 m3) under typical ventilation. |
| | Covers use in room size of 34 m3 |
| | for each use event Covers exposure up to 0,03 hours/event |
| Fuels Liquid: Home space | Covers concentrations up to 100 % |
| heater fuel. | · |
| | covers use up to 26 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 420,00 cm2 |
| | For each use event, covers amount up to 750 g |
| | Covers use in room size of 20 m3 |
| | for each use event Covers exposure up to 8,00 hours/event |
| Fuels Liquid: Lamp oil. | Covers concentrations up to 100 % |
| | covers use up to 52 day/year |
| | Covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 210,00 cm2 |
| | For each use event, covers amount up to 100 g |
| | Covers use in room size of 20 m3 |
| | for each use event Covers exposure up to 0,01 hours/event |

| Section 2.2 Control of Environmental Exposure | | |
|---|--|--|
| No exposure assessment presented for the environment. | | |

| SECTION 3 | EXPOSURE ESTIMATION | |
|--|---------------------|--|
| Section 3.1 - Health | | |
| The ECETOC TRA tool has been used to estimate consumer exposures unless otherwise indicated. | | |

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

Section 3.2 - Environment

No exposure assessment presented for the environment.

SECTION 4 GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO

Section 4.1 - Health

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 - Environment

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

Exposure Scenario - Consumer

| 2xpccaro cocriario co | |
|-----------------------|--|
| 30000001023 | |
| SECTION 1 | EXPOSURE SCENARIO TITLE |
| SECTION 1 | EXPOSORE SCENARIO TITLE |
| Title | Functional Fluids - Consumer |
| Use Descriptor | Sector of Use: SU21 |
| • | Product Categories: PC16, PC17 |
| | Environmental Release Categories: ERC9a, ERC9b |
| Scope of process | Use of sealed items containing functional fluids e.g. transfer |
| | oils, hydraulic fluids, refrigerants. |

| SECTION 2 | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES | |
|---|---|-------|
| Additional Information | No exposure assessment presented for the environment. | |
| Section 2.1 | Control of Consumer Exposure | |
| Product Characteristics | | |
| Physical form of product | Liquid, vapour pressure > 10 Pa at STP | |
| Concentration of the Substance in Mixture/Article | Unless stated otherwise. | |
| | Covers concentration up to (%): 100 % | |
| Amounts Used | | |
| Unless stated otherwise. | | |
| for each use event, covers amount up to (g): | | 2.200 |
| covers skin contact area (cm2): | | 468 |
| Frequency and Duration o | f Use | |
| Unless stated otherwise. | | |
| covers use up to (times/day of use): 0,010 | | 0,010 |
| Exposure (hours/event): 0,167 | | 0,167 |
| Other Operational Condition | ons affecting Exposure | |

Other Operational Conditions affecting Exposure

Unless stated otherwise.

Covers use at ambient temperatures.

Covers use in room size of 20m3

| Product Categories | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES | |
|-------------------------------|---|--|
| Heat transfer fluids Liquids. | Covers concentrations up to 100 % | |
| | covers use up to 4 day/year | |
| | covers use up to 1 times/day of use | |
| | covers skin contact area up to (cm2): 468,00 cm2 | |
| | For each use event, assumes swallowed amount of 2.200 g | |
| | Covers use in a one car garage (34 m3) under typical ventila- | |
| | tion. | |
| | Covers use in room size of 34 m3 | |
| | for each use event Covers exposure up to 0,17 hours/event | |

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

| Hydraulic fluids Liquids. | Covers concentrations up to 100 % covers use up to 4 day/year covers use up to 1 times/day of use | |
|---------------------------|--|--|
| | | |
| | | |
| | covers skin contact area up to (cm2): 468,00 cm2 | |
| | For each use event, covers amount up to 2.200 g Covers use in a one car garage (34 m3) under typical ventila- | |
| | | |
| | tion. | |
| | Covers use in room size of 34 m3 | |
| | for each use event Covers exposure up to 0,17 hours/event | |

| Section 2.2 Control of Environmental Exposure | | |
|---|--|--|
| No exposure assessment presented for the environment. | | |

| SECTION 3 | EXPOSURE ESTIMATION | |
|---|---------------------|--|
| Section 3.1 - Health | | |
| The ECETOC TRA tool has been used to estimate consumer exposures unless otherwise | | |
| indicated. | | |

Section 3.2 - Environment

No exposure assessment presented for the environment.

| SECTION 4 | GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO |
|----------------------|---|
| Section 4.1 - Health | |

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

| Section 4.2 -Environment | |
|--|--|
| No exposure assessment presented for the environment | |

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

Exposure Scenario - Consumer

| 30000001024 | |
|------------------|---|
| SECTION 1 | EXPOSURE SCENARIO TITLE |
| Title | Use in de-icing and anti-icing fluids - Consumer |
| Use Descriptor | Sector of Use: SU21 Product Categories: PC4 Environmental Release Categories: ERC8d |
| Scope of process | De-icing of vehicles and similar equipment by spraying. |

| SECTION 2 | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES | |
|---|---|-------|
| Additional Information | No exposure assessment presented for the environment. | |
| Section 2.1 | Control of Consumer Exposure | |
| Product Characteristics | | |
| Physical form of product | Liquid, vapour pressure > 10 Pa at STP | |
| Concentration of the Substance in Mixture/Article | Unless stated otherwise. | |
| | Covers concentration up to (%): 40 % | |
| Amounts Used | | |
| Unless stated otherwise. | | |
| for each use event, covers amount up to (g): | | 2.000 |
| covers skin contact area (cm2): | | 428 |
| Frequency and Duration o | f Use | |
| Unless stated otherwise. | | |
| covers use up to (times/day of use): | | 1 |
| Covers exposure up to (hours/event): 0,25 | | 0,25 |
| Other Operational Condition | ons affecting Exposure | |

Unless stated otherwise.

Covers use at ambient temperatures.

Covers use in room size of 20m3

| Product Categories | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES |
|---|---|
| Anti-Freeze and de-icing products Washing car window. | Covers concentrations up to 20 % |
| | covers use up to 365 day/year |
| | covers use up to 1 times/day of use |
| | For each use event, covers amount up to 0,5 g |
| | Covers use in a one car garage (34 m3) under typical ventilation. |
| | Covers use in room size of 34 m3 |
| | for each use event Covers exposure up to 0,02 hours/event |
| Anti-Freeze and de-icing | Covers concentrations up to 20 % |

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

| products Pouring into radia- | |
|---|---|
| tor. | |
| | covers use up to 365 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 428,00 cm2 |
| | For each use event, covers amount up to 2.000 g |
| | Covers use in a one car garage (34 m3) under typical ventila- |
| | tion. |
| | Covers use in room size of 34 m3 |
| | for each use event Covers exposure up to 0,17 hours/event |
| Anti-Freeze and de-icing products Lock de-icer. | Covers concentrations up to 50 % |
| | covers use up to 365 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 214,40 cm2 |
| | For each use event, covers amount up to 4 g |
| | Covers use in a one car garage (34 m3) under typical ventila- |
| | tion. |
| | Covers use in room size of 34 m3 |
| | for each use event Covers exposure up to 0,25 hours/event |

| Section 2.2 | Control of Environmental Exposure | |
|---|-----------------------------------|--|
| No exposure assessment presented for the environment. | | |

| SECTION 3 | EXPOSURE ESTIMATION |
|---|---------------------|
| Section 3.1 - Health | |
| The ECETOC TRA tool has been used to estimate consumer exposures unless otherwise | |
| indicated | |

Section 3.2 - Environment

No exposure assessment presented for the environment.

| SECTION 4 | GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO | |
|---|--|--|
| Section 4.1 - Health | | |
| Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management | | |
| Measures/Operational Conditions outlined in Section 2 are implemented. | | |
| Mhara athar Diak Me | anagement Measures/Operational Conditions are adopted than years | |

Measures/Operational Conditions outlined in Section 2 are implemented.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

| Section 4.2 -Environment |
|---|
| No exposure assessment presented for the environment. |

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

Exposure Scenario - Consumer

| 30000001025 | |
|------------------|---|
| SECTION 1 | EXPOSURE SCENARIO TITLE |
| Title | Other Consumer Uses - Consumer |
| Use Descriptor | Sector of Use: SU21 Product Categories: PC28, PC39 Environmental Release Categories: ERC8a, ERC8d |
| Scope of process | Consumer uses e.g. as a carrier in cosmetics/personal care products, perfumes and fragrances. Note: For cosmetic and personal care products, risk assessment only required for the environment under REACH as human health is covered by alternative legislation. |

| SECTION 2 | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES |
|--------------------------------|---|
| Additional Information | No exposure assessment presented for human health. |
| | No exposure assessment presented for the environment. |
| Section 2.1 | Control of Consumer Exposure |
| Product Characteristics | |
| Product Categories | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES |

| SECTION 3 | EXPOSURE ESTIMATION |
|----------------------------|--------------------------|
| Section 3.1 - Health | |
| No exposure assessment pre | sented for human health. |

Section 3.2 -Environment

| SECTION 4 | GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO | |
|--|---|--|
| Section 4.1 - Health | | |
| No exposure assessment presented for human health. | | |

| Section 4.2 -Environment | |
|---|--|
| No exposure assessment presented for the environment. | |

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

Exposure Scenario - Consumer

| 30000001026 | | |
|------------------|--|--|
| SECTION 1 | EXPOSURE SCENARIO TITLE | |
| Title | Water treatment chemicals - Consumer | |
| Use Descriptor | Sector of Use: SU21 Product Categories: PC36, PC37 Environmental Release Categories: ERC8f | |
| Scope of process | Covers the use of the substance for the treatment of water in open and closed systems. | |

| SECTION 2 | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES | |
|---|---|-------------------------|
| Additional Information | No exposure assessment presente | ed for the environment. |
| Section 2.1 | Control of Consumer Exposure | |
| Product Characteristics | | |
| Physical form of product | Liquid, vapour pressure > 10 Pa | |
| Concentration of the Substance in Mixture/Article | Unless stated otherwise. | |
| | Covers concentration up to (%): 20 | 0 % |
| Amounts Used | | |
| Unless stated otherwise. | | |
| for each use event, covers amount up to (g): | | 10 |
| covers skin contact area (cm2): | | 6.600 |
| Frequency and Duration o | f Use | · |
| Unless stated otherwise. | | |
| covers use up to (times/day of use): | | 1 |
| Other Operational Condition | one affecting Evnosure | <u>.</u> |

Other Operational Conditions affecting Exposure

Unless stated otherwise.

Covers use at ambient temperatures.

Covers use in room size of 20m3

| Product Categories | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES |
|---------------------------|---|
| Water softeners | Covers concentrations up to 20 % |
| | covers use up to 365 day/year |
| | covers use up to 1 times/day of use |
| | covers skin contact area up to (cm2): 6.600 cm2 |
| | For each use event, assumes swallowed amount of 0,02 mg |
| | For each use event, covers amount up to 10 g |
| | Covers use in room size of 20 m3 |
| Water treatment chemicals | Covers concentrations up to 20 % |
| | covers use up to 365 day/year |
| | covers use up to 1 times/day of use |

According to EC No 1907/2006 as amended as at the date of this SDS

Isopropyl alcohol-cosmetic

Version Revision Date: SDS Number: Date of last issue: 23.11.2023

5.1 09.10.2024 800001006805 Print Date 16.10.2024

| covers skin contact area up to (cm2): 6.600 cm2 |
|---|
| For each use event, assumes swallowed amount of 0,15 mg |
| For each use event, covers amount up to 10 g |
| Covers use in room size of 20 m3 |

| Section 2.2 | Control of Environmental Exposure | |
|---|-----------------------------------|--|
| No exposure assessment presented for the environment. | | |

| SECTION 3 | EXPOSURE ESTIMATION |
|---|---------------------|
| Section 3.1 - Health | |
| The ECETOC TRA tool has been used to estimate consumer exposures unless otherwise | |

The ECETOC TRA tool has been used to estimate consumer exposures unless otherwise indicated.

Section 3.2 -Environment No exposure assessment presented for the environment.

| SECTION 4 | GUIDANCE TO CHECK COMPLIANCE WITH THE |
|----------------------|---------------------------------------|
| | EXPOSURE SCENARIO |
| Section 4.1 - Health | |

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 -Environment No exposure assessment presented for the environment.